

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385580
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Verma; Naleen Kumar et al.

System for spacing and fastening tubular structures

Abstract

A system for spacing and fastening tubular structures, and a related method. The system includes a spacer element configured to engage a plurality of tubular structures, to spatially separate the plurality of tubular structures from one another, and to distribute stress in the plurality of tubular structures. The system further includes a fastening element configured to extend around at least a portion of an outer surface of the plurality of tubular structures, and to fasten the plurality of tubular structures to the spacer element in an adaptively spaced configuration.

Inventors: Verma; Naleen Kumar (Bengaluru, IN), Bolaños Jimenez; Mario Alberto (Querétaro, MX), Ramachandra; Arun (Bengaluru, IN), Darnell; Jeffrey P. (Cincinnati, OH), Sandy; Michael E. (Liberty Township, OH), Torre; José (Querétaro, MX)

Applicant: General Electric Company (Schenectady, NY)

Family ID: 85957073

Assignee: General Electric Company (Schenectady, NY)

Appl. No.: 18/526724

Filed: December 01, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240093808 A1	Mar. 21, 2024

Related U.S. Application Data

division parent-doc US 17451056 20211015 US 11859743 child-doc US 18526724

Publication Classification

Int. Cl.: F16L3/22 (20060101); F16L3/10 (20060101); F16L3/233 (20060101)

U.S. Cl.:

CPC F16L3/221 (20130101); F16L3/1058 (20130101); F16L3/2334 (20130101);

Field of Classification Search

CPC: F16L (3/221); F16L (3/1058); F16L (3/233); F16L (3/2334); F16L (3/105)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3486725	12/1968	Hidassy	174/40R	F16L 3/237
3632071	12/1971	Cameron	248/205.3	F16L 3/10
3860978	12/1974	Wirth	4/DIG.16	E03C 1/284
3933377	12/1975	Arrowood	248/62	F16L 3/00
4006874	12/1976	McGee	248/55	F16L 3/123
4143709	12/1978	Cunningham	165/172	F28F 9/0135
4393998	12/1982	Allen	248/74.1	F16L 3/18
4438294	12/1983	Meltsch	174/DIG.8	H02G 15/013
4601447	12/1985	McFarland	N/A	N/A
4913386	12/1989	Sugiyama	N/A	N/A
4925136	12/1989	Knott	248/62	F16L 3/237
4971268	12/1989	Dobrowski	244/135R	F16L 3/08
4993669	12/1990	Dyer	248/74.3	B65D 63/16
5027478	12/1990	Suhr	N/A	N/A
5474268	12/1994	Yu	N/A	N/A
5544849	12/1995	Peterson	248/74.1	F16L 3/12
5553666	12/1995	Hartman	166/62	E21B 17/1035
5742982	12/1997	Dodd et al.	N/A	N/A
5755013	12/1997	Fitch	29/447	F16L 3/237
5901756	12/1998	Goodrich	N/A	N/A
6128843	12/1999	Gebka	24/339	A47F 5/0869
6364257	12/2001	Holder	248/74.1	F16L 3/237
6533226	12/2002	Geiger	248/68.1	F16L 3/237
6710249	12/2003	Denton	N/A	N/A
7083152	12/2005	Carullo	248/65	F16L 3/10
8079560	12/2010	Blackwell	403/53	B60R 11/00
8230555	12/2011	Browne et al.	N/A	N/A
8240620	12/2011	Walter	N/A	N/A
8569624	12/2012	Eshima	174/115	H02G 3/32
8590847	12/2012	Guthke et al.	N/A	N/A
8664544	12/2013	Even et al.	N/A	N/A
8770537	12/2013	Go	248/62	F16L 55/035
8853532	12/2013	Eshima	248/74.2	H02G 3/03

9021681	12/2014	Owen	N/A	N/A
9062802	12/2014	Lairie	N/A	B65D 63/1009
D734654	12/2014	Geiger	D8/354	N/A
9212677	12/2014	Owen	N/A	N/A
9217519	12/2014	Masters et al.	N/A	N/A
9534708	12/2016	Cripps, II	N/A	N/A
9587433	12/2016	Sylvester et al.	N/A	N/A
9587448	12/2016	Decker et al.	N/A	N/A
9837802	12/2016	Welch	N/A	N/A
9856998	12/2017	Cripps, II	N/A	N/A
10199620	12/2018	Romand et al.	N/A	N/A
10495126	12/2018	Bejin et al.	N/A	N/A
10663089	12/2019	Sylvester	N/A	F16L 3/137
10745182	12/2019	Reznar	N/A	B65D 63/1072
10850025	12/2019	Bulloch et al.	N/A	N/A
11458909	12/2021	Lenagh	N/A	B60R 16/0215
11532929	12/2021	Robinson	N/A	F16L 3/1066
11859743	12/2023	Verma	N/A	F16L 3/221
2003/0173470	12/2002	Geiger	N/A	N/A
2005/0264012	12/2004	Ignaczak	285/417	F01N 13/1872
2006/0201565	12/2005	Coupe	138/108	E03F 3/02
2009/0272576	12/2008	Medina	N/A	N/A
2011/0147543	12/2010	Koga	248/69	H02G 3/30
2011/0290951	12/2010	Guthke	248/68.1	H02G 3/32
2012/0112014	12/2011	Eshima	248/68.1	H02G 3/32
2014/0259620	12/2013	Hicks	29/525.01	F16L 3/233
2016/0215562	12/2015	Sylvester	N/A	E06C 7/14
2017/0102099	12/2016	Cripps, II	N/A	F16L 3/221
2019/0309672	12/2018	Moetakef	N/A	F16F 1/371
2022/0390042	12/2021	Peterson	N/A	F16L 3/105

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2900565	12/2016	EP	N/A
3284992	12/2017	EP	N/A
3103872	12/2020	FR	B60R 16/0215
2009117247	12/2008	WO	N/A

Primary Examiner: McNichols; Eret C

Attorney, Agent or Firm: Wood Herron & Evans LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a divisional of U.S. patent application Ser. No. 17/451,056 filed on Oct. 15, 2021, the contents of which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

(1) The present disclosure relates to spacing and fastening systems for tubular structures deployed

in engineering assemblies. In particular, the present disclosure relates to spacer elements for supporting and separating tubular structures deployed in engineering assemblies.

BACKGROUND

(2) Gas turbine engines and other engineering assemblies typically include arrays or banks of tubes or pipes deployed in several locations for transport of liquids and gaseous products. Tubes or pipes are typically bundled using permanently joined spacer elements such as brazed or welded blocks and tabs.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Features and advantages of the present disclosure will be apparent from the following description of various exemplary embodiments, as illustrated in the accompanying drawings, wherein like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements.
- (2) FIG. 1A shows a schematic, perspective view of a tube spacing and fastening system for tubular structures, according to an embodiment of the present disclosure.
- (3) FIG. 1B shows an enlarged schematic, perspective front view of a spacer for the tube spacing and fastening system of FIG. 1A, according to an embodiment of the present disclosure.
- (4) FIG. 1C shows an enlarged schematic, perspective back view of a spacer for the tube spacing and fastening system of FIG. 1A, according to an embodiment of the present disclosure.
- (5) FIG. 2A shows a schematic, perspective view of a tube spacing and fastening system for tubular structures, according to an embodiment of the present disclosure.
- (6) FIG. 2B shows a schematic, perspective view of a spacer for the tube spacing and fastening system of FIG. 2A, according to an embodiment of the present disclosure.
- (7) FIG. 3A shows a schematic, perspective view of a tube spacing and fastening system for tubular structures, according to an embodiment of the present disclosure.
- (8) FIG. 3B shows an enlarged schematic, perspective view of a spacer for the tube spacing and fastening system of FIG. 3A, according to an embodiment of the present disclosure.
- (9) FIG. 4 shows a schematic, perspective view of a tube spacing and fastening system for tubular structures, according to an embodiment of the present disclosure.
- (10) FIG. 5 shows a schematic, perspective view of a tube spacing and fastening system for tubular structures, according to an embodiment of the present disclosure.
- (11) FIG. 6A shows a partial perspective view of a spacer for a tube spacing and fastening system, according to an embodiment of the present disclosure.
- (12) FIG. 6B shows a partial perspective view of a spacer for a tube spacing and fastening system, according to an embodiment of the present disclosure.
- (13) FIG. 6C shows a partial perspective view of a spacer for a tube spacing and fastening system, according to an embodiment of the present disclosure.
- (14) FIG. 7 shows a schematic flow diagram of a method of spacing and fastening a number of tubular structures, according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

(15) Features, advantages, and embodiments of the present disclosure are set forth or apparent from a consideration of the following detailed description, drawings, and claims. Moreover, it is to be understood that the following detailed description are exemplary and intended to provide further explanation without limiting the scope of the disclosure as claimed.

(16) Various embodiments are discussed in detail below. While specific embodiments are discussed, this is done for illustration purposes only. A person skilled in the relevant art will recognize that other components and configurations may be used without departing from the spirit

and scope of the present disclosure.

(17) Reference will now be made in detail to present embodiments of the disclosed subject matter, one or more examples of which are illustrated in the accompanying drawings. The detailed description uses numerical and letter designations to refer to features in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar parts of the disclosed subject matter. As used herein, the terms “first,” “second,” “third,” “fourth,” and “exemplary” may be used interchangeably to distinguish one component from another and are not intended to signify location or importance of the individual components.

(18) Further, to more clearly and concisely describe and point out the subject matter, the following definitions are provided for specific terms, which are used throughout the following description and the appended claims, unless specifically denoted otherwise with respect to a particular embodiment. The term “tube spacing and fastening system” as used in the context refers to a group of interacting or interrelated elements that act according to a set of rules to form a unified whole deployed to spatially separate tubes or its equivalents, such as pipes, rods, bars or any tubular structure and at the same time, to fasten them together. The detailed description uses numerical and letter designations to refer to features of tube spacing and fastening systems in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar tube spacing and fastening systems. As used herein, the numerals “20,” “40,” “60,” and “80” may be used interchangeably to distinguish one system from another and are not intended to signify location or importance of the individual systems.

(19) The term “spacer element” as used in the context refers to a device or piece used to create or maintain a desired amount of space between two or more objects. The detailed description uses numerical and letter designations to refer to features of spacer elements in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar spacer elements. As used herein, the numerals “22,” “42,” “62,” and “82” may be used interchangeably to distinguish one spacer element from another and are not intended to signify location or importance of the individual spacer elements.

(20) The term “core part” as used in the context refers to a central and foundational portion of a spacer element, usually distinct from the enveloping portions by a difference in nature or structure or function. The detailed description uses numerical and letter designations to refer to features of core parts in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar core parts. As used herein, the numerals “29,” “45,” and “86” may be used interchangeably to distinguish one core part from another and are not intended to signify location or importance of the individual core parts.

(21) The term “fastening element” as used in the context refers to a device or component that structurally joins or affixes two or more objects together. In general, fasteners are used to create non-permanent joints, that is, joints that can be removed or dismantled without damaging the joining components. The detailed description uses numerical and letter designations to refer to features of fastening elements in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar fastening elements. As used herein, the numerals “23,” “46,” “72,” and “92” may be used interchangeably to distinguish one fastening element from another and are not intended to signify location or importance of the individual fastening elements.

(22) The term “raised slot edge” as used in the context refers to elevated sides of a narrow, elongated depression, groove, notch, slit, or aperture, especially a narrow opening on a spacer element for receiving or admitting something of a planar dimension such as a fastening strap or band. The detailed description uses numerical and letter designations to refer to features of raised slot edges in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar raised slot edges. As used herein, the numerals “54,” and “68” may be used interchangeably to distinguish one raised slot edge from another and are not intended to

signify location or importance of the individual raised slot edges.

(23) The term “top end” as used in the context refers to the highest or uppermost point, portion, or surface of a spacer element. The detailed description uses numerical and letter designations to refer to features of top ends in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar top ends. As used herein, the numerals “37,” and “65” may be used interchangeably to distinguish one top end from another and are not intended to signify location or importance of the individual top ends.

(24) Similarly, the term “bottom end” as used in the context refers to the lowest or lowermost point, portion, or surface of a spacer element. The detailed description uses numerical and letter designations to refer to features of bottom ends in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar bottom ends. As used herein, the numerals “38,” and “66” may be used interchangeably to distinguish one bottom end from another and are not intended to signify location or importance of the individual bottom ends.

(25) The term “top tray slot” as used in the context refers to a narrow, elongated depression, groove, notch, slit, or aperture, especially a narrow opening on top of a spacer element for receiving or admitting something of a planar dimension such as a fastening strap or a band. The detailed description uses numerical and letter designations to refer to features of top tray slots in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar top tray slots. As used herein, the numerals “52,” and “67” may be used interchangeably to distinguish one top tray slot from another and are not intended to signify location or importance of the individual top tray slots.

(26) The term “tube outer surface” as used in the context refers to an outermost or uppermost or exterior boundary or layer or area of a tube. The detailed description uses numerical and letter designations to refer to features of tube outer surfaces in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar tube outer surfaces. As used herein, the numerals “26,” “47,” “73,” and “93” may be used interchangeably to distinguish one tube outer surface from another and are not intended to signify location or importance of the individual tube outer surfaces.

(27) The tube spacing and fastening system of the present disclosure provides for coupling multiple tubular structures together. The tube spacing and fastening system of the present disclosure couples or connects multiple tubular structures together without brazes or welds. In some examples, the tube spacing and fastening system may include a spacer element and a fastening band for coupling the multiple tubular structures. The spacer element functionally addresses an engineering contradiction of holding the tubular structures together and, at the same time, spatially separating them from another. The fastening band extends around the outer surfaces of the tubular structures and fastens them to the spacer element, loosely below a predetermined temperature range and conversely, tightly above the predetermined temperature range.

(28) The spacer element is also configured to distribute stress in each of the plurality of tubular structures in relation to the spacer element. Surface features may be present on the spacer. Further, the tube spacing and fastening system of the present disclosure may allow for coupling of multiple tubular structures in a manner that reduces, prevents, or eliminates high stress concentrations.

(29) Gas turbine engine installations include tubes or conduits carrying fuel, oil, hydraulic fluids or pressurized air. The tubes or conduits are usually bundled together to carry the fluid within or across several compartments and components (such as fan, compressor, turbine) of the engine under a nacelle or to discharge the fluid overboard. Tube or pipe assemblies deployed in engineering assemblies found in aircraft engines, heat exchangers, and nuclear power structures typically bundle the tubes using spacers. The spacers may be permanently joined to the tube bundle, for example, with brazed or welded blocks and tabs. For example, a typical tube assembly of exemplary tubular structures may include, in a non-limiting manner, tubes, pipes, rods, bars, or combinations thereof. In one instance, an exemplary tube assembly may include a bank of

exemplary tubes permanently joined (e.g., brazed or welded) in a clamp forming a clamp-tube assembly. In one instance, an exemplary tube assembly may include a bank of exemplary tubes permanently joined (e.g., brazed or welded) in a spacer forming a permanently joined spacer-tube assembly.

(30) FIG. 1A shows a schematic, perspective view of a tube spacing and fastening system for tubular structures, such as tubes, pipes, rods and bars, according to an embodiment of the present disclosure, typically found in engineering assemblies associated with aircraft engines. Referring to FIG. 1A, a bank of exemplary tubes **12** is assembled in a tube spacing and fastening system **20**. The tube spacing and fastening system **20** may include a spacer element **22** configured to engage the exemplary tubes **12** and spatially separate one exemplary tube **12a** from another exemplary tube **12b**. The spacer element **22** may spatially separate the exemplary tubes **12** and distribute stress in the tube spacing and fastening system **20**. Further, a fastening element **23** is configured to extend around at least a portion of an outer surface **26** of the exemplary tubes **12** and the fastening element **23** is configured to extend around at least a portion of the outer surface **26** of the exemplary tubular structures **12**, and to fasten the exemplary tubes **12** to the spacer element **22** in an adaptively spaced configuration. In one instance, the adaptively spaced configuration may include a first length of the fastening element **23** below a predetermined temperature range and a second length of the fastening element **23** above the predetermined temperature range, such that the first length is different from the second length. Further, in another instance, the adaptively spaced configuration may include a first configuration, wherein the exemplary tubes **12** are movably spaced around the spacer element **22** and a second configuration, wherein the exemplary tubes **12** are immovably spaced around the spacer element **22**.

(31) FIG. 1B shows an enlarged schematic, perspective front view of the spacer element **22** as in the tube spacing and fastening system **20** for exemplary tubes **12** of FIG. 1A. FIG. 1C shows an enlarged schematic, perspective back view of the spacer element **22** for the tube spacing and fastening system **20** of FIG. 1A. Referring to FIGS. 1B and 1C, the spacer element **22** may include two opposing faces, a first cradle bracket **27** and a second cradle bracket **28**, separated by a core part **29** positioned in the center of the spacer element **22** and in between the first cradle bracket **27** and the second cradle bracket **28**. The first cradle bracket **27**, the second cradle bracket **28**, and/or the core part **29** may be concave or may be any shape configured to complement the shape of the exemplary tubes **12**. In one instance, the core part **29** may be a double-concave core part. The spacer element **22** may be a spacer block and may be a solid block. The first cradle bracket **27** and the second cradle bracket **28** may be formed in the body of the spacer element **22**.

(32) With continued reference to FIGS. 1B and 1C, a first contact surface **30** may engage the corresponding first exemplary tube **12a** (FIG. 1A) at the first cradle bracket **27** and a second contact surface **31** may engage the corresponding second exemplary tube **12b** (FIG. 1A) at the second cradle bracket **28**. The first contact surface **30**, the second contact surface **31**, or both, may include a number of exemplary surface features **32**, such as, for example, but not limited to, indentations or protrusions.

(33) Going into more detail, the spacer element **22** employs the first cradle bracket **27** configured to engage the first exemplary tube **12a** (FIG. 1A) and the second cradle bracket **28** configured to engage the second exemplary tube **12b** (FIG. 1A). The core part **29** spatially separates the first cradle bracket **27** from the second cradle bracket **28**, and, thereby, spatially separates the first exemplary tube **12a** engaged in the first cradle bracket **27** and the second exemplary tube **12b** engaged in the second cradle bracket **28**. The spacer element **22** further includes a first recess **33** on one side, carved between the first cradle bracket **27** and a first corresponding surface **35** of the core part **29**. In a similar manner, the spacer element **22** further includes a second recess **34** on the other side, carved between the second cradle bracket **28** and a second corresponding surface **36** of the core part **29**.

(34) The first recess **33** is configured to accommodate a first part **24** (FIG. 1A) of the fastening

element **23** and the second recess **34** is configured to accommodate a second part **25** (FIG. **1A**) of the fastening element **23**. Each of the first recess **33** and the second recess **34** includes a projected lip **49** (FIGS. **1B** and **1C**) and a seat **51** (FIGS. **1B** and **1C**) that, together, keep the fastening element **23** within the respective recess **33** and **34** and prevent from slipping out of the recess, under stress. Continuing to refer to FIGS. **1B** and **1C**, the first cradle bracket **27**, the second cradle bracket **28**, and the core part **29** may join at a top end **37** of the spacer element **22** and at a bottom end **38** of the spacer element **22**.

(35) In an embodiment of the current disclosure, the fastening element **23** may be a wrap-around band made of a shape memory alloy (SMA). Without being held to any particular theory, it is currently believed that the scientific effect of exemplary shape-memory alloys is based on the phenomenon of continuous appearance and disappearance of the martensite phase with falling temperatures and rising temperatures. This thermoelastic behavior is the result of the transformation from a parent austenite phase, stable at an elevated temperature, to the martensite phase. Specifically, when a pre-deformed, shape memory alloy specimen is heated to the temperature of the parent austenite phase, a complete recovery of the deformation takes place. Complete recovery in this process is limited by the fact that strain must not exceed a critical value which ranges, for example, from 3% to 4% for copper shape-memory effect alloys to 6% to 8% for nickel-titanium shape-memory alloys.

(36) The shape-memory effect, as embodied by the fastening element **23** as an SMA band, is a spontaneous, reproducible, and reversible shape change associated with heating and cooling throughout an overall transformation temperature range. Further, it is possible to condition or 'train' a shape-memory alloy to have a shape-memory effect by repeating the cooling and heating process a number of times. The reversible shape change could be, for example, lengthening and shortening as the trained shape-memory alloy sample is cycled between two transitional temperatures.

(37) Referring to FIG. **1A**, when the fastening element **23** is a shape memory alloy band, the fastening element **23** of the current disclosure may have an overall transition temperature range above atmospheric temperature and below a temperature such that the shape memory alloy band may assume a first configuration (length) for tightly supporting the exemplary tubes **12** at a temperature above the overall transition temperature and may assume a second configuration (length) for loosely engaging the exemplary tubes **12** below the overall transition temperature. Thus, for the exemplary tubes **12** to engage with the spacer element **22**, the shape memory alloy band may generate high radial compressive force that swages the underlying exemplary tubes **12**.

(38) In operation, when the fastening element **23** is a shape memory alloy (SMA) band, the band is configured to be oversized in a cooled, martensitic state and, then, during operation, the band is warmed up to a smaller, contracted size to generate an elastic radial compressive force and thereby engage the exemplary tubes **12** with the spacer element **22**. Further, referring to FIG. **1A**, the shape memory alloy (SMA) band, in one embodiment of the current disclosure, generates high radial compressive force and swages (compresses or shrinks) underlying tube surfaces to locally yield at the static metal-to-metal joints by swaging a number of surface features (protrusions or indentations or teeth or dimples or ridges) configured on the contact surfaces and, at the same time, remain in continued contact with the spacer element **22**.

(39) Any shape-memory alloy may be used in the present disclosure as long as it demonstrates an adequate shape-memory effect. In one embodiment of the current disclosure, the shape-memory alloys include nickel-titanium alloys, in weight ratios selected to deform at a temperature above a desired transition temperature. Further, the chemical composition and transition temperature for the shape memory metal (SMA) are further selected to be appropriate for the desired tube spacing and fastening system operating temperature between ambient and about 1000° F.

(40) Thus, exemplary shape memory alloy (SMA) bands for the fastening element **23** of FIG. **1A** utilize their shape-memory characteristic and corresponding configured and memorized length to

provide a temperature-sensitive length change and, thereby, a significant degree of adaptive spacing of the exemplary tubes **12** during operation. Specifically, when the exemplary tubes **12** are at their operating temperature above the transition temperature of the shape memory alloy (SMA) bands, typical shape memory alloy (SMA) bands transform to their memorized shorter length, providing a tight and reduced spacing and lateral loading on the exemplary tubes **12**. Referring to FIGS. **1A**, **1B**, and **1C**, the shape memory alloy (SMA) band for the fastening element **23** of the current disclosure may engage the first cradle bracket **27** and the second cradle bracket **28** and the outer surfaces **26** of the exemplary tubes **12** upon heating above the parent austenite transition temperature range to a high temperature, tight configuration of the shape-memory alloy.

(41) Conversely, once cooled below the martensite transition temperature range, typical shape memory alloy (SMA) bands convert to their low temperature configuration and is in an expanded length or stretched length or oversized length corresponding to the lower temperatures. Typically, such high temperature configurations are associated with operational conditions when the exemplary tubes **12** need to be in compact, tight and immovable contact. Further low temperature configurations are associated with maintenance or shutdown of the engineering spacing and fastening system and the shape memory alloy (SMA) band enable assume a loose configuration enabling a slidable or movable disengagement of the exemplary tubes **12** from their respective cradle brackets and the spacer element **22**. The shape memory alloy (SMA) bands and their shape-memory effect thus inherently provide adaptive spacing for the exemplary tubes **12**, in relation to each other and to the spacer element **22** to which they are fastened.

(42) The stress distribution effect of the shape memory alloy (SMA) bands may be further enhanced by adopting a stress-adaptive configuration of the spacer element **22** and related parts and components. For example, contact surfaces where two or more parts engage and/or interact with each other (e.g., the first contact surface **30** and/or the second contact surface **31**) may include a stress-adaptive configuration (e.g., surface features configured to reduce contact stress between parts). In another embodiment of the disclosure, one, or more, or all, of the joints **39** in spacer element **22** are filleted for optimal stress distribution at the corners where the fastening element **23** engages with the spacer element **22**. In other words, a first exemplary joint **39a** between the first cradle bracket **27** and the top end **37**, a second exemplary joint **39b** between the second cradle bracket **28** and the top end **37**, a third exemplary joint **39c** between the first cradle bracket **27** and the bottom end **38**, and a fourth exemplary joint **39d** between the second cradle bracket **28** and the bottom end **38** are all filleted joints.

(43) Referring to FIGS. **1A**, **1B**, and **1C**, the exemplary tubes **12** have diameter in the range of 0.75 to 1.0 inches and wall thickness in the range of 0.020 to 0.035 inches. The width of the spacer element **22** is of the order of 0.5 inches and the thickness of the shape memory alloy (SMA) band is in the range of 0.020 to 0.063 inches.

(44) Continuing to refer to FIGS. **1B** and **1C**, additional stress distribution configurations may include specially contouring the first contact surface **30** and the second contact surface **31** between the exemplary tubes **12** and the first cradle bracket **27** and the second cradle bracket **28**.

Accordingly, instead of full surface contact between a stiffer block (e.g., spacer element **22**) and a thin-walled tube (e.g., exemplary tubes **12**), which generates higher edge contact stress, the spacer element **22** may include exemplary surface features **32**. The exemplary surface features **32** may be protrusions (also known as ‘beads’) in one instance and may be indentations (also known as ‘dimples’) in another instance. In yet another instance, the surface features **32** may be any combination of protrusions and indentations. The exemplary surface features **32** can be of different shapes with varying cross sections such as spherical-circular (as shown in FIGS. **1B** and **1C**), or elliptical, or square, or trapezoidal, or triangular, or any combination of these. Thus, the exemplary surface features **32** may create a low stress field at discrete points of contact on the exemplary tubes **12**. Specifically, the first exemplary tube **12a** joins the first cradle bracket **27** at the first contact surface **30** and the second exemplary tube **12b** joins the second cradle bracket **28** at the

second contact surface **31**, and either the first contact surface **30**, or the second contact surface **31**, or both include the exemplary surface features **32** that may include protrusions and/or indentations, which may provide effective stress optimization configuration. Thus, referring to FIGS. **1A**, **1B**, and **1C**, the metal-to-metal contacts at the ‘thick-walled’ first cradle bracket **27** and the ‘thick-walled’ second cradle bracket **28** may result in high stresses, so the exemplary surface features **32** (protrusions/indentations) may be included in a non-limiting manner. In other words, the exemplary surface features **32** (protrusions/indentations) may be omitted in another instance, if desired.

(45) FIG. **2A** shows a schematic, perspective view of a tube spacing and fastening system **40** for the exemplary tubes **12**, according to an embodiment of the present disclosure. Referring to FIG. **2A**, the tube spacing and fastening system **40** includes a spacer element **42** with two opposing faces shaped as a first cradle bracket **43** and a second cradle bracket **44** separated by a core part **45**. In an embodiment of the current disclosure, outer surfaces of the first cradle bracket **43** and the second cradle bracket **44** may be marked with exemplary surface features including protrusions/indentations (not visible, such as described with respect to FIGS. **1B** and **1C**).

Continuing to refer to FIG. **2A**, a fastening element **46** is extended around at least part of an outer surface **47** of each of the exemplary tubes **12** in the tube spacing and fastening system **40** to fasten the exemplary tubes **12** to the spacer element **42**. In one instance, the fastening element **46** may be a shape memory alloy (SMA) band.

(46) FIG. **2B** shows an enlarged schematic, perspective view of the spacer element **42** as in the tube spacing and fastening system **40** for the exemplary tubes **12** of FIG. **2A**, according to an embodiment of the present disclosure. Continuing to refer to FIG. **2B**, the spacer element **42** is configured as a solid block that includes a seating slot or groove **52** to accommodate the fastening element **46**, embodied as a shape memory alloy (SMA) band. The fastening element **46**, embodied as a shape memory alloy (SMA) band, typically extends around the spacer element **42** and the exemplary tubes **12**. Further, the seating slot or groove **52** may include raised edges **54** on the spacer element **42** to provide a secure or snug seating arrangement for the fastening element **46**, embodied as a shape memory alloy (SMA) band within the seating slot or groove **52**.

(47) Continuing to refer to FIG. **2B**, additional stress distribution configurations may include specially contouring the contact surfaces between the exemplary tubes **12** and the first cradle bracket **43** and the second cradle bracket **44**. Accordingly, instead of full surface contact between a stiffer block (e.g., the spacer element **42**) and a thin-walled tube (e.g., the exemplary tubes **12**), which generate higher edge contact stress, the spacer element **42** may include exemplary surface features (not shown). The exemplary surface features may be protrusions (also known as ‘beads’) in one instance and may be indentations (also known as ‘dimples’) in another instance. In yet another instance the surface features may be any combination of protrusions and indentations. Thus, the exemplary surface features may create a low stress field at discrete points of contact on the exemplary tubes **12**. Specifically, the first exemplary tube **12a** joins the first cradle bracket **43** at a corresponding first contact surface (not shown) and the second exemplary tube **12b** joins the second cradle bracket **44** at a corresponding second contact surface (not shown), and either the first contact surface or the second contact surface or both include exemplary surface features that may include protrusions and/or indentations, which may provide effective stress distribution configuration. Thus, referring to FIGS. **2A** and **2B**, the metal-to-metal contacts at the ‘thick-walled’ first cradle bracket **43** and the ‘thick-walled’ second cradle bracket **44** may result in high stresses, so exemplary surface features (protrusions/indentations) may be included, in a non-limiting manner. In other words, the exemplary surface features (protrusions/indentations) may be omitted in another instance, as desired.

(48) FIG. **3A** shows a schematic, perspective view of a tube spacing and fastening system **60** for the exemplary tubes **12**, according to an embodiment of the present disclosure. Referring to FIG. **3A**, the bank of exemplary tubes **12** are assembled in a tube spacing and fastening system **60**. Tube spacing and fastening system **60** includes a spacer element **62** with two opposing faces shaped as a

first thin-walled bracket **63** and a second thin-walled bracket **64**. In one embodiment of the disclosure, outer surfaces of the first thin-walled bracket **63** and second thin-walled bracket **64** are marked with protrusions and/or indentations (not shown), such as described with respect to FIGS. **1B** and **1C**. The thin-walled bracket **64** and the thin-walled bracket **63** may function as cradles, such as described with respect to FIGS. **1A** to **2B**, such that the tube spacing and fastening system **60** of FIGS. **3A** and **3B** includes a plurality of cradles (e.g., thin-walled bracket **64** and thin-walled bracket **63**).

(49) FIG. **3B** shows an enlarged schematic, perspective view of the spacer element **62** as part of the tube spacing and fastening system **60** for the exemplary tubes **12** of FIG. **3A**, according to an embodiment of the present disclosure. Continuing to refer to FIG. **3B**, the spacer element **62** has a top end **65**, a bottom end **66**, and a top tray slot **67** with a raised slot edges **68**. Further, referring to FIG. **3A** and FIG. **3B**, a fastening element **72**, embodied as a shape memory alloy (SMA) band, is extended around outer surfaces **73** of the exemplary tubes **12** in the tube spacing and fastening system **60** to fasten them to the spacer element **62**.

(50) The tube spacing and fastening system **60** may include the spacer element **62** with two opposing faces shaped as the first thin-walled bracket **63** and the second thin-walled bracket **64**. In another embodiment of the disclosure, the first thin-walled bracket **63** is configured to engage the first exemplary tube **12a** and the second thin-walled bracket **64** is configured to engage the second exemplary tube **12b**. The first thin-walled bracket **63** and the second thin-walled bracket **64** join each other at the top end **65** on top of the spacer element **62** and further at the bottom end **66** of the spacer element **62**. Further, the first thin-walled bracket **63** and the second thin-walled bracket **64** are spatially separated by a hollow space in between the first thin-walled bracket **63** and the second thin-walled bracket **64**.

(51) Continuing to refer to FIGS. **3A** and **3B**, additional stress distribution configurations may include specially contouring the contact surfaces between the exemplary tubes **12** and the first thin-walled bracket **63** and the second thin-walled bracket **64**. Accordingly, instead of full surface contact between a stiffer block (e.g., the spacer element **62**) and a thin-walled tube (e.g., the exemplary tubes **12**), which generate higher edge contact stress, the spacer element **62** may include exemplary surface features (not shown). The exemplary surface features may be protrusions (also known as ‘beads’) in one instance and may be indentations (also known as ‘dimples’) in another instance. In yet another instance, the surface features may be any combination of protrusions and indentations. Thus, the exemplary surface features may create a low stress field at discrete points of contact on the exemplary tubes **12**. Specifically, the first exemplary tube **12a** joins the first thin-walled bracket **63** at a corresponding first contact surface (not shown) and the second exemplary tube **12b** joins the second thin-walled bracket **64** at a corresponding second contact surface (not shown), and either the first contact surface, or the second contact surface, or both, include exemplary surface features that may include protrusions and/or indentations, which may provide effective stress distribution configuration. Thus, referring to FIGS. **3A** and **3B**, the metal-to-metal contacts at the first thin-walled bracket **63** and the second thin-walled bracket **64** may not result in high stresses, so the exemplary surface features **32** may not be included in a non-limiting manner. In another instance, however, the exemplary surface features **32** may be included and formed as protrusions/indentations, as desired, in order to reduce existing stress.

(52) FIG. **4** is a schematic, perspective view of a tube spacing and fastening system **80** for the exemplary tubes **12** in accordance with an embodiment of the current disclosure. Referring to FIG. **5**, the tube spacing and fastening system **80** includes a spacer element **82**. The spacer element **82** may be any predetermined formation, such as a star formation, or cross formation, or any combination thereof. The spacer element **82** may include one or more radial arms **84** arranged in a star formation. Further, each of the radial arms **84** joins at its respective base with a core part **86**. The radial arms **84** and the core part **86** may be integral and unitary or may be separate parts coupled or connected together. In the non-limiting example of FIG. **4**, there are four exemplary

radial arms **84** extending from the core part **86**, but, in other embodiments, there may be fewer or more than four radial arms **84**. The number of radial arms **84** may be selected based on the number of the exemplary tubes **12** desired to be coupled together.

(53) With continued reference to FIG. 4, an exemplary pair of adjacent radial arms **84a** and **84b** (two adjacent radial arms) and the core part **86** joining at their respective base, may form an exemplary cradle bracket **88**, to engage a corresponding tubular structure, embodied as an outer surface **93** of the exemplary tubes **12**. Accordingly, in the example of FIG. 5, four cradle brackets **88** may be formed to accommodate four exemplary tubes—a first exemplary tube **12a**, a second exemplary tube **12b**, a third exemplary tube **12c** and a fourth exemplary tube **12d**. The tube spacing and fastening system **80** may include the spacer element **82** constructed in a star formation, or a cross formation, or any combination thereof, with the exemplary radial arms **84** extending outward from the core part **86**. In an embodiment, outer surfaces of the radial arms **84** (e.g., the surfaces forming the cradle bracket **88**) may be marked with surface features including protrusions/indentations (not shown), such as described with respect to FIGS. 1B, 1C, 2B, 3B, and 6A to 6C. Continuing to refer to FIG. 4, a fastening element **92**, embodied as a shape memory alloy (SMA) band may be extended around the outer surfaces **93** of each of the exemplary tubes **12** in the tube spacing and fastening system **80** to fasten them to an exemplary star formation, or a cross formation, or any combination thereof, of the spacer element **82**.

(54) FIG. 5 is a schematic, perspective view of a tube spacing and fastening system **100** for the exemplary tubes **12** in accordance with an embodiment of the current disclosure. Referring to FIG. 6, the tube spacing and fastening system **100** includes a spacer element **182**. The spacer element **182** includes three exemplary radial arms **184a**, **184b**, and **184c** arranged in a star formation. Each of the radial arms **184a**, **184b**, and **184c** joins at its respective base with a core part **186**. The radial arms **184a**, **184b**, and **184c** and the core part **186** can be integral and unitary or can be separate parts coupled or connected together.

(55) With continued reference to FIG. 5, an exemplary pair of adjacent radial arms **184b** and **184c** (two adjacent radial arms) and the core part **186** joining at their respective base, form an exemplary cradle bracket **188**, to engage a corresponding tubular structure, embodied as an outer surface **193** of the exemplary tubes **12**. Accordingly, in the example of FIG. 5, three cradle brackets **188** are formed to accommodate three exemplary tubes—the first exemplary tube **12a**, the second exemplary tube **12b**, and the third exemplary tube **12c**. The outer surfaces of the radial arms **184a**, **184b**, and **184c** (e.g., the surfaces forming the cradle bracket **188**) are marked with surface features including protrusions/indentations (not shown), such as described with respect to FIGS. 1B, 1C, 2B, 3B, and 6A to 6C. Continuing to refer to FIG. 5, a fastening element **192**, embodied as a shape memory alloy (SMA) band is extended around the outer surfaces **193** of each of the exemplary tubes **12a**, **12b** and **12c** to fasten them to the spacer element **182**.

(56) FIGS. 6A to 6C show exemplary surface features **32**, which may be provided in any or all of the spacer elements described herein, such as, for example, the spacer element **22** (FIG. 1C), the spacer element **42** (FIG. 2A), the spacer element **62** (FIG. 3A), the spacer element **82** (FIG. 4), and the spacer element **182** (FIG. 5). The exemplary surface features **32** may be prismatic surface features **32a** (FIG. 6A), elongated rectangular surface features **32b** (FIG. 6B), or rounded, semi-spherical surface features **32c** (FIG. 6C). Other shapes are also contemplated, such as, for example, cubes or other polygonal shapes, elliptical, square, trapezoidal, triangular, elongated curved shapes, continuous shapes, discrete shapes, etc. Any combination of the surface features shown and/or the surface features described may be provided on the spacer elements of the present disclosure. The surface features **32** may be protrusions, indentations, or combinations thereof. More than one shape of surface features **32** may be provided on a single bracket surface of a spacer element. More than one shape of surface features **32** may be provided on different bracket surfaces of a single spacer element. The surface features **32** described herein may be formed with additive manufacturing, electrical discharge texturing, or electroforming.

(57) Referring to FIG. 1A to FIG. 6C, the spacer element **22**, the spacer element **42**, the spacer element **62**, the spacer element **82**, and the spacer element **182** may be additively manufactured. Further, specifically, the spacer element **22**, the spacer element **42**, the spacer element **62**, the spacer element **82**, and the spacer element **182** may be optionally contoured with dimples/ridges/beads through additive manufacturing economically. In other embodiments of the disclosure, other manufacturing methods, such as traditional subtractive manufacturing may be employed to produce the parts from typical machined blocks. As for spacing and fastening system material, the spacer elements **22**, **42**, **62**, and **82** are made of steel, Inconel®, or other suitable metals, such as nitinol (Ni—Ti) that meet high temperature applications as well as provide inherent elasticity to retain extending strength needed for braze-free and weld-free joints.

(58) Any of the spacer blocks, fastening elements, and spacing and fastening systems described herein may be combined with all or portions of the other spacer blocks, fastening elements, and spacing and fastening systems described herein. Although a single spacing and fastening system is shown for the exemplary tubes **12**, more may be provided along the length of the exemplary tubes **12**. In such a manner, the tube spacing and fastening systems of the present disclosure may include a plurality of spacer blocks and fastening elements. The number may be selected based on the desired coupling and securement of the exemplary tubes **12**.

(59) FIG. 7 is a block diagram of a method **200** of spacing and fastening tubular structures in accordance with one embodiment of the current disclosure. Referring to FIG. 7, the method **200** of spacing and fastening tubular structures, such as the exemplary tubes **12**, includes in step **202**, providing a spacer element, in step **204**, engaging a plurality of tubular structures to the spacer element, in step **206**, spatially separating the plurality of tubular structures from one another, and in step **208**, distributing stress in the plurality of tubular structures. The method **200** further includes, in step **212**, extending a fastening element around at least a portion of an outer surface of the plurality of tubular structures and in step **214**, fastening the plurality of tubular structures to the spacer element in an adaptively spaced configuration.

(60) In another embodiment of the current disclosure, the method **200** of spacing and fastening tubes further includes non-permanently engaging a first exemplary tube **12a** to a first cradle bracket (FIGS. 1B and 1C, 27; FIG. 2A, 43; FIG. 3A, 63; FIG. 4, 88; FIG. 5, 188), engaging a second exemplary tube **12b** to a second cradle bracket (FIGS. 1B and 1C, 28; FIG. 2A, 44; FIG. 3A, 64; FIG. 4, 88; FIG. 5, 188) such that the first exemplary tube **12a** and the second exemplary tube **12b** are spatially separated.

(61) In one aspect of the disclosure, the tube spacing and fastening systems of the present disclosure use appropriate fastening elements to space and fasten the tubes and/or pipes with their structural integrity intact and without any cutting or shearing of the tubes and/or pipes. The spacing and fastening elements, as described in the embodiments of the current disclosure, thereby, improve on several critical operational performance factors including high stress concentration (K_t) at tube joints, difficulty in controlling uniformness of quality (owing to voids, limited braze/weld witness feature, and lack of coverage), low high-cycle fatigue (HCF) capability of material flux, geometric stress concentration, and rapid transition from flexible tube surfaces to stiff constraining elements.

(62) Although described as engaging the exemplary tubes **12**, the connection provided by the spacer element and the fastening element may be permanent in one instance. In other instances, the connection provided by the spacer element and fastening element to engage the exemplary tubes **12** may be non-permanent. In some embodiments, the spacer element and the fastening element may be retrofit onto the exemplary tubes **12**. The spacer element and the fastening element may be capable of being serviceable or replaceable, in the manufacturing plant or in the field.

(63) The tube spacing and fastening systems of the present disclosure may include shape memory alloy (SMA) bands as a fastening element that provides an advantage over permanently joined spacing and fastening system configurations that sometime hold the tubes too tenaciously during tube reconstitution and/or tend to score the tubes during installation.

(64) The tube spacing and fastening systems of the present disclosure provide a non-brazed, non-welded connection or coupling of tubes. The non-brazed, non-welded tube bundle configurations using shape memory alloy (SMA) bands for connecting the tubes and the spacer element may address issues associated with stress concentration of brazed or welded joints. Shape memory alloy (SMA) bands extended around tubes joining at the spacer element offer smooth stress distribution without any sudden transition of stiffness from spacer element to the tubes.

(65) The tube spacing and fastening systems of the present disclosure may provide adaptive spacing and fastening and dismantling by employing thermally elastic compressive shape memory alloy (SMA) bands that continue to keep tube bundles in continued contact with spacer element even in case of contact wear as is customary for non-brazed and non-welded tube bundle configurations.

(66) The tube spacing and fastening systems of the present disclosure include shape memory alloy (SMA) bands as fastening elements that are provided with a memorized length, and are produced and installed generally around tubes so as to provide tube adaptive spacing. When the shape memory alloy (SMA) bands are at their operating temperature above the transition temperature of the shape memory alloy (SMA) bands, the shape memory alloy (SMA) bands transform to the memorized length, thereby providing reduced spacing and lateral loading to the tubes. The shape memory alloy (SMA) bands thus inherently provide adaptive spacing for the tubes in the tube bundles, in relation to each other and the spacer element.

(67) Exemplary shape memory alloys may include alloys of any of Ni—Ti, or Ni—Ti—Hf, or Ni—Ti—Pd or Ti—Au—Cu

(68) Any of the fastening elements of the present disclosure may be a shape memory alloy band. The shape memory alloy bands operate as fasteners to isolate a joint assembly of one or more tubular structures. In some examples, the shape memory alloy (SMA) properties improve the reliability and performance of tube assembly as compared to conventional metal fasteners. The shape memory alloy (SMA) bands enable a high performing and reliable isolation joint assembly through stress induced martensite transformation in shape memory alloy (SMA) band fasteners. For example, shape memory alloy (SMA) bands have superelasticity, variable stiffness, and high energy dissipation. These features may provide the following benefits:

(69) Superelasticity: NiTi based shape memory alloy (SMA) bands demonstrate superelastic behavior up to eight percent to ten percent of recoverable strain. This is compared to 0.2 percent of recoverable strain in typical metal (e.g., steel). The superelastic behavior allows the shape memory alloy (SMA) fasteners to undergo large deformation under high engine imbalance condition without failure and allows for the shape memory alloy (SMA) band to recover back to the shape memory alloy (SMA) band's initial shape when the load (e.g., engine condition) is released.

(70) Variable stiffness: NiTi based shape memory alloy (SMA) bands demonstrate unique variable stiffness that, combined with superelastic behavior, may be tuned to control the system response under different loading or engine operating condition. That is, tuned to allow control of the degree of fastening of the tubular structures.

(71) High energy dissipation: shape memory alloy (SMA) exhibit high damping properties during martensitic phase transformation through hysteretic damping that may assist control of a vibratory response. NiTi shape memory alloy (SMA) bands may demonstrate high hysteretic material damping up to six percent, which is higher than conventional metal (e.g., steel) bands.

(72) Furthermore, the shape memory alloy (SMA) bands design can be used as an effective isolation system to control tube response under engine vibration and/or imbalance condition as follows:

(73) Normal engine vibration: At lower strains (less than one percent), the elastic modulus of the austenite phase of the shape memory alloy (SMA) band comes into action to withstand normal engine operating condition.

(74) High engine vibration and imbalance loads: Under this engine condition, the shape memory

alloy (SMA) band can be designed to deform to moderate to high strains levels (up to eight percent). At this strain level, the shape memory alloy (SMA) band behaves as a superelastic material with plateau stress. There may be little or no change in stress level, such that tube joint assembly can withstand large range deformation with almost no increase in stress levels. This low elastic modulus behaviour of the shape memory alloy (SMA) band acts as an effective isolation system for the tubular structures from high input vibration or engine imbalance loads.

(75) Extreme engine imbalance condition like blade out: The shape memory alloy (SMA) band can be designed for large strain (eight percent to ten percent) development under extreme engine imbalance condition. Increased elastic modulus and high strength martensitic phase of fastener can withstand extreme imbalance condition without failure and can recover back to the initial shape of the shape memory alloy (SMA) band when the load is released.

(76) The tube spacing and fastening systems of the present disclosure may include multiple configurations of spacer elements including recessed block, solid unrecessed block, thin-walled, cross formation, or star formation spacer elements that provide a wide flexibility in the number of tubes to be engaged and adaptability in the design of the fastening elements to effectively support and spatially separate individual tubes in an assembled bundle. In some examples, the spacer element may be a thick-walled, solid block. Such a block may include surface features on the contact surfaces to reduce stresses between the thin-walled tubes and the thick-walled spacer element. In some examples, the spacer element may be thin-walled.

(77) The tube spacing and fastening systems of the present disclosure may provide effective stress distribution at tube spacing and fastening system joints, low stress field through protrusions, and/or indentations (also known as ‘beads’/‘dimples’) contoured on recessed blocks, solid blocks, thin-walled, cross formation, or star formation spacer elements, filleted joints and, thereby, improve reliability of each configuration of the tube bundle assemblies.

(78) The tube spacing and fastening systems of the present disclosure may provide cost effective configurations that eliminate inspection and quality control issues related to permanently joined tube bundle assemblies such as brazed joints or welded joints. The tube spacing and fastening systems of the present disclosure improves ‘Time on Wing’ with by reducing typical field issues related to brazed or welded joints.

(79) The tube spacing and fastening systems of the present disclosure inherently provide adaptive spacing and compact tube bundle routing for optimal tube packaging that save significant amount of space, cost, and weight. In one instance, the fastening element may be replaced without disregarding the tubes.

(80) Further aspects of the present disclosure are provided by the subject matter of the following clauses.

(81) A system includes a spacer element configured to engage a plurality of tubular structures, to spatially separate the plurality of tubular structures from one another, and to distribute stress in the plurality of tubular structures. A fastening element is configured to extend around at least a portion of an outer surface of the plurality of tubular structures, and to fasten the plurality of tubular structures to the spacer element in an adaptively spaced configuration.

(82) The system according to any preceding clause, wherein the adaptively spaced configuration comprises a first length of the fastening element below a predetermined temperature range and a second length of the fastening element above the predetermined temperature range. The first length is different from the second length.

(83) The system according to any preceding clause, wherein the adaptively spaced configuration comprises a first configuration, wherein the plurality of tubular structures are movably spaced around the spacer element and a second configuration, wherein the plurality of tubular structures are immovably spaced around the spacer element.

(84) The system according to any preceding clause, wherein the spacer element includes a first thin-walled bracket to engage a first tubular structure of the plurality of tubular structures and a

second thin-walled bracket to engage a second tubular structure of the plurality of tubular structures. The first thin-walled bracket and the second thin-walled bracket join at a top end of the spacer element and at a bottom end of the spacer element.

(85) The system according to any preceding clause, wherein the spacer element includes a first cradle bracket configured to engage a first tubular structure of the plurality of tubular structures, a second cradle bracket configured to engage a second tubular structure of the plurality of tubular structures, and a core part separating the first cradle bracket and the second cradle bracket. The first cradle bracket, the second cradle bracket, and the core part join at a top end of the spacer element and at a bottom end of the spacer element.

(86) The system according to any preceding clause, wherein a first joint between the first cradle bracket and the top end, or a second joint between the second cradle bracket and the top end, or a third joint between the first cradle bracket and the bottom end, or a fourth joint between the second cradle bracket and the bottom end, or any combination thereof, comprises a filleted joint.

(87) The system according to any preceding clause, further includes a first recess formed between the first cradle bracket and a first corresponding surface of the core part, and a second recess formed between the second cradle bracket and a second corresponding surface of the core part. The first recess is configured to accommodate a first part of the fastening element, and the second recess is configured to accommodate a second part of the fastening element.

(88) The system according to any preceding clause, wherein a first tubular structure of the plurality of tubular structures engages with the first cradle bracket at a first contact surface and a second tubular structure of the plurality of tubular structures engages with the second cradle bracket at a second contact surface. The first contact surface, or the second contact surface, or both of the first contact surface and the second contact surface includes a plurality of surface features configured to distribute the stress in the plurality of tubular structures.

(89) The system according to any preceding clause, wherein the plurality of surface features comprises a plurality of protrusions, or indentations, or any combination thereof.

(90) The system according to any preceding clause, wherein the spacer element includes a core part positioned at a center of the spacer element, and a plurality of radial arms arranged in a predetermined formation, each radial arm joining at a respective base with the core part. At least one pair of adjacent radial arms and the core part form a cradle bracket configured to engage a corresponding tubular structure in the cradle bracket.

(91) The system according to any preceding clause, wherein the predetermined formation comprises a cross formation, or a star formation, or any combination thereof.

(92) The system according to any preceding clause, wherein the fastening element comprises a shape memory alloy (SMA) band.

(93) The system according to any preceding clause, wherein the shape memory alloy (SMA) band comprises nickel-titanium shape-memory alloy.

(94) A method includes providing a spacer element, engaging a plurality of tubular structures to the spacer element, spatially separating the plurality of tubular structures from one another, and distributing stress in the plurality of tubular structures, extending a fastening element around at least a portion of an outer surface of the plurality of tubular structures, and fastening the plurality of tubular structures to the spacer element in an adaptively spaced configuration.

(95) The method according to any preceding clause, wherein the fastening of the plurality of tubular structures to the spacer element in the adaptively spaced configuration comprises fastening the plurality of tubular structures to the spacer element by a first length of the fastening element below a predetermined temperature range, and fastening the plurality of tubular structures to the spacer element by a second length of the fastening element above the predetermined temperature range. The first length is different from the second length.

(96) The method according to any preceding clause, wherein the fastening of the plurality of tubular structures to the spacer element in the adaptively spaced configuration comprises fastening

the plurality of tubular structures to the spacer element in a first configuration, wherein the plurality of tubular structures are movably spaced around the spacer element, and a second configuration, wherein the plurality of tubular structures are immovably spaced around the spacer element.

(97) The method according to any preceding clause, wherein the engaging of the plurality of tubular structures to the spacer element comprises engaging a first tubular structure of the plurality of tubular structures to a first thin-walled bracket of the spacer element, engaging a second tubular structure of the plurality of tubular structures to a second thin-walled bracket of the spacer element, and joining the first thin-walled bracket, the second thin-walled bracket at a top end of the spacer element and at a bottom end of the spacer element. The spatially separating the plurality of tubular structures from one another comprises spatially separating the first thin-walled bracket and the second thin-walled bracket by a hollow space in between the first thin-walled bracket and the second thin-walled bracket.

(98) The method according to any preceding clause, wherein the engaging of the plurality of tubular structures to the spacer element comprises engaging a first tubular structure of the plurality of tubular structures to a first cradle bracket of the spacer element, engaging a second tubular structure of the plurality of tubular structures to a second cradle bracket of the spacer element, and joining the first cradle bracket, the second cradle bracket, and a core part of the spacer element at a top end of the spacer element and at a bottom end of the spacer element. The spatially separating the plurality of tubular structures from one another comprises spatially separating the first cradle bracket and the second cradle bracket by the core part positioned in between the first cradle bracket and the second cradle bracket.

(99) The method according to any preceding clause, wherein the extending of the fastening element comprises filleting a first joint between the first cradle bracket and the top end, or a second joint between the second cradle bracket and the top end, or a third joint between the first cradle bracket and the bottom end, or a fourth joint between the second cradle bracket and the bottom end, or any combination thereof.

(100) The method according to any preceding clause, wherein the extending of the fastening element comprises accommodating a first part of the fastening element in a first recess between the first cradle bracket and a first corresponding surface of the core part, and accommodating a second part of the fastening element in a second recess between the second cradle bracket and a second corresponding surface of the core part.

(101) The method according to any preceding clause, wherein the engaging of each of the plurality of tubular structures to the spacer element comprises joining a first tubular structure of the plurality of tubular structures and the first cradle bracket at a first contact surface, joining a second tubular structure of the plurality of tubular structures and the second cradle bracket at a second contact surface. The distributing of stress in the plurality of tubular structures comprises providing a plurality of surface features on the first contact surface, or the second contact surface, or both of the first contact surface and the second contact surface.

(102) The method according to any preceding clause, wherein the providing of the plurality of surface features comprises providing a plurality of protrusions, or indentations, or any combination thereof.

(103) The method according to any preceding clause, wherein the providing of the spacer element comprises arranging a plurality of radial arms in a predetermined formation, joining each radial arm at a respective base with a core part of the spacer element, forming a cradle bracket with at least one pair of adjacent radial arms and the core part, and engaging a corresponding one of the plurality of tubular structures in the cradle bracket.

(104) The method according to any preceding clause, wherein the arranging of the plurality of radial arms in the predetermined formation comprises arranging the plurality of radial arms in a cross formation, or arranging the plurality of radial arms in a star formation, or arranging the plurality of radial arms in any combination thereof.

(105) The method according to any preceding clause, wherein the extending the fastening element comprises extending a shape memory alloy (SMA) band.

(106) The method according to any preceding clause, wherein the shape memory alloy (SMA) band comprises nickel-titanium shape-memory alloy.

(107) Although the foregoing description is directed to the preferred embodiments, it is noted that other variations and modifications will be apparent to those skilled in the art, and may be made without departing from the spirit or scope of the disclosure. Moreover, features described in connection with one embodiment may be used in conjunction with other embodiments, even if not explicitly stated above.

Claims

1. A system comprising: a spacer element configured to engage a plurality of tubular structures, to spatially separate the plurality of tubular structures from one another, and to distribute stress in the plurality of tubular structures, wherein the spacer element comprises: a first cradle bracket configured to engage a first tubular structure of the plurality of tubular structures, the first cradle bracket having a shape that compliments a shape of the first tubular structure; a second cradle bracket configured to engage a second tubular structure of the plurality of tubular structures, the second cradle bracket having a shape that compliments a shape of the second tubular structure; a core part separating the first cradle bracket and the second cradle bracket, the core part extending between a top end and bottom end and having a first corresponding surface that has a same shape as the shape of the first cradle bracket and a second corresponding surface that has a same shape as the shape of the second cradle bracket, wherein the core part includes a first side surface that extends from the top end to the bottom end and a second side surface opposite the first side surface that extends from the top end to the bottom end, the spacer element having a first opening defined between the first cradle bracket and the first side surface of the core part and a second opening defined between the second cradle bracket and the first side surface of the core part; a first recess formed between the first cradle bracket and the first corresponding surface of the core part, the first recess having a same shape as the shape of the first cradle bracket and the first corresponding surface; and a second recess formed between the second cradle bracket and the second corresponding surface of the core part, the second recess having a same shape as the shape of the second cradle bracket and the second corresponding surface; and a fastening element having a first continuous band and a second continuous band each configured to extend around at least a portion of an outer surface of the plurality of tubular structures, and to fasten the plurality of tubular structures to the spacer element in an adaptively spaced configuration, wherein the first continuous band of the fastening element is inserted into the first recess through the first opening and extends through the first recess and the second continuous band of the fastening element is inserted into the second recess through the second opening and extends through the second recess.
2. The system of claim 1, wherein the adaptively spaced configuration comprises a first length of the fastening element below a predetermined temperature range and a second length of the fastening element above the predetermined temperature range, the first length being different from the second length.
3. The system of claim 1, wherein the adaptively spaced configuration comprises a first configuration, the plurality of tubular structures are movably spaced around the spacer element and a second configuration, the plurality of tubular structures are immovably spaced around the spacer element.
4. The system of claim 1, wherein the first continuous band and the second continuous band comprise a shape memory alloy (SMA) band, the shape memory alloy (SMA) band comprising a nickel-titanium shape-memory alloy.
5. The system of claim 1, wherein at least one tubular structure of the plurality of tubular structures

engages with the spacer element at a contact surface, the contact surface comprising a plurality of surface features configured to distribute the stress in the plurality of tubular structures, wherein the plurality of surface features comprises a plurality of protrusions, a plurality of indentations, or any combination thereof.

6. The system of claim 5, wherein the plurality of surface features includes different shapes with varying cross sections that include at least one of spherical-circular, elliptical, square, trapezoidal, or triangular.

7. The system of claim 1, wherein the first cradle bracket, the second cradle bracket, and the core part join at the top end of the spacer element or at the bottom end of the spacer element.

8. The system of claim 7, wherein the top end or the bottom end or both comprises a slot with raised slot edges for receiving the fastening element.

9. The system of claim 7, wherein a first joint between the first cradle bracket and the top end, or a second joint between the second cradle bracket and the top end, or a third joint between the first cradle bracket and the bottom end, or a fourth joint between the second cradle bracket and the bottom end, or any combination thereof, comprises a filleted joint.

10. The system of claim 1, wherein the first recess includes a projected lip that prevents the first continuous band of the fastening element from slipping in the first recess, and the second recess includes a projected lip that prevents the second continuous band of the fastening element from slipping in the second recess.

11. The system of claim 1, wherein the first recess includes a seat that prevents the first continuous band of the fastening element from slipping in the first recess, and the second recess includes a seat that prevents the second continuous band of the fastening element from slipping in the second recess.

12. The system of claim 1, wherein the first cradle bracket and the second cradle bracket are concave.

13. A method comprising: providing a spacer element; engaging a plurality of tubular structures to the spacer element, spatially separating the plurality of tubular structures from one another, and distributing stress in the plurality of tubular structures, wherein the engaging of the plurality of tubular structures to the spacer element comprises engaging a first tubular structure of the plurality of tubular structures to a first cradle bracket of the spacer element, engaging a second tubular structure of the plurality of tubular structures to a second cradle bracket of the spacer element, and the spatially separating the plurality of tubular structures from one another comprises spatially separating the first cradle bracket and the second cradle bracket by a core part positioned in between the first cradle bracket and the second cradle bracket; extending a fastening element around at least a portion of an outer surface of the plurality of tubular structures, wherein the extending of the fastening element comprises: inserting a first continuous band of the fastening element into a first recess of the first cradle bracket through a first opening defined between the first cradle bracket and a first side surface of the core part, and inserting a second continuous band of the fastening element into a second recess of the second cradle bracket through a second opening defined between the second cradle bracket and the first side surface of the core part; and accommodating the first continuous band of the fastening element in a first recess between the first cradle bracket and a first corresponding surface of the core part of the spacer element, and accommodating the second continuous band of the fastening element in a second recess between the second cradle bracket and a second corresponding surface of the core part of the spacer element; and fastening the plurality of tubular structures to the spacer element in an adaptively spaced configuration.

14. The method of claim 13, wherein the engaging of each of the plurality of tubular structures to the spacer element comprises joining at least one tubular structure of the plurality of tubular structures at a contact surface, and wherein the distributing of stress in the plurality of tubular structures comprises providing a plurality of surface features on the contact surface, wherein the

plurality of surface features are a plurality of protrusions, a plurality of indentations, or any combination thereof.

15. The method of claim 14, wherein the plurality of surface features includes different shapes with varying cross sections that include at least one of spherical-circular, elliptical, square, trapezoidal, or triangular.

16. The method of claim 13, wherein the engaging of the plurality of tubular structures to the spacer element comprises joining the first cradle bracket, the second cradle bracket, and the core part of the spacer element at a top end of the spacer element or at a bottom end of the spacer element.

17. The method of claim 16, wherein the extending of the fastening element comprises filleting a first joint between the first cradle bracket and the top end, or a second joint between the second cradle bracket and the top end, or a third joint between the first cradle bracket and the bottom end, or a fourth joint between the second cradle bracket and the bottom end, or any combination thereof.

18. The method of claim 13, wherein the extending of the fastening element comprises preventing the first continuous band of the fastening element from slipping in the first recess with a projected lip in the first recess, and preventing the second continuous band of the fastening element from slipping in the second recess with a projected lip in the second recess.

19. The method of claim 13, wherein the extending of the fastening element comprises preventing the first continuous band of the fastening element from slipping in the first recess with a seat in the first recess, and preventing the second continuous band of the fastening element from slipping in the second recess with a seat in the second recess.

20. The method of claim 13, wherein the first cradle bracket and the second cradle bracket are concave.
