

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12411081

Kind Code

B2

Date of Patent

September 09, 2025

Inventor(s)

Huelson; Eric Christopher et al.

Combustion-zone chemical sensing system and associated method

Abstract

A combustion-zone chemical sensing system (**100**) is disclosed that includes pitch reflective optics (**110**) that collimate MIR electromagnetic energy from an input fiber (**150**), a reflector (**120**), catch reflective optics (**112**) that focus reflected MIR electromagnetic energy into an output fiber (**152**), and a detector (**140**) to detect MIR electromagnetic energy from the output fiber. An optical head (**102**) for sensing a combustion zone (**104**) is disclosed that includes pitch reflective optics (**110**) that collimate MIR electromagnetic energy from an input fiber (**150**) towards a reflector (**120**), catch reflective optics (**112**) that focus MIR electromagnetic energy, reflected from the reflector, into an output fiber (**152**), and an alignment housing that interfaces with structure adjacent the combustion zone. A method for determining gas concentration within a combustion zone is disclosed that includes collimating MIR electromagnetic energy exiting from an input fiber to traverse a combustion zone and focusing reflected MIR electromagnetic energy from the combustion zone into an output fiber.

Inventors: Huelson; Eric Christopher (Golden, CO), Masterson; Bernard P. (Louisville, CO), Hayden; Torrey (Arvada, CO)

Applicant: MG Smart Ventures, LLC (Dover, DE)

Family ID: 77914417

Assignee: MG SMART VENTURES, LLC (Dover, DE)

Appl. No.: 18/022526

Filed (or PCT Filed): September 16, 2021

PCT No.: PCT/IB2021/058469

PCT Pub. No.: WO2022/074488

PCT Pub. Date: April 14, 2022

Prior Publication Data

Document Identifier

US 20230314312 A1

Publication Date

Oct. 05, 2023

Related U.S. Application Data

us-provisional-application US 63089555 20201009

Publication Classification

Int. Cl.: G01N21/3504 (20140101)

U.S. Cl.:

CPC G01N21/3504 (20130101); G01N2201/06113 (20130101); G01N2201/0636 (20130101); G01N2201/08 (20130101)

Field of Classification Search

CPC: G01N (21/3504); G01N (2201/06113); G01N (2201/0636); G01N (2201/08); G01N (21/359); G01N (2021/0314); G01N (2021/3155); G01N (2021/3513); G01N (2021/399); G01N (2201/0633); G01J (3/021); G01J (3/42)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7248755	12/2006	Sappey et al.	N/A	N/A
2003/0098412	12/2002	Gentala	N/A	N/A
2005/0162655	12/2004	Nadler	N/A	N/A
2006/0102844	12/2005	Sauer	250/339.13	G01N 21/3504
2007/0242275	12/2006	Spartz	356/451	G01N 21/031
2018/0172580	12/2017	Bjorøy	N/A	N/A
2019/0301737	12/2018	Masterson et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2750609	12/1997	JP	N/A
2005103781	12/2004	WO	N/A
2007087081	12/2006	WO	N/A
2008065336	12/2007	WO	N/A

OTHER PUBLICATIONS

International Preliminary Report on Patentability received for PCT Application No. PCT/IB2021/058469, mailed on Apr. 20, 2023, 11 pages. cited by applicant
International Search Report and Written Opinion received for PCT Application No.

PCT/IB2021/058469, mailed on Nov. 26, 2021, 15 pages. cited by applicant
Masiyano, D., et al., "Use of diffuse reflections in tunable diode laser absorption spectroscopy: implications of laser speckle for gas absorption measurements", Applied Physics B: Lasers and Optics, Vo. 90, 2008, pp. 279-288. cited by applicant
Palmer, J., et al., "Propagation of Optical Radiation", Chapter. 2, the Art of Radiometry, 2009, pp. 11-59. cited by applicant
Severin, P.J., et al., "A Simple Multimode Fiber Interferometric Sensor For Pressure-Related Measurements", Philips Journal of Research, vol. 43, No. 2, 1998, pp. 137-151. cited by applicant

Primary Examiner: Kim; Kiho

Attorney, Agent or Firm: Perilla Knox & Hildebrandt LLP

Background/Summary

RELATED APPLICATIONS

(1) This application is a national phase of PCT/IB2021/058469, filed on Sep. 16, 2021, which claims priority U.S. Provisional Patent Application No. 63/089,555, filed Oct. 9, 2020, which is incorporated herein by reference in their entirety.

BACKGROUND

(2) Tunable diode laser absorption spectroscopy (TDLAS) has been used to monitor combustion including combustion in large-scale furnaces. TDLAS systems monitor the presence or concentration of gases within combustion process chambers and in combustion zones. These systems use near infrared (NIR) and visible light with fiber optic cables to direct electromagnetic energy from a laser on one side of the combustion zone where the light may be absorbed by chemical species in the chamber; remaining light is focused into another fiber optic cable on the other side of the combustion zone and directed to a detector where the signal is detected and analyzed so that a concentration of one or more species can be calculated.

(3) Conventional TDLAS systems thus utilize separate pitch and a catch heads, both connected by fiber optics cables to the laser and the detector, respectively. This allows for maintaining sufficient distances between the electronics, lasers, and detectors of the TDLAS system and the high-temperature combustion process chamber. The pitch head and catch head are located at two locations around the combustion process chamber and may be positioned directly across the chamber to maximize interactions of light with combustion species to thereby increase the signal-to-noise ratio.

SUMMARY OF THE INVENTION

(4) In an embodiment, a combustion-zone chemical sensing system includes pitch reflective optics on a first side of the combustion zone that collimate MIR electromagnetic energy from an input fiber; a reflector on a second side of the combustion zone that reflects collimated MIR electromagnetic energy; catch reflective optics on the first side of the combustion zone that focus reflected MIR electromagnetic energy into an output fiber; and a detector to detect MIR electromagnetic energy from the output fiber.

(5) In an embodiment, an optical head for sensing a combustion zone includes pitch reflective optics that collimate MIR electromagnetic energy from an input fiber towards a reflector; catch reflective optics that focus MIR electromagnetic energy into an output fiber, reflected from the reflector; and an alignment housing that interfaces with structure adjacent the combustion zone and that holds and positions the pitch reflective optics and catch reflective optics with respect to the combustion zone.

(6) In an embodiment, a method for determining gas concentration within a combustion zone includes collimating MIR electromagnetic energy exiting from an input fiber to traverse a combustion zone; and focusing reflected MIR electromagnetic energy from the combustion zone to an output fiber.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) FIG. 1 illustrates a combustion-zone chemical sensing system, according to an embodiment.
- (2) FIG. 2 illustrates an optical head for sensing that may be used with the combustion-zone chemical sensing system of FIG. 1, according to an embodiment
- (3) FIG. 3 illustrates the optical head of FIG. 2 viewed along an orthogonal axis, according to an embodiment.
- (4) FIGS. 4A and 4B show one embodiment of the optical head shown in FIGS. 2 and 3 viewed along two perpendicular side views.
- (5) FIG. 5 is a flowchart illustrating a method for determining gas concentration within a combustion zone and suitable for use with the system of FIG. 1, according to an embodiment.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (6) Using optical techniques to monitor efficiency inside combustion process chambers is advantageous because, among other reasons, invasive monitoring probes may affect the processes being monitored. Tunable diode laser absorption spectroscopy (TDLAS) has been used to monitor a range of combustion processes using a variety of absorption features of gases that are found in combustion environments. Water vapor, carbon dioxide and carbon monoxide are frequent targets due to their relatively strong absorption features, each having known absorption features in the near infrared (NIR) and visible region of the electromagnetic spectrum. In some situations, it would be desirable to expand the bandwidth of light used in TDLAS systems since some molecules have strong absorption features in the longer-wavelength portion of the infrared, specifically within the mid infrared (MIR). Carbon monoxide, for example, has an absorption feature near $\lambda=2302$ nanometers (nm) that exhibits much stronger absorption than any CO absorption features in the NIR and visible.
- (7) Operating TDLAS systems in the infrared is challenging in practice, however, because the materials used in conventional fiber optics often exhibit attenuated transmission at longer wavelengths, which limits the available signal-to-noise ratio of infrared measurements. For this reason, conventional TDLAS uses a CO absorption feature at $\lambda=1560$ nm, which limits the detection limit of CO due to the weaker absorption cross section.
- (8) Another challenge in operating TDLAS systems with MIR electromagnetic energy is that lenses used to focus light into and out of the fiber optic cables display chromatic aberration for longer wavelengths. Conventional lenses use the index of refraction of the lens material to refract light at the lens's surface and redirect it; however, the index of refraction changes with changing wavelength and so it is difficult to design lens-based optical systems that focus not only NIR and visible electromagnetic energy but also MIR electromagnetic energy.
- (9) The present embodiments ameliorate the above-mentioned challenges and allow the use of TDLAS system at visible, NIR, and MIR wavelengths, thereby increasing the detection sensitivity and system functionality.
- (10) In order to maintain sufficient light intensity to perform measurements using MIR electromagnetic energy, the present embodiments describe a TDLAS system with a single optical head (FIGS. 1, 2, 3, 4) mounted to the combustion process chamber. By removing the need for a second optical head, the length of required fiber optic cable is dramatically reduced while sufficient distances are maintained between the combustion process chamber and electrical systems required

to run TDLAS. In conventional two-optical-head setups, additional fiber optic cable is required to connect both the pitch head and the catch head to the electrical components of the system. For a large process chamber, e.g., one with a diameter equal to fifteen meters, the fiber optic cable must travel halfway around the perimeter of the chamber to connect the other optical head to the laser, detector, and associated electronics, adding roughly twenty meters of additional fiber optic cable to the system. Given the low transmissivity of MIR light within the fiber optic cable, there is not sufficient light intensity to perform MIR measurements with the two-head prior art solution.

(11) In combination with the optical head described herein, a reflector is mounted inside the combustion process chamber to redirect electromagnetic energy from the optical head back across the combustion process chamber to the single optical head. In an embodiment, a retroreflector (e.g. a corner-cube mirror) is used as the reflector to direct the incoming light directly back toward the optical head for input to the output fiber optic, where it may be analyzed by associated detector and analysis electronics.

(12) To accommodate a broad bandwidth of light, the combustion-zone chemical sensing system described herein utilizes mirrors that exhibit negligible wavelength dependence over the range of frequencies used. In an embodiment, therefore, an off-axis parabolic mirror is used to collimate light exiting the input fiber optic cable of the optical head; and a second off-axis parabolic mirror at the same optical head is used to focus light into the output fiber optic cable.

(13) FIG. 1 illustrates a combustion-zone chemical sensing system **100** with pitch reflective optics **110**, a reflector **120**, catch reflective optics **112** and a detector **140**. Pitch reflective optics **110** and catch reflective optics **112** are on a first side **106** of a combustion zone **104** and the reflector **120** is on a second side **108** of the combustion zone **104**. The pitch reflective optics **110** collimate MIR electromagnetic energy from an input fiber **150** to form the collimated electromagnetic energy **116** that traverses the combustion zone **104**. The electromagnetic energy is reflected by the reflector **120**, which may be positioned directly across the combustion zone **104** as shown. The reflector **120** may be located at other positions around the combustion zone **104** without departing from the scope herein. The catch reflective optics **112** focus reflected MIR electromagnetic energy into an output fiber **152** where it is conveyed to the detector **140**. In an embodiment, the pitch reflective optics **110** and catch reflective optics **112** both mount to an optical head **102** that holds and positions the pitch reflective optics **110** and catch reflective optics **112** with respect to the combustion zone **104**. In an embodiment, collimated electromagnetic energy **116** interacts with a gas species **118** generated by a combustion source **114** that is located in the combustion zone **104** and some of collimated electromagnetic energy **116** is absorbed, leading to a reduction in the power measured by detector **140**. This absorption may be used to calculate a concentration of the gas species **118** present within the combustion zone **104**. FIG. 1 includes axis indicators **198X**, **198Y**, and **198Z**, which indicate the cartesian-coordinate system with X-axis, Y-axis and Z-axis associated with the combustion-zone chemical sensing system **100** illustrated in FIG. 1.

(14) In an embodiment, the pitch reflective optics **110** further collimate near infrared (NIR) and visible electromagnetic energy in addition to MIR electromagnetic energy. As in the MIR, NIR and visible electromagnetic energy is reflected by reflector **120** and then focused by catch reflective optics **112** into the output fiber **152** and subsequently detected by detector **140**. In this embodiment, the combustion-zone chemical sensing system **100** may be used with MIR, NIR, and visible light, thereby expanding the range of molecules that may be detected and increasing sensitivity of detection. For example, the combustion-zone chemical sensing system **100** may be operated using electromagnetic energy with $\lambda=2302$ nm, strongly absorbed by CO, and with electromagnetic energy of $\lambda=760$ nm, strongly absorbed by O₂.

(15) In an embodiment, the input fiber **150** and the output fiber **152** have a combined length of less than twenty-eight meters. Electromagnetic energy with longer wavelengths, e.g., $\lambda=2302$ nm, is absorbed more than shorter wavelength light, e.g., $\lambda=760$ nm. Reducing the total length of fiber optic cable used in the combustion-zone chemical sensing system **100** increases the total amount of

MIR electromagnetic energy that reaches the combustion zone **104** and the detector **140**, thereby increasing sensitivity of the combustion-zone chemical sensing system **100**.

(16) In an embodiment, the reflector **120** is a retroreflector, which reflects collimated electromagnetic energy **116** back towards the first side **106** of the combustion zone **104** and back to the optical head **102**. Using a retroreflector reduces the alignment requirements necessary for the combustion-zone chemical sensing system **100**, which beneficially decreases installation complexity as well as potential maintenance/reinstallation costs and potential sources of failure during operation.

(17) In an embodiment, the pitch reflective optics **110** has only a single reflective mirror that collimates a broadband range of electromagnetic energy including MIR, NIR, and visible. In an embodiment, the pitch reflective optics **110** is an off-axis parabolic mirror with a focus aligned with the exit of the input fiber **150**. The combustion-zone chemical sensing system **100** may include an input fiber mount **170** to position the exit of the input fiber **150** with respect to the pitch reflective optics **110**.

(18) In an embodiment, the catch reflective optics **112** has only a single reflective mirror that collects and focuses a broadband range of electromagnetic energy including MIR, NIR, and visible. In an embodiment, the catch reflective optics **112** is an off-axis parabolic mirror with a focus that is aligned with the entrance of the output fiber **152**. The combustion-zone chemical sensing system **100** may include an output fiber mount **172** to position the entrance of the output fiber **152** with respect to the catch reflective optics **112**. One or both of the pitch reflective optics **110** and catch reflective optics **112** may each have more than one optical element without departing from the scope hereof.

(19) In an embodiment, the input fiber **150** is a single-mode optical fiber and the output fiber **152** is a multi-mode optical fiber, though input fiber **150** may be a multi-mode fiber and output fiber **152** may be a single-mode fiber without departing from the scope hereof.

(20) In an embodiment, the combustion-zone chemical sensing system **100** includes a laser **154** that generates MIR electromagnetic energy directed into the input fiber **150** and which propagates through the combustion zone **104** as collimated electromagnetic energy **116**. The system may further include a processor **160** that communicatively couples to the detector **140** and the laser **154**. The processor **160** is communicatively coupled to a memory **162** that stores machine readable instructions which, when executed by the processor **160**, determine a concentration of a gas species **118** within the combustion zone **104** based at least on a power measured by the detector **140**.

(21) The laser **154**, or multiple lasers **154**, may generate electromagnetic energy at more than one wavelength, each wavelength associated with a known absorption features of a target gas species, making the combustion-zone chemical sensing system **100** capable of calculating a concentration of more than one gas species **118** present in the combustion zone **104**. For example, the laser **154** may generate electromagnetic energy with $\lambda=2302$ nm, which is strongly absorbed by CO, and generate electromagnetic energy with $\lambda=760$ nm, which is strongly absorbed by O₂. The processor **160** may thereby calculate a concentration of both CO and O₂ based upon the power measured by the detector **140** for electromagnetic energy generated at each wavelength. The combustion-zone chemical sensing system **100** may operate using electromagnetic energy with other wavelengths and may calculate a concentration of other chemical species in addition to or in place of CO and O₂ without departing from the scope herein.

(22) The combustion-zone chemical sensing system **100** may include a window **174** that separates the combustion zone **104** from the optical head **102**. The window **174** may be formed of a material that is transmissive to a range of electromagnetic energy including one or more of MIR, NIR, and visible.

(23) FIG. 2 illustrates the optical head **102** of FIG. 1 shown sensing a combustion zone **204**. Optical head **102** includes pitch reflective optics **110**, catch reflective optics **112**, and an alignment housing **230**. The pitch reflective optics **110** collimates MIR electromagnetic energy from input

fiber **150** toward a reflector **220**. The catch reflective optics **112** focus MIR electromagnetic energy reflected from the reflector **220** into the output fiber **152**. The alignment housing **230** interfaces with a structure **234** adjacent the combustion zone **204**. The structure **234** may be a combustion process chamber, furnace, or other structure associated with a combustion process and may not surround the combustion zone **204** as is shown in FIG. 2. The alignment housing **230** holds and positions the pitch reflective optics **110** and catch reflective optics **112** with respect to the combustion zone **204**. FIG. 2 illustrates a sideview of optical head **102** along with axis indicators **198X**, **198Y**, and **198Z**, which indicate the cartesian-coordinate system with X-axis, Y-axis and Z-axis. The electromagnetic energy collimated by pitch reflective optics **110** propagates parallel to the Z-axis.

(24) In an embodiment, the alignment housing **230** forms a mechanical aperture **236** through which (a) the pitch reflective optics **110** collimate MIR electromagnetic energy into the combustion zone **204** and (b) the catch reflective optics **112** captures MIR electromagnetic energy from the combustion zone **204**.

(25) In an embodiment, the optical head **102** includes the input fiber mount **170** that positions the input fiber **150** with respect to pitch reflective optics **110** and the output fiber mount **172** that positions the output fiber **152** with respect to the catch reflective optics **112**. Both the input fiber mount **170** and output fiber mount **172** are affixed to the alignment housing **230**. In an embodiment, the output fiber **152** is connected to the detector **140** that detects MIR electromagnetic energy from the output fiber **152**.

(26) In an embodiment, the pitch reflective optics **110** collimate NIR and visible electromagnetic energy in addition to MIR electromagnetic energy. Use of MIR, NIR, and visible electromagnetic energy with optical head **102** allows for detection of gas species present in a combustion zone **204** that absorb electromagnetic energy at a wide range of wavelengths, e.g., gas species **118** in combustion zone **104**. In an embodiment, the MIR electromagnetic energy used by optical head **102** has a wavelength between 2250 and 2350 nm, which is useful in monitoring CO gas that absorbs electromagnetic energy strongly at 2302 nm.

(27) In an embodiment, the alignment housing positions the pitch reflective optics **110** and the catch reflective optics **112** such that the MIR electromagnetic energy reflected by the pitch reflective optics **110** is antiparallel to MIR electromagnetic energy immediately before being focused by the catch reflective optics **112**. This is beneficial since it decreases the installation complexity of the optical head **102** and reduces potential maintenance/reinstallation costs and reduces potential sources of failure during operation.

(28) The combustion zone **204** and reflector **220**, are examples of combustion zone **104** and reflector **120** of FIG. 1, respectively, and the descriptions of each respective element apply between the two figures.

(29) FIG. 3 illustrates the optical head **102** viewed along Z-axis, shown as **198Z**, which in an embodiment is parallel to electromagnetic energy collimated by pitch reflective optics **110**. Optical head **102** is compatible with use in combustion-zone chemical sensing system **100**. Optical head **102** includes catch reflective optics **112** as well as input fiber **150**, input fiber mount **170**, output fiber **152** and output fiber mount **172**. Pitch reflective optics **110**, input fiber mount **170**, catch reflective optics **112**, and output fiber mount **172** are attached to the alignment housing **230**.

(30) As shown in FIG. 3, the pitch reflective optics **110** and catch reflective optics **112** may be overlapped when viewed from along the Z-axis and the catch reflective optics **112** are larger than the pitch reflective optics **110**. In practice, the electromagnetic energy collimated by the pitch reflective optics **110** may be slightly divergent (not fully collimated) and once electromagnetic energy is reflected to the catch reflective optics **112** it has expanded. As a result, larger optics are appropriate in order to collect more light. The relative size and position of the pitch reflective optics **110** and catch reflective optics **112** may be varied without departing from the scope herein.

(31) FIGS. 4A and 4B shows a mechanical implementation of the optical head **102**, in an

embodiment, and are best viewed together. FIG. 4A illustrates the optical head **102** viewed along the Y-axis and shows pitch reflective optics **110**, catch reflective optics **112**, output fiber mount **172**, and mechanical aperture **236** all mounted to alignment housing **230**. Output fiber mount **172** positions the output fiber **152** with respect to catch reflective optics **112**. Electromagnetic energy collimated by pitch reflective optics **110** and electromagnetic energy reflected toward catch reflective optics **112** travel through the mechanical aperture **236**, shown edge-on in FIG. 4A. For clarity of illustration, input fiber **150** is not shown and input fiber mount **170** is not indicated in FIG. 4A.

(32) FIG. 4B illustrates the optical head **102** viewed along the Z-axis and shows pitch reflective optics **110**, catch reflective optics **112**, input fiber mount **170**, and mechanical aperture **236** all mounted to alignment housing **230**. Input fiber mount **170** positions the input fiber **150** with respect to pitch reflective optics **110**. Electromagnetic energy collimated by pitch reflective optics **110** and electromagnetic energy reflected toward catch reflective optics **112** travel through the mechanical aperture **236**, shown face-on in FIG. 4B. For clarity of illustration, output fiber **152** is not shown in FIG. 4B.

(33) FIG. 5 is a flowchart illustrating a method **500** for determining gas concentration within a combustion zone. Method **500** may be used with combustion-zone chemical sensing system **100** and alternatively may employ optical head **102**. Method **500** includes blocks **510** and **520**. In embodiments, the method **500** also includes one or more of **512**, **530**, **540**, and **550**.

(34) In block **510** of method **500**, MIR electromagnetic energy exiting an input fiber is collimated and directed to traverse a combustion zone. In one example of block **510**, MIR electromagnetic energy is collimated by the pitch reflective optics **110** after exiting the input fiber **150** and then traverses the combustion zone **104**.

(35) In block **520** of the method **500**, reflected MIR electromagnetic energy from the combustion zone is focused into an output fiber. In one example of block **520**, MIR electromagnetic energy from the combustion zone **104** is focused by the catch reflective optics **112** into the output fiber **152**.

(36) In certain embodiments, the method **500** includes one or more additional blocks of the flowchart in FIG. 5. In block **512**, electromagnetic energy is reflected with one of a reflector and a retroreflector. In one example of block **512**, electromagnetic energy is reflected by the reflector **120** in the form of a retroreflector.

(37) In block **530** of the method **500**, MIR electromagnetic energy from the output fiber is detected with a detector. In one example of block **530**, MIR electromagnetic energy exiting the output fiber **152** is detected by the detector **140**.

(38) In block **540** of the method **500**, NIR and visible electromagnetic energy exiting an input fiber are collimated and directed to traverse a combustion zone. In one example of block **540**, NIR and visible electromagnetic energy are collimated by the pitch reflective optics **110** after exiting the input fiber **150** and then traverses the combustion zone **104**.

(39) In block **550** of the method **500**, reflected NIR and visible electromagnetic energy from the combustion zone are focused into an output fiber. In one example of block **550**, NIR and visible electromagnetic energy from the combustion zone **104** is focused by the catch reflective optics **112** into the output fiber **152**.

(40) Changes may be made in the above methods and systems without departing from the scope hereof. It should thus be noted that the matter contained in the above description or shown in the accompanying drawings should be interpreted as illustrative and not in a limiting sense. The following claims are intended to cover all generic and specific features described herein, as well as all statements of the scope of the present method and system, which, as a matter of language, might be said to fall therebetween.

Combination of Features

(41) (A1) in a first aspect, a combustion-zone chemical sensing system includes pitch reflective

optics on a first side of the combustion zone that collimate MIR electromagnetic energy from an input fiber; a reflector on a second side of the combustion zone that reflects collimated MIR electromagnetic energy; catch reflective optics on the first side of the combustion zone that focus reflected MIR electromagnetic energy into an output fiber; and a detector to detect MIR electromagnetic energy from the output fiber.

(42) (A2) In an embodiment of A1, the pitch reflective optics further collimating NIR and visible electromagnetic energy.

(43) (A3) In an embodiment of either A1 or A2, further including an input fiber and an output fiber, a combined length of the input fiber and the output fiber being less than 28 meters.

(44) (A4) In an embodiment of A3, the output fiber being a multi-mode optical fiber.

(45) (A5) In an embodiment of any of A1 through A4, the reflector being a retroreflector.

(46) (A6) In an embodiment of any of A1 through A5, the pitch reflective optics include an off-axis parabolic mirror and the catch reflective optics include an off-axis parabolic mirror.

(47) (A7) In an embodiment of any of A1 through A6, further including a laser that generates MIR electromagnetic energy conveyed into an input fiber, a processor communicatively coupled to the detector; and memory communicatively coupled to the processor and storing machine readable instructions that, when executed by the processor, calculate a concentration of a gas species within the combustion zone based at least on a power measured by the detector.

(48) (B1) In a second aspect, an optical head for sensing a combustion zone includes pitch reflective optics that collimate MIR electromagnetic energy from an input fiber towards a reflector; catch reflective optics that focus MIR electromagnetic energy into an output fiber, reflected from the reflector; and an alignment housing that interfaces with structure adjacent the combustion zone and that holds and positions the pitch reflective optics and catch reflective optics with respect to the combustion zone.

(49) (B2) In an embodiment of B1, the alignment housing forming a mechanical aperture through which a) the pitch reflective optics collimate MIR electromagnetic energy into the combustion zone and (b) the catch reflective optics captures MIR electromagnetic energy from the combustion zone.

(50) (B3) In an embodiment of either B1 or B2, further including an input fiber mount that positions the input fiber with respect to the pitch reflective optics; and an output fiber mount that positions the output fiber with respect the catch reflective optics

(51) (B4) In an embodiment of any of B1 through B3, the alignment housing positioning the pitch reflective optics and catch reflective optics such that MIR electromagnetic energy reflected by the pitch reflective optics is antiparallel to MIR electromagnetic energy before it is focused by the catch reflective optics.

(52) (B5) In an embodiment of any of B1 through B4, the MIR electromagnetic energy having a wavelength between 2250 and 2350 nanometers.

(53) (B6) In an embodiment of any of B1 through B5, the output fiber being connected to a detector that detects MIR electromagnetic energy from the output fiber.

(54) (B7) In an embodiment of any of B1 through B6, the pitch reflective optics further collimating NIR and visible electromagnetic energy.

(55) (B8) In an embodiment of any of B1 through B7, wherein the pitch reflective optics include an off-axis parabolic mirror and wherein the catch reflective optics include an off-axis parabolic mirror.

(56) (C1) In a third aspect, a method for determining gas concentration within a combustion zone includes collimating MIR electromagnetic energy exiting from an input fiber to traverse a combustion zone; and focusing reflected MIR electromagnetic energy from the combustion zone to an output fiber.

(57) (C2) In an embodiment of C1, further including detecting MIR electromagnetic energy from the output fiber.

(58) (C3) In an embodiment of either C1 or C2, further including collimating NIR and visible

electromagnetic energy exiting from the input fiber to traverse the combustion zone; and focusing NIR and visible reflected electromagnetic energy from the combustion zone into the output fiber.

(59) (C4) In an embodiment of any of C1 through C3, further including reflecting electromagnetic energy with one of a reflector and a retroreflector.

(60) (C5) In an embodiment of any C1 through C4, the step of collimating includes reflecting electromagnetic energy with an off-axis parabolic reflector; and the step of focusing includes focusing electromagnetic energy with an off-axis parabolic reflector.

Claims

1. A combustion-zone chemical sensing system, comprising: pitch reflective optics positioned in a pitch head on a first side of the combustion zone that collimate mid-infrared (MIR) electromagnetic energy from an input fiber; a reflector on a second side of the combustion zone that reflects collimated MIR electromagnetic energy; catch reflective optics in the pitch head on the first side of the combustion zone that focus reflected MIR electromagnetic energy into an output fiber; and a detector to detect MIR electromagnetic energy from the output fiber.
2. The combustion-zone chemical sensing system of claim 1, the pitch reflective optics further collimating NIR and visible electromagnetic energy.
3. The combustion-zone chemical sensing system of claim 1, wherein the pitch head is a single pitch head, and the system further comprises an input fiber and an output fiber coupled to the single pitch head, a combined length of the input fiber and the output fiber being less than 28 meters.
4. The combustion-zone chemical sensing system of claim 3, the input fiber being a single-mode optical fiber and the output fiber being a multimode optical fiber.
5. The combustion-zone chemical sensing system of claim 1, the reflector being a retroreflector.
6. The combustion-zone chemical sensing system of claim 1, wherein the pitch reflective optics comprise an off-axis parabolic mirror and the catch reflective optics comprise an off-axis parabolic mirror.
7. The combustion-zone chemical sensing system of claim 1, further comprising: a laser that generates MIR electromagnetic energy conveyed into an input fiber, a processor communicatively coupled to the detector; and memory communicatively coupled to the processor and storing machine readable instructions that, when executed by the processor, calculate a concentration of a gas species within the combustion zone based at least on a power measured by the detector.
8. An optical head for sensing a combustion zone, comprising: pitch reflective optics that collimate MIR electromagnetic energy from an input fiber towards a reflector, the pitch reflective optics positioned in the optical head on a first side of the combustion zone; catch reflective optics that focus MIR electromagnetic energy into an output fiber, reflected from the reflector, the catch reflective optics positioned in the optical head on the first side of the combustion zone; and an alignment housing that interfaces with structure adjacent the combustion zone and that is configured to hold and position the pitch reflective optics and catch reflective optics with respect to the combustion zone.
9. The optical head of claim 8, the alignment housing forming a mechanical aperture through which a) the pitch reflective optics collimate MIR electromagnetic energy into the combustion zone and (b) the catch reflective optics captures MIR electromagnetic energy from the combustion zone.
10. The optical head of claim 8, the alignment housing further comprising: an input fiber mount that positions the input fiber with respect to the pitch reflective optics; and an output fiber mount that positions the output fiber with respect the catch reflective optics.
11. The optical head of claim 8, the alignment housing positioning the pitch reflective optics and catch reflective optics such that MIR electromagnetic energy reflected by the pitch reflective optics is antiparallel to MIR electromagnetic energy before it is focused by the catch reflective optics.
12. The optical head of claim 8, the MIR electromagnetic energy having a wavelength between

2250 and 2350 nanometers.

13. The optical head of claim 8, the output fiber being connected to a detector that detects MIR electromagnetic energy from the output fiber.

14. The optical head of claim 8, the pitch reflective optics further collimating NIR and visible electromagnetic energy.

15. The optical head of claim 8, wherein the pitch reflective optics comprise an off-axis parabolic mirror and wherein the catch reflective optics comprise an off-axis parabolic mirror.

16. A method for determining gas concentration within a combustion zone, comprising: providing an alignment housing comprising pitch reflective optics and catch reflective optics; interfacing the alignment housing with structure adjacent the combustion zone; collimating mid-infrared (MIR) electromagnetic energy exiting from an input fiber to traverse the combustion zone via the pitch reflective optics; focusing MIR electromagnetic energy reflected from the combustion zone to an output fiber via the catch reflective optics; and holding and positioning the pitch reflective optics and catch reflective optics at a first side of the combustion zone.

17. The method of claim 16, further comprising detecting MIR electromagnetic energy from the output fiber.

18. The method of claim 16, further comprising: collimating NIR and visible electromagnetic energy exiting from the input fiber to traverse the combustion zone; and focusing NIR and visible reflected electromagnetic energy from the combustion zone into the output fiber.

19. The method of claim 16, further comprising reflecting electromagnetic energy with one of a reflector and a retroreflector.

20. The method of claim 16, further wherein: the step of collimating comprises reflecting electromagnetic energy with an off-axis parabolic reflector; and the step of focusing comprising focusing electromagnetic energy with an off-axis parabolic reflector.
