

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411472
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Murakami; Hiroki

Numerical control device

Abstract

Provided is a numerical control device for improving cycle time and machined surface quality. The numerical control device (1) comprises: a machining program reading unit (10) that generates, on the basis of a read machining program, a tool center point sequence indicating a path of a center point of a tool of a machining tool; an interpolation control unit (11) that interpolates the tool center point sequence generated by the machining program reading unit (10); a kinematic conversion unit (12) that performs coordinate-conversion on the tool center point sequence interpolated by the interpolation control unit (11) to obtain a control point sequence indicating a path of a control point by which the position of the tool is determined; a smoothing application unit (13) that performs smoothing by performing smoothing processing on the control point sequence, obtained by the kinematic conversion unit (12), with predetermined parameters; and a drive control unit (14) that controls driving of a machining tool A on the basis of the control point sequence smoothed by the smoothing application unit (13).

Inventors:	Murakami; Hiroki (Yamanashi, JP)
Applicant:	FANUC CORPORATION (Yamanashi, JP)
Family ID:	77614058
Assignee:	FANUC CORPORATION (Yamanashi, JP)
Appl. No.:	17/905399
Filed (or PCT Filed):	February 26, 2021
PCT No.:	PCT/JP2021/007452
PCT Pub. No.:	WO2021/177180
PCT Pub. Date:	September 10, 2021

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Foreign Application Priority Data

JP 2020-037012 Mar. 04, 2020

Publication Classification

Int. Cl.: G05B19/41 (20060101)

U.S. Cl.:

CPC G05B19/41 (20130101); G05B2219/34153 (20130101)

Field of Classification Search

CPC: G05B (19/41); G05B (2219/34153); G05B (2219/34083); G05B (2219/34085)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9377776	12/2015	Nakamura	N/A	G05B 19/4103
2018/0120808	12/2017	Murakami	N/A	G05B 19/4103
2021/0001483	12/2020	Milenkovic	N/A	B25J 9/1666
2021/0001484	12/2020	Bogart	N/A	B25J 13/088

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H01-316185	12/1988	JP	N/A
H09-265310	12/1996	JP	N/A
2008-225825	12/2007	JP	N/A
2009-301232	12/2008	JP	N/A
2009-545826	12/2008	JP	N/A
2018-073097	12/2017	JP	N/A
2018-120543	12/2017	JP	N/A
2019-082851	12/2018	JP	N/A
2020-027410	12/2019	JP	N/A
2020-077311	12/2019	JP	N/A
2012/056554	12/2011	WO	N/A

OTHER PUBLICATIONS

International Search Report issued in PCT/JP2021/007452; mailed Apr. 27, 2021. cited by applicant

Primary Examiner: Cai; Charles

Attorney, Agent or Firm: Studebaker Brackett PLLC

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a numerical control device.

BACKGROUND ART

(2) In the related art, techniques have been adopted for smoothing a path specified by a tool center point to be brought into contact with a workpiece, in a numerical control device of a machining tool (for example, see Japanese Unexamined Patent Application, Publication No. 2018-073097). In Japanese Unexamined Patent Application, Publication No. 2018-073097, as the smoothing techniques, there are disclosed well-known techniques based on Bezier curves, B-spline curves, NURBS curves, simple averages, weighted averages, and the like. In these well-known techniques, the tolerance (allowance) checking is performed after the smoothing, and if the tolerance is exceeded (if the tolerance is not satisfied), the parameter is adjusted by changing the parameter to fall within the tolerance. Patent Document 1: Japanese Unexamined Patent Application, Publication No. 2018-073097

DISCLOSURE OF THE INVENTION

Problems to be Solved by the Invention

(3) However, in the above-described well-known techniques, a path specified by a tool center point different from a control point defining a position of the tool is smoothed, and therefore it is necessary to perform coordinate-conversion (from a coordinate system of the tool center point to a coordinate system of the control point) of the smoothed path. As a result, a path specified by the control point is not smooth in some cases. In this case, deceleration occurs during the operation of the machining tool, which causes lowering of the cycle time and deterioration of the machined surface quality.

(4) Accordingly, it is desired to provide a numerical control device that makes it possible to improve a cycle time and machined surface quality.

Means for Solving the Problems

(5) An aspect of the present disclosure provides a numerical control device comprising a machining program reading unit that generates, on a basis of a read machining program, a tool center point sequence indicating a path of a tool center point of a machining tool, an interpolation control unit that interpolates the tool center point sequence generated by the machining program reading unit, a kinematic conversion unit that performs coordinate-conversion on the tool center point sequence interpolated by the interpolation control unit to obtain a control point sequence indicating a path of a control point defining a position of the tool, a smoothing application unit that performs smoothing by performing smoothing processing on the control point sequence, obtained by the kinematic conversion unit, with a predetermined parameter, and a drive control unit that controls driving of the machining tool on the basis of the control point sequence smoothed by the smoothing application unit.

Effects of the Invention

(6) According to an aspect of the present disclosure, there can be provided a numerical control device that makes it possible to improve a cycle time and machined surface quality.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a block diagram illustrating a functional configuration of a numerical control device according to a first embodiment;

(2) FIG. 2 is a schematic diagram illustrating a path of a tool of a machining tool to be controlled

by the numerical control device according to the first embodiment;

(3) FIG. 3 is a flowchart illustrating a process executed by the numerical control device according to the first embodiment;

(4) FIG. 4 is a block diagram illustrating a functional configuration of a numerical control device according to a second embodiment;

(5) FIG. 5 is a flowchart illustrating a process executed by the numerical control device according to the second embodiment;

(6) FIG. 6 is a block diagram illustrating a functional configuration of a numerical control device according to a third embodiment;

(7) FIG. 7 is a flowchart illustrating a process executed by the numerical control device according to the third embodiment;

(8) FIG. 8 is a block diagram illustrating a functional configuration of a numerical control device according to a fourth embodiment; and

(9) FIG. 9 is a flowchart illustrating a process executed by the numerical control device according to the fourth embodiment.

PREFERRED MODE FOR CARRYING OUT THE INVENTION

(10) Hereinafter, numerical control devices **1**, **2**, **3**, and **4** according to embodiments will be described with reference to the drawings. In the description of a second embodiment and subsequent embodiments, the same reference symbols will be assigned to configurations shared with the other embodiments, and the description thereof will be omitted.

First Embodiment

(11) First, a configuration of the numerical control device **1** will be described with reference to FIGS. **1** and **2**. FIG. **1** is a block diagram illustrating a functional configuration of the numerical control device **1**. FIG. **2** is a schematic diagram illustrating a path of a tool **T** of a machining tool **A** to be controlled by the numerical control device **1**.

(12) The numerical control device **1** illustrated in FIG. **1** includes an arithmetic processing unit (not shown) such as a central processing unit (CPU), a main storage unit (not shown) such as a random access memory (RAM) for storing data that the arithmetic processing unit temporarily requires to execute programs, an auxiliary storage unit (not shown) such as a hard disk drive (HDD) and a solid state drive (SSD) that stores various programs such as a machining program **P**, an input unit (not shown) such as a keyboard, an output unit (not shown) such as a monitor, and a communication unit (not shown) that communicates with the machining tool **A**.

(13) The CPU (not shown) included in the numerical control device **1** executes various programs to thereby implement various functions of a machining program reading unit **10**, an interpolation control unit **11**, a kinematic conversion unit **12**, a smoothing application unit **13**, a drive control unit **14**, and the like.

(14) The machining program reading unit **10** generates, on the basis of a read machining program **P**, a tool center point sequence $P_{\text{sub.tcp}}(t)$ indicating a path of a center point of a tool **T** (see FIG. **2**) of the machining tool **A**. The tool center point sequence $P_{\text{sub.tcp}}(t)$ is formed by expressing a path by means of parametric curves, the path being represented by straight lines, arcs, parametric curves, and the like. The tool center point sequence $P_{\text{sub.tcp}}(t)$ is represented by a five-dimensional vector containing X, Y, and Z axes coordinate values and coordinate values of rotary axes **B** and **C** when the machining tool **A** is a 5-axis machining tool, for example. Note that t is a parameter of the parametric curve.

(15) The interpolation control unit **11** interpolates the tool center point sequence $P_{\text{sub.tcp}}(t)$ generated by the machining program reading unit **10**.

(16) The kinematic conversion unit **12** performs coordinate-conversion (kinematic conversion) on the tool center point sequence $P_{\text{sub.tcp}}(t)$ interpolated by the interpolation control unit **11** to obtain a control point sequence $P_{\text{sub.mcn}}(t)$ indicating a path of a control point defining a position of the tool **T** (see FIG. **2**). $P_{\text{sub.mcn}}(t)$ can be represented as $P_{\text{sub.mcn}}(t) = M_{\text{Math}} \cdot P_{\text{sub.tcp}}(t)$. This

P.sub.mcn(t) is represented by a five-dimensional vector containing X, Y, and Z axes coordinate values and coordinate values of rotary axes B and C when the machining tool A is a 5-axis machining tool, for example. M is a conversion matrix that performs kinematic conversion.

(17) The smoothing application unit **13** performs smoothing by performing smoothing processing on the control point sequence P.sub.mcn(t), obtained by the kinematic conversion unit **12**, with a predetermined parameter u. Thus, the smoothed control point sequence Q.sub.mcn(t) is obtained. Q.sub.mcn(t) can be represented as Q.sub.mcn

(t)=S(u).Math.P.sub.mcn(t)=S(u).Math.M.Math.P.sub.tcp(t). A predetermined parameter u is a variable representing the strength of smoothing. S is an operation for performing the smoothing processing. In S(u), the smoothing processing is not performed at the time of u=0, and the effect of the smoothing processing increases with an increase in u, resulting in the smoothed path, whereas a deviation from an original path increases. For example, when S is a linear filter, its time constant corresponds to u. Note that u may be a fixed value or may be dependent on a parameter t. Making u dependent on the parameter t makes it possible to suppress the effect of the smoothing processing at the corner portion and increase the effect of the smoothing processing at a free-form curve portion.

(18) Specifically, the smoothing application unit **13** includes an inverse kinematic conversion unit **130**, and a tolerance checking unit **131**, and determines a predetermined parameter u by means of numerical calculation.

(19) The inverse kinematic conversion unit **130** performs coordinate-conversion (inverse kinematic conversion) on the control point sequence Q.sub.mcn(t) smoothed by the smoothing application unit **13** to obtain the smoothed tool center point sequence Q.sub.tcp(t). Q.sub.tcp(t) can be represented as Q.sub.tcp(t)=M.sup.-1.Math.Q.sub.mcn(t)=M.sup.-1.Math.S(u).Math.P.sub.mcn(t)=M.sup.-1.Math.S(u).Math.M.Math.P.sub.tcp(t). M.sup.-1 is a conversion matrix that performs inverse kinematic conversion, and is a conversion matrix that performs inverse conversion of M.

(20) The tolerance checking unit **131** performs tolerance checking on the basis of a difference between the tool center point sequence P.sub.tcp(t) before the coordinate-conversion is performed by the kinematic conversion unit **12** and the smoothed tool center point sequence Q.sub.tcp(t) obtained by the inverse kinematic conversion unit **130**. The difference between P.sub.tcp(t) and Q.sub.tcp(t) can be represented as d(t)=|Q.sub.tcp(t)-P.sub.tcp(t)|. A maximum value of u (maximum value of the smoothing strength) satisfying d.sub.Max≤T.sub.tcp is calculated, where d.sub.Max is a maximum value of d(t) and T.sub.tcp is a preset tolerance. This can obtain a smooth path in which the deviation is within T.sub.tcp and the smoothing processing is performed.

(21) The drive control unit **14** controls driving of the machining tool A on the basis of the smoothed control point sequence Q.sub.mcn(t). Specifically, the drive control unit **14** controls, on the basis of the smoothed control point sequence Q.sub.mcn(t), a servo driving unit (not shown) that drives a servo A1 and a spindle driving unit (not shown) that drives a spindle A2, the servo A1 and the spindle A2 being included in the machining tool A.

(22) Next, a process executed by the numerical control device **1** will be described with reference to FIG. 3. FIG. 3 is a flowchart illustrating the process executed by the numerical control device **1**.

(23) As illustrated in FIG. 3, the process executed by the numerical control device **1** includes a machining program reading step S10, an interpolation control step S11, a kinematic conversion step S12, a smoothing strength setting step S13, a smoothing application step S14, an inverse kinematic conversion step S15, a tolerance checking step S16, and a drive control step S18.

(24) In the machining program reading step S10, a tool center point sequence P.sub.tcp(t) indicating a path of a tool center point of a tool T of a machining tool A is generated on the basis of a read machining program P.

(25) In the interpolation control step S11, the tool center point sequence P.sub.tcp(t) generated in the machining program reading step S10 is interpolated.

(26) In the kinematic conversion step S12, coordinate-conversion is performed on the tool center

point sequence $P_{sub}.tcp(t)$ interpolated in the interpolation control step **S11** to obtain a control point sequence $P_{sub}.mcn(t)$ indicating a path of a control point defining a position of the tool T.

(27) In the smoothing strength setting step **S13**, a parameter u is set which is a value of the smoothing strength. A small value is set for the parameter u at first, and the value to be set is gradually increased.

(28) In the smoothing application step **S14**, smoothing is performed by performing smoothing processing on the control point sequence $P_{sub}.mcn(t)$, obtained by the kinematic conversion unit **12**, with the predetermined parameter u obtained in the previous step.

(29) In the inverse kinematic conversion step **S15**, coordinate-conversion is performed on the control point sequence $Q_{sub}.mcn(t)$ smoothed in the smoothing application step **S14** to obtain the smoothed tool center point sequence $Q_{sub}.tcp(t)$.

(30) In the tolerance checking step **316**, tolerance checking is performed on the basis of a difference between the tool center point sequence $P_{sub}.tcp(t)$ before the coordinate-conversion is performed in the kinematic conversion step **S12** and the smoothed tool center point sequence $Q_{sub}.tcp(t)$ obtained in the inverse kinematic conversion step **S15**.

(31) By repeatedly executing Steps **S13** to **S16** according to a result of the determination in **S17**, a maximum value of u satisfying $d_{sub}.Max \leq T_{sub}.tcp$ is calculated by means of numerical calculation, and the control point sequence $Q_{sub}.mcn(t)$ that is subjected to the smoothing processing with the maximum value of u is obtained.

(32) In the drive control step **S18**, driving of the machining tool A is controlled on the basis of the finally obtained control point sequence $Q_{sub}.mcn(t)$.

(33) In this way, a numerical control device **1** includes a machining program reading unit **10** that generates, on a basis of a read machining program P, a tool center point sequence $P_{sub}.tcp(t)$ indicating a path of a center point of a tool T of a machining tool A, an interpolation control unit **11** that interpolates the tool center point sequence $P_{sub}.tcp(t)$ generated by the machining program reading unit **10**, a kinematic conversion unit **12** that performs coordinate-conversion on the tool center point sequence $P_{sub}.tcp(t)$ interpolated by the interpolation control unit **11** to obtain a control point sequence $P_{sub}.mcn(t)$ indicating a path of a control point defining a position of the tool T, a smoothing application unit **13** that performs smoothing by performing smoothing processing on the control point sequence $P_{sub}.mcn(t)$, obtained by the kinematic conversion unit **12**, with a predetermined parameter u , and a drive control unit **14** that controls driving of the machining tool A on the basis of the control point sequence $Q_{sub}.mcn(t)$ smoothed by the smoothing application unit **13**.

(34) In addition, in the numerical control device **1**, the smoothing application unit **13** includes an inverse kinematic conversion unit **130** that performs coordinate-conversion on the control point sequence $Q_{sub}.mcn(t)$ smoothed by the smoothing application unit **13** to obtain the smoothed tool center point sequence $Q_{sub}.tcp(t)$, and a tolerance checking unit **131** that performs tolerance checking on the basis of a difference between the tool center point sequence $P_{sub}.tcp(t)$ before the coordinate-conversion is performed by the kinematic conversion unit **12** and the smoothed tool center point sequence $Q_{sub}.tcp(t)$ obtained by the inverse kinematic conversion unit **130**, and preferably determines the predetermined parameter u by means of numerical calculation.

(35) According to the numerical control device **1** according to the present embodiment, applying smoothing to the control point enables smooth motion of the spindle. This makes it possible to prevent the control point from rapidly operating, whereby the cycle time and the machining surface quality can be improved.

Second Embodiment

(36) Next, a configuration of the numerical control device **2** will be described with reference to FIG. 4. FIG. 4 is a block diagram illustrating a functional configuration of the numerical control device **2**. The present embodiment is different from the first embodiment in that a smoothing application unit **23** that analytically determines a predetermined parameter u is provided instead of

the smoothing application unit **13** that determines a predetermined parameter u by means of numerical calculation.

(37) As illustrated in FIG. 4, a CPU (not shown) included in the numerical control device **2** executes various programs to thereby implement various functions of the smoothing application unit **23**, and the like.

(38) The smoothing application unit **23** performs smoothing by performing smoothing processing on a control point sequence $P.sub.mcn(t)$, obtained by a kinematic conversion unit **12**, with a predetermined parameter u . Note that the smoothing application unit **23** analytically determines the predetermined parameter u . That is, the smoothing application unit **23** calculates u satisfying $d.sub.Max = T.sub.tcp$.

(39) Next, a process executed by the numerical control device **2** will be described with reference to FIG. 5. FIG. 5 is a flowchart illustrating the process executed by the numerical control device **2**.

(40) As illustrated in FIG. 5, the process executed by the numerical control device **2** includes a machining program reading step **S10**, an interpolation control step **S11**, a kinematic conversion step **S12**, a smoothing strength calculation step **S23**, a smoothing application step **S14**, and a drive control step **S18**.

(41) In the smoothing strength calculation step **S23**, a parameter u (u satisfying $d.sub.Max = T.sub.tcp$) is calculated which is a value of the smoothing strength. Note that the other steps are the same as those in the first embodiment.

(42) In this way, a numerical control device **2** includes a machining program reading unit **10** that generates, on a basis of a read machining program P , a tool center point sequence $P.sub.tcp(t)$ indicating a path of a center point of a tool T of a machining tool A , an interpolation control unit **11** that interpolates the tool center point sequence $P.sub.tcp(t)$ generated by the machining program reading unit **10**, a kinematic conversion unit **12** that performs coordinate-conversion on the tool center point sequence $P.sub.tcp(t)$ interpolated by the interpolation control unit **11** to obtain a control point sequence $P.sub.mcn(t)$ indicating a path of a control point defining a position of the tool T , a smoothing application unit **23** that performs smoothing by performing smoothing processing on the control point sequence $P.sub.mcn(t)$, obtained by the kinematic conversion unit **12**, with a predetermined parameter u , and a drive control unit **14** that controls driving of the machining tool A on the basis of the control point sequence $Q.sub.mcn(t)$ smoothed by the smoothing application unit **23**.

(43) In the numerical control device **2**, the smoothing application unit **23** preferably analytically determines the predetermined parameter u .

(44) According to the numerical control device **2** according to the present embodiment, applying smoothing to the control point enables smooth motion of the spindle. This makes it possible to prevent the control point from rapidly operating, whereby the cycle time and the machining surface quality can be improved.

Third Embodiment

(45) Next, a configuration of the numerical control device **3** will be described with reference to FIG. 6. FIG. 6 is a block diagram illustrating a functional configuration of the numerical control device **3**. The present embodiment is different from the first embodiment in that a control point sequence $Q.sub.mcn(t)$ on which the smoothing processing is performed is interpolated instead of interpolating the tool center point sequence $P.sub.tcp(t)$ before the kinematic conversion is performed.

(46) As illustrated in FIG. 6, the CPU (not shown) included in the numerical control device **3** executes various programs to thereby implement various functions of a machining program reading unit **10**, a kinematic conversion unit **12**, a smoothing application unit **13**, an interpolation control unit **11**, a drive control unit **14**, and the like.

(47) The kinematic conversion unit **12** performs coordinate-conversion on the tool center point sequence $P.sub.tcp(t)$ generated by the machining program reading unit **10** to obtain a control point

sequence $P.sub.mcn(t)$ indicating a path of a control point defining a position of the tool T (see FIG. 2).

(48) The interpolation control unit **11** interpolates the control point sequence $Q.sub.mcn(t)$ smoothed by the smoothing application unit **13**.

(49) The drive control unit **14** controls driving of the machining tool A on the basis of the interpolated control point sequence $Q.sub.mcn(t)$.

(50) Next, a process executed by the numerical control device **3** will be described with reference to FIG. 7. FIG. 7 is a flowchart illustrating the process executed by the numerical control device **3**.

(51) As illustrated in FIG. 7, the process executed by the numerical control device **3** includes a machining program reading step **S10**, a kinematic conversion step **S12**, a smoothing strength setting step **S13**, a smoothing application step **S14**, an inverse kinematic conversion step **S15**, a tolerance checking step **S16**, an interpolation control step **S11**, and a drive control step **S18**.

(52) In the kinematic conversion step **S12**, coordinate-conversion is performed on the tool center point sequence $P.sub.tcp(t)$ generated in the machining program reading step **S10** to obtain a control point sequence $P.sub.mcn(t)$ indicating a path of a control point defining a position of the tool T.

(53) In the interpolation control step **S11**, a finally obtained control point sequence $Q.sub.mcn(t)$ is interpolated.

(54) In the drive control step **S18**, driving of the machining tool A is controlled on the basis of the control point sequence $Q.sub.mcn(t)$ interpolated in the interpolation control step **S11**. Note that the other steps are the same as those in the first embodiment.

(55) In this way, a numerical control device **3** includes a machining program reading unit **10** that generates, on a basis of a read machining program P, a tool center point sequence $P.sub.tcp(t)$ indicating a path of a tool center point of a tool T of a machining tool A, a kinematic conversion unit **12** that performs coordinate-conversion on the tool center point sequence $P.sub.tcp(t)$ generated by the machining program reading unit **10** to obtain a control point sequence $P.sub.mcn(t)$ indicating a path of a control point defining a position of the tool T, a smoothing application unit **13** that performs smoothing by performing smoothing processing on the control point sequence $P.sub.mcn(t)$, obtained by the kinematic conversion unit **12**, with a predetermined parameter u, an interpolation control unit **11** that interpolates the control point sequence $Q.sub.mcn(t)$ smoothed by the smoothing application unit **13**, and a drive control unit **14** that controls driving of the machining tool A on the basis of the control point sequence $Q.sub.mcn(t)$ interpolated by the interpolation control unit **11**.

(56) In addition, in the numerical control device **3**, the smoothing application unit **13** includes an inverse kinematic conversion unit **130** that performs coordinate-conversion on the control point sequence $Q.sub.mcn(t)$ smoothed by the smoothing application unit **13** to obtain the smoothed tool center point sequence $Q.sub.tcp(t)$, and a tolerance checking unit **131** that performs tolerance checking on the basis of a difference between the tool center point sequence $P.sub.tcp(t)$ before the coordinate-conversion is performed by the kinematic conversion unit **12** and the smoothed tool center point sequence $Q.sub.tcp(t)$ obtained by the inverse kinematic conversion unit **130**, and preferably determines the predetermined parameter u by means of numerical calculation.

(57) According to the numerical control device **3** according to the present embodiment, applying smoothing to the control point enables smooth motion of the spindle. This makes it possible to prevent the control point from rapidly operating, whereby the cycle time and the machining surface quality can be improved.

Fourth Embodiment

(58) Next, a configuration of the numerical control device **4** will be described with reference to FIG. 8. FIG. 8 is a block diagram illustrating a functional configuration of the numerical control device **4**. The present embodiment is different from the third embodiment in that a smoothing application unit **23** that analytically determines a predetermined parameter u is provided instead of the smoothing application unit **13** that determines a predetermined parameter u by means of

numerical calculation.

(59) As illustrated in FIG. 8, a CPU (not shown) included in the numerical control device **4** executes various programs to thereby implement various functions of the smoothing application unit **23**, and the like.

(60) Next, a process executed by the numerical control device **4** will be described with reference to FIG. 9. FIG. 9 is a flowchart illustrating the process executed by the numerical control device **4**.

(61) As illustrated in FIG. 9, the process executed by the numerical control device **4** includes a machining program reading step **S10**, a kinematic conversion step **S12**, a smoothing strength calculation step **S23**, a smoothing application step **S14**, an interpolation control step **S11**, and a drive control step **S18**. The process contents of each step are as described above.

(62) In this way, a numerical control device **4** includes a machining program reading unit **10** that generates, on a basis of a read machining program P, a tool center point sequence $P.sub.tcp(t)$ indicating a path of a center point of a tool T of a machining tool A, a kinematic conversion unit **12** that performs coordinate-conversion on the tool center point sequence $P.sub.tcp(t)$ generated by the machining program reading unit **10** to obtain a control point sequence $P.sub.mcn(t)$ indicating a path of a control point defining a position of the tool T, a smoothing application unit **23** that performs smoothing by performing smoothing processing on the control point sequence $P.sub.mcn(t)$, obtained by the kinematic conversion unit **12**, with a predetermined parameter u, an interpolation control unit **11** that interpolates the control point sequence $Q.sub.mcn(t)$ smoothed by the smoothing application unit **23**, and a drive control unit **14** that controls driving of the machining tool A on the basis of the control point sequence $Q.sub.mcn(t)$ interpolated by the interpolation control unit **11**.

(63) In the numerical control device **4**, the smoothing application unit **23** preferably analytically determines the predetermined parameter u.

(64) According to the numerical control device **4** according to the present embodiment, applying smoothing to the control point enables smooth motion of the spindle. This makes it possible to prevent the control point from rapidly operating, whereby the cycle time and the machining surface quality can be improved.

(65) Note that the present disclosure is not limited to each embodiment described above, and various changes and modifications are possible.

(66) For example, the $d.sub.Max$ may be obtained by a method different from each embodiment described above. For example, a difference $d(t.sub.1, t.sub.2)$ between $P.sub.tcp(t.sub.1)$ and $Q.sub.tcp(t.sub.2)$ can be represented as $d(t.sub.1, t.sub.2)=|Q.sub.tcp(t.sub.2)-P.sub.tcp(t.sub.1)|$. In an arbitrary value $t.sub.1, t.sub.2$ that minimizes $d(t.sub.1, t.sub.2)$ is obtained, the value of d at that time is denoted by $d_.sub.min(t.sub.1)$. This is because there may be a case where the difference d between $P.sub.tcp(t.sub.1)$ and $Q.sub.tcp(t.sub.1)$ is not minimized. Then, $t.sub.1$ that maximizes $d_.sub.min(t.sub.1)$ is obtained, a value of $d_.sub.min$ at that time is denoted by dux .

(67) In the above-described first and third embodiments, the checking of a tolerance $T.sub.tcp$ is performed on the basis of the difference $d(t)=|Q.sub.tcp(t)-P.sub.tcp(t)|$ between the tool center point sequence $P.sub.tcp(t)$ and the tool center point sequence $Q.sub.tcp(t)$, and the maximum value of u (the maximum value of the smoothing strength) satisfying $d.sub.Max \leq T.sub.tcp$ is calculated, however, instead of this, the checking of the tolerance $T.sub.tcp$ is performed on the basis of difference $d.sub.tcp(t)=|Q.sub.tcp(t)-P.sub.tcp(t)|$ between the tool center point sequence $P.sub.tcp(t)$ and the tool center point sequence $Q.sub.tcp(t)$ and the checking of a tolerance $T.sub.mcn$ is performed on the basis of a difference $d.sub.mcn(t)=|Q.sub.mcn(t)-P.sub.mcn(t)|$ between the control point sequence $P.sub.mcn(t)$ and the control point sequence $Q.sub.mcn(t)$, so that a maximum value of u (a maximum value of the smoothing strength) satisfying both of $d.sub.tcp_Max \leq T.sub.tcp$ and $d.sub.mcn_Max \leq T.sub.mcn$ may be calculated.

(68) In this case, the tolerance checking unit **131** performs the tolerance checking not only on the basis of the difference $d.sub.tcp(t)$ between the tool center point sequence $P.sub.tcp(t)$ before the

coordinate-conversion is performed by the kinematic conversion unit **12** and the smoothed tool center point sequence $Q.sub.tcp(t)$ obtained by the inverse kinematic conversion unit **130**, but also on the basis of the difference $d.sub.mcn(t)$ between the control point sequence $P.sub.mcn(t)$ before the smoothing is performed by the smoothing application unit **13** and the control point sequence $Q.sub.mcn(t)$ smoothed by the smoothing application unit **13**.

(69) In the above-described second and fourth embodiments, u satisfying $d.sub.Max = T.sub.tcp$ where $d.sub.Max$ is a maximum value of the difference $d(t)$ between the tool center point sequence $P.sub.tcp(t)$ and the tool center point sequence $Q.sub.tcp(t)$, however, instead of this, u satisfying both of $d.sub.tcp_Max = T.sub.tcp$ and $d.sub.mcn_Max = T.sub.mcn$ may be calculated where $d.sub.tcp_Max$ is a maximum value of the difference $d.sub.tcp(t)$ between the tool center point sequence $P.sub.tcp(t)$ and the tool center point sequence $Q.sub.tcp(t)$ and $d.sub.mcn_Max$ is a maximum value of the difference $d.sub.mcn(t)$ between the control point sequence $P.sub.mcn(t)$ and the control point sequence $Q.sub.mcn(t)$.

EXPLANATION OF REFERENCE NUMERALS

(70) **1, 2, 3, 4** Numerical control device **10** Machining program reading unit **11** Interpolation control unit **12** Kinematic conversion unit **13, 23** Smoothing application unit **130** Inverse kinematic conversion unit **131** Tolerance checking unit **14** Drive control unit A Machining tool A1 Servo A2 Spindle T Tool P Machining program $P.sub.tcp(t)$ Tool center point sequence $P.sub.mcn(t)$ Control point sequence **S10** Machining program reading step **S11** Interpolation control step **S12** Kinematic conversion step **S13** Smoothing strength setting step **S14** Smoothing application step **S15** Inverse kinematic conversion step **S16** Tolerance checking step **S18** Drive control step **S23** Smoothing strength calculation step

Claims

1. A numerical control device, comprising: a processor configured to function as: a machining program reading unit that generates, on a basis of a read machining program, a tip point sequence indicating a path of a tip point of a tool of a machining tool; an interpolation control unit that interpolates the tip point sequence generated by the machining program reading unit; a kinematic conversion unit that performs coordinate-conversion on the tip point sequence interpolated by the interpolation control unit to obtain a control point sequence indicating a path of a control point defining a position of the tool; a smoothing application unit that performs smoothing by performing smoothing processing on the control point sequence, obtained by the kinematic conversion unit, with a predetermined parameter; and a drive control unit that controls driving of the machining tool on the basis of the control point sequence smoothed by the smoothing application unit, wherein the smoothing application unit includes: an inverse kinematic conversion unit that performs coordinate-conversion on the control point sequence smoothed by the smoothing application unit to obtain the smoothed tip point sequence; and a tolerance checking unit that performs checking whether a maximum value of a difference between the tip point sequence before the coordinate-conversion is performed by the kinematic conversion unit and the smoothed tip point sequence obtained by the inverse kinematic conversion unit is equal to or less than a predetermined threshold value, and determines the predetermined parameter by means of numerical calculation so that the maximum value of the difference is equal to or less than the threshold value.
2. The numerical control device according to claim 1, wherein the tolerance checking unit performs checking whether a maximum value of a difference between the control point sequence before the smoothing is performed by the smoothing application unit and the control point sequence smoothed by the smoothing application unit is equal to or less than a predetermined threshold value.
3. A numerical control device, comprising: a processor configured to function as: a machining program reading unit that generates, on a basis of a read machining program, a tip point sequence indicating a path of a tip point of a tool of a machining tool; a kinematic conversion unit that

performs coordinate-conversion on the tip point sequence generated by the machining program reading unit to obtain a control point sequence indicating a path of a control point defining a position of the tool; a smoothing application unit that performs smoothing by performing smoothing processing on the control point sequence, obtained by the kinematic conversion unit, with a predetermined parameter; an interpolation control unit that interpolates the control point sequence smoothed by the smoothing application unit; and a drive control unit that controls driving of the machining tool on the basis of the control point sequence interpolated by the interpolation control unit, wherein the smoothing application unit includes: an inverse kinematic conversion unit that performs coordinate-conversion on the control point sequence interpolated by the interpolation control unit to obtain the smoothed tip point sequence; and a tolerance checking unit that performs checking whether a maximum value of a difference between the tip point sequence before the coordinate-conversion is performed by the kinematic conversion unit and the smoothed tip point sequence obtained by the inverse kinematic conversion unit is equal to or less than a predetermined threshold value, and determines the predetermined parameter by means of numerical calculation so that the maximum value of the difference is equal to or less than the threshold value.

4. The numerical control device according to claim 3, wherein the tolerance checking unit performs checking whether a maximum value of a difference between the control point sequence before the smoothing is performed by the smoothing application unit and the control point sequence smoothed by the smoothing application unit is equal to or less than a predetermined threshold value.

5. A numerical control device, comprising: a processor configured to function as: a machining program reading unit that generates, on a basis of a read machining program, a tip point sequence indicating a path of a tip point of a tool of a machining tool; an interpolation control unit that interpolates the tip point sequence generated by the machining program reading unit; a kinematic conversion unit that performs coordinate-conversion on the tip point sequence interpolated by the interpolation control unit to obtain a control point sequence indicating a path of a control point defining a position of the tool; a smoothing application unit that performs smoothing by performing smoothing processing on the control point sequence, obtained by the kinematic conversion unit, with a predetermined parameter; and a drive control unit that controls driving of the machining tool on the basis of the control point sequence smoothed by the smoothing application unit, wherein the smoothing application unit includes: an inverse kinematic conversion unit that performs coordinate-conversion on the control point sequence smoothed by the smoothing application unit to obtain the smoothed tip point sequence and analytically determines the predetermined parameter so that a maximum value of a difference between the tip point sequence interpolated by the interpolation control unit before the coordinate-conversion is performed by the kinematic conversion unit and the smoothed tip point sequence obtained by the inverse kinematic conversion unit corresponds to a predetermined threshold value.
