

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250272388

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

Sellmeier; Andreas

RANSOMWARE PROTECTION FOR ARCHIVED DATA

Abstract

A computer-implemented method for protection of archival data is provided. The computer-implement method can comprise creating a first version of an object in an anti-attack store and storing an archival file in the object in the anti-attack store. The anti-attack store has associated anti-attack functionality triggerable based on detecting an attempted change to the object in the anti-attack store. The associated anti-attack functionality comprises automatically creating a new version of the object and automatically applying a retention lock to the first version of the object without applying the attempted change to the first version of the object, the retention lock specifying a retention period for the first version of the object.

Inventors: Sellmeier; Andreas (Baldham, DE)

Applicant: OPEN TEXT SA ULC (Halifax, CA)

Family ID: 1000007710765

Appl. No.: 18/590668

Filed: February 28, 2024

Publication Classification

Int. Cl.: G06F21/55 (20130101); G06F16/11 (20190101)

U.S. Cl.:

CPC G06F21/554 (20130101); G06F16/113 (20190101); G06F16/125 (20190101);
G06F2221/034 (20130101)

Background/Summary

TECHNICAL FIELD

[0001] This disclosure relates generally to network data security. More specifically, this disclosure relates to protecting stored data against ransomware attacks.

BACKGROUND

[0002] The exponential growth of data in the digital age has become a ubiquitous challenge for organizations. The need to retain data for legal, regulatory, and business reasons, along with the failure of users to cull redundant and obsolete data, results in the retention of vast amounts of data that is rarely accessed. This accumulation of data contributes to storage inefficiency and complicates data management tasks.

[0003] Data archiving systems, such as file archiving systems, aim to address these challenges by providing an intelligent, policy-driven approach to the categorization and storage of data. These systems implement policies to store rarely used or old data to archive storage that is typically cheaper, but slower to access, than the stores used for more active files. By segregating active data from archival data, data archiving systems optimize storage utilization and contribute to overall system performance. In addition to storage optimization, data archiving systems can include features to ensure data security and compliance.

[0004] In recent years, organizations have experienced an alarming rise in the prevalence and sophistication of ransomware attacks. Ransomware encrypts a user's files or entire systems, rendering them inaccessible until a ransom is paid to the attacker. Cloud-based file storage systems are not immune from ransomware and other cyberattacks. This poses a threat to data archiving systems that store archival files in cloud storage. Current strategies for addressing a ransomware attack without paying the ransom rely on restoring files from a backup made before the attack. This type of response, however, assumes that a backup is available, and that the backup was not affected by the attack. Often, however, there is no separate backup of archival data.

[0005] As such, there is a need for improved methods of protecting files from ransomware or other cyber-attacks.

SUMMARY

[0006] Embodiments of the present disclosure provide systems, methods, and computer program products for protecting archived data from cyberattacks, such as ransomware attacks. Embodiments can utilize an anti-attack archive store, such as an anti-attack container provided by a cloud storage system. The anti-attack store has associated anti-attack functionality enabled including versioning and automatic application of retention locks. According to one embodiment, an attempted change to an object in the anti-attack store causes the anti-attack store to create a new version of the object and automatically assert a retention lock on the old version of the object. The anti-attack store can further send a notification to an information technology operations system or other system to trigger a remedial action.

[0007] One general aspect includes a computer-implemented method for protection of archival data against cyberattacks. The method includes creating a first version of an object in an anti-attack store and storing an archival file in the object in the anti-attack store. The anti-attack store may include, in some embodiments, an anti-attack container on a cloud storage system. The anti-attack store has associated anti-attack functionality triggerable based on detecting an attempted change to the object in the anti-attack store enabled. The associated anti-attack functionality may include: automatically creating a new version of the object; and automatically applying a retention lock to the first version of the object without applying the attempted change to the first version of the object, the retention lock specifying a retention period for the first version of the object. The attempted change may be made to the new version of the object.

[0008] Another general aspect includes a non-transitory, computer-readable medium storing computer-translatable instructions, the computer-translatable instructions comprising instructions for creating a first version of an object in an anti-attack store and storing an archival file in the

object in the anti-attack store. The anti-attack store may include, in some embodiments, an anti-attack container on a cloud storage system. The anti-attack store has associated anti-attack functionality triggerable based on detecting an attempted change to the object in the anti-attack store. The associated anti-attack functionality may include automatically creating a new version of the object and automatically applying a retention lock to the first version of the object without applying the attempted change to the first version of the object, the retention lock specifying a retention period for the first version of the object.

[0009] Another general aspect includes a network system for data archiving that includes a storage component and a data archiving computer system coupled to the storage component. The data archiving computer system may comprise a data archiving system executable to access an anti-attack container of a cloud storage system; and store an archival file as a first version of an object in the anti-attack container. In some embodiments, the anti-attack container is a container on a cloud storage system. The anti-attack container has associated anti-attack functionality triggerable based on an attempted change to the object. The associated anti-attack functionality may include automatically creating a new version of the object in the anti-attack container and automatically applying a retention lock to the first version of the object without applying the attempted change to the first version of the object, the retention lock specifying a retention period for the first version of the object. The network system may further include an information technology operations system comprising instructions executable to receive a notification from the cloud storage system of an event associated with the object and execute a remedial action in response to the notification.

[0010] In some embodiments, the anti-attack functionality further may include sending a notification of an event associated with the attempted change to a target. The notification of the event associated with the attempted change may include a notification that the new version of the object has been created. According to one embodiment, the notification of the event associated with the attempted change triggers a remedial action. The remedial action, according to one embodiment, includes one or more of blocking a connection, scanning an environment for attacker code, investigating entry points for attacker code, removing attacker code, restoring the first version of the object as a current version of the object, or deleting the new version of the object.

[0011] Embodiments of the present disclosure provide protection against cyberattacks for archived data without requiring the resources that would otherwise be required to maintain additional backups of the archived data for long periods of time.

[0012] These, and other, aspects of the invention will be better appreciated and understood when considered in conjunction with the following description and the accompanying drawings. The following description, while indicating various embodiments of the invention and numerous specific details thereof, is given by way of illustration and not of limitation. Many substitutions, modifications, additions or rearrangements may be made within the scope of the invention, and the invention includes all such substitutions, modifications, additions or rearrangements.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] The drawings accompanying and forming part of this specification are included to depict certain aspects of the invention. A clearer impression of the invention, and of the components and operation of systems provided with the invention, will become more readily apparent by referring to the exemplary, and therefore nonlimiting, embodiments illustrated in the drawings, wherein identical reference numerals designate the same components. Note that the features illustrated in the drawings are not necessarily drawn to scale.

[0014] FIG. 1 is a diagrammatic representation of one embodiment of an enterprise computing system **100** that includes data archiving.

[0015] FIG. 2A and FIG. 2B (collectively, FIG. 2) are diagrammatic representations of one embodiment of providing anti-attack protection for archived data.

[0016] FIG. 3 is a flow chart of one embodiment of providing anti-attack protection for archived data.

[0017] FIG. 4 is a diagrammatic representation of a distributed network environment.

DETAILED DESCRIPTION

[0018] The invention and the various features and advantageous details thereof are explained more fully with reference to the non-limiting embodiments that are illustrated in the accompanying drawings and detailed in the following description. Descriptions of well-known starting materials, processing techniques, components and equipment are omitted so as not to unnecessarily obscure the invention in detail. It should be understood, however, that the detailed description and the specific examples, while indicating some embodiments of the invention, are given by way of illustration only and not by way of limitation. Various substitutions, modifications, additions and/or rearrangements within the spirit and/or scope of the underlying inventive concept will become apparent to those skilled in the art from this disclosure.

[0019] In general, data archiving refers to the movement or copying of data to separate storage for the general purpose of data retention. The storage used for archival data is often less expensive, but slower or more difficult to access, than the storage used for active data. As mentioned above, data archiving systems may use cloud storage for storing archival data.

[0020] Embodiments of the present disclosure generally pertain to methods and systems for protecting archival data from ransomware or other cyber-attacks. More particularly, embodiments relate to protecting archival data in cloud storage. Even more particularly, some embodiments relate to protecting archival data stored in third-party cloud storage systems.

[0021] FIG. 1 is a diagrammatic representation of one embodiment of an enterprise computing system **100** that includes data archiving. In the embodiment illustrated, enterprise computing system **100** includes a plurality of storage components **102** that store structured or unstructured data relevant to the enterprise, such as content related to file systems and enterprise applications. A storage component may comprise any computer system that stores data, such as a client computer, a content management system, a file system, or a database to provide a few examples. Storage components are connected using a network **103**, such as a Local Area Network (LAN), a Wide Area Network (WAN), the Internet, or the like. An information technology operations (ITOps) system **104** is connected to storage components **102** via the network and provides services for managing the IT infrastructure of network **103**.

[0022] Data volume growth in an enterprise computing environment, such as enterprise computing system **100**, can create compliance concerns and increase legal and business risks. However, resource requirements and storage costs make retaining all this data unviable. To help manage data, enterprise computing system **100** comprises a data archiving system **106**. Data archiving system **106** is connected to storage components **102** and ITOps system **104** via network **103**. In some embodiments, data archiving system **106** is provided by a content management system **107** that includes components to manage active files. According to one embodiment, data archiving system **106** and content management system **107** are implemented in software executed by one or more computer systems.

[0023] Data archiving system **106** implements policies **112** to identify data from storage components **102** based on criteria such as usage patterns, relevance, and regulatory requirements and stores the data as archival data to archive store **110**. Archive store **110**, according to one embodiment, is an object-based store that stores data items, such as files, as corresponding objects **114**. The archival data stored in archive store **110** can include archival copies of data being worked on or actively updated in enterprise computing system **100** and archival copies of data that is no longer being worked on or has been removed from storage components **102**. As will be appreciated, data archiving system **106** may include features to ensure data security and compliance, such as

encryption, enforcement of retention policies, and lifecycle management of archival data.

[0024] In some embodiments, data archiving system **106** uploads files or other data items in their native format as archival data for storage in archive store **110**. In other embodiments, data archiving system **106** stores data from storage components **102** to an archive format different from the native format. The archive format, for example, may be a format that compresses data, encrypts data, or combines several native data items together in a single archival file for upload.

[0025] Data archiving system **106** maintains an archiving system data store **115** that stores information used by data archiving system **106** for managing archival and retrieval of data. According to one embodiment, such information comprises archive metadata **116**, archiving policies **112**, and data that defines roles and permissions within the context of archiving. Archive metadata **116** provides data used to manage archiving and retrieval of archival data in archive store **110**. Examples of archive metadata **116** for an archival file include, but are not limited to, native metadata of the file or files stored as the archival file or other metadata collected from storage components **102**, a mapping of the native files to the archival files, the object id of the object in archive store **110** that stores the archival file, the archive policies **112** to which the archival file is subject, permission assignments for permissions enforced by data archiving system **106** for the archival file. Archive policies **112** include policies that define what data to store to archive store **110**, retention policies defining how long archival data is to be retained, lifecycle policies that define how or when to dispose of archival data when the applicable retention period has expired, and other policies.

[0026] As discussed, archive store **110** may be a cloud storage system. Archive store **110** may provide various features for managing content stored on the cloud storage system, such as versioning and retention policies. To this end, archive store **110** maintains cloud storage management store **121** that includes archive storage metadata **122**, policies **124**, roles and permissions and other metadata used for managing a cloud storage system. Examples of archive storage metadata **122** include, but are not limited to, permission assignments for permissions enforced by archive store **110**, versioning information, and metadata specifying policies applied to containers or objects. Policies **124** include, for example, versioning policies, retention policies, anti-attack policies, and lifecycle policies enforced by archive store **110**.

[0027] Archive store **110**, as discussed, supports versioning. As would be appreciated by those in the art, versioning functionality allows several copies of an item to be maintained as multiple versions of the same object. For example, file versioning allows multiple copies of a file to be maintained as different versions of the same file. The different versions are linked using versioning metadata.

[0028] One or more of the storage components **102** or content management system **107** can also support versioning. In accordance with one embodiment, data archiving system **106**, stores each version of item, for versioning controlled by a storage component **102** or content management system **107**, as a different object without using the versioning functionality of archive storage. From the perspective of archive store **110**, each object **114** is a different object, even if multiple objects **114** store what, from the perspective of a storage component **102** or content management system **107**, are different versions of the same item. For example, say content management system maintains a File1, version 1 and File1, version 2 as different versions of the same file and data archiving system **106** archives these versions, data archiving system **106** stores File1, version 1 as Object1 in archive store **110** and File1, version 2 as Object2 without using the versioning functionality of archive store **110**. Thus, from the perspective of archive store **110**, Object1 and Object2 are different objects and not versions of the same object. Moreover, in some embodiments, data archiving system **106** stores data to archive store **110** without applying a retention policy enforceable by archive storage. Instead, data archiving system **106** manages retention based on retention policies that are not propagated to archive store **110**.

[0029] As will be appreciated, users of cloud storage systems typically store data to virtual

containers associated with the user's account. Typically, an account holder can create multiple containers, specify who (e.g., what users or roles) can access the container, and enable certain functionality, such as versioning, on a per container basis. In the illustrated embodiment, data archiving system **106** is configured with credentials or other information to allow data archiving system **106** to access and store data to container **120**. With respect to archival data, a user who may have permission to access the data when it is not archived (e.g., when access is controlled by a storage component **102** or content management system **107**), may not have permission to access the archival version of the data.

[0030] According to one embodiment, the owner or user with sufficient permissions can configure an object with an anti-attack policy. In some embodiments, assigning an anti-attack policy to an object comprises configuring a container as an anti-attack container. For example, objects **114** may be configured with an anti-attack policy by virtue of being in container **120**, where container **120** is configured as an anti-attack container. An anti-attack policy, according to one embodiment, comprises a versioning configuration and a retention policy. When an anti-attack policy is in force on an object and archive store **110** detects an attempted change to the object, archive store **110** automatically creates a new version of the object and places a retention lock on the old version according to the retention policy. The retention lock comprises a retention configuration that specifies how long the object will be retained. For example, the retention lock, in some embodiments, specifies a “retain until time” that indicates the date and time to which the object must be retained. If, for example, the retention policy specifies a time of 30 days, archive store **110** will set the retain until time to be 30 days from when the retention lock is set. The retention configuration may also control, for example, what changes can be made to the specification. For example, the retention configuration may specify that authorized users can change the retention configuration for an object or that the retention configuration cannot be changed for the object.

[0031] In one embodiment, the anti-attack policy may also specify a notification target. When the anti-attack policy is triggered by an edit to the object, archive storage sends a notification to the notification target. In one embodiment, the notification target is ITOps system **104**, which is programmed with rules to take remedial action responsive to the notification. In one embodiment, the remedial action includes one or more of: blocking connections to archive store **110**, scanning the relevant environment (e.g., enterprise computing system **100**) for attacker code, investigating entry points where the attacker code came from, removing the attacker code, restoring the ‘current’ version of attacked objects from the ‘non-current’ version. Setting the system live again when the attacker code has been removed.

[0032] FIG. 2A and FIG. 2B (collectively, FIG. 2) are diagrammatic representations of one embodiment of providing anti-attack protection for archived data. In FIG. 2, a data archiving system **200**, such as data archiving system **106** of FIG. 1, stores archival data to an anti-attack container **202** of an archive store **204**. In one embodiment, archive store **204** comprises a cloud storage system. In an even more particular embodiment, archive store is a third-party cloud storage system provided by a different entity than controls data archiving system **200**. Anti-attack container **202** has associated functionality enabled (e.g., via configuration, in some embodiments) comprising: when archive store **204** detects an attempted change to an object in anti-attack container **202**, archive store **204** creates a new version of the object, and archive store **204** automatically applies a retention lock on the old version of the object.

[0033] In FIG. 2A, the data archiving system **200** creates an object **210** and stores data to be archived to the new object as archival data. For example, data archiving system **200** stores an archival document as an object **210** in anti-attack container **202**. At this point, object **210** is the current object as it is the most current version of the object. Turning to FIG. 2B, attacker code **220** attempts to change the archival document in anti-attack container **202**—for example, ransomware attempts to encrypt object **210**. Archive store **204** stores the changed object **212** as a new version of the object and places a retention lock **214** on object **210**, to which the change was not applied.

Here, object **210** and object **212** are linked by archive store **204** as different versions of the same object. Object **212** is now the current version of the object and object **210** is an old (not current) version of the object.

[0034] Retention lock **214** comprises a retention configuration that specifies how long the object will be retained. For example, the retention lock, in some embodiments, specifies a “retain until time” that indicates the date and time to which the object must be retained. In some embodiments, the retention configuration is based on a policy assigned to anti-attack container **202**. In general, the duration of the retention lock may be selected to allow recovery from the attack. Thus, the retention lock may specify a relatively short retention period (e.g., a week, 30 days, or another period). Retention lock **214** is enforced by archive store **204** rather than a retention policy enforced by data archiving system **200**.

[0035] In some embodiments, the functionality associated with anti-attack container **202** further comprises archive store **204** sending a notification to a target, such as ITOps system **216**, of a predefined event associated with the attempted change. In some embodiments, the predefined event comprises detecting an attempted change to an object in anti-attack container **202** or creating a new version of an object in anti-attack container **202**. In one embodiment, for example, when archive store **204** creates object **212**—i.e., the new version of object **210**—archive store **204** sends a notification of the event to ITOps system **216**. ITOps can take remedial action, such as, but not limited to: blocking connections to archive store **204** or anti-attack container **202**, scanning the relevant environment for attacker code **220**, investigating entry points for attacker code **220**, removing attacker code **220**, restoring the ‘current’ version of attacked objects from the ‘non-current’ version, setting the system live again when attacker code **220** has been removed. In one embodiment, for example, ITOps system deletes object **212**, which makes object **210** the current version of the object again.

[0036] An attack may continue for some time before remedial action can be implemented. In such instances, attacker code **220** may attempt to change object **212**, resulting in yet another version of the object being created. In some embodiments, archive store **204** limits the number of new versions of an object that can be created in anti-attack container **202**, thereby preventing runaway chains of new versions being created. For example, archive store **204** may limit the system to creating only one new version of the object in archive store **204**. In yet another embodiment, archive store **204** may limit the versions on which it places the retention lock. For example, archive store **204**, according to one embodiment, is configured to only place the retention lock on one version of an object. Thus, even if there is a chain of newer versions created in an attack, the remedial action can still delete the new versions.

[0037] FIG. **3** is a flow chart illustrating one embodiment of a method **300** for providing anti-attack protection for archived data. In some embodiments, method **300** of FIG. **3** is embodied as computer-executable instructions on a non-transitory computer readable medium. In even more particular embodiments, steps FIG. **3** are implemented by a data archiving system, a cloud storage system, and an ITOps system.

[0038] At step **302**, an anti-attack storage container is configured at an archive store for a data archiving system. Configuring the anti-attack container may include, for example, setting permissions to allow the data archiving system to store and retrieve data from the container and enabling anti-attack functionality. Enabling anti-attack functionality includes, in one embodiment, enabling versioning on the container and enabling the setting of retention locks on old versions of objects in the anti-attack container when new versions of the objects are created. Configuring the anti-attack container includes, in some embodiments, specifying the retention policy to be applied to old versions of objects in the anti-attack container and setting a target for predefined event notifications with respect to events on objects in the anti-attack container. According to one embodiment, the archive store is a cloud storage system and the anti-attack container is a cloud storage container provided by the cloud storage system.

[0039] At step **304**, the data archiving system creates a new object in the anti-attack container and stores archival data to the object.

[0040] At step **306**, the archive store detects an attempted change to the object and executes the enabled anti-attack functionality. For example, at step **308**, the archive store creates a new version of the object in the anti-attack container and saves the changes to the new version of the object. When the new version of the object is created, the new version becomes the current version and the prior version becomes the old version.

[0041] At step **310**, the archive store applies a retention lock to the old version of the object. The retention lock specifies a retention period for which the older version of the object is to be retained. The retention period, according to one embodiment, is based on a retention policy associated with the anti-attack container. In another embodiment, the retention period is a default retention period.

[0042] At step **312**, the archive store sends a notification of an event associated with the object to a target. For example, in one embodiment, the archive store sends a notification that the archive store has created a new version of the object. In one embodiment, the target is an ITOps system or other system that can execute remedial action.

[0043] At step **314**, remedial action is executed. The remedial action, according to one embodiment, comprises at least one of blocking connections to the archive store or anti-attack container, scanning the relevant environment for attacker code, investigating entry points for the attacker code, removing the attacker code, restoring the 'current' version of attacked objects from a 'non-current' version, or setting the system live again when attacker code has been removed.

[0044] FIG. **3** is merely an illustrative example, and the disclosed subject matter is not limited to the ordering or number of steps illustrated. Embodiments may implement additional steps or alternative steps, omit steps, or repeat steps.

[0045] FIG. **4** is a diagrammatic representation of one embodiment of a distributed network computing environment **400**. In the example illustrated, network computing environment **400** includes network **401** that is bi-directionally coupled to storage components **402**, a data archiving computer system **404**, and an ITOps computer system **408**. Data archiving computer system **404** and ITOps computer system **408** are connected to an archive store **410** via the Internet.

[0046] Storage components **402** are computer systems with related processors, memories and interfaces that store relevant data. Data archiving computer system **404** comprises a computer processor **411** and associated memory **412**. Computer processor **411** may be an integrated circuit for processing instructions, such as, but not limited to a central processing unit (CPU). Memory **412** may include volatile memory, non-volatile memory, semi-volatile memory or a combination thereof. Memory **412**, for example, may include RAM, ROM, flash memory, a hard disk drive, a solid-state drive, an optical storage medium (e.g., CD-ROM), or other computer readable memory or combination thereof. Memory **412** implements a storage hierarchy that includes cache memory, primary memory and secondary memory. In some embodiments, memory **412** includes storage space on a data storage array. Data archiving computer system **404** may also include input/output ("I/O") devices **414**, such as a keyboard, monitor, printer, electronic pointing device (e.g., mouse, trackball, stylus, etc.), or the like, and a communication interface **416**, such as a network interface card, to interface with network **401**. Data archiving computer system **404** includes executable instructions **418** stored on a non-transitory computer readable medium coupled to computer processor **411**. The computer executable instructions of data archiving computer system **404** are executable to provide a data archiving system, such as data archiving system **106** or data archiving system **200**.

[0047] ITOps computer system **408** comprises a computer processor **430** and associated memory **432**. Computer processor **430** may be an integrated circuit for processing instructions, such as, but not limited to a CPU. Memory **432** may include volatile memory, non-volatile memory, semi-volatile memory or a combination thereof. Memory **432**, for example, may include RAM, ROM, flash memory, a hard disk drive, a solid-state drive, an optical storage medium (e.g., CD-ROM), or

other computer readable memory or combination thereof. Memory **432** implements a storage hierarchy that includes cache memory, primary memory and secondary memory. In some embodiments, memory **432** includes storage space on a data storage array. ITOps computer system **408** may also include input/output devices **434**, such as a keyboard, monitor, printer, electronic pointing device (e.g., mouse, trackball, stylus, etc.), or the like, and a communication interface **436**, such as a network interface card, to interface with network **401**.

[0048] ITOps computer system **408** includes executable instructions **438** stored on a non-transitory computer readable medium coupled to computer processor **430**. The computer executable instructions of ITOps computer system **408** are executable to receive notifications from archive store **410** and implement remedial actions.

[0049] Archive store **410** comprises a computer processor **440** and associated memory **442**. Computer processor **440** may be an integrated circuit for processing instructions, such as, but not limited to a CPU. Memory **442** may include volatile memory, non-volatile memory, semi-volatile memory or a combination thereof. Memory **442**, for example, may include RAM, ROM, flash memory, a hard disk drive, a solid-state drive, an optical storage medium (e.g., CD-ROM), or other computer readable memory or combination thereof. Memory **442** implements a storage hierarchy that includes cache memory, primary memory and secondary memory. In some embodiments, memory **442** includes storage space on a data storage array. Data archiving computer system **404** may also include input/output devices **444**, such as a keyboard, monitor, printer, electronic pointing device (e.g., mouse, trackball, stylus, etc.), or the like, and a communication interface **446**, such as a network interface card, to interface with network **401**.

[0050] Archive store **410** includes executable instructions **448** to provide an archive store such as archive store **110** or archive store **204**. More particularly, executable instructions **418** are executable to provide an anti-attack container and anti-attack functionality. In some embodiments, archive store **410** is a cloud storage system.

[0051] While the invention has been described herein with reference to particular embodiments thereof, a latitude of modification, various changes and substitutions are intended in the foregoing disclosures, and it will be appreciated that in some instances some features of embodiments of the invention will be employed without a corresponding use of other features without departing from the scope and spirit of the invention as set forth. Therefore, many modifications may be made to adapt a particular situation or material to the essential scope and spirit of the invention. For example, it will be understood that while embodiments as discussed herein are presented in the context of a browser-based application other embodiments may be applied with equal efficacy to other types of components on computing devices (e.g., other native components, etc.).

[0052] Reference throughout this specification to “one embodiment”, “an embodiment”, or “a specific embodiment” or similar terminology means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment and may not necessarily be present in all embodiments. Thus, respective appearances of the phrases “in one embodiment”, “in an embodiment”, or “in a specific embodiment” or similar terminology in various places throughout this specification are not necessarily referring to the same embodiment. Furthermore, the particular features, structures, or characteristics of any particular embodiment may be combined in any suitable manner with one or more other embodiments. It is to be understood that other variations and modifications of the embodiments described and illustrated herein are possible in light of the teachings herein and are to be considered as part of the spirit and scope of the invention.

[0053] In the description herein, numerous specific details are provided, such as examples of components and/or methods, to provide a thorough understanding of embodiments of the invention. One skilled in the relevant art will recognize, however, that an embodiment may be able to be practiced without one or more of the specific details, or with other apparatus, systems, assemblies, methods, components, materials, parts, and/or the like. In other instances, well-known structures,

components, systems, materials, or operations are not specifically shown or described in detail to avoid obscuring aspects of embodiments of the invention. While the invention may be illustrated by using a particular embodiment, this is not and does not limit the invention to any particular embodiment and a person of ordinary skill in the art will recognize that additional embodiments are readily understandable and are a part of this invention.

[0054] Embodiments discussed herein can be implemented in a computer communicatively coupled to a network (for example, the Internet), another computer, or in a standalone computer. As is known to those skilled in the art, a suitable computer can include a CPU, read-only memory (“ROM”), random access memory, secondary storage, input/output device(s), and interfaces.

[0055] ROM, RAM, and HD are computer memories for storing computer-executable instructions executable by the CPU or capable of being compiled or interpreted to be executable by the CPU. Suitable computer-executable instructions may reside on a computer readable medium (e.g., ROM, RAM, and/or HD), hardware circuitry or the like, or any combination thereof. Within this disclosure, the term “computer readable medium” is not limited to ROM, RAM, and HD and can include any type of data storage medium that can be read by a processor. For example, a computer-readable medium may refer to a data cartridge, a data backup magnetic tape, a floppy diskette, a flash memory drive, an optical data storage drive, a CD-ROM, ROM, RAM, HD, or the like. The processes described herein may be implemented in suitable computer-executable instructions that may reside on a computer readable medium (for example, a disk, CD-ROM, a memory, etc.). Alternatively, the computer-executable instructions may be stored as software code components on a direct access storage device array, magnetic tape, floppy diskette, optical storage device, or other appropriate computer-readable medium or storage device.

[0056] Any suitable programming language can be used to implement the routines, methods or programs of embodiments of the invention described herein. Functions of the disclosed embodiments may be implemented on one computer or shared/distributed among two or more computers in or across a network. Communications between computers implementing embodiments can be accomplished using any electronic, optical, radio frequency signals, or other suitable methods and tools of communication in compliance with known network protocols.

[0057] Different programming techniques can be employed such as procedural or object oriented. Any particular routine can execute on a single computer processing device or multiple computer processing devices, a single computer processor or multiple computer processors. Data may be stored in a single storage medium or distributed through multiple storage mediums and may reside in a single database or multiple databases (or other data storage techniques). Although the steps, operations, or computations may be presented in a specific order, this order may be changed in different embodiments. In some embodiments, to the extent multiple steps are shown as sequential in this specification, some combination of such steps in alternative embodiments may be performed at the same time. The sequence of operations described herein can be interrupted, suspended, or otherwise controlled by another process, such as an operating system, kernel, etc. The routines can operate in an operating system environment or as stand-alone routines. Functions, routines, methods, steps and operations described herein can be performed in hardware, software, firmware or any combination thereof.

[0058] Embodiments described herein can be implemented in the form of control logic in software or hardware or a combination of both. The control logic may be stored in an information storage medium, such as a computer-readable medium, as a plurality of instructions adapted to direct an information processing device to perform a set of steps disclosed in the various embodiments. Based on the disclosure and teachings provided herein, a person of ordinary skill in the art will appreciate other ways and/or methods to implement the invention.

[0059] It is also within the spirit and scope of the invention to implement in software programming or code an of the steps, operations, methods, routines or portions thereof described herein, where such software programming or code can be stored in a computer-readable medium and can be

operated on by a processor to permit a computer to perform any of the steps, operations, methods, routines or portions thereof described herein. In general, the functions of the invention can be achieved by any means as is known in the art. For example, distributed or networked systems, components and circuits can be used. In another example, communication or transfer (or otherwise moving from one place to another) of data may be wired, wireless, or by any other means.

[0060] A “computer-readable medium” may be any medium that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, system or device. The computer readable medium can be, by way of example only but not by limitation, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, system, device, propagation medium, or computer memory. Such a computer-readable medium shall generally be machine readable and include software programming or code that can be human readable (e.g., source code) or machine readable (e.g., object code). Examples of non-transitory computer-readable media can include random access memories, read-only memories, hard drives, data cartridges, magnetic tapes, floppy diskettes, flash memory drives, optical data storage devices, compact-disc read-only memories, and other appropriate computer memories and data storage devices. In an illustrative embodiment, some or all of the software components may reside on a single server computer or on any combination of separate server computers. As one skilled in the art can appreciate, a computer program product implementing an embodiment disclosed herein may comprise one or more non-transitory computer readable media storing computer instructions translatable by one or more processors in a computing environment.

[0061] It will also be appreciated that one or more of the elements depicted in the drawings/figures can be implemented in a more separated or integrated manner, or even removed or rendered as inoperable in certain cases, as is useful in accordance with a particular application. Additionally, any signal arrows in the drawings/figures should be considered only as exemplary, and not limiting, unless otherwise specifically noted.

[0062] As used herein, the terms “comprises,” “comprising,” “includes,” “including,” “has,” “having,” or any other variation thereof, are intended to cover a non-exclusive inclusion. For example, a process, product, article, or apparatus that comprises a list of elements is not necessarily limited only to those elements but may include other elements not expressly listed or inherent to such process, product, article, or apparatus.

[0063] Furthermore, the term “or” as used herein is generally intended to mean “and/or” unless otherwise indicated. For example, a condition A or B is satisfied by any one of the following: A is true (or present) and B is false (or not present), A is false (or not present) and B is true (or present), and both A and B are true (or present). As used herein, a term preceded by “a” or “an” (and “the” when antecedent basis is “a” or “an”) includes both singular and plural of such term, unless clearly indicated within the otherwise (i.e., that the reference “a” or “an” clearly indicates only the singular or only the plural).

Claims

1. A computer-implemented method for protection of archival data, comprising: creating a first version of an object in an anti-attack store; storing an archival file in the object in the anti-attack store, wherein the anti-attack store has associated anti-attack functionality triggerable based on detecting an attempted change to the object in the anti-attack store enabled, the associated anti-attack functionality comprising: automatically creating a new version of the object; and automatically applying a retention lock to the first version of the object without applying the attempted change to the first version of the object, the retention lock specifying a retention period for the first version of the object.

2. The computer-implemented method of claim 1, wherein the associated anti-attack functionality

further comprises: sending a notification of an event associated with the attempted change to a target.

3. The computer-implemented method of claim 2, wherein the notification of the event associated with the attempted change comprises a notification that the new version of the object has been created.

4. The computer-implemented method of claim 2, wherein the notification of the event associated with the attempted change triggers a remedial action, and wherein the remedial action comprises at least one of: blocking a connection; scanning an environment for attacker code; investigating entry points for attacker code; removing the attacker code; restoring the first version of the object as a current version of the object; or deleting the new version of the object.

5. The computer-implemented method of claim 1, wherein the anti-attack store comprises an anti-attack container on a cloud storage system.

6. The computer-implemented method of claim 1, wherein the attempted change is made to the new version of the object.

7. A computer-implemented method for protection of archival data, comprising: creating a first version of an object in an anti-attack store; storing an archival file in the object in the anti-attack store; detecting an attempted change to the object; based on detecting the attempted change to the object, protecting the object from a potential cyber-attack, wherein protecting the object from the potential cyber-attack comprises: automatically creating a new version of the object in the anti-attack store; and automatically applying a retention lock to the first version of the object without applying the attempted change to the first version of the object, the retention lock specifying a retention period for the first version of the object.

8. The computer-implemented method of claim 7, further comprising applying the attempted change to the new version of the object.

9. The computer-implemented method of claim 7, wherein protecting the object from the potential cyber-attack further comprises sending a notification of an event associated with the attempted change to a target.

10. The computer-implemented method of claim 9, wherein the notification of the event associated with the attempted change comprises a notification that the new version of the object has been created.

11. The computer-implemented method of claim 9, wherein the notification of the event associated with the attempted change triggers a remedial action, and wherein the remedial action comprises at least one of: blocking a connection; scanning an environment for attacker code; investigating entry points for attacker code; removing the attacker code; restoring the first version of the object as a current version of the object; or deleting the new version of the object.

12. The computer-implemented method of claim 7, wherein the anti-attack store comprises an anti-attack container of a cloud storage system.

13. A non-transitory, computer-readable medium storing computer-translatable instructions, the computer-translatable instructions comprising instructions for: creating a first version of an object in an anti-attack store; storing an archival file in the object in the anti-attack store, where the anti-attack store has associated anti-attack functionality triggerable based on detecting an attempted change to the object in the anti-attack store enabled, the associated anti-attack functionality comprising: automatically creating a new version of the object; and automatically applying a retention lock to the first version of the object without applying the attempted change to the first version of the object, the retention lock specifying a retention period for the first version of the object.

14. The non-transitory, computer-readable medium of claim 13, wherein the associated anti-attack functionality further comprises: sending a notification of an event associated with the attempted change to a target.

15. The non-transitory, computer-readable medium of claim 14, wherein the notification of the

event associated with the attempted change comprises a notification that the new version of the object has been created.

16. The non-transitory, computer-readable medium of claim 14, wherein the notification of the event associated with the attempted change triggers a remedial action, and wherein the remedial action comprises at least one of: blocking a connection; scanning an environment for attacker code; investigating entry points for attacker code; removing the attacker code; restoring the first version of the object as a current version of the object; or deleting the new version of the object.

17. The non-transitory, computer-readable medium of claim 14, wherein the anti-attack store comprises an anti-attack container on a cloud storage system.

18. A network system for data archiving comprising: a storage component; a data archiving computer system coupled to the storage component, the data archiving computer system comprising a data archiving system executable to: access an anti-attack container of a cloud storage system; and store an archival file as a first version of an object in the anti-attack container, the anti-attack container having associated anti-attack functionality triggerable based on an attempted change to the object, the associated anti-attack functionality comprising: automatically creating a new version of the object in the anti-attack container; and automatically applying a retention lock to the first version of the object without applying the attempted change to the first version of the object, the retention lock specifying a retention period for the first version of the object.

19. The network system of claim 18, further comprising an information technology operations system comprising instructions executable to: receive a notification from the cloud storage system of an event associated with the object; execute a remedial action in response to the notification.

20. The network system of claim 19, wherein the remedial action comprises at least one of: blocking a connection; scanning an environment for attacker code; investigating entry points for attacker code; removing the attacker code; restoring the first version of the object as a current version of the object; or deleting the new version of the object.
