

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283349

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Clark; Douglas et al.

DOOR LOCK ASSEMBLY WITH SAFEGUARDING AGAINST BYPASSING

Abstract

A lock portion of an electronic door lock system includes a first housing and a second housing secured to a backplate of the first housing. The second housing is secured to a first surface of the backplate and only accessible from a second surface of the backplate. One or more wires are secured to the second housing in a service loop and connected to an actuator within the second housing.

Inventors: Clark; Douglas (Wallingford, CT), Leites; Rick (Milford, CT), Morstatt; Scott (Maryville, TN), Palmieri; Eric (Rocky Hill, CT), Ramachandran; Sharath Kumar (Rocky Hill, CT)

Applicant: ASSA ABLOY Access and Egress Hardware Group, Inc. (New Haven, CT)

Family ID: 83887171

Assignee: ASSA ABLOY Access and Egress Hardware Group, Inc. (New Haven, CT)

Appl. No.: 19/214352

Filed: May 21, 2025

Related U.S. Application Data

parent US continuation 17736724 20220504 PENDING child US 19214352

us-provisional-application US 63184524 20210505

us-provisional-application US 63232811 20210813

Publication Classification

Int. Cl.: E05B9/08 (20060101); E05B9/00 (20060101); E05B47/00 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application claims the benefit under 35 U.S.C. § 119 (e) to U.S. Provisional Application Ser. No. 63/184,524, entitled “DOOR LOCK ASSEMBLY WITH SAFEGUARDING AGAINST BYPASSING,” filed May 5, 2021, and to U.S. Provisional Application Ser. No. 63/232, 811 entitled “DOOR LOCK ASSEMBLY WITH SAFEGUARDING AGAINST BYPASSING,” filed Aug. 13, 2021, each of which is herein incorporated by reference in its entirety.

FIELD

[0002] This disclosure relates generally to door lock assemblies, including bored lock assemblies, mortise lock assemblies, exit devices, and deadbolt assemblies.

BACKGROUND

[0003] It has become increasingly common for exterior doors to be equipped with electromechanical locking systems. Such locking systems include electrical hardware. Often, these electromechanical locking systems include portions mounted on both the inside and outside surfaces of the door.

SUMMARY

[0004] In some embodiments, a handing assembly for a door lock system comprises a housing including an opening, a disc positioned in the housing, wherein the disc includes an outer spindle extending from the disc through the opening, and a spring configured to bias the disc toward a first position. The handing assembly also comprises a catch configured to engage the disc when the disc is moved from the first position to a second position and to retain the disc in the second position.

[0005] In some embodiments, a method of handing a handle of a door lock system comprises moving a disc from a first position to a second position in a first direction, biasing the disc toward the first position with a spring in a second direction opposite the first direction, retaining the disc in the second position by engaging a first recess of the disc with a catch, and moving the outer spindle to a third position in the first direction while the catch is engaged with the first recess.

[0006] In some embodiments, a door lock system comprises a first spindle and a second spindle extending along a lock axis. The door lock system further comprises a lock body wherein the first spindle is configured to engage a first side of the lock body to bias the lock body in a first direction along the lock axis, and the second spindle is configured to engage a second side of the lock body opposite the first side of the lock body to bias the lock body in a second direction along the lock axis. The first direction is opposite the second direction, and the first spindle and the second spindle exert equal and opposite forces on the lock body.

[0007] In some embodiments, a method for installing a lock body in a door comprises engaging a first spindle on a first side of a lock body along a lock axis, wherein the first spindle biases the lock body in a first direction along the lock axis. The method further comprises engaging a second spindle on a second side of a lock body along the lock axis, wherein the second spindle biases the lock body in a second direction opposite the first direction, and wherein the first spindle and the second spindle exert equal and opposing forces on the lock body to center the lock body along a central plane of a door.

[0008] In some embodiments, a lock portion of an electronic door lock system comprises a first housing including a backplate having a first surface and a second surface opposite the first surface, wherein the second surface is configured to be mounted against a door surface. The lock portion

further comprises a second housing disposed within the first housing and attached to the first surface of the backplate, wherein the second housing is secured to the backplate by one or more fasteners that are only accessible from the second surface of the backplate. The lock portion further comprises an actuator disposed in the second housing and one or more power wires contained within the second housing, wherein the one or more power wires are connected to the actuator, wherein the one or more power wires are configured to selectively supply power to the actuator, and wherein the one or more power wires are secured to the second housing in a loop.

[0009] In some embodiments, a method of securing wiring in an electronic door lock system comprises passing a wire into a first housing through a first opening in a backplate of the first housing, inserting the wire into a second opening of a second housing disposed in the first housing, wherein the second housing is attached to a first surface of the backplate, looping the wire around a ledge attached to the second housing such that a first section of the wire overlaps a second section of the wire, and compressing the first section and the second section together to form a loop.

[0010] In some embodiments, a door lock system comprises a lock spindle aligned along a lock axis, a first end of the lock spindle configured to engage a lock body, an outer spindle aligned along the lock axis and cooperating with the lock spindle, the outer lock spindle having a first diameter, and a disc operatively connected to the outer spindle. The disc has an opening centered on the lock axis to slidingly receive the lock spindle along the lock axis. The disc has a second diameter larger than the first diameter, wherein the opening and the lock spindle have complementary shapes, and wherein torque is transmitted from a handle to the disc and from the disc to the lock spindle via the opening.

[0011] In some embodiments, a method of operating a door lock system comprises inserting a lock spindle aligned along a lock axis through an opening in a disc to engage a first end of the lock spindle in a lock body, wherein the opening and the lock spindle have complementary shapes. The method further comprises rotating an outer spindle operatively coupled to the disc about the lock axis, wherein torque is transmitted from the outer spindle to the disc and from the disc to the lock spindle via the opening.

[0012] In some embodiments, a door lock system comprises a handle attached to an outer spindle extending along a lock axis and a locking block disposed in the handle, wherein the locking block is moveable along the lock axis between a first position and a second position. The door lock system further comprises a lock spindle configured to engage a portion of the locking block to move the locking block from the first position to the second position.

[0013] In some embodiments, a method of removing a handle from a door lock system comprise biasing a locking block disposed in a handle in a first direction along a lock axis to a first position, wherein when the locking block is in the first position, a first portion of the locking block is positioned adjacent a catch that secures the handle to an outer spindle. The method further comprises moving the locking block along a lock axis in a second direction, opposite the first direction, from the first position to a second position, wherein when the locking block is in the second position, a second portion of the locking block is positioned adjacent the catch. The method further comprises moving the catch from an engaged position to a disengaged position.

[0014] In some embodiments, a door lock system comprises an exterior lock portion including an exterior escutcheon and an exterior housing, a printed circuit board disposed between the exterior escutcheon and the exterior housing, and a gasket disposed on a first side of the printed circuit board, wherein the gasket includes an L-shaped perimeter that wraps around a perimeter of the circuit board and covers a portion of a second side of the printed circuit board. The door lock system further comprises a plate disposed between the gasket and the exterior escutcheon, wherein the plate is configured to compress the L-shaped perimeter of the gasket against a ridge that protrudes from the exterior housing, wherein the ridge is configured to compress into the L-shaped perimeter to create a seal around the printed circuit board.

[0015] In some embodiments, a door lock system comprises an exterior lock portion and an outer

spindle disposed in the exterior lock portion that extends through an opening in the exterior lock portion. The door lock system further comprises a gasket disposed in the exterior lock portion, wherein the gasket includes an opening through which the outer spindle extends, the opening including a beveled perimeter having a smaller diameter on an outer surface than a diameter on an inner surface, wherein the smaller diameter of the opening is smaller than a diameter of the outer spindle such that the smaller diameter is configured to compress against the outer spindle.

[0016] In some embodiments, a door lock system comprises an interior housing having a battery compartment disposed therein, the interior housing including a slanted surface at least partially surrounding the battery compartment wherein the slanted surface includes a rib that protrudes from the slanted surface around at least a portion of the battery compartment. The door lock system further comprises a battery cover enclosing the battery compartment, and wherein an inner surface of the battery cover includes a slanted surface that complements the slanted surface on the housing. The door lock system further comprises a first compressible insert disposed between the slanted surface of the housing and the slanted surface of the battery cover, wherein the rib on the slanted surface is configured to compress into the first compressible insert.

[0017] It should be appreciated that the foregoing concepts, and additional concepts discussed below, may be arranged in any suitable combination, as the present disclosure is not limited in this respect. Further, other advantages and novel features of the present disclosure will become apparent from the following detailed description of various non-limiting embodiments when considered in conjunction with the accompanying figures.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0018] The accompanying drawings are not intended to be drawn to scale. In the drawings, each identical or nearly identical component that is illustrated in various figures may be represented by a like numeral. For purposes of clarity, not every component may be labeled in every drawing. In the drawings:

[0019] FIG. 1 is a perspective view of an embodiment of a door lock system;

[0020] FIG. 2 is a perspective view of an embodiment of an interior lock portion with a handing assembly;

[0021] FIG. 3 is a perspective view of the interior lock portion of FIG. 2 attached to a door with the handing assembly set as left-handed;

[0022] FIG. 4 is a perspective view of the interior lock portion of FIG. 2 with an outer cover of the interior lock portion removed to expose the handing assembly;

[0023] FIG. 5 is an exploded perspective view of the handing assembly of FIG. 2;

[0024] FIG. 6 is a perspective view of an embodiment of an outer spindle and a disc of the handing assembly of FIG. 5;

[0025] FIG. 7 is a rear perspective view of an embodiment of a housing of the handing assembly of FIG. 5;

[0026] FIG. 8A is a front schematic view of an embodiment of the handing assembly in a default position;

[0027] FIG. 8B is a front schematic view of an embodiment of the handing assembly in a left home position;

[0028] FIG. 8C is a front schematic view of an embodiment of the handing assembly in a right home position;

[0029] FIG. 9 is a flowchart of a method of operating the handing assembly according to one embodiment;

[0030] FIG. 10 is a perspective view of a door lock system according to one embodiment;

[0031] FIG. **11** is a side view of the door lock system of FIG. **10**;

[0032] FIG. **12** is an exploded rear perspective view of components in an interior lock portion according to one embodiment;

[0033] FIG. **13** is an exploded rear view of the components of FIG. **12**;

[0034] FIG. **14** is a side schematic view of the components of FIG. **12**;

[0035] FIG. **15** is an exploded view of an embodiment of components in an exterior lock portion;

[0036] FIG. **16** is an exploded rear perspective view of the components of FIG. **15**;

[0037] FIG. **17** is an exploded rear perspective view of the components of FIG. **15**;

[0038] FIG. **18** is a front schematic view of an embodiment of a spindle coupler;

[0039] FIG. **19** is a side schematic view of the components of FIG. **15**;

[0040] FIG. **20A** is a side schematic view of an embodiment of a lock body positioned in a door prior to installation of an exterior lock portion and an interior lock portion on the door;

[0041] FIG. **20B** is a side schematic view of the lock body of FIG. **20A** positioned in a door with an exterior lock portion installed on the door;

[0042] FIG. **20C** is a side schematic view of the lock body of FIG. **20A** positioned in a door with an exterior lock portion and an interior lock portion installed on the door;

[0043] FIG. **21** is a perspective view of an embodiment of an exterior lock portion with an outer cover of the lock portion removed to expose a secondary housing;

[0044] FIG. **22A** is a perspective view of the exterior lock portion of FIG. **21** with the cover removed to expose components in the secondary housing;

[0045] FIG. **22B** is an enlarged view of section **22B** of FIG. **22A**;

[0046] FIG. **23A** is a side schematic view of the exterior lock portion of FIG. **21**;

[0047] FIG. **23B** is an enlarged view of section **23B** of FIG. **23A**;

[0048] FIG. **24** is a flowchart of a method for running wiring between an interior lock portion and an exterior lock portion of a door lock system according to one embodiment;

[0049] FIG. **25** is a perspective view of an embodiment of a door lock assembly with an exterior lock portion with a keyless handle;

[0050] FIG. **26** is an exploded view of the exterior lock portion of FIG. **25**;

[0051] FIG. **27** is a rear perspective view of the exterior lock portion of FIG. **25**;

[0052] FIG. **28** is an exploded rear perspective view of locking components in the exterior lock portion of FIG. **25**;

[0053] FIG. **29A** is a top schematic view of components in the exterior lock portion of FIG. **25**;

[0054] FIG. **29B** is an enlarged view of section **29B** of FIG. **29A**;

[0055] FIG. **30A** is a top schematic view of the components in FIG. **29A** in an unlocked position;

[0056] FIG. **30B** is an enlarged view of section **30B** of FIG. **30A**;

[0057] FIG. **31** is a rear perspective view of an exterior lock spindle disposed in a spindle coupler of the exterior lock portion of FIG. **25**;

[0058] FIG. **32** is a rear perspective view of the spindle coupled of FIG. **31**;

[0059] FIG. **33** is a side schematic view of the locking components of the exterior lock portion of FIG. **25** with the exterior lock spindle in a pushed in and rotated position;

[0060] FIG. **34** is an exploded front perspective view of an exterior lock portion, according to an embodiment;

[0061] FIG. **35** is an exploded rear perspective view of the exterior lock portion of FIG. **34**;

[0062] FIG. **36A** is a rear perspective view of a gasket of the exterior lock portion of FIG. **34**;

[0063] FIG. **36B** is a cross-sectional view of the gasket of FIG. **36A** taken along line **36B**;

[0064] FIG. **37A** is a front view of an exterior housing of the exterior lock portion of FIG. **34**;

[0065] FIG. **37B** is a perspective cross sectional view of the exterior housing of FIG. **37A** taken along line **37B**;

[0066] FIG. **37C** is an enlarged view of section **37C** of FIG. **37B**;

[0067] FIG. **38A** is a side schematic view of the exterior lock portion of FIG. **34**;

[0068] FIG. 38B is an enlarged view of section 38B of FIG. 38A;
[0069] FIG. 38C is an enlarged view of section 38C of FIG. 38A;
[0070] FIG. 39A is a top schematic view of components of the exterior lock portion of FIG. 34;
[0071] FIG. 39B is an enlarged view of section 39B of FIG. 39A;
[0072] FIG. 40 is an exploded rear perspective view of an interior lock portion, according to an embodiment;
[0073] FIG. 41 is an exploded front perspective view of the interior lock portion of FIG. 40;
[0074] FIG. 42A is a front perspective view of a gasket of the interior lock portion of FIG. 40;
[0075] FIG. 42B is a side perspective cross sectional view of the gasket of FIG. 42A taken along line 42B;
[0076] FIG. 43A is a front view of an interior housing of the interior lock portion of FIG. 40;
[0077] FIG. 43B is a side perspective cross sectional view of the interior housing of FIG. 43A taken along line 43B;
[0078] FIG. 43C is an enlarged view of section 43C of FIG. 43B;
[0079] FIG. 44 is a front perspective view of a plate of the interior lock portion of FIG. 40;
[0080] FIG. 45A is a side perspective schematic view of the interior lock portion of FIG. 40;
[0081] FIG. 45B is an enlarged view of section 45B of FIG. 45A;
[0082] FIG. 46 is a front perspective view of the interior lock portion of FIG. 40 with a handle removed and battery cover displaced upwards;
[0083] FIG. 47 is a rear perspective view of the batter cover of FIG. 46;
[0084] FIG. 48A is a side schematic view of the interior lock portion of FIG. 40 with the battery cover in place;
[0085] FIG. 48B is a side schematic view of the interior lock portion of FIG. 40 with the battery cover displaced upwards;
[0086] FIG. 49A is a top schematic view of the interior lock portion of FIG. 40 with the battery cover in place;
[0087] FIG. 49B is an enlarged view of section 49B of FIG. 49A;
[0088] FIG. 50A is a front perspective schematic view of an interior lock portion with a battery cover removed;
[0089] FIG. 50B is a side perspective cross-sectional view of the interior lock portion of FIG. 50A taken along line 50B, with a battery cover in place;
[0090] FIG. 51 is a perspective view of an embodiment of a door lock system utilized with a mortise locking arrangement;
[0091] FIG. 52A is a perspective view of an embodiment of a door lock system utilized with an exit device on an interior door;
[0092] FIG. 52B is a perspective view of an exterior scutcheon of the door lock system of FIG. 52A; and
[0093] FIG. 53 is a perspective view of an embodiment of a door lock system utilized with a deadbolt locking arrangement.

DETAILED DESCRIPTION

[0094] Handles and locks in door lock systems are either left-handed or right-handed, depending on which way a door swings open. If door lock systems with the wrong handing are installed, the door may not open or close properly and/or the handles may be installed upside down or rotate in the wrong direction. In conventional systems, changing the handing of the locks and handles may not be possible, or it may be difficult and require extra tools and/or components to disassemble and reassemble the door lock system to provide the appropriate handing.

[0095] In view of the above, the inventors have recognized and appreciated designs for a door lock system in which the handles can each be quickly and reliably set as left-handed or right-handed to accommodate the door on which the door lock system is installed. In this manner, the door lock system may be universal for any door installation, whether it be left-handed or right-handed. The

door lock system may be purchased or shipped with or without handles attached. The handing of the door lock system need not be considered prior to installation and the handles may be initially in a default position, or otherwise not set as either left-handed or right-handed. During installation on a door, the rotating a handle or a handing assembly on the door lock system in one of two directions from the default position to a left or right home position may set the handing of the handles based on the door's swing. The handing may also be optionally returned to the default position and subsequently reset to the left or right home position without disassembling the door lock system or any extra tools. The handing of the door lock system may be set and/or reset prior to or after handles have been attached to the door lock system.

[0096] In some embodiments, a door lock system may include a toolless handing assembly disposed at least partially in the lock portion that may set the handing of a handle. The handing assembly may include a rotatable disc within a housing. An outer spindle attached to the disc may extend through an opening in the housing to allow a user to rotate the disc from an initial, default position, to a right or left home position. For example, the installer may rotate the spindle clockwise for a left handle or rotate the spindle counterclockwise for a right handle. A spring may maintain the disc in the default position, where the spring may be unloaded until the outer spindle rotates the disc to either the left or right home position, causing the spring to load. Once in the left or right home position, a catch may engage a recess in the disc to retain the disc in the respective home position and to counter the force exerted on the disc by the loaded spring. The catch may retain the disc in the home position but allow rotation of the disc in a range of motion to allow the handle to rotate and open the door. The loaded spring may also cause a handle attached to the door lock system to return to the set home position after pressure has been applied to rotate the handle and open the door.

[0097] In some embodiments, a handing assembly may include an adjustment lever attached to the end of the outer spindle to assist in rotating the outer spindle and disc from a default position to a home position. In some embodiments, the adjustment lever may include an arrow or other position marker to indicate which way to turn the spindle to set the appropriate handing. For example, in some embodiments the arrow or other position marker may indicate which direction to rotate the adjustment lever so that the position maker points to a door latch. In some embodiments, the adjustment lever may be removed and replaced with a handle before the handing has been set. In such embodiments, the handle may be employed to rotate the spindle to set the appropriate handing for the door lock system. In some embodiments, the adjustment lever may be removed and replaced with a handle after the handing has been set. In some embodiments, a handle may be initially attached to the outer spindle and no adjustment lever may be employed, as the present disclosure is not so limited.

[0098] The inventors have further recognized and appreciated designs for a toolless handing assembly that can reset the handing of a door lock system without taking apart the door lock system or otherwise replacing components of the door lock system. As discussed previously, in some embodiments the handing assembly may include a catch configured to engage a recess form in a disc when a spindle is moved to a home position from a default position. To reset the handing assembly, the catch may be released from the recess in the disc, causing the disc to rotate back to the default position due to the force of a spring. In some embodiments, the catch may be spring loaded to bias the catch toward the recess in the disc. To release the catch and reset the handing assembly, a user may simply move the spring-loaded catch from an engaged position to a disengaged position (e.g., pull up on the spring-loaded catch). In other embodiments, the handing assembly may include an opening in a lock portion backplate that the catch may protrude through. When the door lock system is installed on a door, a surface of the door may push against the catch to move the catch to an engaged position to engage the catch in the recess in the disc. The surface of the door may also hold the catch in the recess in the disc and inhibit the catch from moving to a disengaged position. Removing the door lock system from the door (or, in some embodiments,

a portion of the door lock system including at least the catch) may remove the force holding the catch in the engaged position, thereby allowing the catch to move to the disengaged position and allowing the spring to rotate the disc. Once the catch is in the disengaged position, the spring may automatically reset the handing assembly to the default position. The door lock system could then be reinstalled on the same or a new door with a different handing, if desired.

[0099] Door lock systems are not only left or right handed, but are also manufactured to fit doors of particular standard door thicknesses. Typically, door lock systems made for doors with one thickness may not be installed on doors with other thicknesses. Conventional door locks may be designed to meet security and wear standards and therefore may be made with rigid parts to comply with these standards, making it difficult to change the dimension of the lock system to fit doors of different thicknesses. Furthermore, a lock body installed in the door typically needs to be centered in the door to align with a latch. Accordingly, installing a conventional door lock system designed for one door thickness onto a door with a different door thickness may result in a poorly performing or non-functional door lock.

[0100] In view of the above, the inventors have recognized and appreciated designs for a door lock system that may automatically and reliably adjust to doors of different thicknesses. In this manner, the door lock system may be universal for typical door installation, no matter the typical door thickness. In particular, the inventors have appreciated the benefits of a door lock system including self-adjusting spindles that engage and position a lock body in a door. The spindles may each exert an opposing and equal force that centers the lock body within the door and align the lock body with a latch regardless of the door thickness.

[0101] In some embodiments, a door lock system may include a lock body positioned within an opening of a door. The lock body may include openings on each side of the lock body to receive a pair of lock spindles that position the lock body within the door. The openings may be symmetrically aligned on the lock body (e.g., the openings may be disposed on opposing sides of the lock body) and the lock spindles and the openings may be aligned along a common axis that is perpendicular to a plane of the door. The spindles may be slidably held within an exterior lock portion and an interior lock portion installed on an exterior and interior side of the door. The spindles may slide horizontally through an opening in a rear surface of the exterior and interior lock portions. In some embodiments, springs may bias the lock spindles toward the lock body through the openings in the rear surfaces. The springs may exert opposing forces on each of the lock spindles to position the lock body in the door. In some embodiments, the springs may have equal spring constants such that the springs exert approximately equal and opposing forces on each of the lock spindles to center the lock body in the door. In other embodiments, the springs may have unequal spring constants such that the springs exert unequal, opposing forces on each of the lock spindles to maintain the lock body in an off-centered alignment in the door, as the present disclosure is not so limited. The openings in the rear surface of the lock portions may include ridges that engage ledges on the lock spindles to prevent the springs from pushing the lock spindles completely through the openings.

[0102] Conventional handlesets in door lock systems include a trim plate that is mounted to an exterior side of a door and a handle (e.g., knob or lever) rotationally attached via a shank to a cylindrical spindle through an opening in the plate. The cylindrical spindle may engage an opening in a lock body inside the door. When the handle is rotated, the handle may rotate the shank and spindle about a center axis perpendicular to a plane of the door, and the lock body may convert the rotational motion into linear motion to retract a latch in the door and allow the door to be opened. Because of tolerances in each of the connections between the components and because of the mounting arrangement for the door lock system in the door, a handle may be able to shift and partially rotate without opening the door. Accordingly, such conventional arrangements may result in a loose (also referred to as “waggle”) handle. Furthermore, the shank and spindle typically have small diameters relative to their lengths along the center axis. Accordingly, the long, thin spindles

may not sufficiently stabilize the handle, and the handle may move or shift from the center axis, also resulting in such a loose handle.

[0103] In view of the above, the inventors have recognized and appreciated designs for a door lock system that efficiently and reliably translates torque from a handle to a lock body and reduces or eliminates unwanted movement of a handle. In some embodiments, rotational motion may be directly translated to a disc with a large diameter that retains the lock spindle in a spindle opening. The lock spindle and the spindle opening may have complementary non-circular shapes and sizes such that the lock spindle is coupled to the disc about the center axis. The spindle lock being coupled to the disc and the increased diameter of the disc more efficiently transmits torque through the lock spindle on a lock body when a handle is rotated, and better supports the handle along a center axis.

[0104] Electronic door lock systems may include data wires and power wires interconnecting various electrical components. The data wires may transmit information between an exterior and interior lock portion regarding the state of the system (e.g., unlocked, locked, access denied, access granted, etc.). The power wires may power operating components, such as an actuator that may actuate to lock and unlock the system. With electronic door lock systems, it may be beneficial to unlock the door from an exterior side. An exterior lock portion may include an input device for a user to present a credential. For example, the exterior lock portion may include a keypad to enter in an access code or a scanner for a user to scan in an access code (e.g., using an RFID card, fingerprint or other biometric identifier, smartphone, etc.). Once the credential is verified, the door lock system may automatically unlock or allow a user to manually unlock the system. Electronic door locks may be utilized in any of the embodiments described herein.

[0105] Typically, a valid electronic signal transmitted along the data wires is required to cause a processor to send power to the actuator to unlock the system (e.g., after presenting an authorized credential). However, if the power wires connected to the actuator are accessed externally (i.e., the door lock system is breached) then an alternate power source may be connected to the wires to actuate the actuator and unlock the system without proper credentials.

[0106] In view of the above, the inventors have recognized and appreciated designs for an electronic door lock system that includes a reinforcement area to protect power wires from being accessed during an attempted breach of the system. In the event an exterior lock portion has been damaged and/or parts of the lock portion have been removed, the power wires may remain protected inside a secondary housing, which may be formed of a durable material like metal (e.g., stainless steel). The secondary housing may be attached (e.g., back screwed) to a backplate that is mounted to a door by an interior lock portion. Accordingly, the secondary housing may not be removable from the backplate from the exterior side. In this manner, even if all other components of the exterior lock portion have been removed, the secondary housing may not be breached, and the power wires may remain protected inside the secondary housing.

[0107] In some embodiments, a door lock system may include a secondary housing to hold and protect the data and/or power wires that control the operating components. The secondary housing may include a cover with wings extending from sides of the cover. The wings may be attached to a backplate via screw holes inserted from the rear of the backplate. The screws may only be removed from the rear of the backplate. Thus, the cover may not be removed from the exterior side of the lock portion (i.e., the side facing away from the door). Accordingly, the components housed inside of the secondary housing may not be non-destructively accessible from the exterior side of a door.

[0108] The inventors have further recognized and appreciated designs for a door lock system that secures wiring within a secondary housing. In some embodiments, power wires may connect to an actuator that is also securely held within the secondary housing, but data wires may extend through an opening in the secondary housing to connect to an electronic component (e.g., light emitting diode array, credential reader, keypad, etc.) in the exterior lock portion outside the secondary housing. The power wires and the data wires may be connected as part of the same wiring loop

until they split to connect to their respective electric components. In some instances, an unauthorized user attempting to bypass the door lock system may attempt to access the power wires by pulling on the exposed data wires to also pull the power wires out of the secondary housing. Accordingly, in some embodiments, the wiring may be installed in the secondary housing by wrapping the wires around and compressing the wires between various ledges and ridges formed by the secondary housing to create a wire loop. Looping and compressing the wires into a loop may relieve any strain placed on the wires if someone were to pull on the exposed data wires. Specifically, the loop may inhibit an unauthorized user's ability to pull the power wires out of the secondary housing by applying force to the accessible data wires. In some embodiments, the secondary housing may include various ridges and ledges to compress, wrap, and pinch the data and power wires as they pass into the exterior lock portion from an opening in a metal backplate and travel through the secondary housing to their respective operating components. Thus, the door lock system provides a secure system that safeguards against attempts to bypass the electric locking components.

[0109] Door lock systems may include a mechanism to remove a door handle, such as in the event a user desires to replace the handle. For example, some handles may include a small opening to access a handle catch disposed inside the handle that secures the handle to a shank. The handle may be removed by inserting an object into the opening and moving the handle catch to disengage the catch from the handle. Once the handle is removed, however, the door lock security may be compromised. In many door lock systems, a key cylinder in the handle and shank may prevent the catch from being disengaged from the handle when the key cylinder is rotated to a locked state. The key cylinder may be shaped and positioned in the shank such that the catch may be moved only when the lock cylinder has been rotated to an unlocked state. When the key cylinder is in a locked state, however, the key cylinder may prevent the catch from being moved by someone attempting to breach the lock.

[0110] Some embodiments of door lock systems (whether electronic or not) may have handles that are key free, or may not include a key cylinder in the handle that can selectively block movement of a catch to prevent removal of the handle. Such embodiments are referred to as “keyless” cylinders hereinafter. In view of the above, the inventors have recognized and appreciated designs for a secure handle with a keyless cylinder that may be removed via an opening to access a handle catch that secures the handle to a shank. In some embodiments, the keyless cylinder may include a locking block disposed in the handle that is moveable between a locked state, which prevents a handle catch from being pushed in, and an unlocked state, which allows the handle catch to be pushed in to disengage the handle.

[0111] In some embodiments, the locking block may be spring loaded or otherwise biased in a first direction along a lock axis toward the door to a locked position. The locking block may only be moved in a second direction, opposite the first direction, to an unlocked state by pushing a lock spindle in the second direction. The lock spindle may exert a force on the locking block in the second direction and overcome the spring force to move the locking block to the unlocked position. The lock spindle may only be accessed from an inner side of a backplate of the exterior lock portion when the lock portion is removed from the door. Because the back plate is back screwed to the door from an interior side, the exterior lock portion may only be removed from an interior side of the door. A user needs to already have access to an interior side of the door to remove the lock portion from the door and push in the lock spindle to move the locking block to the second, unlocked position. Accordingly, only in this unlocked position, may an exterior handle be removed.

[0112] In some embodiments, the lock spindle is slidably disposed in a square opening of a spindle coupler and is spring loaded to be biased out of the lock portion in the second direction toward a door. Accordingly, a user trying to remove a handle would need to continuously hold the lock spindle in the pushed in position against the spring force in the second direction, and therefore would only have one hand to both insert an object into the handle opening to push in the handle

catch and pull off the handle. In view of the above, the inventors have recognized and appreciated designs for a lock spindle that can be held in the pushed in position. In some embodiments, the lock spindle may include notches on corners near a first end that, when the lock spindle is pushed in the second direction through the square opening, the notches line up with ridges in the opening of the spindle coupler. The ridges may allow the lock spindle to be rotated about the lock axis. In the rotated state, the notches may include ledges that engage a rear surface of the spindle coupler to hold the lock spindle in the pushed-in position along the lock axis. With the lock spindle held in the pushed in position, a user may use both hands to remove the exterior handle.

[0113] When exterior portions of door locks are installed, it is unlikely that the internal environment of those exterior portions are entirely isolated from the external environments. Air from the environment could enter the housing of the door lock from any gap in the housing, whether the gap was intentional or not. For example, air from the environment may enter from the inside of the door through door prep holes, from around the exterior housing through any gaps between housing components or between the housing and the door, from any gap formed between the housing and the handle extending from the housing, or from any other naturally formed gap or accidentally formed gap in the housing. Since the air within the housing is partially isolated from the environment, the internal temperature and humidity does not immediately change as the environment changes and instead slowly equilibrates with the environment as environmental air leaks into the housing.

[0114] In regions where temperature and humidity changes dramatically over the course of a day, when the environment warms up, hot and humid air can enter into the housing of a door lock, contacting the colder air within. Similarly, when the environment cools, cold and dry air can leak into the housing and contact warmer and more humid air within the housing. Due to the possibility of gas exchange between the inside and outside of the housing, without wishing to be limited to theory, the changing conditions within the housing can result in condensation forming within the housing. As one of skill in the art would understand, condensation making contact with either electrical or mechanical components of an electronic door lock system could lead to damage of the door lock system. Recognizing this possibility, the inventors have contemplated that electrical door lock systems could be improved.

[0115] In one embodiment, an electronic door lock system includes specifically designed gaskets and housing components, shaped such that the gaskets are compressed between portions of the door lock housing having a perimeter ridge that presses into the gasket, creating a seal around electrical and mechanical components to mitigate gas exchange or water flow between the inside of the housing and the outside of the housing.

[0116] For the purposes of this disclosure, the terms “inner” and “inward” refer to being closer to the door and the terms “outer” and “outward” refer to being further from the door. The terms “upper” and “upward” refer to the direction away from the ground, while the terms “lower” and “downward” refer to the direction pointing towards the ground. One of skill in the art should understand that although the embodiments herein are described as being in a certain orientation, the systems and devices described are not limited to the described orientation and could function and apply in different orientations as well. The side of the door facing the area to be secured will be referred to as the “interior,” and the side opposite the area to be secured will be referred to as the “exterior.”

[0117] It should be understood that unless otherwise differentiated, when air and/or water flow is referred to as entering or potentially entering the housing, or the exterior or interior portions of the door lock, unless otherwise differentiated, both refer to air and/or water penetrating beyond the surfaces of the door lock that are intended to contact the outside environment such that air and/or water enters the internal environment of the door lock.

[0118] In some embodiments, an electronic door lock system may include a first gasket in an exterior lock portion sized and shaped to match an entire surface of a circuit board disposed in the

exterior lock portion between the first gasket and an exterior housing. The gasket may cover a first side of the circuit board and include an L-shaped perimeter that wraps around a perimeter edge of the circuit board and partially onto a second side of the circuit board. An outer plate may be disposed between the first gasket and a front cover of the exterior lock portion. These components may be secured and tightened together via screws and screw holes such that the outer plate compresses the l-shaped perimeter of the first gasket against a ledge in the exterior housing that extends circumferentially around the entire perimeter of the circuit board. The ledge may include a triangular shaped ridge that presses into the L-shaped perimeter of the gasket to seal against entry of water and air.

[0119] The inventors have also contemplated that air and water could enter the mechanical area of the exterior lock portion through a possible gap between the door handle and the exterior escutcheon of the exterior lock portion. For example, an outer spindle or shank may extend through an opening in a front cover housing to receive a handle. Because air and water may leak in through this opening, the inventors have appreciated and recognized designs to mitigate air flow through this opening while still allowing the outer spindle to rotate to open a door. In some embodiments, the first gasket includes an opening with a beveled perimeter. The beveled perimeter may have an outer diameter smaller than an inner diameter and a diameter of an outer spindle such that the beveled perimeter pushes outward and compresses against a surface of the outer spindle, creating a seal around the outer spindle while still allowing the outer spindle to rotate within the opening to open a door.

[0120] In some embodiments, an electronic door lock system may include a second gasket disposed in an interior housing of an interior lock portion. The second gasket may cover a first side of a circuit board and include an L-shaped perimeter that surrounds a perimeter edge of the circuit board. An inner plate disposed between a back plate of the interior lock portion and a second side of the circuit board may compress the perimeter of the gasket against a wall in the interior housing. The wall may have a shape that matches the perimeter of the gasket, resulting in uniform compression around the gasket perimeter, and sealing the circuit board from entry of water and air. The wall may include a beveled edge that presses into the perimeter of the gasket, providing additional gasket sealing to further ensure that air and gas flow is obstructed between the compressing surfaces.

[0121] In some embodiments, the second gasket and/or the interior housing include a plurality of openings that could be designed to permit the passage of components from the electrical door lock system that are designed to extend into or through the gasket and/or a surface in the interior housing. For example, these components could include but are not limited to: fasteners to secure the housing, power and/or signal connections, and/or drive bars connecting to the latch. The inventors have also recognized that if the openings are not exactly the same size as the component that extends through the opening, a passage for air and water to enter portions of the door lock could be created. In these embodiments, the openings may include protruding beveled ledges that circumferentially surround the openings that compress into a surface of the gasket when the lock portion is assembled, mitigating air and water flow through these openings. Furthermore, an opening in the gasket may include a protruding rib that extends from the outer surface of the second gasket and circumferentially surround the opening. The protruding rib may press against a corresponding protruding ledge of the interior housing to form a seal when the lock portion is assembled.

[0122] Batteries in electronic door lock systems risk corrosion if exposed to moisture. The inventors have recognized and appreciated designs for sealing battery compartments from entry of water and air. In some embodiments, a battery compartment may be disposed on a slanted surface of an interior housing of an interior lock portion. The sloped surface may include one or more ribs that extend around the battery compartment. The interior housing may include a battery cover that slides up and down the interior housing to remove and attach the cover. The battery cover may

include an inner sloped surface that matches the sloped surface on the front cover such that the slanted surfaces are positioned next to each other when the cover is attached. A compressible insert may be disposed between the slanted surface such that when the battery cover is fully attached to the interior housing, the one or more ribs may press into the compressible insert to create a seal against water entry around the battery compartment. The sloped surfaces prevent the ribs from pressing into the compressible insert until the cover is fully attached to allow the cover to easily slide up and down to change the batteries.

[0123] The material for the first and second gaskets may be any suitable material that can compress and create a suitable seal. In one embodiment, the gasket is formed of a flexible material. In one embodiment, the gasket is formed from a rubber-like material. In one embodiment, the gasket is formed silicone rubber material. Plastic materials may also be used.

[0124] The gasket body may have a thickness of equal to or greater than approximately 0.5 mm, 0.75 mm, 1 mm, or 1.25 mm. The gasket body may have a thickness of less than or equal to approximately 1.5 mm, 1.75 mm, 2 mm, 2.5 mm, 3 mm. The materials for the compressible insert may be any suitable that can compress and create a suitable seal. In one embodiment, the compressible insert is made of foam. In one embodiment, the compressible insert may be made of a rubber-like material or a plastic material.

[0125] Turning to the figures, specific non-limiting embodiments are described in further detail. It should be understood that the various systems, components, features, and methods described relative to these embodiments may be used either individually and/or in any desired combination as the disclosure is not limited to only the specific embodiments described herein.

[0126] FIG. 1 illustrates a door lock system **100** installed on a door **102** in accordance with some embodiments. The door lock system **100** includes an exterior lock portion **104**, an exterior handle **106**, an interior lock portion **108**, an interior handle **110**, a lock body inside the door (see FIG. 10), and a lock latch **112**. In some embodiments as shown in FIG. 1, the door lock system **100** may be an electronic locking system. The embodiment of FIG. 1 illustrates a left-handed reverse lock with a door that swings open toward the exterior side. When the exterior handle **106** is rotated downward in a counterclockwise direction relative to a plane of the door, the lock body converts the rotational motion into linear motion to retract the lock latch **112** and allow the door **102** to be opened. The exterior handle **106** may include a lock cylinder **114** or other access entry system such as a keypad or device configured to receive an electronic credential or command that prevents the lock body from retracting the latch **112** until a key or other credential is presented. Similarly, the interior handle **110** may be rotated downward in a clockwise direction relative to the plane of the door to release the latch **112** to open the door **102**. In some embodiments, no credential may be required before the interior handle may be rotated to release the latch **112** to open the door **102**.

Handing Assembly

[0127] FIG. 2 illustrates an embodiment of the interior lock portion **108** without the interior handle **110**. In some embodiments, the state of the interior lock portion **108** in FIG. 2 may be a state in which the interior lock portion is initially installed on a door. In some embodiments, the interior lock portion **108** includes a handing assembly **200** to set the handing of the handle **110**. The handing assembly **200** may include an outer spindle **202** that extends through an opening **204** in the face of the interior lock portion **108**. In some embodiments the handing assembly may include an adjustment lever **206** attached to the outer spindle **202**. The handing assembly **200** may have a default position, such as with the adjustment lever **206** pointing upward as shown in FIG. 2, before the handing is set. Rotating the handing assembly **200** a set number of degrees, such as 90 degrees, about axis **10** may set the handle with either a left or right handing, depending on which way the tool **200** is rotated. axis **10** extends in a direction perpendicular to the lock portion and door. Once set, the handing assembly is in a home position. Depending on the direction the handing assembly is rotated, the handing assembly may be in a left home position or a right home position. As discussed in more detail below with respect to FIGS. 5 and 8A-8C, the adjustment tool may include

a catch **220** that locks the handing assembly **200** in a respective home position while allowing the handle **110** to rotate to open the lock latch **112**.

[0128] In some embodiments, the adjustment lever **206** may include an arrow indicating the door latch where the lock latch **112** is located on the edge of the door indicating which way to turn the handing assembly **200**. It should be noted that the adjustment lever **206** may be optional and not required to use to the adjustment tool. In some embodiments, the adjustment lever **206** may be discarded after setting the handing of the handle.

[0129] As shown in FIG. 3, the handing assembly **200** of an interior lock portion **108** on an interior side of a door **102** may be set in a right home position (e.g., the handle sticks out to the right when viewing an exterior of the door) and may be ready to receive a handle. A handle (e.g., a lever or knob) may be any type of door hardware that may be attached to the outer spindle **202**. As shown in FIG. 3, the adjustment lever **206** and outer spindle **202** have been rotated 90 degrees in a first (e.g., clockwise) direction relative to a plane of the door **102** about axis **10**. In some embodiments, the door lock system **100** may be shipped without interior or exterior handles **110**, **106**. The separate interior and/or exterior handles may be attached to the outer spindle **202** after setting the handing. The handing may be set as either left or right and may be reset as desired even after handles **106**, **110** are attached. Although the interior lock portion is illustrated in the figures, the same concepts apply to the exterior lock portion **104** for handing the exterior handle **106**.

[0130] FIG. 4 illustrates the handing assembly **200** attached to a backplate **208** of the interior lock portion **108** shown in FIG. 3, according to some embodiments. As shown in FIG. 4, the adjustment tool **200** may include a housing **210** with an opening **212** through which the outer spindle **202** extends. The opening **212** and outer spindle **202** may have complementary circular shapes such that the outer spindle **202** may rotate within opening **212** about axis **10**. The housing **210** may be round and have a perimeter wall **214** that extends from the backplate **208** in a direction along axis **10**. The housing **210** may also include screw holes **216** for attaching the adjustment tool to the backplate **208**.

[0131] FIG. 5 is an exploded perspective view of a handing assembly **200** attached to a backplate **208** of the interior lock portion shown in FIG. 3. As shown in FIGS. 4 and 5, in accordance with some embodiments, the housing **210** may include a catch holder **218** for pivotally retaining a catch **220** that, as explained below, holds the adjustment tool **200** in the home position when the initial handing is set. The catch holder **218** may extend radially from the perimeter wall **214** of the housing **210** along backplate **208**. The catch holder **218** may include two walls **222** that extend along the perimeter wall **214** with pin holes **226** for pivotally holding the catch **220** via pin **224**. Pin **224** may be integrally formed with the catch **220** or may extend through an opening in the catch **220**. As shown in the embodiment of FIG. 5, the perimeter wall **214** may have a slot **228** positioned between walls **222** for allowing a first end **230** of the catch **220** to pivot into the housing **210**. In some embodiments, the catch holder **218** and catch **220** may be held completely within the housing **210** and not extend from the housing **210**.

[0132] In some embodiments as shown in FIGS. 4 and 5, the backplate **208** may include an opening **234** that allows a second end **232** of the catch **220**, opposite the first end **230**, to extend through the back of the interior lock portion **108** (for example, see FIG. 10). In some embodiments, when the lock portion is installed on a door **102**, a door surface may contact the catch and force the catch **220** to pivot away from the door surface such that the first end **230** of the catch **220** pivots into the housing slot **228** to engage a disc **240** (i.e., an engaged position), as discussed further below. In some embodiments, a spring (not shown) may bias the first end **230** of the catch **220** into the housing slot **228**. That is, the spring may bias the catch from a disengaged position toward an engaged position.

[0133] FIG. 5 is an expanded perspective view of the handing assembly **200** of the interior lock portion **108**. As shown in FIG. 5, the handing assembly **200** may include housing **210** attached to backplate **208** and outer cover **236**. The handing assembly also includes an adjustment lever **206**.

The handing assembly cooperates with an outer spindle **202** that extends through opening **212** in the housing. The adjustment lever **206** attaches to one end of the outer spindle. A disc **240** is attached to the other end outer spindle **202**, and a spring **250** is positioned between the outer spindle **202** and disc **240**. A catch **220** is operatively connected to the spindle **202**. The outer cover **236** may be attached to a front face of interior lock portion **108** (not shown in FIG. 5) to provide structural integrity and alignment. The outer cover **236** may include screw holes **237** for screws to attach the outer cover **236** to the front face of the lock portion, and the housing **210** may have larger diameter holes **238** to accommodate screw heads of the screws to allow the outer cover **236** to lie flush on the housing **210**. In some embodiments the handing assembly may not include an outer cover **236**.

[0134] FIG. 6 shows a perspective view of the outer spindle **202** and disc **240** shown in FIG. 5. As shown in FIGS. 5 and 6, in some embodiments, the outer spindle **202** may include a disc **240** at one end that is perpendicular to the outer spindle **202**. The outer spindle **202** and disc **240** may be integrally formed or may be two separate pieces directly connected together such that they rotate as one piece. The housing **210** may be positioned over disc **240** and the outer spindle **202** may extend through opening **212** of the housing **210**. Outer spindle **202** and disc **240** may be centered on axis **10** and rotate together about axis **10** within opening **212** of the housing **210**. In some embodiments, disc **240** may include a perimeter wall **242** that extends toward outer spindle **202** in a direction parallel to axis **10**. The disc wall **242** may include elongated recesses **244** and **246** along its outer edge. As will be discussed further below, the elongated recesses **244** are configured to receive a catch to set the handing of a door lock system. The disc wall **242** may also include a ledge **248** attached or integrally formed on an inside edge of the wall.

[0135] In some embodiments, a torsion spring (see FIGS. 5 and 8A-8C) may be positioned around the outer spindle **202** within disc wall **242**. The torsion spring **250** may include ends **252**, **254** that extend radially from a main circular body of the spring. The ends **252**, **254** may contact the ledge **248** on disc wall **242**. When the outer spindle **202** and disc **240** rotate, as explained more fully below with reference to FIGS. 8A-8C, the ledge **248** may contact and force an end **252**, **254** of the torsion spring **250** to rotate with the ledge **248**.

[0136] As shown in the embodiment of FIG. 7, the housing **210** may include a protrusion **260** that extends from an inner surface of the housing **210**. The inner surface of the housing **210** may be parallel to a plane of the door and the protrusion may extend perpendicular to the plane of the door. The protrusion **260** may extend a sufficient distance from the inner surface such that when the housing **210** is attached to the backplate **208**, the protrusion **260** may contact and restrict rotation of an end **252**, **254** of the torsion spring **250**.

[0137] FIGS. 8A-8C illustrate how the handing assembly **200** sets the handing of handle **110** by rotating the outer spindle **202** and disc **240**. When the handing assembly **200** is in the default position, as shown in FIG. 8A, a ledge **248** of disc **240** may be located at a bottom position below the protrusion **260** of the housing **210**. The ends **252**, **254** of torsion spring **250** may be positioned on either side of ledge **248** and protrusion **260** and the torsion spring **250** may be unloaded. The catch **220** may be pivoted up and away from the disc **240** in a disengaged position. In some embodiments, the catch **220** may be biased toward the disc **240** (e.g., by a spring, door surface, etc.).

[0138] As shown in FIG. 8B, the handing assembly **200** may be set to a right home position (e.g., the handle points to the right when viewing an exterior of a door), according to some embodiments. The outer spindle **202** and disc **240** may be rotated 90 degrees in a first direction (e.g., clockwise) relative to the position shown in FIG. 8A. Ledge **248**, rotating with disc **240**, may contact end **254** of torsion spring **250**, forcing the end **254** to rotate with the ledge **248**. The protrusion **260** on the housing **210** may restrain the other end **252** while ledge **248** rotates and pulls end **254** away from end **252**, causing the torsion spring **250** to load. The loaded torsion spring **250** may bias the disc **240** in a second direction (e.g., counterclockwise), opposite the first direction, back to the initial

default position.

[0139] As shown in FIG. 8B, once the disc **240** has been rotated to the right home position and spring **250** has been loaded (as shown by arrow “R”), catch **220** may pivot down and engage recess **246** at edge **258** in an engaged position to hold the disc **240** in the right home position against the torsional force of spring **250**. The catch **220** may be urged forward toward the disc **240** due to a door surface applying force to a back end of the catch when the lock portion is installed on the door. In some embodiments, a spring may bias the catch **220** to engage edge **258**, which may supplement or replace the force applied by the door surface. In some embodiments, once the handing is set to the right home position, a handle may then be attached to the outer spindle **202**. Turning the handle in the first direction (e.g., clockwise) may rotate the disc **240** and cause the lock body to release latch **112** and allow door **102** to open. While disc **240** rotates, the catch **220** may slide along the elongated recess **246**. The spring **250** may cause the handle **110** to return to the home position after the handle is rotated and pressure is released.

[0140] In some embodiments, from the state shown in FIG. 8B the catch **220** may be lifted and pivoted away from disc **240** to a disengaged position to release the disc **240** and reset the handing assembly **200** to the default position. The spring **250** may return and maintain the disc **240** at the default position shown in FIG. 8A. In some embodiments, the handing assembly **200** may be reset even after a handle is installed on the outer spindle.

[0141] As shown in FIG. 8C, the handing assembly **200** may be set to a left home position (e.g., handle points to the left when viewing an exterior of the door), in accordance with some embodiments. The outer spindle **202** and disc **240** may be rotated 90 degrees in the second direction (e.g., counterclockwise, as shown by arrow “L”) relative to the position shown in FIG. 8A. Ledge **248**, rotating with disc **240**, may contact end **252** of torsion spring **250**, forcing the ends **252** to rotate with the ledge **248**. The protrusion **260** on the housing **210** may restrain the other end **254** while ledge **248** rotates and pulls end **252** away from end **254**, causing the torsion spring **250** to load. The loaded torsion spring **250** may bias the disc **240** in the first direction, opposite the second direction, back to the initial default position.

[0142] Once disc **240** has been rotated to the left home position and spring **250** has been loaded, catch **220** may pivot and engage recess **244** at ledge **256** in an engaged position to hold the disc **240** in the left home position against the torsional force of spring **250**. A handle may be attached to the outer spindle **202** if a handle has not already been attached. Turning the handle in the second direction relative to the position shown in FIG. 8A may rotate disc **240** and cause the lock body to release latch **112** and allow door **102** to open. While disc **240** rotates, the catch **220** may slide along the elongated recess **244**. The spring **250** may cause the handle to return to the home position after the door has been opened and the handle is released.

[0143] It should be noted that the torsion spring **250** may bias the disc **240** to the default position from either the left or right home position. In addition, when in the left or right home positions (e.g., with the catch **220** engaged with a recess **244**, **246** of disc **240**), the same torsion spring **250** may also bias the disc **240** to the left and right home positions after the handle has been rotated to open the door. Thus, the torsion spring may bias the disc **240** to the default position (catch **220** not engaged) or to a home position (catch **220** engaged with disc) depending on whether the catch **220** is engaged with the disc.

[0144] FIG. 9 is a flowchart for a method of setting and resetting a handing assembly in accordance with some embodiments. In step **900**, the handing assembly is in the default position and the torsion spring is unloaded. In this default position, the adjustment lever or handle may be pointing in an upward position relative to the door. The handing assembly may be set as either left or right handed depending on the desired or required direction of door swing.

[0145] In step **902**, the outer spindle of handing assembly may be rotated in a first direction about a center axis until the handing assembly reaches a home position. In some embodiments, the outer spindle is rotated 90 degrees, but the angular extent may vary depending on the desired handle and

rotational motion required to release the latch. The first direction may be either clockwise or counterclockwise relative to a plane of the door. As the outer spindle rotates, the disc attached to outer spindle may also rotate and cause the torsion spring to load, as described above with reference to FIGS. **8A-8C**. Once in the home position, in step **904**, the catch may engage a recess within the disc to hold the disc in the rotated position against the torsional force of the torsion spring. The handing assembly may now be in a first home position. The first home position may be a right or left home position.

[0146] Optionally, the handing may be reset or reconfigured even after the handing assembly **200** has been set in the first home position. To reset the handing, in step **906**, the catch may be released from the handing assembly. Without the catch countering the force of the loaded torsion spring, the spring may cause the handing assembly to rotate back to the default position. The catch may be released by lifting it out of the recess in the disc. In some embodiments, the catch automatically releases from the disc when the lock portion is removed from the door, as the door surface no longer pushes the catch forward into the disc recess.

[0147] When in the default position, the adjustment lever may again be pointing upwards. To reset the handing assembly, in step **908**, the outer spindle of the handing assembly may be rotated in a second direction about the center axis. The rotation of disc may cause the torsion spring to load, as described above with reference to FIGS. **8A-8C**. In step **910**, the catch may engage a recess in the disc and lock the handing assembly in the second home position. It should be noted that steps **906** through **910** are optional and not required to set the initial handing of the handing assembly.

Self-Adjusting Spindles & Waggle Reduction

[0148] FIG. **10** is an exploded view of an embodiment of a door lock system **100** including a lock body **400**, an exterior lock portion **104**, and an interior lock portion **108**. According to the embodiment of FIG. **10**, the door lock system is configured to fit a variety of door thicknesses. In particular, as discussed further below, the exterior lock portion and interior lock portion are configured to align and center the lock body over a range of door thicknesses while maintaining the ability to transmit torque to the lock body.

[0149] As shown in FIG. **10**, a backplate **308** of the exterior lock portion **104** may include rods **402** that extend from the backplate **308** in a direction perpendicular to the backplate **308**. A backplate **208** of the interior lock portion **108** may have pins **404** that extend from the backplate **208** in a direction perpendicular to the backplate **208** and aligned to mate with the rods **402** of the exterior lock portion **104** when the door lock system **100** is installed on a door. When installing the door lock system **100** on a door (see FIG. **11**), the rods **402** and pins **404** may be connected through openings in the door (e.g., cylindrical holes perpendicular to a plane of the door). In the embodiment of FIG. **10**, the pins **404** are received within the rods **402**. The rods **402** and pins **404** may assist in aligning and stabilizing the exterior lock portion **104** and interior lock portion **108** on the door **102**. In particular, the rods **402** and pins **404** may prevent relative movement of the interior lock portion **108** and exterior lock portion **104** in a plane parallel to a plane of a door. In other embodiments, an exterior lock portion **104** may have pins **404** that are received in rods **402** in an interior lock portion **108**, as the present disclosure is not so limited. The pins **404** may slide within rods **402** to allow the interior lock portion **108** to move relative to the exterior lock portion **104** along axis **10** (e.g., perpendicular to a plane of a door) such that the door lock system **100** may be installed on doors of different thicknesses. In some embodiments, the pins **404** may be screws configured to threadedly engage the rods **402** to adjust the relative spacing between the interior lock portion **108** and the exterior lock portion **104**.

[0150] In some embodiments, an exterior lock spindle **430** may extend through a first backplate opening **432** in backplate **308** of the exterior lock portion **104**. The exterior lock spindle **430** may enter a first opening **434** in a first side of the lock body **400**. The exterior lock spindle **430** and the first opening **434** may have complementary shapes and be sized to create a snug fit, such that torque may be transmitted between the exterior lock spindle and the first opening **434**. In some

embodiments as shown in FIG. 10, the exterior lock spindle 430 and the first opening 434 have complementary square shapes. Of course, any shape may be employed, including, but not limited to, a spline and a D-shape. Similar to the exterior lock spindle 430, an interior lock spindle 420 may extend through a second backplate opening 422 in a backplate 208 of the interior lock portion 108 and enter a second opening (not shown) in a second side of the lock body 400, opposite the first side of the lock body along axis 10 (e.g., perpendicular to a door). The second opening may also be shaped and sized to create a snug fit with the interior spindle 420, such that torque may be transmitted between the interior lock spindle 420 and the second opening. In some embodiments as shown in FIG. 10, the interior lock spindle 420 and the second opening in the lock body 400 have complementary square shapes. Of course, any shape may be employed, including, but not limited to, a spline and a D-shape. As will be discussed further below, the exterior lock spindle 430 and the interior lock spindle 420 may assist in supporting and centering the lock body in an opening in a door (not shown) when installed on the door. Additionally, the exterior spindle 430 and interior spindle 420 are configured to transmit torque to the lock body to selectively retract a latch 112.

[0151] In some embodiments, the backplate 308 of the exterior lock portion 104 may include a rail 440 that extends from the backplate 308 in a direction perpendicular to the backplate 308. A rail 440 may alternatively, or additionally, extend from the backplate 208 of the interior lock portion 108. The rail 440 may enter a channel 442 in the lock body 400. The channel 442 may be sized and shaped to create a snug fit while allowing the rail 440 to slide within channel 442. That is, the rail 440 may allow the lock body 400 to slide along the rail along axis 10 (e.g., perpendicular to a plane of a door) while inhibiting movement of the lock body in any other direction (e.g., parallel to a plane of a door). The rail 440 may extend a sufficient distance from the backplate 308 to enter the channel 442 while accommodating different door thicknesses. As shown in FIG. 10, the rail 440 and channel 442 are offset from the axis 10 and the first opening 434 and the second opening in the lock body 400, such that the rail 440 may resist rotation of the lock body 400 when torque is transmitted through the first opening 434 and second opening in the lock body. In some embodiments, the channel 442 may extend through an entire width of the lock body 400 along a direction parallel to axis 10. In such embodiments, the lock body 400 may be reversible (i.e., rotated 180 degrees about axis 10, perpendicular to the door). The lock body 400 may be symmetrical such that the first opening 434 on the first side of the lock body and the second opening on the second side of the lock body may receive either the exterior spindle 430 or the interior spindle 420. Thus, the door lock system 100 may provide a universal door lock system 100 that may be either right-handed or left-handed, simply by reversing the direction of the lock body 400 in the door, and by setting the adjustment tool for the exterior lock portion 104 and the interior lock portion 108 with the appropriate handing, as described above.

[0152] FIG. 11 illustrates a schematic of a door lock system 100 installed on a door 102. In some embodiments, the lock body 400 may be positioned in an opening (not shown) in the door 102 between the interior lock portion 104 and the interior lock portion 108 aligned along axis 10. As will be described below, an exterior spindle 430 and an interior spindle 420 may position and hold the lock body 400 in line with a center plane 20 of door 102, which is centered between an exterior and interior surface of the door 102. As shown in FIG. 11, pins 404 of the interior lock portion 108 are slidably received within rods 402 of the exterior lock portion 104. As shown in FIG. 11, a rail 440 may be slidably received in an opening in the lock body 400. In the arrangement of FIG. 11, the rail 440 may extend into a first side of the lock body and through an entire width of the lock body and out a second side of the lock body 400. In other arrangements, the rail may not extend through an entire width of the lock body. The rail 440 may stabilize and align the lock body 400 once the door lock system 100 is installed on the door, preventing the lock body 400 from rotating while still allowing the lock body 400 to slide in a direction parallel to axis 10 to accommodate different door thicknesses.

[0153] In some embodiments, the door lock system 100 may be installed on doors of various

thicknesses. In some embodiments, the door may have a thickness that is greater than or equal to $1\frac{3}{8}$, $1\frac{3}{4}$, or 2 inches. In some embodiments, a door may have a thickness that is less than or equal to $2\frac{3}{4}$, $2\frac{1}{4}$, or 2 inches. Any suitable thickness of the above-references ranges is possible (e.g., the door may have a thickness greater than or equal to $1\frac{3}{8}$ and less than or equal to $2\frac{1}{4}$). In some embodiments, rods **402** may be equal to or less than $1\frac{3}{8}$ inches in length. When installed on doors that are $1\frac{3}{8}$ inch thick, the rods may extend across the entire thickness of the door and pins **404** will be received entirely within rods **402**. Similarly, rail **440** may also be equal to or less than $1\frac{3}{8}$ inches and may extend through the entire width of the lock body **400**. To accommodate thicker doors, the rods **402** and pins **404** may slide apart along axis **10**, exposing a section of the pins **404**, as shown in FIG. **11**.

[0154] According to the embodiment of FIG. **11** and as described further below, the interior spindle **420** and the exterior spindle **430** may be spring loaded and extend into the lock body. In particular, the springs urge the exterior spindle and the interior spindle into engagement with the lock body **400** regardless of the thickness of the door. The springs associated with the interior spindle **430** and the exterior spindle **420** may have equal spring constants, such that the force applied by the exterior spindle and interior spindle to the lock body centers the lock body in the door **102** (e.g., aligns the lock body with plane **20**). Thus, the door lock system **100** may be installed on doors of varying thicknesses and handing requirements. Of course, it should be noted that features related to the universal fit of the door lock system on doors of different thicknesses may be employed in some embodiments without features related to the universal fit of the door lock system on doors of different handing. Likewise, in some embodiments a door lock system including universal handing features as described herein may be employed without features related to features for universal thickness fit, as the present disclosure is not so limited

[0155] Once installed, the door lock system **100** may be operated by rotating the outer spindle **202** on either the exterior lock portion **104** to rotate exterior spindle **430** or by rotating outer spindle **202** on the interior lock portion **108** to rotate interior spindle **420**. The lock body **400** may translate the rotational motion of the exterior spindle **430** or the interior spindle **420** into linear motion to retract a lock latch **112** (see FIG. **10**) and allow the door **102** to open.

[0156] The components within the interior lock portion **108** between the outer spindle **202** and an interior lock spindle **420** according to some embodiments will be described with reference to FIGS. **12-14** below. The components within the exterior lock portion **104** between the outer spindle **302** and an exterior lock spindle **430** according to some embodiments will be described with reference to FIGS. **15-19** below. It should be noted that the interior lock portion **108** may not include all of the components of the exterior lock portion **104** (e.g., in some embodiments, the interior lock portion may not include components required to prevent the interior handle **110** from rotating). It should also be noted that the components described below in FIGS. **12-19**, although described specific to an interior or exterior lock portion, may be included in either the interior or exterior lock portion, and are not limited to a specific lock portion.

[0157] FIG. **12** is an expanded rear perspective view of transmission components in an interior lock portion aligned along axis **10** and that allow a handle to be employed to retract a latch of a lock body. In some embodiments as shown in FIG. **12**, the transmission components include a handle **110**, a housing **210**, and an outer spindle **202** attached to a disc **240**. The outer spindle **202** may extend through an opening **212** in the housing **210** and receive the handle **110**. In some embodiments, an optional adjustment lever **206** may be attached to the outer spindle **202** see FIGS. **3-5**). The adjustment lever **206** may be removed after the handing of the handing assembly has been set and the handle **110** attached, as described above.

[0158] In some embodiments as shown in FIG. **12**, the transmission components include a spindle holder **450**, a spring **470**, and an interior lock spindle **420**. The interior lock spindle **420** may be received within opening **452** of the spindle holder **450**. As further described below, the spring **470** may bias the interior lock spindle **420** out of the opening **452** along axis **10** into a through hole **406**

of the disc **240**. In some embodiments as shown in FIG. **12**, the spring **470** may be positioned on a protrusion **454** in opening **452** that also centers and stabilizes the spring **470**. The spindle holder **450** may be received in an opening **458** of the outer spindle **302**. The opening **458** may extend through the outer spindle **202** to the through hole **406** in the disc **240**, creating an elongated channel through the outer spindle **202** and disc **240**.

[0159] FIG. **13** is an exploded, rear perspective view of the interior lock spindle **420**, the outer spindle **202**, and the disc **240** of FIG. **12**. As noted above, the spring **470** and interior lock spindle **420** may be received within opening **452** of the spindle holder **450** and the spring **470** may bias the interior lock spindle **420** out of the opening **452** into the through hole **406** of the disc **240**. The through hole **406** may have a depth along axis **10** and extend from a rear surface **456** of the disc **240**, forming a round edge **460** around through hole **406**. The through hole **406** may be sized and shaped to complement the size and shape of the exterior spindle **420**. The disc **240** may stabilize the interior lock spindle **420** (e.g., prevent rotation about axis **10** relative to the disc **240**) while allowing the interior lock spindle **420** to slide horizontally within the through hole **406** along axis **10**. In some embodiments, the exterior spindle **420** may have a cross-section, parallel to a plane of disc **240**, that is square, or square with tapered corners, or otherwise shaped to engage the through hole **406** to apply a torque to the disc **240**.

[0160] In some embodiments, a front surface of the interior lock spindle **420** may include one or more ledges **464**. As shown in FIG. **13**, in some embodiments a ledge **464** may extend radially from each tapered corner **462** of the interior lock spindle **420**, when viewing a cross section of the front surface of the interior lock spindle **420**. An outside circumference of the ledges **464** may complement an inside circumference of the opening **452** of the spindle holder **450**, and the ledges **464** may contact and slide along the inside circumference of opening **452**, helping position and stabilize the interior lock spindle **420** in the spindle holder **450**.

[0161] In some embodiments, the spring **470** may be compressed between a surface of the opening **452** in the spindle holder **450** and a front surface of the interior lock spindle **420**. The spring **470** may bias the interior lock spindle **420** out of the opening **452** and through the through hole **406** of the disc **240**. To prevent the interior lock spindle **420** from being pushed completely through the through hole **406**, the through hole **406** may include one or more ribs **466** positioned around the circumference of the through hole **406** to catch the ledges **464** on the interior lock spindle **420**. As shown in FIG. **13**, the ribs **466** may be positioned at each corner, when viewing a cross section of a rear surface of the through hole **406**. It should be noted that the ledge **464** and rib **466** may extend in varying angular extents around a circumference of the interior lock spindle **420** and/or through hole **406**.

[0162] FIG. **14** shows a side cross-sectional view of the components of FIGS. **12-13** taken along axis **10**. In some embodiments, the disc **240** may be positioned adjacent to a backplate (not shown in FIG. **14**) of the interior lock portion. As shown in FIG. **14**, the disc **240** may hold and stabilize an interior lock spindle **420** along a length of axis **10**.

[0163] In some embodiments, a housing **210** may be attached to the backplate **208** (e.g., using screws) and the housing **210** and the backplate may hold and support the outer spindle **202** and disc **240**, spindle holder **450**, spring **470**, and interior lock spindle **430**. In some embodiments, the outer spindle **202**, disc **240**, spindle holder **450**, spring **470**, and interior lock spindle **420** may be at least partially contained between the housing **210** and the backplate **208**.

[0164] As shown in FIG. **14**, the handle **110** may be installed on the outer spindle **202** and the outer spindle **202** may be held within the handle **110**. Rotating the handle **110** may rotate the outer spindle **202** and correspondingly the disc **240**. Torque applied to the handle **110** may be directly translated to the disc **240** through the outer spindle **202**. The disc **240** may torque the lock spindle **420** directly to turn the lock spindle **420** in the second opening (opposite opening **434**) of the lock body **400** to release the latch **112** (see FIG. **10**). The disc **240** may have a larger diameter than a diameter of the outer spindle **202**. In some embodiments, a ratio of the diameter of the disc **240** to

the diameter of the outer spindle may be at least 1.5, 1.75, 2, or 2.5.

[0165] As shown in FIG. 14, the spring 470 may compress against a surface of an opening 452 in the spindle holder 450 on one end and against a front surface of the interior lock spindle 420 on a second end opposite the first end, biasing the interior lock spindle 420 out of the opening 452 and through the through hole 406 of the disc 240. Ribs 466 of the disc 240 may catch ledges 464 on the front surface of the interior lock spindle 420 to prevent the spring 470 from pushing the interior lock spindle 420 completely through the through hole 406. A rear side of the interior lock spindle 420, opposite the spring 470, may enter an opening in a lock body and exert a force against the lock body in a direction along axis 10.

[0166] FIG. 15 is an expanded perspective view of transmission components in an exterior lock portion aligned along axis 10 and that allow a handle to selectively retract a latch of a lock body. In some embodiments as shown in FIG. 15, the transmission components include an adjustment lever 306, a housing 310, and an outer spindle 302 attached to a disc 340. The outer spindle 302 may extend through an opening 312 in the housing 310 and receive the adjustment lever 306. In some embodiments, the adjustment lever 306 may be attached to a lock cylinder 114, and the lock cylinder 114 may be received in the outer spindle 302. In some embodiments, the adjustment lever 306 may be optional, or may be removed after the handling of the handling assembly has been set, as described above. In some embodiments, when the adjustment lever 306 is removed another handle (e.g., a lever) may be attached to the outer spindle 302. The lock cylinder 114 may include a driver 528 extending from a rear end of the lock cylinder 114 that may be received in a front opening 526 of a spindle holder 550. The driver 528 may be rotated about axis 10 when a key (not shown) is inserted into the lock cylinder and rotated. As described further below, according to some embodiments, the driver 528 may rotate the spindle holder 550 to lock and unlock the door lock system 100.

[0167] FIG. 16 is an exploded rear perspective view of the components shown in FIG. 15. As shown in FIG. 16, the spindle holder 550 may be inserted into an opening 558 in a rear surface 556 of disc 340 opposite the outer spindle 302. The opening 558 may extend through the disc 340 to the outer spindle 302, creating an elongated channel through the outer spindle 302 and disc 340. In such an embodiment, the lock cylinder 114 may be inserted into a front side of the outer spindle 302 and the spindle holder 550 may be inserted into the opening 558 on the rear side of disc 340 such that the driver 528 of the lock cylinder 114 may be inserted into the opening 526 of the spindle holder 550 (see FIG. 15). In some embodiments, the spindle holder 550 may include a plate 568 that extends radially from a rear end of the spindle holder 550 parallel to a plane of disc 340. The plate 568 may be round as shown in FIG. 16. The spindle holder 550 may be inserted into opening 558 of disc 340 such that plate 568 may lie flush against the rear surface of disc 340. The spindle holder 550 may include an opening 552 in a surface opposite the disc 340. In some embodiments the spindle holder opening 552 may extend only partially within spindle holder 550 and may not connect with the opening 526 (see FIG. 15) on the opposite side of the spindle holder 550.

[0168] In some embodiments as shown in FIGS. 15-16, the transmission components include a spring 570 and an exterior lock spindle 430 that may be received within opening 552 of the spindle holder 550. As further described below, the spring 570 may bias the exterior spindle 430 out of the opening 552 along axis 10 into a through hole 506 of a spindle coupler 500. The spindle coupler 500 may be round and positioned parallel to a plane of disc 340. In some embodiments the spindle coupler may be a disc 501.

[0169] In some embodiments, a slider 520 may be positioned between the spindle holder 550 and the spindle coupler 500, on a rear side of the spindle holder 550 against a surface of plate 568 opposite disc 340. The slider may move in a downward and upward direction parallel to a plane of the door to put the door lock system in a locked or unlocked state. The slider 520 may include a projection 522 that extends from a top portion of the slider 520. The projection 522 may be positioned within a groove 514 on a top portion of a front surface 502 of the spindle coupler 500,

such that rotation of the spindle coupler correspondingly rotates the slider 520. In a downward position, projection 522 may engage a notch 516 in the perimeter wall 342 of disc 340. Accordingly, in the downward position, the slider 520 may transmit torque between the disc 340 and the spindle coupler 500. In an upward position, the projection 522 does not engage the disc 340 and clears the notch 516, such that no torque may be transmitted between the disc and the spindle coupler 500. Accordingly, in such a position, the slider mechanically isolates the spindle coupler from the disc 340 and an exterior handle. If a user turns the exterior handle when the slider is in the upward position, the exterior handle may turn without driving the spindle coupler 500, thereby ensuring the door lock system remains locked. In some embodiments as shown in FIG. 16, the slider 520 may include one or more tabs 524 on a bottom portion of the slider to engage in the insert 508 (see FIG. 15) on a front surface 502 of the spindle coupler 500 when the slider 520 is in the downward position. Such an embodiment may balance torque applied by the projection 522, as torque is applied from the spindle coupler 500 to the slider 520 in two locations opposite one another relative to axis 10.

[0170] In some embodiments, an actuator (for example, see FIGS. 22A-22B) above the projection 522 may actuate a rod to exert a force against the projection 522 and move the slider 520 within the groove 514 to the downward position. When the actuator is not exerting any force on projection 522, a spring (not shown) may bias the slider 520 upwards toward the upward position such that the projection 522 does not engage the notch 516 such that the disc 340 and the spindle coupler 500 are not rotationally fixed together and the door lock system is locked.

[0171] In some embodiments as shown in FIGS. 15-17, the lock cylinder 114 may move the slider 520 between the unlocked (e.g., downward) position and locked (e.g., upward) positions. In some embodiments, the slider 520 may have an internal perimeter that surrounds the opening 552 on the spindle holder 550. The opening 552 may include symmetrical cams 554 that extend from a rear surface of the plate 568 in a direction along axis 10. The cams 554 may match a shape of the internal perimeter of slider 520 (see FIG. 17). Of course, while a particular arrangement is shown in the present embodiment, in other embodiments the internal perimeter and cams may have any suitable shape, as the present disclosure is not so limited. As noted above, the slider 520 may be spring loaded and biased toward an upward, locked position (e.g., when cams are aligned horizontally, as shown in FIG. 17). When the lock cylinder 114 is rotated to an unlocked position, the spindle holder may also be rotated (e.g., by the driver 528) and the cams 554 on the spindle holder 550 may cam the slider 520 to the downward, unlocked position. The lock cylinder 114 may hold the slider 520 in the downward or upward position until the handle 304 rotates the spindle coupler 500. In some embodiments, the driver 528 of the lock cylinder may be used to drive the spindle coupler 500 with the cams 554 of the spindle holder 550 once the slider 520 is in the downward position.

[0172] FIG. 17 is an enlarged, exploded rear perspective view of the spindle holder 550, slider 520, spring 570, exterior lock spindle 430, and spindle coupler 500 of FIG. 16. As noted above, the spring 570 and exterior spindle 430 may be received within opening 552 of the spindle holder 550 and the spring 570 may bias the exterior spindle 430 out of the opening 552 into the through hole 506 of the spindle coupler 500. The through hole 506 may have a depth along axis 10 and extend from a rear surface 510 of the spindle coupler 500, forming a round edge 560 around through hole 506. The through hole 506 may be sized and shaped to complement the size and shape of the exterior spindle 430. The spindle coupler 500 may stabilize the exterior lock spindle 430 (i.e., prevent rotation about or relative to axis 10) while allowing the exterior spindle 430 to slide horizontally within the through hole 506 along axis 10. In some embodiments, the exterior spindle 430 may have a cross-section, parallel to a plane of disc 340, that is square, or square with tapered corners, or otherwise shaped to engage the through hole 506 to apply a rotational force to the spindle coupler 500. Of course, any suitable shape for the cross-section of the spindle may be employed that allows the spindle to transmit torque to the spindle coupler 500, as the present

disclosure is not so limited.

[0173] In some embodiments, a front surface of the exterior spindle **430** may include one or more ledges **564**. As shown in FIG. **17**, in some embodiments a ledge **564** may extend radially from each tapered corner **562** of the exterior spindle **430**, when viewing a cross section of the front surface of the exterior spindle **430**. An outside circumference of the ledges **564** may complement an inside circumference of the opening **552** of the spindle holder **550**, and the ledges **564** may contact and slide along the inside circumference of opening **552**, helping position and stabilize the exterior lock spindle **430** in the spindle holder **550**.

[0174] In some embodiments, the spring **570** may be compressed between a surface of the opening **552** in the spindle holder **550** and a front surface of the exterior spindle **430**. The spring may bias the exterior spindle **430** out of the opening **552** and through the through hole **506** of the spindle coupler **500**. To prevent the exterior spindle **430** from being pushed completely through the through hole **506**, the through hole **506** may include one or more ribs **566** positioned around the circumference of the through hole **506** to catch the ledges **564** on the exterior spindle **430**. As shown in FIG. **17**, the ribs **566** may be positioned at each corner, when viewing a cross section of a rear surface of the through hole **506**. It should be noted that the ledge **564** and rib **566** may extend in varying angular extents around a circumference of the exterior spindle **430** and/or through hole **506**.

[0175] In some embodiments, the spindle coupler **500** may include one or more tabs **512** extending from a rear surface **510** that are spaced a radial distance from axis **10**. The tabs **512** may extend through elongated slots **530** in a backplate **308** (for example, see FIG. **10**). The elongated slots **530** may be round and have an angular extent sufficient to allow the tabs **512** to slide within the slots **530** when the spindle coupler **500** rotates. The tabs **512** may be positioned in a center of the elongated slots **530** and may move along the slots **530** in either direction when someone rotates a handle attached to the lock portion (i.e., to open a door). The circular edge **560** may also extend through an opening in the backplate **308**.

[0176] FIG. **18** is a schematic of a plane view of rear surface **510** of the spindle coupler **500**. The tabs **512** and the circular edge **560** around through hole **506** may extend through complementary shaped openings in a backplate **308**. By extending through the backplate **308**, the tabs **512** and circular edge **560** may stabilize the components in FIGS. **15-16** and prevent “waggle,” or unwanted movement of the handle, or movement other than rotation about axis **10**, giving the effect that the handle may be loose. The tabs **512** may be spaced a distance from axis **10** and may have a greater diameter **30** than a diameter of the circular edge **560**. Positioning the tabs **512** a distance from axis **10** may help to stabilize the spindle coupler **500** and the exterior lock spindle **430** as it rotates, preventing unwanted waggle.

[0177] FIG. **19** shows a side cross-sectional view of the components of FIGS. **15-16** taken along axis **10**. In some embodiments, a spindle coupler **500** may be positioned adjacent to a backplate (not shown in FIG. **18**) of the exterior lock portion. As shown in FIG. **19**, the spindle coupler **500** may hold and stabilize an exterior spindle **430** along a length of axis **10**. Tabs **512** and circular edge **560** may extend from a rear surface of the spindle coupler **500** to engage openings in the backplate, to further stabilize the spindle coupler **500** and exterior spindle **430**, as described above.

[0178] In some embodiments, a housing **310** may be attached to the backplate **308** (e.g., using screws) and the housing **310** and the backplate may hold and support the outer spindle **302** and disc **340**, spindle holder **550**, slider **520**, spring **570**, exterior spindle **430**, and spindle coupler **500**. In some embodiments, the outer spindle **302**, disc **340**, spindle holder **550**, slider **520**, spring **570**, exterior spindle **430**, and spindle coupler **500** may be at least partially contained between the housing **310** and the backplate **308**. A torsion spring **350** may be disposed around the outer spindle **302**.

[0179] As shown in FIG. **19**, the exterior handle **106** may be installed on the outer spindle **302** and the outer spindle **302** may be held within the handle **106**. Rotating the exterior handle **106** may

rotate the outer spindle **302** and the disc **340**. The disc **340** may be coupled to the spindle coupler **500** when the slider **520** is in the downward, unlocked position. In this unlocked position, the torque applied to the exterior handle **106** may be directly translated to the spindle coupler **500** through the outer spindle **302** and disc **340**. The spindle coupler **500** may apply torque to the exterior spindle **430** directly to turn the lock spindle **430** in the first opening **434** of the lock body **400** to release the latch **112** (see FIG. **10**).

[0180] In some embodiments, the disc **340** may have a larger diameter than a diameter of the outer spindle **302**. In some embodiments, a ratio of the diameter of the disc **340** to the diameter of the outer spindle **302** may be at least 1.5, 1.75, 2, or 2.5. In some embodiments, the spindle coupler **500** may have a larger diameter than a diameter of the outer spindle **302**. In some embodiments, a ratio of the diameter of the spindle coupler **500** to the diameter of the outer spindle **302** may be at least 1.5, 1.75, 2, or 2.5. In other embodiments, the diameter of the disc **340** may be approximately the same as the diameter of the spindle coupler **500**.

[0181] As shown in FIG. **19**, the spring **570** may compress against a surface of an opening **552** in the spindle holder **550** on one end and against a front surface of the exterior spindle **430** on a second end opposite the first end, biasing the exterior spindle **430** out of the opening **552** and through the through hole **506** of the spindle coupler **500**. Ribs **566** of the spindle coupler **500** may catch ledges **564** on the front surface of the exterior spindle **430** to prevent the spring **570** from pushing the exterior spindle **430** completely through the spindle coupler **500**. A rear side of the exterior lock spindle **430**, opposite the spring **570**, may enter an opening in a lock body and exert a force against the lock body in a direction along axis **10**.

[0182] FIGS. **20A-20C** is a schematic illustrating an embodiment of a method for installing a door lock system. As shown in FIGS. **20A-20C**, the door lock system includes a lock body **400** disposed between an exterior spindle **430** and an interior spindle **420**. The exterior spindle **430** is biased toward the lock body by an exterior spindle spring **570** and the interior spindle **420** is biased toward the lock body by an interior spindle spring **470**. Springs **570**, **470** and spindles **430**, **420** may automatically center a lock body **400** with a plane **20**, which is parallel to a plane of a door on which the door lock system may be installed. As shown in FIG. **20A**, the spring **570** and spindle **430** may be components in an exterior lock portion and the spring **470** and spindle **420** may be components in an interior lock portion. In FIG. **20A**, the exterior lock portion and the interior lock portion may not be installed on a door and the spindles **430**, **420** may not contact the lock body **400**.

[0183] In FIG. **20B**, the exterior lock portion may be installed on the door first and the exterior spindle **430** may engage the lock body (e.g., by entering an opening in the lock body). In some embodiments, the spring **570** may exert a force on the exterior spindle **430**, which in turn may exert a force on the lock body **400**, pushing the lock body away from the exterior spindle **430** in a direction perpendicular to plane **20**.

[0184] In FIG. **20C**, the interior lock portion may be installed on the door and the interior spindle **420** may engage the lock body **400** (e.g., by entering an opening in the lock body) on a side of the lock body **400** opposite the side of the exterior spindle **420**. The springs **570**, **470**, and spindles **430**, **420** may be aligned on an axis perpendicular to plane **20**. In some embodiments, the spring **470** may exert a force on the interior spindle **420**, which in turn may exert a force on the lock body **400**, pushing the lock body away from the interior spindle **420** in a direction perpendicular to plane **20**. The force of spring **570** and the force of spring **470** may be equal (e.g., the springs may have equal spring constants), such that the spindles **430**, **420** exert equal, opposing forces on the lock body **400**, causing the lock body **400** to automatically center within the door along plane **20**, regardless of the thickness of the door. Thus, the door lock system **100**, as described above, may be a universal door lock system that may be installed on doors of varying thicknesses. Although the lock body **400** is shown in FIG. **20C** as centered in the door **20**, in other embodiments the springs **570**, **470** may have unequal spring constants such that the springs exert unequal, opposing forces on the

lock body **400** to maintain the lock body in an off-centered position in the door, as the disclosure is not so limited.

[0185] It should be noted that while the exterior lock portion components are shown being installed on a door first in the embodiment of FIGS. **20A-20C**, in other embodiments the interior lock portion components may be installed first, as the present disclosure is not so limited. In some embodiments, the interior and exterior lock portion components may be installed simultaneously. Regardless of order of installation, opposing springs associated with the opposing spindles may bias the lock body **400** toward alignment with plane **20**, equidistant from opposing door surfaces. Accordingly, any suitable order of installation may be employed, as the present disclosure is not so limited.

Security

[0186] In some embodiments, the door lock systems may be an electronic door lock system that includes data wires and power wires interconnecting various electrical components. As described below, an exterior lock portion may include a second housing to protect the power wires from an attempted data breach.

[0187] FIG. **21** is a perspective view of an exterior lock portion **104** with parts of the lock portion removed to reveal a backplate **308**. In some embodiments, the door lock system may be an electronic door lock system. As shown in FIG. **21**, wiring **602** may electronically connect an interior lock portion to the exterior lock portion. For example, wiring **602** may connect an electronic component **618** in the exterior lock portion to an electronic component **620** in the interior lock portion. The wiring **602** may travel from the electronic component **620** in the interior lock portion, out through a slit **636** in a backplate **208** of the interior lock portion, through an opening in a door, and in through a slit **638** in the backplate **308** of the exterior lock portion to the electronic component **618** in the exterior lock portion (see FIG. **10**).

[0188] In some embodiments, the exterior lock portion **104** may include a secondary housing **600** to enclose and protect operating components of the exterior lock portion **104**, including the wiring **602**. The secondary housing **600** may include a cover **604** with wings **606** that have screw holes **608** for attaching the cover **604** to the backplate **308** from the rear side (i.e., side facing the door) of the exterior lock portion. In some embodiments, the backplate **308**, the secondary housing **600**, and/or the cover **604** may be made of a durable material such as metal (e.g., stainless steel). By being back-screwed to the backplate **308**, the secondary housing may only be removed by accessing the rear side of the backplate **308**. If someone were to remove parts of the exterior lock portion in an attempt to access the wiring and circumvent the lock system, the cover **604** may not be removed from the backplate **308** without removing the exterior lock portion **104** from the door in order to access the rear side of the backplate **308**. In some embodiments, the exterior lock portion **104** and the interior lock portion **108** may be secured to the door via rods **402** and pins **404** extending from the backplates of each lock portion (see FIGS. **10-11**). The pins **404** may be screws that screw into threads on the interior surface of the rods **402** to clamp the exterior lock portion onto an exterior of the door. In this manner, the exterior lock portion **104** may only be non-destructively removed from the door from an interior side of the door via the interior lock portion.

[0189] FIGS. **22A-22B** show the embodiment of the door lock system of FIG. **21** with a cover **604** removed, showing a rear housing **610** of the secondary housing **600**. The rear housing **610** may be made of a durable material such as metal. As shown in FIG. **22B**, the operating components within the secondary housing **600** may include an actuator **622** and wiring **602**. The wiring **602** may include data wires and/or power wires. The data wires **616** may pass through an opening **612** in the secondary housing **600** to connect to an electrical component **618** in an exterior lock portion **104**. The data wires **616** may only be reader wires and are not electrically related to the physical locking function of the door lock system. The power wires **624** may be contained entirely within and protected by the secondary housing **600**. The power wires **624** may connect to the actuator **622** that controls the locking state of the door lock system (e.g., by moving a projection **522** of a slider **520**

into locked and unlocked positions, as described above with reference to FIGS. 15-17).

[0190] FIGS. 23A-23B depict cross-sectional views of the door lock system shown in FIG. 21, where the cross-section is taken perpendicular to a plane defined by the backplate 308. FIGS. 23A-23B illustrate a path of the wiring 602 from the interior electrical component 620 to the exterior electronic component 618. The wiring 602 may enter the exterior lock portion through a slit 638 in a backplate 308 of the exterior lock portion. The slit 638 may be positioned below the rear housing 610. The wires 602 may then travel up between a rear surface of the secondary housing 600 and the backplate 308. The rear housing 610 may have an elongated channel (not shown) within the rear surface for the wires to pass between the rear housing 610 and the backplate 308. The wires 602 may be compressed within the elongated channel between the rear housing 610 and the backplate to secure the wires 602 in the exterior lock portion. The wires 602 may then travel over a ridge 630 at a top surface of the rear housing 610 that extends from a portion 628 (see FIG. 22B) of the rear housing 610. The wires 602 may then travel back down and loop under a looping ledge 632. The looping ledge may have a square cross-section and may extend from a portion 626 (see FIG. 22B) of the rear housing 610 or it may extend from an inside surface of the cover 604. The wiring 602 may then travel back and form a wire loop 614 in the secondary housing 600. In some embodiments, a projection 634 may extend from a back surface of the rear housing 610 that may pinch the wires above the looping ledge 632 against the cover 604.

[0191] After the projection 634 secures the wires against the cover 604, the power wires 624 may split from wire loop 614 and terminate at the actuator 622 (see FIG. 22B). The data wires 616 may travel back up over ridge 630 and pass through an opening 612 in the cover 604 and connect to the electronic component 618. The ridge 630 may compress the wires 602 against the cover 604, further securing the wires 602 in the secondary housing 600.

[0192] According to the embodiment of FIGS. 23A-23B, the secondary housing 600 and wire loop 614 may serve to protect the power wires 624 from being pulled from the secondary housing 600. If someone were to pull on the data wires 616, the ridge 630, projection 634, and looping ledge 632 would prevent the wires 602 from being pulled from the secondary housing, and specifically may prevent the power wires from being pulled out with the data wires. In this manner, an unauthorized user may be inhibited from accessing the power wires that control the actuator disposed in the exterior lock portion.

[0193] FIG. 24 is a flowchart for a method of running and securing a wire in a first housing of a door lock system in accordance with some embodiments. In step 1000, a wire may be passed into a first housing through a first opening in a backplate of the first housing. In some embodiments the first housing may be an exterior lock portion and the wire may electrically connect one or more electrical components in an interior lock portion to one or more electrical components in the exterior lock portion.

[0194] In step 1002, the wire may be inserted into a second opening of a second housing disposed in the first housing. In some embodiments, the second housing may be a metal housing that is secured to a first side of the backplate of the first housing from a second side of the backplate, opposite the first side. The second housing may only be non-destructively removed from the first housing by accessing the second side of the backplate. In some embodiments, the second side of the backplate may be secured to an exterior side of a door and non-destructively removable only from an interior side of the door.

[0195] In some embodiments, the second housing may be positioned above the first opening and the second opening may be positioned at an upper surface of the second housing. In this manner, the wire may travel upwards (e.g., in a direction parallel to a plane of the door) between the first opening and the second opening before being entering the second housing through the second opening. The wire may be compressed and secured between the first side of the backplate and the second housing. In some embodiments a ridge may be positioned at an upper surface of the second housing adjacent to the second opening. The wire may enter the second opening after traveling

upward to the second opening and wrap around the ridge to reverse direction and continue downward (e.g., in a direction parallel to a plane of the door).

[0196] In step **1002**, the wire may be looped around a ledge attached to the second housing. In some embodiments, the wire may enter the second opening and initially travel in one direction (e.g., parallel to a plane of the door). The wire may then loop around the ledge to reverse direction and continue in an opposite direction within the second housing. In some embodiments the wire may enter an opening at the top of the second housing, travel downwards, loop around the ledge, and then travel back in an upwards direction to form a wire loop.

[0197] In step **1004**, a first section of the wire may overlap a second section of the wire after looping the wire around the ledge. The first section of the wire may be a length of the wire between the second opening and the ledge, and the second section of the wire may be a length of the wire after the ledge. The first section and the second section may form the wire loop.

[0198] In step **1006**, the first section of the wire and the second section of the wire may be compressed together within the second housing to secure the wire loop in the second housing. A projection may extend from a first surface in the second housing to clamp the wire loop between the projection and a second surface of the second housing.

[0199] In some embodiments, the wire may connect to an operating component positioned in the second housing. In some embodiments, the wire may travel out of the second opening and connect to an electrical component in the first housing. The second opening may be sized to compress the wire in the opening to secure the wire in the second housing. The wire may connect electrical components in the interior lock portion and the exterior lock portion. The second housing and the wire loop may protect the wires in the exterior lock portion that control a locking state of the door lock system in the event of an attempted breach.

Keyless Option

[0200] Some embodiments of a door lock system may include a handle with a keyless cylinder, i.e., a handle without a key cylinder. As shown in FIG. 25, an exterior lock portion **701** attached to a door **703** includes a handle **700** with a keyless cylinder. The handle **700** includes an opening **702** to access a handle catch disposed inside the handle that secures the handle **700** to the door lock. Although described with respect to an exterior handle, it should be appreciated that an interior handle may also include a keyless cylinder, as the disclosure is not so limited.

[0201] FIG. 26 shows an exploded view of the exterior keyless handle **700** according to some embodiments. As illustrated in FIG. 26, an outer spindle **704** extends through an opening in the exterior lock portion **701**. The outer spindle **704** and exterior lock portion **701** may be similar to and may include similar components as those described above in other embodiments. In this embodiment, a handle **700** is attached and secured to the outer spindle **704** via a handle catch **708**. One end of the handle catch **708** extends through an opening **712** in the outer spindle **704** and an opposite end of the handle catch **708** is disposed in a groove **713** on an interior side of handle **700** (see FIGS. 29A-29B) in an engaged position to secure the handle to the outer spindle. To remove the handle **700** from the outer spindle **704**, an object may be inserted into opening **702** on the handle to push the handle catch **708** radially inward out of the groove **713** to a disengaged position.

[0202] A locking block **706** is slidably disposed in the outer spindle **702** along a lock axis **10**. The locking block **706** may be installed in the outer spindle **704** by a customer before a handle is attached. The locking block **706** may be made of metal or other durable material with a high melting point that cannot be deformed or otherwise compromised by someone trying to breach the lock system. When installed, the locking block **706** may be moveable in a direction along the lock axis **10** between a first, locked position and a second, unlocked position. As will be discussed further below, the locking block **706** is shaped and sized such that when the locking block **706** is in the locked position, the locking block **706** prevents the handle catch **708** from being moved radially inward from the engaged position to the disengaged position. A spring **714** disposed in the handle between the handle and the locking block **706** biases the locking block **706** in a first direction

toward the door to the first, locked position.

[0203] The locking block **708** may only be moved in a second direction, opposite the first direction, to the second, unlocked position, by accessing components from an inner side of the lock portion (i.e., a side facing the door **102** when installed). As shown in FIG. **27**, a lock spindle **716** extends through an opening in a backplate **710** of the exterior lock portion **701**. The lock spindle engages a lock body (not shown) when installed on a door. As will be discussed in more detail below, pushing the lock spindle **716** in a direction into the exterior lock portion **701** may cause the lock spindle to contact a portion of the locking block **706** in the outer spindle and exert a force in the second direction on the locking block. The force in the second direction may overcome the force of the spring **714** and cause the locking block **706** to move to the second, unlocked position. In this unlocked position, the handle catch **708** may then be moved to the disengaged position and the handle may be removed.

[0204] As discussed above, an exterior lock portion **701** is installed on an exterior side of a door such that the exterior lock portion may only be removed from an interior side of the door.

Accordingly, to remove the handle, someone must have access to the interior side of the door to first remove the exterior lock portion **701** from the door and then access the exterior lock spindle **716** on an inner side of the exterior lock portion. As such, the door lock system provides security from someone on an exterior side of a door who may try to remove a keyless cylinder handle to breach the lock.

[0205] FIG. **28** is an exploded rear view of components in the exterior lock portion disposed along lock axis **10**, according to some embodiments. As shown in FIG. **28**, a first end of the lock spindle **716** extends through an opening **724** of a spindle coupler **722**. A second end of the lock spindle **716** extends into an opening **731** on a first side of a spindle holder **730**. The opening **731** extends through the spindle holder **730** in a direction along lock axis **10** from the first side to a second side, opposite the first side. The lock spindle is configured to slide in the spindle holder along the lock axis **10**.

[0206] The second side of the spindle holder **730** is disposed in an opening **707** on a disc **705** coupled to the outer spindle **704**. In some embodiments, the disc **705** may be integrally formed with the outer spindle **704** and the opening **707** may extend completely through the outer spindle **704**. A piece **718** is disposed in the opening **707** between the outer spindle **704** and the spindle holder **730**. A projection **719** extends from the piece **718** in a direction along the lock axis **10** into the opening **731** of the spindle holder. A spring **720** is disposed on the projection **719** that extends through opening **731** and contacts the second end of the lock spindle **716** to bias the lock spindle **716** in a direction toward the spindle coupler **722**. As mentioned above, the lock spindle **716** may include tabs **717** extending radially from the second end of the lock spindle to prevent the lock spindle from extending completely through the opening **724** of the spindle coupler.

[0207] FIG. **29A** is a top perspective cross-sectional view of the keyless cylinder handle when the locking block is in the first, locked position, according to some embodiments. As shown, the locking block **706** is biased to the first, locked position via spring **714**. As shown in FIG. **29B**, the handle catch **708** is disposed in a groove **713** on the internal surface of the handle **700** to secure the handle to the outer spindle. In this locked position, a surface **711** of the locking block **706** is positioned over the opening **702** to prevent the handle catch **708** from moving radially inward out of groove **713** to the disengaged position. If someone attempted to insert an object into opening **702** of the handle **700**, the locking block **706** would prevent the handle catch **708** from being moved to the disengaged position to release the handle.

[0208] As shown in FIG. **29A**, the piece **718** is disposed in opening **707** of the outer spindle **704**. The piece is shaped such that the piece **718** may not occupy the entire cross-sectional area of the opening **707**, allowing a portion **723** of the locking block **706** to extend inwardly within the opening **707** past the piece **718**. Spring **720** is disposed on projection **719** of the piece **718** and extends into an opening on the second side of the exterior lock spindle **716**. Spring **720** biases the

lock spindle **716** through opening **724** of the spindle coupler in a direction away from the piece **718**. In some embodiments, an internal surface of the opening **707** of the outer spindle may include a ledge **721** to engage a portion of the piece **718** to position the piece **718** in the outer spindle and prevent the piece from moving outward past a certain point toward the locking block **706**. As such, spring **720** may not exert any forces on the locking block in the second direction.

[0209] FIG. **30A** is a top cross-sectional view of the keyless cylinder handle when the locking block **706** has been moved to the second, unlocked position, according to some embodiments. As shown in FIG. **30A**, a force has been exerted on lock spindle **716** in the second direction sufficient to overcome a force of the spring **720** (not shown) and cause the exterior lock spindle **716** to move in the second direction. The second end of the lock spindle **716** then contacts the portion **723** of the locking block **706** and exerts a force on the locking block **716** to cause the locking block to move in the second direction. As shown in FIG. **30B**, surface **711** of the locking block **706** is no longer positioned over opening **702** nor aligned with handle catch **708**. A surface **715** of the locking block is now positioned over the handle catch. Surface **715** is on a portion of the locking block having a smaller diameter than a portion of the locking block with surface **711**, and as such, surface **715** is spaced radially inward from the internal surface of the outer spindle. Someone may now insert an object into opening **702** to move the handle catch **708** toward surface **715** out of the groove **713** in the handle **700**. With the handle catch in the disengaged position, the handle may now be removed. In some embodiments, surface **715** may act like a stop to prevent the handle catch **708** from being pushed radially inward too far into the outer spindle **704**.

[0210] FIG. **31** shows a perspective view of the lock spindle **716** in the spindle coupler **705**. In some embodiments, a first end of the lock spindle **716** includes indents **740**. The indents **740** may be shaped to correspond to a screwdriver head or other object that may be inserted into the indents to push in and rotate the lock spindle in the opening **724** of the spindle coupler **705**. The lock spindle **716** may also include notches **742** near the first end on each corner that extend along a longitudinal length of the lock spindle. The notches **742** may correspond to ridges **744** arranged around opening **724** of the spindle coupler **705**, shown in FIG. **32**. The lock spindle may be pushed inwards along the lock axis **10** (i.e., in the second direction) until the notches **724** line up with ridges **744** such that the ridges **744** allow the lock spindle **716** to be rotated about lock axis **10**. In the rotated state, ledges **746** of notches **742** engage a rear surface of the spindle coupler **705** to hold the lock spindle **716** in the pushed-in position along lock axis **10**.

[0211] FIG. **33** is a side cross-sectional perspective view of the lock spindle **716** pushed in and rotated about lock axis **10**. In this position, the second end of the lock spindle may press against portion **723** of the locking block to move the locking block to the second, unlocked position. With the lock spindle **716** retained in this position and holding the locking block in the unlocked position, a user attempting to remove the handle may have two free hands to remove the handle. For example, the user may use one hand to insert an object into opening **702** to disengage the handle catch **708** and may use the other hand to grasp the handle **700** and remove the handle from the outer spindle **702**.

Weatherization

[0212] According to some embodiments, the door lock system described herein may include various gaskets and sealing methods to protect internal electrical components from external humidity. FIGS. **34** and **35** show an exterior lock portion **800** of the door lock system. In this embodiment, the external lock portion **800** includes a printed circuit board **804**, a gasket **802**, and a plate **808** disposed between an exterior housing **806** and an exterior escutcheon **810**. The exterior housing **806** is configured to be installed on an exterior surface of a door (not shown) and has an open front for receiving the printed circuit board **804**, the gasket **802**, and the plate **808**. Screws **814** disposed around a circumference of the lock portion secure and uniformly compress together these components between the exterior housing **806** and the escutcheon **810** to form a moisture barrier seal, as will be described below. The exterior housing **806** also includes lock and housing

components, such as an outer spindle **816** and cover **818**, described in embodiments above. The circuit board **804**, gasket **802**, plate **808**, and escutcheon **810** include openings **820**, **824**, **826**, **828**, respectively, through which the outer spindle **816** extends to receive a handle **812** on the outer side of the escutcheon **810**.

[0213] In this embodiment, the printed circuit board **804** is formed of a substantially elongate and planar body and is sized and shaped to be slightly smaller than the open front of the exterior housing such that it fits within and substantially covers the open front of the exterior housing **806**. It should be noted that the printed circuit board **804** can be other shapes and sizes that fit within exterior housing **806**, as the disclosure is not so limited. The opening **820** in the printed circuit board **804** is sized and shaped to allow the cover **818** to extend through the opening. The printed circuit board **804** also includes screw holes **832** aligned with screw holes **830** of the exterior housing for screws **814** to pass through.

[0214] In this embodiment, a gasket **802** is disposed on the outer side of the printed circuit board **804**. The gasket **802** is formed of a substantially elongate and planar body and is shaped to match the circuit board and the open front of the exterior housing. As shown in FIGS. **36A-36B**, the gasket includes a first L-shaped perimeter **840** that extends around the entire gasket **802** and wraps around a perimeter edge of the circuit board. The L-shape first extends in a direction perpendicular to the body of the gasket inwardly toward the printed circuit board and then in a direction parallel to the body of the gasket radially inwardly. The gasket is shaped to match the printed circuit board and is slightly larger in size than the printed circuit board such that the first L-shaped perimeter **840** extends over a perimeter edge of the printed circuit board and onto an inner side of the printed circuit board around the entire perimeter of the circuit board (see FIG. **38A-38B**).

[0215] The gasket **802** includes screw holes **834** that align with screw holes **804** of the printed circuit board **804** and the screw holes **830** of the exterior housing. The screw holes **834** extend through protrusions **842** that protrude from an inner side of the gasket toward the printed circuit board. The protrusions **842** are sized and shaped to match the screw holes **832** and **830** such that when the exterior lock portion is assembled, the protrusions **842** extend through screw holes **832** of the printed circuit board and into screw holes **830** of the exterior housing. A first end of the protrusions **842** abuts an inner ledge **843** of screw holes **830** (see FIG. **38B**).

[0216] In this embodiment, the gasket **802** includes a recess **821** that extends from an outer side of the gasket that is shaped and sized to receive cover **818** disposed on the exterior housing. As shown in FIGS. **36A-36B**, the recess **821** includes walls **822** that extend in a direction perpendicular to the body of the gasket to a surface **823** that is parallel to the body of the gasket. Surface **823** includes opening **824** through which the outer spindle **816** extends. As will be discussed further below, the opening **824** includes a beveled perimeter **856** that compresses against the surface of the outer spindle to create a seal around the outer spindle while still allowing the outer spindle to rotate within the opening **824**.

[0217] Similar to the first L-shaped perimeter **840** of the gasket **802**, the recess **821** includes a second L-shaped perimeter **844** that extends from the inner side of the gasket. The L-shape first extends in a direction perpendicular to the body of the gasket inwardly toward the printed circuit board and then in a direction parallel to the body of the gasket radially outward. The perimeter of opening **820** in the printed circuit board is received in the L-shaped perimeter of the recess **821** such that the L-shape wraps around the perimeter of opening **820** and extends partially onto the inner side of the circuit board (see FIGS. **38A** and **38C**).

[0218] Returning to FIGS. **34** and **35**, in this embodiment, the plate **808** is formed of a substantially elongate and planar body and is shaped and sized to match the gasket **802** and the open front of the exterior housing **806**. The opening **826** in plate **808** is sized and shaped to match the recess **821** such that the recess **821** fits into and extends through the opening **821**. The plate **808** includes screw holes **836** that align with the screw holes **834** of the gasket and screw holes **838** of the exterior escutcheon **810**. The screw holes **838** include protrusions that extend toward the plate **808**

and through screw holes **836** and into a second end of the protrusions **842** of the gasket (see FIG. **38B**).

[0219] In this embodiment, plate **808** includes a plate perimeter **846** that extends inwardly in a direction perpendicular to the body of the plate toward the gasket **802**. As discussed below, an end of the plate perimeter **846** includes a beveled edge configured to compress against the outer side of the perimeter of gasket **802** (see FIG. **38B**). The plate also includes first and second ribs **848** and **850** that extend inwardly in a direction perpendicular to the body of the plate and are configured to contact the outer side of the gasket. The first rib **848** is disposed around opening **826** and aligns with the second L-shaped perimeter **844** of the gasket **802**. The second rib **850** is disposed radially inward from the plate perimeter **846**. As shown, the second rib **850** may surround screw holes **836** such that the second rib **850** contacts the gasket around protrusions **842** of gasket **802**. When the exterior lock portion is assembled, the plate perimeter **846** and first and second ribs **848** and **850** of the plate **808** compress against the outer side of the gasket **802**, compressing the gasket against the exterior housing **806** with uniform compression around the perimeters **840**, **844** of the gasket and creating an air and watertight seal around the printed circuit board **804**.

[0220] FIGS. **37A-37C** show the outer side of the exterior housing **806**. The exterior housing includes a first ledge **853** disposed around the perimeter of the exterior housing. The first ledge is set inward from an outermost portion **861** of the exterior housing perimeter. When the exterior lock portion is assembled, the gasket **802**, printed circuit board **804**, and plate **806** are disposed and compressed between the ledge **853** and the exterior escutcheon **810** and the first ledge **853** is aligned with the first L-shaped perimeter **840** of the gasket **802**. The first ledge **853** extends almost entirely around the perimeter of the exterior housing. In other embodiments, the ledge may extend entirely around the perimeter of the exterior housing. As shown in FIG. **37C**, the first ledge **853** includes a first ridge **854** that protrudes from the ledge in a direction toward the gasket **802**. The first ridge **854** may have a triangular shape or a tapered end that is configured to compress into the first L-shaped perimeter **840** of the gasket **802** when the lock portion is assembled (see FIG. **38B**). [0221] In this embodiment, as shown in FIG. **37A**, the exterior housing **806** also includes a second ledge **857** disposed around an opening for the lock components (e.g., cover **818**) in the exterior housing that is aligned with the second L-shaped perimeter **844** of the gasket **802** when the exterior lock portion is assembled. The second ledge **857** extends entirely around the opening for the lock components. The second ledge **857** includes a second ridge **858** that protrudes from the ledge in a direction toward the gasket **802**. The second ridge **858** may have a triangular shape or a tapered end that is configured to compress into the second L-shaped perimeter **844** of the gasket **802** when the lock portion is assembled (see FIG. **38C**).

[0222] FIGS. **38A-38C** show side perspective schematic views of the exterior lock portion when assembled. The screws **814** pass through screw holes **830** from the inner side of the exterior housing, through screw holes **832** of the printed circuit board, **834** of the gasket, and **836** of the plate, and into screw holes **838** of the exterior escutcheon **810**. The screw holes **838** include internal threads such that when the screws **814** are screwed into holes **838**, the screws grip the threads and cause the exterior escutcheon to move toward the exterior housing until an innermost portion **863** of the exterior escutcheon perimeter contacts the outermost portion **861** of the exterior housing perimeter. When the exterior escutcheon and the exterior housing are brought together, the plate, gasket, and printed circuit board are uniformly compressed between the exterior housing and the exterior escutcheon.

[0223] As shown in FIGS. **38A-38C**, the exterior escutcheon **810** presses the plate **808** against the gasket **802**, pressing the plate perimeter **846**, the first rib **848**, and the second rib **850** against the gasket **802**. As best shown in FIG. **38B**, the plate perimeter **846** presses against the outer side of the gasket **802** at the first L-shaped perimeter **840**. The first L-shaped perimeter **840** wraps around the perimeter edge of the printed circuit board **804** and compresses against the ledge **853** of the exterior housing **806**. The first ridge **854** presses into the first L-shaped perimeter **840**, creating a seal

between the gasket **802** and the exterior housing **806** to protect the printed circuit board **804** from water and air that may leak in through seams in the housing.

[0224] Also shown in FIG. **38B**, the screw holes **838** extends into the protrusions **842** of the gasket **802**, compressing the protrusions **842** between an innermost end of the screw holes **838** and an inner ledge **843** of screw holes **830** to seal against entry of water and air. The screw holes **834** of the gasket may also be sized to fit tightly around screws **814** to further seal against water and air entry around the screws **814**.

[0225] As shown in FIGS. **38A** and **38C**, the second L-shaped perimeter **844** around recess **821** in the gasket is sized and shaped such that the second L-shaped perimeter **844** wraps around perimeter of opening **820** in the printed circuit board **804**. The second L-shaped perimeter **844** extends fully around opening **820**. When the exterior lock portion **800** is assembled and screws **814** are tightened, recess **821** of the gasket extends through opening **826** of the plate **808** and the second rib **848** of the plate **808** compresses against the outer side of the gasket. The second rib **848** is positioned such that it compresses the second L-shaped perimeter **844**, which is wrapped around the edge of the opening **820** of the printed circuit board **804**, against the second ledge **857** of the exterior housing **806**. The second ridge **858** presses into the second L-shaped perimeter **844** creating a seal between the gasket **802** and the exterior housing **806** to protect the printer circuit board **804** from water and air that may leak in through the handle or lock components in the exterior lock portion.

[0226] As shown in FIGS. **39A-38B**, the outer spindle **816** extends through openings **820**, **824**, **826**, **828**, of a circuit board **804**, gasket **802**, plate **808**, and exterior escutcheon **810**, respectively, and receives a handle **812**. The opening **824** of surface **823** of gasket **802** includes a beveled perimeter **856** such that the opening has a smaller diameter on an outer side of the surface **823** than an inner side of surface **823** (see FIG. **36B**). A diameter of the outer spindle **816** matches the size of the larger diameter of the beveled perimeter on the inner side of surface **823** and thus is larger than the smaller diameter of beveled perimeter **856**. When the exterior lock portion is assembled, rim **852** surrounding opening **828** of the exterior escutcheon **810** (see FIG. **35**) compresses a portion of the surface **823** around opening **824** against the cover **818** in the exterior housing **806**. The outer spindle **816** extends through opening **824**, and the smaller diameter of the beveled perimeter **856** deforms in an outward direction and compresses against the outer spindle **816**, as best shown in FIG. **39B**. The rim **852** has a diameter sufficiently larger than the diameter of the outer spindle to provide space for the beveled perimeter to deform around the outer spindle without compressing the perimeter **856** between the rim and the outer spindle. Accordingly, the beveled perimeter forms a seal around the outer spindle to prevent entry of water and air through the handle while still allowing the outer spindle to rotate when a handle is rotated to release a door latch and open the door.

[0227] Accordingly, the gasket **802** entirely seals the printed circuit board **804** against entry of water and air in the exterior lock portion due to the first L-shaped perimeter **840**, the second L-shaped perimeter **844**, beveled perimeter **856**, and the protrusions **842** being compressed between the respective components.

[0228] Now turning to an interior side of a door, FIGS. **40** and **41** show an interior lock portion **860** of the door lock system. In this embodiment, the interior lock portion **860** includes a printed circuit board **866**, a gasket **864**, and a plate **868** disposed between a back plate **870** and an interior escutcheon **862**. The back plate **870** is configured to be installed on an interior surface of a door (not shown). The gasket **864**, the printed circuit board **866**, and the plate **868** are disposed within a top portion of the interior housing **862**. Screws **874** extend through screw holes **878** in the plate **868** from an inner side of the plate in an outward direction to screw holes **876** in the interior housing **862** to compress the circuit board **866** and the gasket **864** between the plate **868** and the interior housing **862** to form a water and airtight seal around the circuit board **866**, as will be described below. The interior housing **862** may be attached to the back plate **870** via screws (not shown) or

other attachment means (e.g., press or snap fit). The back plate **870** also includes lock and housing components, such as an outer spindle **880** and cover **879**. The outer spindle **880** extends through an opening in the interior housing **862** to receive a handle **872** on the outer side of the interior housing **862**. It should be noted that although components are described herein specific to the interior lock portion and the exterior lock portion, any components may be included in either the interior or exterior lock portions, as the disclosure is not so limited.

[0229] In this embodiment, as shown in FIGS. **42A-42B**, the gasket **864** is formed of a substantially planar body **871** that is shaped to match a cavity **875** in the top portion of the interior housing **862** defined by a cavity wall **886** that extends entirely around the cavity **875** (see FIGS. **40** and **43A**). The gasket include an L-shaped perimeter that extends around the circumference of the body **871**. The L-shaped perimeter includes a first wall **882** that extends in a direction perpendicular to the body **871** from an inner side of the gasket around an entire perimeter of the body **871**. A second wall **884** parallel to the body **871** extends radially outward from an inner end of the first wall **882** around the entire gasket **864**. As shown in FIGS. **40-41**, the printed circuit board **866** is formed of a substantially elongate and planar body and is sized and shaped to fit within the first wall **882** on an inner side of the gasket **864**.

[0230] The gasket **864** is disposed in the cavity **875** of the interior housing such that the first wall **882** fits within the cavity wall **886** and an innermost portion of the cavity wall **886** presses into an outer side of the second wall **884** (see FIG. **45B**). The body **871** may include one or more openings **881**, **885** to allow electrical components to extend through the gasket to connect the printed circuit board to electrical components (e.g., power, data) in the interior housing. As non-limiting examples, the gasket body may include slits **885** to allow a metal coil (not shown) to pass through the gasket and connect the circuit board to a battery or other power supply in the interior housing, or an opening **881** to allow a connector to extend through the gasket that connects power or data wires between an internal and external lock portion (see FIGS. **50A-50B**).

[0231] FIG. **43A** shows a back view of the interior housing **862**. A cavity wall **886** extends entirely around cavity **875**. The interior housing includes screw holes **876** positioned around the cavity **875** to receive screws **874** to connect plate **868** to the interior housing. Although six screw holes are shown, more or less may be used in various positions within or outside of the cavity. The interior housing may include openings **889** and **1102** positioned within the cavity to allow various electrical components to extend through a surface of the cavity to electrically connect components positioned on an outer side of the interior housing (e.g., power supply, lights, data wires) to the circuit board **866** or electrical components in an exterior lock portion. As shown in FIGS. **43B-43C**, the cavity wall **886** includes a beveled edge at the innermost portion. The beveled edge is configured to compress into the first wall **882** of the gasket. The openings **889** and opening **1102** also include a beveled protruding ledge **887** around the entire opening. The beveled edges around each opening are configured to press against the outer surface of body **871** of the gasket **864** when the interior lock portion is assembled to seal each opening against entry of water and gas.

[0232] As shown in FIG. **44**, in this embodiment, a plate **868** is formed of a substantially planar body and is shaped and sized to match the cavity wall **886** of the interior housing. The plate **868** includes screw holes **878** positioned to match the screw holes **876** in the interior housing. The plate includes a plate perimeter **873** that extends outwardly in a direction perpendicular to the body of the plate toward the interior housing. The plate perimeter **873** may extend completely or partially (as shown) around the perimeter of the plate. The plate **868** also includes first and second ribs **888** and **890**, respectively, that extend outwardly from an outer side of the plate in a direction perpendicular to a body of the plate. The ribs **888** and **890** are sized and positioned on the plate near the plate perimeter **873** such that the second wall **884** of the gasket is received between the ribs. The ribs **888** and **890** may extend completely or partially around (as shown) the perimeter of the plate.

[0233] FIGS. **45A-45B** show a cross-sectional schematic view of part of an assembled interior lock

portion with the interior housing **862** connected to the back plate **870** and the gasket, circuit board, and plate therebetween. As shown in FIGS. **45A-45B**, screws **874** extend through the screw holes **878** in the plate **868** toward the interior housing into screw holes **876** of the interior housing to connect the plate to the interior housing. An outer end of the plate perimeter **873** contacts a surface of the interior housing that acts like a hard stop when the plate **868** is fastened to the interior housing via screws. When the plate is fastened to the interior housing, the gasket and the printed circuit board are compressed between the plate and the interior housing.

[0234] As shown in FIG. **45B**, the first rib **888** of the plate extends outward a farther distance than the second rib **890** such that the first rib extends outward around an end of the second wall **844** of the gasket and over the cavity wall **886** of the interior housing and contacts a surface of the interior housing. The second rib **890** extends outward around the first wall **882** of the gasket and contacts an inner surface of the printed circuit board **866**. As such, the plate **868**, when tightened to the interior housing (e.g., via screws **874**), compresses the gasket and the circuit board into the interior housing, pressing the beveled edge of cavity wall **886** into an outer side of the second wall **884**, and therefor forming a seal between the gasket and the interior housing to prevent water and air from entering. The second wall **884** and the cavity wall **886** extend entirely around the perimeter of the gasket, and as such, a seal is formed around the entire circuit board perimeter which is disposed within the first wall **882** on an inner side of the gasket.

[0235] FIG. **46** shows a front perspective view of the interior housing **862** according to one embodiment with a battery cover **892** displaced upwards. As shown in FIG. **46**, the interior housing includes a battery compartment **894** disposed on a slanted surface **896** of the interior housing to receive one or more batteries. The battery cover **892** may be slid up and down to attach and remove the cover from the interior housing and access the battery compartment. To prevent water and humid air from entering the battery compartment and potentially corroding the batteries, the slanted surface **896** includes one or more ribs **898** that surround at least the sides and top of the battery compartment **894**. As shown in FIG. **47**, these ribs **898** are configured to press into a first compressible insert **1104** disposed on an inner surface of the battery cover around a battery compartment **1108**. The first compressible insert may be made of foam or any other compressible material. The inner surface of the battery cover is slanted to match the slanted surface **896** on the interior housing such that when the battery cover is attached to the interior housing, the first compressible insert **1104** is compressed between the slanted surface **896** and the inner surface of the battery cover.

[0236] FIG. **48A** shows a side cross-sectional schematic view of the interior housing **862** with the battery cover **892** attached and FIG. **48B** shows a side cross-sectional schematic view of the interior housing **862** with the battery cover **892** detached and displaced upwards. In the attached position of FIG. **48A**, the ribs **898** along a top portion of slanted surface press into the first compressible insert **1104**, sealing the battery compartment against entry of water and air. Because the surfaces are slanted, the ribs **898** only press into the first compressible insert when the battery cover is attached to the interior housing. As shown in FIG. **48B**, the first compressible insert is not in contact with the slanted surface **896** of the front cover when the battery cover is displaced upwards. As such, the battery cover may be slide up and down to remove or attached the cover without the ribs **898** pressing into the first compressible insert **1104**, allowing the cover **892** to be easily removed and attached without the ribs **898** rubbing against and damaging the first compressible insert **1104**.

[0237] FIGS. **49A-49B** show a top cross-sectional schematic view of the interior housing through the battery compartment with the battery cover attached. As shown in FIG. **49B**, the ribs **898** along the side of the slanted surface **896** compress into the first compressible insert **1104** when the battery cover is attached to the interior housing, sealing the sides of the battery compartment against entry of water and air. Because of the slanted surfaces, when the battery cover is slid upwards to detach the cover from the interior housing, the first compressible insert moves away and off the slanted

surface **896** such that the ribs no longer compress into the first compressible insert (see FIG. **48B**). Although the illustrated embodiment shows two ribs, it should be appreciated that any number of ribs may be disposed on the slanted surface **896**.

[0238] As shown in FIGS. **50A-50B**, in some embodiments the interior lock portion may include a connector **1108** that connects to the circuit board and a power supply in the interior housing. In this embodiment, the connector **1108** is disposed in an opening **1102** (see FIG. **43A**) of the interior housing and an opening **881** of the gasket **864** (see FIGS. **42A-42B**). The opening **881** of the gasket includes a protruding rib **883** in outward direction that extends around the entire perimeter of the opening **881**. The connector may include wires **1110** that extend from the connector over slanted surface **896** on the outer side of the interior housing inward through an opening **1100** in the interior housing. The slanted surface **896** may include a surface **1112** between openings **1100** and **1102** (see FIG. **46**) which does not include ribs **898** to allow the wires to pass without being compressed by the ribs. Rather, to seal against entry of water and air, a second compressible insert **1106** may be disposed on the surface **1112** between the surface **1112** and an inner side of the wires **1110**. When the battery cover is attached, the surface **1112** compresses the second compressible insert **1106** against the inner side of the wires while the first compressible insert **1104** is compressed against an outer side of the wires **1110**. The first and second compressible inserts are made of materials that deform sufficiently such that the inserts compress into grooves between the wires **1110**, creating a seal above the connector **1108** against entry of water and air.

[0239] Also shown in FIG. **50B**, the protruding rib **883** around opening **881** of gasket **864**, in which the connector is disposed, is pressed against a beveled protruding ledge **887** on the inner side of the interior housing around opening **1102**. The protruding rib **883** and the protruding ledge **887** extend completely around the opening **1102**, forming a water and airtight seal between the gasket and the interior housing around the opening **1102**. Although only the opening **1102** is shown, it should be noted that any openings **889** in the interior housing may form a seal with the outer side of the gasket against water and air entry in a similar way.

Other Lock Configurations

[0240] Although the door lock system is shown to be utilized with a cylindrical lock in the embodiments shown in FIGS. **1-50**, the present disclosure is not so limited, and the door lock system may be used with other locking arrangements. Examples of alternative locking arrangements include but are not limited to a mortise lock, an exit device, and a deadbolt

[0241] In one embodiment, the door lock system may be used with a mortise lock, as shown in FIG. **51**, with an exterior lock portion **1202** mounted to a door **1204**. Mortise locks are common in both commercial and residential and allow users to lock a door for both entrance and exits. A door **1204** is partially hollowed out along the edge of the door and a lock body **1200** is inserted into the cavity. The lock body **1200** uses a latch **1206** or similar device to keep the door closed and can be opened by a handle **1208** and unlocked with a key or control system.

[0242] In another embodiment, the door lock system may be used with an exit device, as shown in FIGS. **52A-52B**. Exit devices are door features that allow users to open a door from one side. They are typically installed on the face of a door and includes a push bar to allow a user to easily open the door. The push bar moves a latch so that the door can be opened. Some exit devices can be locked or unlocked for the entrance direction, but the exit direction is always unlocked. As shown in FIG. **52A**, an exit device **1300** is mounted to an interior side of a door **1302**. An interior lock portion **1304** may be mounted in a separate housing from the exit device, as shown. In other embodiments, the interior lock portion **1304** may be formed in the same housing as the exit device. FIG. **52B** shows an exterior lock portion **1306** mounted to the exterior side of the door **1302**.

[0243] In still another embodiment, the door lock system may be used with a deadbolt, as shown in FIG. **53**. Deadbolts operate in a similar fashion to previously mentioned cylinder locks, however instead of a latch and spring, a bolt **1406** is used. The bolt **1406** extends into a strike when the door is locked by a key, handle, or control system physically turning so that the bolt translates into the

strike. FIG. 53 shows an exterior lock portion **1400** with dead bolt assembly **1404** mounted to a door **1402**. In some embodiments, the exterior lock portion may include a handle (not shown), or a handle may be mounted to the door **1402** separate from the door lock system.

[0244] With the above-described devices and methods, a secure and weather sealed door lock system may be configured to fit any typical door regardless of the conventional door thickness and handing requirements. The lock body and interior and exterior handles may be positioned and set to accommodate all door swings, including left, right, left reverse, and right reverse. No tools or disassembly may be required to set and/or reset the handing of the handles.

[0245] It should be understood that the foregoing description of the invention is intended merely to be illustrative thereof and that other embodiments, modifications, and equivalents of the invention are within the scope of the invention recited in the claims appended hereto. Further, the door lock system described above includes various features that may be employed singularly or in any suitable combination.

Claims

1-19. (canceled)

20. A lock portion of an electronic door lock system, the lock portion comprising: a first housing including a backplate having a surface configured to be mounted against a door surface; a second housing extending from the backplate; an actuator disposed in the second housing, the actuator configured to actuate the electronic door lock system between an unlocked state and a locked state; and one or more wires contained within the second housing, wherein the one or more wires are wrapped around a ledge disposed in the second housing to form a wire loop configured to resist removal of the one or more wires from the second housing.

21. The lock portion of claim 20, wherein the one or more wires comprise one or more power wires, wherein the one or more power wires are configured to selectively supply power to the actuator.

22. The lock portion of claim 21, further comprising one or more data wires, wherein a first section of the one or more data wires form part of the wire loop and a second section of the one or more data wires are disposed outside of the second housing.

23. The lock portion of claim 20, wherein the actuator is a solenoid.

24. The lock portion of claim 20, wherein the second housing is formed of metal.

25. The lock portion of claim 20, wherein the second housing comprises a rear surface, wherein the rear surface includes an elongated channel between the second housing and the backplate, wherein the elongated channel is configured to compress a section of the one or more wires between the second housing and the backplate.

26. The lock portion of claim 22, wherein the one or more data wires form part of the wire loop that enters and exits through an opening in the second housing.

27. The lock portion of claim 20, wherein the ledge extends from an inner surface of the second housing.

28. A lock portion of an electronic door lock system, the lock portion comprising: a first housing including a backplate having a first surface and a second surface opposite the first surface, wherein the second surface is configured to be mounted against a door surface; a second housing extending from the backplate; an actuator disposed in the second housing, the actuator configured to actuate the electronic door lock system between an unlocked state and a locked state; and one or more wires contained within the second housing wherein the one or more wires are compressed by a projection in the second housing to secure the one or more wires in the second housing.

29. The lock portion of claim 28, wherein the one or more wires comprise one or more power wires, wherein the one or more power wires are configured to selectively supply power to the actuator.

- 30.** The lock portion of claim 28, wherein the projection extends from a first surface of the second housing.
- 31.** The lock portion of claim 28, wherein the projection compresses the one or more wires against a second surface of the second housing.
- 32.** The lock portion of claim 28, wherein the one or more wires are configured to resist removal from the second housing.
- 33.** The lock portion of claim 28, further comprising a ridge at a top surface of the second housing, the ridge configured to further secure the one or more wires in the second housing.
- 34.** The lock portion of claim 28, wherein the second housing includes a cover secured to the first surface of the backplate, wherein the cover can only be removed by accessing the second surface of the backplate.
- 35.** The lock portion of claim 28, wherein the second housing is disposed within the first housing and attached to the first surface of the backplate, wherein the second housing is secured to the backplate by one or more fasteners that are only accessible from the second surface of the backplate.
-