

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287217

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Alasti; Mehdi et al.

TERRESTRIAL AND NON-TERRESTRIAL NETWORK INTERFERENCE MITIGATION

Abstract

Systems and methods for mitigating terrestrial network downlink transmission interference on non-terrestrial network uplink transmissions or mitigating. The system determines that terrestrial network downlink transmissions for a terrestrial network and non-terrestrial network uplink transmissions for a non-terrestrial network utilize a same frequency band. One or more terrestrial cells of the terrestrial network that are in a coverage area of a non-terrestrial network satellite of the non-terrestrial network are identified. The one or more terrestrial network cells are instructed to utilize at least a first bandwidth utilization scheme for terrestrial network downlink transmissions. And the non-terrestrial network satellite of the non-terrestrial network is instructed to utilize a second bandwidth utilization scheme for non-terrestrial network uplink transmissions, wherein the second bandwidth utilization scheme is different from the first bandwidth utilization scheme.

Inventors: Alasti; Mehdi (Arlington, VA), Sohi; Gurpreet (Parker, CO), Chenumolu; Siddhartha (Ashburn, VA), Gupta; Sourabh (Ashburn, VA)

Applicant: DISH Wireless L.L.C. (Englewood, CO)

Family ID: 1000007783658

Appl. No.: 18/600398

Filed: March 08, 2024

Publication Classification

Int. Cl.: H04W16/14 (20090101); H04W16/30 (20090101); H04W84/06 (20090101)

U.S. Cl.:

CPC H04W16/14 (20130101); H04W16/30 (20130101); H04W84/06 (20130101)

Background/Summary

BACKGROUND

[0001] The use of cellular networks continues to expand and people are becoming more reliant on the speed, efficiency, and uptime of these networks. Advancements in cellular networks has allowed users to connect to a cellular network via a terrestrial network or a non-terrestrial network. But cellular devices are often designed to communicate with the network using specific frequencies, which can result in communication collisions, interference, delayed transmissions, or other communication issues. It is with respect to these and other considerations that the embodiments described herein have been made.

BRIEF SUMMARY

[0002] Briefly, embodiments are directed to systems and methods for mitigating terrestrial network downlink transmission interference on non-terrestrial network uplink transmissions. When terrestrial network downlink transmissions for a terrestrial network and non-terrestrial network uplink transmissions for a non-terrestrial network utilize a same frequency band, one or more bandwidth utilization schemes are selected for one or more terrestrial network cells and for a non-terrestrial network satellite. The one or more terrestrial network cells are instructed to utilize at least a first bandwidth utilization scheme for terrestrial network downlink transmissions. And the non-terrestrial network satellite of the non-terrestrial network is instructed to utilize a second bandwidth utilization scheme for non-terrestrial network uplink transmissions, wherein the second bandwidth utilization scheme is different from the first bandwidth utilization scheme. In some embodiments, the first bandwidth utilization scheme is generated to include a first order in which the one or more terrestrial network cells are to use bandwidth parts; and the second bandwidth utilization scheme is generated to include a second order in which the non-terrestrial network satellite is to use other bandwidth parts.

[0003] In some embodiments, the one or more terrestrial network cells are grouped into a first cluster and a second cluster. The first bandwidth utilization scheme is selected for the first cluster and a third bandwidth utilization scheme is selected for the second cluster. Each terrestrial network cell in the first cluster is instructed to utilize the first bandwidth utilization scheme for terrestrial network downlink transmissions, and each terrestrial network cell in the second cluster is instructed to utilize the third bandwidth utilization scheme for terrestrial network downlink transmissions

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] Non-limiting and non-exhaustive embodiments are described with reference to the following drawings. In the drawings, like reference numerals refer to like parts throughout the various figures unless otherwise specified.

[0005] For a better understanding of the present invention, reference will be made to the following Detailed Description, which is to be read in association with the accompanying drawings:

[0006] FIG. 1 illustrates a context diagram of an environment for employing terrestrial network and non-terrestrial network interference mitigation techniques in accordance with embodiments described herein;

[0007] FIG. 2 is a context diagram of a non-limiting example illustration of an environment with terrestrial network downlink transmission interference on non-terrestrial network uplink transmissions in accordance with embodiments described herein;

[0008] FIGS. 3A-3B are context diagrams of non-limiting example illustrations of techniques for mitigating the interference illustrated in FIG. 2 in accordance with embodiments described herein;

[0009] FIG. 4 illustrates a logical flow diagram showing one embodiment of a process for selecting bandwidth utilization schemes for non-terrestrial and terrestrial network cells to implement the mitigation techniques illustrated in FIGS. 3A-3B in accordance with embodiments described herein;

[0010] FIG. 5 illustrates a logical flow diagram showing one embodiment of a process for a terrestrial network cell to implement a bandwidth utilization scheme selected in FIG. 4 in accordance with embodiments described herein;

[0011] FIG. 6 illustrates a logical flow diagram showing one embodiment of a process for a non-terrestrial network satellite to implement a bandwidth utilization scheme selected in FIG. 4 in accordance with embodiments described herein;

[0012] FIG. 7 is a context diagram of a non-limiting example illustration of an environment with terrestrial network uplink transmission interference on non-terrestrial network uplink transmissions in accordance with embodiments described herein;

[0013] FIGS. 8A-8B are context diagrams of non-limiting example illustrations of techniques for mitigating the interference illustrated in FIG. 7 in accordance with embodiments described herein;

[0014] FIG. 9 illustrates a logical flow diagram showing one embodiment of a process for selecting bandwidth utilization schemes for non-terrestrial and terrestrial network cells to implement the mitigation techniques illustrated in FIGS. 8A-8B in accordance with embodiments described herein;

[0015] FIG. 10 illustrates a logical flow diagram showing one embodiment of a process for a terrestrial network cell to implement a bandwidth utilization scheme selected in FIG. 9 in accordance with embodiments described herein;

[0016] FIG. 11 is a context diagram of a non-limiting example illustration of an environment with terrestrial network downlink transmission interference on non-terrestrial network downlink transmissions in accordance with embodiments described herein;

[0017] FIG. 12 is a context diagram of a non-limiting example illustration of an environment with non-terrestrial network downlink transmission interference on terrestrial network downlink transmissions in accordance with embodiments described herein;

[0018] FIGS. 13A-13B are context diagrams of non-limiting example illustrations of techniques for mitigating the interference illustrated in FIGS. 11-12 in accordance with embodiments described herein;

[0019] FIG. 14 illustrates a logical flow diagram showing one embodiment of a process for selecting bandwidth utilization schemes for non-terrestrial and terrestrial network cells to implement the mitigation techniques illustrated in FIGS. 13A-13B in accordance with embodiments described herein;

[0020] FIG. 15 illustrates a logical flow diagram showing one embodiment of a process for a non-terrestrial network satellite to implement a bandwidth utilization scheme selected in FIG. 14 in accordance with embodiments described herein;

[0021] FIG. 16 illustrates a logical flow diagram showing one embodiment of a process for a border terrestrial network cell to implement a bandwidth utilization scheme selected in FIG. 14 in accordance with embodiments described herein;

[0022] FIGS. 17-19 illustrate logical flow diagrams showing various embodiments of processes for utilizing at least one artificial intelligence mechanism to predict network interference in accordance with embodiments described herein;

[0023] FIG. 20 shows a system diagram that describes one implementation of computing systems for implementing embodiments described herein.

DETAILED DESCRIPTION

[0024] The following description, along with the accompanying drawings, sets forth certain specific details in order to provide a thorough understanding of various disclosed embodiments. However, one skilled in the relevant art will recognize that the disclosed embodiments may be

practiced in various combinations, without one or more of these specific details, or with other methods, components, devices, materials, etc. In other instances, well-known structures or components that are associated with the environment of the present disclosure, including but not limited to the communication systems and networks, have not been shown or described in order to avoid unnecessarily obscuring descriptions of the embodiments. Additionally, the various embodiments may be methods, systems, media, or devices. Accordingly, the various embodiments may be entirely hardware embodiments, entirely software embodiments, or embodiments combining software and hardware aspects.

[0025] Throughout the specification, claims, and drawings, the following terms take the meaning explicitly associated herein, unless the context clearly dictates otherwise. The term “herein” refers to the specification, claims, and drawings associated with the current application. The phrases “in one embodiment,” “in another embodiment,” “in various embodiments,” “in some embodiments,” “in other embodiments,” and other variations thereof refer to one or more features, structures, functions, limitations, or characteristics of the present disclosure, and are not limited to the same or different embodiments unless the context clearly dictates otherwise. As used herein, the term “or” is an inclusive “or” operator, and is equivalent to the phrases “A or B, or both” or “A or B or C, or any combination thereof,” and lists with additional elements are similarly treated. The term “based on” is not exclusive and allows for being based on additional features, functions, aspects, or limitations not described, unless the context clearly dictates otherwise. In addition, throughout the specification, the meaning of “a,” “an,” and “the” include singular and plural references.

[0026] FIG. 1 illustrates a context diagram of an environment **100** for employing terrestrial network and non-terrestrial network interference mitigation techniques in accordance with embodiments described herein. Environment **100** includes a plurality of terrestrial network cells **112a-112c**, a non-terrestrial network satellite **128**, a plurality of user devices **124a-124c**, and a terrestrial network and non-terrestrial network interference mitigation system **102**, which may be in communication via a communication network **110**. Communication network **110** includes one or more wired or wireless networks, which may include a series of smaller or private connected networks that carry information between the terrestrial network cells **112a-112c** and the terrestrial network and non-terrestrial network interference mitigation system **102**.

[0027] The user devices **124a-124c** are computing devices that receive and transmit cellular communication messages or data with the terrestrial network cells **112a-112c** or the non-terrestrial network satellite **128**. The user devices **112a-112c** may include any combination of user devices that are configured to communicate with only terrestrial network cells **112a-112c**, are configured to communicate with only non-terrestrial network satellite **128**, or are configured to communicate with both the terrestrial network cells **112a-112c** and the non-terrestrial network satellite **128**.

Examples of user devices **124a-124c** may include, but are not limited to, mobile devices, smartphones, tablets, cellular-enabled laptop computers, very small aperture terminals (VSAT), Earth station in motion (ESIM), or other computing devices that can communication with a cellular network. User devices **124a-124c** that are connected to or in communication with a terrestrial network cell **112** may be referred to as terrestrial user devices, and user devices **124a-124c** that are connected to or in communication with a non-terrestrial network satellite **128** may be referred to as non-terrestrial user devices. Although FIG. 1 shows three user devices **124a-124c**, embodiments are not so limited. Rather, one user device or a plurality of user devices may be employed.

[0028] The terrestrial network cells **112a-112c** are ground-based cellular towers that together provide the hardware infrastructure of a terrestrial network or a terrestrial cellular communications network. The terrestrial network cells **112a-112c** may be individually referred to as a terrestrial network cell **112** or collectively referred to as terrestrial network cells **112**. The non-terrestrial network satellite **128** is a satellite-based cellular system or satellite that provides the hardware infrastructure of a non-terrestrial network or a non-terrestrial cellular communications network. In some embodiments or situations, the non-terrestrial network satellite **128** may also be referred to as

a non-terrestrial network cell or as a non-terrestrial network payload depending on the architecture, configuration, or deployment of the non-terrestrial network. In some embodiments, a non-terrestrial network in 3GPP may refer to or include geostationary (GEO) satellites, low Earth orbit (LEO) satellites, or medium Earth orbit (MEO) satellites, or high-altitude platform stations (HAPS). The terrestrial network cells **112a-112c** and the non-terrestrial network satellite **128** may include or be in communication with base stations, radio back haul equipment, antennas, or other devices, which are not illustrated for ease of discussion. Although FIG. **1** shows three terrestrial network cells **112a-112c**, embodiments are not so limited. Rather, one terrestrial network cell or a plurality of terrestrial network cells may be employed. Similarly, although FIG. **1** shows one non-terrestrial network satellite **128**, embodiments are not so limited. Rather, one non-terrestrial network satellite or a plurality of non-terrestrial network satellites may be employed.

[0029] The terrestrial network and the non-terrestrial network supported by the terrestrial network cells **112a-112c** and the non-terrestrial network satellite **128** may be collectively referred to as a cellular communications network (also referred to as a wireless network), e.g., a 5G cellular communications network. Although embodiments are described herein with the terrestrial network and the non-terrestrial network being part of a collective cellular network, embodiments are not so limited. Embodiments described herein may also be employed in environments where the terrestrial network and the non-terrestrial network are separate, independent networks.

[0030] Terrestrial network cells **112** and the non-terrestrial network satellite **128** provide compatible cellular communications over a coverage area. The coverage area of each terrestrial network cell **112** may vary depending on the elevation antenna of the terrestrial network cell, the height of the antenna of the terrestrial network cell above the ground, the electrical tilt of the antenna, the transmit power utilized by the terrestrial network cell, or other capabilities that can be different from one type of terrestrial network cell to another or from one type of hardware to another. Likewise, the coverage area of the non-terrestrial network satellite **128** may vary depending on the orbit or position of the non-terrestrial network satellite, the elevation angle of the non-terrestrial network satellite, the transmit power utilized by the non-terrestrial network satellite, or other hardware capabilities of the non-terrestrial network satellite. The overall capacity of the terrestrial network created by the terrestrial network cells **112a-112c** and the non-terrestrial network created by the non-terrestrial network satellite **128** depends on the coverage of each cell and the interference that the cells may have on each other.

[0031] In various embodiments, a group of terrestrial network cells **112a-112c** that make up the cellular communication network may be referred to as a “market.” A market may be for a particular city, neighborhood, geographical area, or other selected or specified cluster of cells. Similarly, a non-terrestrial network satellite **128** may have a coverage area that includes one or more markets of terrestrial network cells, and in many situations, the coverage area of the non-terrestrial network satellite **128** is much larger than a particular market for a group of terrestrial network cells. In situations where the coverage area of a terrestrial network cell overlaps (or borders) the coverage area of a non-terrestrial network satellite, the various techniques described herein may be employed to mitigate interference between the cells.

[0032] The terrestrial network and non-terrestrial network interference mitigation system **102** is configured to perform embodiments described herein to select specific bandwidth utilization schemes to be utilized by the terrestrial network cells **112a-112c** and the non-terrestrial network satellite **128** depending on the interference. The terrestrial network and non-terrestrial network interference mitigation system **102** then instructs the terrestrial network cells **112a-112c** and the non-terrestrial network satellite **128** to utilize the specific bandwidth utilization scheme selected for that cell. The terrestrial network cells **112a-112c** and the non-terrestrial network satellite **128** are configured to utilize or employ the specific bandwidth utilization scheme in which they are instructed to use.

[0033] FIG. **2** is a context diagram of a non-limiting example illustration of an environment **200**

where terrestrial network downlink transmission interference on non-terrestrial network uplink transmissions in accordance with embodiments described herein.

[0034] Environment **200** includes a non-terrestrial network satellite **228**, terrestrial network cells **212a-212c**, and user devices **224a-224e**, which may be embodiments, of the non-terrestrial network satellite **128**, the terrestrial network cells **112a-112c**, and the user devices **124a-124c** in FIG. **1**, respectively. These elements are given separate reference numbers for ease of illustration. The terrestrial network cells **212a-212c** have respective coverage areas **210a-210c**, which at least partially overlap the coverage area **214** of the non-terrestrial network satellite **228**.

[0035] In this illustration, the non-terrestrial network satellite **228** is utilizing non-terrestrial network uplink transmission **206** to receive data from user device **224d**. And the terrestrial network cells **212a**, **212b**, and **212c** are utilizing terrestrial network downlink transmissions **208a**, **208b**, and **208c** to transmit data to user devices **224a**, **224b**, and **224c**, respectively. These terrestrial network downlink transmissions utilized by the terrestrial network cells **212a**, **212b**, and **212c** may cause interference **204a**, **204b**, and **204c**, respectively, on the non-terrestrial network uplink transmission **206** received by the non-terrestrial network satellite **228**.

[0036] FIGS. **3A-3B** are context diagrams of non-limiting example illustrations of techniques for mitigating the interference illustrated in FIG. **2** in accordance with embodiments described herein. Environment **300A** in FIG. **3A** is an embodiment of environment **200** in FIG. **2**, but with only terrestrial network cell **212a**, non-terrestrial network satellite **228**, and user devices **224a** and **224e** being illustrated. Environment **300A** also include user device **224e**.

[0037] To reduce the terrestrial network downlink transmission interference **204a** on the non-terrestrial network uplink transmissions **206**, the coverage area **210a** of the terrestrial network cell **212a** is divided into multiple regions. In this illustration a first region **340** is closest to the terrestrial network cell **212a** and a second region **342** is further away from the terrestrial network cell **212a** compared to the first region **340**. In some embodiments, the first region **340** may be referred to as an inner coverage area of the terrestrial network cell **212a** and the second region **342** may be referred to as an outer coverage area of the terrestrial network cell **212a**.

[0038] In some embodiments, the first region **340** and second region **342** may be defined as specific geographic areas relative to the terrestrial network cell **212a**. In other embodiments, the first region **340** and second region **342** may be defined by other location or positioning indicators, such as ranges of CQIs. Although FIG. **3A** illustrates two regions, embodiments are not so limited. For example, three or more regions may also be defined for separate bandwidth part select schemes.

[0039] By dividing the coverage area **210a** into multiple regions **340** and **342**, the terrestrial network cell **212** can utilize separate bandwidth utilization schemes for terrestrial network downlink transmissions to user devices **224a** and **224e**. For example, the terrestrial network cell **212a** can utilize less transmit power for terrestrial network downlink transmission **208e** to transmit data to user device **224e**. But the terrestrial network cell **212a** can select specific bandwidth parts (BWPs) for terrestrial network downlink transmission **208a** to transmit data to user device **224a**. Likewise, the non-terrestrial network satellite **228** can select specific bandwidth parts for non-terrestrial network uplink transmission **206** to receive data from user device **224d**, where these specific bandwidth parts are selected in a different order than the specific bandwidth parts selected by the terrestrial network cell **212a**, which is illustrated in FIG. **3B**.

[0040] FIG. **3B** illustrates bandwidth utilization schemes **300B**. In particular, the terrestrial and non-terrestrial networks have a total bandwidth spectrum **350** available. Terrestrial network cells are instructed to utilize bandwidth utilization scheme **356**, and non-terrestrial network satellite is instructed to utilize bandwidth utilization scheme **358**.

[0041] When transmitting data to user devices within the outer region of a terrestrial cell's coverage area, i.e., terrestrial user devices having a low CQI, the terrestrial network cell can assign lower bandwidth parts **252a** for terrestrial network downlink transmissions to those user devices based on

the bandwidth utilization scheme **356**. For user devices within the inner region of a terrestrial cell's coverage area, i.e., terrestrial user devices having a high CQI, the terrestrial network cell can assign all bandwidth parts **252c** for terrestrial network downlink transmissions to those user devices based on the bandwidth utilization scheme **358**, but transmit with lower transmit power. And for user devices having low-CQIs or mid-CQIs, the terrestrial network cell can assign lower and middle bandwidth parts **252b** for terrestrial network downlink transmissions to those user devices. [0042] Conversely, the non-terrestrial network satellite can assign bandwidth parts for non-terrestrial network uplink transmissions from non-terrestrial user devices based on the non-terrestrial network satellite bandwidth utilization scheme **358**. For example, higher bandwidth parts **354a** can be assigned for high priority data, higher and medium bandwidth parts **354b** can be assigned for medium priority data, and all bandwidth parts **354c** can be assigned for low priority data.

[0043] Although the non-terrestrial network satellite bandwidth utilization scheme illustrates higher bandwidth parts for high priority data and the terrestrial network cell bandwidth utilization scheme illustrates lower bandwidth parts for lower CQI user devices, embodiments are not so limited. For example, in some embodiments, the non-terrestrial network satellite bandwidth utilization scheme may utilize lower bandwidth parts for high priority data and the terrestrial network cell bandwidth utilization scheme may utilize higher bandwidth parts for lower CQI user devices.

[0044] In some embodiments, the bandwidth parts described throughout the description and figures may be one or more physical resource blocks (PRB), where each PRB is a section or band of frequency spectrum for a given amount of time (e.g., during a transmission time slot) that user devices or cells can utilize to transmit data to one another. The selection of specific bandwidth parts may also be referred to as a PRB allocation scheme or strategy to allocate specific PRBs.

[0045] The operation of certain aspects will now be described with respect to FIGS. **4-6**.

[0046] FIG. **4** illustrates a logical flow diagram showing one embodiment of a process **400** for selecting bandwidth utilization schemes for non-terrestrial and terrestrial network cells to implement the mitigation techniques illustrated in FIGS. **3A-3B** in accordance with embodiments described herein. In at least one of various embodiments, process **400** may be implemented by or executed via circuitry or on one or more computing devices, such as terrestrial network and non-terrestrial network interference mitigation system **102** in FIG. **1**, or one or more terrestrial or non-terrestrial cells.

[0047] Process **400** begins, after a start block, at block **402**, where the system determines that terrestrial network downlink transmissions and non-terrestrial network uplink transmissions utilize a same frequency spectrum. In some embodiments, this determination is based on the capabilities of user devices being able to access both the terrestrial and non-terrestrial network using the same frequency spectrum. In other embodiments, this determination is based on the terrestrial and non-terrestrial networks attempting to communicate with user devices using the same frequency spectrum.

[0048] Process **400** proceeds after block **402** to block **404**, where terrestrial network cells located within (or have a coverage area partially overlapping) a non-terrestrial network coverage area are identified. In some embodiments, the terrestrial network cells may be identified based on their geographic location and their known or expected coverage area (e.g., based on the antenna or radio hardware, height, etc.), which can then be compared to the known or expected coverage area of a non-terrestrial network satellite. If the coverage area of a terrestrial network cell at least partially overlaps the coverage area of the non-terrestrial network satellite, then that terrestrial network cell is identified.

[0049] Process **400** continues after block **404** at block **405**, where the identified terrestrial network cells are grouped into a plurality of different clusters. In some embodiments, the terrestrial network cells may be grouped such that the coverage area of each terrestrial network cell in a cluster is adjacent to or partially overlaps the coverage area of at least one other terrestrial network cell in the

same cluster. In other embodiments, the terrestrial network cells may be grouped such that the coverage area of each terrestrial network cell in a cluster is not adjacent to nor partially overlaps the coverage area of at least one other terrestrial network cell in the same cluster. In various embodiments, the number of identified terrestrial network cells in a cluster may be set or selected by an administrator.

[0050] Process **400** proceeds after block **405** to block **406**, where a cluster of terrestrial network cells is selected. In various embodiments, each cluster is selected and processed such that a bandwidth utilization scheme is selected for each terrestrial network cell in each cluster.

[0051] Process **400** continues after block **406** at block **408**, where a first bandwidth utilization scheme is selected for the selected cluster of terrestrial network cells. The first bandwidth utilization scheme defines which bandwidth parts the terrestrial network cells of that cluster are to utilize for terrestrial network downlink transmissions, which is described in more detail in conjunction with FIGS. 3A-3B and FIG. 5. In some embodiments, the first bandwidth utilization scheme also indicates how the terrestrial network cells in the cluster are to divide their coverage area into multiple regions.

[0052] In various embodiments, the first bandwidth utilization scheme may also schedule the SSBs (synchronization signal block) of the terrestrial network cells in selected cluster such that they are at different time-slots or in frequency domains from the terrestrial network cells in other clusters.

[0053] Process **400** proceeds next after block **408** to block **410**, where terrestrial network cells of the selected cluster are instructed to utilize the first bandwidth utilization scheme. In some embodiments, each terrestrial network cell may store a plurality of different possible bandwidth utilization schemes. An indication of the first bandwidth utilization scheme is then transmitted to the terrestrial network cells, such that the terrestrial network cells can select the previously-stored bandwidth utilization scheme that matches the first bandwidth utilization scheme. In other embodiments, the details of the first bandwidth utilization scheme are transmitted to the terrestrial network cells.

[0054] Process **400** continues next after block **410** at decision block **412**, where a determination is made whether another cluster of terrestrial network cells is selected. In various embodiments, each cluster is sequentially selected so that each cluster is selected. If another cluster of terrestrial network cells is to be selected, process **400** loops to block **406** to select another cluster; otherwise, process **400** flows to block **414**.

[0055] At block **414**, a second bandwidth utilization scheme is selected for the non-terrestrial network satellite. The second bandwidth utilization scheme defines which bandwidth parts the non-terrestrial network satellite is to utilize for non-terrestrial network uplink transmissions, which is described in more detail in conjunction with FIGS. 3A-3B and FIG. 6.

[0056] Process **400** proceeds after block **414** to block **416**, where the non-terrestrial network satellite is instructed to utilize the second bandwidth utilization scheme. In some embodiments, the non-terrestrial network satellite may store a plurality of different possible bandwidth utilization schemes. An indication of the second bandwidth utilization scheme is then transmitted to the non-terrestrial network satellite, such that the non-terrestrial network satellite can select the previously-stored bandwidth utilization scheme that matches the second bandwidth utilization scheme. In other embodiments, the details of the second bandwidth utilization scheme are transmitted to the non-terrestrial network satellite.

[0057] After block **416**, process **400** terminates or otherwise returns to a calling process to perform additional actions.

[0058] FIG. 5 illustrates a logical flow diagram showing one embodiment of a process **500** for a terrestrial network cell to implement a bandwidth utilization scheme selected in FIG. 4 in accordance with embodiments described herein. In at least one of various embodiments, process **500** may be implemented by or executed via circuitry or on one or more computing devices, such as terrestrial network cell **112** in FIG. 1.

[0059] Process **500** begins, after a start block, at block **502**, where a bandwidth utilization scheme is received for the target terrestrial network cell to utilize for terrestrial network downlink transmissions. In various embodiments, this bandwidth utilization scheme is the first bandwidth utilization scheme that the target terrestrial network cell is instructed to use at block **410** in FIG. **4**.

[0060] Process **500** proceeds after block **502** to block **504**, where an SSB schedule is utilized to connect with user devices in the coverage area of the target terrestrial network cell. In various embodiments, the SSB schedule is defined in the received bandwidth utilization schedule.

[0061] Process **500** continues after block **504** at block **506**, where the coverage area of the target terrestrial network cell is divided into a plurality of regions. As described herein, e.g., in FIG. **3A**, the coverage area may be divided into an inner coverage area and an outer coverage area.

[0062] Process **500** proceeds next after block **506** at block **508**, where CQIs (channel quality indicator) for user devices connected to the target terrestrial network cell are obtained. In at least one embodiment, the CQI data provides an indication of how far away the user devices are from the target terrestrial network cell. In other embodiments, other location/distance indicators, such as GPS or other location/positioning information, may be obtained from the user devices.

[0063] Process **500** continues next after block **508** to decision block **510**, where a determination is made whether the target terrestrial network cell has data to transmit to a user device. If the target terrestrial network cell has data to transmit to the user device, then process **500** proceeds to decision block **512**; otherwise, process **500** loops to block **508** to obtain additional CQIs (or other location/distance/positioning indicators or information) for user devices and to determine if the target terrestrial network cell has data to transmit to a user device.

[0064] At decision block **512**, a determination is made whether the user device is located in a region closer to the target terrestrial network cell or a further away region based on the obtained CQI for that user device. In various embodiments, the CQI data, or other location/distance indicators (e.g., GPS or other location/positioning information), may be compared to the various regions of the coverage area of the target terrestrial network cell. If the user device is located in a region closer to the target terrestrial network cell, then process **500** flows to block **514**; otherwise, process **500** flows to block **516**.

[0065] At block **514**, the target terrestrial network cell transmits data to the user device using reduced transmit power. In some embodiments, the level in which the transmit power is reduced may be determined by how far away the user device is from the target terrestrial network cell. In other embodiments, the reduced transmit power may be a selected or predetermined level. After block **514**, process **500** terminates or otherwise returns to a calling process to perform other actions.

[0066] If, at decision block **512**, the user device is not located in a region closer to the target terrestrial network cell, then process **500** flows from decision block **512** to block **516**. At block **516**, a bandwidth part is selected for the data transmission based on the received bandwidth utilization scheme. As discussed in FIG. **3B**, different bandwidth parts may be utilized for transmitting data to user devices at various different distances away from the target terrestrial network cell.

[0067] Process **500** proceeds after block **516** at block **518**, where the target terrestrial network cell transmits data to the user device using the selected bandwidth part. After block **518**, process **500** terminates or otherwise returns to a calling process to perform other actions.

[0068] Although process **500** is illustrated as terminating or ending, embodiments are not so limited. In some embodiments, process **500** may loop after block **514** or block **518** to block **508** to obtain additional CQIs (or other location/distance/positioning indicators or information) for user devices and to determine if the target terrestrial network cell has data to transmit to a user device.

[0069] Moreover, in some embodiments, block **504** may be optional and may not be employed, or it may be employed separately. For example, process **500** may employ blocks **502**, **506**, **508**, **510**, **512**, **514**, **516**, and **518** to utilize separate bandwidth parts without utilizing the SSB scheduling. In other embodiments, process **500** may employ blocks **502** and **504** alone without the other

illustrated blocks. In this way, SSB scheduling of different terrestrial network cells at different timeslots can be utilized to prevent the SSBs from those terrestrial network cells appearing at the same time and combining to create a higher interference for the non-terrestrial network satellite. Thus, the SSB scheduling and the bandwidth utilization (BWP) management described in FIG. 5 may be performed together or independent from one another.

[0070] FIG. 6 illustrates a logical flow diagram showing one embodiment of a process **600** for a non-terrestrial network satellite to implement a bandwidth utilization scheme selected in FIG. 4 in accordance with embodiments described herein. In at least one of various embodiments, process **600** may be implemented by or executed via circuitry or on one or more computing devices, such as non-terrestrial network satellite **128** in FIG. 1.

[0071] Process **600** begins, after a start block, at block **602**, where a bandwidth utilization scheme is received for the non-terrestrial network satellite to utilize for non-terrestrial network uplink transmissions. In various embodiments, this bandwidth utilization scheme is the second bandwidth utilization scheme that the non-terrestrial network satellite is instructed to use at block **416** in FIG. 4

[0072] Process **600** proceeds after block **602** at decision block **604**, where a determination is made whether the non-terrestrial network satellite is to receive data from a user device. If the non-terrestrial network satellite is to receive communications or data from a user device, then process **600** flows to block **606**; otherwise, process **600** loops to decision block **604** to wait until the non-terrestrial network satellite is to receive data from a user device.

[0073] At block **606**, the non-terrestrial network satellite instructs the user device to transmit the data to the non-terrestrial network satellite using selected bandwidth parts abased on a priority of the data and the received bandwidth utilization scheme. As discussed in FIG. 3B, the user device may transmit to the non-terrestrial network satellite high priority data using a high bandwidth parts, medium priority using high and middle bandwidth parts, and low priority data using any bandwidth part.

[0074] After block **606**, process **600** terminates or otherwise returns to a calling process to perform other actions. Although process **600** is illustrated as terminating or ending, embodiments are not so limited. In some embodiments, process **600** may loop after block **606** to decision block **604** determine additional data is to be received from the user device or if data is to be received from another user device.

[0075] FIG. 7 is a context diagram of a non-limiting example illustration of an environment **700** with terrestrial network uplink transmission interference on non-terrestrial network uplink transmissions in accordance with embodiments described herein.

[0076] Environment **700** includes a non-terrestrial network satellite **728**, a terrestrial network cell **712**, and user devices **724a-724c**, which may be embodiments, of the non-terrestrial network satellite **128**, the terrestrial network cells **112a-112c**, and the user devices **124a-124c** in FIG. 1, respectively. These elements are given separate reference numbers for ease of illustration. The terrestrial network cell **712** has a coverage area **710**, which at least partially overlap the coverage area (not illustrated) of the non-terrestrial network satellite **728**.

[0077] In this illustration, the terrestrial network cell **712** is utilizing non-terrestrial network uplink transmissions **708a-708b** to receive data from user device **724a-724b**. These terrestrial network uplink transmissions may cause interference **704a** and **707b** on non-terrestrial network uplink transmissions **706** received by the non-terrestrial network satellite **728** from user device **724c**.

[0078] FIGS. 8A-8B are context diagrams of non-limiting example illustrations of techniques for mitigating the interference illustrated in FIG. 7 in accordance with embodiments described herein. Environment **800A** in FIG. 8A is an embodiment of environment **700** in FIG. 7.

[0079] To reduce the terrestrial network uplink transmission interference **704a** and **704b** on the non-terrestrial network uplink transmissions **706**, the coverage area **710** of the terrestrial network cell **712** is divided into multiple regions. In this illustration a first region **840** is closest to the tower

(or antenna) of the terrestrial network cell **712** and a second region **842** is further away from the down (or antenna) of the terrestrial network cell **712** compared to the first region **840**. In some embodiments, the first region **840** may be referred to as an inner coverage area of the terrestrial network cell **712** and the second region **842** may be referred to as an outer coverage area of the terrestrial network cell **712**. In some embodiments, the first region **840** and the second region **842** may cover the same or similar areas to the first region **340** and the second region **342** in FIG. 3A. In other embodiments, the first region **840** and the second region **842** may cover different areas from the first region **340** and the second region **342** in FIG. 3A.

[0080] In some embodiments, the first region **840** and second region **842** may be defined as specific geographic areas relative to the tower or antenna of the terrestrial network cell **712**. In other embodiments, the first region **840** and second region **842** may be defined by other location or positioning indicators, such as ranges of CQIs. Although FIG. 8A illustrates two regions, embodiments are not so limited. For example, three or more regions may also be defined for separate bandwidth part select schemes.

[0081] By dividing the coverage area **710** into multiple regions **840** and **842**, the terrestrial network cell **712** can utilize separate bandwidth utilization schemes for terrestrial network uplink transmissions from user devices **724a** and **724b**. For example, the terrestrial network cell **712** can instruct user device **724a** in the first region **840** to use all available bandwidth parts for terrestrial network uplink transmission **708a**. But the terrestrial network cell **712** can instruct user device **724b** in the second region **842** to use specific bandwidth parts (BWPs) for terrestrial network uplink transmissions **708b**. Likewise, the non-terrestrial network satellite **228** can instruct non-terrestrial user device **724c** to use specific bandwidth parts for non-terrestrial network uplink transmission **706** to receive data from user device **724c**, where these specific bandwidth parts are selected in a different order than the specific bandwidth parts selected by the terrestrial network cell **712**, which is illustrated in FIG. 8B.

[0082] FIG. 8B illustrates bandwidth utilization schemes **800B**. In particular, the terrestrial and non-terrestrial networks have a total bandwidth spectrum **850** available. Terrestrial network cells are instructed to utilize bandwidth utilization scheme **856**, and non-terrestrial network satellite is instructed to utilize bandwidth utilization scheme **858**.

[0083] When communicating with user devices within the outer region of a terrestrial cell's coverage area, e.g., terrestrial user devices having a low CQI, the terrestrial network cell can instruct those user devices to use higher bandwidth parts **852b** for terrestrial network uplink transmissions based on the bandwidth utilization scheme **856**. For user devices within the inner region of a terrestrial cell's coverage area, e.g., terrestrial user devices having a high CQI, the terrestrial network cell can instruct those user devices to use all available bandwidth parts **252a** for terrestrial network uplink transmissions based on the bandwidth utilization scheme **858**.

[0084] Conversely, the non-terrestrial network satellite can instruct non-terrestrial user devices to use lower bandwidth parts for non-terrestrial network uplink transmissions based on the non-terrestrial network satellite bandwidth utilization scheme **358**.

[0085] Although the non-terrestrial network satellite bandwidth utilization scheme illustrates lower bandwidth parts for non-terrestrial user devices and the terrestrial network cell bandwidth utilization scheme illustrates higher bandwidth parts for lower CQI user devices, embodiments are not so limited. For example, in some embodiments, the non-terrestrial network satellite bandwidth utilization scheme may utilize higher bandwidth parts for non-terrestrial user devices and the terrestrial network cell bandwidth utilization scheme may utilize lower bandwidth parts for lower CQI user devices.

[0086] The operation of certain aspects will now be described with respect to FIGS. 9-10.

[0087] FIG. 9 illustrates a logical flow diagram showing one embodiment of a process **900** for selecting bandwidth utilization schemes for non-terrestrial and terrestrial network cells to implement the mitigation techniques illustrated in FIGS. 8A-8B in accordance with embodiments

described herein. In at least one of various embodiments, process **900** may be implemented by or executed via circuitry or on one or more computing devices, such as terrestrial network and non-terrestrial network interference mitigation system **102** in FIG. **1**, or one or more terrestrial or non-terrestrial cells.

[0088] Process **900** begins, after a start block, at block **902**, where the system determines that terrestrial network uplink transmissions and non-terrestrial network uplink transmissions utilize a same frequency spectrum. In some embodiments, this determination is based on the capabilities of user devices being able to access both the terrestrial and non-terrestrial network using the same frequency spectrum. In other embodiments, this determination is based on the terrestrial and non-terrestrial networks attempting to communicate with user devices using the same frequency spectrum.

[0089] Process **900** proceeds after block **902** at block **904**, where a coverage area of a target terrestrial network cell is determined. In some embodiments, the coverage area may be known or estimated based on the capabilities of the terrestrial network cell hardware. In other embodiments, an administrator may set or define the coverage area of the target terrestrial network cell.

[0090] Process **900** continues after block **904** to block **906**, where a first bandwidth utilization scheme is selected for user devices outside the terrestrial network cell coverage area. This first bandwidth utilization scheme is selected for non-terrestrial network uplink transmissions from non-terrestrial user devices. The first bandwidth utilization scheme defines which bandwidth parts the non-terrestrial user devices are to utilize for non-terrestrial network uplink transmissions to a non-terrestrial network satellite, which is described in more detail in conjunction with FIGS. **8A-8B**.

[0091] Process **900** proceeds after block **906** to block **908**, where the non-terrestrial network satellite is instructed to utilize the first bandwidth utilization scheme. In some embodiments, the non-terrestrial network satellite forwards, or otherwise communicates, the first bandwidth utilization scheme to the non-terrestrial user devices. In other embodiments, the non-terrestrial network satellite informs the non-terrestrial user devices which bandwidth parts to use for non-terrestrial network uplink transmissions. In various embodiments, the non-terrestrial user devices may store a plurality of different possible bandwidth utilization schemes. The non-terrestrial network satellite can then transmit an indication of the first bandwidth utilization scheme to the non-terrestrial user devices.

[0092] Process **900** continues after block **908** at block **910**, where a second bandwidth utilization scheme is selected for user devices within the target terrestrial network cell coverage area. The second bandwidth utilization scheme defines which bandwidth parts the terrestrial user devices are to utilize for terrestrial network uplink transmissions, which is described in more detail in conjunction with FIGS. **8A-8B** and FIG. **10**. In some embodiments, the second bandwidth utilization scheme also indicates how the target terrestrial network cell is to divide its coverage area into multiple regions.

[0093] Process **900** proceeds after block **910** to block **912**, where the target terrestrial network cell is instructed to utilize the second bandwidth utilization scheme. In some embodiments, the terrestrial network cell forwards, or otherwise communicates, the second bandwidth utilization scheme to the terrestrial user devices. In other embodiments, the terrestrial network cell informs the terrestrial user devices which bandwidth parts to use for terrestrial network uplink transmissions. In various embodiments, the terrestrial user devices may store a plurality of different possible bandwidth utilization schemes. The terrestrial network cell can then transmit an indication of the second bandwidth utilization scheme to the terrestrial user devices.

[0094] After block **912**, process **900** terminates or otherwise returns to a calling process to perform additional actions.

[0095] FIG. **10** illustrates a logical flow diagram showing one embodiment of a process **1000** for a terrestrial network cell to implement a bandwidth utilization scheme selected in FIG. **9** in accordance with embodiments described herein. In at least one of various embodiments, process

1000 may be implemented by or executed via circuitry or on one or more computing devices, such as terrestrial network cell **112** in FIG. **1**.

[0096] Process **1000** begins, after a start block, at block **1002**, where a bandwidth utilization scheme is received for the target terrestrial network cell to utilize for terrestrial network uplink transmissions from terrestrial user devices. In various embodiments, this bandwidth utilization scheme is the second bandwidth utilization scheme that the target terrestrial network cell is instructed to use at block **912** in FIG. **9**.

[0097] Process **1000** proceeds after block **1002** to block **1004**, where the coverage area of the target terrestrial network cell is divided into a plurality of regions. As described herein, e.g., in FIG. **8A**, the coverage area may be divided into an inner coverage area and an outer coverage area.

[0098] Process **1000** continues after block **1004** at block **1006**, where a terrestrial user device connected to the target terrestrial network cell is selected. In various embodiments, each terrestrial user device connected to the target terrestrial network cell is sequentially selected and instructed which bandwidth part to use for terrestrial network uplink transmissions.

[0099] Process **1000** proceeds next after block **1006** at block **1008**, where CQIs (channel quality indicator) for user devices connected to the target terrestrial network cell are obtained. In various embodiments, block **1008** may employ embodiments of block **508** in FIG. **5** to obtain CQI data from terrestrial user devices. Similar to block **508**, other location/distance indicators, such as GPS or other location/positioning information, may be obtained from the user devices.

[0100] Process **1000** continues next after block **1008** to decision block **1010**, where a determination is made whether the selected user device is located in a region closer to the target terrestrial network cell or a further away region based on the obtained CQI (or other location/distance indicators) for that user device. In various embodiments, the CQI data, or other location/positioning information, may be compared to the various regions of the coverage area of the target terrestrial network cell. If the selected user device is located in a region closer to the target terrestrial network cell, then process **1000** flows to block **1012**; otherwise, process **1000** flows to block **1016**.

[0101] At block **1012**, the target terrestrial network cell transmits instructs the selected user device to transmit data to the target terrestrial cell using any available bandwidth part. After block **1012**, process **1000** flows to decision block **1014**.

[0102] If, at decision block **1010**, the selected user device is not located in a region closer to the target terrestrial network cell, then process **1000** flows from decision block **1010** to block **1016**. At block **1016**, a bandwidth part is selected for the user device to use for terrestrial network uplink transmission based on the received bandwidth utilization scheme, as illustrated in FIG. **8B**.

[0103] Process **1000** proceeds after block **1016** at block **1018**, where the target terrestrial network cell instructs the selected user device to transmit data to the target terrestrial network cell using the selected bandwidth part. After block **1018**, process **1000** flows to decision block **1014**.

[0104] At decision block **1014**, a determination is made whether another user device is selected. In various embodiments, each terrestrial user device connected to the target terrestrial network cell is selected and instructed on which bandwidth parts to use for terrestrial network uplink transmissions. If another user device is to be selected, process **1000** loops to block **1006**; otherwise, process **1000** terminates or otherwise returns to a calling process to perform other actions.

[0105] Although process **1000** is illustrated as terminating or ending, embodiments are not so limited. In some embodiments, process **1000** may continually loop to block **1006** to select terrestrial user devices as new devices enter the coverage area of the target terrestrial network cell.

[0106] FIG. **11** is a context diagram of a non-limiting example illustration of an environment **11** with terrestrial network downlink transmission interference on non-terrestrial network downlink transmissions in accordance with embodiments described herein;

[0107] Environment **1100** includes a non-terrestrial network satellite **1128**, terrestrial network cells **1112a-1112c**, and user devices **1124a-1124d**, which may be embodiments, of the non-terrestrial network satellite **128**, the terrestrial network cells **112a-112c**, and the user devices **124a-124c** in

FIG. 1, respectively. These elements are given separate reference numbers for ease of illustration. The terrestrial network cells **1112a-1112c** have respective coverage areas **1110a-1110c**, which at least partially overlap the coverage area **1114** of the non-terrestrial network satellite **1128**. [0108] In this illustration, the non-terrestrial network satellite **1128** is utilizing non-terrestrial network downlink transmission **1106** to transmit data to user device **1124d**. And the terrestrial network cells **1112a**, **1112b**, and **1112c** are utilizing terrestrial network downlink transmissions **1108a**, **1108b**, and **1108c** to transmit data to user devices **1124a**, **1124b**, and **1124c**, respectively. These terrestrial network downlink transmissions utilized by the terrestrial network cells **1112a**, **1112b**, and **1112c** may cause interference **1104a**, **1104b**, and **1104c**, respectively, on the non-terrestrial network downlink transmission **1106** transmitted by the non-terrestrial network satellite **1128** to the user device **1124d**. In this situation, an exclusion zone **1130** is generated or defined to mitigate the interference.

[0109] FIG. 12 is a context diagram of a non-limiting example illustration of an environment **1200** with non-terrestrial network downlink transmission interference on terrestrial network downlink transmissions in accordance with embodiments described herein. Environment **1200** may be similar to environment **1100** in FIG. 11, but with different interference implications.

[0110] Environment **1200** includes a non-terrestrial network satellite **1228**, terrestrial network cells **1212a-1212c**, and user devices **1224a-1224d**, which may be embodiments, of the non-terrestrial network satellite **128**, the terrestrial network cells **112a-112c**, and the user devices **124a-124c** in FIG. 1, respectively. These elements are given separate reference numbers for ease of illustration. The terrestrial network cells **1212a-1212c** have respective coverage areas **1210a-1210c**, which at least partially overlap the coverage area **1214** of the non-terrestrial network satellite **1228**.

[0111] In this illustration, the non-terrestrial network satellite **1228** is utilizing non-terrestrial network downlink transmission **1206** to transmit data to user device **1224d**. And the terrestrial network cells **1212a**, **1212b**, and **1212c** are utilizing terrestrial network downlink transmissions **1208a**, **1208b**, and **1208c** to transmit data to user devices **1224a**, **1224b**, and **1224c**, respectively. The non-terrestrial network downlink transmission utilized by the non-terrestrial network satellite **1228** may cause interference **1204a**, **1204b**, and **1204c**, respectively, on the terrestrial network downlink transmissions transmitted by the terrestrial network cells **1212a-1212c** to the user devices **1212a-1212c**.

[0112] FIGS. 13A-13B are context diagrams of non-limiting example illustrations of techniques for mitigating the interference illustrated in FIGS. 11-12 in accordance with embodiments described herein. Environment **1300A** in FIG. 13A is an embodiment of environment **1100** in FIG. 11 and environment **1200** in FIG. 12. For ease of illustration, environment **1300A** is illustrated with non-terrestrial network satellite **1328**, terrestrial network cells **1308a-1308g**, and user device **1324a-1324b**.

[0113] To reduce the terrestrial network downlink transmission interference on non-terrestrial network downlink transmissions and the non-terrestrial network downlink transmission interference on terrestrial network downlink transmissions, as discussed in FIGS. 11 and 12, an exclusion zone **1340** is defined or generated for a specific market or group of terrestrial network cells **1308a-1308g**. The exclusion zone **1340** is an area near or outside of an edge of a terrestrial network-only zone **1330**, where the terrestrial network-only zone **1330** is defined as the cumulative coverage area of the terrestrial network cells **1308a-1308g**.

[0114] The terrestrial network cells **1308a-1308g** may be further grouped or defined based on their position within the terrestrial network-only zone relative to the exclusion zone. For example, the terrestrial network cells that have a coverage area adjacent to the exclusion zone may be referred to as border cells, whereas terrestrial network cells that have a coverage area that is not adjacent to the exclusion zone may be referred to as non-border cells. In this case, terrestrial network cells **1308b-1308g** are border cells and terrestrial network cell **1308a** is a non-border cell.

[0115] In this illustration, user device **1324a** is located within the exclusion zone **1340** and user

device **1324b** is located within a coverage area of border terrestrial cell **1308f**, but near the exclusion zone **1340**. The non-terrestrial network satellite **1328** can utilize a specific bandwidth utilization scheme for non-terrestrial network downlink transmissions to user device **1324a**, whereas the border terrestrial network cell **1308f** can utilize a different specific bandwidth utilization scheme for terrestrial network downlink transmissions to user device **1324b**. For example, the non-terrestrial network satellite **1328** can transmit data to user device **1324a** in the exclusion zone using specific bandwidth parts for non-terrestrial network downlink transmissions. But the border terrestrial network cell **1308f** can transmit data to user device **1324b** using different specific bandwidth parts for terrestrial network downlink transmissions. In this way, the non-terrestrial network downlink transmissions and the terrestrial network downlink transmissions utilize different bandwidth parts for user devices in or near the exclusion zone **1340**. Non-border terrestrial network cell **1308a** can use all bandwidth parts.

[0116] In some embodiments, the border terrestrial network cells **1308b-1308g** may also divide their coverage areas into multiple regions such that terrestrial network downlink transmissions to user devices in the closer region (or in a region further from the exclusion zone) can be made using lower transmit power, similar to what is described in conjunction with FIG. 3A.

[0117] FIG. 13B illustrates bandwidth utilization schemes **1300B**. In particular, the terrestrial and non-terrestrial networks have a total bandwidth spectrum **1350** available. Non-border terrestrial network cells are instructed to utilize bandwidth utilization scheme **1360**, border terrestrial network cells are instructed to utilize bandwidth utilization scheme **1354**, and non-terrestrial network satellite is instructed to utilize bandwidth utilization scheme **1358**.

[0118] When communicating with user devices near the edge of the exclusion zone, the border terrestrial network cell can transmit data to those user devices using higher bandwidth parts **1354** for terrestrial network downlink transmissions based on the bandwidth utilization scheme **1356**. For user devices within the exclusion zone, the non-terrestrial network satellite can transmit data to those user devices to using lower bandwidth parts **1352** for non-terrestrial network downlink transmissions based on the bandwidth utilization scheme **1358**. And non-border terrestrial network cells can transmit data to user devices using all bandwidth parts **1356** for terrestrial network downlink transmissions based on the bandwidth utilization scheme **1360**.

[0119] Although the non-terrestrial network satellite bandwidth utilization scheme illustrates lower bandwidth parts for non-terrestrial user devices in the exclusion zone and the border terrestrial network cell bandwidth utilization scheme illustrates higher bandwidth parts for user devices near the exclusion zone, embodiments are not so limited. For example, in some embodiments, the non-terrestrial network satellite bandwidth utilization scheme may utilize higher bandwidth parts for non-terrestrial user devices in the exclusion zone and the border terrestrial network cell bandwidth utilization scheme may utilize lower bandwidth parts for user devices near the exclusion zone. Accordingly, embodiments may be employed such that the bandwidth utilization of terrestrial and non-terrestrial cells do not overlap or are used to reduce an amount of overlap.

[0120] The operation of certain aspects will now be described with respect to FIGS. 14-16.

[0121] FIG. 14 illustrates a logical flow diagram showing one embodiment of a process **1400** for selecting bandwidth utilization schemes for non-terrestrial and terrestrial network cells to implement the mitigation techniques illustrated in FIGS. 13A-13B in accordance with embodiments described herein. In at least one of various embodiments, process **1400** may be implemented by or executed via circuitry or on one or more computing devices, such as terrestrial network and non-terrestrial network interference mitigation system **102** in FIG. 1, or one or more terrestrial or non-terrestrial cells.

[0122] Process **1400** begins, after a start block, at block **1402**, where the system determines that terrestrial network downlink transmissions and non-terrestrial network downlink transmissions utilize a same frequency spectrum. In some embodiments, this determination is based on the capabilities of user devices being able to access both the terrestrial and non-terrestrial network

using the same frequency spectrum. In other embodiments, this determination is based on the terrestrial and non-terrestrial networks attempting to communicate with user devices using the same frequency spectrum.

[0123] Process **1400** proceeds after block **1402** at block **1404**, where a coverage area of each terrestrial network cell is determined within the coverage area of the non-terrestrial network satellite. In some embodiments, the coverage areas may be known or estimated based on the capabilities of the hardware of the terrestrial network cells and the non-terrestrial network satellite. In other embodiments, an administrator may set or define the coverage area of the terrestrial network cells and the non-terrestrial network satellite.

[0124] Process **1400** continues after block **1404** to block **1406**, where an exclusion zone is generated based on the coverage areas of the terrestrial network cells. In various embodiments, the exclusion zone is generated or defined an area near an edge of the market coverage area of the terrestrial network cells, where terrestrial network cells or the non-terrestrial network satellite can transmit data to user devices in the exclusion zone, but the signal strength between the user devices and the terrestrial network cells is below a threshold value. Accordingly, the exclusion zone is an area where user devices should connect with the non-terrestrial network satellite, but may experience interference from the terrestrial network cells.

[0125] Process **1400** proceeds after block **1406** to block **1408**, where a first bandwidth utilization scheme is selected for the non-terrestrial network satellite for non-terrestrial network downlink transmissions to user devices within and outside the exclusion zone. For user devices within the exclusion zone, the first bandwidth utilization scheme defines which bandwidth parts the non-terrestrial network satellite is to utilize for non-terrestrial network downlink transmissions, which is described in more detail in conjunction with FIGS. **13A-13B**. Although for user devices outside the exclusion zone that connect to the non-terrestrial network satellite, the first bandwidth utilization scheme indicates that the non-terrestrial network satellite can use any available bandwidth parts for non-terrestrial network downlink transmissions with user devices outside the exclusion zone.

[0126] Process **1400** continues after block **1408** to block **1410**, where the non-terrestrial network satellite is instructed to utilize the first bandwidth utilization scheme when communicating with user devices within or outside the exclusion zone. In some embodiments, the non-terrestrial network satellite may store a plurality of different possible bandwidth utilization schemes. An indication of the first bandwidth utilization scheme is then transmitted to the non-terrestrial network satellite, such that the non-terrestrial network satellite can select the previously-stored bandwidth utilization scheme that matches the first bandwidth utilization scheme. In other embodiments, the details of the first bandwidth utilization scheme are transmitted to the non-terrestrial network satellite.

[0127] Process **1400** proceeds after block **1410** to block **1412**, where a second bandwidth utilization scheme is selected for border terrestrial network cells. The second bandwidth utilization scheme defines which bandwidth parts the border terrestrial network cells are to utilize for terrestrial network downlink transmissions with user devices near the exclusion zone, which is described in more detail in conjunction with FIGS. **13A-13B** and FIG. **16**. In some embodiments, the second bandwidth utilization scheme also indicates how the border terrestrial network cells are to divide their coverage area into regions for using the second bandwidth utilization scheme. In various embodiments, the border terrestrial network cells are those terrestrial network cells whose coverage area is adjacent to or partially overlaps the exclusion zone.

[0128] Process **1400** continues after block **1412** at block **14**, where the border terrestrial network cells are instructed to utilize the second bandwidth utilization scheme. In some embodiments, the border terrestrial network cells may store a plurality of different possible bandwidth utilization schemes. An indication of the second bandwidth utilization scheme is then transmitted to the border terrestrial network cells, such that the border terrestrial network cells can select the previously-stored bandwidth utilization scheme that matches the second bandwidth utilization scheme. In other

embodiments, the details of the second bandwidth utilization scheme are transmitted to the border terrestrial network cells.

[0129] Process **1400** proceeds after block **1414** to block **1416**, where a third bandwidth utilization scheme is selected for non-border terrestrial network cells. The third bandwidth utilization scheme defines which bandwidth parts, such as any available bandwidth part, the non-border terrestrial network cells are to utilize for terrestrial network downlink transmissions with user devices, which is described in more detail in conjunction with FIGS. **13A-13B**. In various embodiments, the non-border terrestrial network cells are those terrestrial network cells whose coverage area is not adjacent to nor partially overlaps the exclusion zone.

[0130] Process **1400** continues after block **1416** at block **1418**, where the non-border terrestrial network cells are instructed to utilize the third bandwidth utilization scheme. In some embodiments, the non-border terrestrial network cells may store a plurality of different possible bandwidth utilization schemes. An indication of the third bandwidth utilization scheme is then transmitted to the non-border terrestrial network cells, such that the non-border terrestrial network cells can select the previously-stored bandwidth utilization scheme that matches the third bandwidth utilization scheme. In other embodiments, the details of the third bandwidth utilization scheme are transmitted to the non-border terrestrial network cells.

[0131] After block **1418**, process **1400** terminates or otherwise returns to a calling process to perform additional actions.

[0132] FIG. **15** illustrates a logical flow diagram showing one embodiment of a process **1500** for a non-terrestrial network satellite to implement a bandwidth utilization scheme selected in FIG. **14** in accordance with embodiments described herein. In at least one of various embodiments, process **1500** may be implemented by or executed via circuitry or on one or more computing devices, such as non-terrestrial network satellite **128** in FIG. **1**.

[0133] Process **1500** begins, after a start block, at block **1502**, where a bandwidth utilization scheme is received for the non-terrestrial network satellite to utilize for non-terrestrial network downlink transmissions. In various embodiments, this bandwidth utilization scheme is the first bandwidth utilization scheme that the non-terrestrial network satellite is instructed to use at block **1410** in FIG. **14**.

[0134] Process **1500** proceeds after block **1502** to decision block **1504**, where a determination is made whether the non-terrestrial network satellite has data to transmit to a user device. If the non-terrestrial network satellite has data to transmit to a user device, then process **1500** proceeds to block **1506**; otherwise, process **1500** loops to decision block **1504** to wait for data to transmit to a non-terrestrial user device.

[0135] Process **1500** continues after block **1504** at block **1506**, where a location of the user device is determined. In various embodiments, the location of the user device is determined using GPS or other location information provided by the user device.

[0136] Process **1500** proceeds after block **1506** to decision block **1508**, where a determination is made whether the user device is located with an exclusion zone. In some embodiments, the user device location may be compared to the area defined as the exclusion zone to determine if the user device is within or outside the exclusion zone. If the user device is located within the exclusion zone, then process **1500** flows to block **1510**; otherwise, process **1500** flows to block **1514**.

[0137] At block **1510**, a bandwidth part is selected for the data transmission based on the received bandwidth utilization scheme. As discussed in FIG. **13B**, different bandwidth parts may be utilized for non-terrestrial downlink transmissions to user devices within the exclusion zone and terrestrial downlink transmissions to user devices near the exclusion zone.

[0138] Process **1500** proceeds after block **1510** to block **1512**, where the non-terrestrial network satellite transmits data to the user device in the exclusion zone using the selected bandwidth part. After block **1512**, process **1500** terminates or otherwise returns to a calling process to perform other actions.

[0139] If, at decision block **1508**, the user device is determined to be located outside the exclusion zone, process **1500** flows from decision block **1508** to block **1514**. At block **1514**, the non-terrestrial network satellite transmits data to the user device outside the exclusion zone using any available bandwidth part. After block **1514**, process **1500** terminates or otherwise returns to a calling process to perform other actions.

[0140] Although process **1500** is illustrated as terminating or ending, embodiments are not so limited. In some embodiments, process **1500** may loop after block **1512** or block **1514** to decision block **1504** to wait for data to transmit to a non-terrestrial user device.

[0141] FIG. **16** illustrates a logical flow diagram showing one embodiment of a process **1600** for a border terrestrial network cell to implement a bandwidth utilization scheme selected in FIG. **14** in accordance with embodiments described herein. In at least one of various embodiments, process **1600** may be implemented by or executed via circuitry or on one or more computing devices, such as terrestrial network cell **112** in FIG. **1**.

[0142] Process **1600** begins, after a start block, at block **1602**, where a bandwidth utilization scheme is received for a border terrestrial network cell to utilize for terrestrial network downlink transmissions. In various embodiments, this bandwidth utilization scheme is the second bandwidth utilization scheme that the border terrestrial network cell is instructed to use at block **1414** in FIG. **14**.

[0143] Process **1600** proceeds after block **1602** to decision block **1604**, where a determination is made whether the border terrestrial network cell has data to transmit to a user device. If the border terrestrial network cell has data to transmit to a user device, then process **1600** proceeds to block **1606**; otherwise, process **1600** loops to decision block **1604** to wait for data to transmit to a terrestrial user device.

[0144] Process **1600** continues after block **1604** at block **1606**, where a location of the user device is determined. In various embodiments, the location of the user device is determined using CQI data, GPS, or other location information provided by the user device.

[0145] Process **1600** proceeds after block **1606** to decision block **1608**, where a determination is made whether the user device is located near an edge of an exclusion zone. In some embodiments, the user device location may be compared to the area defined as the exclusion zone to determine if the user device is near the exclusion zone. The user device may be near the exclusion zone if it is located within a threshold distance from an edge of the exclusion zone. If the user device is located near the exclusion zone, then process **1600** flows to block **1610**; otherwise, process **1600** flows to block **1614**.

[0146] At block **1610**, a bandwidth part is selected for the data transmission based on the received bandwidth utilization scheme. As discussed in FIG. **13B**, different bandwidth parts may be utilized for non-terrestrial downlink transmissions to user devices within the exclusion zone and terrestrial downlink transmissions to user devices near the exclusion zone.

[0147] Process **1600** proceeds after block **1610** to block **1612**, where the border terrestrial network cell transmits data to the user device near the exclusion zone using the selected bandwidth part. After block **1612**, process **1600** terminates or otherwise returns to a calling process to perform other actions.

[0148] If, at decision block **1608**, the user device is determined to be located away from the exclusion zone (e.g., the user device is located outside a threshold distance from an edge of the exclusion zone), process **1600** flows from decision block **1608** to block **1614**. At block **1614**, the border terrestrial network cell transmits data to the user device using any available bandwidth part. After block **1614**, process **1600** terminates or otherwise returns to a calling process to perform other actions.

[0149] Although process **1600** is illustrated as terminating or ending, embodiments are not so limited. In some embodiments, process **1600** may loop after block **1612** or block **1614** to decision block **1604** to wait for data to transmit to a terrestrial user device.

[0150] As described herein, one or more bandwidth utilization schemes may be selected for use by one or more terrestrial network cells or one or more non-terrestrial network satellites to reduce various network interferences. In some embodiments, the network interference may be predicted, such that the bandwidth utilization schemes may be dynamically selected or modified to proactively reduce or mitigate network interference. The operation of certain aspects will now be described with respect to FIGS. **17-19**.

[0151] FIG. **17** illustrates a logical flow diagram showing an embodiment of a process **1700** for utilizing at least one artificial intelligence mechanism to predict terrestrial network downlink transmission interference on non-terrestrial network uplink transmissions in accordance with embodiments described herein.

[0152] Process **1700** begins, after a start block at block **1702**, where first history data is obtained on terrestrial network downlink transmissions. In various embodiments, the terrestrial network downlink transmission history data includes a plurality of previous data regarding transmissions from at least one terrestrial network cell to at least one user device. The history data may include a variety of information related to the terrestrial network downlink transmissions, including, locations of terrestrial network cells, locations of user devices, configuration or settings of the terrestrial network cells, configuration or settings of the user devices, hardware capabilities of the terrestrial network cells, hardware capabilities of the user devices, quality information of the transmissions, etc.

[0153] Process **1700** proceeds after block **1702** to block **1704**, where second history data is obtained on non-terrestrial network uplink transmissions. In various embodiments, the non-terrestrial network uplink transmission history data includes a plurality of previous data regarding transmissions from at least one user device to at least one non-terrestrial network satellite. The history data may include a variety of information related to the non-terrestrial network uplink transmissions, including, position or location of the non-terrestrial network satellite, locations of user devices, configuration or settings of the non-terrestrial network satellite, configuration or settings of the user devices, hardware capabilities of the non-terrestrial network satellite, hardware capabilities of the user devices, quality information of the transmissions, etc.

[0154] Process **1700** continues after block **1704** at block **1706**, where at least one artificial intelligence mechanism is employed on the first and second history data to generate or train a model of terrestrial network downlink transmission interference on non-terrestrial network uplink transmissions. The artificial intelligence mechanisms may be neural networks, machine learning models, etc. In some embodiments, the first history data and the second history data are used as input into the at least one artificial intelligence mechanism, such that the generated, trained, or resulting model predicts how terrestrial network downlink transmissions may cause interference on non-terrestrial network uplink transmissions.

[0155] Process **1700** proceeds after block **1706** to block **1708**, where terrestrial network downlink transmission interference is predicted on target non-terrestrial network uplink transmissions based on the generated/trained model. In various embodiments, the input to the model may include locations of terrestrial network cells, location of the non-terrestrial network satellite, predicted locations of user devices, configuration or settings of the terrestrial network cells, configuration or settings of the non-terrestrial network satellite, configuration or settings of user devices, hardware capabilities of the terrestrial network cells, hardware capabilities of the non-terrestrial network satellite, hardware capabilities of the user devices, expected quality information, etc. The output of the model may be a predicted amount or type of interference that terrestrial network downlink transmissions may have on non-terrestrial network uplink transmissions.

[0156] Process **1700** continues after block **1708** at block **1710**, where one or more bandwidth utilization schemes for the terrestrial network cells or the non-terrestrial network satellite may be modified based on the predicted terrestrial network downlink transmission interference. In various embodiments, the bandwidth utilization scheme that is modified may be one or more of the

bandwidth utilization schemes discussed in conjunction with FIGS. 2, 3A-3B, and 4-6. Such modifications may include, but are not limited to changes in which bandwidth parts are selected for transmissions, size or number of regions utilized by terrestrial network cells, utilization of reduced transmit power, etc., or some combination thereof.

[0157] After block **1710**, process **1700** terminates or otherwise returns to a calling process to perform other actions.

[0158] FIG. **18** illustrates a logical flow diagram showing an embodiment of a process **1800** for utilizing at least one artificial intelligence mechanism to predict terrestrial network uplink transmission interference on non-terrestrial network uplink transmissions in accordance with embodiments described herein.

[0159] Process **1800** begins, after a start block at block **1802**, where first history data is obtained on non-terrestrial network uplink transmissions. In various embodiments, the non-terrestrial network uplink transmission history data includes a plurality of previous data regarding transmissions from at least one user device to at least one non-terrestrial network satellite. The history data may include a variety of information related to the non-terrestrial network uplink transmissions, including, locations of non-terrestrial network satellites, locations of user devices, configuration or settings of the non-terrestrial network satellites, configuration or settings of the user devices, hardware capabilities of the non-terrestrial network satellites, hardware capabilities of the user devices, quality information of the transmissions, etc.

[0160] Process **1800** proceeds after block **1802** to block **1804**, where second history data is obtained on terrestrial network uplink transmissions. In various embodiments, the terrestrial network uplink transmission history data includes a plurality of previous data regarding transmissions from at least one user device to at least one terrestrial network cell. The history data may include a variety of information related to the terrestrial network uplink transmissions, including, position or location of terrestrial network cells, locations of user devices, configuration or settings of the terrestrial network cells, configuration or settings of the user devices, hardware capabilities of the terrestrial network cells, hardware capabilities of the user devices, quality information of the transmissions, etc.

[0161] Process **1800** continues after block **1804** at block **1806**, where at least one artificial intelligence mechanism is employed on the first and second history data to train or generate a model of terrestrial network uplink transmission interference on non-terrestrial network uplink transmissions. The artificial intelligence mechanisms may be neural networks, machine learning models, etc. In some embodiments, the first history data and the second history data are used as input into the at least one artificial intelligence mechanism, such that the generated, trained, or resulting model predicts how terrestrial network uplink transmissions may cause interference on non-terrestrial network uplink transmissions.

[0162] Process **1800** proceeds after block **1806** to block **1808**, where terrestrial network uplink transmission interference is predicted on target non-terrestrial network uplink transmissions based on the generated/trained model. Similar to block **1708** in FIG. 7, the input to the model may include locations of terrestrial network cells, location of the non-terrestrial network satellite, predicted locations of user devices, configuration or settings of the terrestrial network cells, configuration or settings of the non-terrestrial network satellite, configuration or settings of user devices, hardware capabilities of the terrestrial network cells, hardware capabilities of the non-terrestrial network satellite, hardware capabilities of the user devices, expected quality information, etc. The output of the model may be a predicted amount or type of interference that terrestrial network uplink transmissions may have on non-terrestrial network uplink transmissions.

[0163] Process **1800** continues after block **1808** at block **1810**, where one or more bandwidth utilization schemes for the terrestrial network cells or the non-terrestrial network satellite may be modified based on the predicted terrestrial network uplink transmission interference. In various embodiments, the bandwidth utilization scheme that is modified may be one or more of the

bandwidth utilization schemes discussed in conjunction with FIGS. 7, 8A-8B, and 9-10. Such modifications may include, but are not limited to changes in which bandwidth parts are selected for transmissions, size or number of regions utilized by terrestrial network cells, etc., or some combination thereof.

[0164] After block **1810**, process **1800** terminates or otherwise returns to a calling process to perform other actions.

[0165] FIG. **19** illustrates a logical flow diagram showing an embodiment of a process **1800** for utilizing at least one artificial intelligence mechanism to predict terrestrial network downlink transmission interference on non-terrestrial network downlink transmissions and to predict non-terrestrial network downlink transmission interference on terrestrial network downlink transmissions in accordance with embodiments described herein.

[0166] Process **1900** begins, after a start block at block **1902**, where first history data is obtained on terrestrial network downlink transmissions. In various embodiments, block **1902** may employ embodiments of block **1702** in FIG. **17** to obtain the terrestrial network downlink transmission history data.

[0167] Process **1900** proceeds after block **1902** to block **1904**, where second history data is obtained on non-terrestrial network downlink transmissions. In various embodiments, the non-terrestrial network downlink transmission history data includes a plurality of previous data regarding transmissions from at least one non-terrestrial network satellite to at least one user device. The history data may include a variety of information related to the non-terrestrial network downlink transmissions, including, position or location of the non-terrestrial network satellite, locations of user devices, configuration or settings of the non-terrestrial network satellite, configuration or settings of the user devices, hardware capabilities of the non-terrestrial network satellite, hardware capabilities of the user devices, quality information of the transmissions, etc.

[0168] Process **1900** continues after block **1904** at block **1906**, where at least one artificial intelligence mechanism is employed on the first and second history data to generate or train a model of terrestrial network downlink transmission interference on non-terrestrial network downlink transmissions. The artificial intelligence mechanisms may be neural networks, machine learning models, etc. In some embodiments, the first history data and the second history data are used as input into the at least one artificial intelligence mechanism, such that the generated, trained, or resulting model predicts how terrestrial network downlink transmissions cause interference on non-terrestrial network downlink transmissions.

[0169] Process **1900** proceeds after block **1906** to block **1908**, where terrestrial network downlink transmission interference is predicted on target non-terrestrial network downlink transmissions based on the generated/trained model. In various embodiments, the input to the model may include locations of terrestrial network cells, location of the non-terrestrial network satellite, predicted locations of user devices, configuration or settings of the terrestrial network cells, configuration or settings of the non-terrestrial network satellite, configuration or settings of user devices, hardware capabilities of the terrestrial network cells, hardware capabilities of the non-terrestrial network satellite, hardware capabilities of the user devices, expected quality information, etc. The output of the model may be a predicted amount or type of interference that terrestrial network downlink transmissions may have on non-terrestrial network downlink transmissions.

[0170] Process **1900** continues after block **1908** at block **1910**, where one or more bandwidth utilization schemes for the non-terrestrial network satellite may be modified based on the predicted terrestrial network downlink transmission interference. In various embodiments, the bandwidth utilization scheme that is modified may be one or more of the bandwidth utilization schemes discussed in conjunction with FIGS. **11**, **13A-13B**, and **14-15**. Such modifications may include, but are not limited to changes in which bandwidth parts are selected for transmissions, size or position of the exclusion zone, etc., or some combination thereof.

[0171] Process **1900** continues after block **1910** at block **1912**, where at least one artificial

intelligence mechanism is employed on the first and second history data to generate or train a model of non-terrestrial network downlink transmission interference on terrestrial network downlink transmissions. The artificial intelligence mechanisms may be neural networks, machine learning models, etc. In some embodiments, the first history data and the second history data are used as input into the at least one artificial intelligence mechanism, such that the generated, trained, or resulting model predicts how non-terrestrial network downlink transmissions cause interference on terrestrial network downlink transmissions.

[0172] Process **1900** proceeds after block **1912** to block **1914**, where non-terrestrial network downlink transmission interference is predicted on target terrestrial network downlink transmissions based on the generated/trained model. In various embodiments, the input to the model may include locations of terrestrial network cells, location of the non-terrestrial network satellite, predicted locations of user devices, configuration or settings of the terrestrial network cells, configuration or settings of the non-terrestrial network satellite, configuration or settings of user devices, hardware capabilities of the terrestrial network cells, hardware capabilities of the non-terrestrial network satellite, hardware capabilities of the user devices, expected quality information, etc. The output of the model may be a predicted amount or type of interference that non-terrestrial network downlink transmissions may have on terrestrial network downlink transmissions.

[0173] Process **1900** continues after block **1914** at block **1916**, where one or more bandwidth utilization schemes for one or more border terrestrial network cells may be modified based on the predicted non-terrestrial network downlink transmission interference. In various embodiments, the bandwidth utilization scheme that is modified may be one or more of the bandwidth utilization schemes discussed in conjunction with FIGS. **12**, **13A-13B**, **14**, and **16**. Such modifications may include, but are not limited to changes in which bandwidth parts are selected for transmissions, size or position of the exclusion zone, etc., or some combination thereof.

[0174] After block **1916**, process **1900** terminates or otherwise returns to a calling process to perform other actions.

[0175] FIG. **20** shows a system diagram that describes one implementation of computing systems for implementing embodiments described herein. System **2000** includes terrestrial network and non-terrestrial network interference mitigation system **102**, non-terrestrial network satellite **128**, terrestrial network cells **112a-112c**, user devices **124a-124c**, similar to what is described herein.

[0176] As described herein, the terrestrial network and non-terrestrial network interference mitigation system **102** is a computing device that can perform functionality described herein for selecting bandwidth utilization schemes for terrestrial network cells **112a-112b** and non-terrestrial network satellite **128** to utilize to mitigate interference. One or more special purpose computing systems may be used to implement the terrestrial network and non-terrestrial network interference mitigation system **102**. Accordingly, various embodiments described herein may be implemented in specialized software, hardware, firmware, or in some combination thereof. The terrestrial network and non-terrestrial network interference mitigation system **102** includes memory **2002**, processor **2014**, network connections **2022**, input/output (I/O) interfaces **2018**, and other computer-readable media **2020**.

[0177] Processor **2014** includes one or more processors, one or more processing units, programmable logic, circuitry, or one or more other computing components that are configured to perform embodiments described herein or to execute computer instructions to perform embodiments described herein. In some embodiments, a processor system of the terrestrial network and non-terrestrial network interference mitigation system **102** may include a single processor **2014** that operates individually to perform actions. In other embodiments, a processor system of the terrestrial network and non-terrestrial network interference mitigation system **102** may include a plurality of processors **2014** that operate to collectively perform actions, such that one or more processors **2014** may operate to perform some, but not all, of such actions. Reference herein to “a processor system” of the terrestrial network and non-terrestrial network interference mitigation

system **102** refers to one or more processors **2014** that individually or collectively perform actions. And reference herein to “the processor system” of the terrestrial network and non-terrestrial network interference mitigation system **102** refers to 1) a subset or all of the one or more processors **2014** comprised by “a processor system” of the remote server **102** and 2) any combination of the one or more processors **2014** comprised by “a processor system” of the terrestrial network and non-terrestrial network interference mitigation system **102** and one or more other processors **2014**.

[0178] Memory **2002** may include one or more various types of non-volatile or volatile storage technologies. Examples of memory **2002** include, but are not limited to, flash memory, hard disk drives, optical drives, solid-state drives, various types of random-access memory (“RAM”), various types of read-only memory (“ROM”), other computer-readable storage media (also referred to as processor-readable storage media), or other memory technologies, or any combination thereof. Memory **2002** may be utilized to store information, including computer-readable instructions that are utilized by a processor system of one or more processors **2014** to perform actions, including at least some embodiments described herein.

[0179] Memory **2002** may have stored thereon transmission management module **2004**. The transmission management module **2004** is configured to select bandwidth utilization schemes and to instruct cells to utilize the selected bandwidth utilization schemes, as described herein. In some embodiments, the transmission management module **2004** may also employ one or more artificial intelligence mechanisms to generate or train models of interference to dynamically modify one or more bandwidth utilization schemes.

[0180] Memory **2002** may also store other programs and data **2010**, such as historical transmission data, bandwidth utilization schemes, etc.

[0181] Network connections **2022** is configured to communicate with other computing devices, such as to instruct non-terrestrial network satellite **128** or terrestrial network cells **112a-112c** to utilize selected bandwidth utilizations schemes. I/O interfaces **2018** may include interfaces for various input or output devices, such as USB interfaces, physical buttons, keyboards, haptic interfaces, tactile interfaces, or the like. Other computer-readable media **2020** may include other types of stationary or removable computer-readable media, such as removable flash drives, external hard drives, or the like.

[0182] The non-terrestrial network satellite **128**, terrestrial network cells **112a-112c**, and user devices **124a-124c** may be implemented as special purpose computing systems to employ embodiments described herein. Accordingly, various embodiments described herein may be implemented in specialized software, hardware, firmware, or in some combination thereof. The non-terrestrial network satellite **128**, terrestrial network cells **112a-112c**, and user devices **124a-124c** may include memory, processors, network interfaces, input/output (I/O) interfaces, other computer-readable media, and other components, which are not shown for ease of illustration.

[0183] The following is a summarization of the claims as originally filed.

[0184] A method may be summarized as comprising: determining that terrestrial network downlink transmissions for a terrestrial network and non-terrestrial network uplink transmissions for a non-terrestrial network utilize a same frequency band; identifying one or more terrestrial cells of the terrestrial network that are in a coverage area of a non-terrestrial network satellite of the non-terrestrial network; instructing the one or more terrestrial network cells to utilize at least a first bandwidth utilization scheme for terrestrial network downlink transmissions; and instructing the non-terrestrial network satellite of the non-terrestrial network to utilize a second bandwidth utilization scheme for non-terrestrial network uplink transmissions, wherein the second bandwidth utilization scheme is different from the first bandwidth utilization scheme.

[0185] The method may instruct the one or more terrestrial network cells to utilize at least the first bandwidth utilization scheme for the terrestrial network downlink transmissions by: selecting the first bandwidth utilization scheme for a first terrestrial network cell of the one or more terrestrial

network cells; instructing the first terrestrial network cell to utilize the first bandwidth utilization scheme for terrestrial network downlink transmissions; selecting a third bandwidth utilization scheme for a second terrestrial network cell of the one or more terrestrial network cells, wherein the third bandwidth utilization scheme is different from the first bandwidth utilization scheme and different from the second bandwidth utilization scheme; and instructing the second terrestrial network cell to utilize the third bandwidth utilization scheme for terrestrial network downlink transmissions.

[0186] The method may instruct the one or more terrestrial network cells to utilize at least the first bandwidth utilization scheme for terrestrial network downlink transmissions by: grouping the one or more terrestrial network cells into a plurality of clusters; for each corresponding cluster, selecting a separate bandwidth utilization scheme; and instructing each terrestrial network cell in each corresponding cluster to utilize the separate bandwidth utilization scheme selected for the corresponding cluster for terrestrial network downlink transmissions.

[0187] The method may instruct the one or more terrestrial network cells to utilize at least the first bandwidth utilization scheme for terrestrial network downlink transmissions by: grouping the one or more terrestrial network cells into a first cluster and a second cluster; selecting the first bandwidth utilization scheme for the first cluster; instructing each terrestrial network cell in the first cluster to utilize the first bandwidth utilization scheme for terrestrial network downlink transmissions; selecting a third bandwidth utilization scheme for the second cluster, wherein the third bandwidth utilization scheme is different from the first bandwidth utilization scheme and different from the second bandwidth utilization scheme; and instructing each terrestrial network cell in the second cluster to utilize the third bandwidth utilization scheme for terrestrial network downlink transmissions.

[0188] The method may instruct the one or more terrestrial network cells to utilize at least the first bandwidth utilization scheme for terrestrial network downlink transmissions by: grouping the one or more terrestrial network cells into a plurality of clusters; and for each corresponding cluster, instructing each terrestrial network cell in the corresponding cluster to schedule synchronization signal blocks at a corresponding time-slot for the corresponding cluster, wherein the corresponding time-slot is different for each corresponding cluster.

[0189] The method may instruct the one or more terrestrial network cells to utilize at least the first bandwidth utilization scheme for terrestrial network downlink transmissions by: grouping the one or more terrestrial network cells into a plurality of clusters; and for each corresponding cluster, instructing each terrestrial network cell in the corresponding cluster to schedule synchronization signal blocks in a corresponding frequency domain for the corresponding cluster, wherein the corresponding frequency domain is different for each corresponding cluster.

[0190] The method may, further comprise: generating the first bandwidth utilization scheme to include a first order in which the one or more terrestrial network cells are to allocate physical resource blocks; and generating the second bandwidth utilization scheme to include a second order in which the non-terrestrial network satellite is to allocate physical resource blocks, wherein the second order is different from the first order.

[0191] The method may, further comprise: generating the first bandwidth utilization scheme to instruct each corresponding terrestrial network cell of the one or more terrestrial network cells to allocate physical resource blocks starting with a lowest available frequency for user devices closest to the corresponding terrestrial network cell; and generating the second bandwidth utilization scheme to instruct the non-terrestrial network satellite to allocate physical resource blocks starting with a highest available frequency for high priority transmissions.

[0192] Another method may be summarized as comprising: in response to terrestrial network downlink transmissions for a terrestrial network and non-terrestrial network uplink transmissions for a non-terrestrial network utilizing a same frequency band, receiving, by a terrestrial cell of the terrestrial network, a bandwidth utilization scheme; dividing, by the terrestrial cell, a coverage area

of the terrestrial cell into at least a first region and a second region, wherein the first region is closer to the terrestrial cell than the second region; obtaining, by the terrestrial cell, a corresponding location indicator for each user device connected to the terrestrial cell; determining, by the terrestrial cell, whether each user device connected to the terrestrial cell is in the first region or the second region based on the corresponding location indicator for each user device; for each user device determined to be in the first region, transmitting, by the terrestrial cell, data to the user device using a reduced transmit power; and for each user device determined to be in the second region: selecting, by the terrestrial cell, a bandwidth part for data to be transmitted to the user device based on the received bandwidth utilization scheme; and transmitting, by the terrestrial cell, the data to the user device using the selected bandwidth part.

[0193] The other method may determine whether each user device connected to the terrestrial cell is in the first region or the second region by: determining, by the terrestrial cell, whether each user device connected to the terrestrial cell is in the first region or the second region based on the corresponding location indicator channel quality indicator received from a corresponding user device.

[0194] The other method may select a bandwidth part for data to be transmitted to the user device by: selecting, by the terrestrial cell, a first set of physical resource blocks for user devices having a first location relative to the terrestrial cell and a second set of physical resource blocks for user devices having a second location relative to the terrestrial cell.

[0195] In some embodiments, the bandwidth utilization scheme includes a specific synchronization signal block schedule for the terrestrial cell to utilize.

[0196] The other method may further comprise: utilizing, by the terrestrial cell, a synchronization signal block schedule defined in the received bandwidth utilization scheme to connect with user devices in the coverage area of the terrestrial cell.

[0197] A system may be summarized as comprising: a non-terrestrial cell of a non-terrestrial network; a plurality of terrestrial cells of a terrestrial network; and a computing device. The computing device may comprise: a memory configured to store computer instructions; and a processor system configured to execute the computer instructions to: determine that terrestrial network downlink transmissions for the terrestrial network and non-terrestrial network uplink transmissions for the non-terrestrial network utilize a same frequency band; determine that the plurality of terrestrial cells are in a coverage area of the non-terrestrial cell; group the plurality of terrestrial cells into a plurality of clusters; for each corresponding cluster, selecting a separate bandwidth utilization scheme; instruct each terrestrial cell in each corresponding cluster to utilize the separate bandwidth utilization scheme selected for the corresponding cluster for terrestrial network downlink transmissions; and instruct the non-terrestrial network satellite to utilize another bandwidth utilization scheme for non-terrestrial network uplink transmissions, wherein the other bandwidth utilization scheme is different from the separate bandwidth utilization schemes for the plurality of clusters.

[0198] The processor system of the computing device in the system may select the separate bandwidth utilization scheme for each corresponding cluster by being configured to execute the computer instructions to: select a first bandwidth utilization scheme for a first cluster of terrestrial cells; and select a second bandwidth utilization scheme for a second cluster of terrestrial cells, wherein the second bandwidth utilization scheme is different from the first bandwidth utilization scheme.

[0199] The processor system of the computing device in the system may select the separate bandwidth utilization scheme for each corresponding cluster by being configured to execute the computer instructions to: select a first synchronization signal block schedule for a first cluster of terrestrial cells; and select a second synchronization signal block schedule for a second cluster of terrestrial cells, wherein the second synchronization signal block schedule is different from the first synchronization signal block schedule.

[0200] The processor system of the computing device in the system may select the separate bandwidth utilization scheme for each corresponding cluster by being configured to execute the computer instructions to: select a first time slot for synchronization signal block transmissions for a first cluster of terrestrial cells; and select a second time slot for synchronization signal block transmissions for a second cluster of terrestrial cells, wherein the second time slot is different from the first time slot.

[0201] The processor system of the computing device in the system may select the separate bandwidth utilization scheme for each corresponding cluster by being configured to execute the computer instructions to: select a first frequency domain for synchronization signal block transmissions for a first cluster of terrestrial cells; and select a second frequency domain for synchronization signal block transmissions for a second cluster of terrestrial cells, wherein the second frequency domain is different from the first frequency domain.

[0202] Each terrestrial cell of the plurality of terrestrial cells in the system may be configured to: receive a bandwidth utilization scheme; divide a coverage area of the terrestrial cell into at least a first region and a second region, wherein the first region is closer to the terrestrial cell than the second region; obtain a corresponding location indicator for each user device connected to the terrestrial cell; determine whether each user device connected to the terrestrial cell is in the first region or the second region based on the corresponding location indicator for each user device; for each user device determined to be in the first region, transmit; and for each user device determined to be in the second region: select a bandwidth part for data to be transmitted to the user device based on the received bandwidth utilization scheme; and transmit the data to the user device using the selected bandwidth part.

[0203] The processor of the computing device may be configured to further execute the computer instructions to: generate the separate bandwidth utilization schemes for each corresponding cluster to include a first order in which corresponding terrestrial cells of each corresponding cluster are to allocate physical resource blocks; and generate the other bandwidth utilization scheme to include a second order in which the non-terrestrial cell is to allocate physical resource blocks, wherein the second order is different from the first order.

[0204] The various embodiments described above can be combined to provide further embodiments. These and other changes can be made to the embodiments in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the claims to the specific embodiments disclosed in the specification and the claims, but should be construed to include all possible embodiments along with the full scope of equivalents to which such claims are entitled. Accordingly, the claims are not limited by the disclosure.

Claims

1. A method, comprising: determining that terrestrial network downlink transmissions for a terrestrial network and non-terrestrial network uplink transmissions for a non-terrestrial network utilize a same frequency band; identifying one or more terrestrial cells of the terrestrial network that are in a coverage area of a non-terrestrial network satellite of the non-terrestrial network; instructing the one or more terrestrial network cells to utilize at least a first bandwidth utilization scheme for terrestrial network downlink transmissions; and instructing the non-terrestrial network satellite of the non-terrestrial network to utilize a second bandwidth utilization scheme for non-terrestrial network uplink transmissions, wherein the second bandwidth utilization scheme is different from the first bandwidth utilization scheme.
2. The method of claim 1, wherein instructing the one or more terrestrial network cells to utilize at least the first bandwidth utilization scheme for the terrestrial network downlink transmissions comprises: selecting the first bandwidth utilization scheme for a first terrestrial network cell of the one or more terrestrial network cells; instructing the first terrestrial network cell to utilize the first

bandwidth utilization scheme for terrestrial network downlink transmissions; selecting a third bandwidth utilization scheme for a second terrestrial network cell of the one or more terrestrial network cells, wherein the third bandwidth utilization scheme is different from the first bandwidth utilization scheme and different from the second bandwidth utilization scheme; and instructing the second terrestrial network cell to utilize the third bandwidth utilization scheme for terrestrial network downlink transmissions.

3. The method of claim 1, wherein instructing the one or more terrestrial network cells to utilize at least the first bandwidth utilization scheme for terrestrial network downlink transmissions comprises: grouping the one or more terrestrial network cells into a plurality of clusters; for each corresponding cluster, selecting a separate bandwidth utilization scheme; and instructing each terrestrial network cell in each corresponding cluster to utilize the separate bandwidth utilization scheme selected for the corresponding cluster for terrestrial network downlink transmissions.

4. The method of claim 1, wherein instructing the one or more terrestrial network cells to utilize at least the first bandwidth utilization scheme for terrestrial network downlink transmissions comprises: grouping the one or more terrestrial network cells into a first cluster and a second cluster; selecting the first bandwidth utilization scheme for the first cluster; instructing each terrestrial network cell in the first cluster to utilize the first bandwidth utilization scheme for terrestrial network downlink transmissions; selecting a third bandwidth utilization scheme for the second cluster, wherein the third bandwidth utilization scheme is different from the first bandwidth utilization scheme and different from the second bandwidth utilization scheme; and instructing each terrestrial network cell in the second cluster to utilize the third bandwidth utilization scheme for terrestrial network downlink transmissions.

5. The method of claim 1, wherein instructing the one or more terrestrial network cells to utilize at least the first bandwidth utilization scheme for terrestrial network downlink transmissions comprises: grouping the one or more terrestrial network cells into a plurality of clusters; and for each corresponding cluster, instructing each terrestrial network cell in the corresponding cluster to schedule synchronization signal blocks at a corresponding time-slot for the corresponding cluster, wherein the corresponding time-slot is different for each corresponding cluster.

6. The method of claim 1, wherein instructing the one or more terrestrial network cells to utilize at least the first bandwidth utilization scheme for terrestrial network downlink transmissions comprises: grouping the one or more terrestrial network cells into a plurality of clusters; and for each corresponding cluster, instructing each terrestrial network cell in the corresponding cluster to schedule synchronization signal blocks in a corresponding frequency domain for the corresponding cluster, wherein the corresponding frequency domain is different for each corresponding cluster.

7. The method of claim 1, further comprising: generating the first bandwidth utilization scheme to include a first order in which the one or more terrestrial network cells are to allocate physical resource blocks; and generating the second bandwidth utilization scheme to include a second order in which the non-terrestrial network satellite is to allocate physical resource blocks, wherein the second order is different from the first order.

8. The method of claim 1, further comprising: generating the first bandwidth utilization scheme to instruct each corresponding terrestrial network cell of the one or more terrestrial network cells to allocate physical resource blocks starting with a lowest available frequency for user devices closest to the corresponding terrestrial network cell; and generating the second bandwidth utilization scheme to instruct the non-terrestrial network satellite to allocate physical resource blocks starting with a highest available frequency for high priority transmissions.

9. A method, comprising: in response to terrestrial network downlink transmissions for a terrestrial network and non-terrestrial network uplink transmissions for a non-terrestrial network utilizing a same frequency band, receiving, by a terrestrial cell of the terrestrial network, a bandwidth utilization scheme; dividing, by the terrestrial cell, a coverage area of the terrestrial cell into at least a first region and a second region, wherein the first region is closer to the terrestrial cell than the

second region; obtaining, by the terrestrial cell, a corresponding location indicator for each user device connected to the terrestrial cell; determining, by the terrestrial cell, whether each user device connected to the terrestrial cell is in the first region or the second region based on the corresponding location indicator for each user device; for each user device determined to be in the first region, transmitting, by the terrestrial cell, data to the user device using a reduced transmit power; and for each user device determined to be in the second region: selecting, by the terrestrial cell, a bandwidth part for data to be transmitted to the user device based on the received bandwidth utilization scheme; and transmitting, by the terrestrial cell, the data to the user device using the selected bandwidth part.

10. The method of claim 9, wherein determining whether each user device connected to the terrestrial cell is in the first region or the second region comprises: determining, by the terrestrial cell, whether each user device connected to the terrestrial cell is in the first region or the second region based on the corresponding location indicator received from a corresponding user device.

11. The method of claim 9, wherein selecting a bandwidth part for data to be transmitted to the user device comprises: selecting, by the terrestrial cell, a first set of physical resource blocks for user devices having a first location relative to the terrestrial cell and a second set of physical resource blocks for user devices having a second location relative to the terrestrial cell.

12. The method of claim 9, wherein the bandwidth utilization scheme includes a specific synchronization signal block schedule for the terrestrial cell to utilize.

13. The method of claim 9, further comprising: utilizing, by the terrestrial cell, a synchronization signal block schedule defined in the received bandwidth utilization scheme to connect with user devices in the coverage area of the terrestrial cell.

14. A system, comprising: a non-terrestrial cell of a non-terrestrial network; a plurality of terrestrial cells of a terrestrial network; and a computing device, comprising: a memory configured to store computer instructions; and a processor system configured to execute the computer instructions to: determine that terrestrial network downlink transmissions for the terrestrial network and non-terrestrial network uplink transmissions for the non-terrestrial network utilize a same frequency band; determine that the plurality of terrestrial cells are in a coverage area of the non-terrestrial cell; group the plurality of terrestrial cells into a plurality of clusters; for each corresponding cluster, selecting a separate bandwidth utilization scheme; instruct each terrestrial cell in each corresponding cluster to utilize the separate bandwidth utilization scheme selected for the corresponding cluster for terrestrial network downlink transmissions; and instruct the non-terrestrial network satellite to utilize another bandwidth utilization scheme for non-terrestrial network uplink transmissions, wherein the other bandwidth utilization scheme is different from the separate bandwidth utilization schemes for the plurality of clusters.

15. The system of claim 14, wherein the processor selects the separate bandwidth utilization scheme for each corresponding cluster by being configured to execute the computer instructions to: select a first bandwidth utilization scheme for a first cluster of terrestrial cells; and select a second bandwidth utilization scheme for a second cluster of terrestrial cells, wherein the second bandwidth utilization scheme is different from the first bandwidth utilization scheme.

16. The system of claim 14, wherein the processor selects the separate bandwidth utilization scheme for each corresponding cluster by being configured to execute the computer instructions to: select a first synchronization signal block schedule for a first cluster of terrestrial cells; and select a second synchronization signal block schedule for a second cluster of terrestrial cells, wherein the second synchronization signal block schedule is different from the first synchronization signal block schedule.

17. The system of claim 14, wherein the processor selects the separate bandwidth utilization scheme for each corresponding cluster by being configured to execute the computer instructions to: select a first time slot for synchronization signal block transmissions for a first cluster of terrestrial cells; and select a second time slot for synchronization signal block transmissions for a second

cluster of terrestrial cells, wherein the second time slot is different from the first time slot.

18. The system of claim 14, wherein the processor selects the separate bandwidth utilization scheme for each corresponding cluster by being configured to execute the computer instructions to: select a first frequency domain for synchronization signal block transmissions for a first cluster of terrestrial cells; and select a second frequency domain for synchronization signal block transmissions for a second cluster of terrestrial cells, wherein the second frequency domain is different from the first frequency domain.

19. The system of claim 14, wherein each terrestrial cell of the plurality of terrestrial cells is configured to: receive a bandwidth utilization scheme; divide a coverage area of the terrestrial cell into at least a first region and a second region, wherein the first region is closer to the terrestrial cell than the second region; obtain a corresponding location indicator for each user device connected to the terrestrial cell; determine whether each user device connected to the terrestrial cell is in the first region or the second region based on the corresponding location indicator for each user device; for each user device determined to be in the first region, transmit; and for each user device determined to be in the second region: select a bandwidth part for data to be transmitted to the user device based on the received bandwidth utilization scheme; and transmit the data to the user device using the selected bandwidth part.

20. The system of claim 14, wherein the processor is configured to further execute the computer instructions to: generate the separate bandwidth utilization schemes for each corresponding cluster to include a first order in which corresponding terrestrial cells of each corresponding cluster are to allocate physical resource blocks; and generate the other bandwidth utilization scheme to include a second order in which the non-terrestrial cell is to allocate physical resource blocks, wherein the second order is different from the first order.
