

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250275709

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Talkachova; Alena

ATRIAL FIBRILLATION INSTABILITY DIAGNOSIS AND TREATMENT

Abstract

In a method of identifying a type of AF complexity and/or a treatment of AF based on the type of AF complexity, electrocardiogram (ECG) data associated with a patient is received, the ECG data includes AF signals corresponding to AF episodes. An AF burden (AFB) score is calculated using the ECG data based upon a frequency of the AF episodes or a duration of the AF episodes. An electrical burden (EB) score indicating a variation and distribution of electrical properties of the AF signals is calculated based on EB values of the ECG data in accordance with a plurality of approaches. A complexity AF score is calculated by summing the AFB and the EB scores. A type of AF complexity and/or a treatment is identified based on the complexity AF score. The complexity AF score, the identified type and/or the identified treatment is output on a display device.

Inventors: Talkachova; Alena (Shoreview, MN)

Applicant: Regents of the University of Minnesota (Minneapolis, MN)

Family ID: 96881561

Appl. No.: 19/061008

Filed: February 24, 2025

Related U.S. Application Data

us-provisional-application US 63560010 20240301

Publication Classification

Int. Cl.: A61B5/361 (20210101); A61B5/339 (20210101)

U.S. Cl.:

Background/Summary

FIELD

[0001] Embodiments of the present disclosure relate to systems and methods for diagnosing particular types of Atrial Fibrillation using electrocardiogram data and identifying a targeted treatment of the diagnosed condition.

BACKGROUND

[0002] Atrial Fibrillation (AF) is a common cardiac arrhythmia in the United States that increases the risk of stroke and can lead to other fatal heart disease. By 2050, it is estimated that 6-12 million people in the United States will have AF.

[0003] Clinically, AF is categorized into paroxysmal, persistent, long-standing persistent, and permanent AF. AF typically begins as paroxysmal episodes but can progress to more severe forms that do not resolve spontaneously. As AF progresses, the risk of cardiovascular complications and worsened symptoms increases. Early identification and appropriate management of AF progression are crucial for improving patient outcomes and treatment strategies. However, most data and analysis on AF and AF progression are gathered with intermittent and short rhythm monitoring, providing limited information on the total burden and the temporal pattern of AF.

[0004] Various metrics have been developed to quantify the complexity and severity of AF by assessing its presence in electrocardiograms (ECGs), including AF burden (AFB). Different definitions of AFB have been presented, such as the duration of the longest AF episode, and the total number of AF episodes during a monitoring period. Typically, AFB is calculated as the percentage of time that a patient is in AF, and does not account for any information regarding complexity of the AF ECG signal. Therefore, current AFB metrics have several limitations preventing them from becoming reliable clinical tools for therapeutic decisions regarding AF management, such as stroke risk and mortality. Assessing risk of AF from different aspects remains crucial for improving patient outcomes.

[0005] Using various aspects of AF signal characteristics for risk assessment helps improve patient outcomes. At present, several prognostic scores are available to identify patients at risk of developing sustained forms of AF. Many prognostic scores incorporate question-based scales for risk assessment, which determine frequency, duration, and severity of AF episodes for risk stratification. However, these scores may be challenging to use in everyday clinical practice, due to the qualitative nature of patient responses. Other risk assessments such as the HATCH score and Framingham-AF incorporate quantitative metrics only.

SUMMARY

[0006] Embodiments of the present disclosure operate to improve the treatment of AF using a complexity AF score that is based on the intrinsic complexity of ECG signals recorded during AF. The complexity AF score is used to identify a type of AF condition or AF complexity the patient has, which may be used to identify a corresponding treatment for the AF condition.

[0007] In a computer-implemented method of identifying a type of AF complexity and/or a treatment of AF based on the type of AF complexity according to one embodiment, electrocardiogram (ECG) data associated with a patient undergoing a series of AF episodes is received, the ECG data includes AF signals corresponding to the AF episodes. An AF burden (AFB) score is calculated using the ECG data based upon a frequency of the AF episodes or a duration of the AF episodes. An electrical burden (EB) score indicating a variation and distribution of electrical properties of the AF signals is calculated based on EB values of the ECG data corresponding to a AF complexity metrics calculated in accordance with a plurality of approaches.

A complexity AF score is calculated by summing the AFB and the EB scores. A type of AF complexity and/or a treatment corresponding to the type of AF complexity is identified based on the complexity AF score. The complexity AF score, the type of AF complexity, and/or the treatment for the type of AF complexity is output on a display device.

[0008] One embodiment of a system for identifying a type of atrial fibrillation (AF) complexity and/or a treatment of AF based on the type of AF includes memory, a display device and a controller. The controller is configured to: receive electrocardiogram (ECG) data associated with a patient undergoing a series of AF episodes, the ECG data including AF signals corresponding to the AF episodes; calculate an AF burden (AFB) score using the ECG data based upon a frequency of the AF episodes or a duration of the AF episodes; calculate an electrical burden (EB) score indicating a variation and distribution of electrical properties of the AF signals based on EB values of the ECG data corresponding to a AF complexity metrics calculated in accordance with a plurality of approaches; calculate a complexity AF score comprising a sum of the AFB and the EB scores; identify a type of AF complexity and/or a treatment corresponding to the type of AF complexity based on the complexity AF score; and output the complexity AF score, the type of AF complexity, and/or the treatment for the type of AF complexity on a display device.

[0009] This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter. The claimed subject matter is not limited to implementations that solve any or all disadvantages noted in the Background.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a flowchart illustrating a method of treating an AF condition of a patient, in accordance with embodiments of the present disclosure.

[0011] FIG. 2 is a simplified diagram of an example system for performing one or more steps of the method, in accordance with embodiments of the present disclosure.

[0012] FIG. 3 is a table illustrating an example of categorizations (low, middle or high) of AFB values and average EB values and their corresponding EB score.

[0013] FIG. 4 is a simplified diagram of an example of a controller, in accordance with embodiments of the present disclosure.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0014] Embodiments of the present disclosure are described more fully hereinafter with reference to the accompanying drawings. Elements that are identified using the same or similar reference characters refer to the same or similar elements. The various embodiments of the present disclosure may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the present disclosure to those skilled in the art.

[0015] The diagnosis of medical conditions determines the corresponding treatments for the conditions to minimize the effects of the conditions. As mentioned above, patients suffering from AF may fall into different categories (e.g., paroxysmal, persistent, long-standing persistent, and permanent AF) having different treatments. For example, patients with paroxysmal AF may be successfully treated with a drug regimen that may provide little benefit to a patient with sustained or permanent AF. Instead, heart tissue ablation treatments are typically more effective in treating patients with sustained or permanent AF. Therefore, it is accepted that paroxysmal AF is typically less complex than persistent and permanent AF, and therefore might require different treatment

approaches.

[0016] Embodiments of the present disclosure relate to methods of identifying a complexity of a particular type of AF condition a patient has from among a plurality of different types of AF conditions, for which different treatments are recommended, based on a complexity AF score. The complexity AF score incorporates both an AFB score and an EB score. The AFB score reflects the frequency or duration of AF episodes, while the EB score assesses the variation and distribution of AF signals' electrical properties over time, using different metrics. The combination of these metrics into the complexity AF score provides a more comprehensive understanding of AF complexity and aids in the identification of high-risk patients who may benefit from more intensive monitoring or therapeutic interventions. As a result, the complexity AF score may be used to identify a complexity of a particular type of AF and a corresponding treatment to treat the AF condition. Accordingly, the methods of the present disclosure allow a physician to prescribe and/or apply a recommended treatment for a patient's AF condition, while avoiding potentially unnecessary and ineffective treatments. As a result, embodiments of the present disclosure operate to improve the efficiency and efficacy of AF treatments.

[0017] FIG. 1 is a flowchart illustrating a method of treating an AF condition of a patient, in accordance with embodiments of the present disclosure. FIG. 2 is an example of a system **100** for performing one or more steps of the method.

[0018] Some embodiments of the method utilize ECGs, which are a common cardiovascular diagnostic test used to diagnose and treat different heart conditions including AF. ECGs generally relate to a measurement of electrical potential differentials or voltage differences between various locations on the surface of a patient's body. The ECG is formed by a plot of the voltage difference over time, such as at a rate of 300-500 voltage difference samples per second.

[0019] Embodiments of the system **100** include a controller **102**, memory **104**, an ECG device **106**, and/or a display **114**. The memory **104** includes one or more memory devices or databases, and represents local memory, remote memory, and/or memory of the controller **102**, for example. The controller **102** generally operates to perform one or more functions described herein including steps of the method of FIG. 1, in response to the execution of program instructions, which may be stored in the memory **104**, memory of the controller **102**, and/or another source of memory. The memory **104** and other memory described herein includes any suitable patent eligible memory and does not include transitory waves or signals.

[0020] The ECG device **106** may be a conventional device used to collect ECG data of a patient **110**. ECG data **112** that is acquired using the ECG device **106** may be stored in the memory **104** for use by the controller **102**.

[0021] The controller **102** processes the ECG data **112** that is received from the ECG device **106** for a patient and/or obtained from the memory **104** to identify a type of AF complexity and/or AF condition the patient has, and the corresponding treatment, in accordance with the method of FIG. 1. The system **100** may include a display **114** for displaying information, such as the identified type of AF condition and/or the corresponding treatment for the AF condition. The controller **102** may communicate data **116** using conventional techniques, such as data relating to the ECG data **112**, the identified AF condition type, the determined treatment, and/or other information, such as the calculated values discussed below and information stored in the memory **104**, for example.

[0022] At **120** of the method, ECG data **112** is acquired from a patient **110** during an episode of AF. This ECG data **112** may be collected and obtained using the ECG device **106** and/or obtained from the memory **104**. The ECG data **112** may comprise distinct electrical potential measurements taken over a period of time in accordance with conventional techniques. For example, the ECG data **112** may be collected at a frequency of about 128 Hz. Additionally, the ECG device **106** or the controller **102** may filter the collected ECG data **112**, such as using a bandpass filter (e.g., 0.5-40 Hz) to remove baseline wander and/or noise, for example. Also, the ECG data **112** may relate to a single examination of the patient **110** or multiple examinations of the patient **110**.

[0023] At **124** of the method, the controller **102** calculates an AFB score **126**, which indicates a frequency or duration of AF episodes in the ECG data. In one embodiment, the ECG data **112** is processed by the controller **102** to identify the duration of any AF episodes and the total recording duration. The AF episodes may be identified by the controller using conventional techniques, such as change in heart rate variability, and the duration may be determined based on a sampling frequency of the ECG data or a corresponding time measurement, or through a manual process.

[0024] In one embodiment, an AFB value for the ECG data **112** is determined by calculating the percentage of time that the patient has AF rhythm as defined by Equation 1.

$$[00001] \text{ AFB} = \frac{\text{totaldurationofAFrhythm}}{\text{totaldurationofrecording}} \times 100. \quad (1)$$

[0025] In some embodiments, the AFB value may be classified as low (L), medium (M), or high (H). The classification of the AFB values may be based on predefined thresholds. For example, a threshold AFB value of 20% may separate the low classification from medium classification, and a threshold AFB value of 80% may separate the medium classification from the high classification, as indicated in Table 1 of FIG. 3.

[0026] In one embodiment, the AFB score is assigned based on the classification of the AFB value. For example, an AFB score of 0 may be assigned when the AFB value is classified as low, an AFB score of 1 may be assigned when the AFB value is classified as medium, and an AFB score of 2 may be assigned when the AFB value is classified as high, as indicated in FIG. 3. In one example, an AFB value less than about 20% may be classified as low, an AFB value in the range of about 20-80% may be classified as medium, and an AFB value greater than about 80% may be classified as high.

[0027] At **126** of the method, an EB score **128** is calculated or determined using the controller **102** and is used to assess electrical instability in AF signals. Studies have shown that the EB does not correlate with AFB and can have different values for both low AFB as well as for high AFB. Accordingly, the electrical instability of the AF signal has been found to be an independent and supplemental marker to the AFB score, thus describing another aspect of complexity of AF signals.

[0028] Additionally, temporal changes in complexity of dominant frequency (DF), multi-scale frequency (MSF), multi-scale entropy (MSE), and Shannon entropy (SE) do not directly correlate with the AFB. For instance, DF and SE complexity over time may be different between patients with high AFB and patients with low AFB. These findings underscore the distinction between EB and AFB, highlighting their divergent roles in characterizing ECG signals.

[0029] Step **126** may be performed before, after, concurrently or partially concurrently with the performance of step **124**. In one embodiment, the controller **102** calculates or determines the EB score **128** based on EB values **130**. The EB values **130** may be calculated by partitioning the ECG data **112** into predefined segments, each corresponding to a time interval. Embodiments of the time intervals include include 10-60 second intervals, such as 30-second intervals, or other time intervals. Thus, when the ECG data **112** comprises data from a 20 hour ECG recording, the ECG data **112** may be divided into 2400 30-second segments.

[0030] EB values corresponding to conventional AF complexity metrics may be calculated for each ECG data segment using the controller **102** in accordance with various approaches including DF, MSF, MSE, SE, and/or other approaches. The controller **102** may then determine a percentage of signals that deviate beyond one standard deviation (SD) from the distribution of AF complexity, measured through the different approaches ([appr]). For example, the controller **102** may perform a calculation for EB values **130** as indicated in Equation 2.

$$[00002] \text{ EB}_{[\text{appr}]} = \frac{\text{count}(\text{.Math.}[\text{appr}] \text{ values} - \text{mean}([\text{appr}] \text{ values}) .\text{Math.} > \text{SD}([\text{appr}] \text{ values}))}{N([\text{appr}] \text{ values})} \times 100. \quad (2)$$

[0031] Here, the notation $N([\text{appr}] \text{ values})$ denotes the total number of estimated values for each approach (DF, MSF, MSE, SE etc), which relates to the number of ECG data segments that are being analyzed. For example, when the ECG data **112** is divided into 2400 30-second segments

from a 20 hour ECG recording, 2400 ECG data segments are analyzed by the controller **102** under each approach.

[0032] In some embodiments, a number of outliers in the AF complexity metrics (numerator), EB.sub.[appr] represent different levels of ECG instability, based on the specific approach used to calculate it. Therefore, it can reflect, for example, frequency-based, statistical-based, and information-based complexity of the ECG data **112** (e.g., signal or recording) during AF.

[0033] Each of the EB values **130** calculated using Eq. 2 may be classified in step **126** as a low complexity value indicating electrical stability of the ECG signal or data **112**, or a high complexity value indicating electrical instability in the ECG signal or data **112** based on a threshold EB value. The threshold EB value for designating the EB values as low or high complexity may be set based on the particular approach. For example, an EB value threshold of 25% may be used, such that an EB value **130** of less than or equal to 25% is classified as low complexity and an EB value of greater than 25% is classified as high complexity.

[0034] To ensure an equal contribution from the EB and AFB calculations, the average of the EB values (<EB>) calculated for the different approaches may be classified as low (L), medium (M), or high (H) based on a number of EB values (e.g., 2) classified as high complexity, and the EB score is assigned based on the classification, as indicated in Table 1 of FIG. 3. For example, an EB score of 0 may be assigned when the average EB value is classified as low, an EB score of 1 may be assigned when the average EB value is classified as medium, and an EB score of 2 may be assigned when the average EB value is classified as high, as indicated in FIG. 3.

[0035] At **132** of the method, a complexity AF score **134** for a patient is calculated or determined using the controller **102** based on the AFB score **126** and the EB score **128** for the patient. The complexity AF score **134** indicates a likelihood of a patient developing complex AF. The incorporation of both the AFB and EB in the complexity AF score provides valuable insights into the temporal and electrical instability of the AF signals in the ECG data. The AFB score **126** reflects the frequency or duration of AF episodes, while the EB score **128** assesses the variation and distribution of AF signals' electrical properties over time, using different metrics or approaches. Combining these metrics provides a more comprehensive understanding of AF complexity, aiding in the identification of high-risk patients who may benefit from more intensive monitoring or therapeutic interventions. Thus, the complexity AF score is effective at describing the complexity of AF, such as paroxysmal AF and persistent AF and provides a more comprehensive evaluation of AF dynamics than that provided through an analysis of the AFB score **126** and the EB score **128** individually. As a result, the complexity AF score **134** may be used to determine effective targeted treatment strategies for AF patients, while avoiding potentially unnecessary and ineffective treatments.

[0036] Patients with a low AFB score **126** and a low EB score **128** have a lower risk of developing complex AF. This is because both time-based complexity metrics of the AF signals are classified as low. Conversely, patients with a high AFB score **126** and a high EB score **128** have a higher risk of developing complex AF due to unstable ECG signals.

[0037] In one embodiment, the complexity AF score **134** is calculated in step **132** by summing the AFB score **126** and the EB score **128**. Thus, the AFB score **126** and the EB score **128** may be assigned values based on a complexity level as described above with reference to Table 1, and the complexity AF score **134** may be calculated by adding the scores corresponding to the complexity levels together. Based on these example AFB scores **126** and EB scores **128**, the complexity AF score can range from 0-4. A complexity AF score **134** of zero (0) may, for example, indicate sinus rhythm, a low complexity AF score of 1-2 may indicate that the patient has a moderate chance of developing complex AF, and a high AF score of 3-4 may indicate that the patient has a high chance of developing complex AF.

[0038] The complexity AF score **134** may be stored in the memory **104**. In some embodiments, the controller **102** may output information that includes or relates to the AF score, such as by

communicating the information to a database, issuing a report (e.g., document, email, etc.) containing the information, and/or outputting the information in another form, for example.

[0039] At **136** of the method, a type of AF condition **138** and/or a corresponding recommended treatment **140** may be identified by the controller **102**, such as through a mapping of complexity AF scores **134** to a plurality of AF condition types **138** and treatments **140** stored in the memory **104**.

[0040] Examples of the AF condition types that may be identified based on a complexity AF score include paroxysmal and persistent AF. Examples of the recommended treatments **140** that correspond to the identified condition types include a drug regimen, such as heart rate controlling drugs (for example, beta blockers and calcium channel blockers), or heart rhythm controlling drugs (for example, potassium and sodium channel blockers), for low complexity AF scores **134**, and an ablation treatment of heart tissue may be recommended for high complexity AF scores **134**.

[0041] Information that includes or relates to the AF condition type **138** and/or the recommended treatment **140** may be stored in the memory **104** and/or output by the controller **102**, such as by communicating the information to a database, issuing a report (e.g., document, email, etc.) containing the information, and/or outputting the information in another form, for example.

[0042] In some embodiments, the AF condition type **138** of the patient may be treated at **142** of the method using the recommended treatment **140** corresponding to the complexity AF score **134** or AF condition type **138**.

[0043] The controller **102** may take on any suitable form and may represent a single controller or multiple controllers. FIG. **4** is a simplified diagram of an example of the controller **102** in accordance with embodiments of the present disclosure. The controller **102** may include one or more processors **150** and memory **152**. The one or more processors **150** are configured to perform various functions of the system **100** described herein, such as steps of the method of FIG. **1**, and/or other functions described herein, in response to the execution of instructions contained in the memory **152**.

[0044] The one or more processors **150** may be components of one or more computer-based systems, and may include one or more control circuits, microprocessor-based engine control systems, and/or one or more programmable hardware components, such as a field programmable gate array (FPGA). The memory **152** represents local and/or remote memory or computer readable media and may represent the memory **104** of the system **100**. Such memory **152** comprises any suitable patent subject matter eligible computer readable media and does not include transitory waves or signals. Examples of the memory **152** include conventional data storage devices, such as hard disks, CD-ROMs, optical storage devices, magnetic storage devices and/or other suitable data storage devices. The controller **102** may include circuitry **154** for use by the one or more processors **150** to receive input signals **156** (e.g., ECG signals), issue control signals **158** (e.g., signals that control the display **114**, etc.), and/or communicate data **160**, such as in response to the execution of the instructions stored in the memory **152** by the one or more processors **150**.

[0045] Although the embodiments of the present disclosure have been described with reference to preferred embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the present disclosure.

Claims

1. A computer-implemented method of identifying a type of atrial fibrillation (AF) complexity and/or a treatment of AF based on the type of AF comprising: receiving electrocardiogram (ECG) data associated with a patient undergoing a series of AF episodes, the ECG data including AF signals corresponding to the AF episodes; calculating an AF burden (AFB) score using the ECG data based upon a frequency of the AF episodes or a duration of the AF episodes; calculating an electrical burden (EB) score indicating a variation and distribution of electrical properties of the AF signals based on EB values of the ECG data corresponding to a AF complexity metrics calculated

in accordance with a plurality of approaches; calculating a complexity AF score comprising a sum of the AFB and the EB scores; identifying a type of AF complexity and/or a treatment corresponding to the type of AF complexity based on the complexity AF score; and outputting the complexity AF score, the type of AF complexity, and/or the treatment for the type of AF complexity on a display device.

2. The method according to claim 1 wherein: identifying the type of AF complexity and/or the treatment corresponding to the type of AF complexity based on the complexity AF score comprises identifying the type of AF and the treatment corresponding to the identified type of AF based on the complexity AF score; outputting the complexity AF score, the type of AF complexity and/or the treatment for the type of AF complexity comprises outputting the AF score, the type of AF complexity and the treatment on the display device; and the method includes treating the patient in accordance with the identified treatment.

3. The method according to claim 2, wherein the treatment is selected from the group consisting of: applying a drug regimen to the patient when the AF score indicates a low complexity type of AF; and ablating heart tissue of the patient when the AF score indicates a high complexity type of AF.

4. The method according to claim 1, wherein the AFB score is calculated based on an AFB value, which is calculated using the following equation: $AFB = \frac{\text{totaldurationofAFrhythm}}{\text{totaldurationofrecording}} \times 100$, wherein the “total duration of AF rhythm” corresponds to a duration of the AF episodes, and the “total duration of recording” corresponds to the period corresponding to the ECG data.

5. The method according to claim 4, wherein the EB values of the ECG data for each approach (EB[appr]) are calculated based on the following equation:

$$EB_{[appr]} = \frac{\text{count}(.Math. [appr]values - \text{mean}([appr]values) .Math. > SD([appr]values))}{N([appr]values)} \times 100, \text{ wherein “appr”}$$

corresponds to an AF complexity metric calculated using the approach, “[appr] values” denotes AF complexity metric values of the AF signals in the ECG data calculated using the particular approach, “count(|[appr]values–mean([appr] values)|>SD([appr] values)” denotes a count of the absolute value of the [appr] values minus the mean of the [appr] values being greater than a standard deviation of the [appr] values, and N([appr] values) denotes a total number of the [appr] values.

6. The method according to claim 5, wherein the ECG data is partitioned into predefined segments, and each [appr] value corresponds to the AF complexity metric value in one of the segments.

7. The method according to claim 6, wherein the predefined segments of the ECG data each correspond to a time interval of 10-60 seconds.

8. The method according to claim 6, wherein the plurality of approaches are selected from the group consisting of dominant frequency (DF), multiscale frequency (MSF), multiscale entropy (MSE) and Shannon entropy (SE).

9. The method according to claim 6, wherein the EB score is based on an average of the EB values from the plurality of approaches.

10. The method according to claim 9, including: classifying the average of the EB values as low complexity indicating electrical stability or high complexity indicating electrical instability based on a threshold EB value; and assigning the EB score based on a number of the EB values classified as high complexity.

11. The method according to claim 10, including: classifying the AFB value as low complexity, a medium complexity or a high complexity; and assigning the AFB score based on the classification of the AFB value.

12. A system for identifying a type of atrial fibrillation (AF) complexity and/or a treatment of AF based on the type of AF comprises: memory; a display device; and a controller configured to: receive electrocardiogram (ECG) data associated with a patient undergoing a series of AF episodes, the ECG data including AF signals corresponding to the AF episodes; calculate an AF burden (AFB) score using the ECG data based upon a frequency of the AF episodes or a duration of the AF

episodes; calculate an electrical burden (EB) score indicating a variation and distribution of electrical properties of the AF signals based on EB values of the ECG data corresponding to a AF complexity metrics calculated in accordance with a plurality of approaches; calculate a complexity AF score comprising a sum of the AFB and the EB scores; identify a type of AF complexity and/or a treatment corresponding to the type of AF complexity based on the complexity AF score; and output the complexity AF score, the type of AF complexity, and/or the treatment for the type of AF complexity on a display device.

13. The system according to claim 12 wherein: the identification of the type of AF complexity and/or the treatment corresponding to the type of AF complexity identified based on the complexity AF score comprises identifying the type of AF and the treatment corresponding to the identified type of AF based on the complexity AF score; and the output of the complexity AF score, the type of AF complexity and/or the treatment for the type of AF complexity comprises an output of the AF score, the type of AF complexity and the treatment on the display device.

14. The system according to claim 13, wherein the identified treatment is selected from the group consisting of: applying a drug regimen to the patient when the AF score indicates a low complexity type of AF; and ablating heart tissue of the patient when the AF score indicates a high complexity type of AF.

15. The system according to claim 12, wherein the AFB score is calculated based on an AFB value, which is calculated using the following equation: $AFB = \frac{\text{totaldurationofAFrhythm}}{\text{totaldurationofrecording}} \times 100$, wherein the “total duration of AF rhythm” corresponds to a duration of the AF episodes, and the “total duration of recording” corresponds to the period corresponding to the ECG data.

16. The system according to claim 15, wherein the EB values of the ECG data for each approach (EB[appr]) are calculated based on the following equation:

$$EB_{[appr]} = \frac{\text{count}(.Math. [appr]values - \text{mean}([appr]values) .Math. > SD([appr]values))}{N([appr]values)} \times 100, \text{ wherein “appr”}$$

corresponds to an AF complexity metric calculated using the approach, “[appr] values” denotes AF complexity metric values of the AF signals in the ECG data calculated using the particular approach, “count(|[appr]values–mean([appr] values)|>SD([appr] values)” denotes a count of the absolute value of the [appr] values minus the mean of the [appr] values being greater than a standard deviation of the [appr] values, and N([appr] values) denotes a total number of the [appr] values.

17. The system according to claim 16, wherein the controller is configured to partition the ECG data into predefined segments, and each [appr] value corresponds to the AF complexity metric value in one of the segments.

18. The system according to claim 17, wherein the plurality of approaches are selected from the group consisting of dominant frequency (DF), multiscale frequency (MSF), multiscale entropy (MSE) and Shannon entropy (SE).

19. The system according to claim 18, wherein the controller is configured to: classify an average of the EB values as low complexity indicating electrical stability or high complexity indicating electrical instability based on a threshold EB value; and assigning the EB score based on a number of the EB values classified as high complexity.

20. The system according to claim 19, wherein the controller is configured to: classify the AFB value as low complexity, a medium complexity or a high complexity; and assign the AFB score based on the classification of the AFB value.
