

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285040

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Woo; Jae Yul et al.

ELECTRONIC DEVICE, SERVER AND METHOD FOR PROVIDING A PERSONAL MOBILITY SERVICE OF A SERVER

Abstract

An embodiment server includes a communication device, a memory configured to store information about personal mobility vehicles and user information about users, and a control device electrically connected to the communication device and the memory, the control device being configured to receive a first authentication request of a first user of an electronic device from the electronic device through the communication device, receive an authentication request of a first personal mobility vehicle of the plurality of personal mobility vehicles from the first personal mobility vehicle through the communication device, authenticate the first authentication request of the first user, authenticate the authentication request of the first personal mobility vehicle, and transmit unlock information of the first personal mobility vehicle to the first personal mobility vehicle through the communication device based on both authentications.

Inventors: Woo; Jae Yul (Seoul, KR), Kim; Soobin (Seoul, KR), Woo; Seunghyun (Seoul, KR), An; Rowoon (Seoul, KR)

Applicant: Hyundai Motor Company (Seoul, KR); Kia Corporation (Seoul, KR)

Family ID: 81588541

Appl. No.: 19/218928

Filed: May 27, 2025

Foreign Application Priority Data

KR 10-2020-0151861

Nov. 13, 2020

Related U.S. Application Data

parent US division 17502886 20211015 parent-grant-document US 12340321 child US 19218928

Publication Classification

Int. Cl.: **G06Q10/02** (20120101); **B60R25/24** (20130101); **G06Q30/0283** (20230101); **G06Q30/0645** (20230101); **G06Q50/40** (20240101); **G07C9/00** (20200101); **G07C9/22** (20200101); **G07C9/27** (20200101); **G07C9/32** (20200101); **G07C9/38** (20200101); **G07F17/00** (20060101)

U.S. Cl.:

CPC **G06Q10/02** (20130101); **B60R25/24** (20130101); **G06Q30/0284** (20130101); **G06Q50/40** (20240101); **G07C9/00571** (20130101); **G07C9/22** (20200101); **G07C9/27** (20200101); **G07C9/32** (20200101); **G07C9/38** (20200101); **G07F17/0057** (20130101); **G06Q30/0645** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a divisional of U.S. patent application Ser. No. 17/502,886, filed on Oct. 15, 2021, which claims the benefit of Korean Patent Application No. 10-2020-0151861, filed on Nov. 13, 2020, which applications are hereby incorporated herein by reference.

TECHNICAL FIELD

[0002] The disclosure relates to an electronic device, a server, and a method for providing a personal mobility service of the server.

BACKGROUND

[0003] A personal mobility vehicle is a device for transporting an individual, and may include an electric wheel, an electric kickboard, an electric skateboard, and/or an electric bicycle. Recently, due to the increase in demand for personal mobility vehicles, the number of personal mobility-sharing service providers has been increased.

[0004] Until now, services of the personal mobility-sharing service providers have not been integrated, and thus a single integrated service has not been provided. The personal mobility-sharing service providers each provide separate services so as to allow a user to use only the service of the sharing service providers to which the user has subscribed. Accordingly, in the conventional manner, for a user to use services of different sharing service providers, the user has to install all different applications provided from the sharing service providers and subscribe to the services, which may cause inconvenience.

SUMMARY

[0005] Therefore, an embodiment of the disclosure provides an electronic device, a server, and a method for providing a personal mobility service of the server, capable of providing a personal mobility service capable of accommodating various platforms of personal mobility service providers.

[0006] For example, an embodiment of the disclosure provides an electronic device, a server, and a method for providing a personal mobility service of the server, capable of providing a personal mobility service capable of allowing a user to rent, use, and return a personal mobility vehicle by using a user's electronic device, and/or to pay a usage fee of the personal mobility vehicle by using the user's electronic device.

[0007] Additional embodiments of the disclosure will be set forth in part in the description which follows and, in part, will be obvious from the description, or may be learned by practice of the disclosure.

[0008] In accordance with an embodiment of the disclosure, a server includes a communication device, a memory configured to store information about a plurality of personal mobility vehicles and user information about users, and a control device electrically connected to the communication device and the memory. The control device is configured to receive a first authentication request of a user of an electronic device from the electronic device through the communication device, configured to receive an authentication request of a first personal mobility vehicle from the first personal mobility vehicle through the communication device, configured to authenticate the first authentication request of the user based on the user information about the users stored in the memory, and authenticate the authentication request of the first personal mobility vehicle based on the information about the plurality of personal mobility vehicles stored in the memory, and configured to transmit unlock information of the first personal mobility vehicle to the first personal mobility vehicle through the communication device based on the authentication of the first authentication request and the authentication of the authentication request of the first personal mobility vehicle.

[0009] The control device may be configured to receive service use request information of the server from the electronic device through the communication device, configured to authenticate, in response to receiving the service use request information of the server, a second authentication request of the user based on the user information about the users stored in the memory, and configured to transmit authentication completion information about the second authentication request of the user to the electronic device through the communication device.

[0010] The control device may be configured to receive, from the electronic device through the communication device, at least one piece of information between information about a selection of the first personal mobility vehicle by the electronic device and information about communication between the electronic device and the first personal mobility vehicle, and configured to authenticate the first authentication request and the authentication request of the first personal mobility vehicle based on the reception of the at least one piece of information.

[0011] The control device may be configured to transmit authentication completion information about the first authentication request to the electronic device through the communication device, and transmit authentication completion information about the authentication request of the first personal mobility vehicle to the first personal mobility vehicle through the communication device, and configured to transmit unlock information of the first personal mobility vehicle to the first personal mobility vehicle through the communication device based on the transmission of the authentication completion information about the first authentication request and the transmission of the authentication completion information about the authentication request of the first personal mobility vehicle.

[0012] The control device may be configured to receive use time information and use distance information of the first personal mobility vehicle from the electronic device through the communication device, configured to calculate, in response to receiving the use time information and the use distance information, a service usage fee of the first personal mobility vehicle of the electronic device based on a predetermined fee calculation condition corresponding to personal mobility vehicle use times and use distances, and configured to transmit information about the service usage fee to the electronic device through the communication device.

[0013] When the information of the first personal mobility vehicle is stored in a first server of a first service provider and the user information of the electronic device is stored in a second server of a second service provider, the service usage fee may include a first fee of the first server and a second fee of the second server.

[0014] The control device may be configured to receive service information about the first personal mobility vehicle from the first server of the first service provider through the communication device, and configured to transmit the service information about the first personal mobility vehicle to the electronic device through the communication device.

[0015] The control device may be configured to convert a communication protocol of the first server into a predetermined standard protocol of the server.

[0016] In accordance with another embodiment of the disclosure, an electronic device includes an input device, a display, a communicator, and a processor electrically connected to the input device, the display, and the communicator. The processor is configured to control the display to output information about a plurality of personal mobility vehicles included in each of a plurality of service providers based on current location information of the electronic device or location information selected through the input device, configured to transmit, based on the communication with a first personal mobility vehicle among the plurality of personal mobility vehicles through the communicator, a first information about the first personal mobility vehicle to a server, and configured to receive service information about the first personal mobility vehicle from the server through the communicator in response to the transmission of the first information.

[0017] The plurality of personal mobility vehicles may include personal mobility vehicles available in a region corresponding to the current location information of the electronic device or the location information selected through the input device.

[0018] The processor may be configured to receive information about a service usage fee of the first personal mobility vehicle from the server through the communicator when the processor identifies termination of the use of the first personal mobility vehicle.

[0019] The processor may be configured to identify termination of the use of the first personal mobility vehicle based on a user input through the input device or a release of the communication with the first personal mobility vehicle.

[0020] The processor may be configured to transmit use time information and use distance information of the first personal mobility vehicle to the server through the communicator when the processor identifies termination of the use of the first personal mobility vehicle.

[0021] The service usage fee of the first personal mobility vehicle may include a first fee based on a first service of a first service provider that provides the service of the first personal mobility vehicle and the use of the first personal mobility vehicle, and a second fee based on a second service of a second service provider subscribed to by the user of the electronic device and the use of a platform of the second service provider.

[0022] The selected location information may include information about at least one region selected through the input device, and the plurality of personal mobility vehicles included in each of the plurality of service providers may be located in the at least one region.

[0023] The processor may be configured to control the display to output information about whether the plurality of service providers and the plurality of personal mobility vehicles included in the plurality of service providers, which are available to the user of the electronic device, are present or not.

[0024] In accordance with another embodiment of the disclosure, a method for providing a personal mobility service of a server includes receiving, by a server, a first authentication request of a user of an electronic device from the electronic device, receiving, by the server, an authentication request of a first personal mobility vehicle from the first personal mobility vehicle, authenticating, by the server, the first authentication request of the user based on pre-stored user information about users, and authenticating, by the server, the authentication request of the first personal mobility vehicle based on pre-stored information about a plurality of personal mobility vehicles, and transmitting, by the server, unlock information of the first personal mobility vehicle to the first personal mobility vehicle based on the authentication of the first authentication request and the authentication of the authentication request of the first personal mobility vehicle.

[0025] The method may further include receiving, by the server, service use request information from the electronic device, in response to receiving the service use request information of the server, authenticating, by the server, a second authentication request of the user based on the pre-stored user information about the users, and transmitting, by the server, authentication completion

information about the second authentication request of the user to the electronic device.

[0026] In accordance with another embodiment of the disclosure, a personal mobility vehicle includes a communication module and a control device electrically connected to the communication module. The control device is configured to communicate with a server through the communication module, configured to identify whether or not the personal mobility vehicle communicates with an electronic device through the communication module based on the electronic device being mounted to at least one portion of a frame, and configured to release the communication with the server based on the communication with the electronic device.

[0027] The control device may be configured to receive unlock information of the personal mobility vehicle transmitted from the server through the communication-connected electronic device, and configured to unlock the personal mobility vehicle based on the unlock information.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] These and/or other embodiments of the disclosure will become apparent and more readily appreciated from the following description of exemplary embodiments, taken in conjunction with the accompanying drawings, in which:

[0029] FIG. 1 is a block diagram illustrating a system according to an embodiment of the disclosure;

[0030] FIG. 2A is a block diagram illustrating a personal mobility vehicle according to an embodiment of the disclosure;

[0031] FIG. 2B is a view illustrating a type of the personal mobility vehicle according to an embodiment of the disclosure;

[0032] FIG. 3 is a view illustrating an operation of the system according to an embodiment of the disclosure;

[0033] FIG. 4 is a flow chart illustrating an operation of a server according to an embodiment of the disclosure;

[0034] FIG. 5 is a flow chart illustrating an operation of an electronic device according to an embodiment of the disclosure;

[0035] FIGS. 6A and 6B are flow charts illustrating an operation of the system according to an embodiment of the disclosure; and

[0036] FIG. 7 is a view illustrating a screen of a display of the electronic device according to an embodiment of the disclosure.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0037] In the following description, like reference numerals refer to like elements throughout the specification. Well-known functions or constructions are not described in detail since they would obscure one or more exemplar embodiments with unnecessary detail. Terms such as “unit”, “module”, “member”, and “block” may be embodied as hardware or software. According to embodiments, a plurality of “units”, “modules”, “members”, and “blocks” may be implemented as a single component or a single “unit”, “module”, “member”, and “block” may include a plurality of components.

[0038] It will be understood that when an element is referred to as being “connected” to another element, it can be directly or indirectly connected to the other element, wherein the indirect connection includes “connection via a wireless communication network”.

[0039] Also, when a part “includes” or “comprises” an element, unless there is a particular description contrary thereto, the part may further include other elements, not excluding the other elements.

[0040] Throughout the description, when a member is “on” another member, this includes not only

when the member is in contact with the other member, but also when there is another member between the two members.

[0041] It will be understood that, although the terms first, second, third, etc., may be used herein to describe various elements, the specification should not be limited by these terms. These terms are only used to distinguish one element from another element.

[0042] As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

[0043] An identification code is used for the convenience of the description but is not intended to illustrate the order of each step. Each step may be implemented in an order different from the illustrated order unless the context clearly indicates otherwise.

[0044] Reference will now be made in detail to embodiments of the disclosure, examples of which are illustrated in the accompanying drawings.

[0045] FIG. 1 is a block diagram illustrating a system 1 according to an embodiment of the disclosure, FIG. 2A is a block diagram illustrating a personal mobility vehicle according to an embodiment of the disclosure, and FIG. 2B is a view illustrating a type of the personal mobility vehicle according to an embodiment of the disclosure.

[0046] Referring to FIG. 1, the system 1 may include personal mobility vehicles 10, management servers 100, a server 150, and/or an electronic device 1000.

[0047] The personal mobility vehicles 10 may include a first personal mobility vehicle 12 and/or a second personal mobility vehicle 14.

[0048] The first personal mobility vehicle 12 and the second personal mobility vehicle 14 may include components corresponding to a personal mobility vehicle 200 of FIG. 2A, and may be implemented in a form corresponding to a personal mobility vehicle 200 of FIG. 2B.

[0049] Referring to FIG. 2A, the personal mobility vehicle 200 may include a battery 202, a communication module 204, a driving device 206, and/or a control device 208.

[0050] The battery 202 may supply power to at least one component of the personal mobility vehicle 200 (the communication module 204, the driving device 206 and/or the control device 208). For example, the battery 202 may supply power required to drive the personal mobility vehicle 200.

[0051] The communication module 204 may establish a wired and/or wireless communication channel between the personal mobility vehicle 200 and an external device, such as one of the management servers 100, the server 150 and/or the electronic device 1000, and support the communication between the personal mobility vehicle 200 and the external device through the established communication channel. For example, the communication module 204 may include a wireless communication module (e.g., a cellular communication module, a Wi-Fi communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) and/or a wired communication module (e.g., a local area network (LAN) or a power line communication module), and thus the communication module 204 may communicate with the external device. The communication module 204 may include communication circuitry.

[0052] The driving device 206 may control at least one motor of the personal mobility vehicle 200 and an operation of the at least one motor, such as a rotation direction and/or a rotation speed. For example, the driving device 206 may be controlled by the control device 208.

[0053] The control device 208 (also referred to as a control circuit or a processor) may control at least one other component of the personal mobility vehicle 200 (e.g., a hardware component (e.g., the battery 202, the communication module 204, and/or the driving device 206) or a software component (software program)) and may perform various data processing and calculations.

[0054] The control device 208 may include a processor (not shown) and a memory (not shown). For example, an operating system configured to accommodate multiple platforms (iPhone operating system (iOS), alternative operating system (AOS), etc.) may be stored in the memory.

[0055] The control device **208** may identify whether the personal mobility vehicle **200** communicates with the electronic device **1000** through the communication module **204**.

[0056] When a specified condition is satisfied (e.g., periodically at a predetermined time interval), the control device **208** may transmit location information of the personal mobility vehicle **200** to a management server of the personal mobility vehicle **200** among the management servers **100**, the server **150** and/or the electronic device **1000** through the communication module **204**.

[0057] For example, although not shown, the personal mobility vehicle **200** may further include a GPS module. The control device **208** may identify location information of the personal mobility vehicle **200** based on output signals of the GPS module, and the control device **208** may transmit the location information of the personal mobility vehicle **200** to the management server of the personal mobility vehicle **200** among the management servers **100**, the server **150** and/or the electronic device **1000** through the communication module **204**.

[0058] When a specified condition is satisfied (e.g., periodically at a predetermined time interval), the control device **208** may transmit information about the battery **202** (such as a charge amount) to the management server of the personal mobility vehicle **200** among the management servers **100**, the server **150** and/or the electronic device **1000** through the communication module **204**.

[0059] Referring to FIG. 2B, the personal mobility vehicle **200** may include a handle **212**, wheels **214** and **216**, and/or a footrest **218**.

[0060] The electronic device **1000** may be positioned and fixed to at least a portion **250** of a frame connected to the handle **212** of the personal mobility vehicle **200**.

[0061] For example, a structure, such as a mount (also referred to as a bracket) provided to fix the electronic device **1000** to at least a portion of the frame connected to the handle **212** of the personal mobility vehicle **200**, may be provided, and thus the electronic device **1000** may be fixed to the personal mobility vehicle **200** through the structure.

[0062] The personal mobility vehicle **200** may communicate with the electronic device **1000** through the wired or wireless communication.

[0063] For example, the personal mobility vehicle **200** may be implemented in such a way that a cable connected to the personal mobility vehicle **200** is connected to a connection terminal of the electronic device **1000** when the electronic device **1000** is mounted to the at least a portion **250** of the frame of the personal mobility vehicle **200**.

[0064] Alternatively, the personal mobility vehicle **200** may communicate with the electronic device **1000** through the wireless communication based on a control signal received from the electronic device **1000** through the communication module **204**, or based on a user input through an input device (not shown) of the personal mobility vehicle **200**.

[0065] For example, when the personal mobility vehicle **200** communicates with the electronic device **1000** through the wired or wireless communication, the battery **202** of the personal mobility vehicle **200** may be automatically charged. For example, the personal mobility vehicle **200** may further include a wireless charging circuit (not shown), and thus when the electronic device **1000** is mounted on the at least a portion **250** of the frame, the personal mobility vehicle **200** may wirelessly receive power from the electronic device **1000** through the wireless charging circuit.

[0066] For example, when the personal mobility vehicle **200** communicates with the electronic device **1000** through the wired or wireless communication, the personal mobility vehicle **200** may allow the electronic device **1000** to perform functions, such as a function of providing information about the battery **202** (such as a charging amount) of the personal mobility vehicle **200**, a function of communication with the management server of the personal mobility vehicle **200** among the management servers **100**, and/or the server **150** and/or a navigation function.

[0067] Although not shown, the personal mobility vehicle **200** may further include components such as a radar, a front light, an audio device, a rear wheel cover, a braking device, a suspension, a brake lever, a pressure sensor, a rear light and/or a haptic device.

[0068] In addition, a minimum of simple mechanisms and functions may be applied to the personal

mobility vehicle **200**, and a complicated operation process is performed in the communication-connected electronic device **1000**. Accordingly, it is possible to minimize the complicated operation process of the personal mobility vehicle **200** so as to reduce a manufacturing cost.

[0069] The management servers **100** may include a first server **102** and/or a second server **104**.

[0070] The management servers **100** may be servers for service provision of service providers that provide a sharing service of the personal mobility vehicles **10**.

[0071] For example, the management servers **100** may be servers of service providers registered (or subscribed) to the service of the server **150**.

[0072] For example, each of a plurality of service providers may locate the personal mobility vehicles **10** in one region or several regions, and provide a sharing service that allows users to use the personal mobility vehicles **10**.

[0073] For example, when it is assumed that a plurality of service providers includes a first service provider and a second service provider, the first server **102** may be a server of the first service provider, and the second server **104** may be a server of the second service provider. For example, the first service provider may provide a sharing service of personal mobility vehicles **10** of a first region, and the second service provider may provide a sharing service of personal mobility vehicles **10** of a second region.

[0074] The first server **102** may provide a sharing service for personal mobility vehicles including a first personal mobility vehicle **12** of the first service provider. The second server **104** may provide a sharing service for personal mobility vehicles including a second personal mobility vehicle **14** of the second service provider.

[0075] Although not shown, each of the first server **102** and the second server **104** may include a communication device configured to communicate with an external device, a memory configured to store data, and a control device configured to control components and configured to perform various data processing and calculation.

[0076] The server **150** may include a communication device **151**, a memory **153**, and a control device **155**.

[0077] The communication device **151** (also referred to as communication circuitry) may establish a wired and/or wireless communication channel between the server **150** and an external device, such as the personal mobility vehicles **10**, the management servers **100** and/or the electronic device **1000**, and support the communication between the server **150** and the external device through the established communication channel. For example, the communication device **151** may include a wireless communication module (e.g., a cellular communication module, a Wi-Fi communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) and thus the communication device **151** may communicate with the external device. The communication device **151** may include communication circuitry.

[0078] The memory **153** may store various data used by at least one component (the communication device **151** and/or the control device **155**) of the server **150**, particularly, the memory **153** may store input data or output data about software programs and instructions related to the software program. For example, the memory **153** may include a volatile memory and/or a non-volatile memory.

[0079] The memory **153** may store a program (or application program) related to sharing and/or management of the personal mobility vehicles **10**.

[0080] The memory **153** may store information about the plurality of personal mobility vehicles **10** included in the plurality of service providers, for example, servers of the plurality of service providers, that is, the management servers **100**. For example, the information about the plurality of personal mobility vehicles **10** may include identification information and information about a service provider corresponding to each of the plurality of personal mobility vehicles **10**.

[0081] The memory **153** may store user information about a user who is subscribed to services of the plurality of service providers.

[0082] The control device **155** (also referred to as a control circuit or a processor) may control at least one other component of the server **150** (e.g., a hardware component (e.g., the communication device **151** and/or the memory **153**) or a software component (software program)) and may perform various data processing and calculations. The control device **155** may include a processor and a memory.

[0083] The control device **155** may manage the personal mobility vehicles **10** based on information that is about the personal mobility vehicles **10** included in the plurality of service providers and is stored in the memory **153**.

[0084] Based on user information that is about a user who is subscribed to the service of each of the plurality of service providers and that is stored in the memory **153**, the control device **155** may provide a sharing service that allows a user to use the personal mobility vehicles **10**.

[0085] For example, based on the communication between the electronic device **1000** and the first personal mobility vehicle **12** through the communication device **151**, the control device **155** may perform user authentication for a user, having an intention to use the first personal mobility vehicle **12**, of the electronic device **1000** and authentication of the first personal mobility vehicle **12**.

[0086] For example, in order to unlock the first personal mobility vehicle **12**, the control device **155** may transmit first information including unlock information of the first personal mobility vehicle **12** to the first personal mobility vehicle **12** through the communication device **151**.

[0087] For example, the control device **155** may receive service information related to the first personal mobility vehicle from the first server **102** of the first service provider through the communication device **151**, and transmit the information to the electronic device **1000**. For example, when the control device **155** receives at least one piece of information, which is between information about selection of the first personal mobility vehicle **12** by the electronic device **1000** and information about communication between the electronic device **1000** and the first personal mobility vehicle **12**, from the electronic device **1000** through the communication device **151**, the control device **155** may receive service information about the first personal mobility vehicle **12** from the first server **102**.

[0088] For example, when the control device **155** receives information about completion of use of the first personal mobility vehicle **12** from the electronic device **1000** through the communication device **151**, the control device **155** may calculate a service usage fee according to the use of the first personal mobility vehicle **12**, and transmit information about the service usage fee to the electronic device **1000**.

[0089] The electronic device **1000** may include an input device **1002**, a display **1004**, a communicator **1006**, a memory **1008**, and/or a processor **1010**.

[0090] The input device **1002** may receive a command or data from an external (e.g., a user) of the electronic device **1000**. For example, the input device **1002** may include a keypad, a touch screen, and/or a microphone.

[0091] The display **1004** may visually provide information to the user of the electronic device **1000**. For example, the display **1004** may include a liquid crystal display (LCD), a light emitting diode (LED) display, and/or an organic light emitting diode (OLED) display. For example, the display **1004** may display a variety of content (e.g., text, images, videos, icons and/or symbols).

[0092] The display **1004** may include a touchscreen, and may receive a touch, a gesture, proximity, and/or hovering input using an electronic pen or a part of the user's body.

[0093] The communicator **1006** (also referred to as communication circuitry) may establish a wired and/or wireless communication channel between the electronic device **1000** and an external device, such as the personal mobility vehicles **10**, the management servers **100** and/or the server **150**, and support the communication between the electronic device **1000** and the external device through the established communication channel. For example, the communicator **1006** may include a wireless communication module (e.g., a cellular communication module, a Wi-Fi communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS))

communication module) and/or a wired communication module (e.g., a local area network (LAN) or a power line communication module), and thus the communicator **1006** may communicate with the external device. The communicator **1006** may include communication circuitry.

[0094] The memory **1008** may store various data used by at least one component (the input device **1002**, the display **1004**, the communicator **1006**, and/or the processor **1010**) of the electronic device **1000**, particularly, the memory **1008** may store input data and output data about software programs and instructions related to the software program. For example, the memory **1008** may include a volatile memory and/or a non-volatile memory.

[0095] The memory **1008** may store a program (or application program) of the sharing service of the personal mobility vehicles **10** related to sharing and/or managing of the personal mobility vehicles **10**.

[0096] The processor **1010** (also referred to as a control circuit or a control device) may control at least one other component of the electronic device **1000** (e.g., a hardware component (e.g., the input device **1002**, the display **1004**, the communicator **1006** and/or the memory **1008**) or software components (software programs)), and perform various data processing and calculation. The processor **1010** may include a memory.

[0097] The processor **1010** may allow a user to subscribe to any one service among the plurality of service providers based on a user input through the input device **1002**.

[0098] The processor **1010** may request authentication of the user of the electronic device **1000** based on the communication with the server **150** through the communicator **1006**.

[0099] For example, when an application of the sharing service is executed, and/or when a user logs in after executing the application of the sharing service, the processor **1010** may request authentication of the user of the electronic device **1000** to the server **150** through the communicator **1006**.

[0100] For example, when the electronic device **1000** communicates with any one personal mobility vehicle, such as the first personal mobility vehicle **12**, through the wired or wireless communication, the processor **1010** may request the authentication of the user of the electronic device **1000** to the server **150** through the communicator **1006**.

[0101] Based on current location information of the electronic device **1000** or location information selected through the input device **1002**, the processor **1010** may control the display **1004** to output information about the plurality of personal mobility vehicles **10** included in each of the plurality of service providers.

[0102] For example, although not shown, the electronic device **1000** may further include a GPS module, and the processor **1010** may identify current location information of the electronic device **1000** through the GPS module. Alternatively, the processor **1010** may identify location information about a selected location based on a user input through the input device **1002**.

[0103] For example, the processor **1010** may control the display **1004** to output only information about the plurality of personal mobility vehicles **10** included in each of the plurality of service providers located in a region corresponding to the current location information of the electronic device **1000** or the selected location information.

[0104] Based on the current location information of the electronic device **1000**, the processor **1010** may provide information about a personal mobility vehicle available to the user of the electronic device **1000**.

[0105] Based on the communication with any one personal mobility vehicle, such as the first personal mobility vehicle **12**, among the plurality of personal mobility vehicles through the communicator **1006**, the processor **1010** may transmit first information about the first personal mobility vehicle **12** to the server **150**.

[0106] For example, the first information about the first personal mobility vehicle **12** may include identification information of the first personal mobility vehicle **12** and/or information of the first service provider of the first personal mobility vehicle **12**.

[0107] When the electronic device **1000** communicates with the personal mobility vehicle **10**, the processor **1010** may control the display **1004** to output a predetermined user interface (UI) for controlling the electronic device **1000**.

[0108] In response to the transmission of the first information about the first personal mobility vehicle **12**, the processor **1010** may receive information about the first personal mobility vehicle **12** from the server **150** through the communicator **1006**.

[0109] For example, service information about the first personal mobility vehicle **12** may include information about a description of a function, a usage fee, an available time and/or an available distance of the first personal mobility vehicle **12**.

[0110] When the use of the first personal mobility vehicle **12** is terminated, the processor **1010** may perform the authentication of the user of the electronic device **1000**, locking of the first personal mobility vehicle **12** and/or payment of the usage fee of the first personal mobility vehicle **12** based on the communication with the server **150** and/or the communication with the first personal mobility vehicle **12** through the communicator **1006**.

[0111] For example, in order to allow a user to check a usage fee of the first personal mobility vehicle **12**, the processor **1010** may output information of the first personal mobility vehicle **12** used by the user, information about the first service provider of the first personal mobility vehicle **12**, and usage fee details, on the display **1004**.

[0112] The electronic device **1000** may include a smartphone, a tablet personal computer, a mobile phone, and/or a wearable device.

[0113] FIG. **3** is a view illustrating an operation of the system **1** according to an embodiment of the disclosure.

[0114] Referring to FIG. **3**, the server **150** may be implemented with a standardized platform architecture, and may be configured to control different kinds of devices and different kinds of services by integrating hardware control protocols and communication protocols.

[0115] The server **150** may be configured to standardize protocols different for each device and/or sharing service in a sharing service platform of the personal mobility vehicles **10**, and configured to allow the sharing service platform of the personal mobility vehicles **10** to be applicable to the device and/or the service to which the different protocols are applied.

[0116] For example, when the server **150** communicates with a first personal mobility vehicle **31** of a company A, a second personal mobility vehicle **33** of the company A, and a third personal mobility vehicle **35** of a company B, the server **150** may convert a control protocol of the first personal mobility vehicle **31** of the company A, a control protocol of the second personal mobility vehicle **33** of the company A, and a control protocol of the third personal mobility vehicle **35** of the company B into a standard hardware control protocol so as to standardize each of the protocols.

[0117] For example, when the server **150** communicates with a first electronic device **3001** of a user using a service of a company X, a second electronic device **3003** of a user using a service of a company Y, and a third electronic device **3005** of a user using a service of a company Z, the server **150** may convert a service communication protocol of a server of the company X, a service communication protocol of a server of the company Y, and a service communication protocol of a server of the company Z into a standard communication protocol so as to standardize each of the protocols.

[0118] The standardization of protocol is a known technique, and detailed description of standardization of each protocol is omitted.

[0119] The server **150** configured to standardize a control protocol and a communication protocol may provide a compatibility function, and particularly, when a service provider, which provides a personal mobility service subscribed to by a user, is different from a service provider that manages a personal mobility vehicle that the user wants to use, the compatibility function is capable of allowing the user to use the personal mobility vehicle that the user wants to use, through a user's electronic device **1000**.

[0120] The electronic device **1000**, which communicates with one of the personal mobility vehicles **10**, such as the first personal mobility vehicle **12**, may assist communication between an external device and the first personal mobility vehicle **12** through the communication.

[0121] For example, in comparison with the first personal mobility vehicle **12**, the electronic device **1000** may more efficiently perform an operation, such as subscription to the service provider, user authentication, and payment for the first personal mobility vehicle **12**.

[0122] For example, the electronic device **1000** may receive a message from the first service provider of the first personal mobility vehicle **12** through subscription to the service provided by the first service provider of the first personal mobility vehicle **12**. In this case, the service provider of the first personal mobility vehicle **12** may secure a service royalty.

[0123] FIG. **4** is a flow chart illustrating an operation of the server **150** (and/or the control device **155** of the server **150**) according to an embodiment of the disclosure.

[0124] The server **150** may receive a first authentication request of a user of the electronic device **1000** from the electronic device **1000** through the communication device **151** (**402**).

[0125] Through the communication device **151**, the server **150** may receive an authentication request of the first personal mobility vehicle **12** from the first personal mobility vehicle **12** included in the first service provider among the plurality of service providers (**404**).

[0126] The server **150** may authenticate the first authentication request of the user of the electronic device **1000** and authenticate the authentication request of the first personal mobility vehicle **12** (**406**).

[0127] The server **150** may authenticate the first authentication request of the user of the electronic device **1000** based on user information that is about a user who is subscribed to the services of each of the plurality of service providers and is stored in the memory **153**.

[0128] For example, subscription to the services of each of the plurality of service providers may indicate that user information is stored in the server of each of the plurality of service providers.

[0129] The server **150** may authenticate the authentication request of the first personal mobility vehicle **12** based on information that is about the plurality of personal mobility vehicles **10** included in each of the plurality of service providers and is stored in the memory **153**.

[0130] For example, through the communication device **151**, the server **150** may receive at least one piece of information, which is between information about the selection of the first personal mobility vehicle **12** by the electronic device **1000** and information about the communication between the electronic device **1000** and the first personal mobility vehicle **12**, from the electronic device **1000**. Based on the reception of the least one piece of information, the server **150** may authenticate the first authentication request of the user of the electronic device **1000** and authenticate the authentication request of the first personal mobility vehicle **12**.

[0131] Based on the authentication for the first authentication request, and the authentication for the authentication request of the first personal mobility vehicle **12**, the server **150** may transmit first information including unlock information of the first personal mobility vehicle **12** to the first personal mobility vehicle **12** through the communication device **151** (**408**).

[0132] When the server **150** completes the authentication (also referred to as authentication approval) based on the performance of the authentication of the first authentication request, the server **150** may transmit authentication completion information about the first authentication request to the electronic device **1000** through the communication device **151**.

[0133] When the server **150** completes the authentication (also referred to as authentication approval) based on the performance of the authentication of the first personal mobility vehicle **12**, the server **150** may transmit authentication completion information about the authentication request of the first personal mobility vehicle **12** to the first personal mobility vehicle **12** through the communication device **151**.

[0134] Based on the transmission of the authentication completion information about the first authentication request and the transmission of the authentication completion information about the

authentication request of the first personal mobility vehicle **12**, the server **150** may transmit the first information including the unlock information of the first personal mobility vehicle **12** to the first personal mobility vehicle **12** through the communication device **151**. For example, the first information may further include the authentication completion information about the first authentication request.

[0135] In addition to the above-described embodiment, the server **150** may receive service use request information of the server **150** from the electronic device **1000** through the communication device **151**.

[0136] For example, the service use request information of the server **150** may be information transmitted by the electronic device **1000** when the electronic device **1000** executes the application of the sharing service and/or when a user logs in after the execution of the application of the sharing service.

[0137] In response to the reception of the service use request information of the server **150**, the server **150** may authenticate a second authentication request of the user of the electronic device **1000** based on the user information that is about the user who is subscribed to the services of each of the plurality of service providers and is stored in the memory **153**.

[0138] Based on the completion of the authentication for the second authentication request, the server **150** may transmit authentication completion information about the second authentication request of the user to the electronic device **1000** through the communication device **151**.

[0139] In addition to the above-described embodiment, the server **150** may receive second information including use time information and use distance information of the first personal mobility vehicle **12** from the electronic device **1000**.

[0140] In response to the reception of the second information, the server **150** may calculate a service usage fee of the first personal mobility vehicle **12** of the user of the electronic device **1000** based on a predetermined fee calculation condition of the plurality of service providers corresponding to the personal mobility vehicle use time and use distance.

[0141] For example, when the information of the first personal mobility vehicle is stored in the first server **102** of the first service provider and the user information of the electronic device **1000** is stored in the second server of the second service provider, the service usage fee may include a first fee of the first service provider and a second fee of the second service provider.

[0142] For example, that the information of the user of the electronic device **1000** is stored (or registered) in the second server **104** of the second service provider may mean that the user of the electronic device **1000** is subscribed to the service of the second service provider.

[0143] For example, the first fee may be determined based on a first service of the first service provider and the use of the first personal mobility vehicle **12**. The second fee may be determined based on a second service of the second service provider and the use of the platform of the second service provider.

[0144] The server **150** may transmit information about the service usage fee of the first personal mobility vehicle **12** to the electronic device **1000** through the communication device **151**.

[0145] Further, in addition to the above-described embodiment, the server **150** may receive service information related to the first personal mobility vehicle **12** from the first server **102** of the first service provider through the communication device **151**.

[0146] For example, the server **150** may convert the communication protocol of the first server **102** into a predetermined standard protocol of the server **150** and based on this, the server **150** may receive service information about the first personal mobility vehicle **12** from the first server **102**.

[0147] For example, the service information about the first personal mobility vehicle **12** may include a description of a function, a usage fee, an available time and/or an available distance of the first personal mobility vehicle **12**.

[0148] The server **150** may transmit the service information related to the first personal mobility vehicle **12** to the electronic device **1000** through the communication device **151**.

[0149] In addition to the above-described embodiment, the server **150** may receive a personal mobility vehicle search request from the electronic device **1000**.

[0150] In response to the reception of the personal mobility vehicle search request from the electronic device **1000**, the server **150** may search for a personal mobility vehicle and transmit information about the searched personal mobility vehicle to the electronic device **1000**.

[0151] Accordingly, the electronic device **1000** receiving the information about the personal mobility vehicle from the server **150** may select the first personal mobility vehicle **12** through a user input, and communicate with the first personal mobility vehicle **12**.

[0152] In addition to the above-described embodiment, the server **150** may identify protocols of the electronic device **1000** and the first server **102** when performing the above-described operations, and when the protocols are different, the server **150** may perform standardization of the protocols (translation and re-transmission between protocols, etc.)

[0153] FIG. 5 is a flow chart illustrating an operation of the electronic device **1000** (and/or the processor **1010** of the electronic device **1000**) according to an embodiment of the disclosure.

[0154] The electronic device **1000** may identify current location information of the electronic device **1000** or location information selected through the input device **1002** (**502**).

[0155] Based on the current location information of the electronic device **1000** or the location information selected through the input device **1002**, the electronic device **1000** may control the display **1004** to output information about the plurality of personal mobility vehicles **10** included in each of the plurality of service providers (**504**).

[0156] The plurality of personal mobility vehicles may include personal mobility vehicles available in a region corresponding to the current location information of the electronic device **1000** or the location information selected through the input device **1002**.

[0157] The electronic device **1000** may identify communication with the first personal mobility vehicle **12** among the plurality of personal mobility vehicles **10** through the communicator **1006** (**506**).

[0158] The electronic device **1000** may transmit first information about the first personal mobility vehicle **12** to the server **150** based on the communication with the first personal mobility vehicle **12** (**508**).

[0159] In response to the transmission of the first information, the electronic device **1000** may receive service information of the first personal mobility vehicle **12** from the server **150** through the communicator **1006** (**510**).

[0160] For example, the service information related to the first personal mobility vehicle **12** may include information about a description of a function, a usage fee, an available time and/or an available distance of the first personal mobility vehicle **12**.

[0161] In addition to the above-described embodiment, the electronic device **1000** may provide notification, such as information about a service region in which personal mobility vehicles are available (and/or information about whether available personal mobility vehicles are present or not), to a user based on the location information of the electronic device **1000**.

[0162] Further, in addition to the above-described embodiment, the electronic device **1000** may identify termination of the use of the first personal mobility vehicle **12** based on a user input through the input device **1002** or the release of the communication with the first personal mobility vehicle **12**.

[0163] When the electronic device **1000** identifies termination of the use of the first personal mobility vehicle **12**, the electronic device **1000** may receive information about the service usage fee of the first personal mobility vehicle **12** from the server **150** through the communicator **1006**.

[0164] For example, the service usage fee of the first personal mobility vehicle **12** may include the first fee based on the first service of the first service provider providing the service of the first personal mobility vehicle **12** and the use of the first personal mobility vehicle **12**, and the second fee based on the second service of the second service provider subscribed to by the user of the

electronic device **1000**, and the use of the platform of the second service provider.

[0165] Based on the reception of information about the service usage fee, the electronic device **1000** may provide a payment function that allows the user to pay the usage fee. When the electronic device **1000** provides the payment function, the electronic device **1000** may provide information about the first personal mobility vehicle **12** corresponding to a payment target and information about companies of the payment target, such as the first and second service providers. [0166] When the electronic device **1000** identifies the termination of the use of the first personal mobility vehicle **12**, the electronic device **1000** may transmit the use time information and the use distance information of the first personal mobility vehicle **12** to the server **150** through the communicator **1006**.

[0167] When the electronic device **1000** identifies the termination of the use of the first personal mobility vehicle **12**, the electronic device **1000** may transmit use termination information including lock information to lock the first personal mobility vehicle **12** to the first personal mobility vehicle **12** through the communicator **106**.

[0168] FIGS. **6A** and **6B** are flow charts illustrating an operation of the system **1** according to an embodiment of the disclosure.

[0169] The electronic device **1000** (and/or the processor **1010** of the electronic device **1000**) may execute the application that provides the sharing service of the personal mobility vehicles **10** (**601**).

[0170] In response to the execution of the application that provides the sharing service of the personal mobility vehicles **10**, the electronic device **1000** may identify pre-stored user login information or receive login information through the user input, and based on this, the electronic device **1000** may perform a user login operation.

[0171] In response to the execution of the application, the electronic device **1000** may transmit the first authentication request of the user of the electronic device **1000** to the server **150** through the communicator **1006** (**603**).

[0172] Based on the reception of the first authentication request, the server **150** (and/or the control device **155** of the server **150**) may perform first authentication of the user of the electronic device **1000** (**605**).

[0173] The server **150** may complete, that is approve, the first authentication of the user of the electronic device **1000** based on the reception of the first authentication request.

[0174] The server **150** may transmit approval information about the first authentication request through the communication device **151** in response to the performance of the first authentication (**607**).

[0175] The electronic device **1000** may output information about the personal mobility vehicles **10** available to the user based on the reception of approval information about the first authentication request through the communicator **1006** (**609**).

[0176] As shown in FIG. **7**, the electronic device **1000** may control the display **1004** to output a screen of information about the personal mobility vehicles **10** available to the user.

[0177] FIG. **7** is a view illustrating a screen of the display **1004** of the electronic device **1000** according to an embodiment of the disclosure.

[0178] Referring to FIG. **7**, when service providers of personal mobility vehicles available to a user are a first service provider **702** and a second service provider **704**, the electronic device **1000** may provide visual effects to distinguish the two companies from each other. Further, the electronic device **1000** may visually display the available personal mobility vehicles included in the first service provider **702**, and visually display the available personal mobility vehicles included in the second service provider **704**.

[0179] The electronic device **1000** may identify the selection of the first personal mobility vehicle **12** of the first service provider in response to the output information of the personal mobility vehicles available to the user (**611**).

[0180] The electronic device **1000** may identify the selection of the first personal mobility vehicle

12 based on a user input through the input device **1002**.

[0181] The electronic device **1000** may transmit information that the first personal mobility vehicle **12** is selected to the server **150** through the communicator **1006** (**613**).

[0182] The electronic device **1000** may communicate with the first personal mobility vehicle **12** (**615**).

[0183] Based on the electronic device **1000** being mounted to the first personal mobility vehicle **12** or based on the user input through the input device **1002**, the electronic device **1000** may communicate with the first personal mobility vehicle **12** through the wired or wireless communication.

[0184] Based on the selection of the first personal mobility vehicle **12** and/or the communication with the first personal mobility vehicle **12**, the electronic device **1000** may transmit a second authentication request of the user of the electronic device **1000** to the server **150** through the communicator **1006** (**617**).

[0185] The server **150** may perform second authentication of the user of the electronic device **1000** based on the reception of the second authentication request (**619**).

[0186] Based on the performance of the second authentication, the server **150** may transmit approval information about the second authentication request to the electronic device **1000** through the communication device **151** (**621**).

[0187] The first personal mobility vehicle **12** may transmit an authentication request of the first personal mobility vehicle **12** to the server **150** through the communication module based on the communication with the electronic device **1000** (**623**).

[0188] The server **150** may authenticate the first personal mobility vehicle **12** based on the authentication request of the first personal mobility vehicle **12** (**625**).

[0189] Based on the performance of the authentication of the first personal mobility vehicle **12**, the server **150** may transmit approval information about the authentication request of the first personal mobility vehicle **12** to the first personal mobility vehicle **12** through the communication device **151** (**627**).

[0190] Based on the reception of the approval information, the first personal mobility vehicle **12** may unlock the first personal mobility vehicle **12** (**629**).

[0191] Based on the unlocking of the first personal mobility vehicle **12**, the first personal mobility vehicle **12** may transmit unlock completion information to the electronic device **1000** through the communication module (**631**).

[0192] Based on the reception of the unlock completion information, the electronic device **1000** may identify start of using the first personal mobility vehicle **12** (**633**).

[0193] In addition to the above-described embodiment, when communicating with the first personal mobility vehicle **12**, the electronic device **1000** may transmit the information related to the communication with the first personal mobility vehicle **12** to the server **150**.

[0194] In addition to the above-described embodiment, the user of the electronic device **1000** may be subscribed to (referred to as registration authentication) a service of one of the service providers, which is registered in the sharing service of the personal mobility vehicles **10** of the server **150**, such as a service of the first service provider (referred to as a local service) or a service of the second service provider.

[0195] Accordingly, the user of the electronic device **1000** may use the sharing service of the personal mobility vehicles **10** of the server **150**, based on the information of the user subscribed to the service of one of the service providers, which is registered in the sharing service of the personal mobility vehicles **10** of the server **150**.

[0196] For example, the electronic device **1000** may use a sharing service of the personal mobility vehicles **10** of the server **150** through the login to a service of any one service provider.

[0197] In addition to the above-described embodiment, when the server **150** receives information that the electronic device **1000** selects the first personal mobility vehicle **12**, the server **150** may

identify that a reservation process of the first personal mobility vehicle **12** is in progress.

[0198] The server **150**, which identifies that the reservation process of the first personal mobility vehicle **12** is in progress, may identify whether or not the electronic device **1000** communicates with the first personal mobility vehicle **12** within a predetermined reservation effective time (e.g., 5 minutes).

[0199] When the electronic device **1000** does not communicate with the first personal mobility vehicle **12** within the predetermined reservation effective time (e.g., 5 minutes), the server **150** may identify that the reservation process of the first personal mobility vehicle **12** is canceled. For example, when the server **150** does not receive information that the electronic device **1000** communicates with the first personal mobility vehicle **12**, from the electronic device **1000**, the server **150** may identify that the reservation process of the first personal mobility vehicle **12** is canceled.

[0200] During the predetermined reservation effective time, the server **150** may prevent the first personal mobility vehicle **12** from being exposed to another user through the communication device **151** or the server **150** may provide information that the reservation process is in progress to another user. Therefore, during the predetermined reservation effective time, another user cannot select the first personal mobility vehicle **12**.

[0201] When the electronic device **1000** does not communicate with the first personal mobility vehicle **12** within the predetermined reservation effective time, the server **150** may expose the first personal mobility vehicle **12** to another user or the server **150** may stop providing information that the reservation process is in progress in order that another user can select the first personal mobility vehicle **12**.

[0202] In addition to the above-described embodiment, when the user of the electronic device **1000** terminates the use of the first personal mobility vehicle **12**, the electronic device **1000** may communicate with the server **150** to allow the server **150** to perform the user authentication, to transmit the information about locking the first personal mobility vehicle **12** to the first personal mobility vehicle **12**, and to transmit information related to a service usage fee of the first personal mobility vehicle **12** to the electronic device **1000**. Therefore, it is possible to allow the user to pay the service usage fee through the electronic device **1000**.

[0203] In addition to the above-described embodiment, the server **150** may identify a protocol (e.g., a control protocol and a communication protocol) of the electronic device **1000** and a protocol (e.g., a control protocol and a communication protocol) of the first server **102** of the first service provider. When the protocol of the electronic device **1000** is different from the protocol of the first server **102**, the server **150** may perform standardization of protocols (translation and retransmission between protocols, etc.). The server **150** may perform communication between the electronic device **1000** and the first server **102** based on standardization of protocols.

[0204] Further, according to the above-described embodiment, it is possible to enhance the service stability by performing double user authentication, the first authentication of the user, and the second authentication of the user. For example, when the electronic device **1000** executes an application and when the electronic device **1000** communicates with the first personal mobility vehicle **12**, the electronic device **1000** may perform the user authentication through the communication with the first server **102**, and thus it is possible to secure the stability of the sharing service of the personal mobility vehicles **10**.

[0205] According to the above-described embodiment, a user may control the personal mobility vehicles **12**, **14**, and **200**, which have a simple structure, through a personal device, such as the electronic device **1000**, and the electronic device **1000** may use personal mobility vehicles of different service providers by sharing the function of the personal mobility vehicle.

[0206] Through the electronic device **1000**, a user may subscribe to a service of any one service provider that provides a personal mobility sharing service in a frequently used region.

[0207] Based on subscription information about the service of any one service provider, the user

may use not only the subscribed service of the service provider but also an unsubscribed service of a service provider through the electronic device **1000**.

[0208] For example, the electronic device **1000** may identify a personal mobility vehicle available in a desired location based on the location of the electronic device **1000** or location information selected by the user.

[0209] For example, through the communication with the personal mobility vehicle and the communication with the server **150** in which the services of the service providers are registered, the electronic device **1000** may allow the user to use a personal mobility vehicle of a service provider to which the user is not subscribed. In this case, the server **150** may provide a standard protocol in the control and communication, and standardize different protocols between the electronic device **1000**, and/or the management server **100**, thereby communicating with other devices.

[0210] The user may allow the electronic device **1000** to communicate with a personal mobility vehicle, which is desired to be used, through the wired or wireless communication, and based on the communication, the user may occupy and use the personal mobility vehicle.

[0211] When the user returns the personal mobility vehicle after the use of the personal mobility vehicle is completed, the user may allow the electronic device **1000** to perform user authentication and payment through the communication with the server **150**. When the service provider subscribed to by the user is different from a service provider including a personal mobility vehicle actually used by the user, the server **150** may calculate a service usage fee based on the service of two service providers and transmit the service usage fee to the electronic device **1000**, thereby allowing the user to pay the service usage fee.

[0212] As is apparent from the above description, it is possible to design a personal mobility vehicle having a simple structure so as to share functions of the personal mobility vehicle with a user's personal electronic device.

[0213] Further, it is possible to allow a user who is subscribed to a personal mobility sharing service of one service provider to use a personal mobility sharing service of various service providers.

[0214] For example, a user who is subscribed to a personal mobility sharing service of a service provider that provides a personal mobility service in a first region can easily use a personal mobility sharing service of a service provider that provides a personal mobility service in a second region.

[0215] Meanwhile, the disclosed embodiments may be embodied in the form of a recording medium storing instructions executable by a computer. The instructions may be stored in the form of program code and, when executed by a processor, may generate a program module to perform the operations of the disclosed embodiments. The recording medium may be embodied as a computer-readable recording medium.

[0216] The computer-readable recording medium includes all kinds of recording media in which instructions which can be decoded by a computer are stored. For example, there may be a read only memory (ROM), a random access memory (RAM), a magnetic tape, a magnetic disk, a flash memory, and an optical data storage device.

[0217] Although a few embodiments of the disclosure have been shown and described, it would be appreciated by those skilled in the art that changes may be made in these embodiments without departing from the principles and spirit of the disclosure, the scope of which is defined in the claims and their equivalents.

Claims

1. An electronic device comprising: an input device; a display; a communicator; and a processor electrically connected to the input device, the display, and the communicator, wherein the processor is configured to: control the display to output information about a plurality of personal mobility

vehicles included in each of a plurality of service providers based on current location information of the electronic device or location information selected through the input device; transmit, based on communication with a first personal mobility vehicle among the plurality of personal mobility vehicles through the communicator, first information about the first personal mobility vehicle to a server; and receive service information about the first personal mobility vehicle from the server through the communicator in response to the transmission of the first information.

2. The electronic device of claim 1, wherein the plurality of personal mobility vehicles comprises personal mobility vehicles available in a region corresponding to the current location information of the electronic device or the location information selected through the input device.

3. The electronic device of claim 1, wherein the processor is configured to identify termination of use of the first personal mobility vehicle based on a user input through the input device or a release of the communication with the first personal mobility vehicle.

4. The electronic device of claim 3, wherein the processor is configured to receive information about a service usage fee of the first personal mobility vehicle from the server through the communicator in response to the processor identifying the termination of the use of the first personal mobility vehicle.

5. The electronic device of claim 4, wherein the processor is configured to transmit use time information and use distance information of the first personal mobility vehicle to the server through the communicator in response to the processor identifying the termination of the use of the first personal mobility vehicle.

6. The electronic device of claim 4, wherein the service usage fee of the first personal mobility vehicle comprises: a first fee based on a first service of a first service provider configured to provide the first personal mobility vehicle and the use of the first personal mobility vehicle; and a second fee based on a second service of a second service provider subscribed to by a user of the electronic device and a use of a platform of the second service provider.

7. The electronic device of claim 1, wherein: the selected location information comprises information about a region selected through the input device; and the plurality of personal mobility vehicles included in each of the plurality of service providers is located in the region.

8. The electronic device of claim 1, wherein the processor is configured to control the display to output information about whether the plurality of service providers and the plurality of personal mobility vehicles included in the plurality of service providers that are available to a user of the electronic device are present or not.

9. The electronic device of claim 1, wherein the service information comprises information about a description of a function, a usage fee, an available time and/or an available distance of the first personal mobility vehicle.

10. The electronic device of claim 1, wherein the processor is configured to send a first authentication request through the communicator.

11. The electronic device of claim 10, wherein the processor is configured to receive information about a service usage fee.

12. The electronic device of claim 11, wherein the information about the service usage fee is based on use time information and use distance information of the first personal mobility vehicle.

13. An electronic device comprising: a display; a communicator; a processor; a non-transitory memory storing a program that, when executed by the processor, causes the processor: control the display to output information about a plurality of personal mobility vehicles included in each of a plurality of service providers based on location information; cause the communicator to transmit first information about a first personal mobility vehicle to a server, the first information being based on communication with the first personal mobility vehicle among the plurality of personal mobility vehicles; and receive service information about the first personal mobility vehicle from the server in response to the transmission of the first information.

14. The electronic device of claim 13, wherein the location information comprises current location

information of the electronic device.

15. The electronic device of claim 13, further comprising an input device, wherein the location information comprises location information selected through the input device.

16. The electronic device of claim 13, wherein the plurality of personal mobility vehicles comprises personal mobility vehicles available in a region corresponding to the location information.

17. The electronic device of claim 13, wherein the processor is configured to identify termination of use of the first personal mobility vehicle based on a user input or a release of the communication with the first personal mobility vehicle.

18. The electronic device of claim 17, wherein the processor is configured to receive information about a service usage fee of the first personal mobility vehicle from the server through the communicator in response to the processor identifying the termination of the use of the first personal mobility vehicle.

19. The electronic device of claim 18, wherein the processor is configured to transmit use time information and use distance information of the first personal mobility vehicle to the server through the communicator in response to the processor identifying the termination of the use of the first personal mobility vehicle.

20. A method of operating an electronic device that comprises an input device, a display, and a communicator, the method comprising: controlling the display to output information about a plurality of personal mobility vehicles included in each of a plurality of service providers based on current location information of the electronic device or location information selected through the input device; transmitting, based on communication with a first personal mobility vehicle among the plurality of personal mobility vehicles through the communicator, first information about the first personal mobility vehicle to a server; and receiving service information about the first personal mobility vehicle from the server through the communicator in response to the transmission of the first information.
