

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250276640

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Anderson; Kasen Keith et al.

---

### REARVIEW MIRROR ASSEMBLY

---

#### Abstract

A rearview mirror assembly that includes a housing and a printed circuit board (PCB) located in the housing. The rearview mirror assembly further includes a monitoring system that includes an image capturing module, an illumination source connected to the PCB, and an optical element aligned with the illumination source. The optical element is configured to redirect an illumination from the illumination source toward an occupant position in an automobile.

---

**Inventors:** Anderson; Kasen Keith (Jenison, MI), Veenman; Steven J. (Hudsonville, MI), Pothoof; Brett C. (Holland, MI), Fish, JR.; Richard T. (Hudsonville, MI), Lintz; Joshua D. (Allendale, MI)

**Applicant:** GENTEX CORPORATION (ZEELAND, MI)

**Family ID:** 90471392

**Assignee:** GENTEX CORPORATION (ZEELAND, MI)

**Appl. No.:** 19/211780

**Filed:** May 19, 2025

#### Related U.S. Application Data

parent US continuation 18375607 20231002 parent-grant-document US 12330560 child US 19211780

us-provisional-application US 63378118 20221003

---

#### Publication Classification

**Int. Cl.:** B60R1/12 (20060101); B60R1/04 (20060101); F21V5/00 (20180101); F21V23/04 (20060101)

**U.S. Cl.:**

CPC **B60R1/1207** (20130101); **B60R1/04** (20130101); **F21V5/00** (20130101); **F21V23/0478** (20130101); B60R2001/1223 (20130101)

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application a continuation application of U.S. patent application Ser. No. 18/375,607, filed Oct. 2, 2023, entitled “REARVIEW MIRROR ASSEMBLY,” and claims priority to and the benefit under 35 U.S.C. § 119(e) of U.S. Provisional Application No. 63/378,118, filed on Oct. 3, 2022, entitled “REARVIEW MIRROR ASSEMBLY,” the disclosure of which is hereby incorporated herein by reference in its entirety.

### **FIELD OF THE DISCLOSURE**

[0002] The present disclosure generally relates to a rearview mirror assembly and, more particularly, to a rearview mirror assembly with a driver monitoring system that includes an optical element for redirecting and spreading an illumination.

### **SUMMARY OF THE DISCLOSURE**

[0003] According to one aspect of the present disclosure, a rearview mirror assembly includes a housing and a printed circuit board (PCB) located in the housing. The rearview mirror assembly further includes a monitoring system that includes an image capturing module, an illumination source connected to the PCB, and an optical element aligned with the illumination source. The optical element is configured to redirect and spread an illumination from the illumination source toward an occupant position in an automobile.

[0004] According to another aspect of the present disclosure, a rearview mirror assembly includes a housing and a printed circuit board (PCB) located in the housing. The rearview mirror assembly further includes a monitoring system that includes an image capturing module, an illumination source connected to the PCB, and an optical element aligned with the illumination source that includes a plurality of wedges each extending to an apex. The plurality of wedges is configured to redirect and spread an illumination from the illumination source toward an occupant position in an automobile.

[0005] According to another aspect of the present disclosure, a rearview mirror assembly includes a housing, a transmission element at least partially located in the housing, and a printed circuit board (PCB) located in the housing. The rearview mirror assembly further includes a monitoring system that includes an image capturing module, an illumination source connected to the PCB, and an optical element aligned with the illumination source that includes a plurality of wedges each extending to an apex. The plurality of wedges is configured to redirect and spread an illumination from the illumination source toward an occupant position in an automobile.

[0006] These and other features, advantages, and objects of the present disclosure will be further understood and appreciated by those skilled in the art by reference to the following specification, claims, and appended drawings.

---

## **Description**

### **BRIEF DESCRIPTION OF THE DRAWINGS**

[0007] In the drawings:

[0008] FIG. 1 is a top perspective view of an automobile that incorporates a rearview mirror assembly, in accordance with one aspect of the present disclosure;

[0009] FIG. 2 is a front view of a rearview mirror assembly, in accordance with one aspect of the present disclosure;

[0010] FIG. 3A is a cross-sectional side view of a rearview mirror assembly with an illumination source and an optical element in a first arrangement, in accordance with one aspect of the present disclosure;

[0011] FIG. 3B is a cross-sectional side view of a rearview mirror assembly with an illumination source and an optical element in a second arrangement, in accordance with one aspect of the present disclosure;

[0012] FIG. 3C is a cross-sectional side view of a rearview mirror assembly with an illumination source and an optical element in a third arrangement, in accordance with one aspect of the present disclosure;

[0013] FIG. 3D is a cross-sectional side view of a rearview mirror assembly with an illumination source and an optical element in a fourth arrangement, in accordance with one aspect of the present disclosure;

[0014] FIG. 3E is a cross-sectional side view of a rearview mirror assembly with an illumination source and an optical element in a fifth arrangement, in accordance with one aspect of the present disclosure;

[0015] FIG. 4A is a side perspective view of an illumination source and an optical element with a first construction that redirects and spreads illumination from the illumination source, in accordance with one aspect of the present disclosure;

[0016] FIG. 4B is a rear view of an illumination source and an optical element with a first construction that redirects and spreads illumination from the illumination source, in accordance with one aspect of the present disclosure;

[0017] FIG. 5A is a side view of an illumination source and an optical element with a second construction that redirects and spreads illumination from the illumination source, in accordance with one aspect of the present disclosure;

[0018] FIG. 5B is a rear view of an illumination source and an optical element with a second construction that redirects and spreads illumination from the illumination source, in accordance with one aspect of the present disclosure;

[0019] FIG. 6A is a side perspective view of an illumination source and an optical element with a third construction that redirects illumination and spreads from the illumination source, in accordance with one aspect of the present disclosure;

[0020] FIG. 6B is a rear view of an illumination source and an optical element with a third construction that redirects illumination and spreads from the illumination source, in accordance with one aspect of the present disclosure;

[0021] FIG. 7A is a rear view of an illumination source and an optical element with a fourth construction that redirects and spreads illumination from the illumination source, in accordance with one aspect of the present disclosure;

[0022] FIG. 7B is a front view of an illumination source and an optical element with a fourth construction that redirects and spreads illumination from the illumination source, in accordance with one aspect of the present disclosure;

[0023] FIG. 8A is side perspective view of an illumination source and an optical element with a fifth construction that redirects illumination and spreads from the illumination source, in accordance with one aspect of the present disclosure;

[0024] FIG. 8B is a rear view of an illumination source and an optical element with a fifth construction that redirects illumination and spreads from the illumination source, in accordance with one aspect of the present disclosure; and

[0025] FIG. 9 is a side perspective view of an illumination source and an optical element with a sixth construction that redirects illumination and spreads from the illumination source, in accordance with one aspect of the present disclosure.

## DETAILED DESCRIPTION

[0026] The present illustrated embodiments reside primarily in combinations of method steps and apparatus components related to a rearview mirror assembly with a driver monitoring system that includes an optical element for redirecting and spreading an illumination. Accordingly, the apparatus components and method steps have been represented, where appropriate, by conventional symbols in the drawings, showing only those specific details that are pertinent to understanding the embodiments of the present disclosure so as not to obscure the disclosure with details that will be readily apparent to those of ordinary skill in the art having the benefit of the description herein. Further, like numerals in the description and drawings represent like elements.

[0027] For purposes of description herein, the terms “upper,” “lower,” “right,” “left,” “rear,” “front,” “vertical,” “horizontal,” and derivatives thereof, shall relate to the disclosure as oriented behind the rearview mirror assembly. Unless stated otherwise, the term “front” shall refer to the surface of the device closer to an intended viewer of the device, and the term “rear” shall refer to the surface of the device further from the intended viewer of the device. However, it is to be understood that the disclosure may assume various alternative orientations, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification are simply exemplary embodiments of the inventive concepts defined in the appended claims. Hence, specific dimensions and other physical characteristics relating to the embodiments disclosed herein are not to be considered as limiting, unless the claims expressly state otherwise.

[0028] The terms “including,” “comprises,” “comprising,” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by “comprises a . . .” does not, without more constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises the element.

[0029] Referring to FIGS. 1-6B, reference numeral **10** generally designates a rearview mirror assembly. The rearview mirror assembly **10** includes a housing **12** and a printed circuit board **14** (PCB) located in the housing. The rearview mirror assembly **10** further includes a monitoring system **16** that includes an image capturing module **18** (e.g., a camera), an illumination source **20** connected to the PCB **14**, and an optical element **22** coupled to the PCB **14** and aligned with the illumination source **20**. The optical element **22** is configured to redirect and spread an illumination from the illumination source **20** toward an occupant position **24** (e.g., a driver position) in an automobile **26**.

[0030] With reference to FIG. 1, various embodiments of rearview mirror assembly **10** may be incorporated with one or more structures. For example, a traditional rearview mirror location in the automobile **26** may employ the rearview mirror assembly **10**. In other embodiments, components of the rearview mirror assembly **10** may be incorporated in an emergency vehicle, a residential vehicle, an airplane, a rail vehicle, or the like. In some embodiments, the rearview mirror assembly **10** may not include a reflective element and instead operate as a dimmable display. Generally speaking, the rearview mirror assembly **10** may be incorporated into any environment wherein monitoring the occupant position **24** may be beneficial.

[0031] With reference to FIGS. 2 and 3A, the housing **12** of the rearview mirror assembly **10** includes a bezel **27** that defines an opening **28** and a transmission element **30** (FIG. 3A) is located in the opening **28**. The transmission element **30** includes a front surface **32** that faces the occupant position **24** and a rear surface **34** that generally faces away from the occupant position **24** (FIG. 3A). The transmission element **30** may be configured and/or otherwise coupled to an electro-optic device containing an electro-optic medium **33**. As such, the transmission element **30** can be switched between a reflective state, wherein the electro-optic medium **33** is in a transmissive state and the rearview mirror assembly **10** operates as a mirror and a darkened state wherein the electro-

optic medium **33** has a reduced optical transmission (e.g., to reduce glare). A reflective layer (not shown) may be located between the housing **12** and the transmission element **30** to reflect light in the reflective state. More particularly, the reflective layer may be located between a substrate that defines the rear surface **34** and the electro-optic medium **33**. A display device **35** may be located between the housing **12** and the electro-optic medium **33** for displaying information to a driver from the monitoring system **16**. A reflection rate of the transmission element **30** may be consistently lower in front of the display device **35**. The electro-optic device and electro-optic medium **33** as disclosed herein may be a single-layer, single-phase component, multi-layer component, or multi-phase component, as described in U.S. Pat. No. 5,928,572 entitled "Electrochromic Layer And Devices Comprising Same," U.S. Pat. No. 5,998,617 entitled "Electrochromic Compounds," U.S. Pat. No. 6,020,987 entitled "Electrochromic Medium Capable of Producing a Pre-selected Color," U.S. Pat. No. 6,037,471 entitled "Electrochromic Compounds," U.S. Pat. No. 6,141,137 entitled "Electrochromic Media for Producing a Pre-selected Color," U.S. Pat. No. 6,249,369 entitled "Coupled Electrochromic Compounds With Photostable Dication Oxidation States," U.S. Pat. No. 6,137,620 entitled "Electrochromic Media With Concentration Enhanced Stability, Process for the Preparation Thereof and Use in Electrochromic Devices," and U.S. Pat. No. 6,519,072 entitled "Electrochromic Device"; and International Patent Application Publication Nos. WO 98/42796 entitled "Electrochromic Polymeric Solid Films, Manufacturing Electrochromic Devices Using Such Solid Films, and Processes for Making Such Solid Films and Devices," and WO 99/02621 entitled "Electrochromic Polymer System," which are herein incorporated by reference in their entirety. The present disclosure may also be used with a display mirror system, such as that described in U.S. Pat. Nos. 9,505,349 and 10,739,591, which are hereby incorporated herein by reference in their entireties.

[0032] With continued reference to FIGS. **2** and **3A**, the PCB **14** may include a plurality of PCBs **14** or a single PCB **14**. For example, the features of the transmission element **30** and the monitoring system **16** may operate from the PCB **14** and the image capturing module **18** may operate from a separate PCB (e.g., second PCB **15**). The PCBs **14** and **15** may be located in the housing **12** and completely encased by a combination of the housing **12** and the transmission element **30**. The housing **12** may include a connection hub **36** and the connection hub **36** may be connected to a mounting member **38**. The mounting member **38** is configured to be connected to the automobile **26** (or other environment) and the housing **12** is moveable relative to the mounting member **38** to orient the transmission element **30** at various angles relative to an occupant position **24** (or other environmental position) to obtain different environmental views and/or orientations relative to a vehicle operator. The PCBs **14** and **15** may be connected with an interior **40** of the housing **12** and moves with the housing **12** as it is adjusted relative to the mounting member **38**. In some embodiments, a carrier element **43** may connect one or both of the PCBs **14**, **15** to the housing **12**. In some embodiments, the carrier element **43** may also connect the transmission element **30** to the housing **12**. The image capturing module **18**, the illumination source **20**, and the optical element **22** may, likewise, move with the housing **12** as it is adjusted relative to the mounting member **38**. In some embodiments, the illumination element **20** and PCB **14** are located on an opposite side (e.g., left or right) of the connection hub **36** than the image capturing module **18** and second PCB **15**. In some embodiments, the image capturing module **18** may be located outside of the housing **12**. In still other embodiments, and as illustrated in FIG. **2**, the illumination source **20** and optical element **22** may be aligned in a center of the transmission element **30** (e.g., aligned with the connection hub **36**). In this manner, the optical element **22** may be switched (e.g., rotated 180°) during manufacture to redirect light for left and right driver side monitoring. Further, the image capturing module **18** may be located towards a right or left side of the optical element **22**.

[0033] With reference now to FIG. **3A**, the illumination source **20** may be directly connected with the PCB **14** and the optical element **22** may be held in a spaced relationship from the illumination source **20** with a connection body **42**. For example, the connection body **42** may be configured as

pins (e.g., one or more), as clips, and/or one or more of the carrier elements **43** that connect the PCB **14** to the housing **12**. The connection body **42** may be directly connected to the optical element **22** and extend to and be directly connected with at least one of the PCBs **14**, the illumination source **20**, the carrier elements **43**, the housing **12**, or the transmission element **30** (FIG. 3B). The optical element **22** may include an outer perimeter and the connection body **42** may connect to the outer perimeter or internal thereto. For example, in some embodiments, the optical element **22** may include apertures adjacent to the outer perimeter for receiving the connection body **42**. In some embodiments, the connection body **42** may be connected to the optical element **22** by other means, for example, adhesive, clips, and/or the like. The connection body **42** may connect to the PCB **14** and/or the illumination source **20** with similar means as it connects to the optical element **22**.

[0034] With reference now to FIGS. 3C-3E, the optical element **22** may be connected directly to the transmission element **30**, for example, via a wetting out process and direct adhering with an adhesive (e.g., an optical adhesive). For example, as shown in FIG. 3C, the optical element **22** may be located on a side of the front surface **32** of the transmission element **30** (e.g., connected to the front surface **32**). In other embodiments, such as the arrangement shown in FIG. 3D, the optical element **22** may be located on a side of the rear surface **34** of the transmission element **30** (e.g., connected to the rear surface **34** and/or otherwise located between the rear surface **34** and the illumination source **20**). In other embodiments, such as the arrangement shown in FIG. 3E, the optical element **22** may extend through a portion of the housing **12**, such as a bottom edge of the bezel **27**. The illumination source **20** may include two or more illumination sources **20** and the optical element **22** may include two or more optical elements **22**. In some embodiments, the two or more the illumination sources **20** may be aligned with a single optical element **22**. In some embodiments, each of the two or more illumination sources **20** may be aligned with a different optical element **22**.

[0035] With reference now to FIGS. 1-3E, the illumination source **20** may be configured to project the light for a variety of operational principles. For example, the light source **20** may be configured to project a flood illumination (e.g., in the visible and/or infrared spectrum). In this manner, the optical element **22** may redirect and spread the food illumination to different locations around the automobile **26**. In some embodiments, the light may be projected in a structured light pattern (e.g., that is at least one of redirected and/or spread by the optical element **22**). The image capturing module **18** may capture images of the structure light pattern and a control system (e.g., located on the first and/or second PCB **14**, **15**) may be configured to extrapolate images of the structured light for two-dimensional ("2D") and/or three-dimensional ("3D") information about, for example, occupant position **24**. In this manner, the rearview mirror assembly **10** (e.g., the monitoring system **16**) may be utilized for driver monitoring capabilities. In addition, it should be appreciated that the illumination source **20** may be configured to project the light of other operational principles for driver monitoring within 2D or 3D space.

[0036] With reference now to FIGS. 4A-4B, the optical element **22** and the illumination source **20** are isolated from other components of the rearview mirror assembly **10**. The optical element **22** is illustrated in accordance with a first construction. The optical element **22** includes a first major surface **48** that faces the illumination source **20** and a second major surface **49** that faces away from the illumination source **20**. The first major surface **48** defines at least one refractive element **50**. The at least one refractive element **50** may include a plurality of wedges **52** arranged vertically that both redirect and uniformly spread illumination from the illumination source **20** in a horizontal direction as indicated by the arrows in FIG. 4A. More particularly, each of the wedges **52** may include a slanted face **54** that extends outwardly from the first major surface **48** in a horizontal direction to an apex **56**, and a cliff portion **58** may extend from the apex **56** to an adjacent wedge **52**. In some embodiments, the slanted face **54** of the wedges **52** are curved (e.g., concave or convex) for concentrating or spreading the illumination. The apex **56** may also be curved (e.g.,

defined by a radius) and the cliff portion **58** may be angled from the apex **56** towards or away from the slanted face **54**. Each wedge **52** extends across (e.g., linearly) the first major surface **48** from a top side **60** to a bottom side **62** of the optical element **22**. The optical element **22** may be tapered such that one side **60**, **62** is thicker (“T”) than the other side **60**, **62** to bend the light (i.e., illumination from the illumination source **20**) vertically to redirect light in a vertical direction as indicated by the arrows in FIG. **4B**. In some embodiments, the top side **60** is thinner than the bottom side **62**. In this manner, the direction of taper may further bend the light in a vertically downward direction. In some embodiments, the taper may be on the first major surface **48** and the second major surface **49** may be substantially planar. In some embodiments, one of the major surfaces **48**, **49** (e.g., the second major surface **49**) may be curved (e.g., concave or convex) for concentrating or spreading the illumination. In some embodiments, the taper may be on the second major surface **49** and the apex **56** of each wedge **52** may extend to a plane. In some embodiments, two or more wedges **52** may each include a slanted face **54** that slopes at different pitches or exhibits different curvatures for further redirection and spreading of the light.

[0037] With reference now to FIGS. **5A** and **5B**, an optical element **122** is illustrated in accordance with a second construction. Unless otherwise specified, the optical element **122** may be incorporated into at least the structure in FIG. **1** and other structures described herein. In addition, the optical element **122** may include similar features, elements, and materials as the other constructions set forth herein. More particularly, the optical element **122** includes a first major surface **148** that faces the illumination source **20** and a second major surface **149** that faces away from the illumination source **20**. The first major surface **148** defines at least one refractive element **150**. The at least one refractive element **150** may include a plurality of wedges **152** arranged horizontally to redirect and uniformly spread illumination from the illumination source **20** in a vertical direction as indicated by the arrows in FIG. **5A**. More particularly, each of the wedges **152** may include a slanted face **154** that extends outwardly from the first major surface **148** in a vertical direction to an apex **156**, and a cliff portion **158** may extend from the apex **156** to an adjacent wedge **152**. In some embodiments, the slanted face **154** of the wedges **152** are curved (e.g., concave or convex) for concentrating or spreading the illumination. The apex **156** may also be curved (e.g., defined by a radius) and the cliff portion **158** may be angled from the apex **156** towards or away from the slanted face **154**. Each wedge **152** extends across (e.g., linearly) the first major surface **148** from a right side **164** to a left side **166** of the optical element **122**. The optical element **122** may be tapered such that one side **164**, **166** is thicker (“T”) than the other side **164**, **166** to bend light horizontally. In some embodiments, the left side **166** is thinner than the right side **164**. In this manner, the direction of taper may further bend the light in a horizontally rightward direction. In some embodiments, the taper may be on the first major surface **148** and the second major surface **149** may be substantially planar. In some embodiments, one of the major surfaces **148**, **149** (e.g., the second major surface **149**) may be curved (e.g., concave or convex) for concentrating or spreading the illumination. In some embodiments, the taper may be on the second major surface **149** and the apex **156** of each wedge **152** may extend to a plane. In some embodiments, two or more wedges **152** may each include a slanted face **154** that slopes at different pitches or exhibits different curvatures.

[0038] With reference now to FIGS. **6A** and **6B**, an optical element **222** is illustrated in accordance with a third construction. Unless otherwise specified, the optical element **222** may be incorporated into at least the structure in FIG. **1** and other structures described herein. In addition, the optical element **222** may include similar features, elements, and materials as the other constructions set forth herein. More particularly, the optical element **222** includes a first major surface **248** that faces the illumination source **20** and a second major surface **249** that faces away from the illumination source **20**. The first major surface **248** defines at least one refractive element **250**. The at least one refractive element **250** may include a plurality of wedges **252** arranged diagonally to redirect and uniformly spread illumination from the illumination source **20** in a diagonal (i.e., both horizontally

and vertically) direction as indicated by the arrows in FIG. 6A. More particularly, each of the wedges **252** may include a slanted face **254** that extends outwardly from the first major surface **248** in a diagonal direction to an apex **256**, and a cliff portion **258** may extend from the apex **256** to an adjacent wedge **252**. In some embodiments, the slanted face **254** of the wedges **252** are curved (e.g., concave or convex) for concentrating or spreading the illumination. The apex **256** may also be curved (e.g., defined by a radius) and the cliff portion **258** may be angled from the apex **256** towards or away from the slanted face **254**. Each wedge **252** extends across (e.g., linearly) the first major surface **248** in a direction between a top side **260** and a bottom side **262**. The optical element **222** (e.g., the top side **260** and the bottom side **262**) is located at an angle from the illumination source **20**. In some embodiments, each wedge **252** extends across (e.g., linearly) the first major surface **248** at an angle between a top side **260** and a bottom side **262** and the top side **260** and bottom side **262** are parallel to top and bottom edges of the optical element **22**. The optical element **222** may be tapered such that one side **260**, **262** is thicker (“T”) than the other side **260**, **262** to bend light further in a diagonal direction. In some embodiments, the top side **260** is thinner than the bottom side **262**. In this manner, the direction of taper may further bend the light in a diagonally downward and rightward direction as indicated by the arrows in FIG. 6B. In some embodiments, the taper may be on the first major surface **248** and the second major surface **249** may be substantially planar. In some embodiments, one of the major surfaces **248**, **249** (e.g., the second major surface **249**) may be curved (e.g., concave or convex) for concentrating or spreading the illumination. In some embodiments, the taper may be on the second major surface **249** and the apex **256** of each wedge **252** may extend to a plane. In some embodiments, two or more wedges **252** may each include a slanted face **254** that slopes at different pitches or exhibits different curvatures. In some embodiments, the taper may be in a diagonal direction.

[0039] With reference now to FIGS. 7A and 7B, an optical element **322** is illustrated in accordance with a fourth construction. Unless otherwise specified, the optical element **322** may be incorporated into at least the structure in FIG. 1 and other structures described herein. In addition, the optical element **322** may include similar features, elements, and materials as the other constructions set forth herein. More particularly, the optical element **322** includes a first major surface **348** that faces the illumination source **20** and a second major surface **349** that faces away from the illumination source **20**. The first major surface **348** and the second major surface **349** each define at least one refractive element **350**. More particularly, the at least one refractive element **350** on the first major surface **348** includes a plurality of wedges **352** arranged vertically to redirect and uniformly spread illumination from the illumination source **20** in a horizontal direction. The at least one refractive element **350** on the second major surface **349** includes a plurality of wedges **352** arranged horizontally to redirect illumination from the illumination source **20** in a vertical direction. Each of the wedges **352** may include a slanted face **354** that extends outwardly from the first major surface **348** to an apex **356**, and a cliff portion **358** may extend from the apex **356** to an adjacent wedge **352**. In some embodiments, the slanted face **354** of the wedges **352** are curved (e.g., concave or convex) for concentrating or spreading the illumination. The apex **356** may also be curved (e.g., defined by a radius) and the cliff portion **358** may be angled from the apex **356** towards or away from the slanted face **354**. Each wedge **352** on the first major surface **348** extends across (e.g., linearly) the first major surface **348** from a top side **360** to a bottom side **362** of the optical element **322**. On the other hand, each wedge **352** on the second major surface **349** extends across (e.g., linearly) the first major surface **348** from a right side **364** to a left side **366** of the optical element **322**. In this manner, illumination is redirected and uniformly spread in a horizontal direction as it passes through the first major surface **348** and then is redirected and uniformly spread in a vertical direction as it passes through the second major surface **349** as indicated by the arrows in FIGS. 7A and 7B. It should be appreciated that the fourth construction can, alternatively, be more generally described as having the first major surface **348** with a refractive element **350** and a second major surface **349** with a refractive element **350** that is perpendicular to the refractive element **350** on the



first major surface **348**. In some embodiments, the wedges **352** on the first major surface **348** and/or the wedges **352** on the second major surface **349** may be angled relative to the sides **360**, **362**, **364**, **366** such that the light is bent in a diagonal direction, for example, similar to the configuration in FIGS. **6A** and **6B**. In some embodiments, two or more wedges **352** may include a slanted face **354** that each slopes at different pitches or exhibits different curvatures.

[0040] With reference now to FIGS. **4A-7B**, the pitch, curvature, size, and extension (e.g., the horizontal direction, the vertical direction, and/or the diagonal direction) of the wedges **52**, **152**, **252**, and **352** affects the redirection of the light from the illumination source **20**. Likewise, the varying thickness **T** may further be utilized to affect the redirection of the light from the illumination source **20**. In addition, the number of wedges **52**, **152**, **252**, and **352** affects the spread of the light from the illumination source **20**. In this manner, the spread and redirection of the light can be controlled to focus the light onto areas of the automobile **26** and/or other structures of interest (e.g., the occupant location **24**).

[0041] With reference now to FIGS. **8A** and **8B**, an optical element **422** is illustrated in accordance with a fifth construction. Unless otherwise specified, the optical element **422** may be incorporated into at least the structure in FIG. **1** and other structures described herein. In addition, the optical element **422** may include similar features, elements, and materials as the other constructions set forth herein. More particularly, the optical element **422** includes a first major surface **448** that faces the illumination source **20** and a second major surface **449** that faces away from the illumination source **20**. The first major surface **448** defines at least one refractive element **450**. The at least one refractive element **450** may include a plurality of wedges **452** arranged in a tower-grid pattern to redirect and uniformly spread illumination from the illumination source **20** in a diagonal (i.e., both horizontally and vertically) direction as indicated by the arrows in FIG. **8B**. More particularly, each of the wedges **452** may include a diagonally slanted face **454** that extends outwardly from the first major surface **448** in a diagonal direction to an apex **456**, and a cliff portion **458** may extend from the apex **456** to an adjacent wedge **452**. Each wedge **452** extends only partially across the first major surface **448** in the tower-grid pattern. In some embodiments, the slanted face **454** of the wedges **452** are curved (e.g., concave or convex) for concentrating or spreading the illumination. The apex **456** may also be curved (e.g., defined by a radius) and the cliff portion **458** may be angled from the apex **456** towards or away from the slanted face **454**. The optical element **422** may be tapered such that one of a top side **460**, a bottom side **462**, a right side **464**, or a left side **466** is thicker ("T") than an opposite side **460**, **462**, **464**, **466** to bend light further in a direction (e.g., diagonally, horizontally, or vertically). In some embodiments, the taper may be on the first major surface **448** and the second major surface **449** may be substantially planar. In some embodiments, one of the major surfaces **448**, **449** (e.g., the second major surface **449**) may be curved (e.g., concave or convex) for concentrating or spreading the illumination. In some embodiments, the taper may be on the second major surface **449** and the apex **456** of each wedge **452** may extend to a plane. In some embodiments, at least two of the wedges **452** each include a slanted face **454** extending in different directions, slope at a different pitch, and/or exhibit different curvatures.

[0042] With reference now to FIG. **9**, an optical element **522** is illustrated in accordance with a sixth construction. Unless otherwise specified, the optical element **522** may be incorporated into at least the structure in FIG. **1** and other structures described herein. In addition, the optical element **522** may include similar features, elements, and materials as the other constructions set forth herein. More particularly, the optical element **522** includes a first major surface **548** that faces the illumination source **20** and a second major surface **549** that faces away from the illumination source **20**. The optical element **522** may be tapered such that one of a top side **560**, a bottom side **562**, a right side **564**, or a left side **566** is thicker ("T") than an opposite side **560**, **562**, **564**, **566** to redirect light in a direction (e.g., diagonally, horizontally, or vertically). In some embodiments, the taper may be on the first major surface **548** and the second major surface **549** may be substantially planar. In some embodiments, one of the major surfaces **548**, **549** (e.g., the second major surface

**549**) may be curved (e.g., concave or convex) for concentrating or spreading the illumination. In some embodiments, the taper may be on the second major surface **549** and may be substantially planar or curved (e.g., convex or concave). The fifth construction may not include any wedges. In some embodiments, the taper may be in a diagonal direction.

[0043] With reference now to each of the constructions illustrated in FIGS. **1-9**, the optical elements **22, 122, 222, 322, 422, 522** may be formed of a material configured to transmit infrared light. For example, the material may include at least one of polycarbonate, silicon, or acrylic. The material may further include an additive that is configured to absorb light outside of the infrared spectrum. For example, the additive may include a dye, dye pellets, and/or a film that absorbs wavelengths outside of the infrared spectrum. In this manner, the optical element **22, 122, 222, 322, 422, 522** may be substantially opaque outside of the illumination spectrum (e.g., infrared or near-infrared) to reduce and/or prevent red glow of the illumination. The monitoring system **16** and the transmission element **30** (e.g., electro-activating the electro-optic medium **33**) may operate from a single PCB (e.g., the first or the second PCB **14, 15**). With reference now to FIGS. **4A-8B**, the wedges **52, 152, 252, 352, 452** may be provided for reducing the overall thickness **T** requirements of the optical elements **22, 122, 222, 322, 422** under the principles of the Fresnel lens. More particularly, the wedges **52, 152, 252, 352, 452** divides the optical elements **22, 122, 222, 322, 422** to a plurality of sections. In some embodiments, the wedges **52, 152, 252, 352, 452** are uniform for simplifying manufacturing.

[0044] It should also be appreciated that the disclosure is not strictly limited to the various constructions of the optical elements **22, 122, 222, 322, 422, 522** described herein. For example, in some embodiments, the wedge patterns (FIGS. **4A-6B** and **8A**) may be located on a second major surface rather than a first major surface. Likewise, various additional constructions may be implemented that include a first major surface with one of the wedge patterns (FIGS. **4A-6B** and **8A**) and a second major surface with the same or a different one of the wedge patterns (FIGS. **4A-6B** and **8A**). In addition, the taper of thickness **T** may be modified (e.g., diagonally, horizontally, or vertically) in any of the constructions in order to redirect light in a diagonal (e.g., upward and leftward, downward and leftward, upward and rightward, downward and rightward), horizontal (e.g., leftward or rightward), or vertical (e.g., upward or downward) direction as needed. The taper may be located on the first major surface **48, 148, 248, 348, 448**, and **548** or the second major surface **49, 149, 249, 349, 449**, and **549**. It should be appreciated that light will be directed in a direction of the thicker part of the taper and or wedge **52, 152, 252, 352**, and **448**. Accordingly, various constructions may be defined as having a first wedge pattern on a first major surface that is configured to redirect and spread light uniformly in a diagonal (e.g., upward and leftward, downward and leftward, upward and rightward, downward and rightward), horizontal (e.g., leftward or rightward), or vertical (e.g., upward or downward) direction. Similarly, various constructions may be defined as having a second wedge pattern on a second major surface that is configured to redirect and spread light uniformly in a diagonal (e.g., upward and leftward, downward and leftward, upward and rightward, downward and rightward), horizontal (e.g., leftward or rightward), or vertical (e.g., upward or downward) direction. Generally speaking, light will be directed in a direction of the apex of the wedge. In some embodiments, various constructions may include a first wedge pattern on a first major surface, a second wedge pattern on a second major surface, and a taper in a horizontal, vertical, or diagonal direction. In some embodiments, various constructions may include a wedge pattern on a first major surface, a planar second major surface, and a taper. In some embodiments, various constructions may include a planar first major surface, a wedge pattern on a second major surface, and a taper as described herein. In some embodiments, various constructions may include a taper on the first and/or second major surface.

[0045] The disclosure herein is further summarized in the following paragraphs and is further characterized by combinations of any and all of the various aspects described therein.

[0046] According to one aspect, a rearview mirror assembly includes a housing and a printed circuit board (PCB) located in the housing. The rearview mirror assembly further includes a monitoring system that includes an image capturing module, an illumination source connected to the PCB, and an optical element aligned with the illumination source. The optical element is configured to redirect and spread an illumination from the illumination source toward an occupant position in an automobile.

[0047] According to another aspect, an image capturing module is located in a housing.

[0048] According to yet another aspect, a connection body connects an optical element to a PCB in a spaced relationship from an illumination source.

[0049] According to another aspect, a connection body includes a pair of pins extending from an optical element to a PCB

[0050] According to yet another aspect, a connection body includes a pair of clips extending from an optical element to a PCB.

[0051] According to another aspect, an optical element includes a first major surface facing an illumination source and a second major surface facing away from the illumination source.

[0052] According to yet another aspect, a first major surface of an optical element defines at least one refractive element.

[0053] According to another aspect, at least one refractive element includes a plurality of wedges arranged vertically to redirect and spread the illumination in a horizontal direction.

[0054] According to yet another aspect, at least one refractive element includes a plurality of wedges arranged horizontally to redirect and spread the illumination in a vertical direction.

[0055] According to another aspect, at least one refractive element includes a plurality of wedges arranged diagonally to redirect and spread the illumination in a horizontal direction and a vertical direction.

[0056] According to yet another aspect, a transmission element is located in a housing and transmits an illumination therethrough into an automobile and a second major surface of an optical element is directly adhered to the transmission element.

[0057] According to another aspect, at least one refractive element includes a first plurality of wedges arranged in at least one of a vertical or horizontal orientation and a second major surface defines at least one second refractive element including a second plurality of wedges arranged perpendicular to the first plurality of wedges on the first major surface.

[0058] According to yet another aspect, an optical element is formed of at least one of polycarbonate, silicon, or acrylic.

[0059] According to another aspect, the optical element includes at least one additive configured to absorb light outside of the infrared spectrum.

[0060] According to yet another aspect, an illumination source is configured to transmit infrared light.

[0061] According to another aspect of the present disclosure, a rearview mirror assembly includes a housing, a transmission element at least partially located in the housing, and a printed circuit board (PCB) located in the housing. The rearview mirror assembly further includes a monitoring system that includes an image capturing module, an illumination source connected to the PCB, and an optical element aligned with the illumination source that includes a plurality of wedges each extending to an apex. The plurality of wedges is configured to redirect and spread an illumination from the illumination source toward an occupant position in an automobile.

[0062] According to another aspect, the plurality of wedges is arranged in a tower-grid pattern.

[0063] According to yet another aspect, a connection body connects an optical element to a PCB in a spaced relationship from an illumination source.

[0064] According to yet another aspect of the present disclosure, a rearview mirror assembly includes a housing and a printed circuit board (PCB) located in the housing. The rearview mirror assembly further includes a monitoring system that includes an image capturing module, an

illumination source connected to the PCB, and an optical element aligned with the illumination source. The optical element is configured to redirect and spread an illumination from the illumination source toward an occupant position in an automobile. A connection body connects the optical element in a spaced relationship from the illumination source.

[0065] According to another aspect, a connection body is configured to connect an optical element to one of a PCB, a housing, or a transmission element.

[0066] It will be understood by one having ordinary skill in the art that construction of the described disclosure and other components is not limited to any specific material. Other exemplary embodiments of the disclosure disclosed herein may be formed from a wide variety of materials, unless described otherwise herein.

[0067] For purposes of this disclosure, the term “coupled” (in all of its forms, couple, coupling, coupled, etc.) generally means the joining of two components (electrical or mechanical) directly or indirectly to one another. Such joining may be stationary in nature or movable in nature. Such joining may be achieved with the two components (electrical or mechanical) and any additional intermediate members being integrally formed as a single unitary body with one another or with the two components. Such joining may be permanent in nature or may be removable or releasable in nature unless otherwise stated.

[0068] It is also important to note that the construction and arrangement of the elements of the disclosure, as shown in the exemplary embodiments, is illustrative only. Although only a few embodiments of the present innovations have been described in detail in this disclosure, those skilled in the art who review this disclosure will readily appreciate that many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter recited. For example, elements shown as integrally formed may be constructed of multiple parts, or elements shown as multiple parts may be integrally formed, the operation of the interfaces may be reversed or otherwise varied, the length or width of the structures and/or members or connectors or other elements of the system may be varied, and the nature or number of adjustment positions provided between the elements may be varied. It should be noted that the elements and/or assemblies of the system may be constructed from any of a wide variety of materials that provide sufficient strength or durability, in any of a wide variety of colors, textures, and combinations. Accordingly, all such modifications are intended to be included within the scope of the present innovations. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions, and arrangement of the desired and other exemplary embodiments without departing from the spirit of the present innovations.

[0069] It will be understood that any described processes or steps within described processes may be combined with other disclosed processes or steps to form structures within the scope of the present disclosure. The exemplary structures and processes disclosed herein are for illustrative purposes and are not to be construed as limiting.

[0070] It is also to be understood that variations and modifications can be made on the aforementioned structures and methods without departing from the concepts of the present disclosure, and further it is to be understood that such concepts are intended to be covered by the following claims unless these claims by their language expressly state otherwise.

## Claims

1. A rearview mirror assembly comprising: a housing; a printed circuit board (PCB) located in the housing; a monitoring system comprising: an image capturing module; an illumination source connected to the PCB; and an optical element aligned with the illumination source including a first major surface facing the illumination source and a second major surface facing away from the

illumination source, and a plurality of wedges on at least one of the first major surface and the second major surface to redirect and spread an illumination from the illumination source toward a desired position in an automobile.

**2.** The rearview mirror assembly of claim 1, wherein the plurality of wedges each include a slanted face slopping to define a pitch and two or more of the plurality of wedges include slanted faces slopping to define different pitches.

**3.** The rearview mirror assembly of claim 2, wherein the plurality of wedges are only located on the one of the first major surface and the second major surface.

**4.** The rearview mirror assembly of claim 3, wherein the plurality of wedges are located on the first major surface.

**5.** The rearview mirror assembly of claim 1, wherein the plurality of wedges includes a first plurality of wedges on the first major surface and a second plurality of wedges on the second major surface.

**6.** The rearview mirror assembly of claim 5, wherein the first plurality of wedges extend transversely to the second plurality of wedges.

**7.** The rearview mirror assembly of claim 6, wherein the first plurality of wedges are arranged in at least one of a vertical or horizontal orientation for directing the illumination in a first direction and the second plurality of wedges are arranged perpendicular to the first plurality of wedges on the first major surface for directing the illumination in a second direction that is different than the first direction.

**8.** The rearview mirror assembly of claim 5, wherein the plurality of wedges include each include a slanted face slopping to define a pitch and the first plurality of wedges include slanted faces slopping to define different pitches than the second plurality of wedges.

**9.** The rearview mirror assembly of claim 1, wherein the plurality of wedges each include a slanted face slopping from an apex in a first direction to define a pitch and a taper along a second direction that is different than the first direction to define a reduction in thickness of the optical element in the second direction.

**10.** The rearview mirror assembly of claim 9, wherein the plurality of wedges are located on the first major surface and the apex of each wedge becomes closer to the second major surface in the second direction.

**11.** The rearview mirror assembly of claim 10, wherein the slanted face defined by each of the plurality of wedges each include a substantially equal pitch.

**12.** A rearview mirror assembly comprising: a housing; a printed circuit board (PCB) located in the housing; a monitoring system comprising: an image capturing module; an illumination source connected to the PCB; and an optical element aligned with the illumination source including a first major surface facing the illumination source and a second major surface facing away from the illumination source, a plurality of wedges arranged in a tower-grid pattern on at least one of the first major surface and the second major surface to redirect and spread an illumination from the illumination source toward a desired position in an automobile.

**13.** The rearview mirror assembly of claim 12, wherein the optical element defines an outer perimeter and the tower-grid pattern includes a plurality of rows and columns of wedges.

**14.** The rearview mirror assembly of claim 13, wherein the tower-grid pattern extends substantially across the entire outer perimeter.

**15.** The rearview mirror assembly of claim 12, wherein the plurality of wedges each include a slanted face extending to an apex.

**16.** The rearview mirror assembly of claim 15, wherein the apex of each of the plurality of wedges are oriented in the same direction.

**17.** The rearview mirror assembly of claim 15, wherein two or more slanted faces of the plurality of wedges slope at different pitches.

**18.** The rearview mirror assembly of claim 15, wherein the optical element defines a thickness that

tapers between opposite sides of the optical element.

**19.** A rearview mirror assembly comprising: a housing; an electro-optic element at least partially located in the housing; a printed circuit board (PCB) located in the housing; a monitoring system comprising: an image capturing module; an illumination source connected to the PCB; and an optical element spaced from and aligned with the illumination source and coupled directly to the PCB with a connection body, the optical element configured to redirect an illumination from the illumination source toward a desired position in an automobile.

**20.** The rearview mirror assembly of claim 19, wherein the optical element includes a first major surface facing the illumination source and a second major surface facing away from the illumination source, and a first plurality of wedges on the first major surface and a second plurality of wedges on the second major surface to redirect and spread an illumination from the illumination source.

---