

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279492

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

LIN; Tingxiao et al.

FOIL RECOVERY APPARATUS

Abstract

A foil recovery apparatus is provided and includes a base, a conveying device, and a collecting device. The conveying device includes a conveyor belt and a first roller set. The first roller set includes a first conveying roller and a second conveying roller. The conveyor belt is driven around the first conveying roller and the second conveying roller for transmission. The collecting device includes a storage bin and a carrying platform. The storage bin includes a pushing plate and defines a receiving cavity. The storage bin defines a first opening. The pushing plate and the first opening are located on two opposite sides of the receiving cavity, respectively, and the first opening is opposite to the pushing plate. The carrying platform includes a pressing plate. The storage bin is disposed at one side of the second conveying roller away from the first conveying roller.

Inventors: LIN; Tingxiao (Xiamen, CN), CHEN; Jiazhu (Xiamen, CN)

Applicant: Hithium Tech HK Limited (Kowloon, HK)

Family ID: 90523199

Appl. No.: 19/035572

Filed: January 23, 2025

Foreign Application Priority Data

CN 202410241446.7

Mar. 04, 2024

Publication Classification

Int. Cl.: H01M10/54 (20060101); F26B13/28 (20060101); F26B21/00 (20060101)

U.S. Cl.:

CPC H01M10/54 (20130101); F26B13/28 (20130101); F26B21/004 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority under 35 U.S.C. § 119 (a) to and the benefit of Chinese Patent Application No. 202410241446.7, filed Mar. 4, 2024, the entire disclosure of which is incorporated herein by reference.

TECHNICAL FIELD

[0002] The disclosure relates to the field of battery cell recovery technology, and in particular, to a foil recovery apparatus.

BACKGROUND

[0003] In a positive electrode of a secondary battery, aluminum foil generally serves as a substrate, and a positive electrode material is uniformly coated on both sides of the aluminum foil. In a negative electrode of the secondary battery, copper foil generally serves as a substrate, and a negative electrode material is uniformly coated on both sides of the copper foil. In order to reduce pollution and improve energy utilization efficiency, old battery cells are typically recycled. In the old battery cells, a foil (including the aluminum foil and the copper foil) is coated with electrode materials on the surface. Therefore, during the recycling process, the foil in the old battery cells needs to be cleaned first, and then the cleaned foil is collected. However, currently, the collection of the cleaned foil is mostly done manually, leading to low collection efficiency and increased foil recycling costs.

SUMMARY

[0004] A foil recovery apparatus includes a base, a conveying device, and a collecting device. The conveying device includes a conveyor belt and a first roller set, the first roller set is connected to the base and includes a first conveying roller and a second conveying roller, the conveyor belt has a carrying surface, the first conveying roller is opposite to the second conveying roller in a first direction, the conveyor belt is driven around the first conveying roller and the second conveying roller for transmission, and the first direction is a conveying direction of the conveyor belt. The collecting device includes a storage bin and a carrying platform. The storage bin includes a pushing plate and defines a receiving cavity, the storage bin defines a first opening, the pushing plate and the first opening are located on two opposite sides of the receiving cavity in the first direction, respectively, and the carrying platform includes a pressing plate. In the first direction, the storage bin is disposed at one side of the second conveying roller away from the first conveying roller, the carrying platform is disposed at one side of the storage bin where the first opening is defined, the pressing plate is opposite to the pushing plate, the conveying device is configured to convey a foil into the receiving cavity, and the pressing plate is operable to enter the receiving cavity through the first opening to compress the foil within the receiving cavity along with the pushing plate.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] To describe technical solutions in embodiments of the disclosure more clearly, the following briefly introduces the accompanying drawings required for describing the embodiments.

Apparently, the accompanying drawings in the following description merely illustrate some embodiments of the disclosure. Those of ordinary skill in the art may also obtain other accompanying drawings based on these provided herein without creative efforts.

[0006] FIG. 1 is a schematic structural view of a foil recovery apparatus provided in embodiments of the disclosure.

[0007] FIG. 2 is a schematic structural view of a conveying device of the foil recovery apparatus in

FIG. 1.

[0008] FIG. 3 is a schematic structural view illustrating an assembly of a conveyor belt of the conveying device in FIG. 2.

[0009] FIG. 4 is a schematic structural view illustrating an assembly of a pressing belt of the conveying device in FIG. 2.

[0010] FIG. 5 is a schematic structural view of a dewatering member of a dewatering assembly in FIG. 1.

[0011] FIG. 6 is a schematic structural view illustrating an assembly of a pressing belt and a dewatering assembly in FIG. 1.

[0012] FIG. 7 is a schematic structural view of a separation member of a dewatering assembly in FIG. 1.

[0013] FIG. 8 is a schematic structural view of a collecting device of the foil recovery apparatus in FIG. 1, viewed from a first direction.

[0014] FIG. 9 is a schematic structural view of the collecting device in FIG. 8, viewed from a second direction.

[0015] FIG. 10 is a schematic structural view of a carrying platform in FIG. 8.

[0016] FIG. 11 is an exploded schematic structural view of the carrying platform in FIG. 10.

[0017] FIG. 12 is a partial exploded schematic structural view of the carrying platform in FIG. 11.

[0018] FIG. 13 is a schematic structural view of a cutting member in FIG. 8.

[0019] Reference numbers are described as follows: [0020] **1000**—foil recovery apparatus, **400**—base, **100**—conveying device, **200**—dewatering assembly, **300**—collecting device, **30**—conveyor belt, **40**—pressing belt, **90**—rotary brush, **10**—first conveying roller, **20**—second conveying roller, **50**—first common roller, **60**—second common roller, **70**—third common roller, **80**—connecting roller, **31**—carrying surface, **32**—connecting surface, **33**—air hole, **41**—pressing surface, **42**—rotating surface, **220**—dewatering member, **230**—separation member, **240**—isolation plate, **221**—clamping portion, **2211**—fixed plate, **2212**—first swinging arm, **2213**—second swinging arm, **2214**—first pressing roller, **2215**—second pressing roller, **2216**—first connecting rod, **2217**—second connecting rod, **231**—connection portion, **232**—blow nozzle, **310**—storage bin, **320**—carrying platform, **360**—recovery member, **370**—cutting member, **311**—bottom plate, **312**—side plate, **313**—pushing plate, **314**—sliding rail, **315**—switch driving member, **3151**—drive shaft, **3111**—receiving surface, **3112**—transition surface, **3131**—abutting surface, **3132**—sliding surface, **3133**—sliding groove, **3134**—slider, **330**—carrying member, **340**—pushing member, **350**—guiding member, **331**—carrying plate, **332**—pressing plate, **333**—mounting plate, **3311**—carrying surface, **3312**—mounting surface, **351**—guiding rod, **352**—sleeve, **353**—linear bearing, **3331**—drive hole, **3332**—balance hole, **3321**—pressing surface, **3322**—pushing surface, **361**—recovery basket, **362**—fixing portion, **3611**—inner surface, **3612**—outer surface, **363**—recovery opening, **371**—fixed frame, **372**—connecting shaft, **373**—scraping blade, **3711**—first plate body, **3712**—second plate body, **3713**—mounting portion, **3731**—limiting portion, **3732**—scraping portion, **S1**—conveying start point, **S2**—conveying end point, **M1**—first roller set, **M2**—second roller set, **600**—driving motor, **43**—ventilation hole, **O**—pressing region, **2321**—outlet, **3161**—first opening, **3162**—second opening, **316**—receiving cavity, **3531**—first end face, **3532**—second end face, **3533**—through hole, **3521**—through hole, **341**—pushing rod, **3734**—scraping end, **3733**—connection hole.

DETAILED DESCRIPTION

[0021] The technical solutions in embodiments of the disclosure are clearly and completely described in the following with reference to the accompanying drawings in the embodiments of the disclosure. Apparently, the described embodiments are merely part of rather than all of the embodiments of the disclosure. All other embodiments obtained by those of ordinary skill in the art based on the embodiments of the disclosure without creative efforts are within the scope of the disclosure.

[0022] Referring to FIG. 1, FIG. 1 is a schematic structural view of a foil recovery apparatus provided in the embodiments of the disclosure. The embodiments of the disclosure provide a foil recovery apparatus **1000**. The foil recovery apparatus **1000** includes a base **400**, a conveying device **100**, a dewatering assembly **200**, and a collecting device **300**. The conveying device **100** is configured to convey a foil. The conveying device **100** has a conveying start point **S1** and a conveying end point **S2**. The conveying start point **S1** and the conveying end point **S2** are disposed at two opposite ends of the conveying device **100**, respectively. The dewatering assembly **200** is located between the conveying start point **S1** and the conveying end point **S2** of the conveying device **100**. The dewatering assembly **200** is configured to dewater the foil conveyed by the conveying device **100**. The collecting device **300** is disposed at the conveying end point **S2** of the conveying device **100**, and is configured to compress and collect the foil.

[0023] It may be noted that the foil recovery apparatus **1000** provided in the embodiments of the disclosure is applicable to foils including, but not limited to, aluminum foil, copper foil, silver foil, and foils made of other materials, which is not specifically limited herein. The conveying start point **S1** and the conveying end point **S2** correspond to the two opposite ends of the conveying device **100** in a first direction and are not specific structures on the conveying device **100**, and thus do not impose specific structural limitations on the conveying device **100**.

[0024] Only a partial structure of the base **400** is illustrated in FIG. 1, which does not impose any limitations on the overall structure of the base **400**. The base **400** may also include other structures. The base **400** can be formed as a single-piece structure or a modular structure, which is not specifically limited herein.

[0025] For ease of illustration, a length direction of the foil recovery apparatus **1000** illustrated in FIG. 1 is defined as X-axis direction, which may also be referred to as a first direction. The first direction is also a direction in which the conveying device **100** performs transmission. A width direction of the foil recovery apparatus **1000** is Y-axis direction. A height direction of the foil recovery apparatus **1000** is Z-axis direction, which may also be referred to as a second direction. X-axis direction, Y-axis direction, and Z-axis direction are mutually perpendicular to each other. Orientation terms such as “up” and “down” referred to in the embodiments of the disclosure are described with reference to orientations illustrated in FIG. 1, where positive Z-axis direction is defined as “up” and negative Z-axis direction is defined as “down”. These terms do not impose any limitations on the foil recovery apparatus **1000**. The terms “same”, “equal”, or “parallel” referred to herein allow for a certain tolerance.

[0026] Referring to FIGS. 2 to 4, FIG. 2 is a schematic structural view of the conveying device of the foil recovery apparatus in FIG. 1, FIG. 3 is a schematic structural view illustrating an assembly of a conveyor belt of the conveying device in FIG. 2, and FIG. 4 is a schematic structural view illustrating an assembly of a pressing belt of the conveying device in FIG. 2.

[0027] The conveying device **100** includes a first roller set **M1**, a second roller set **M2**, a conveyor belt **30**, a pressing belt **40**, and a rotary brush **90**. All the first roller set **M1**, the second roller set **M2**, and the rotary brush **90** are mounted to the base **400**. The conveyor belt **30** is wound around the first roller set **M1** and the second roller set **M2**. The pressing belt **40** is wound around the second roller set **M2**.

[0028] The first roller set **M1** includes a first conveying roller **10** and a second conveying roller **20**. The first conveying roller **10** is opposite to the second conveying roller **20** in the first direction (X-axis direction). Two opposite ends of the first conveying roller **10** are rotatably connected to the base **400**. Two opposite ends of the second conveying roller **20** are rotatably connected to the base **400**. The first conveying roller **10** and the second conveying roller **20** are respectively connected to two opposite ends of the base **400**. The first conveying roller **10** is parallel to the second conveying roller **20**. The first conveying roller **10** is located at the conveying start point **S1** of the conveying device **100**. The second conveying roller **20** is located at the conveying end point **S2** of the conveying device **100**. At least one of the first conveying roller **10** or the second conveying roller

20 is connected to a driving motor **600**. In this embodiment, the first conveying roller **10** includes two sub-conveying rollers. The second conveying roller **20** is connected to the driving motor **600**, which is configured to drive the second conveying roller **20** to rotate.

[0029] In other embodiments, the first conveying roller **10** may include only one sub-conveying roller. Alternatively, the first conveying roller **10** may include three or more sub-conveying rollers. Alternatively, the first conveying roller **10** may also be connected to the driving motor **600**. Alternatively, both the first conveying roller **10** and the second conveying roller **20** may be connected to the driving motor **600**.

[0030] It may be noted that the sub-conveying roller of the first conveying roller **10** may be the same as or different from a sub-conveying roller of the second conveying roller **20** in structure, which is not specifically limited herein.

[0031] In the first direction (X-axis direction), the second roller set **M2** is located between the first conveying roller **10** and the second conveying roller **20**. The second roller set **M2** includes a first common roller **50**, a second common roller **60**, a third common roller **70**, and two connecting rollers **80**. Two opposite ends of the first common roller **50** are rotatably connected to the base **400**. Two opposite ends of the second common roller **60** are rotatably connected to the base **400**. Two opposite ends of the third common roller **70** are rotatably connected to the base **400**. Two opposite ends of each of the two connecting rollers **80** are rotatably connected to the base **400**. In the first direction, the first common roller **50** and the third common roller **70** are opposite to each other and are located between the first conveying roller **10** and the second conveying roller **20**. In the second direction (Z-axis direction), the second common roller **60** is spaced apart from the first common roller **50** and the third common roller **70**. An orthographic projection of the second common roller **60** on the conveyor belt **30** is located between an orthographic projection of the first common roller **50** on the conveyor belt **30** and an orthographic projection of the third common roller **70** on the conveyor belt **30**. In the second direction (Z-axis direction), one of the two connecting rollers **80** is opposite to and spaced apart from the first common roller **50**, and another one of the two connecting rollers **80** is opposite to and spaced apart from the third common roller **70**. Both the two connecting rollers **80** are disposed at one side of the second common roller **60** away from the first common roller **50** and the third common roller **70**. In this embodiment, one of the two connecting rollers **80** is connected to the driving motor **600**, and the driving motor **600** is configured to drive the connecting roller **80** connected to the driving motor **600** to rotate. In other embodiments, the first common roller **50**, the second common roller **60**, the third common roller **70**, and the another one of the two connecting rollers **80** may also be connected to the driving motor **600**.

[0032] It may be noted that the first common roller **50**, the second common roller **60**, the third common roller **70**, and the two connecting rollers **80** may be the same as or different from each other in structure, which is not specifically limited herein.

[0033] The conveyor belt **30** is a loop. The conveyor belt **30** includes a carrying surface **31** and a connecting surface **32**. The carrying surface **31** is opposite to the connecting surface **32** in a thickness direction of the conveyor belt **30**. The carrying surface **31** is configured to carry the foil. The conveyor belt **30** defines multiple air holes **33** that are evenly distributed. In the thickness direction of the conveyor belt **30**, the multiple air holes **33** extend through both the carrying surface **31** and the connecting surface **32** of the conveyor belt **30**. It is noted that, the air holes **33** facilitate air passing through the conveyor belt **30** to contact a surface of the foil that is close to the conveyor belt **30**. This not only aids in drying the foil but also contributes to a more stable contact between the foil and the conveyor belt **30**.

[0034] It may be noted that the multiple air holes **33** on the conveyor belt **30** in FIG. 2 are illustrated for illustrative purposes only, and does not impose specific limitations on the distribution position and quantity of the multiple air holes **33**.

[0035] The conveyor belt **30** is driven sequentially around the first conveying roller **10**, the second roller set **M2**, and the second conveying roller **20** for transmission. Specifically, the conveyor belt

30 is arranged, through the first conveying roller **10** and the first common roller **50**, around the second common roller **60** in the second direction (Z-axis direction), and then arranged, through the third common roller **70**, around the second conveying roller **20** in the first direction (X-axis direction), to achieve cyclic transmission. The connecting surface **32** of the conveyor belt **30** is rotatably connected to the first conveying roller **10**, the second common roller **60**, and the second conveying roller **20**. The carrying surface **31** of the conveyor belt **30** is rotatably connected to the first common roller **50** and the third common roller **70**. In some embodiments, all the first conveying roller **10**, the second common roller **60**, and the second conveying roller **20** are rotatably connected to the connecting surface **32** of the conveyor belt **30**. Both the first common roller **50** and the third common roller **70** are rotatably connected to the carrying surface **31** of the conveyor belt **30**.

[0036] The pressing belt **40** is a loop. The pressing belt **40** includes a pressing surface **41** and a rotating surface **42**. The pressing surface **41** is opposite to the rotating surface **42** in a thickness direction of the pressing belt **40**. The pressing belt **40** defines multiple ventilation holes **43**. The multiple ventilation holes **43** extend through both the pressing surface **41** and the rotating surface **42** in the thickness direction of the pressing belt **40**. The multiple ventilation holes **43** are evenly distributed.

[0037] It may be noted that the multiple ventilation holes **43** on the pressing belt **40** in FIG. 4 is illustrated for illustrative purposes only, and does not impose specific limitations on the distribution position and quantity of the multiple ventilation holes **43**.

[0038] The pressing belt **40** is driven around the second roller set M2 for transmission. The pressing belt **40** is configured to perform transmission in the second direction (Z-axis direction). Specifically, the pressing belt **40** is arranged, through the first common roller **50**, around the second common roller **60** in the second direction, and then arranged, through the third common roller **70**, around the two connecting rollers **80** in the second direction, to achieve cyclic transmission. The rotating surface **42** of the pressing belt **40** is rotatably connected to the first common roller **50**, the third common roller **70**, and the two connecting rollers **80**. The pressing surface **41** of the pressing belt **40** is rotatably connected to the second common roller **60**. It may be understood that the entire pressing belt **40** has an n-shape.

[0039] In this embodiment, the driving motor **600** connected to the second conveying roller **20** is configured to drive the second conveying roller **20** to rotate, rotation of the second conveying roller **20** can drive the conveyor belt **30** to move, and movement of the conveyor belt **30** can in turn drive the first conveying roller **10** and the second common roller **60** to rotate. The driving motor **600** connected to one of the two connecting rollers **80** is configured to drive the connecting roller **80** to rotate, rotation of the connecting roller **80** can drive the pressing belt **40** to move, and movement of the pressing belt **40** can in turn drive the another one of the two connecting rollers **80**, the first common roller **50**, and the third common roller **70** to rotate.

[0040] A rotational linear velocity of the first conveying roller **10**, a rotational linear velocity of the second conveying roller **20**, a rotational linear velocity of the first common roller **50**, a rotational linear velocity of the second common roller **60**, a rotational linear velocity of the third common roller **70**, and a rotational linear velocity of the two connecting rollers **80** are the same as each other. A rotational direction of the first conveying roller **10**, a rotational direction of the second conveying roller **20**, and a rotational direction of the second common roller **60** are the same as each other. A rotational direction of the first common roller **50**, a rotational direction of the third common roller **70**, and a rotational direction of each of the two connecting rollers **80** each are opposite to the rotational direction of the second conveying roller **20**.

[0041] The conveyor belt **30** is in contact with the pressing belt **40** to form a pressing region O when the conveyor belt **30** is driven around the second roller set M2 for transmission. Part of the conveyor belt **30** in the pressing region O and part of the pressing belt **40** in the pressing region O disengage from each other when the part of the conveyor belt **30** in the pressing region O

disengages from the second roller set M2, to allow the part of the conveyor belt 30 in the pressing region O to move in the first direction (X-axis direction) and the part of the pressing belt 40 in the pressing region O to move in the second direction (Z-axis direction). In the case where the foil is placed on the carrying surface 31 of the conveyor belt 30, when the conveyor belt 30 conveys the foil to the second roller set M2 for transmission, the foil will be clamped between the pressing belt 40 and the conveyor belt 30. When the part of the conveyor belt 30 in the pressing region O disengages from the second roller set M2, the foil will continue to move along with the conveyor belt 30 in the first direction (X-axis direction).

[0042] It may be noted that during operation of the foil recovery apparatus 1000, the conveyor belt 30 and the pressing belt 40 continuously move. Therefore, part of the conveyor belt 30 corresponding to the pressing region O is not a fixed part of the conveyor belt 30, but changes dynamically as the conveyor belt 30 moves. Similarly, part of the pressing belt 40 corresponding to the pressing region O is not a fixed part of the pressing belt 40, but changes dynamically as the pressing belt 40 moves.

[0043] In the first direction (X-axis direction), the rotary brush 90 is disposed at one side of the second conveying roller 20 away from the first conveying roller 10. That is, the rotary brush 90 is positioned at the conveying end point S2 of the conveying device 100. Two opposite ends of the rotary brush 90 are rotatably connected to the base 400. The rotary brush 90 is connected to the driving motor. A rotational direction of the rotary brush 90 is the same as that of the second conveying roller 20. A rotational linear velocity of the rotary brush 90 is greater than a linear velocity of the conveyor belt 30. For example, the rotational linear velocity of the rotary brush 90 is 1.2 times that of the conveyor belt 30. In the embodiments of the disclosure, a ratio of the rotational linear velocity of the rotary brush 90 to the linear velocity of the conveyor belt 30 is not specifically limited.

[0044] Referring to FIG. 1, the dewatering assembly 200 includes a dewatering member 220, a separation member 230, and an isolation plate 240.

[0045] Referring to FIG. 5, FIG. 5 is a schematic structural view of the dewatering member of the dewatering assembly in FIG. 1. The dewatering member 220 includes two clamping portions 221. The two clamping portions 221 are arranged adjacently.

[0046] Each clamping portion 221 includes a fixed plate 2211, two first swinging arms 2212, two second swinging arms 2213, a first pressing roller 2214, a second pressing roller 2215, a first connecting rod 2216, and a second connecting rod 2217. In a width direction of the clamping portion 221, the two fixed plates 2211 are opposite to each other. In a height direction of the clamping portion 221, the two first swinging arms 2212 are connected to one end of the fixed plate 2211 away from the second swinging arm 2213, and the two second swinging arms 2213 are connected to one end of the fixed plate 2211 away from the first swinging arm 2212. One end of one of the two first swinging arms 2212 and one end of another one of the two first swinging arms 2212 are rotatably connected to the two fixed plates 2211, respectively. The first pressing roller 2214 is located between and connected to another end of the one of the two first swinging arms 2212 and another end of the another one of the two first swinging arms 2212. One end of one of the two second swinging arms 2213 and one end of another one of the two second swinging arms 2213 are rotatably connected to the two fixed plates 2211, respectively. The second pressing roller 2215 is located between and connected to another end of the one of the two second swinging arms 2213 and another end of the another one of the two second swinging arms 2213. The first connecting rod 2216 is located between and connected to the two first swinging arms 2212. The second connecting rod 2217 is located between and connected to the two second swinging arms 2213.

[0047] Referring to FIG. 5 and FIG. 6, FIG. 6 is a schematic structural view illustrating an assembly of the pressing belt and the dewatering assembly in FIG. 1. The dewatering member 220 is fixed to the base 400. In the first direction, the dewatering member 220 is located between the first common roller 50 and the second common roller 60. In the second direction, the dewatering

member **220** is located between the first common roller **50** and the second common roller **60**. The pressing region **O** formed by a close contact between the conveyor belt **30** and the pressing belt **40**, can pass through the two clamping portions **221**. Specifically, the two fixed plates **2211** of the two clamping portions **221** are arranged adjacently. In a height direction of the dewatering member **220**, the first swinging arms **2212** of the two clamping portions **221** are disposed at the same end, and the second swinging arms **2213** of the two clamping portions **221** are disposed at the same end. The two first swinging arms **2212** of each of the two clamping portions **221** can rotate synchronously. The two second swinging arms **2213** of each of the two clamping portions **221** can rotate synchronously. The first pressing rollers **2214** of the two clamping portions **221** are arranged adjacently to form a first pair of pressing rollers. The second pressing rollers **2215** of the two clamping portions **221** are arranged adjacently to form a second pair of pressing rollers. The rotation of the two first swinging arms **2212** of each of two clamping portions **221** can drive the first pressing roller **2214** to move towards or away from the pressing region **O**. Similarly, the rotation of the two second swinging arms **2213** of each of the two clamping portions **221** can drive the second pressing roller **2215** to move towards or away from the pressing region **O**. In other embodiments, two clamping portions **221** may form only one pair of pressing rollers. For example, each clamping portion **221** may omit the two second swinging arms **2213**, the second pressing roller **2215**, and the second connecting rod **2217**.

[0048] Referring to FIG. 7, FIG. 7 is a schematic structural view of the separation member of the dewatering assembly in FIG. 1. The separation member **230** includes two connection portions **231** and a blow nozzle **232**. Two opposite ends of the blow nozzle **232** are connected to the two connection portions **231**, respectively. The blow nozzle **232** extends in a length direction of the separation member **230**. The blow nozzle **232** has an outlet **2321**. The outlet **2321** is disposed on one side of the blow nozzle **232** in a width direction of the blow nozzle **232**. Airflow can be blown out through the outlet **2321**. In this embodiment, the outlet **2321** is a continuous slit that extends in a length direction of the blow nozzle **232**.

[0049] In other embodiments, the outlet **2321** may be a discontinuous gap; alternatively, the outlet **2321** may be formed by multiple air outlets arranged at intervals in the length direction of the blow nozzle **232**.

[0050] Referring to FIG. 6, the separation member **230** is fixed to the base **400**. Two opposite ends of the blow nozzle **232** are connected to the base **400** through the two connection portions **231**, respectively. In the first direction (X-axis direction), the blow nozzle **232** and the dewatering member **220** are located at two opposite sides of the second common roller **60**, respectively. It may be understood that, in the first direction (X-axis direction), the blow nozzle **232** is spaced apart from the dewatering member **220**. After passing through the two clamping portions **221**, the pressing region **O** continues to move, passing through the second common roller **60**, to the blow nozzle **232**. Multiple outlets **2321** of the blow nozzle **232** face towards the pressing region **O**.

[0051] In the first direction (X-axis direction), the isolation plate **240** is located between the dewatering member **220** and the separation member **230**. Two surfaces of the isolation plate **240**, which are opposite to each other in a thickness direction of the separation member **230**, face towards the dewatering member **220** and the separation member **230**, respectively. In the second direction (Z-axis direction), an orthographic projection of the isolation plate **240** on the base **400** falls within an orthographic projection of the second common roller **60** on the base **400**.

[0052] It may be understood that the foil is placed on the carrying surface **31** of the conveyor belt **30**. The conveyor belt **30** can bring the foil to move towards the conveying end point **S2** of the conveying device **100**. When the foil reaches the first common roller **50**, the foil will rotate around the first common roller **50** along with the conveyor belt **30**. The conveyor belt **30** and the pressing belt **40** are pressed together to form the pressing region **O** where the foil is sandwiched between the pressing surface **41** of the pressing belt **40** and the carrying surface **31** of the conveyor belt **30**. The foil then moves towards the second common roller **60** along with the pressing belt **40** and the

conveyor belt **30**. During movement of the foil from the first common roller **50** to the second common roller **60**, the foil will pass through two clamping portions **221**. The two first pressing rollers **2214** may press the foil, squeezing out the moisture carried by the foil. The two second pressing rollers **2215** may also press the foil, squeezing out the moisture carried by the foil. In essence, as the foil moves from the first common roller **50** to the second common roller **60**, the foil undergoes two stages of moisture squeezing.

[0053] When the foil reaches the second common roller **60**, the foil will rotate around the second common roller **60** along with the conveyor belt **30** and the pressing belt **40**. The foil continues to move towards the third common roller **70** along with the conveyor belt **30** and the pressing belt **40**. The foil is sandwiched between the pressing surface **41** of the pressing belt **40** and the carrying surface **31** of the conveyor belt **30**. When the foil passes through the blow nozzle **232**, the airflow blown from the blow nozzle **232** will pass through the ventilation hole **43** of the pressing belt **40** and reach a position between the pressing surface **41** of the pressing belt **40** and the foil, thereby drying any remaining moisture between the foil and the pressing belt **40**. This reduces an adhesive force between the foil and the pressing belt **40** due to moisture, facilitating the subsequent disengagement of the foil from the pressing belt **40**. Since the isolation plate **240** and the separation member **230** are respectively disposed at two opposite sides of the pressing belt **40**, when the blow nozzle **232** of the separation member **230** blows air towards the pressing belt **40**, some water droplets on the pressing belt **40** may be blown towards the isolation plate **240** and drip along a surface of the isolation plate. Therefore, the isolation plate **240** helps to prevent water droplets from being blown towards part of the conveyor belt **30** and part of the pressing belt **40** that are between the first common roller **50** and the second common roller **60**, improving the dewatering efficiency of the dewatering member **220**.

[0054] When the foil reaches the third common roller **70** along with the conveyor belt **30** and the pressing belt **40** and the foil rotates around the third common roller **70** along with the conveyor belt **30**, the conveyor belt **30** will disengage from the third common roller **70**, and the part of the conveyor belt **30** in the pressing region O will disengage from the part of the pressing belt **40** in the pressing region O. The foil will separate from the pressing belt **40** and continue to move towards the conveying end point S2 of the conveying device **100** along with the conveyor belt **30**. When the foil moves to the conveying end point S2 of the conveying device **100** along with the conveyor belt **30**, the rotary brush **90** can cause the foil to separate from the conveyor belt **30** at an edge of the rotary brush **90**, thus driving the entire foil to disengage from the conveyor belt **30** and slide along the rotary brush **90** into the collecting device **300**.

[0055] Referring to FIG. 8 and FIG. 9, FIG. 8 is a schematic structural view of the collecting device of the foil recovery apparatus in FIG. 1, viewed from a first direction, and FIG. 9 is a schematic structural view of the collecting device in FIG. 8, viewed from a second direction. The collecting device **300** includes a storage bin **310**, a carrying platform **320**, a recovery member **360**, and a cutting member **370**. The carrying platform **320**, the cutting member **370**, the storage bin **310**, and the recovery member **360** are sequentially connected.

[0056] The storage bin **310** includes a bottom plate **311**, two side plates **312**, a pushing plate **313**, two sliding rails **314**, and a switch driving member **315**. The bottom plate **311** has a receiving surface **3111** and a transition surface **3112**. The receiving surface **3111** and the transition surface **3112** are opposite to each other in a thickness direction of the bottom plate **311**. The two side plates **312** protrude from the receiving surface **3111** of the bottom plate **311** and extend in a direction away from the receiving surface **3111**. An included angle is defined between the receiving surface **3111** and each of the two side plates **312**. In a width direction of the storage bin **310**, the two side plates **312** are opposite to each other. The two side plates **312** and the bottom plate **311** define a receiving cavity **316**. In a length direction of the storage bin **310**, a first opening **3161** and a second opening **3162** are defined at intervals between the two side plates **312**. The first opening **3161** and the second opening **3162** are respectively disposed at two opposite sides of the receiving cavity **316**.

and are in communication with the receiving cavity **316**.

[0057] In this embodiment, the pushing plate **313** is disposed at the second opening **3162**. The pushing plate **313** includes an abutting surface **3131** and a sliding surface **3132**. The abutting surface **3131** and the sliding surface **3132** are opposite to each other in a thickness direction of the pushing plate **313**. The sliding surface **3132** of the pushing plate **313** defines two sliding grooves **3133**. The two sliding grooves **3133** are spaced apart from each other in a width direction of the pushing plate **313**. Each sliding groove **3133** extends in the second direction.

[0058] It may be noted that two sliders **3134** may protrude from the abutting surface **3131** of the pushing plate **313**, and each of the two sliders **3134** defines the sliding groove **3133**. Alternatively, the two sliding grooves **3133** may be directly defined on the sliding surface **3132** of the abutting surface **3131**. The disclosure does not impose any specific limitations on this.

[0059] In this embodiment, the two sliding rails **314** are disposed outside the receiving cavity **316**. In a width direction of the collecting device **300**, the two sliding rails **314** are disposed at two opposite sides of the receiving cavity **316**, respectively. In the first direction, multiple sliding rails **314** are disposed at one side of the second opening **3162** away from the first opening **3161**. Each of the two sliding rails **314** protrudes from the receiving surface **3111** of the bottom plate **311** and extends in a direction away from the receiving surface **3111**. Both of the two sliding rails **314** extend in the second direction.

[0060] The pushing plate **313** is slidably connected to the two sliding rails **314** through the two sliding grooves **3133**. The switch driving member **315** includes a drive shaft **3151**. The drive shaft **3151** is connected to the pushing plate **313**. The drive shaft **3151** is configured to drive the two sliding grooves **3133** of the pushing plate **313** to move along the two sliding rails **314**. In other words, the drive shaft **3151** is configured to drive the pushing plate **313** to move in the second direction. In the second direction, the pushing plate **313** can cover the second opening **3162** when the pushing plate **313** moves towards the bottom plate **311**, and the pushing plate **313** can expose the second opening **3162** when the pushing plate **313** moves away from the bottom plate **311**. In this embodiment, the switch driving member **315** is a switch cylinder. In other embodiments, the switch driving member **315** may be a linear motor. The disclosure does not impose specific limitations on this.

[0061] In the first direction, the storage bin **310** is disposed at one side of the rotary brush **90** away from the conveyor belt **30**. In the second direction, the storage bin **310** is disposed at one side of the rotary brush **90** away from the second roller set **M2**. The storage bin **310** is connected to the base **400**.

[0062] Referring to FIG. **10** and FIG. **11**, FIG. **10** is a schematic structural view of the carrying platform in FIG. **8**, and FIG. **11** is an exploded schematic structural view of the carrying platform in FIG. **10**. The carrying platform **320** includes a carrying member **330**, a pushing member **340**, and two guiding members **350**. The carrying member **330** includes a carrying plate **331**, a pressing plate **332**, and a mounting plate **333**. The carrying plate **331** includes a carrying surface **3311** and a mounting surface **3312**. The carrying surface **3311** is opposite to the mounting surface **3312** in a thickness direction of the carrying plate **331**. The pressing plate **332** is connected to one end of the carrying plate **331** in a length direction of the carrying plate **331**. The pressing plate **332** protrudes from the mounting surface **3312** of the carrying plate **331** and extends in a direction away from the mounting surface **3312**. An included angle is defined between the pressing plate **332** and the mounting surface **3312**. The carrying plate **331** and the pressing plate **332** form an L-shaped structure. The pressing plate **332** has a pressing surface **3321** and a pushing surface **3322**. The pressing surface **3321** is opposite to the pushing surface **3322** in a thickness direction of the pressing plate **332**. The mounting plate **333** protrudes from the mounting surface **3312** of the carrying plate **331** and extends in a direction away from the mounting surface **3312**. An included angle is defined between the mounting plate **333** and the mounting surface **3312**. In a length direction of the carrying platform **320**, the mounting plate **333** is disposed at one side of the

pressing surface **3321** of the pressing plate **332** away from the pushing surface **3322**, and the mounting plate **333** is spaced apart from the pressing plate **332**. The mounting plate **333** defines a drive hole **3331** and two balance holes **3332**. All the drive hole **3331** and the two balance holes **3332** extend through two surfaces of the mounting plate **333** that are opposite to each other in a thickness direction of the mounting plate **333**. In a width direction of the carrying platform **320**, the two balance holes **3332** are symmetrically disposed at two opposite sides of the drive hole **3331**, respectively.

[0063] The pushing member **340** includes a pushing rod **341**. In this embodiment, the pushing member **340** is a pushing rod cylinder. In other embodiments, the pushing member **340** may be a linear motor. The disclosure does not impose specific limitations on this.

[0064] Referring to FIG. **12**, FIG. **12** is a partial exploded schematic structural view of the carrying platform in FIG. **11**. Each guiding member **350** includes a guiding rod **351**, a sleeve **352**, and a linear bearing **353**. The linear bearing **353** has a first end face **3531** and a second end face **3532**. The first end face **3531** is opposite to the second end face **3532** in a thickness direction of the linear bearing **353**. The linear bearing **353** defines a through hole **3533**. In the thickness direction of the linear bearing **353**, the through hole **3533** extends through both the first end face **3531** and the second end face **3532**.

[0065] The sleeve **352** defines a through hole **3521**. The through hole **3521** extends through two surfaces of the sleeve **352** that are opposite to each other in a length direction of the sleeve **352**. A diameter of the through hole **3533** of the linear bearing **353** is larger than that of the through hole **3521** of the sleeve **352**. The sleeve **352** of each guiding member **350** is connected to the second end face **3532** of the linear bearing **353**. The through hole **3521** of the sleeve **352** is coaxially aligned with the through hole **3533** of the linear bearing **353**. The guiding rod **351** of each guiding member **350** sequentially extends through the sleeve **352** and the linear bearing **353**. The guiding rod **351** is movable back and forth through the through hole **3521** of the sleeve **352** and the through hole **3533** of the linear bearing **353**. In other embodiments, each guiding member **350** may omit the sleeve **352**, and only include the guiding rod **351** and the linear bearing **353**.

[0066] In the first direction, the carrying platform **320** is disposed at one side of the receiving cavity **316** away from the pushing plate **313**. Specifically, the carrying member **330** is slidably connected to the base **400**. The pushing member **340** is connected to the base **400**. The pushing member **340** is movably connected to the pressing plate **332** of the carrying member **330**. In the first direction, the pressing plate **332** is opposite to the pushing plate **313**. In the width direction of the collecting device **300**, the pressing plate **332** of the carrying platform **320** is limited between the two side plates **312**. The mounting plate **333** is disposed at one side of the pressing plate **332** away from the second opening **3162**. In the second direction, the carrying plate **331** of the carrying platform **320** is spaced apart from the bottom plate **311** of the storage bin **310**.

[0067] The pushing rod **341** of the pushing member **340** extends through the drive hole **3331** of the mounting plate **333** and is connected to the pushing surface **3322** of the pressing plate **332**. The pushing rod **341** of the pushing member **340** is configured to drive the pressing plate **332** to move back and forth in the first direction within the receiving cavity **316** of the storage bin **310**. In the width direction of the collecting device **300**, the two guiding members **350** are disposed at two opposite sides of the pushing member **340**, respectively. The first end face **3531** of the linear bearing **353** of each guiding member **350** is fixed to the pushing surface **3322** of the pressing plate **332**. The sleeve **352** extends through one of the balance holes **3332** of the mounting plate **333** and is connected to a wall of the balance hole **3332**. The guiding rod **351** sequentially extends through the sleeve **352** and the linear bearing **353** and is connected to the pushing surface **3322** of the pressing plate **332**.

[0068] It may be understood that the pushing member **340** is capable of driving the pressing plate **332** to move, within the receiving cavity **316**, from the first opening **3161** towards the pushing plate **313**, such that the carrying plate **331** can cover the receiving cavity **316**. The pushing member

340 is also capable of driving the pressing plate **332** to move, within the receiving cavity **316**, away from the pushing plate **313**, such that the carrying plate **331** can expose the receiving cavity **316**. During movement of the pressing plate **332** driven by the pushing member **340**, the guiding rod **351** of each guiding member **350** can move through the through hole **3521** of the sleeve **352** and the through hole **3533** of the linear bearing **353**. The two guiding members **350** are symmetrically located at two opposite sides of the pushing member **340**, respectively. The two guiding members **350** enable the pressing plate **332** to maintain balanced force distribution during movement.

[0069] Referring to FIG. **8** and FIG. **9**, the recovery member **360** includes a recovery basket **361** and multiple fixing portions **362**. The recovery basket **361** includes an inner surface **3611** and an outer surface **3612**. The inner surface **3611** is opposite to the outer surface **3612** in a thickness direction of the recovery basket **361**. The inner surface **3611** defines a recovery opening **363**. The multiple fixing portions **362** are fixed to the outer surface **3612** of the recovery member **360** and are arranged around the recovery opening **363** at intervals. The fixing portions **362** are used to secure a recovery bag. The recovery basket **361** is fixed to the bottom plate **311**. In the first direction, the recovery opening **363** is disposed at one side of the second opening **3162** away from the receiving cavity **316**. In this embodiment, the recovery basket **361** is fixed to the transition surface **3112** of the bottom plate **311**.

[0070] Referring to FIG. **13**. FIG. **13** is a schematic structural view of the cutting member in FIG. **8**. The cutting member **370** includes a fixed frame **371**, a connecting shaft **372**, and multiple scraping blades **373**. The fixed frame **371** includes a first plate body **3711**, a second plate body **3712**, and two mounting portions **3713**. The first plate body **3711** includes a first face and a second face. The first face is opposite to the second face in a thickness direction of the first plate body **3711**. The two second plate bodies **3712** are connected to two opposite ends of the first plate body **3711** in a length direction of the first plate body **3711**, respectively. The two second plate bodies **3712** each protrude from the first face of the first plate body **3711** and extend in a direction away from the first face. An included angle is defined between the first face and each of the two second plate bodies **3712**. The two mounting portions **3713** are connected to the two second plate bodies **3712**, respectively. Two opposite ends of the connecting shaft **372** are connected to the two mounting portions **3713**, respectively. The connecting shaft **372** extends in a length direction of the cutting member **370**. It may be understood that one end of the connecting shaft **372** is indirectly connected to one of the two second plate bodies **3712** via a mounting portion **3713**, and another end of the connecting shaft **372** is indirectly connected to another one of the two second plate bodies **3712** via another mounting portion **3713**.

[0071] In this embodiment, each scraping blade **373** includes a limiting portion **3731** and a scraping portion **3732**. The limiting portion **3731** and the scraping portion **3732** of each scraping blade **373** are connected to each other. An included angle is defined between an extension direction of the limiting portion **3731** and an extension direction of the scraping portion **3732**, where the included angle is less than 180°. Each limiting portion **3731** defines a connection hole **3733** at one end of the limiting portion **3731** close to the scraping portion **3732**. A scraping end **3734** is disposed at one end of each scraping portion **3732** away from the limiting portion **3731**. Each scraping end **3734** is a pointed tooth.

[0072] Each scraping blade **373** is sleeved on the connecting shaft **372** through the connection hole **3733**, and each scraping blade **373** is capable of rotating around the connecting shaft **372**. It may be understood that each scraping blade **373** is rotatably connected to the connecting shaft **372**. The multiple scraping blades **373** are spaced apart from each other in an extending direction of the connecting shaft **372**. An included angle defined between the limiting portion **3731** and the scraping portion **3732** of each scraping blade **373** is oriented towards the same side of the fixed frame **371** in a width direction of the fixed frame **371**. During rotation of the multiple scraping blades **373** around the connecting shaft **372**, the first plate body **3711** of the fixed frame **371** limits the limiting portion **3731** of each scraping blade **373**, ensuring that the included angle between the

limiting portion **3731** and the scraping portion **3732** of each scraping blade **373** is always oriented towards the same side of the fixed frame **371** in the width direction of the fixed frame **371** [0073] It may be noted that, in other embodiments, the multiple scraping blades **373** may be integrally connected.

[0074] The cutting member **370** is fixed to the base **400** and is located between the storage bin **310** and the carrying platform **320**. In the second direction, the cutting member **370** is disposed at one side of the carrying plate **331** away from the pressing plate **332**. The connecting shaft **372** of the cutting member **370** extends in the width direction of the collecting device **300**. In the first direction, the included angle defined between the limiting portion **3731** and the scraping portion **3732** of each of the multiple scraping blades **373** is oriented towards the storage bin **310**. The scraping end **3734** of each of the multiple scraping blades **373** is in contact with the carrying surface **3311** of the carrying plate **331**.

[0075] Referring to FIG. 1, the collecting device **300** has an initial state. In the initial state, the carrying platform **320** is positioned at an initial position. Specifically, in the initial state, the pressing plate **332** of the carrying platform **320** is disposed at the first opening **3161** of the storage bin **310**. When the foil slides into the collecting device **300** along the rotary brush **90**, the foil will fall into the storage bin **310** of the collecting device **300**.

[0076] When the foil in the storage bin **310** accumulates to a certain amount, the pushing rod **341** of the pushing member **340** will push the pressing plate **332** to move towards the pushing plate **313**. During movement of the pressing plate **332** within the receiving cavity **316** of the storage bin **310**, the pressing plate **332** can push the foil in the storage bin **310** to the pushing plate **313**. As the pressing plate **332** moves towards the pushing plate **313**, the pressing plate **332** can drive the carrying plate **331** to move towards the storage bin **310**, causing the carrying plate **331** to cover the receiving cavity **316** of the storage bin **310**. When the foil slides into the collecting device **300** along the rotary brush **90**, the foil will fall onto the carrying plate **331** of the carrying platform **320**. When the pressing plate **332** reaches near the pushing plate **313**, the pressing plate **332** continues to move towards the pushing plate **313** to press the foil between the pressing plate **332** and the pushing plate **313**, causing the foil to be compressed into a foil block after being pressed.

Subsequently, the switch driving member **315** controls the pushing plate **313** to move upward to expose the second opening **3162**. The pushing rod **341** of the pushing member **340** continues to push the pressing plate **332** to move towards the recovery member **360**, so that the pressing plate **332** can push the foil block, formed by compressing, into the recovery opening **363**, allowing the foil block to fall into the recovery bag secured by the fixing portion **362** of the recovery member **360**, achieving the recovery of the foil. Afterward, the collecting device **300** returns to the initial state, with the carrying platform **320** returning to the initial position.

[0077] During the process of the carrying platform **320** returning to the initial position, because the scraping ends **3734** of the multiple scraping blades **373** of the cutting member **370** are in contact with the carrying surface **3311** of the carrying plate **331**, and the included angle defined between the limiting portion **3731** and the scraping portion **3732** of each of the multiple scraping blades **373** is oriented towards the storage bin **310**, the foil on the carrying plate **331**, when passing through the cutting member **370**, will be scraped off by the scraping ends **3734** of the multiple scraping blades **373**, causing the foil to fall into the storage bin **310** from the carrying plate **331**.

[0078] It may be understood that the foil recovery apparatus **1000** provided in the embodiments of the disclosure includes the conveying device **100**, where the conveyor belt **30** of the conveying device **100** is capable of transporting the foil to the second roller set **M2**. When the conveyor belt **30** conveys the foil to move around the second roller set **M2**, the conveyor belt **30** and the pressing belt **40** are pressed together to form the pressing region **O**. The foil is sandwiched between the pressing belt **40** and the conveyor belt **30**, and the foil will move through the dewatering member **220**, which can dewater the foil. Subsequently, the foil moves through the blow nozzle **232**, which can remove the water between the foil and the pressing belt **40** to reduce the adhesive force

between the foil and the pressing belt **40**. The foil continues to move along with the conveyor belt **30** towards the collecting device **300**, and the foil will be compressed and collected after moving through the collecting device **300**. The collecting device **300** is capable of automatically collecting the dewatered foil. Therefore, the foil recovery apparatus **1000** provided in the embodiments of the disclosure can remove the moisture from the foil during the recovery process and collect the dewatered foil, thereby improving the foil recovery efficiency.

[0079] The embodiments of the disclosure are described in detail above, specific examples are used herein to describe the principle and implementation manners of the disclosure. The description of the above embodiments is merely used to help understand the method and the core idea of the disclosure. Meanwhile, those of ordinary skill in the art may make modifications to the specific implementation manners and the application scope according to the idea of the disclosure. In summary, the contents of the specification should not be construed as limiting the disclosure.

Claims

1. A foil recovery apparatus, comprising a base, a conveying device, and a collecting device, wherein the conveying device comprises a conveyor belt and a first roller set, the first roller set is connected to the base and comprises a first conveying roller and a second conveying roller, the conveyor belt has a carrying surface, the first conveying roller is opposite to the second conveying roller in a first direction, the conveyor belt is driven around the first conveying roller and the second conveying roller for transmission, and the first direction is a conveying direction of the conveyor belt; the collecting device comprises a storage bin and a carrying platform, wherein the storage bin comprises a pushing plate and defines a receiving cavity, the storage bin defines a first opening, the pushing plate and the first opening are located on two opposite sides of the receiving cavity in the first direction, respectively, and the carrying platform comprises a pressing plate; and in the first direction, the storage bin is disposed at one side of the second conveying roller away from the first conveying roller, the carrying platform is disposed at one side of the storage bin where the first opening is defined, the pressing plate is opposite to the pushing plate, the conveying device is configured to convey a foil into the receiving cavity, and the pressing plate is operable to enter the receiving cavity through the first opening to compress the foil within the receiving cavity along with the pushing plate.
2. The foil recovery apparatus according to claim 1, wherein the conveying device further comprises a pressing belt and a second roller set, wherein the second roller set is connected to the base and located between the first conveying roller and the second conveying roller, the conveyor belt is driven around the second roller set for transmission, the pressing belt is driven around the second roller set for transmission, the pressing belt is configured to perform transmission in a second direction, and the conveyor belt is in contact with the pressing belt to form a pressing region when the conveyor belt is driven around the second roller set for transmission.
3. The foil recovery apparatus according to claim 2, further comprising a dewatering assembly, wherein the dewatering assembly comprises two clamping portions, both of the two clamping portions are connected to the base and arranged in parallel, the pressing region is operable to pass through the two clamping portions, the foil is sandwiched and clamped by part of the conveyor belt in the pressing region and part of the pressing belt in the pressing region when the conveyor belt conveys the foil to enable the foil to move around the second roller set, the part of the conveyor belt in the pressing region and the part of the pressing belt in the pressing region disengage from each other when the part of the conveyor belt in the pressing region disengages from the second roller set to allow the part of the conveyor belt in the pressing region to move in the first direction and the part of the pressing belt in the pressing region to move in the second direction, and the second direction is perpendicular to the first direction.
4. The foil recovery apparatus according to claim 3, wherein the second roller set comprises a first

common roller, a second common roller, a third common roller, and two connecting rollers, the first common roller and the third common roller are opposite to each other in the first direction and located between the first conveying roller and the second conveying roller, the second common roller is spaced apart from both the first common roller and the third common roller in the second direction, an orthographic projection of the second common roller on the conveyor belt is located between an orthographic projection of the first common roller on the conveyor belt and an orthographic projection of the third common roller on the conveyor belt, and in the second direction, one of the two connecting rollers is spaced apart from and arranged opposite to the first common roller, and another one of the two connecting rollers is spaced apart from and arranged opposite to the second common roller; all the first conveying roller, the second conveying roller, and the second common roller are rotatable in a same direction, and all the first common roller, the third common roller, and the two connecting rollers are rotatable in a direction opposite a direction in which the second conveying roller is rotatable; the conveyor belt is arranged, through the first conveying roller and the first common roller, around the second common roller disposed in the second direction, and then arranged, through the third common roller, around the second conveying roller in the first direction, to achieve cyclic transmission; and the pressing belt is arranged, through the first common roller, around the second common roller disposed in the second direction, and then arranged, through the third common roller, around the two connecting rollers disposed in the second direction, to achieve cyclic transmission.

5. The foil recovery apparatus according to claim 4, wherein the dewatering assembly further comprises a blow nozzle, the blow nozzle has an outlet, and the outlet is disposed on one side of the blow nozzle in a width direction of the blow nozzle; and two opposite ends of the blow nozzle are connected to the base, and the blow nozzle is spaced apart from the two clamping portions in the first direction, wherein when the pressing region passes through the two clamping portions in the second direction, and then passes through the second common roller and reaches the blow nozzle, the outlet faces towards the pressing region.

6. The foil recovery apparatus according to claim 5, wherein the dewatering assembly further comprises an isolation plate mounted to the base, the isolation plate is located between the two clamping portions and the blow nozzle in the first direction, and two surfaces of the isolation plate, opposite each other in a thickness direction of the isolation plate, faces towards the two clamping portions and the blow nozzle, respectively.

7. The foil recovery apparatus according to claim 6, wherein each of the two clamping portions comprises two first swinging arms and a first pressing roller, the two first swinging arms are opposite to each other in a width direction of the foil recovery apparatus, one end of each of the two first swinging arms is rotatably connected to the base, and the first pressing roller is located between and connected to another end of one of the two first swinging arms and another end of another one of the two first swinging arms; and the two first swinging arms of each of the two clamping portions are rotatable to drive the first pressing roller to move towards or away from the pressing region.

8. The foil recovery apparatus according to claim 7, wherein each of the two clamping portions further comprises two second swinging arms and a second pressing roller, the two second swinging arms are opposite to each other in the width direction of the foil recovery apparatus, one end of each of the two second swinging arms is rotatably connected to the base, and the second pressing roller is located between and connected to another end of one of the two second swinging arms and another end of another one of the two second swinging arms, and the second pressing roller is spaced apart from the first pressing roller in the second direction; and the two second swinging arms of each of the clamping portions are rotatable to drive the second pressing roller to move towards or away from the pressing region.

9. The foil recovery apparatus according to claim 1, wherein the conveying device further comprises a rotary brush connected to the base, the rotary brush is located between the conveyor

belt and the receiving cavity in the first direction, and the rotary brush is rotatable in a same direction as the second conveying roller; and the rotary brush is configured to separate the foil from the conveyor belt to make the foil slide along the rotary brush into a receiving cavity of the collecting device.

10. The foil recovery apparatus according to claim 2, wherein the carrying platform further comprises a carrying plate and a pushing member, the pressing plate protrudes from one end of the carrying plate in the first direction, and an included angle is defined between the pressing plate and the carrying plate; and the carrying plate is slidably connected to the base, and the pushing member is connected to the base and the pressing plate, wherein the pushing member is configured to drive the pressing plate to move, within the receiving cavity, from the first opening towards the pushing plate to cover the receiving cavity, or to drive the pressing plate to move, within the receiving cavity, away from the pushing plate to expose the receiving cavity.

11. The foil recovery apparatus according to claim 10, wherein the storage bin further defines a second opening, the first opening and the second opening are located at two opposite ends of the receiving cavity in the first direction, respectively, and the pushing plate is disposed at the second opening; the storage bin further comprises two sliding rails and a switch driving member, wherein the two sliding rails extend in the second direction, the pushing plate defines two sliding grooves that extend in the second direction, and the pushing plate is slidably connected to the two sliding rails via the two sliding grooves; and the switch driving member is mounted to the base, and the switch driving member is configured to drive the pushing plate to move in the second direction to expose or cover the second opening.

12. The foil recovery apparatus according to claim 11, wherein the carrying platform further comprises a mounting plate disposed at one side of the pressing plate, the mounting plate is spaced apart from and opposite to the pressing plate in the first direction and defines a drive hole and two balance holes, and the two balance holes are symmetrically disposed at two opposite sides of the drive hole in a width direction of the foil recovery apparatus; the carrying platform further comprises two guiding members, wherein each of the two guiding member comprises a guiding rod, a sleeve, and a linear bearing, and the sleeve defines a through hole, and the linear bearing defines a through hole; and the linear bearing of each of the two guiding members is connected to the pressing plate, the sleeves of the two guiding members extend through the two balance holes, respectively, the sleeve and the linear bearing of each of the two guiding member are connected to and coaxially arranged with each other, and the guiding rod of each of the two guiding members extends through the sleeve and the linear bearing in sequence, abuts against the pressing plate, and is capable of moving back and forth along a wall of the through hole of the sleeve and a wall of the through hole of the linear bearing.

13. The foil recovery apparatus according to claim 12, wherein the collecting device further comprises a cutting member, the cutting member comprises a connecting shaft and a plurality of scraping blades, each of the plurality of scraping blades has a scraping end, and the plurality of scraping blades are rotatably connected to the connecting shaft and spaced apart from each other in the width direction of the foil recovery apparatus; and in the second direction, the cutting member is disposed at one side of the carrying plate away from the receiving cavity, two opposite ends of the connecting shaft are connected to the base, the scraping end of each of the plurality of scraping blades is in contact with the carrying plate, the pushing member is configured to drive the carrying plate to move away from the pushing plate, and the scraping ends of the plurality of scraping blades are capable of scraping the foil carried by the carrying plate into the receiving cavity.

14. The foil recovery apparatus according to claim 13, wherein the cutting member further comprises a fixed frame, the fixed frame comprises a first plate body and two second plate bodies, and both of the two second plate bodies protrude from a same surface of the first plate body and are disposed at two opposite ends of the first plate body, respectively; each of the plurality of scraping blades comprises a limiting portion and a scraping portion, wherein one end of the limiting portion

is connected to one end of the scraping portion, an included angle is defined between the limiting portion and the scraping portion, the scraping end is disposed on one end of the scraping portion away from the limiting portion, and the limiting portion defines a connection hole at one end of the limiting portion close to the scraping portion; and two opposite ends of the connecting shaft are connected to the two second plate bodies, respectively, each of the plurality of scraping blade is sleeved on the connecting shaft via the connection hole, and the included angle between the limiting portion and the scraping portion of each of the plurality of scraping blades is oriented towards the storage bin.

15. The foil recovery apparatus according to claim 11, wherein the collecting device further comprises a recovery member, the recovery member comprises a recovery basket and a plurality of fixing portions, the recovery basket comprises an inner surface and an outer surface, the inner surface and the outer surfaces are opposite to each other in a thickness direction of the recovery basket, the inner surface defines a recovery opening, the plurality of fixing portions are fixed to the outer surface of the recovery member and arranged around the recovery opening at intervals, the recovery basket is connected to the storage bin, and the recovery opening is disposed at one side of the second opening away from the receiving cavity in the first direction.

16. The foil recovery apparatus according to claim 2, wherein the second roller set comprises a first common roller, a second common roller, a third common roller, and two connecting rollers; and all the first conveying roller, the second common roller, and the second conveying roller are rotatably connected to a connecting surface of the conveyor belt opposite the carrying surface, and both the first common roller and the third common roller are rotatably connected to the carrying surface of the conveyor belt.

17. The foil recovery apparatus according to claim 1, wherein the conveyor belt defines a plurality of air holes that are evenly distributed, each of the plurality of air holes extends through the carrying surface and a connecting surface of the conveyor belt opposite the carrying surface.

18. The foil recovery apparatus according to claim 2, wherein the pressing belt defines a plurality of ventilation holes that are evenly distributed, each of the plurality of ventilation holes extends through two surfaces of the pressing belt that are opposite to each other in a thickness direction of the pressing belt.

19. The foil recovery apparatus according to claim 2, wherein the second roller set comprises a first common roller, a second common roller, a third common roller, and two connecting rollers; and a rotational direction of the first conveying roller, a rotational direction of the second conveying roller, and a rotational direction of the second common roller are the same as each other.

20. The foil recovery apparatus according to claim 1, wherein the second roller set comprises a first common roller, a second common roller, a third common roller, and two connecting rollers; and a rotational direction of the first common roller, a rotational direction of the third common roller, and a rotational direction of each of the two connecting rollers each are opposite to the rotational direction of the second conveying roller.
