

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279611

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Advey; Alexander Joseph

RETRACTABLE SEAL SHROUD

Abstract

A connector includes a housing and a seal shroud. The housing includes a seal positioned along an exterior surface of the housing. The seal shroud is adjacent to the housing and is movable between a first position and a second position. The seal shroud at least partially covers the seal of the housing in the second position. The seal shroud exposes the seal to an interior facing surface of a second connector in the first position. The second connector is configured to couple with the connector.

Inventors: Advey; Alexander Joseph (Ann Arbor, MI)

Applicant: Yazaki North America, Inc. (Canton, MI)

Family ID: 90790811

Assignee: Yazaki North America, Inc. (Canton, MI)

Appl. No.: 19/213632

Filed: May 20, 2025

Related U.S. Application Data

parent US continuation 17969319 20221019 parent-grant-document US 12334671 child US 19213632

Publication Classification

Int. Cl.: H01R13/52 (20060101); H01R13/516 (20060101); H01R13/639 (20060101)

U.S. Cl.:

CPC H01R13/5213 (20130101); H01R13/516 (20130101); H01R13/5219 (20130101); H01R13/639 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a Continuation of U.S. patent application Ser. No. 17/969,319, filed Oct. 19, 2022, the entire disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

[0002] This application relates generally to wire electrical connector assemblies and, more specifically, to seal shrouds for insulating seals on the connector assemblies.

[0003] Automobiles may contain a number of seals provided around an outer surface of electrical components. Such seals may surround (or partially surround) a juncture or connection between two electrical components, thereby protecting or insulating the juncture from external elements (such as rain or water, particulates, and so forth).

SUMMARY

[0004] Some seals for electrical components may include seal shrouds. For example, the seals may be protected by a seal shroud provided axially around the seal. The seal shrouds may be formed within a housing of the electrical component, where the seal shrouds may be fixed relative to the seal. As such, the housing and seal shroud may define a larger construction than needed, which can be difficult for packaging or installation into tight spaces of the automobiles.

[0005] In one aspect, this disclosure is directed to a connector assembly. The connector assembly includes a first connector and a second connector. The first connector includes a first locking mechanism. The second connector includes a housing and a seal shroud. The housing includes a seal positioned along an exterior surface of the housing. The seal shroud surrounds the housing and includes a second locking mechanism configured to mate with the first locking mechanism. The seal shroud is movable between a first position and a second position while the first locking mechanism is mated with the second locking mechanism. The seal shroud at least partially covers the seal of the housing in the first position and the seal shroud exposes the seal to an interior facing surface of the first connector in the second position.

[0006] In some embodiments, the first locking mechanism includes a tab extending along an exterior surface of the first connector. The second locking mechanism includes a protrusion extending along an interior surface of the seal shroud. In some embodiments, the seal shroud covers the seal when the first locking mechanism is unmated from the second locking mechanism. In some embodiments, the housing includes a track having an inclined portion to urge the seal shroud in the second position. A notch is configured to secure the seal shroud in the second position to cover the seal when the second connector is unmated from the first connector.

[0007] In some embodiments, the second connector further includes a track provided along at least a portion of the housing. The seal shroud is repositionable along the track between the first position and the second position. In some embodiments, the housing includes a notch extending along an exterior surface of the housing. The housing defines a length extending from an end of the second connector and the notch. The seal shroud is repositionable between the first position and the second position along the length of the housing. In some embodiments, the seal is peripherally provided around the second connector. The seal shroud is slidably repositionable along a longitudinal axis

between a forward position and a rearward position. In some embodiments, the housing includes a second seal positioned along an interior facing surface of the housing. The second seal is configured to engage an electrical wire.

[0008] In some embodiments, the housing includes a notch extending along an exterior surface of the housing. The notch is configured to abut the seal shroud to axially reposition to cover the seal when the second connector is positioning from the second position to the first position. In some embodiments, the first connector includes a first alignment port and the second connector includes a second alignment port. The first alignment port axially aligned with the second alignment port when the first connector is mated to the second connector. The first and second alignment ports are configured to receive a fastener therethrough.

[0009] In another aspect, this disclosure is directed to a connector assembly. The connector assembly includes a second connector configured to mate with a first connector. The first connector includes a first locking mechanism. The second connector includes a housing and a seal shroud. The housing includes a seal positioned along an exterior surface of the housing. The seal shroud surrounds the housing and includes a second locking mechanism configured to mate with the first locking mechanism. The seal shroud is movable between a first position and a second position while the first locking mechanism is mated with the second locking mechanism. The seal shroud at least partially covers the seal of the housing in the first position and the seal shroud exposes the seal to an interior facing surface of the first connector in the second position.

[0010] In some embodiments, the seal shroud covers the seal when the first locking mechanism is unmated from the second locking mechanism. In some embodiments, the first locking mechanism includes a tab extending along an exterior surface of the first connector. The second locking mechanism includes a protrusion extending along an interior surface of the seal shroud. In some embodiments, the first connector includes a first alignment port and the second connector includes a second alignment port. The first alignment port axially aligned with the second alignment port when the first connector is mated to the second connector. The first and second alignment ports are configured to receive a fastener therethrough. In some embodiments, the housing includes a notch extending along an exterior surface of the housing. The notch is configured to abut the seal shroud to axially reposition to cover the seal when the second connector is positioning from the second position to the first position.

[0011] In some embodiments, the seal is peripherally provided around the second connector. The seal shroud is slidably repositionable along a longitudinal axis between a forward position and a rearward position. In some embodiments, the housing includes a track having an inclined portion to urge the seal shroud in the second position. A notch is configured to secure the seal shroud in the second position to cover the seal when the second connector is unmated from the first connector. In some embodiments, the second connector further includes a track provided along at least a portion of the housing. The seal shroud is repositionable along the track between the first position and the second position.

[0012] In yet another aspect, this disclosure is directed to a connector assembly. The connector assembly includes a first connector and a second connector. The second connector includes a housing and a movable component. The housing includes a seal positioned along an exterior surface of the housing. The movable component is at least partially surrounding the housing. The movable component is positionable between a first position and a second position. The movable component is configured to partially cover the seal when the movable component is in the second position. The first position is a position of the movable component distal the first connector and the second position is a position of the movable component proximate the first connector.

[0013] In some embodiments, the first connector includes a first locking mechanism. The movable component is configured to engage the first locking mechanism when the first connector is mated with the second connector to maintain the position of the movable component over the seal.

[0014] This summary is illustrative only and is not intended to be in any way limiting. Other

aspects, inventive features, and advantages of the devices or processes described herein will become apparent in the detailed description set forth herein, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements.

Description

BRIEF DESCRIPTION OF THE FIGURES

[0015] The disclosure will become more fully understood from the following detailed description, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements, in which:

[0016] FIG. 1 is an exploded view of a connector assembly according to an exemplary embodiment.

[0017] FIG. 2 is a perspective view of the connector assembly of FIG. 1, shown in a mated position, according to an exemplary embodiment.

[0018] FIG. 3 is a perspective view of a first connector of the connector assembly of FIG. 1, according to an exemplary embodiment.

[0019] FIG. 4 is a cross-section view of the connector assembly of FIG. 2, according to an exemplary embodiment.

[0020] FIG. 5 is a perspective view the second connector of the connector assembly of FIG. 4, according to an exemplary embodiment.

[0021] FIG. 6 is a detailed perspective view of the second connector of the connector assembly of FIG. 4, shown without a seal shroud, according to an exemplary embodiment.

[0022] FIG. 7 is a perspective view of a seal shroud of the second connector of the connector assembly of FIG. 4, according to an exemplary embodiment.

[0023] FIG. 8 is a cross-section view of the second connector of the connector assembly of FIG. 4, according to an exemplary embodiment.

DETAILED DESCRIPTION

[0024] Before turning to the figures, which illustrate the exemplary embodiments in detail, it should be understood that the present application is not limited to the details or methodology set forth in the description or illustrated in the figures. It should also be understood that the terminology is for the purpose of description only and should not be regarded as limiting.

[0025] Referring to the FIGURES generally, the various exemplary embodiments disclosed herein relate to a connector assembly. The connector assembly includes a first connector and a second connector. The first connector includes an interface extending from an end of the first connector. The interface includes a protrusion extending outward from the interface. The second connector includes a housing formed about a body of the second connector. The housing may be positioned proximate an exterior of the second connector. A seal may be positioned around an exterior of the housing of the second connector. A seal shroud may be coupled to the second connector on an exterior portion relative to the housing. The seal shroud may be repositionable between a first position and a second position. The first position may be a position in which the seal shroud is positioned distal the first connector. The second position may be a position in which the seal shroud is positioned proximate the second connector. The seal shroud may be repositionable along a track. The track may extend along an exterior surface of the housing, where the track extends substantially parallel to an axis defined through a midpoint of the second connector. The seal shroud may include an interface positioned at an end of the seal shroud. When the first connector is mated with the second connector, the interface of the seal shroud may engage the protrusion of the first connector. When the first connector is repositioning from the mated position to an unmated position, the seal shroud may be engaged with the interface of the first connector until the seal shroud is positioned at an end of the track. As such, the seal may always be covered to prevent the

seal from becoming damaged.

[0026] Referring to FIGS. 1-3, a connector assembly **100** is shown, according to an exemplary embodiment. The connector assembly **100** may be used in a vehicle application, where the connector assembly **100** provides electrical energy therethrough. In some embodiments, the connector assembly **100** may be used for alternate applications and environments (e.g., industrial applications, home applications, or any other application or use case).

[0027] The connector assembly **100** may include a first connector **110** and a second connector **120**. The first connector **110** may be selectively coupled with the second connector **120**. In other embodiments, the first connector **110** may be fixedly coupled with the second connector **120** (e.g., the first connector **110** may be secured to the second connector **120** via a fastener, etc.). The connector assembly **100** may be configurable or movable between an unmated position and a mated position. As shown in FIG. 1, the connector assembly **100** is in the unmated position, where the first connector **110** is not coupled to the second connector **120**. As shown in FIG. 2, the connector assembly **100** is in the mated position, where the first connector **110** is coupled to the second connector **120**. When the connector assembly **100** is in the mated position, and as described in greater detail below, electrical energy may flow through the connector assembly **100**. Accordingly, when the connector assembly **100** is in the unmated position, electrical energy may not flow through the connector assembly. As will be discussed in greater detail herein, to mate the first connector **110** with the second connector **120**, the second connector **120** may be inserted into the first connector **110** along an axis. In other embodiments, the second connector **120** may be rotatable about an axis upon engaging the second connector **120** into the first connector **110** to secure or lock the connector assembly **100**.

[0028] The first connector **110** may be defined as a female connector, and the second connector **120** may be defined as a male connector. The female connector may include an aperture in which the male connector may be engaged within. Upon engagement of the male connector within the aperture, electrical energy may flow through the connector assembly. In some embodiments, the first connector **110** may be defined as a male connector, and the second connector **120** may be defined as a female connector. In still some embodiments, both the first and second connectors **110**, **120** may be male connectors that are received in a sleeve or coupling. In still some embodiments, both the first and second connectors **110**, **120** may be female connectors that receive a protrusion or corresponding male portion from an additional component.

[0029] Referring specifically to FIG. 2, the first connector **110** may include a device interface **210**. The device interface **210** may be an external interface provided at an end of the first connector **110**, proximate the second connector **120**. The device interface **210** may include a sidewall extending substantially outward from an end of the first connector **110**. The sidewall may define the aperture in which the second connector **120** may be received therein. In other embodiments, the device interface **210** may not include the sidewall, where instead the aperture is recessed into a body of the first connector **110**.

[0030] Referring specifically to FIG. 2-FIG. 4, the second connector **120** may include a housing **220**. The housing **220** may be defined by an exterior surface of the second connector **120**. The housing **220** may define a body of the second connector **120**. The housing **220** may extend along at least a portion of a length of the second connector **120**. In some embodiments, the housing **220** extends along an entire length of the second connector **120**. The housing **220** may include an internal passageway. The internal passageway may extend at least partially through the housing **220**. By way of example, the internal passageway may extend through an entire length of the housing **220**. The internal passageway may define a passage for which an electrical wire **230** may be provided therethrough. The electrical wire **230** may be one or more wire components that extend through the second connector **120** and deliver the flow of electrical energy through the connector assembly **100**.

[0031] The second connector **120** may further include a seal shroud **240**. The seal shroud **240** may

be coupled to the housing **220**. In other embodiments, the seal shroud **240** may be coupled to another component of the second connector **120** (e.g. electrical wire **230**, etc.). As will be described in greater detail herein, the seal shroud **240** may be slidably repositionable along the housing **220** between a first position and a second position. The first position may be a position where the seal shroud **240** abuts the device interface **210**. The second position may be a position where the seal shroud **240** is not positioned against the device interface **210**. By way of example, the second position may be any position of the seal shroud **240** where the seal shroud **240** is not positioned against the device interface **210**.

[0032] Referring now to FIG. 3-FIG. 4, the first connector **110** may include a first locking mechanism, shown as protrusion **310**. The protrusion **310** may be a tab, bump, extruded portion, ridge, etc. The protrusion **310** may be positioned on an outer wall of the device interface **210**. In other embodiments, the protrusion **310** may be positioned on an inner wall of the device interface **210**. In still other embodiments, the protrusion **310** may be positioned on both the outer and inner walls of the device interface **210**. By way of example, the first connector **110** may include two protrusions **310**. The two protrusions **310** may be positioned on opposite sides of the device interface **210**. In another example, the two protrusions **310** may be positioned on adjacent sides of the device interface **210**. As can be appreciated, the first connector **110** may include any number of protrusions **310** that would be sufficient for receiving the seal shroud **240** (e.g., one, two, three, four, five, six, etc.). As will be described in greater detail herein, the protrusion(s) **310** may be configured to engage and/or receive one or more portions of the seal shroud **240**.

[0033] Referring specifically to FIG. 4, the first connector **110** and the second connector **120** may include respective apertures, shown as first aperture **410** and second aperture **420**. The first aperture **410** may be positioned on, and extend through, a top of the device interface **210**. Accordingly, the second aperture **420** may be positioned on, and extend at least partially through, a top of the housing **220**. The first aperture **410** may define a substantially similar diameter as the second aperture **420**. In some embodiments, the first aperture **410** may define a substantially different diameter as the second aperture **420** (e.g., the diameter of the first aperture **410** may be greater than the diameter of the second aperture **420**, etc.). As can be appreciated, when the second connector **120** is mated with the first connector **110**, the first aperture **410** and the second aperture **420** may be coaxially aligned. When the apertures **410**, **420** are coaxially aligned, the connector assembly **100** may include a fastener (e.g., bolt, screw, pin, dowel, etc.) that is received within the apertures **410**, **420**. The fastener may be configured to secure the second connector **120** within the first connector **110**, to prevent the second connector **120** from repositioning into the unmated position.

[0034] The second connector **120** may include a first seal **430**. The first seal **430** may be positioned proximate the exterior surface of the housing **220**. In one example, the first seal **430** may be positioned within a slot (e.g., recess, cavity, groove, etc.) formed around the exterior surface of the housing **220**. In another example, the first seal **430** may be positioned around the exterior surface of the housing **220** where the first seal **430** extends axially outward from the housing **220**. As shown in FIG. 4, the first seal **430** may be engaged against an inner wall of the device interface **210** when the connector assembly **100** is in the mated position. As will be described in greater detail herein, the first seal **430** may be axially covered when the connector assembly **100** is in both the unmated position and the mated position to protect the first seal **430** from debris, particulate, external forces or elements, etc.

[0035] Referring now to FIG. 5, the second connector **120** may include a first end **510** and a second end **520**. The first end **510** may be positioned proximate the electrical wire **230** and the second end **520** may be positioned proximate the second aperture **420**, opposite the first end **510**. The first connector **110** may receive the second connector **120** proximate the second end **520**. The second connector **120** may include a track **530**. The track **530** may be positioned along a portion of the exterior surface of the housing **220**, proximate the first end **510**. In other embodiments, the track **530** may be positioned proximate the second end **520**. In still other embodiments, the track **530**

may extend entirely along the length of the housing **220** between the first end **510** and the second end **520**. The seal shroud **240** may be repositionable along the track **530**. The seal shroud **240** may be repositionable between the first position and the second position by engaging and disengaging a portion of the seal shroud **240** (e.g., first portion **710** from FIG. 7) with an interface (e.g., interface **810** from FIG. 8) to lock or secure the seal shroud **240** in a particular position.

[0036] Referring now to FIG. 6-FIG. 7, the track **530** may include a second groove **610**. The second groove **610** may extend along at least a portion of the length of the track **530**. The groove **620** and the second groove **610** may be orthogonal to one another. In other embodiments, the groove **620** and the second groove **610** may be angular or parallel to one another. The second groove **610** may extend along a midpoint of the track **530** such that the track **530** is separated into two substantially similar track members in which the seal shroud **240** may reposition along.

[0037] The interface (e.g., interface **810** from FIG. 8) of the seal shroud **240** may include a first portion **710** and a second portion **720**. The first portion **710** may be provided perpendicular to the second portion **720**. In other embodiments, the first portion **710** may be provided parallel to the second portion **720**. As can be appreciated, when the seal shroud **240** is in the first position, the first portion **710** may not be positioned within the groove **620** and the second portion **720** may be positioned within the second groove. Additionally or alternatively, when the seal shroud **240** is in the second position, the first portion **710** may be positioned within the groove **620** and the second portion **720** may be positioned within the second groove **610**. The track **530** may include one or more additional grooves such that the first portion **710** and the second portion **720** may be received within to create additional positions or stops for the seal shroud **240**.

[0038] Referring to FIG. 7, the second tab **550** of the seal shroud **240** may include one or more outer tabs, shown as outer tab **730**, and an inner tab **740**. The inner tab **740** may be centrally located between the outer tabs **730**. In other embodiments, the second tab **550** may include one outer tab **730** with the inner tab **740** being positioned adjacent the outer tab **730**. The inner tab **740** may be spaced apart from the outer tabs **730** by a space, where the inner tab **740** may flex relative to the outer tabs **730**. The inner tab **740** may flex outward relative to the outer tabs **730** when the seal shroud **240** is repositioning. More specifically, the inner tab **740** may include a tab, protrusion, tooth, etc. that is configured to engage the protrusion of the first connector **110** (e.g., protrusion **310** of FIG. 3). By way of example, when the first and second connectors **110**, **120** are mated, the seal shroud **240** may be engaged against the device interface **210** such that the protrusion of the inner tab **740** is engaged with the protrusion **310** of the device interface **210**. As such, the protrusion of the inner tab **740** may be engaged with the protrusion **310** of the device interface **210** when the seal shroud **240** is in the first position. Additionally or alternatively, the protrusion of the inner tab **740** may be engaged with the protrusion **310** of the device interface **210** when the seal shroud **240** is in the second position. Upon unmating the first connector **110** from the second connector **120**, the protrusion **310** of the device interface **210** may maintain engagement with the protrusion of the inner tab **740** to reposition the seal shroud **240** from the first position to the second position. When the seal shroud **240** is repositioned into the second position, the first portion **710** of the interface **810** may be received within the groove **620** to disengage the protrusion **310** of the device interface **210** from the protrusion of the inner tab **740**. Accordingly, the seal shroud **240** may maintain constant axial arrangement over the first seal **430** to provide a level of protection to the first seal **430**.

[0039] As discussed above, the seal shroud **240** may be movable between a first position and a second position. As shown in FIGS. 2 and 4, the first position may be a position where the seal shroud **240** abuts the device interface **210**. As shown in FIG. 5, the second position may be a position where the seal shroud **240** is not positioned against the device interface **210**. More specifically, the seal shroud **240** may include a first tab **540** positioned axially above the track **530**. Referring now to FIGS. 6 and 8, the first tab **540** may be engaged within the track **530** where the seal shroud **240** slides along the track **530**. Additionally, when the seal shroud **240** is in the first

position, the first tab **540** may be at least partially positioned within a slot defined within an outer portion of the housing **220** where the track **530** is provided therethrough. In some embodiments, the first tab **540** may not be positioned within the slot when the seal shroud **240** is in the first position. In other embodiments, the seal shroud **240** may be positioned over the outer portion of the housing **220** when the seal shroud **240** is in the first position. By way of example, the seal shroud **240** may include two first tabs **540**. The two first tabs **540** may be positioned on opposite sides of the seal shroud **240**. In other embodiments, the two first tabs **540** may be positioned on adjacent sides of the seal shroud **240**. As can be appreciated, each of the two first tabs **540** may be positioned within the respective slot defined within the housing **220** when the seal shroud **240** is in the first position.

[0040] The seal shroud **240** may receive a second tab **550** extending outward from a body of the seal shroud **240** along the housing **220**. The second tab **550** may be coupled to the seal shroud **240** at an opposite end from the first tab **540**. In other embodiments, the second tab **550** may be coupled to the seal shroud **240** adjacent the first tab **540**. The second tab **550** may include three elongated members (e.g., tabs, fingers, etc.) extending from the body of the seal shroud **240**. As will be discussed in greater detail herein, at least one of the three elongated members may be configured to interface with the protrusion **310**. By way of example, the seal shroud **240** may include two second tabs **550**. The two second tabs **550** may be positioned on opposite sides of the seal shroud **240**. In other embodiments, the two second tabs **550** may be positioned on adjacent sides of the seal shroud **240**. As can be appreciated, each of the two second tabs **550** may be configured to interface with the respective protrusion **310** when the connector assembly is in the mated position.

[0041] Referring now to FIG. **8**, the seal shroud **240** may include a second locking mechanism, shown as interface **810**. The interface **810** may be one of a tab, protrusion, tooth, etc. The interface **810** may be positioned proximate an end of the first tab **540** of the seal shroud **240**. That is, the interface **810** may be positioned at the end of the first tab **540** of the seal shroud **240** distal the second aperture **420**. In other embodiments, the interface **810** may be positioned proximate the second aperture **420** or positioned proximate a central portion of the seal shroud **240**. The interface **810** may protrude from an inner surface of the seal shroud **240** to engage a component positioned axially inward the seal shroud **240**. In other embodiments, the interface **810** may protrude outward to engage a component positioned axially outward the seal shroud **240**. The interface **810** may protrude inward from the seal shroud **240** to engage at least a portion of the track **530**. The track **530** may include a groove **620** extending substantially perpendicular to a length of the track **530**. The groove **620** may be configured to receive the interface **810** to substantially secure the seal shroud **240** in the second position. The track **530** may include an inclined portion sloped towards the groove **620**. The inclined portion may be configured to bias and/or otherwise urge the seal shroud **240** into the second position via the interface **810**. An end of the track **530**, opposite the inclined portion, may be substantially protrude outward at an angle relative to the housing **220** (e.g., 60 degrees, 70 degrees, 80 degrees, 90 degrees, 100 degrees, 110 degrees, etc.). The interface **810** may abut the end of the track **530** to prohibit the seal shroud **240** from repositioning past the track **530**.

[0042] The second connector **120** may further include a second seal **830**. The second seal **830** may be positioned inward an outer edge of the housing **220**. In other embodiments, the second seal **830** may be positioned proximate the outward edge of the housing **220**. The second seal **830** may be configured to engage the electrical wire **230**. In other embodiments, the second seal **830** may engage another component of the second connector **120**. The second seal **830** may be positioned axially inward to the first seal **430** relative to a connector axis **840** (e.g., longitudinal axis). In other embodiments, the second seal **830** may be positioned axially outward to the first seal **430**. In still other embodiments, the second seal **830** may be axially aligned with the first seal **430**. The connector axis **840** may extend along a midpoint of the electrical wire **230**. In other examples, the connector axis **840** may extend along a midpoint of the second connector **120**.

[0043] The connector axis **840** may define an axis in which the seal shroud **240** may reposition

along. The seal shroud **240** may be repositionable between the first position and the second position along the connector axis **840**. As can be appreciated, the first connector **110** and the second connector **120** may be matable along the connector axis **840** to urge movement of the seal shroud **240** between the first and second positions.

[0044] Although this description may discuss a specific order of method steps, the order of the steps may differ from what is outlined. Also two or more steps may be performed concurrently or with partial concurrence. Such variation will depend on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various connection steps, processing steps, comparison steps, and decision steps.

[0045] As utilized herein, the terms “approximately”, “about”, “substantially”, and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and claimed are considered to be within the scope of the invention as recited in the appended claims.

[0046] It should be noted that the term “exemplary” as used herein to describe various embodiments is intended to indicate that such embodiments are possible examples, representations, and/or illustrations of possible embodiments (and such term is not intended to connote that such embodiments are necessarily extraordinary or superlative examples).

[0047] The terms “coupled,” “connected,” and the like, as used herein, mean the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent, etc.) or moveable (e.g., removable, releasable, etc.). Such joining may be achieved with the two members or the two members and any additional intermediate members being integrally formed as a single unitary body with one another or with the two members or the two members and any additional intermediate members being attached to one another.

[0048] References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below,” “between,” etc.) are merely used to describe the orientation of various elements in the figures. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

[0049] It is important to note that the construction and arrangement of the connector assembly as shown in the exemplary embodiments is illustrative only. Although only a few embodiments of the present disclosure have been described in detail, those skilled in the art who review this disclosure will readily appreciate that many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter recited. For example, elements shown as integrally formed may be constructed of multiple parts or elements. It should be noted that the elements and/or assemblies of the components described herein may be constructed from any of a wide variety of materials that provide sufficient strength or durability, in any of a wide variety of colors, textures, and combinations. Accordingly, all such modifications are intended to be included within the scope of the present inventions. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions, and arrangement of the preferred and other exemplary embodiments without departing from scope of the present disclosure or from the spirit of the appended claims.

Claims

1. A connector assembly, comprising: a first connector; and a second connector selectively coupled to the first connector comprising: a housing including a seal positioned along an exterior surface of the housing; and a seal shroud adjacent to the housing, the seal shroud movable between a first position and a second position, the seal shroud at least partially covering the seal of the housing in the second position, and the seal shroud exposing the seal to an interior-facing surface of the first connector in the first position.
2. The connector assembly of claim 1, wherein the first connector includes a first locking mechanism along an exterior surface of the first connector, and wherein the second connector includes a second locking mechanism extending along an interior surface of the seal shroud.
3. The connector assembly of claim 1, wherein the seal shroud covers the seal when the first connector is uncoupled from the second connector.
4. The connector assembly of claim 1, wherein the housing comprises a track having an inclined portion to bias the seal shroud in the second position, and wherein a notch is configured to secure the seal shroud in the second position to cover the seal when the second connector is uncoupled from the first connector.
5. The connector assembly of claim 1, wherein the second connector further comprises a track provided along at least a portion of the housing, the seal shroud being repositionable along the track between the first position and the second position.
6. The connector assembly of claim 1, wherein the housing comprises a notch extending along an exterior surface of the housing, and wherein the housing defines a length extending from an end of the second connector and the notch, the seal shroud being repositionable between the first position and the second position along the length of the housing.
7. The connector assembly of claim 1, wherein the seal is peripherally provided around the second connector, and wherein the seal shroud is slidably repositionable along a longitudinal axis between a forward position and a rearward position.
8. The connector assembly of claim 1, wherein the housing comprises a second seal positioned along an interior facing surface of the housing, the second seal configured to engage an electrical wire.
9. The connector assembly of claim 1, wherein the housing comprises a notch extending along an exterior surface of the housing, the notch configured to abut the seal shroud to axially reposition to cover the seal when the seal shroud is moving from the first position to the second position.
10. The connector assembly of claim 1, wherein the first connector comprises a first alignment port and the second connector comprises a second alignment port, the first alignment port configured to be axially aligned with the second alignment port when the first connector is coupled to the second connector, the first alignment port and the second alignment port configured to receive a fastener therethrough.
11. The connector assembly of claim 1, wherein the first connector includes a device interface positioned at a distal end of the first connector, wherein the seal shroud abuts the device interface in the first position.
12. The connector assembly of claim 11, wherein the seal shroud is positioned away from the device interface in the second position.
13. A connector, comprising: a housing including a seal positioned along an exterior surface of the housing; and a seal shroud adjacent to the housing, the seal shroud movable between a first position and a second position, the seal shroud at least partially covering the seal of the housing in the second position, and the seal shroud exposing the seal to an interior facing surface of a second connector, configured to couple with the connector, in the first position.
14. The connector of claim 13, wherein the seal shroud covers the seal when the connector is

uncoupled from the second connector.

15. The connector of claim 13, further comprising a first alignment port configured to be axially aligned with a second alignment port of the second connector when the connector is coupled to the second connector, the first alignment port and the second alignment port configured to receive a fastener therethrough.

16. The connector of claim 13, wherein the housing comprises a notch extending along an exterior surface of the housing, the notch configured to abut the seal shroud to axially reposition to cover the seal when the seal shroud is positioning from the first position to the second position.

17. The connector of claim 13, the seal is peripherally provided around the second connector, and wherein the seal shroud is slidably repositionable along a longitudinal axis between a forward position and a rearward position.

18. The connector of claim 13, wherein the housing comprises a track having an inclined portion to bias the seal shroud in the second position, and wherein a notch is configured to secure the seal shroud in the second position to cover the seal when the connector is uncoupled from the second connector.

19. The connector of claim 13, wherein the seal shroud is repositionable along a track of the second connector between the first position and the second position.

20. A connector assembly comprising: a first connector; and a second connector comprising: a housing including a seal positioned along an exterior surface of the housing; and a movable component at least partially adjacent to the housing, the movable component positionable between a first position and a second position and configured to partially cover the seal when the movable component is in the second position; wherein the first position corresponds to the movable component being distally located relative to the first connector and the second position corresponds to the movable component being proximally located relative to the first connector, and wherein the movable component is configured to maintain its position over the seal when the first connector is coupled to the second connector.
