

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397777
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Tsuda; Fumiya

Travel assistance method and travel assistance device

Abstract

A travel assistance method sets a target slip angle, estimates or detects an actual slip angle, sets a target braking/driving force by, when a sign of the vehicle body slip angle rotating in a turning direction of the vehicle is defined as positive and a sign of the vehicle body slip angle rotating in an opposite direction to the turning direction is defined as negative, correcting a required braking/driving force in such a manner as to increase a braking/driving force for a rear wheel or reduce a braking/driving force generated on a front wheel when the actual slip angle is larger than the target slip angle and correcting the required braking/driving force in such a manner as to reduce a braking/driving force for the rear wheel or increase a braking/driving force generated on the front wheel when the actual slip angle is smaller than the target slip angle.

Inventors:	Tsuda; Fumiya (Kanagawa, JP)
Applicant:	Nissan Motor Co., Ltd. (Yokohama, JP); Renault S.A.S. (Boulogne-Billancourt, FR)
Family ID:	1000008779462
Assignee:	Nissan Motor Co., Ltd. (Yokohama, JP); Renault S.A.S. (Boulogne-Billancourt, FR)
Appl. No.:	18/854447
Filed (or PCT Filed):	April 05, 2022
PCT No.:	PCT/IB2022/000177
PCT Pub. No.:	WO2023/194760
PCT Pub. Date:	October 12, 2023

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Publication Classification

Int. Cl.: **B60W30/045** (20120101); **B60W10/04** (20060101); **B60W10/18** (20120101);
B60W40/103 (20120101); **B60W40/105** (20120101)

U.S. Cl.:

CPC **B60W30/045** (20130101); **B60W10/04** (20130101); **B60W10/18** (20130101);
B60W40/103 (20130101); **B60W40/105** (20130101); B60W2520/10 (20130101);
B60W2520/125 (20130101); B60W2520/14 (20130101); B60W2520/20 (20130101);
B60W2540/10 (20130101); B60W2540/12 (20130101); B60W2540/18 (20130101);
B60W2720/14 (20130101); B60W2720/20 (20130101)

Field of Classification Search

CPC: B60W (30/045); B60W (10/04); B60W (10/18); B60W (40/103); B60W (40/105); B60W
(2520/10); B60W (2520/125); B60W (2520/14); B60W (2520/20); B60W (2540/10);
B60W (2540/12); B60W (2540/18); B60W (2720/14); B60W (2720/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4767588	12/1987	Ito	701/41	B62D 7/159
10899225	12/2020	Kishi	N/A	B60K 23/0808
11247561	12/2021	Gully	N/A	N/A
12017642	12/2023	Luo et al.	N/A	N/A
2007/0032937	12/2006	Yamaguchi	701/41	B60W 30/045
2011/0035129	12/2010	Yasui	701/70	B60T 8/17558
2011/0218700	12/2010	Mori	701/31.4	B60W 10/06
2011/0218706	12/2010	Mori	701/36	B60W 30/025
2018/0118220	12/2017	Kimura	N/A	B60W 10/20
2020/0164744	12/2019	Kishi	N/A	B60K 23/0808
2022/0080838	12/2021	Hwang et al.	N/A	N/A
2023/0339456	12/2022	Luo et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112752691	12/2020	CN	N/A
102012013611	12/2012	DE	B60T 8/17551
102013214804	12/2014	DE	B60W 30/02
0914997	12/1998	EP	B60T 8/1755
2578460	12/2012	EP	B60T 8/17552
3315371	12/2017	EP	B60T 8/17552
H03-070633	12/1990	JP	N/A
H10-016738	12/1997	JP	N/A
H11-240458	12/1998	JP	N/A

2003-194209	12/2002	JP	N/A
2018-069998	12/2017	JP	N/A
2020-083073	12/2019	JP	N/A
2020-192938	12/2019	JP	N/A
2021-142883	12/2020	JP	N/A
WO-2006013645	12/2005	WO	B60T 8/1755
WO-2019059131	12/2018	WO	B60W 40/112

Primary Examiner: Sarwar; Babar

Attorney, Agent or Firm: Young Basile Hanlon & MacFarlane, P.C.

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a travel assistance method and a travel assistance device.

BACKGROUND

(2) In JP H03-70633 A described below, a torque control device that, in order to increase turning performance, increases a torque distribution to the front wheel side when an actual yaw rate is larger than a target yaw rate and increases a torque distribution to the rear wheel side when the actual yaw rate is smaller than the target yaw rate is described.

SUMMARY

(3) Although a driver can achieve a desired yaw rate by operating a steering wheel, the driver cannot simultaneously achieve a desired yaw rate and a desired vehicle body slip angle. When the vehicle body slip angle becomes excessive or insufficient, the driver is influenced by a difference of a line of sight from a travel direction of a vehicle. Thus, there are some cases where the driver steers the steering wheel more than necessary or the amount of steering is insufficient. As a result, it sometimes becomes difficult to perform steering operation to cause the vehicle to turn along a desired travel line.

(4) An object of the present invention is to facilitate steering operation to cause a vehicle to turn along a desired travel line.

(5) According to an aspect of the present invention, there is provided a travel assistance method including: detecting vehicle speed of a vehicle; detecting a steering angle of a steering wheel; setting a required braking/driving force according to an operation amount of an accelerator pedal or a brake pedal operated by a driver; setting a target value of a vehicle body slip angle, the vehicle body slip angle being an angle from a longitudinal direction of a vehicle body to a travel direction of the vehicle, as a target slip angle, based on the vehicle speed and the steering angle; estimating or detecting an actual slip angle, the actual slip angle being an actual vehicle body slip angle; setting a target braking/driving force by, when a sign of the vehicle body slip angle rotating in a turning direction of the vehicle is defined as positive and a sign of the vehicle body slip angle rotating in an opposite direction to the turning direction is defined as negative, correcting the required braking/driving force in such a manner as to increase a braking/driving force for a rear wheel or reduce a braking/driving force generated on a front wheel when the actual slip angle is larger than the target slip angle and correcting the required braking/driving force in such a manner as to reduce a braking/driving force for the rear wheel or increase a braking/driving force generated on the front wheel when the actual slip angle is smaller than the target slip angle; and generating the target braking/driving force in the vehicle.

(6) According to an aspect of the present invention, it is possible to facilitate steering operation to

cause a vehicle to turn along a desired travel line.

(7) The object and advantages of the invention will be realized and attained by means of the elements and combinations particularly pointed out in the claims. It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are not restrictive of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic configuration diagram of an example of a travel assistance device of an embodiment;
- (2) FIGS. 2A to 2D are explanatory diagrams of a vehicle body slip angle;
- (3) FIGS. 3A to 3D are schematic diagrams illustrative of examples of a target slip angle and an actual slip angle when a vehicle turns to the left;
- (4) FIGS. 4A to 4D are schematic diagrams illustrative of examples of the target slip angle and the actual slip angle when the vehicle turns to the right;
- (5) FIG. 5 is a block diagram of an example of a functional configuration of a controller in FIG. 1;
- (6) FIG. 6 is a block diagram of an example of a functional configuration of a braking/driving force correction value calculation unit;
- (7) FIG. 7 is a flowchart of an example of a travel assistance method of the embodiment; and
- (8) FIG. 8 is a block diagram of a variation of the functional configuration of the braking/driving force correction value calculation unit.

DETAILED DESCRIPTION

(9) (Configuration)

(10) FIG. 1 is a schematic configuration diagram of an example of a travel assistance device of an embodiment. A travel assistance device **10** adjusts a vehicle body slip angle of a vehicle **1** by controlling a braking/driving force for at least one of front wheels **2F** (a front left wheel **2FL** and a front right wheel **2FR**) and rear wheels **2R** (a rear left wheel **2RL** and a rear right wheel **2RR**) of the vehicle **1** and assists steering operation of the vehicle **1** performed by a driver.

(11) The travel assistance device **10** includes a wheel speed sensor **11**, a steering angle sensor **12**, a switch (SW) **13**, a yaw rate sensor **14**, an acceleration sensor **15**, a brake sensor **16**, an accelerator opening sensor **17**, a controller **18**, a drive controller **19**, actuators **20**, a turning device **21**, a braking device **22**, and a drive source **23**.

(12) The wheel speed sensor **11** detects wheel speed V_w of the vehicle **1**. For example, the wheel speed sensor **11** may detect an average value of wheel speeds of the front left wheel **2FL**, the front right wheel **2FR**, the rear left wheel **2RL**, and the rear right wheel **2RR** as the wheel speed V_w .

(13) The steering angle sensor **12** detects a steering angle $\theta_s(s)$ of a steering wheel. Herein, a sign of a steering angle $\theta_s(s)$ rotating leftward (counterclockwise) is defined as positive (plus), and a sign of a steering angle $\theta_s(s)$ rotating rightward (clockwise) is defined as negative (minus).

(14) The switch (SW) **13** is an operation element for accepting a selection input that a passenger (for example, the driver) of the vehicle **1** inputs to select a response characteristic of the vehicle **1** responding to driving operation performed by the driver.

(15) For example, the switch **13** may be a switch to switch driving modes that represent driving characteristics of the vehicle **1**. For example, the driving modes may include a first mode (for example, a sport mode) in which the response characteristic of the vehicle **1** responding to the driving operation performed by the driver is high and a second mode (for example, an economy mode) in which the response characteristic of the vehicle **1** responding to the driving operation is gentle. The response characteristic of the vehicle **1** responding to the driving operation may be, for example, a response characteristic of a steered angle of steered wheels with respect to operation of

the steering wheel, a drive characteristic with respect to operation of an accelerator pedal, or a braking characteristic with respect to a brake pedal. The controller **18** changes the response characteristic of the vehicle **1** responding to the driving operation performed by the driver, based on a setting state of the switch **13**.

(16) The yaw rate sensor **14** detects a yaw rate of the vehicle **1**.

(17) The acceleration sensor **15** detects lateral acceleration that is acceleration in the vehicle width direction of the vehicle **1**.

(18) The brake sensor **16** detects a brake operation amount Br that is an operation amount of the brake pedal operated by the driver.

(19) The accelerator opening sensor **17** detects an accelerator operation amount Ac that is an operation amount of the accelerator pedal operated by the driver.

(20) The controller **18** is an electronic control unit (ECU) that performs travel assistance control of the vehicle **1**. The controller **18** includes a processor **18a** and peripheral components, such as a storage device **18b**. The processor **18a** may be, for example, a central processing unit (CPU) or a micro-processing unit (MPU). The storage device **18b** may include a semiconductor storage device, a magnetic storage device, an optical storage device, or the like. The storage device **18b** may include registers, a cache memory, and a memory, such as a read only memory (ROM) and a random access memory (RAM), that is used as a main storage device. Functions of the controller **18**, which will be described below, are achieved by, for example, the processor **18a** executing computer programs stored in the storage device **18b**.

(21) Note that the controller **18** may be formed using dedicated hardware for performing various types of information processing that will be described below. For example, the controller **18** may include a functional logic circuit that is implemented in a general-purpose semiconductor integrated circuit. For example, the controller **18** may include a programmable logic device (PLD), such as a field-programmable gate array (FPGA), and the like.

(22) The drive controller **19** is an electronic control unit that controls a driving force that the drive source **23** generates on at least one of the front wheels **2F** and the rear wheels **2R**, based on the accelerator operation amount Ac detected by the accelerator opening sensor **17** and a braking/driving force correction value Cr set by the controller **18**. Specifically, the drive controller **19** calculates a pre-correction target driving force $Fd0$, based on the accelerator operation amount Ac . The drive controller **19** causes the drive source **23** to generate a target driving force Fd that is obtained by correcting the pre-correction target driving force $Fd0$ with the braking/driving force correction value Cr set by the controller **18**.

(23) The drive controller **19** includes a processor and peripheral components, such as a storage device. The processor may be, for example, a CPU or an MPU. The storage device may include a semiconductor storage device, a magnetic storage device, an optical storage device, or the like. The storage device may include registers, a cache memory, and a memory, such as a ROM and a RAM, that is used as a main storage device. Functions of the drive controller **19**, which will be described below, are achieved by, for example, the processor executing computer programs stored in the storage device. The drive controller **19** may be formed using dedicated hardware for performing various types of information processing that will be described below. For example, the drive controller **19** may include a functional logic circuit that is implemented in a general-purpose semiconductor integrated circuit. For example, the drive controller **19** may include a PLD, such as an FPGA, or the like.

(24) The drive controller **19** may be a separate controller from the controller **18** or the drive controller **19** and the controller **18** may be an integrated controller.

(25) The actuators **20** cause the turning device **21** and the braking device **22** to operate in accordance with control signals from the controller **18** and generate a vehicle behavior of the vehicle **1**. The actuators **20** include a steering actuator and a brake control actuator. The steering actuator causes the turning device **21** to operate and controls a steering direction and the amount of

steering of the vehicle **1**. The brake control actuator causes the braking device **22** to operate and generate a friction braking force and thereby controls front-rear deceleration of the vehicle **1**.

(26) Next, travel assistance control performed by the travel assistance device **10** of the embodiment will be described. Although as described above, the driver can achieve a desired yaw rate by operating the steering wheel, the driver cannot achieve a desired yaw rate and a desired vehicle body slip angle at the same time.

(27) FIGS. 2A to 2D are now referred to. Herein, the “vehicle body slip angle” is defined by an angle β from a vehicle body longitudinal direction db of the vehicle **1** to a travel direction dd of the vehicle **1**. In FIGS. 2A to 2D, a reference sign P denotes a position of the center of gravity of the vehicle **1**, and a reference sign Ld denotes a travel line (travel trajectory) of the vehicle **1** that is turning.

(28) Herein, a sign of the vehicle body slip angle β rotating leftward (counterclockwise) is defined as positive (plus), and the sign of the vehicle body slip angle β rotating rightward (clockwise) is defined as negative (minus).

(29) As illustrated in FIG. 2A, when the vehicle body longitudinal direction db while the vehicle **1** is turning to the left is directed to an outer side of the turning of the travel direction dd , the sign of the vehicle body slip angle β is positive, and as illustrated in FIG. 2B, when the vehicle body longitudinal direction db while the vehicle **1** is turning to the left is directed to an inner side of the turning of the travel direction dd , the sign of the vehicle body slip angle β is negative.

(30) As illustrated in FIG. 2C, when the vehicle body longitudinal direction db while the vehicle **1** is turning to the right is directed to the outer side of the turning of the travel direction dd , the sign of the vehicle body slip angle β is negative, and as illustrated in FIG. 2D, when the vehicle body longitudinal direction db while the vehicle **1** is turning to the right is directed to an inner side of the turning of the travel direction dd , the sign of the vehicle body slip angle β is positive.

(31) In the following description, a state in which the vehicle body longitudinal direction db while the vehicle **1** is turning is directed to the outer side of the turning of the travel direction dd as illustrated in FIGS. 2A and 2C is referred to as “outwardly-directed state”, and a state in which the vehicle body longitudinal direction db while the vehicle **1** is turning is directed to an inner side of the turning of the travel direction dd as illustrated in FIGS. 2B and 2D is referred to as “inwardly-directed state”.

(32) In general, when vehicle speed is comparatively low, the vehicle **1** tends to be brought into the outwardly-directed state, and when the vehicle speed is comparatively high, the vehicle **1** tends to be brought into the inwardly-directed state. When the vehicle **1** is in the outwardly-directed state, the driver tends to attempt to increase the amount of steering more than necessary due to a difference of a line of sight of the driver from the travel direction dd of the vehicle **1**, and conversely, when the vehicle **1** is in the inwardly-directed state, the driver tends to attempt to reduce the amount of steering. Thus, when the vehicle body slip angle is excessive or insufficient, it sometimes becomes difficult to perform steering operation to cause a vehicle to turn along a desired travel line.

(33) Therefore, the travel assistance device **10** of the embodiment sets a target slip angle $\beta_t(s)$ that is a target value of the vehicle body slip angle, based on vehicle speed V and the steering angle $\theta_s(s)$. The target slip angle $\beta_t(s)$ is an angle from a target value of the vehicle body longitudinal direction db (hereinafter, sometimes referred to as “target vehicle body longitudinal direction db_t ”) to the travel direction dd of the vehicle **1**. The travel assistance device **10** controls a braking/driving force for at least one of the front wheels **2F** and the rear wheels **2R** in such a way that an actual slip angle $\beta_a(s)$ that is an actual vehicle body slip angle comes close to the target slip angle $\beta_t(s)$.

(34) FIGS. 3A to 3D are schematic diagrams illustrative of examples of the target slip angle $\beta_t(s)$ and the actual slip angle $\beta_a(s)$ when the vehicle **1** turns to the left.

(35) In the example in FIG. 3A, while the vehicle body longitudinal direction db is directed to the outer side of the turning of the travel direction dd ($\beta_a(s) > 0$), the target vehicle body longitudinal

direction dbt is directed to the inner side of the turning of the travel direction dd ($\beta_t(s) < 0$). That is, the actual slip angle $\beta_a(s)$ is larger than the target slip angle $\beta_t(s)$. In this case, the travel assistance device **10** controls a braking/driving force for at least one of the front wheels **2F** and the rear wheels **2R** in such a way that the actual slip angle $\beta_a(s)$ decreases (that is, in such a way that the vehicle body longitudinal direction db rotates toward the inner side of the turning). For example, the travel assistance device **10** reduces a braking/driving force for the front wheels **2F** or increases a braking/driving force for the rear wheels **2R**. The travel assistance device **10** may reduce the braking/driving force for the front wheels **2F** and increase the braking/driving force for the rear wheels **2R**.

(36) In the example in FIG. 3B, although both the vehicle body longitudinal direction db and the target vehicle body longitudinal direction dbt are directed to the outer side of the turning of the travel direction dd, the vehicle body longitudinal direction db is directed to the outer side of the turning of the target vehicle body longitudinal direction dbt. That is, the actual slip angle $\beta_a(s)$ is larger than the target slip angle $\beta_t(s)$ ($\beta_a(s) > \beta_t(s) > 0$). In this case, the travel assistance device **10** also controls a braking/driving force for at least one of the front wheels **2F** and the rear wheels **2R** in such a way that the actual slip angle $\beta_a(s)$ decreases.

(37) In the example in FIG. 3C, while the vehicle body longitudinal direction db is directed to the inner side of the turning of the travel direction dd ($\beta_a(s) < 0$), the target vehicle body longitudinal direction dbt is directed to the outer side of the turning of the travel direction dd ($\beta_t(s) > 0$). That is, the actual slip angle $\beta_a(s)$ is smaller than the target slip angle $\beta_t(s)$. In this case, the travel assistance device **10** controls a braking/driving force for at least one of the front wheels **2F** and the rear wheels **2R** in such a way that the actual slip angle $\beta_a(s)$ increases (that is, in such a way that the vehicle body longitudinal direction db rotates toward the outer side of the turning). For example, the travel assistance device **10** increases a braking/driving force for the front wheels **2F** or reduces a braking/driving force for the rear wheels **2R**. The travel assistance device **10** may increase the braking/driving force for the front wheels **2F** and reduce the braking/driving force for the rear wheels **2R**.

(38) In the example in FIG. 3D, although both the vehicle body longitudinal direction db and the target vehicle body longitudinal direction dbt are directed to the inner side of the turning of the travel direction dd, the vehicle body longitudinal direction db is directed to the inner side of the turning of the target vehicle body longitudinal direction dbt. That is, the actual slip angle $\beta_a(s)$ is smaller than the target slip angle $\beta_t(s)$ ($\beta_a(s) < \beta_t(s) < 0$). In this case, the travel assistance device **10** also controls a braking/driving force for at least one of the front wheels **2F** and the rear wheels **2R** in such a way that the actual slip angle $\beta_a(s)$ increases.

(39) FIGS. 4A to 4D are schematic diagrams illustrative of examples of the target slip angle $\beta_t(s)$ and the actual slip angle $\beta_a(s)$ when the vehicle **1** turns to the right.

(40) In the example in FIG. 4A, while the vehicle body longitudinal direction db is directed to the outer side of the turning of the travel direction dd ($\beta_a(s) < 0$), the target vehicle body longitudinal direction dbt is directed to the inner side of the turning of the travel direction dd ($\beta_t(s) > 0$). That is, the actual slip angle $\beta_a(s)$ is smaller than the target slip angle $\beta_t(s)$. In this case, the travel assistance device **10** controls a braking/driving force for at least one of the front wheels **2F** and the rear wheels **2R** in such a way that the actual slip angle $\beta_a(s)$ increases (that is, in such a way that the vehicle body longitudinal direction db rotates toward the inner side of the turning). For example, the travel assistance device **10** reduces a braking/driving force for the front wheels **2F** or increases a braking/driving force for the rear wheels **2R**. The travel assistance device **10** may reduce the braking/driving force for the front wheels **2F** and increase the braking/driving force for the rear wheels **2R**.

(41) In the example in FIG. 4B, although both the vehicle body longitudinal direction db and the target vehicle body longitudinal direction dbt are directed to the outer side of the turning of the travel direction dd, the vehicle body longitudinal direction db is directed to the outer side of the

turning of the target vehicle body longitudinal direction dbt . That is, the actual slip angle $\beta_a(s)$ is smaller than the target slip angle $\beta_t(s)$ ($\beta_a(s) < \beta_t(s) < 0$). In this case, the travel assistance device **10** also controls a braking/driving force for at least one of the front wheels **2F** and the rear wheels **2R** in such a way that the actual slip angle $\beta_a(s)$ increases.

(42) In the example in FIG. **4C**, while the vehicle body longitudinal direction db is directed to the inner side of the turning of the travel direction dd ($\beta_a(s) > 0$), the target vehicle body longitudinal direction dbt is directed to the outer side of the turning of the travel direction dd ($\beta_t(s) < 0$). That is, the actual slip angle $\beta_a(s)$ is larger than the target slip angle $\beta_t(s)$. In this case, the travel assistance device **10** controls a braking/driving force for at least one of the front wheels **2F** and the rear wheels **2R** in such a way that the actual slip angle $\beta_a(s)$ decreases (that is, in such a way that the vehicle body longitudinal direction db rotates toward the outer side of the turning). For example, the travel assistance device **10** increases a braking/driving force for the front wheels **2F** or reduces a braking/driving force for the rear wheels **2R**. The travel assistance device **10** may increase the braking/driving force for the front wheels **2F** and reduces the braking/driving force for the rear wheels **2R**.

(43) In the example in FIG. **4D**, although both the vehicle body longitudinal direction db and the target vehicle body longitudinal direction dbt are directed to the inner side of the turning of the travel direction dd , the vehicle body longitudinal direction db is directed to the inner side of the turning of the target vehicle body longitudinal direction dbt . That is, the actual slip angle $\beta_a(s)$ is larger than the target slip angle $\beta_t(s)$ ($\beta_a(s) > \beta_t(s) > 0$). In this case, the travel assistance device **10** also controls a braking/driving force for at least one of the front wheels **2F** and the rear wheels **2R** in such a way that the actual slip angle $\beta_a(s)$ decreases.

(44) Since because of this configuration, the vehicle body slip angle β (the actual slip angle $\beta_a(s)$) of the vehicle **1** can be appropriately controlled, the vehicle body slip angle β can be prevented from becoming excessive or insufficient. As a result, steering operation to cause a vehicle to turn along a desired travel line is facilitated.

(45) It should be noted that while in the example of the left turn in FIGS. **3A** to **3D**, the sign of the vehicle body slip angle β rotating in a turning direction of the vehicle **1** is defined as positive, in the example of right turn in FIGS. **4A** to **4D**, the sign of the vehicle body slip angle β rotating in the turning direction of the vehicle **1** is defined as negative.

(46) Therefore, in the case of the right turn, when it is also defined that the sign of the vehicle body slip angle β rotating in the turning direction of the vehicle **1** is positive and the sign of the vehicle body slip angle β rotating in an opposite direction to the turning direction is negative, the travel assistance device **10** reduces a braking/driving force for the front wheels **2F** or increases a braking/driving force for the rear wheels **2R** when the actual slip angle $\beta_a(s)$ is larger than the target slip angle $\beta_t(s)$ (that is, as illustrated in FIGS. **3A**, **3B**, **4A**, and **4B**, the vehicle body longitudinal direction db is directed to the outer side of the turning of the target vehicle body longitudinal direction dbt). Alternatively, the travel assistance device **10** reduces a braking/driving force for the front wheels **2F** and increases a braking/driving force for the rear wheels **2R**. On the other hand, when the actual slip angle $\beta_a(s)$ is smaller than the target slip angle $\beta_t(s)$ (that is, as illustrated in FIGS. **3C**, **3D**, **4C**, and **4D**, the vehicle body longitudinal direction db is directed to the inner side of the turning of the target vehicle body longitudinal direction dbt), the travel assistance device **10** increases a braking/driving force for the front wheels **2F** or reduces a braking/driving force for the rear wheels **2R**. Alternatively, the travel assistance device **10** increases a braking/driving force for the front wheels **2F** and reduces a braking/driving force for the rear wheels **2R**.

(47) FIG. **5** is a block diagram of an example of a functional configuration of the controller **18**. The controller **18** includes a vehicle speed calculation unit **30**, a required torque calculation unit **31**, an actual slip angle estimation unit **32**, a target slip angle calculation unit **33**, and a braking/driving force correction value calculation unit **34**.

(48) The wheel speed V_w detected by the wheel speed sensor **11**, the steering angle $\theta_s(s)$ detected by the steering angle sensor **12**, the brake operation amount Br detected by the brake sensor **16**, the accelerator operation amount Ac detected by the accelerator opening sensor **17**, and the pre-correction target driving force $Fd0$ calculated by the drive controller **19** are input to the controller **18**.

(49) The vehicle speed calculation unit **30** calculates vehicle speed V of the vehicle **1**, based on the wheel speed V_w and inputs information about the vehicle speed V to the actual slip angle estimation unit **32** and the target slip angle calculation unit **33**. The required torque calculation unit **31** calculates required braking/driving torque T_d matching the brake operation amount Br or the accelerator operation amount Ac by the driver and inputs information about the required braking/driving torque T_d to the target slip angle calculation unit **33**.

(50) The actual slip angle estimation unit **32** estimates an actual slip angle $\beta_a(s)$, based on at least the vehicle speed V and the steering angle $\theta_s(s)$. For example, the actual slip angle estimation unit **32** may estimate the actual slip angle $\beta_a(s)$, based on the equation (1) below.

$$(51) \quad [\text{Math1}] \quad a(s) = G \cdot \frac{1 + T \cdot s}{1 + \frac{2}{n} \cdot \frac{s}{\omega_n} + \frac{s^2}{\omega_n^2}} \cdot s(s) \quad (1) \quad [\text{Math2}] \quad n = \frac{2l}{V} \sqrt{\frac{K_f K_r}{mI}} \sqrt{1 + AV^2} \quad [\text{Math3}]$$

$$= \frac{m(l_f^2 K_f + l_r^2 K_r) + I(K_f + K_r)}{2l \sqrt{mIK_f K_r} (1 + AV^2)} \quad [\text{Math4}] \quad G = \frac{1 - \frac{m l_f K_r}{2l_r K_f} V^2}{1 + AV^2} \cdot \frac{l_r}{T} \quad [\text{Math5}] \quad T = \frac{IV}{2l_r K_r} \cdot \frac{1}{1 - \frac{m l_f K_r}{2l_r K_f} V^2} \quad [\text{Math6}]$$

$$A = -\frac{m}{2l^2} \frac{l_f K_f - l_r K_r}{K_f K_r}$$

(52) In the above-described equation, m is weight of a vehicle, I is a yaw inertia radius, l is a wheelbase, $l_{sub.f}$ is distance from a center P of gravity of the vehicle **1** to an axle of the front wheels, $l_{sub.r}$ is distance from the center P of gravity to an axle of the rear wheels, $K_{sub.f}$ is equivalent cornering power of the front wheels, and $K_{sub.r}$ is equivalent cornering power of the rear wheels.

(53) The target slip angle calculation unit **33** estimates a target slip angle $\beta_t(s)$, based on at least the vehicle speed V and the steering angle $\theta_s(s)$. For example, the target slip angle calculation unit **33** may estimate the target slip angle $\beta_t(s)$, based on the equation (2) below.

$$(54) \quad [\text{Math7}] \quad t(s) = K1 \times G \cdot \frac{1 + T \cdot s}{1 + \frac{2}{n} \cdot \frac{s}{\omega_n} + \frac{s^2}{\omega_n^2}} \cdot s(s) \quad (2)$$

(55) $K1$ in the equation (2) is slip angle gain, and by appropriately adjusting an absolute value and a sign of the slip angle gain $K1$, to what extent the target slip angle $\beta_t(s)$ is to be made larger or smaller than the actual slip angle $\beta_a(s)$ can be set. That is, to what extent the target vehicle body longitudinal direction db_t is to be inclined to the inner side of the turning or the outer side of the turning with respect to the vehicle body longitudinal direction db can be set.

(56) For example, when the vehicle speed V is comparatively low, the vehicle **1** tends to be brought into the outwardly-directed state, and when the vehicle speed V is comparatively high, the vehicle **1** tends to be brought into the inwardly-directed state. Thus, the target slip angle calculation unit **33** may set the target slip angle $\beta_t(s)$ according to the vehicle speed V .

(57) Specifically, when the sign of the vehicle body slip angle β rotating in the turning direction of the vehicle **1** is defined as positive and the sign of the vehicle body slip angle β rotating in the opposite direction to the turning direction is defined as negative, a larger target slip angle $\beta_t(s)$ may, for example, be set in a case when the vehicle speed V is high in which the vehicle **1** tends to be the inwardly-directed state than in a case when the vehicle speed V is low in which the vehicle **1** tends to be the outwardly-directed state. For example, the target slip angle may be set in such a manner that the higher the vehicle speed V is, the larger the target slip angle is. Because of this configuration, the vehicle **1** can be prevented from being brought into the inwardly-directed state when the vehicle speed V is high. In addition, by preventing the vehicle **1** from being brought into the outwardly-directed state when the vehicle speed V is low, bringing the vehicle **1** into the inwardly-directed state is facilitated.

(58) The braking/driving force correction value calculation unit **34** calculates a braking/driving force correction value C_r by which a required braking/driving force matching the brake operation amount B_r or the accelerator operation amount A_c by the driver is corrected, according to the actual slip angle $\beta_a(s)$ and the target slip angle $\beta_t(s)$.

(59) FIG. **6** is a block diagram of an example of a functional configuration of the braking/driving force correction value calculation unit **34**. In FIG. **6**, a configuration to calculate a braking/driving force correction value C_r by which a driving force for the rear wheels **2R** is corrected, according to the actual slip angle $\beta_a(s)$ and the target slip angle $\beta_t(s)$ is illustrated.

(60) The braking/driving force correction value calculation unit **34** includes a subtracter **40**, a gain multiplication unit **41**, a sign inversion unit **42**, a sign calculation unit **43**, a multipliers **44** and **46**, and a limiter **45**.

(61) The subtracter **40** subtracts the actual slip angle $\beta_a(s)$ from the target slip angle $\beta_t(s)$ and thereby calculates a slip angle difference $\Delta\beta = \beta_t(s) - \beta_a(s)$. The gain multiplication unit **41** outputs a product $P \times \Delta\beta$ obtained by multiplying the slip angle difference $\Delta\beta$ by a proportional gain P to the multiplier **44**.

(62) The sign inversion unit **42** inverts a sign of the steering angle $\theta_s(s)$, and the sign calculation unit **43** outputs a value “1” when a sign of a steering angle after the sign of the steering angle $\theta_s(s)$ is inverted ($-1 \times \theta_s(s)$) is positive and outputs “-1” when the sign is negative. The multiplier **44** normalizes the sign of the slip angle difference $\Delta\beta$ by multiplying the slip angle difference $\Delta\beta$ by the output from the sign calculation unit **43**.

(63) Because of this configuration, in whichever case of the left turn or the right turn, the sign of the slip angle difference $\Delta\beta$ is set positive when the vehicle body longitudinal direction db is directed to the outer side of the turning of the target vehicle body longitudinal direction db_t . Because of this configuration, the sign of the braking/driving force correction value C_r is set positive. In addition, when the vehicle body longitudinal direction db is directed to the inner side of the turning of the target vehicle body longitudinal direction db_t , the sign of the slip angle difference $\Delta\beta$ is set negative. Because of this configuration, the sign of the braking/driving force correction value C_r is set negative.

(64) The limiter **45** limits an upper limit and a lower limit of output of the multiplier **44** (that is, the slip angle difference $\Delta\beta$ the sign of which is normalized), and the multiplier **46** calculates a braking/driving force correction value C_r by multiplying the pre-correction target driving force F_{d0} by the limited slip angle difference $\Delta\beta$.

(65) The drive controller **19** in FIG. **1** calculates a target driving force F_d by adding the braking/driving force correction value C_r to the pre-correction target driving force F_{d0} and controls the drive source **23** in such a way that a driving force generated on the rear wheels **2R** coincides with the target driving force F_d .

(66) Thus, when the vehicle body longitudinal direction db is directed to the outer side of the turning of the target vehicle body longitudinal direction db_t , the vehicle body slip angle β is controlled in such a manner that a driving force for the rear wheels **2R** increases and the vehicle body longitudinal direction db rotates in a direction toward the inner side of the turning. Conversely, when the vehicle body longitudinal direction db is directed to the inner side of the turning of the target vehicle body longitudinal direction db_t , the vehicle body slip angle β is controlled in such a manner that a driving force for the rear wheels **2R** decreases and the vehicle body longitudinal direction db rotates in a direction toward the outer side of the turning.

(67) Although the example of the braking/driving force correction value calculation unit **34** in FIG. **6** calculates a braking/driving force correction value C_r by which a driving force for the rear wheels **2R** is corrected, the braking/driving force correction value calculation unit **34** may calculate a braking/driving force correction value C_r by which a driving force for the front wheels **2F** is corrected. In this case, the braking/driving force correction value calculation unit **34** normalizes the sign of the slip angle difference $\Delta\beta$ in a reverse manner to the case in FIG. **6**. Because of this

configuration, when the vehicle body longitudinal direction db is directed to the outer side of the turning of the target vehicle body longitudinal direction dbt, the sign of the braking/driving force correction value Cr is set negative, and when the vehicle body longitudinal direction db is directed to the inner side of the turning of the target vehicle body longitudinal direction dbt, the sign of the braking/driving force correction value Cr is set positive.

(68) The drive controller **19** in FIG. **1** calculates a target driving force Fd by adding the braking/driving force correction value Cr to the pre-correction target driving force Fd0 and controls the drive source **23** in such a way that a driving force generated on the front wheels **2F** coincides with the target driving force Fd.

(69) Thus, when the vehicle body longitudinal direction db is directed to the outer side of the turning of the target vehicle body longitudinal direction dbt, the vehicle body slip angle β is controlled in such a manner that a driving force for the front wheels **2F** decreases and the vehicle body longitudinal direction db rotates in a direction toward the inner side of the turning.

Conversely, when the vehicle body longitudinal direction db is directed to the inner side of the turning of the target vehicle body longitudinal direction dbt, the vehicle body slip angle β is controlled in such a manner that a driving force for the front wheels **2F** increases and the vehicle body longitudinal direction db rotates in a direction toward the outer side of the turning.

(70) Further, the braking/driving force correction value calculation unit **34** may calculate, as braking/driving force correction values Cr, a braking/driving force correction value CrF by which a driving force for the front wheels **2F** is corrected and a braking/driving force correction value CrR by which a driving force for the rear wheels **2R** is corrected, at the same time. In this case, when the vehicle body longitudinal direction db is directed to the outer side of the turning of the target vehicle body longitudinal direction dbt, the drive controller **19** reduces a driving force for the front wheels **2F** and also increases a driving force for the rear wheels **2R**. Conversely, when the vehicle body longitudinal direction db is directed to the inner side of the turning of the target vehicle body longitudinal direction dbt, the drive controller **19** increases a driving force for the front wheels **2F** and also reduces a driving force for the rear wheels **2R**. That is, a sign of the braking/driving force correction value CrF is different from a sign of the braking/driving force correction value CrR.

Magnitude of the braking/driving force correction value CrF and magnitude of the braking/driving force correction value CrR may be equal to each other or may be different from each other. When the magnitude of the braking/driving force correction value CrF and the magnitude of the braking/driving force correction value CrR are made equal to each other, the braking/driving force correction value calculation unit **34** may calculate a braking/driving force correction value Cr for at least one of the front wheels **2F** and the rear wheels **2R**, invert a sign of the calculated braking/driving force correction value Cr, and set the braking/driving force correction value Cr the sign of which is inverted as the other braking/driving force correction value ($-Cr$). By setting the braking/driving force correction value CrF and the braking/driving force correction value CrR to correction values having different signs and the same magnitude, a driving force of the entire vehicle **1** can be prevented from changing due to correction of wheel braking/driving forces for the front wheels **2F** and the rear wheels **2R**.

(71) In addition, when the vehicle **1** decelerates (that is, when the required braking/driving torque Td is braking torque), the braking/driving force correction value calculation unit **34** may calculate, as with the above-described braking/driving force correction value Cr by which the pre-correction target driving force Fd0 is corrected, a braking/driving force correction value Cr by which a friction braking force generated by the braking device **22** or a regenerative braking force generated by the drive source **23** is corrected. That is, when the vehicle body longitudinal direction db is directed to the outer side of the turning of the target vehicle body longitudinal direction dbt, the braking/driving force correction value calculation unit **34** may calculate a braking/driving force correction value Cr that reduces a braking force for the front wheels **2F** or a braking/driving force correction value Cr that increases a braking force for the rear wheels **2R**. The braking/driving force

correction value calculation unit **34** may calculate a braking/driving force correction value C_r that reduces a braking force for the front wheels **2F** and also increases a braking force for the rear wheels **2R**.

(72) Conversely, when the vehicle body longitudinal direction db is directed to the inner side of the turning of the target vehicle body longitudinal direction dbt , the braking/driving force correction value calculation unit **34** may calculate a braking/driving force correction value C_r that increases a braking force for the front wheels **2F** or a braking/driving force correction value C_r that reduces a braking force for the rear wheels **2R**. The braking/driving force correction value calculation unit **34** may calculate a braking/driving force correction value C_r that increases a braking force for the front wheels **2F** and also reduces a braking force for the rear wheels **2R**.

(73) The drive controller **19** calculates a target regenerative braking force according to an operation amount of the accelerator pedal or a brake pedal operated by the driver and controls the drive source **23** in such a way that a regenerative braking force obtained by correcting the calculated target regenerative braking force with the braking/driving force correction value C_r is generated.

(74) Alternatively, the controller **18** calculates a target friction braking force according to an operation amount of the accelerator pedal or a brake pedal operated by the driver and controls the brake control actuator in the actuators **20** in such a way that a friction braking force obtained by correcting the calculated target friction braking force with the braking/driving force correction value C_r is generated.

(75) (Operation)

(76) FIG. 7 is a flowchart of an example of a travel assistance method of the embodiment.

(77) In step **S1**, the steering angle sensor **12** detects a steering angle $\theta_s(s)$ of the steering wheel. The controller **18** detects vehicle speed V of the vehicle **1**. The drive controller **19** calculates a pre-correction target driving force F_{d0} .

(78) In step **S2**, the controller **18** estimates a target slip angle $\beta_t(s)$, based on at least the vehicle speed V and the steering angle $\theta_s(s)$.

(79) In step **S3**, the controller **18** estimates an actual slip angle $\beta_a(s)$, based on at least the vehicle speed V and the steering angle $\theta_s(s)$.

(80) In step **S4**, the controller **18** calculates a slip angle difference $\Delta\beta = \beta_t(s) - \beta_a(s)$.

(81) In step **S5**, the controller **18** calculates a braking/driving force correction value C_r , based on the slip angle difference $\Delta\beta$.

(82) In step **S6**, the drive controller **19** calculates a target driving force F_d to be generated on wheels by correcting the pre-correction target driving force F_{d0} with the braking/driving force correction value C_r and causes the drive source **23** to generate the target driving force F_d .

Subsequently, the process terminates.

(83) (Variations)

(84) Variations of the embodiment will be described below. Note that in the following variations, the sign of the vehicle body slip angle β rotating in a turning direction of the vehicle **1** is defined as positive, and the sign of the vehicle body slip angle β rotating in an opposite direction to the turning direction is defined as negative. In addition, the sign of the required braking/driving torque T_d that is driving torque is defined as positive, and the sign of the required braking/driving torque T_d that is braking torque is defined as negative. (1) When as the braking/driving force correction value C_r , a correction value increasing a braking/driving force for the front wheels **2F** and also a correction value reducing a braking/driving force for the rear wheels **2R** are calculated or a correction value reducing a braking/driving force for the front wheels **2F** and also a correction value increasing a braking/driving force for the rear wheels **2R** are calculated, the target slip angle calculation unit **33** may set a smaller target slip angle $\beta_t(s)$ when the required braking/driving torque T_d is large than when the required braking/driving torque T_d is small. For example, the target slip angle calculation unit **33** may set the target slip angle $\beta_t(s)$ in such a manner that the larger the required braking/driving torque T_d is, the smaller the target slip angle $\beta_t(s)$ is. For

example, the target slip angle calculation unit **33** may set a smaller target slip angle $\beta_t(s)$ when the required braking/driving torque T_d is driving torque than when the required braking/driving torque T_d is braking force. Because of this configuration, it is possible to prevent occurrence of understeer at the time of driving and occurrence of oversteer at the time of braking. (2) The target slip angle calculation unit **33** may set a smaller value of the target slip angle when lateral acceleration is large than when lateral acceleration is small. For example, the target slip angle calculation unit **33** may set the target slip angle $\beta_t(s)$ in such a manner that the larger the lateral acceleration is, the smaller the target slip angle $\beta_t(s)$ is. Because of this configuration, it is possible to prevent occurrence of understeer when the lateral acceleration is large. (3) When a driving mode of the vehicle **1** is set by an operation of the switch **13** by the driver (that is, when a response characteristic of the vehicle **1** responding to a driving operation performed by the driver is set), the target slip angle calculation unit **33** may set a larger target slip angle $\beta_t(s)$ when the response characteristic is high than when the response characteristic is low. For example, the target slip angle calculation unit **33** may set a larger target slip angle $\beta_t(s)$ when the driving mode of the vehicle **1** is the first mode than when the driving mode is the second mode. Because of this configuration, it is possible to set the vehicle body slip angle β of the vehicle **1** according to preference of the passenger. (4) The controller **18** may set a target yaw rate, based on the steering angle $\theta_s(s)$ and the vehicle speed V , detect an actual yaw rate that is an actual yaw rate generated in the vehicle **1**, and set a target braking/driving force by correcting the required braking/driving force in such a manner as to, when the actual yaw rate is smaller than the target yaw rate, increase a braking/driving force for the rear wheels **2R** or reduce a braking/driving force generated on the front wheels **2F**. Because of this configuration, the vehicle body slip angle β can be controlled in such a way that when the actual yaw rate is smaller than the target yaw rate (that is, when understeer occurs), the vehicle **1** is brought into the inwardly-directed state, and driving feeling is improved. (5) The braking/driving force correction value calculation unit **34** may calculate a braking/driving force correction value C_r , based on, in addition to the slip angle difference $\Delta\beta$, a slip angular velocity difference $\Delta\beta'$ obtained by subtracting an actual slip angular velocity that is a differential value of the actual slip angle $\beta_a(s)$ from a target slip angular velocity that is a differential value of the target slip angle $\beta_t(s)$. Because of this configuration, it is possible to improve responsiveness of the braking/driving force correction value C_r with respect to change in the target slip angle $\beta_t(s)$ and the actual slip angle $\beta_a(s)$.

(85) FIG. **8** is a block diagram of the variation of the functional configuration of the braking/driving force correction value calculation unit **34**. The braking/driving force correction value calculation unit **34** includes, in addition to the functional configuration described with reference to FIG. **6**, differentiators **50** and **51**, a subtracter **52**, a gain multiplication unit **53**, multipliers **54** and **55**, and an adder **56**.

(86) The differentiators **50** and **51** and the subtracter **52** calculate a slip angular velocity difference $\Delta\beta'$. The gain multiplication unit **53** outputs a product $D \times \Delta\beta'$ obtained by multiplying the slip angular velocity difference $\Delta\beta'$ by a differential gain D to the multiplier **54**. The multiplier **54** normalizes a sign of the slip angular velocity difference $\Delta\beta'$ by multiplying the slip angular velocity difference $\Delta\beta'$ by the output from the sign calculation unit **43**. The multiplier **55** multiplies the pre-correction target driving force F_{d0} by the output from the multiplier **54** (that is, the slip angular velocity difference $\Delta\beta'$ the sign of which is normalized), and the adder **56** calculates a braking/driving force correction value C_r by summing multiplication results of the multipliers **46** and **55**.

(87) Because of this configuration, the braking/driving force correction value calculation unit **34** of the variation calculates a braking/driving force correction value C_r that increases a driving force for the rear wheels **2R** when the actual slip angular velocity is larger than the target slip angular velocity and reduces a driving force for the rear wheels **2R** when the actual slip angular velocity is smaller than the target slip angular velocity.

(88) As with the above-described embodiment, by normalizing the sign of the slip angular velocity

difference $\Delta\beta'$ in a reverse manner to the sign in FIG. 8, the braking/driving force correction value calculation unit **34** can calculate a braking/driving force correction value C_r for correcting a driving force for the front wheels **2F**. In addition, the braking/driving force correction value calculation unit **34** may calculate, as with the braking/driving force correction values C_r for correcting a driving force, a braking/driving force correction value C_r for correcting a braking force.

Advantageous Effects of Embodiment

(89) (1) The controller **18** detects vehicle speed of the vehicle **1**. The steering angle sensor **12** detects a steering angle of the steering wheel. The controller **18** sets a required braking/driving force according to an operation amount of the accelerator pedal or the brake pedal operated by the driver, sets a target value of a vehicle body slip angle β , the vehicle body slip angle β being an angle from the longitudinal direction db of the vehicle body to the travel direction dd of the vehicle **1**, as a target slip angle $\beta_t(s)$, based on the vehicle speed and the steering angle, estimates or detects an actual slip angle $\beta_a(s)$, the actual slip angle $\beta_a(s)$ being an actual vehicle body slip angle, and sets a target braking/driving force by, when a sign of a vehicle body slip angle rotating in a turning direction of the vehicle **1** is defined as positive and a sign of a vehicle body slip angle rotating in an opposite direction to the turning direction is defined as negative, correcting the required braking/driving force in such a manner as to increase a braking/driving force for the rear wheels or reduce a braking/driving force generated on the front wheels when the actual slip angle $\beta_a(s)$ is larger than the target slip angle $\beta_t(s)$ and correcting the required braking/driving force in such a manner as to reduce a braking/driving force for the rear wheels or increase a braking/driving force generated on the front wheels when the actual slip angle $\beta_a(s)$ is smaller than the target slip angle $\beta_t(s)$. The drive source **23** or the actuator **20** and the turning device **21** generate the target braking/driving force in the vehicle.

(90) Since because of this configuration, the vehicle body slip angle β of the vehicle **1** can be appropriately controlled, the vehicle body slip angle can be prevented from becoming excessive or insufficient. As a result, steering operation to cause a vehicle to turn along a desired travel line is facilitated. (2) The controller **18** may set a target braking/driving force by correcting the required braking/driving force in such a manner as to increase a braking/driving force for the rear wheels and reduce a braking/driving force generated on the front wheels when the actual slip angle $\beta_a(s)$ is smaller than the target slip angle $\beta_t(s)$ and correcting the required braking/driving force in such a manner as to reduce a braking/driving force for the rear wheels and increase a braking/driving force generated on the front wheels when the actual slip angle $\beta_a(s)$ is larger than the target slip angle $\beta_t(s)$. Because of this configuration, it is possible to prevent a braking/driving force of the entire vehicle **1** from changing due to correction of wheel braking/driving forces for the front wheels **2F** and the rear wheels **2R**. (3) The controller **18** may set a larger target slip angle $\beta_t(s)$ when the vehicle speed is high than when the vehicle speed is low. Because of this configuration, when the vehicle speed V is comparatively low, the vehicle **1** can be prevented from being brought into the outwardly-directed state, and when the vehicle speed V is comparatively high, the vehicle **1** can be prevented from being brought into the inwardly-directed state.

(91) All examples and conditional language provided herein are intended for the pedagogical purposes of aiding the reader in understanding the invention and the concepts contributed by the inventor to further the art, and are not to be construed as limitations to such specifically recited examples and conditions, nor does the organization of such examples in the specification relate to a showing of the superiority and inferiority of the invention. Although one or more embodiments of the present invention have been described in detail, it should be understood that the various changes, substitutions, and alterations could be made hereto without departing from the spirit and scope of the invention.

REFERENCE SIGNS LIST

(92) **1** Vehicle **2F** Front wheel **2R** Rear wheel **10** Travel assistance device **11** Wheel speed sensor **12** Steering angle sensor **13** Switch **14** Yaw rate sensor **15** Acceleration sensor **16** Brake sensor **17**

Accelerator opening sensor **18** Controller **18a** Processor **18b** Storage device **19** Drive controller **20**
Actuator **21** Turning device **22** Braking device **23** Drive source **30** Vehicle speed calculation unit
31 Required torque calculation unit **32** Actual slip angle estimation unit **33** Target slip angle
calculation unit **34** Braking/driving force correction value calculation unit **40, 52** Subtractor **41, 53**
Gain multiplication unit **42** Sign inversion unit **43** Sign calculate unit **44, 46, 54, 55** Multiplier **45**
Limiter **50, 51** Differentiator **56** Adder

Claims

1. A travel assistance method comprising: detecting vehicle speed of a vehicle; detecting a steering angle of a steering wheel; setting a required braking/driving force according to an operation amount of an accelerator pedal or a brake pedal operated by a driver; setting a target value of a vehicle body slip angle, the vehicle body slip angle being an angle from a longitudinal direction of a vehicle body to a travel direction of the vehicle, as a target slip angle, based on the vehicle speed and the steering angle; estimating or detecting an actual slip angle based on at least the vehicle speed and the steering angle, the actual slip angle being an actual vehicle body slip angle; setting a target braking/driving force by, when a sign of the vehicle body slip angle rotating in a turning direction of the vehicle is defined as positive and a sign of the vehicle body slip angle rotating in an opposite direction to the turning direction is defined as negative, correcting the required braking/driving force in such a manner as to increase a braking/driving force for both of a rear right wheel and a rear left wheel or reduce a braking/driving force generated on both of a front right wheel and a front left wheel when the actual slip angle is larger than the target slip angle and correcting the required braking/driving force in such a manner as to reduce a braking/driving force for both of the rear right wheel and the rear left wheel or increase a braking/driving force generated on both of the front right wheel and the front left wheel when the actual slip angle is smaller than the target slip angle; generating the target braking/driving force in the vehicle; and controlling the vehicle based on the generated target braking/driving force in the vehicle.
2. The travel assistance method according to claim 1, wherein the travel assistance method sets the target braking/driving force by correcting the required braking/driving force in such a manner as to increase a braking/driving force for both of the rear right wheel and the rear left wheel and reduce a braking/driving force generated on both of the front right wheel and the front left wheel when the actual slip angle is larger than the target slip angle and correcting the required braking/driving force in such a manner as to reduce a braking/driving force for both of the rear right wheel and the rear left wheel and increase a braking/driving force generated on both of the front right wheel and the front left wheel when the actual slip angle is smaller than the target slip angle.
3. The travel assistance method according to claim 2, wherein when a sign of the required braking/driving force, the required braking/driving force being a driving force, is defined as positive and a sign of the required braking/driving force, the required braking/driving force being a braking force, is defined as negative, the travel assistance method sets a smaller value of the target slip angle when the required braking/driving force is large than when the required braking/driving force is small.
4. The travel assistance method according to claim 3, wherein the travel assistance method sets a smaller value of the target slip angle when the required braking/driving force is a driving force than when the required braking/driving force is a braking force.
5. The travel assistance method according to claim 1, wherein the travel assistance method sets a larger value of the target slip angle when the vehicle speed is high than when the vehicle speed is low.
6. The travel assistance method according to claim 1, further comprising: detecting lateral acceleration of the vehicle; and setting a smaller value of the target slip angle when the lateral acceleration is large than when the lateral acceleration is small.

7. The travel assistance method according to claim 1, further comprising: changing a response characteristic of the vehicle responding to driving operation performed by the driver, based on a selection input from the driver; and setting a larger value of the target slip angle when the response characteristic is high than when the response characteristic is low.
8. The travel assistance method according to claim 1, further comprising: calculating a target slip angular velocity, the target slip angular velocity being a differential value of the target slip angle, and an actual slip angular velocity, the actual slip angular velocity being a differential value of the actual slip angle; and correcting the required braking/driving force in such a manner as to increase a braking/driving force for a rear wheel or reduce a braking/driving force generated on a front wheel when the actual slip angular velocity is larger than the target slip angular velocity and correcting the required braking/driving force in such a manner as to reduce a braking/driving force for the rear wheel or increase a braking/driving force generated on the front wheel when the actual slip angular velocity is smaller than the target slip angular velocity.
9. The travel assistance method according to claim 1, further comprising: setting a target yaw rate, based on the steering angle and the vehicle speed; detecting an actual yaw rate, the actual yaw rate being an actual yaw rate generated in the vehicle; and setting a target braking/driving force by correcting the required braking/driving force in such a manner as to increase a braking/driving force for both of the rear right wheel and the rear left wheel or reduce a braking/driving force generated on both of the front right wheel and the front left wheel when the actual yaw rate is smaller than the target yaw rate.
10. A travel assistance device comprising: a vehicle speed sensor configured to detect vehicle speed of a vehicle; a steering angle sensor configured to detect a steering angle of a steering wheel; a controller configured to set a required braking/driving force according to an operation amount of an accelerator pedal or a brake pedal operated by a driver, set a target value of a vehicle body slip angle, the vehicle body slip angle being an angle from a longitudinal direction of a vehicle body to a travel direction of the vehicle, as a target slip angle, based on the vehicle speed and the steering angle, estimate or detect an actual slip angle based on at least the vehicle speed and the steering angle, the actual slip angle being an actual vehicle body slip angle, and set a target braking/driving force by, when a sign of the vehicle body slip angle rotating in a turning direction of the vehicle is defined as positive and a sign of the vehicle body slip angle rotating in an opposite direction to the turning direction is defined as negative, correcting the required braking/driving force in such a manner as to increase a braking/driving force for both of a rear right wheel and a rear left wheel or reduce a braking/driving force generated on both of a front right wheel and a front left wheel when the actual slip angle is larger than the target slip angle and correcting the required braking/driving force in such a manner as to reduce a braking/driving force for both of the rear right wheel and the rear left wheel or increase a braking/driving force generated on both of the front right wheel and the front left wheel when the actual slip angle is smaller than the target slip angle; and a driving force source or a braking device configured to generate the target braking/driving force in the vehicle and control the vehicle based on the generated target braking/driving force in the vehicle.
-