

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397878
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Hedlund; Michael A. et al.

Systems and methods of adjustable suspensions for off-road recreational vehicles

Abstract

A damping control system is provided for an off-road recreational vehicles having a suspension located between a ground engaging member and a vehicle frame and including at least one adjustable shock absorber having an adjustable damping characteristic based on an input from a sensor.

Inventors: Hedlund; Michael A. (Roseau, MN), Rhodes; Trevor F. (Badger, MN), Graus; Jonathon P. (Stacy, MN), Olson; Kyle W. (Coon Rapids, MN), Anderson; Justin T. (Stacy, MN)

Applicant: Polaris Industries Inc. (Medina, MN)

Family ID: 1000008779324

Assignee: Polaris Industries Inc. (Medina, MN)

Appl. No.: 17/325062

Filed: May 19, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210362806 A1	Nov. 25, 2021

Related U.S. Application Data

us-provisional-application US 63027833 20200520

Publication Classification

Int. Cl.: B60G17/019 (20060101); B60G17/015 (20060101); B62M27/02 (20060101)

U.S. Cl.:

CPC B62M27/02 (20130101); B60G17/015 (20130101); B60G2300/322 (20130101); B60G2500/10 (20130101); B60G2600/02 (20130101); B62M2027/025 (20130101); B62M2027/026

Field of Classification Search

CPC: B60G (17/019); B60G (17/015); B60G (2300/322); B60G (2500/10); B60W (10/22); B60W (30/045); B62M (27/02); B62M (2027/025); B62M (2027/026); B62M (2027/028)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3013442	12/1960	Fox et al.	N/A	N/A
3623565	12/1970	Ward et al.	N/A	N/A
3737001	12/1972	Rasenberger	N/A	N/A
3760246	12/1972	Wright et al.	N/A	N/A
3861229	12/1974	Domaas	N/A	N/A
3933213	12/1975	Trowbridge	N/A	N/A
3952829	12/1975	Gray	N/A	N/A
3982446	12/1975	Van Dyken	N/A	N/A
4075841	12/1977	Hamma et al.	N/A	N/A
4112885	12/1977	Iwata et al.	N/A	N/A
4116006	12/1977	Wallis	N/A	N/A
4319658	12/1981	Collonia et al.	N/A	N/A
4327948	12/1981	Beck et al.	N/A	N/A
4340126	12/1981	Larson	N/A	N/A
4453516	12/1983	Filsinger	N/A	N/A
4462480	12/1983	Yasui et al.	N/A	N/A
4508078	12/1984	Takeuchi et al.	N/A	N/A
4580537	12/1985	Uchiyama	N/A	N/A
4600215	12/1985	Kuroki et al.	N/A	N/A
4620602	12/1985	Capriotti	N/A	N/A
4658662	12/1986	Rundle	N/A	N/A
4671235	12/1986	Hosaka	N/A	N/A
4681292	12/1986	Thomas	267/132	B62J 1/02
4688533	12/1986	Otobe	N/A	N/A
4691676	12/1986	Kikuchi	N/A	N/A
4691677	12/1986	Hotate et al.	N/A	N/A
4722548	12/1987	Hamilton et al.	N/A	N/A
4741554	12/1987	Okamoto	N/A	N/A
4749210	12/1987	Sugasawa	N/A	N/A
4759329	12/1987	Nobuo et al.	N/A	N/A
4765296	12/1987	Ishikawa et al.	N/A	N/A
4770438	12/1987	Sugasawa et al.	N/A	N/A
4779895	12/1987	Rubel	N/A	N/A
4781162	12/1987	Ishikawa et al.	N/A	N/A
4785782	12/1987	Tanaka et al.	N/A	N/A
4787353	12/1987	Ishikawa et al.	N/A	N/A
4805923	12/1988	Soltis	N/A	N/A
4809179	12/1988	Klingler et al.	N/A	N/A
4809659	12/1988	Tamaki et al.	N/A	N/A
4817466	12/1988	Kawamura et al.	N/A	N/A
4819174	12/1988	Furuno et al.	N/A	N/A

4826205	12/1988	Kouda et al.	N/A	N/A
4827416	12/1988	Kawagoe et al.	N/A	N/A
4831533	12/1988	Skoeldheden	N/A	N/A
4838780	12/1988	Yamagata et al.	N/A	N/A
4856477	12/1988	Hanaoka et al.	N/A	N/A
4860708	12/1988	Yamaguchi et al.	N/A	N/A
4862854	12/1988	Oda et al.	N/A	N/A
4867474	12/1988	Smith	N/A	N/A
4881428	12/1988	Ishikawa et al.	N/A	N/A
4893501	12/1989	Sogawa	N/A	N/A
4895343	12/1989	Sato	N/A	N/A
4898137	12/1989	Fujita et al.	N/A	N/A
4898138	12/1989	Nishimura et al.	N/A	N/A
4901695	12/1989	Kabasin et al.	N/A	N/A
4903983	12/1989	Fukushima et al.	N/A	N/A
4905783	12/1989	Bober	N/A	N/A
4913006	12/1989	Tsuyama et al.	N/A	N/A
4919097	12/1989	Mitui et al.	N/A	N/A
4926636	12/1989	Tadokoro et al.	N/A	N/A
4927170	12/1989	Wada	N/A	N/A
4930082	12/1989	Harara et al.	N/A	N/A
4934667	12/1989	Pees et al.	N/A	N/A
4949262	12/1989	Buma et al.	N/A	N/A
4949989	12/1989	Kakizaki et al.	N/A	N/A
4961146	12/1989	Kajiwara	N/A	N/A
4966247	12/1989	Masuda	N/A	N/A
4969695	12/1989	Maehata et al.	N/A	N/A
5000278	12/1990	Morishita	N/A	N/A
5002028	12/1990	Arai et al.	N/A	N/A
5002148	12/1990	Miyake et al.	N/A	N/A
5015009	12/1990	Ohyama et al.	N/A	N/A
5018408	12/1990	Bota et al.	N/A	N/A
5024460	12/1990	Hanson et al.	N/A	N/A
5029328	12/1990	Kamimura et al.	N/A	N/A
5033328	12/1990	Shimanaka	N/A	N/A
5036939	12/1990	Johnson et al.	N/A	N/A
5037128	12/1990	Okuyama et al.	N/A	N/A
5040114	12/1990	Ishikawa et al.	N/A	N/A
5054813	12/1990	Kakizaki	N/A	N/A
5060744	12/1990	Katoh et al.	N/A	N/A
5062657	12/1990	Majeed	N/A	N/A
5071157	12/1990	Majeed	N/A	N/A
5071158	12/1990	Yonekawa et al.	N/A	N/A
5076385	12/1990	Terazawa et al.	N/A	N/A
5078109	12/1991	Yoshida et al.	N/A	N/A
5080392	12/1991	Bazergui	N/A	N/A
5083811	12/1991	Sato et al.	N/A	N/A
5088464	12/1991	Meaney	N/A	N/A
5090728	12/1991	Yokoya et al.	N/A	N/A
5092298	12/1991	Suzuki et al.	N/A	N/A
5092624	12/1991	Fukuyama et al.	N/A	N/A
5096219	12/1991	Hanson et al.	N/A	N/A
5105923	12/1991	Iizuka	N/A	N/A

5113345	12/1991	Mine et al.	N/A	N/A
5113821	12/1991	Fukui et al.	N/A	N/A
5114177	12/1991	Fukunaga et al.	N/A	N/A
5129475	12/1991	Kawano et al.	N/A	N/A
5134566	12/1991	Yokoya et al.	N/A	N/A
5144559	12/1991	Kamimura et al.	N/A	N/A
5150635	12/1991	Minowa et al.	N/A	N/A
5163538	12/1991	Derr et al.	N/A	N/A
5170343	12/1991	Matsuda	N/A	N/A
5174263	12/1991	Meaney	N/A	N/A
5189615	12/1992	Rubel et al.	N/A	N/A
5218540	12/1992	Ishikawa et al.	N/A	N/A
5233530	12/1992	Shimada et al.	N/A	N/A
5253728	12/1992	Matsuno et al.	N/A	N/A
5265693	12/1992	Rees et al.	N/A	N/A
5307777	12/1993	Sasajima et al.	N/A	N/A
5314362	12/1993	Nagahora	N/A	N/A
5315295	12/1993	Fujii	N/A	N/A
5337239	12/1993	Okuda	N/A	N/A
5342023	12/1993	Kuriki et al.	N/A	N/A
5343396	12/1993	Youngblood	N/A	N/A
5343780	12/1993	McDaniel et al.	N/A	N/A
5350187	12/1993	Shinozaki	N/A	N/A
5361209	12/1993	Tsutsumi	N/A	N/A
5361213	12/1993	Fujieda et al.	N/A	N/A
5362094	12/1993	Jensen	N/A	N/A
5366236	12/1993	Kuriki et al.	N/A	N/A
5375872	12/1993	Ohtagaki et al.	N/A	N/A
5377107	12/1993	Shimizu et al.	N/A	N/A
5383680	12/1994	Bock et al.	N/A	N/A
5384705	12/1994	Inagaki et al.	N/A	N/A
5390121	12/1994	Wolfe	N/A	N/A
5391127	12/1994	Nishimura	N/A	N/A
RE34906	12/1994	Tamaki et al.	N/A	N/A
5406920	12/1994	Murata et al.	N/A	N/A
5413540	12/1994	Streib et al.	N/A	N/A
5443558	12/1994	Ibaraki et al.	N/A	N/A
5444621	12/1994	Matsunaga et al.	N/A	N/A
5446663	12/1994	Sasaki et al.	N/A	N/A
5467751	12/1994	Kumagai	N/A	N/A
5475593	12/1994	Townend	N/A	N/A
5475596	12/1994	Henry et al.	N/A	N/A
5483448	12/1995	Liubakka et al.	N/A	N/A
5485161	12/1995	Vaughn	N/A	N/A
5487006	12/1995	Kakizaki et al.	N/A	N/A
5490487	12/1995	Kato et al.	N/A	N/A
5510985	12/1995	Yamaoka et al.	N/A	N/A
5514049	12/1995	Kamio et al.	N/A	N/A
5515273	12/1995	Sasaki et al.	N/A	N/A
5521825	12/1995	Unuvar et al.	N/A	N/A
5524724	12/1995	Nishigaki et al.	N/A	N/A
5550739	12/1995	Hoffmann et al.	N/A	N/A
5555499	12/1995	Yamashita et al.	N/A	N/A

5575737	12/1995	Weiss	N/A	N/A
5586032	12/1995	Kallenbach et al.	N/A	N/A
5611309	12/1996	Kumagai et al.	N/A	N/A
5632503	12/1996	Raad et al.	N/A	N/A
5645033	12/1996	Person et al.	N/A	N/A
5678847	12/1996	Izawa et al.	N/A	N/A
5713428	12/1997	Linden et al.	N/A	N/A
5749596	12/1997	Jensen et al.	N/A	N/A
5774820	12/1997	Linden et al.	N/A	N/A
5832398	12/1997	Sasaki et al.	N/A	N/A
5845726	12/1997	Kikkawa et al.	N/A	N/A
5873802	12/1998	Tabata et al.	N/A	N/A
5880532	12/1998	Stopher	N/A	N/A
5890870	12/1998	Berger et al.	N/A	N/A
5897287	12/1998	Berger et al.	N/A	N/A
5921889	12/1998	Nozaki et al.	N/A	N/A
5922038	12/1998	Horiuchi et al.	N/A	N/A
5938556	12/1998	Lowell	N/A	N/A
5957992	12/1998	Kiyono	N/A	N/A
5992558	12/1998	Noro et al.	N/A	N/A
6000702	12/1998	Streiter	N/A	N/A
6002975	12/1998	Schiffmann et al.	N/A	N/A
6016795	12/1999	Ohki	N/A	N/A
6019085	12/1999	Sato et al.	N/A	N/A
6032752	12/1999	Karpik et al.	N/A	N/A
6038500	12/1999	Weiss	N/A	N/A
6070681	12/1999	Catanzarite et al.	N/A	N/A
6073072	12/1999	Ishii et al.	N/A	N/A
6073074	12/1999	Saito et al.	N/A	N/A
6076027	12/1999	Raad et al.	N/A	N/A
6078252	12/1999	Kulczycki et al.	N/A	N/A
6086510	12/1999	Kadota	N/A	N/A
6094614	12/1999	Hiwatashi	N/A	N/A
6112866	12/1999	Boichot et al.	N/A	N/A
6120399	12/1999	Okeson et al.	N/A	N/A
6122568	12/1999	Madau et al.	N/A	N/A
6124826	12/1999	Garthwaite et al.	N/A	N/A
6125326	12/1999	Ohmura et al.	N/A	N/A
6125782	12/1999	Takashima et al.	N/A	N/A
6134499	12/1999	Goode et al.	N/A	N/A
6138069	12/1999	Ellertson et al.	N/A	N/A
6148252	12/1999	Iwasaki et al.	N/A	N/A
6154703	12/1999	Nakai et al.	N/A	N/A
6155545	12/1999	Noro et al.	N/A	N/A
6157297	12/1999	Nakai	N/A	N/A
6157890	12/1999	Nakai et al.	N/A	N/A
6161908	12/1999	Takayama et al.	N/A	N/A
6167341	12/1999	Gourmelen et al.	N/A	N/A
6170923	12/2000	Iguchi et al.	N/A	N/A
6176796	12/2000	Lislegard	N/A	N/A
6178371	12/2000	Light et al.	N/A	N/A
6181997	12/2000	Badenoch et al.	N/A	N/A
6192305	12/2000	Schiffmann	N/A	N/A

6206124	12/2000	Mallette et al.	N/A	N/A
6217480	12/2000	Iwata et al.	N/A	N/A
6226389	12/2000	Lemelson et al.	N/A	N/A
6240365	12/2000	Bunn	N/A	N/A
6244398	12/2000	Girvin et al.	N/A	N/A
6244986	12/2000	Mori et al.	N/A	N/A
6249728	12/2000	Streiter	N/A	N/A
6249744	12/2000	Morita	N/A	N/A
6254108	12/2000	Germain et al.	N/A	N/A
6260650	12/2000	Gustavsson	N/A	N/A
6263858	12/2000	Pursifull et al.	N/A	N/A
6275763	12/2000	Lotito et al.	N/A	N/A
6276333	12/2000	Kazama et al.	N/A	N/A
6288534	12/2000	Starkweather et al.	N/A	N/A
6290034	12/2000	Ichimaru	N/A	N/A
6318337	12/2000	Pursifull	N/A	N/A
6318490	12/2000	Laning	N/A	N/A
6343248	12/2001	Rizzotto et al.	N/A	N/A
6351704	12/2001	Koerner	N/A	N/A
6352142	12/2001	Kim	N/A	N/A
6370458	12/2001	Shal et al.	N/A	N/A
6370472	12/2001	Fosseen	N/A	N/A
6371884	12/2001	Channing	N/A	N/A
6379114	12/2001	Schott et al.	N/A	N/A
6427115	12/2001	Sekiyama	N/A	N/A
6456908	12/2001	Kumar	N/A	N/A
6463385	12/2001	Fry	N/A	N/A
6470852	12/2001	Kanno	N/A	N/A
6476714	12/2001	Mizuta	N/A	N/A
6483201	12/2001	Klarer	N/A	N/A
6483467	12/2001	Kushida et al.	N/A	N/A
6485340	12/2001	Kolb et al.	N/A	N/A
6488609	12/2001	Morimoto et al.	N/A	N/A
6502025	12/2001	Kempen	N/A	N/A
6507778	12/2002	Koh	N/A	N/A
6513611	12/2002	Ito et al.	N/A	N/A
6526342	12/2002	Burdock et al.	N/A	N/A
6551153	12/2002	Hattori	N/A	N/A
6573827	12/2002	McKenzie	N/A	N/A
6581710	12/2002	Sprinkle et al.	N/A	N/A
6604034	12/2002	Speck et al.	N/A	N/A
6644318	12/2002	Adams et al.	N/A	N/A
6647328	12/2002	Walker	N/A	N/A
6655233	12/2002	Evans et al.	N/A	N/A
6657539	12/2002	Yamamoto et al.	N/A	N/A
6675577	12/2003	Evans	N/A	N/A
6684140	12/2003	Lu	N/A	N/A
6685174	12/2003	Behmenburg et al.	N/A	N/A
6699085	12/2003	Hattori	N/A	N/A
6704643	12/2003	Suhre et al.	N/A	N/A
6738705	12/2003	Kojima et al.	N/A	N/A
6738708	12/2003	Suzuki et al.	N/A	N/A
6752401	12/2003	Burdock	N/A	N/A

6757606	12/2003	Gonring	N/A	N/A
6761145	12/2003	Matsuda et al.	N/A	N/A
6772061	12/2003	Berthiaume et al.	N/A	N/A
6795764	12/2003	Schmitz et al.	N/A	N/A
6820712	12/2003	Nakamura	N/A	N/A
6834736	12/2003	Kramer et al.	N/A	N/A
6839630	12/2004	Sakamoto	N/A	N/A
6845314	12/2004	Fosseen	N/A	N/A
6845829	12/2004	Hafendorfer	N/A	N/A
6848420	12/2004	Ishiguro et al.	N/A	N/A
6848956	12/2004	Ozawa	N/A	N/A
6851495	12/2004	Sprinkle et al.	N/A	N/A
6851679	12/2004	Downey et al.	N/A	N/A
6860826	12/2004	Johnson	N/A	N/A
6874467	12/2004	Hunt et al.	N/A	N/A
6876924	12/2004	Morita et al.	N/A	N/A
6880532	12/2004	Kerns et al.	N/A	N/A
6886529	12/2004	Suzuki et al.	N/A	N/A
6887182	12/2004	Nakatani et al.	N/A	N/A
6889654	12/2004	Ito	N/A	N/A
6895318	12/2004	Barton et al.	N/A	N/A
6895518	12/2004	Wingen	N/A	N/A
6897629	12/2004	Wilton et al.	N/A	N/A
6938508	12/2004	Saagge	N/A	N/A
6941209	12/2004	Liu	N/A	N/A
6942050	12/2004	Honkala et al.	N/A	N/A
6945541	12/2004	Brown	N/A	N/A
6964259	12/2004	Raetzman	N/A	N/A
6964260	12/2004	Samoto et al.	N/A	N/A
6976689	12/2004	Hibbert	N/A	N/A
6990401	12/2005	Neiss et al.	N/A	N/A
7005976	12/2005	Hagenbuch	N/A	N/A
7011174	12/2005	James	N/A	N/A
7032895	12/2005	Folchert	N/A	N/A
7035836	12/2005	Caponetto et al.	N/A	N/A
7036485	12/2005	Koerner	N/A	N/A
7044260	12/2005	Schaedler et al.	N/A	N/A
7055454	12/2005	Whiting et al.	N/A	N/A
7055497	12/2005	Maehara et al.	N/A	N/A
7055545	12/2005	Mascari et al.	N/A	N/A
7058490	12/2005	Kim	N/A	N/A
7058506	12/2005	Kawase et al.	N/A	N/A
7066142	12/2005	Hanasato	N/A	N/A
7070012	12/2005	Fecteau	N/A	N/A
7076351	12/2005	Hamilton et al.	N/A	N/A
7077713	12/2005	Watabe et al.	N/A	N/A
7077784	12/2005	Banta et al.	N/A	N/A
7086379	12/2005	Blomenberg et al.	N/A	N/A
7092808	12/2005	Lu et al.	N/A	N/A
7096851	12/2005	Matsuda et al.	N/A	N/A
7097166	12/2005	Folchert	N/A	N/A
7104352	12/2005	Weinzierl	N/A	N/A
7123189	12/2005	Lalik et al.	N/A	N/A

7124865	12/2005	Turner et al.	N/A	N/A
7136729	12/2005	Salman et al.	N/A	N/A
7140619	12/2005	Hrovat et al.	N/A	N/A
7163000	12/2006	Ishida et al.	N/A	N/A
7168709	12/2006	Niwa et al.	N/A	N/A
7171945	12/2006	Matsuda et al.	N/A	N/A
7171947	12/2006	Fukushima et al.	N/A	N/A
7182063	12/2006	Keefover et al.	N/A	N/A
7184873	12/2006	Idsinga et al.	N/A	N/A
7185630	12/2006	Takahashi et al.	N/A	N/A
7220153	12/2006	Okuyama	N/A	N/A
7233846	12/2006	Kawauchi et al.	N/A	N/A
7234707	12/2006	Green et al.	N/A	N/A
7235963	12/2006	Wayama	N/A	N/A
7249986	12/2006	Otobe et al.	N/A	N/A
7259357	12/2006	Walker	N/A	N/A
7260319	12/2006	Watanabe et al.	N/A	N/A
7260471	12/2006	Matsuda et al.	N/A	N/A
7270335	12/2006	Hio et al.	N/A	N/A
7280904	12/2006	Kaji	N/A	N/A
7286919	12/2006	Nordgren et al.	N/A	N/A
7287511	12/2006	Matsuda	N/A	N/A
7287760	12/2006	Quick et al.	N/A	N/A
7305295	12/2006	Bauerle et al.	N/A	N/A
7311082	12/2006	Yokoi	N/A	N/A
7315779	12/2007	Rioux et al.	N/A	N/A
7316288	12/2007	Bennett et al.	N/A	N/A
7318410	12/2007	Yokoi	N/A	N/A
7322435	12/2007	Lillbacka et al.	N/A	N/A
7325533	12/2007	Matsuda	N/A	N/A
7331326	12/2007	Arai et al.	N/A	N/A
7354321	12/2007	Takada et al.	N/A	N/A
7359787	12/2007	Ono et al.	N/A	N/A
7367247	12/2007	Horiuchi et al.	N/A	N/A
7367316	12/2007	Russell et al.	N/A	N/A
7367854	12/2007	Arvidsson	N/A	N/A
7380538	12/2007	Gagnon et al.	N/A	N/A
7386378	12/2007	Lauwerys et al.	N/A	N/A
7399210	12/2007	Yoshimasa	N/A	N/A
7401794	12/2007	Laurent et al.	N/A	N/A
7413196	12/2007	Borowski	N/A	N/A
7416458	12/2007	Suemori et al.	N/A	N/A
7421954	12/2007	Bose	N/A	N/A
7422495	12/2007	Kinoshita et al.	N/A	N/A
7427072	12/2007	Brown	N/A	N/A
7431013	12/2007	Hotta et al.	N/A	N/A
7433774	12/2007	Sen et al.	N/A	N/A
7441789	12/2007	Geiger et al.	N/A	N/A
7445071	12/2007	Yamazaki et al.	N/A	N/A
7454282	12/2007	Mizuguchi	N/A	N/A
7454284	12/2007	Fosseen	N/A	N/A
7458360	12/2007	Irihune et al.	N/A	N/A
7461630	12/2007	Maruo et al.	N/A	N/A

7475746	12/2008	Tsukada et al.	N/A	N/A
7478689	12/2008	Sugden et al.	N/A	N/A
7483775	12/2008	Karaba et al.	N/A	N/A
7486199	12/2008	Tengler et al.	N/A	N/A
7505836	12/2008	Okuyama et al.	N/A	N/A
7506633	12/2008	Cowan	N/A	N/A
7510060	12/2008	Izawa et al.	N/A	N/A
7523737	12/2008	Deguchi et al.	N/A	N/A
7526665	12/2008	Kim et al.	N/A	N/A
7529609	12/2008	Braunberger et al.	N/A	N/A
7530345	12/2008	Plante et al.	N/A	N/A
7533750	12/2008	Simmons et al.	N/A	N/A
7533890	12/2008	Chiao	N/A	N/A
7571039	12/2008	Chen et al.	N/A	N/A
7571073	12/2008	Gamberini et al.	N/A	N/A
7598849	12/2008	Gallant et al.	N/A	N/A
7600762	12/2008	Yasui et al.	N/A	N/A
7611154	12/2008	Delaney	N/A	N/A
7630807	12/2008	Yoshimura et al.	N/A	N/A
7641208	12/2009	Barron et al.	N/A	N/A
7644934	12/2009	Mizuta	N/A	N/A
7647143	12/2009	Ito et al.	N/A	N/A
7684911	12/2009	Seifert et al.	N/A	N/A
7707012	12/2009	Stephens	N/A	N/A
7711468	12/2009	Levy	N/A	N/A
7740256	12/2009	Davis	N/A	N/A
7751959	12/2009	Boon et al.	N/A	N/A
7771313	12/2009	Cullen et al.	N/A	N/A
7778741	12/2009	Rao et al.	N/A	N/A
7810818	12/2009	Bushko	N/A	N/A
7815205	12/2009	Barth et al.	N/A	N/A
7822514	12/2009	Erickson	N/A	N/A
7823106	12/2009	Baker et al.	N/A	N/A
7823891	12/2009	Bushko et al.	N/A	N/A
7826959	12/2009	Namari et al.	N/A	N/A
7862061	12/2010	Jung	N/A	N/A
7885750	12/2010	Lu	N/A	N/A
7899594	12/2010	Messih et al.	N/A	N/A
7912610	12/2010	Saito et al.	N/A	N/A
7926822	12/2010	Ohletz et al.	N/A	N/A
7940383	12/2010	Noguchi et al.	N/A	N/A
7942427	12/2010	Lloyd	N/A	N/A
7950486	12/2010	Van et al.	N/A	N/A
7959163	12/2010	Beno et al.	N/A	N/A
7962261	12/2010	Bushko et al.	N/A	N/A
7963529	12/2010	Oteman et al.	N/A	N/A
7970512	12/2010	Lu et al.	N/A	N/A
7975794	12/2010	Simmons	N/A	N/A
7984915	12/2010	Post et al.	N/A	N/A
8005596	12/2010	Lu et al.	N/A	N/A
8027775	12/2010	Takenaka et al.	N/A	N/A
8032281	12/2010	Bujak et al.	N/A	N/A
8050818	12/2010	Mizuta	N/A	N/A

8050857	12/2010	Lu et al.	N/A	N/A
8056392	12/2010	Ryan et al.	N/A	N/A
8065054	12/2010	Tarasinski et al.	N/A	N/A
8075002	12/2010	Pionke et al.	N/A	N/A
8086371	12/2010	Furuichi et al.	N/A	N/A
8087676	12/2011	McIntyre	N/A	N/A
8095268	12/2011	Parison et al.	N/A	N/A
8108104	12/2011	Hrovat et al.	N/A	N/A
8113521	12/2011	Lin et al.	N/A	N/A
8116938	12/2011	Itagaki et al.	N/A	N/A
8121757	12/2011	Song et al.	N/A	N/A
8170749	12/2011	Mizuta	N/A	N/A
8190327	12/2011	Poilbout	N/A	N/A
8195361	12/2011	Kajino et al.	N/A	N/A
8204666	12/2011	Takeuchi et al.	N/A	N/A
8209087	12/2011	Haeggglund et al.	N/A	N/A
8214106	12/2011	Ghoneim et al.	N/A	N/A
8219262	12/2011	Stiller	N/A	N/A
8229642	12/2011	Post et al.	N/A	N/A
8260496	12/2011	Gagliano	N/A	N/A
8271175	12/2011	Takenaka et al.	N/A	N/A
8296010	12/2011	Hirao et al.	N/A	N/A
8308170	12/2011	Van et al.	N/A	N/A
8315764	12/2011	Chen et al.	N/A	N/A
8315769	12/2011	Braunberger et al.	N/A	N/A
8321088	12/2011	Brown et al.	N/A	N/A
8322497	12/2011	Marjoram et al.	N/A	N/A
8352143	12/2012	Lu et al.	N/A	N/A
8355840	12/2012	Ammon et al.	N/A	N/A
8359149	12/2012	Shin	N/A	N/A
8374748	12/2012	Jolly	N/A	N/A
8376373	12/2012	Conradie	N/A	N/A
8396627	12/2012	Jung et al.	N/A	N/A
8417417	12/2012	Chen et al.	N/A	N/A
8424832	12/2012	Robbins et al.	N/A	N/A
8428839	12/2012	Braunberger et al.	N/A	N/A
8434774	12/2012	Leclerc et al.	N/A	N/A
8437935	12/2012	Braunberger et al.	N/A	N/A
8442720	12/2012	Lu et al.	N/A	N/A
8444161	12/2012	Leclerc et al.	N/A	N/A
8447489	12/2012	Murata et al.	N/A	N/A
8457841	12/2012	Knoll et al.	N/A	N/A
8473157	12/2012	Savaresi et al.	N/A	N/A
8517395	12/2012	Knox et al.	N/A	N/A
8532896	12/2012	Braunberger et al.	N/A	N/A
8534397	12/2012	Grajkowski et al.	N/A	N/A
8534413	12/2012	Nelson et al.	N/A	N/A
8548678	12/2012	Ummethala et al.	N/A	N/A
8550221	12/2012	Paulides et al.	N/A	N/A
8571776	12/2012	Braunberger et al.	N/A	N/A
8573605	12/2012	Di Maria	N/A	N/A
8626388	12/2013	Oikawa	N/A	N/A
8626389	12/2013	Sidlosky	N/A	N/A

8641052	12/2013	Kondo et al.	N/A	N/A
8645024	12/2013	Daniels	N/A	N/A
8666596	12/2013	Arenz	N/A	N/A
8672106	12/2013	Laird et al.	N/A	N/A
8672337	12/2013	Van et al.	N/A	N/A
8676440	12/2013	Watson	N/A	N/A
8682530	12/2013	Nakamura	N/A	N/A
8682550	12/2013	Nelson et al.	N/A	N/A
8682558	12/2013	Braunberger et al.	N/A	N/A
8684887	12/2013	Krosschell	N/A	N/A
8700260	12/2013	Jolly et al.	N/A	N/A
8712599	12/2013	Westpfahl	N/A	N/A
8712639	12/2013	Lu et al.	N/A	N/A
8718872	12/2013	Hirao et al.	N/A	N/A
8725351	12/2013	Selden et al.	N/A	N/A
8725380	12/2013	Braunberger et al.	N/A	N/A
8731774	12/2013	Yang	N/A	N/A
8770594	12/2013	Tominaga et al.	N/A	N/A
8827019	12/2013	Deckard et al.	N/A	N/A
8903617	12/2013	Braunberger et al.	N/A	N/A
8954251	12/2014	Braunberger et al.	N/A	N/A
8972712	12/2014	Braunberger	N/A	N/A
8994494	12/2014	Koenig et al.	N/A	N/A
8997952	12/2014	Goetz	N/A	N/A
9010768	12/2014	Kinsman et al.	N/A	N/A
9022156	12/2014	Bedard	N/A	N/A
9027937	12/2014	Ryan et al.	N/A	N/A
9038791	12/2014	Marking	N/A	N/A
9123249	12/2014	Braunberger et al.	N/A	N/A
9151384	12/2014	Kohler et al.	N/A	N/A
9162573	12/2014	Grajkowski et al.	N/A	N/A
9205717	12/2014	Brady et al.	N/A	N/A
9211924	12/2014	Safranski et al.	N/A	N/A
9327726	12/2015	Braunberger et al.	N/A	N/A
9327789	12/2015	Vezina et al.	N/A	N/A
9365251	12/2015	Safranski et al.	N/A	N/A
9371002	12/2015	Braunberger	N/A	N/A
9381810	12/2015	Nelson et al.	N/A	N/A
9381902	12/2015	Braunberger et al.	N/A	N/A
9428028	12/2015	Hawksworth	N/A	N/A
9428242	12/2015	Ginther et al.	N/A	N/A
9429235	12/2015	Krosschell et al.	N/A	N/A
9527362	12/2015	Scheuerell et al.	N/A	N/A
9643538	12/2016	Braunberger et al.	N/A	N/A
9643616	12/2016	Lu	N/A	B60W 30/045
9662954	12/2016	Scheuerell et al.	N/A	N/A
9665418	12/2016	Arnott	N/A	N/A
9695899	12/2016	Smith	N/A	N/A
9771084	12/2016	Norstad	N/A	N/A
9802621	12/2016	Gillingham et al.	N/A	N/A
9809195	12/2016	Giese et al.	N/A	N/A
9830821	12/2016	Braunberger et al.	N/A	N/A
9834184	12/2016	Braunberger	N/A	N/A

9834215	12/2016	Braunberger et al.	N/A	N/A
9855986	12/2017	Braunberger et al.	N/A	N/A
9868385	12/2017	Braunberger	N/A	N/A
9878693	12/2017	Braunberger	N/A	N/A
9920810	12/2017	Smeljanskij	N/A	N/A
9945298	12/2017	Braunberger et al.	N/A	N/A
10005335	12/2017	Brady et al.	N/A	N/A
10046694	12/2017	Braunberger et al.	N/A	N/A
10086698	12/2017	Grajkowski et al.	N/A	N/A
10154377	12/2017	Post et al.	N/A	N/A
10195989	12/2018	Braunberger et al.	N/A	N/A
10202159	12/2018	Braunberger et al.	N/A	N/A
10220765	12/2018	Braunberger	N/A	N/A
10227041	12/2018	Braunberger et al.	N/A	N/A
10266164	12/2018	Braunberger	N/A	N/A
10363941	12/2018	Norstad	N/A	N/A
10384682	12/2018	Braunberger et al.	N/A	N/A
10391989	12/2018	Braunberger	N/A	N/A
10406884	12/2018	Oakden-Graus et al.	N/A	N/A
10410520	12/2018	Braunberger et al.	N/A	N/A
10436125	12/2018	Braunberger et al.	N/A	N/A
10578184	12/2019	Gilbert	N/A	N/A
10704640	12/2019	Galasso	N/A	N/A
10723408	12/2019	Pelot	N/A	N/A
10731724	12/2019	Laird	N/A	N/A
10774896	12/2019	Hamers	N/A	N/A
10933710	12/2020	Tong	N/A	N/A
10981429	12/2020	Tsiaras	N/A	N/A
11001120	12/2020	Cox	N/A	N/A
11110913	12/2020	Krosschell et al.	N/A	N/A
11124036	12/2020	Brady et al.	N/A	N/A
11148748	12/2020	Galasso	N/A	N/A
11152555	12/2020	Hiller	N/A	N/A
11162555	12/2020	Haugen	N/A	N/A
11192424	12/2020	Tabata	N/A	N/A
11235634	12/2021	Lavallee	N/A	N/A
11279198	12/2021	Marking	N/A	N/A
11285964	12/2021	Norstad et al.	N/A	N/A
11306798	12/2021	Cox	N/A	N/A
11351834	12/2021	Cox	N/A	N/A
11400784	12/2021	Brady et al.	N/A	N/A
11400785	12/2021	Brady et al.	N/A	N/A
11400786	12/2021	Brady et al.	N/A	N/A
11400787	12/2021	Brady et al.	N/A	N/A
11413924	12/2021	Cox	N/A	N/A
11448283	12/2021	Strickland	N/A	N/A
11472252	12/2021	Tong	N/A	N/A
11479075	12/2021	Graus et al.	N/A	N/A
11975584	12/2023	Graus et al.	N/A	N/A
2001/0005803	12/2000	Cochofel et al.	N/A	N/A
2001/0021887	12/2000	Obradovich et al.	N/A	N/A
2001/0035166	12/2000	Kerns et al.	N/A	N/A
2001/0052756	12/2000	Noro et al.	N/A	N/A

2002/0045977	12/2001	Uchiyama et al.	N/A	N/A
2002/0082752	12/2001	Obradovich	N/A	N/A
2002/0113185	12/2001	Ziegler	N/A	N/A
2002/0115357	12/2001	Hiki et al.	N/A	N/A
2002/0125675	12/2001	Clements et al.	N/A	N/A
2002/0177949	12/2001	Katayama et al.	N/A	N/A
2002/0193935	12/2001	Hashimoto et al.	N/A	N/A
2003/0014174	12/2002	Giers	N/A	N/A
2003/0036360	12/2002	Russell et al.	N/A	N/A
2003/0036823	12/2002	Mahvi	N/A	N/A
2003/0038411	12/2002	Sendrea	N/A	N/A
2003/0046000	12/2002	Morita et al.	N/A	N/A
2003/0047994	12/2002	Koh	N/A	N/A
2003/0054831	12/2002	Bardmesser	N/A	N/A
2003/0062025	12/2002	Samoto et al.	N/A	N/A
2003/0125857	12/2002	Madau et al.	N/A	N/A
2003/0187555	12/2002	Lutz et al.	N/A	N/A
2003/0200016	12/2002	Spillane et al.	N/A	N/A
2003/0205867	12/2002	Coelingh et al.	N/A	N/A
2004/0010383	12/2003	Lu et al.	N/A	N/A
2004/0015275	12/2003	Herzog et al.	N/A	N/A
2004/0024515	12/2003	Troupe et al.	N/A	N/A
2004/0026880	12/2003	Bundy	N/A	N/A
2004/0034460	12/2003	Folkerts et al.	N/A	N/A
2004/0041358	12/2003	Hrovat et al.	N/A	N/A
2004/0090020	12/2003	Braswell	N/A	N/A
2004/0094912	12/2003	Niwa et al.	N/A	N/A
2004/0107591	12/2003	Cuddy	N/A	N/A
2004/0216550	12/2003	Fallak et al.	N/A	N/A
2004/0226538	12/2003	Cannone et al.	N/A	N/A
2004/0245034	12/2003	Miyamoto et al.	N/A	N/A
2005/0004736	12/2004	Belcher et al.	N/A	N/A
2005/0023789	12/2004	Suzuki et al.	N/A	N/A
2005/0027428	12/2004	Gloria et al.	N/A	N/A
2005/0045148	12/2004	Katsuragawa et al.	N/A	N/A
2005/0077696	12/2004	Ogawa	N/A	N/A
2005/0098964	12/2004	Brown	N/A	N/A
2005/0131604	12/2004	Lu	N/A	N/A
2005/0133006	12/2004	Frenz et al.	N/A	N/A
2005/0149246	12/2004	McLeod	N/A	N/A
2005/0155571	12/2004	Hanasato	N/A	N/A
2005/0178628	12/2004	Uchino et al.	N/A	N/A
2005/0217953	12/2004	Bossard	N/A	N/A
2005/0267663	12/2004	Naono et al.	N/A	N/A
2005/0279244	12/2004	Bose	N/A	N/A
2005/0280219	12/2004	Brown	N/A	N/A
2005/0284446	12/2004	Okuyama	N/A	N/A
2006/0014606	12/2005	Sporl et al.	N/A	N/A
2006/0017240	12/2005	Laurent et al.	N/A	N/A
2006/0018636	12/2005	Watanabe et al.	N/A	N/A
2006/0052909	12/2005	Cherouny	N/A	N/A
2006/0064223	12/2005	Voss	N/A	N/A
2006/0065239	12/2005	Tsukada et al.	N/A	N/A

2006/0112930	12/2005	Matsuda et al.	N/A	N/A
2006/0162681	12/2005	Kawasaki	N/A	N/A
2006/0191739	12/2005	Koga	N/A	N/A
2006/0224294	12/2005	Kawazoe et al.	N/A	N/A
2006/0226611	12/2005	Xiao et al.	N/A	N/A
2006/0229811	12/2005	Herman et al.	N/A	N/A
2006/0235602	12/2005	Ishida et al.	N/A	N/A
2006/0243246	12/2005	Yokoi	N/A	N/A
2006/0243247	12/2005	Yokoi	N/A	N/A
2006/0247840	12/2005	Matsuda et al.	N/A	N/A
2006/0270520	12/2005	Owens	N/A	N/A
2006/0278197	12/2005	Takamatsu et al.	N/A	N/A
2006/0284387	12/2005	Klees	N/A	N/A
2007/0007742	12/2006	Allen	N/A	N/A
2007/0028888	12/2006	Jasem	N/A	N/A
2007/0039770	12/2006	Barrette et al.	N/A	N/A
2007/0045028	12/2006	Yamamoto et al.	N/A	N/A
2007/0050095	12/2006	Nelson et al.	N/A	N/A
2007/0050125	12/2006	Matsuda et al.	N/A	N/A
2007/0068490	12/2006	Matsuda	N/A	N/A
2007/0073461	12/2006	Fielder	N/A	N/A
2007/0096672	12/2006	Endo et al.	N/A	N/A
2007/0118268	12/2006	Inoue et al.	N/A	N/A
2007/0119419	12/2006	Matsuda	N/A	N/A
2007/0120332	12/2006	Bushko et al.	N/A	N/A
2007/0126628	12/2006	Lalik et al.	N/A	N/A
2007/0142167	12/2006	Kanafani et al.	N/A	N/A
2007/0151544	12/2006	Arai et al.	N/A	N/A
2007/0158920	12/2006	Delaney	N/A	N/A
2007/0168125	12/2006	Petrik	N/A	N/A
2007/0169744	12/2006	Maruo et al.	N/A	N/A
2007/0178779	12/2006	Takada et al.	N/A	N/A
2007/0192001	12/2006	Tatsumi et al.	N/A	N/A
2007/0213920	12/2006	Igarashi et al.	N/A	N/A
2007/0227796	12/2006	Simmons et al.	N/A	N/A
2007/0239331	12/2006	Kaplan	N/A	N/A
2007/0240917	12/2006	Duceppe	N/A	N/A
2007/0244619	12/2006	Peterson	N/A	N/A
2007/0246010	12/2006	Okuyama et al.	N/A	N/A
2007/0247291	12/2006	Masuda et al.	N/A	N/A
2007/0255462	12/2006	Masuda et al.	N/A	N/A
2007/0255466	12/2006	Chiao	N/A	N/A
2007/0260372	12/2006	Langer	N/A	N/A
2007/0271026	12/2006	Hijikata	N/A	N/A
2007/0294008	12/2006	Yasui et al.	N/A	N/A
2008/0004773	12/2007	Maeda	N/A	N/A
2008/0015767	12/2007	Masuda et al.	N/A	N/A
2008/0022969	12/2007	Frenz et al.	N/A	N/A
2008/0059034	12/2007	Lu	N/A	N/A
2008/0078355	12/2007	Maehara et al.	N/A	N/A
2008/0091309	12/2007	Walker	N/A	N/A
2008/0114521	12/2007	Doering	N/A	N/A
2008/0115761	12/2007	Deguchi et al.	N/A	N/A

2008/0119984	12/2007	Hrovat et al.	N/A	N/A
2008/0172155	12/2007	Takamatsu et al.	N/A	N/A
2008/0178838	12/2007	Ota	N/A	N/A
2008/0178839	12/2007	Oshima et al.	N/A	N/A
2008/0178840	12/2007	Oshima et al.	N/A	N/A
2008/0183353	12/2007	Post et al.	N/A	N/A
2008/0243334	12/2007	Bujak et al.	N/A	N/A
2008/0243336	12/2007	Fitzgibbons	N/A	N/A
2008/0269989	12/2007	Brenner et al.	N/A	N/A
2008/0275606	12/2007	Tarasinski et al.	N/A	N/A
2008/0287256	12/2007	Unno	N/A	N/A
2008/0300768	12/2007	Hijikata	N/A	N/A
2009/0008890	12/2008	Woodford	N/A	N/A
2009/0020966	12/2008	Germain	N/A	N/A
2009/0037051	12/2008	Shimizu et al.	N/A	N/A
2009/0071437	12/2008	Samoto et al.	N/A	N/A
2009/0076699	12/2008	Osaki et al.	N/A	N/A
2009/0093928	12/2008	Getman et al.	N/A	N/A
2009/0095252	12/2008	Yamada	N/A	N/A
2009/0095254	12/2008	Yamada	N/A	N/A
2009/0096598	12/2008	Tengler et al.	N/A	N/A
2009/0108546	12/2008	Ohletz et al.	N/A	N/A
2009/0132154	12/2008	Fuwa et al.	N/A	N/A
2009/0171546	12/2008	Tozuka et al.	N/A	N/A
2009/0173562	12/2008	Namari et al.	N/A	N/A
2009/0229568	12/2008	Nakagawa	N/A	N/A
2009/0234534	12/2008	Stempnik et al.	N/A	N/A
2009/0240427	12/2008	Siereveld et al.	N/A	N/A
2009/0243339	12/2008	Orr et al.	N/A	N/A
2009/0254249	12/2008	Ghoneim et al.	N/A	N/A
2009/0254259	12/2008	The	N/A	N/A
2009/0261542	12/2008	McIntyre	N/A	N/A
2009/0287392	12/2008	Thomas	N/A	N/A
2009/0308682	12/2008	Ripley et al.	N/A	N/A
2009/0312147	12/2008	Oshima et al.	N/A	N/A
2009/0321167	12/2008	Simmons	N/A	N/A
2010/0012399	12/2009	Hansen	N/A	N/A
2010/0016120	12/2009	Dickinson et al.	N/A	N/A
2010/0017059	12/2009	Lu et al.	N/A	N/A
2010/0017070	12/2009	Doering et al.	N/A	N/A
2010/0023236	12/2009	Morgan et al.	N/A	N/A
2010/0057297	12/2009	Itagaki et al.	N/A	N/A
2010/0059964	12/2009	Morris	N/A	N/A
2010/0109277	12/2009	Furrer	N/A	N/A
2010/0113214	12/2009	Krueger et al.	N/A	N/A
2010/0121529	12/2009	Savaresi et al.	N/A	N/A
2010/0131131	12/2009	Kamio et al.	N/A	N/A
2010/0138142	12/2009	Pease	N/A	N/A
2010/0140009	12/2009	Kamen et al.	N/A	N/A
2010/0145579	12/2009	O'Brien	N/A	N/A
2010/0145581	12/2009	Hou	N/A	N/A
2010/0145595	12/2009	Bellistri et al.	N/A	N/A
2010/0152969	12/2009	Li et al.	N/A	N/A

2010/0181416	12/2009	Sakamoto et al.	N/A	N/A
2010/0191420	12/2009	Honma et al.	N/A	N/A
2010/0203933	12/2009	Eyzaguirre et al.	N/A	N/A
2010/0211261	12/2009	Sasaki et al.	N/A	N/A
2010/0219004	12/2009	MacKenzie	N/A	N/A
2010/0230876	12/2009	Inoue et al.	N/A	N/A
2010/0238129	12/2009	Nakanishi et al.	N/A	N/A
2010/0252972	12/2009	Cox et al.	N/A	N/A
2010/0253018	12/2009	Peterson	N/A	N/A
2010/0259018	12/2009	Honig et al.	N/A	N/A
2010/0276906	12/2009	Galasso et al.	N/A	N/A
2010/0282210	12/2009	Itagaki	N/A	N/A
2010/0301571	12/2009	Van et al.	N/A	N/A
2011/0022266	12/2010	Ippolito et al.	N/A	N/A
2011/0035089	12/2010	Hirao et al.	N/A	N/A
2011/0035105	12/2010	Jolly	N/A	N/A
2011/0036656	12/2010	Nicoson	N/A	N/A
2011/0074123	12/2010	Fought et al.	N/A	N/A
2011/0109060	12/2010	Earle et al.	N/A	N/A
2011/0153158	12/2010	Acocella	N/A	N/A
2011/0166744	12/2010	Lu et al.	N/A	N/A
2011/0186360	12/2010	Brehob et al.	N/A	N/A
2011/0190972	12/2010	Timmons et al.	N/A	N/A
2011/0270509	12/2010	Whitney et al.	N/A	N/A
2011/0297462	12/2010	Grajkowski et al.	N/A	N/A
2011/0297463	12/2010	Grajkowski et al.	N/A	N/A
2011/0301824	12/2010	Nelson et al.	N/A	N/A
2011/0301825	12/2010	Grajkowski et al.	N/A	N/A
2011/0307155	12/2010	Simard	N/A	N/A
2012/0017871	12/2011	Matsuda	N/A	N/A
2012/0018263	12/2011	Marking	N/A	N/A
2012/0029770	12/2011	Hirao et al.	N/A	N/A
2012/0053790	12/2011	Oikawa	N/A	N/A
2012/0053791	12/2011	Harada	N/A	N/A
2012/0055745	12/2011	Buettner et al.	N/A	N/A
2012/0065860	12/2011	Isaji et al.	N/A	N/A
2012/0078470	12/2011	Hirao et al.	N/A	N/A
2012/0119454	12/2011	Di Maria	N/A	N/A
2012/0136506	12/2011	Takeuchi et al.	N/A	N/A
2012/0139328	12/2011	Brown et al.	N/A	N/A
2012/0168268	12/2011	Bruno et al.	N/A	N/A
2012/0191301	12/2011	Benyo et al.	N/A	N/A
2012/0191302	12/2011	Sternecker et al.	N/A	N/A
2012/0222908	12/2011	Mangum	N/A	N/A
2012/0222927	12/2011	Marking	N/A	N/A
2012/0247888	12/2011	Chikuma et al.	N/A	N/A
2012/0253601	12/2011	Ichida et al.	N/A	N/A
2012/0265402	12/2011	Post et al.	N/A	N/A
2012/0277953	12/2011	Savaresi et al.	N/A	N/A
2013/0009350	12/2012	Wolf-Monheim	N/A	N/A
2013/0018559	12/2012	Epple et al.	N/A	N/A
2013/0030650	12/2012	Norris et al.	N/A	N/A
2013/0041545	12/2012	Baer et al.	N/A	N/A

2013/0060423	12/2012	Jolly	N/A	N/A
2013/0060444	12/2012	Matsunaga et al.	N/A	N/A
2013/0074487	12/2012	Herold et al.	N/A	N/A
2013/0079988	12/2012	Hirao et al.	N/A	N/A
2013/0092468	12/2012	Nelson et al.	N/A	N/A
2013/0096784	12/2012	Kohler et al.	N/A	N/A
2013/0096785	12/2012	Kohler et al.	N/A	N/A
2013/0096793	12/2012	Krosschell	N/A	N/A
2013/0103259	12/2012	Eng et al.	N/A	N/A
2013/0124045	12/2012	Suzuki et al.	N/A	N/A
2013/0158799	12/2012	Kamimura	N/A	N/A
2013/0161921	12/2012	Cheng et al.	N/A	N/A
2013/0173119	12/2012	Izawa	N/A	N/A
2013/0190980	12/2012	Ramirez Ruiz	N/A	N/A
2013/0197732	12/2012	Pearlman et al.	N/A	N/A
2013/0197756	12/2012	Ramirez Ruiz	N/A	N/A
2013/0218414	12/2012	Meitinger et al.	N/A	N/A
2013/0226405	12/2012	Koumura et al.	N/A	N/A
2013/0253770	12/2012	Nishikawa et al.	N/A	N/A
2013/0261893	12/2012	Yang	N/A	N/A
2013/0304319	12/2012	Daniels	N/A	N/A
2013/0328277	12/2012	Ryan et al.	N/A	N/A
2013/0334394	12/2012	Parison et al.	N/A	N/A
2013/0338869	12/2012	Tsumano	N/A	N/A
2013/0341143	12/2012	Brown	N/A	N/A
2013/0345933	12/2012	Norton et al.	N/A	N/A
2014/0001717	12/2013	Giovanardi et al.	N/A	N/A
2014/0005888	12/2013	Bose et al.	N/A	N/A
2014/0012467	12/2013	Knox et al.	N/A	N/A
2014/0038755	12/2013	Ijichi et al.	N/A	N/A
2014/0046539	12/2013	Wijffels et al.	N/A	N/A
2014/0058606	12/2013	Hilton	N/A	N/A
2014/0095022	12/2013	Cashman et al.	N/A	N/A
2014/0125018	12/2013	Brady et al.	N/A	N/A
2014/0129083	12/2013	O'Connor et al.	N/A	N/A
2014/0131971	12/2013	Hou	N/A	N/A
2014/0136048	12/2013	Ummethala et al.	N/A	N/A
2014/0156143	12/2013	Evangelou et al.	N/A	N/A
2014/0167372	12/2013	Kim et al.	N/A	N/A
2014/0232082	12/2013	Oshita	N/A	N/A
2014/0239602	12/2013	Blankenship et al.	N/A	N/A
2014/0316653	12/2013	Kikuchi et al.	N/A	N/A
2014/0353933	12/2013	Hawksworth et al.	N/A	N/A
2014/0353934	12/2013	Yabumoto	N/A	N/A
2014/0358373	12/2013	Kikuchi et al.	N/A	N/A
2015/0039199	12/2014	Kikuchi	N/A	N/A
2015/0046034	12/2014	Kikuchi	N/A	N/A
2015/0057885	12/2014	Brady et al.	N/A	N/A
2015/0081170	12/2014	Kikuchi	N/A	N/A
2015/0081171	12/2014	Ericksen et al.	N/A	N/A
2015/0084290	12/2014	Norton et al.	N/A	N/A
2015/0217778	12/2014	Fairgrieve et al.	N/A	N/A
2015/0329141	12/2014	Preijert	N/A	N/A

2015/0352920	12/2014	Lakehal-Ayat et al.	N/A	N/A
2016/0059660	12/2015	Brady et al.	N/A	N/A
2016/0107498	12/2015	Yamazaki	N/A	N/A
2016/0121689	12/2015	Park et al.	N/A	N/A
2016/0121905	12/2015	Gillingham et al.	N/A	N/A
2016/0121924	12/2015	Norstad	N/A	N/A
2016/0153516	12/2015	Marking	N/A	N/A
2016/0200164	12/2015	Tabata	N/A	N/A
2016/0214455	12/2015	Reul et al.	N/A	N/A
2016/0280331	12/2015	Mangum	N/A	N/A
2016/0347142	12/2015	Seong et al.	N/A	N/A
2017/0008363	12/2016	Ericksen et al.	N/A	N/A
2017/0043778	12/2016	Kelly	N/A	N/A
2017/0087950	12/2016	Brady et al.	N/A	N/A
2017/0129298	12/2016	Lu et al.	N/A	N/A
2017/0129390	12/2016	Akaza et al.	N/A	N/A
2017/0321729	12/2016	Melcher	N/A	N/A
2018/0001729	12/2017	Goffer et al.	N/A	N/A
2018/0009443	12/2017	Norstad	N/A	N/A
2018/0126817	12/2017	Russell et al.	N/A	N/A
2018/0141543	12/2017	Krosschell	N/A	B60W 30/02
2018/0264902	12/2017	Schroeder	N/A	N/A
2018/0297435	12/2017	Brady et al.	N/A	N/A
2018/0339566	12/2017	Ericksen et al.	N/A	N/A
2018/0354336	12/2017	Oakden-Graus	N/A	N/A
2018/0361853	12/2017	Grajkowski et al.	N/A	N/A
2019/0100071	12/2018	Tsiaras et al.	N/A	N/A
2019/0118898	12/2018	Ericksen et al.	N/A	N/A
2019/0389478	12/2018	Norstad	N/A	N/A
2020/0016953	12/2019	Oakden-Graus et al.	N/A	N/A
2020/0096075	12/2019	Lindblad	N/A	N/A
2020/0156430	12/2019	Oakden-Graus et al.	N/A	N/A
2020/0223279	12/2019	McKeefery	N/A	N/A
2020/0269648	12/2019	Halper	N/A	N/A
2020/0282786	12/2019	Lorenz	N/A	N/A
2021/0031579	12/2020	Booth	N/A	N/A
2021/0070124	12/2020	Brady et al.	N/A	N/A
2021/0070125	12/2020	Brady et al.	N/A	N/A
2021/0070126	12/2020	Brady et al.	N/A	N/A
2021/0086578	12/2020	Brady et al.	N/A	N/A
2021/0088100	12/2020	Woelfel	N/A	N/A
2021/0102596	12/2020	Malmborg et al.	N/A	N/A
2021/0108696	12/2020	Randall	N/A	N/A
2021/0162830	12/2020	Graus et al.	N/A	N/A
2021/0162833	12/2020	Graus et al.	N/A	N/A
2021/0206263	12/2020	Grajkowski et al.	N/A	N/A
2021/0300140	12/2020	Ericksen	N/A	N/A
2021/0316716	12/2020	Krosschell et al.	N/A	N/A
2021/0379957	12/2020	Tabata	N/A	N/A
2022/0016949	12/2021	Graus et al.	N/A	N/A
2022/0032708	12/2021	Tabata	N/A	N/A
2022/0041029	12/2021	Randall	N/A	N/A
2022/0056976	12/2021	Anderson	N/A	N/A

2022/0088988	12/2021	Menden	N/A	N/A
2022/0266844	12/2021	Norstad et al.	N/A	N/A
2022/0324282	12/2021	Brady et al.	N/A	N/A
2022/0388362	12/2021	Graus et al.	N/A	N/A
2022/0397194	12/2021	Kohler	N/A	N/A
2023/0013665	12/2022	Gagnon	N/A	B62D 55/07
2023/0079941	12/2022	Graus et al.	N/A	N/A
2024/0123972	12/2023	Krosschell et al.	N/A	N/A
2024/0190448	12/2023	Norstad et al.	N/A	N/A
2024/0262151	12/2023	Graus et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2012323853	12/2013	AU	N/A
2015328248	12/2016	AU	N/A
2260292	12/1999	CA	N/A
2851626	12/2012	CA	N/A
2963790	12/2015	CA	N/A
2965309	12/2015	CA	N/A
3018906	12/2018	CA	N/A
1129646	12/1995	CN	N/A
2255379	12/1996	CN	N/A
2544987	12/2002	CN	N/A
1660615	12/2004	CN	N/A
1664337	12/2004	CN	N/A
1746803	12/2005	CN	N/A
1749048	12/2005	CN	N/A
1810530	12/2005	CN	N/A
101088829	12/2006	CN	N/A
101417596	12/2008	CN	N/A
101522444	12/2008	CN	N/A
101549626	12/2008	CN	N/A
101868363	12/2009	CN	N/A
201723635	12/2010	CN	N/A
102069813	12/2010	CN	N/A
102168732	12/2010	CN	N/A
201914049	12/2010	CN	N/A
202040257	12/2010	CN	N/A
102616104	12/2011	CN	N/A
102627063	12/2011	CN	N/A
102678808	12/2011	CN	N/A
202449059	12/2011	CN	N/A
102729760	12/2011	CN	N/A
202468817	12/2011	CN	N/A
102840265	12/2011	CN	N/A
103079934	12/2012	CN	N/A
103303088	12/2012	CN	N/A
103318184	12/2012	CN	N/A
103507588	12/2013	CN	N/A
104755348	12/2014	CN	N/A
104768782	12/2014	CN	N/A
105564437	12/2015	CN	N/A
106183688	12/2015	CN	N/A
106218343	12/2015	CN	N/A

106794736	12/2016	CN	N/A
103857576	12/2016	CN	N/A
107406094	12/2016	CN	N/A
107521449	12/2016	CN	N/A
107521499	12/2016	CN	N/A
109203900	12/2018	CN	N/A
110121438	12/2018	CN	N/A
110691705	12/2019	CN	N/A
3811541	12/1987	DE	N/A
4017255	12/1989	DE	N/A
4323589	12/1993	DE	N/A
4328551	12/1993	DE	N/A
19508302	12/1995	DE	N/A
19922745	12/1999	DE	N/A
60029553	12/2006	DE	N/A
102010020544	12/2010	DE	N/A
102012101278	12/2012	DE	N/A
0361726	12/1989	EP	N/A
0398804	12/1989	EP	N/A
0403803	12/1989	EP	N/A
0544108	12/1992	EP	N/A
0546295	12/1992	EP	N/A
0405123	12/1992	EP	N/A
0473766	12/1993	EP	N/A
0691226	12/1995	EP	N/A
0745965	12/1995	EP	N/A
0829383	12/1997	EP	N/A
0953470	12/1998	EP	N/A
1005006	12/1999	EP	N/A
1022169	12/1999	EP	N/A
1172239	12/2001	EP	N/A
1219475	12/2001	EP	N/A
1238833	12/2001	EP	N/A
1258706	12/2001	EP	N/A
1355209	12/2002	EP	N/A
1449688	12/2003	EP	N/A
1481876	12/2003	EP	N/A
1164897	12/2004	EP	N/A
2123933	12/2008	EP	N/A
2216191	12/2009	EP	N/A
2268496	12/2010	EP	N/A
2397349	12/2010	EP	N/A
2517904	12/2011	EP	N/A
3150454	12/2016	EP	N/A
3204248	12/2016	EP	N/A
2935642	12/2009	FR	N/A
2233939	12/1990	GB	N/A
2234211	12/1990	GB	N/A
2259063	12/1992	GB	N/A
2262491	12/1992	GB	N/A
2329728	12/1998	GB	N/A
2377415	12/2002	GB	N/A
2412448	12/2004	GB	N/A

2441348	12/2007	GB	N/A
2445291	12/2007	GB	N/A
20130233813	12/2013	IN	N/A
01-208212	12/1988	JP	N/A
02-155815	12/1989	JP	N/A
03-137209	12/1990	JP	N/A
04-368211	12/1991	JP	N/A
05-178055	12/1992	JP	N/A
06-156036	12/1993	JP	N/A
07-117433	12/1994	JP	N/A
07-186668	12/1994	JP	N/A
08-332940	12/1995	JP	N/A
09-203640	12/1996	JP	N/A
2898949	12/1998	JP	N/A
2956221	12/1998	JP	N/A
11-321754	12/1998	JP	N/A
3087539	12/1999	JP	N/A
2001-018623	12/2000	JP	N/A
3137209	12/2000	JP	N/A
2001-121939	12/2000	JP	N/A
2001-233228	12/2000	JP	N/A
2001-278089	12/2000	JP	N/A
2002-219921	12/2001	JP	N/A
2003-328806	12/2002	JP	N/A
2008-273246	12/2007	JP	N/A
2009-035220	12/2008	JP	N/A
2009-160964	12/2008	JP	N/A
4584510	12/2009	JP	N/A
2011-126405	12/2010	JP	N/A
5149443	12/2012	JP	N/A
2013-173490	12/2012	JP	N/A
2013-189109	12/2012	JP	N/A
10-2008-0090833	12/2007	KR	N/A
M299089	12/2005	TW	N/A
92/10693	12/1991	WO	N/A
96/05975	12/1995	WO	N/A
97/27388	12/1996	WO	N/A
99/59860	12/1998	WO	N/A
00/53057	12/1999	WO	N/A
02/20318	12/2001	WO	N/A
2004/009433	12/2003	WO	N/A
2004/098941	12/2003	WO	N/A
2009/008816	12/2008	WO	N/A
2009/133000	12/2008	WO	N/A
2012/028923	12/2011	WO	N/A
2015/004676	12/2014	WO	N/A
2016/057555	12/2015	WO	N/A
2016/069405	12/2015	WO	N/A
2020/089837	12/2019	WO	N/A

OTHER PUBLICATIONS

Ackermann et al., “Robust steering control for active rollover avoidance of vehicles with elevated center of gravity”, Jul. 1998, pp. 1-6. cited by applicant

Bhattacharyya et al., "An Approach to Improve Vehicle Stability in Vehicles Using Suspension Relative Position Sensors and Lateral Acceleration Sensors", Dec. 2005, 100 pages. cited by applicant

Hac et al., "Improvements in vehicle handling through integrated control of chassis systems", Int. J. of Vehicle Autonomous Systems(IJVAS), vol. 1, No. 1, 2002, pp. 83-110. cited by applicant

Huang et al., "Nonlinear Active Suspension Control Design Applied to a Half-Car Model", Proceedings of the 2004 IEEE International Conference on Networking, Mar. 21-23, 2004, pp. 719-724. cited by applicant

Article 34 Amendment, issued by the European Patent Office, dated Aug. 29, 2016, for related International patent application No. PCT/US2015/057132; 34 pages. cited by applicant

English translation of Examination Report issued by the State Intellectual Property Office of People's Republic of China, dated Jun. 1, 2015, for Chinese Patent Application No. 201180037804.3; 13 pages. cited by applicant

European Search Report issued by the European Patent Office, dated Feb. 10, 2017, for corresponding European patent application No. 16193006; 7 pages. cited by applicant

Examination Report issued by the European Patent Office, dated Aug. 1, 2016, for European Patent Application No. 11724931.8; 5 pages. cited by applicant

Examination Report issued by the State Intellectual Property Office of People's Republic of China, dated Feb. 3, 2016, for Chinese Patent Application No. 201180037804.3; 14 pages. cited by applicant

Examination Report No. 1 issued by the Australian Government IP Australia, dated Apr. 15, 2014, for Australian Patent Application No. 2011261248; 5 pages. cited by applicant

Examination Report No. 1 issued by the Australian Government IP Australia, dated Jan. 12, 2017, for corresponding Australian patent application No. 2015271880; 6 pages. cited by applicant

Examination Report No. 2 issued by the Australian Government IP Australia, dated Jun. 29, 2017, for Australian Patent Application No. 2015271880; 8 pages. cited by applicant

Examination Report No. 2 issued by the Australian Government IP Australia, dated May 29, 2015, for Australian Patent Application No. 2011261248; 8 pages. cited by applicant

Examination Report No. 3 issued by the Australian Government IP Australia, dated Dec. 1, 2017, for Australian Patent Application No. 2015271880; 7 pages. cited by applicant

Extended European Search Report issued by the European Patent Office, dated Sep. 7, 2018, for European Patent Application No. 18183050.6; 7 pages. cited by applicant

International Preliminary Report on Patentability in PCT Application Serial No. PCT/US15/57132, issued Jan. 30, 2017 (6 pages). cited by applicant

International Preliminary Report on Patentability issued by the International Bureau of WIPO, Dec. 4, 2012, for International Application No. PCT/US2011/039165; 9 pages. cited by applicant

International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US2011/39165, dated Jan. 3, 2012; 15 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2015/057132, mailed on May 13, 2016, 17 pages. cited by applicant

Office Action issued by the Canadian Intellectual Property Office, dated Apr. 21, 2017, for corresponding Canadian patent application No. 2,801,334; 3 pages. cited by applicant

Office Action issued by the Canadian Intellectual Property Office, dated Oct. 1, 2019, for Canadian Patent Application No. 2,965,309; 8 pages. cited by applicant

Office Action issued by the Mexican Patent Office, dated Jun. 25, 2014, for corresponding Mexican patent application No. MX/a/2012/014069; 2 pages. cited by applicant

3Drive Compact Throttle Controller, Blitz Power USA, <http://pivotjp.com/product/thf_c/the.html>; earliest known archive via Internet Archive Wayback Machine Aug. 27, 2009; <http://web.archive.org/web/20090827154111/http://pivotjp.com/product/thf_c/the.html>; see appended screenshot retrieved from the Internet Nov. 30, 2015; 2 pages. cited by applicant

Compare: Three Selectable Terrain Management Systems, Independent Land Rover News Blog, retrieved from <https://web.archive.org/web/20120611082023/> . . . ; archive date Jun. 11, 2012; 4 pages. cited by applicant

EDFC Active Adjust Damping Force Instantly according to G-Force & Speed, TEIN, retrieved from <https://web.archive.org/web/20140528221849/> . . . ; archive date May 28, 2014; 18 pages. cited by applicant

EDFC Active Adjust Damping Force Instantly according to G-Force & Speed, TEIN, retrieved from <https://web.archive.org/web/20160515190809/> . . . ; archive date May 15, 2016; 22 pages. cited by applicant

Examination Report No. 1 issued by the Australian Government IP Australia, dated Aug. 10, 2018, for

Australian Patent Application No. 2015328248; 2 pages. cited by applicant

First drive: Ferrari's easy-drive supercar, GoAuto.com.au, Feb. 16, 2010; 4 pages. cited by applicant

Gangadurai et al.; Development of control strategy for optimal control of a continuously variable transmission operating in combination with a throttle controlled engine; SAE International; Oct. 12, 2005. cited by applicant

Ingalls, Jake; Facebook post
<https://www.facebook.com/groups/877984048905836/permalink/110447996625624-2>; Sep. 11, 2016; 1 page. cited by applicant

International Preliminary Report on Patentability issued by the European Patent Office, dated Apr. 11, 2017, for International Patent Application No. PCT/US2015/054296; 7 pages. cited by applicant

International Preliminary Report on Patentability issued by the International Bureau of WIPO, dated Dec. 10, 2019, for International Patent Application No. PCT/US2018/036383; 8 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/IB2019/060089, mailed on Jun. 3, 2021, 22 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2013/068937, mailed on May 21, 2015, 8 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2017/062303, mailed on May 31, 2019, 23 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/IB2019/060089, mailed on May 29, 2020, 24 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2013/068937, mailed on Feb. 26, 2014, 10 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2015/054296, mailed on Dec. 18, 2015, 9 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2021/033199, mailed on Aug. 23, 2021, 14 pages. cited by applicant

International Search Report issued by the International Searching Authority, dated Jun. 7, 2018, for related International Patent Application No. PCT/US2017/062303; 7 pages. cited by applicant

International Search Report of the International Searching Authority, dated Aug. 31, 2018, for International Patent Application No. PCT/US2018/036383; 7 pages. cited by applicant

Mckay et al., Delphi Electronic Throttle Control Systems for Model Year 2000; Driver Features, System Security, and OEM Benefits. ETC for the Mass Market, Electronic Engine Controls 2000: Controls (SP-1500), SAE 2000 World Congress, Detroit, MI, Mar. 6-9, 2000, 13 pages. cited by applicant

Office Action issued by the Canadian Intellectual Property Office, dated Jul. 26, 2019, for Canadian Patent Application No. 2,963,790; 3 pages. cited by applicant

Office Action issued by the Canadian Intellectual Property Office, dated Jun. 22, 2021, for Canadian Patent Application No. 3,043,481; 3 pages. cited by applicant

Office Action issued by the Canadian Intellectual Property Office, dated May 10, 2021, for Canadian Patent Application No. 2,890,996; 3 pages. cited by applicant

Scott Tsuneishi, "2005 Subaru WRX Sti-Blitz Throttle Controller," Oct. 1, 2008, Super Street Online, <<http://www.superstreetonline.com/how-to/engine/turp-0810-2005-subam-wrx-sti-blitz-throttle-controller>>; see appended screenshot retrieved from the Internet Nov. 30, 2015; 11 pages. cited by applicant

Throttle Controller, Blitz Power USA, <<http://www.blitzpowerusa.com/products/throcon/throcon.html>>; earliest known archive via Internet Archive Wayback Machine Sep. 14, 2009: <<http://web.archive.org/web/20090914102957/http://www.blitzpowerusa.com/products/throcon/throcon.html>>; see appended screenshot. cited by applicant

Trebi-Ollennu et al., Adaptive Fuzzy Throttle Control of an All Terrain Vehicle, 2001, Abstract. cited by applicant

Unno et al.; Development of Electronically Controlled DVT Focusing on Rider's Intention of Acceleration and Deceleration; SAE International; Oct. 30, 2007. cited by applicant

Written Opinion issued by the International Searching Authority, dated Jun. 7, 2018, for related International Patent Application No. PCT/US2017/062303; 22 pages. cited by applicant

Written Opinion of the International Searching Authority, dated Aug. 31, 2018, for International Patent Application No. PCT/US2018/036383; 8 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2021/033199, mailed on Dec. 1, 2022, 11 pages. cited by applicant
New 2022! Lightweight iQS Intelligent Quick Switch, Fox Factory, Inc., available at <https://www.ridefox.com/content.php?c=iqs>, 2022; 10 pages. cited by applicant
TracTive, The Art of Suspension, available at <https://web.archive.org/web/20200322131710/https://tractivesuspension.com/snowmobile/>; 2020; 2 pages. cited by applicant
Vincent Bourque-Veilleux, “iACT: Arctic Cat redefines trail suspension standards”, sledmagazine.com; Feb. 27, 2018, <https://sledmagazine.com/iact-arctic-cat-redefines-trail-suspension-standards/>; 4 pages. cited by applicant

Primary Examiner: Laguarda; Gonzalo

Background/Summary

RELATED APPLICATION

(1) The present application is related to U.S. Provisional Application No. 63/027,833, filed May 20, 2021, titled SYSTEMS AND METHODS OF ADJUSTABLE SUSPENSIONS FOR OFF-ROAD RECREATIONAL VEHICLES, the entire disclosure of which is expressly incorporated by reference herein.

BACKGROUND AND SUMMARY OF THE DISCLOSURE

(2) The present disclosure relates to improved suspension for off-road recreational vehicles and, in particular, to systems and methods of damping control for shock absorbers of off-road recreational vehicles.

(3) Currently some off-road vehicles include adjustable shock absorbers. These adjustments include spring preload, high and low speed compression damping and/or rebound damping. In order to make these adjustments, the vehicle is stopped and the operator makes an adjustment at each shock absorber location on the vehicle. A tool is often required for the adjustment. Some off-road vehicles also include adjustable electric shocks along with sensors for active ride control systems. Exemplary systems are disclosed in U.S. Pat. No. 9,010,768 and US Published Patent Application No. 2016/0059660, both assigned to the present assignee and the entire disclosures of each expressly incorporated by reference herein.

(4) In an exemplary embodiment of the present disclosure, a snowmobile for propelled movement relative to the ground is provided. The snowmobile comprising a plurality of ground engaging members including an endless track positioned along a centerline vertical longitudinal plane of the snowmobile have having a lateral width, a left front ski positioned on a left side of the centerline vertical longitudinal plane of the snowmobile, and a right front ski positioned on a right side of the centerline vertical longitudinal plane of the snowmobile; a frame supported by the plurality of ground engaging members; a steering system supported by the frame and operatively coupled to the left front ski and the right front ski to control a direction of travel of the snowmobile; a left ski suspension operatively coupling the left front ski to the frame; a right ski suspension operatively coupling the right front ski to the frame; a track suspension operatively coupling the endless track to the frame, the track suspension including a first adjustable shock absorber, the first adjustable shock absorber having at least one adjustable damping characteristic, the first adjustable shock absorber being laterally positioned within the lateral width of the endless track; a plurality of sensors supported by the ground engaging members; and at least one electronic controller operatively coupled to the first adjustable shock absorber, the at least one electronic controller based on inputs from the plurality of sensors alters at least one damping characteristic of the first adjustable shock absorber.

(5) In an example thereof, the first adjustable shock absorber of the first suspension is positioned within an interior bounded by the endless track.

(6) In another example thereof, the track suspension further comprises a second adjustable shock absorber having at least one adjustable damping characteristic, the second adjustable shock absorber being laterally

positioned within the lateral width of the endless track, the first adjustable shock absorber is a front track adjustable shock absorber and the second adjustable shock absorber is a rear track adjustable shock absorber. In a variation thereof, the second adjustable shock absorber of the track suspension is positioned within the interior bounded by the endless track. In another variation thereof, the second adjustable shock absorber of the track suspension is positioned outside of the interior bounded by the endless track. In a further variation thereof, the second adjustable shock absorber of the track suspension is positioned above the endless track. In a refinement thereof, the front track adjustable shock absorber is positioned forward of the rear track adjustable shock absorber.

(7) In a further example thereof, the at least one electronic controller alters the at least one damping characteristic of the first adjustable shock absorber while the snowmobile is moving relative to the ground. In a variation thereof, the at least one electronic controller alters a compression damping characteristic of the first adjustable shock absorber. In another variation thereof, the at least one electronic controller alters a rebound damping characteristic of the first adjustable shock absorber. In a further variation thereof, the at least one electronic controller alters both a compression damping characteristic of the first adjustable shock absorber and a rebound damping characteristic of the first adjustable shock absorber.

(8) In still another example thereof, the snowmobile further comprises a third adjustable shock absorber and a fourth adjustable shock absorber, the third adjustable shock absorber is part of the left ski suspension operatively coupling the left front ski to the frame and the fourth adjustable shock absorber is part of the right ski suspension operatively coupling the right front ski to the frame.

(9) In still a further example, a first damping characteristic of the first adjustable shock absorber is adjusted by the at least one electronic controller based on a longitudinal acceleration of the snowmobile. In a variation thereof, a first damping characteristic of the first adjustable shock absorber and a first damping characteristic of the second adjustable shock absorber are adjusted by the at least one electronic controller based on a longitudinal acceleration of the snowmobile. In another variation thereof, a first damping characteristic of the first adjustable shock absorber, a first damping characteristic of the second adjustable shock absorber, a first damping characteristic of the third adjustable shock absorber, and a first damping characteristic of the fourth adjustable shock absorber are adjusted by the at least one electronic controller based on a longitudinal acceleration of the snowmobile. In a further variation thereof, the longitudinal acceleration of the snowmobile is measured by the plurality of sensors. In still a further variation thereof, the longitudinal acceleration of the snowmobile is estimated by the at least one electronic controller. In yet another variation thereof, the longitudinal acceleration of the snowmobile is predicted by the at least one electronic controller.

(10) In yet another example thereof, a first damping characteristic of the first adjustable shock absorber is adjusted by the at least one electronic controller based on a vehicle pitch motion of the snowmobile. In a variation thereof, a first damping characteristic of the first adjustable shock absorber and a first damping characteristic of the second adjustable shock absorber are adjusted by the at least one electronic controller based on a vehicle pitch motion of the snowmobile. In another variation thereof, a first damping characteristic of the first adjustable shock absorber, a first damping characteristic of the second adjustable shock absorber, a first damping characteristic of the third adjustable shock absorber, and a first damping characteristic of the fourth adjustable shock absorber are adjusted by the at least one electronic controller based on a predicted vehicle pitch motion of the snowmobile. In still another variation thereof, the at least one electronic controller determines the snowmobile is predicted to travel at a generally constant longitudinal acceleration, the at least one electronic controller alters a rebound damping characteristic for the third adjustable shock absorber and alters a rebound damping characteristic for the fourth adjustable shock absorber. In yet another variation thereof, the at least one electronic controller determines the snowmobile is predicted to travel at a generally constant longitudinal acceleration, the at least one electronic controller increases a rebound damping characteristic for the third adjustable shock absorber and increases a rebound damping characteristic for the fourth adjustable shock absorber. In yet still another variation thereof, the at least one electronic controller determines the snowmobile is predicted to travel at a generally constant longitudinal acceleration, the at least one electronic controller alters a compression damping characteristic for the third adjustable shock absorber and alters a compression damping for the fourth adjustable shock absorber. In still yet a further variation thereof, the at least one

electronic controller determines the snowmobile is predicted to travel at a generally constant longitudinal acceleration, the at least one electronic controller decreases a compression damping characteristic for the third adjustable shock absorber and decreases a compression damping for the fourth adjustable shock absorber. In still another variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a rearward pitch of the snowmobile and alters a compression damping characteristic of the first adjustable shock absorber. In yet another variation, the at least one electronic controller determines the predicted vehicle pitch motion indicates a rearward pitch of the snowmobile and increases a compression damping characteristic of the first adjustable shock absorber. In still yet another variation, the at least one electronic controller determines the predicted vehicle pitch motion indicates a rearward pitch of the snowmobile and alters a compression damping characteristic of the second adjustable shock absorber. In a further still variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a rearward pitch of the snowmobile and increases a compression damping characteristic of the second adjustable shock absorber. In a yet further still variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a rearward pitch of the snowmobile and alters a rebound damping characteristic of the second adjustable shock absorber. In another still variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a rearward pitch of the snowmobile and increases a rebound damping characteristic of the second adjustable shock absorber. In a further variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a rearward pitch of the snowmobile, the at least one electronic controller increases a rebound damping characteristic for the third adjustable shock absorber, increases a rebound damping characteristic for the fourth adjustable shock absorber, alters the compression damping characteristic of the first adjustable shock absorber, and increases the compression damping characteristic of the second adjustable shock absorber. In still another variation, the at least one electronic controller determines the predicted vehicle pitch motion indicates a rearward pitch of the snowmobile based on an indication of a throttle increase. In yet still another variation, the at least one electronic controller determines the predicted vehicle pitch motion indicates a rearward pitch of the snowmobile based on an indication of an engine torque increase. In a further still variation, the at least one electronic controller determines the predicted vehicle pitch motion indicates a rearward pitch of the snowmobile based on an indication of an increased vehicle acceleration. In a further yet still variation thereof, the at least one electronic controller determines the snowmobile is predicted to travel at a generally constant longitudinal deceleration, the at least one electronic controller increases a compression damping characteristic for the third adjustable shock absorber and increases a compression damping characteristic for the fourth adjustable shock absorber.

(11) In yet a further example, thereof, the at least one electronic controller determines the snowmobile is predicted to travel at a generally constant longitudinal deceleration, the at least one electronic controller increases a rebound damping characteristic for the first adjustable shock absorber.

(12) In still another example thereof, the at least one electronic controller determines the snowmobile is predicted to travel at a generally constant longitudinal deceleration, the at least one electronic controller alters a compression damping for the first adjustable shock absorber. In a variation thereof, the at least one electronic controller determines the snowmobile is predicted to travel at a generally constant longitudinal deceleration, the at least one electronic controller increases a rebound damping characteristic of the second adjustable shock absorber.

(13) In another variation thereof, the at least one electronic controller determines the snowmobile is predicted to travel at a generally constant longitudinal deceleration, the at least one electronic controller alters a compression damping of the second adjustable shock absorber. In still a further variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a forward pitch of the snowmobile and alters a rebound damping characteristic of the first adjustable shock absorber. In yet still a further variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a forward pitch of the snowmobile and increases a damping characteristic of the first adjustable shock absorber. In a further yet variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a forward pitch of the snowmobile and alters a rebound damping characteristic of the second adjustable shock absorber. In a still further variation thereof, the at least one electronic controller determines the predicted vehicle pitch

motion indicates a forward pitch of the snowmobile and increases a rebound damping characteristic of the second adjustable shock absorber. In a yet still further variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a forward pitch of the snowmobile and alters a compression damping characteristic of the second adjustable shock absorber. In a further still variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a forward pitch of the snowmobile, the at least one electronic controller increases a compression damping characteristic for the third adjustable shock absorber, increases a compression damping characteristic for the fourth adjustable shock absorber, alters a rebound damping characteristic of the first adjustable shock absorber, and alters a rebound damping characteristic of the second adjustable shock absorber. In yet a further still variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a forward pitch of the snowmobile, the at least one electronic controller increases a compression damping characteristic for the third adjustable shock absorber, increases a compression damping characteristic for the fourth adjustable shock absorber, increases a rebound damping characteristic of the first adjustable shock absorber, and increases a rebound damping characteristic of the second adjustable shock absorber. In another variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a forward pitch of the snowmobile based on an indication of a throttle decrease. In a further variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a forward pitch of the snowmobile based on an indication of an application of the brake. In yet another variation thereof, the at least one electronic controller determines the predicted vehicle pitch motion indicates a forward pitch of the snowmobile based on an indication of a decreased vehicle acceleration.

(14) In still another example thereof, at least one of a first damping characteristic of the first adjustable shock absorber, a first damping characteristic of the second adjustable shock absorber, a first damping characteristic of the third adjustable shock absorber, and a first damping characteristic of the fourth adjustable shock absorber are adjusted by the at least one electronic controller based on a turning of the snowmobile. In yet a further variation thereof, the at least one of the first damping characteristic of the first adjustable shock, the first damping characteristic of the second adjustable shock, the first damping characteristic of the third adjustable shock, and the first damping characteristic of the fourth adjustable shock are adjusted by the at least one electronic controller based on the turning of the snowmobile corresponding to a corner entry. In still another variation thereof, the at least one of the first damping characteristic of the first adjustable shock, the first damping characteristic of the second adjustable shock, the first damping characteristic of the third adjustable shock, and the first damping characteristic of the fourth adjustable shock are adjusted by the at least one electronic controller based on the turning of the snowmobile corresponding to a time subsequent to a corner entry. In a further still variation, the at least one electronic controller determines the snowmobile is making a left turn, the at least one electronic controller increases a compression damping characteristic for the fourth adjustable shock absorber. In another variation thereof, the at least one electronic controller determines the snowmobile is making the left turn, the at least one electronic controller decreases a compression damping characteristic of the fourth adjustable shock absorber. In a further variation thereof, the at least one electronic controller determines the snowmobile is making the left turn, the at least one electronic controller increases a rebound damping characteristic of the fourth adjustable shock absorber. In still another variation thereof, the at least one electronic controller determines the snowmobile is making the left turn, the at least one electronic controller decreases a compression damping characteristic of the first adjustable shock absorber. In yet still another variation thereof, the at least one electronic controller determines the snowmobile is making the left turn, the at least one electronic controller increases a rebound damping characteristic of the first adjustable shock absorber. In another variation thereof, the at least one electronic controller determines the snowmobile is making a right turn, the at least one electronic controller increases a compression damping characteristic for the third adjustable shock absorber. In a further variation thereof, the at least one electronic controller determines the snowmobile is making the right turn, the at least one electronic controller decreases a compression damping characteristic of the fourth adjustable shock absorber. In another variation thereof, the at least one electronic controller determines the snowmobile is making the right turn, the at least one electronic controller increases a rebound damping characteristic of the fourth adjustable shock absorber. In a yet still further variation thereof, the

at least one electronic controller determines the snowmobile is making the right turn, the at least one electronic controller decreases a compression damping characteristic of the first adjustable shock absorber. In a further variation thereof, the at least one electronic controller determines the snowmobile is making the right turn, the at least one electronic controller increases a rebound damping characteristic of the first adjustable shock absorber.

(15) In still a further example thereof, the at least one electronic controller adjusts a first damping characteristic of the first adjustable shock absorber to promote a lifting of the skis of the snowmobile. In a variation thereof, a compression damping characteristic of the first adjustable shock absorber is altered to promote a lifting of the skis of the snowmobile. In another variation thereof, the compression damping characteristic of the first adjustable shock absorber is decreased to promote a lifting of the skis of the snowmobile. In a further variation thereof, the compression damping characteristic of the first adjustable shock absorber is increased to promote a lifting of the skis of the snowmobile. In still another variation thereof, the at least one electronic controller adjusts a first damping characteristic of the first adjustable shock absorber and a first damping characteristic of the second adjustable shock absorber to promote a lifting of the skis of the snowmobile. In a further variation thereof, a compression damping characteristic of the second adjustable shock absorber is altered to promote the lifting of the skis of the snowmobile and to cause a wheelie. In a further still variation thereof, the compression damping characteristic of the second adjustable shock absorber is decreased to promote the lifting of the skis of the snowmobile and to cause the wheelie. In another variation thereof, a rebound damping characteristic of the second adjustable shock absorber is altered to promote the lifting of the skis of the snowmobile and to prevent a wheelie. In yet another variation thereof, the rebound damping characteristic of the second adjustable shock absorber is increased to promote the lifting of the skis of the snowmobile and to prevent the wheelie. In a further variation thereof, the at least one electronic controller adjusts a first damping characteristic of the first adjustable shock absorber, a first damping characteristic of the second adjustable shock absorber, a first damping characteristic of the third adjustable shock absorber, and a first damping characteristic of the fourth adjustable shock absorber to promote a lifting of the skis of the snowmobile. In a yet a further variation, a compression damping characteristic of the second adjustable shock absorber is altered to promote the lifting of the skis of the snowmobile and to cause a wheelie. In a further yet variation, the compression damping characteristic of the second adjustable shock absorber is decreased to promote the lifting of the skis of the snowmobile and to cause the wheelie. In a further still variation, a rebound damping characteristic of the third adjustable shock absorber is altered and a rebound damping characteristic of the fourth adjustable shock absorber is altered to promote the lifting of the skis of the snowmobile and to cause the wheelie. In another variation, the rebound damping characteristic of the third adjustable shock absorber is decreased and the rebound damping characteristic of the fourth adjustable shock absorber is decreased to promote the lifting of the skis of the snowmobile and to cause the wheelie. In yet a further variation, a rebound damping characteristic of the second adjustable shock absorber is altered to promote the lifting of the skis of the snowmobile and to prevent a wheelie. In still a variation, the rebound damping characteristic of the second adjustable shock absorber is increased to promote the lifting of the skis of the snowmobile and to prevent the wheelie. In yet still a further variation, a rebound damping characteristic of the third adjustable shock absorber is altered and a rebound damping characteristic of the fourth adjustable shock absorber is altered to promote the lifting of the skis of the snowmobile and to prevent the wheelie. In further still variation, the rebound damping characteristic of the third adjustable shock absorber is increased and the rebound damping characteristic of the fourth adjustable shock absorber is increased to promote the lifting of the skis of the snowmobile and to prevent the wheelie. In yet another variation, the damping characteristic of the first adjustable shock absorber is adjusted for a first condition and thereafter allowed to further adjust based on the plurality of sensors. In yet a further variation, the damping characteristic of the first adjustable shock absorber and the damping characteristic of the second adjustable shock absorber are adjusted for a first condition and thereafter allowed to further adjust based on the plurality of sensors. In a further still variation, the damping characteristic of the first adjustable shock absorber, the damping characteristic of the second adjustable shock absorber, the damping characteristic of the third adjustable shock absorber, and the damping characteristic of the fourth adjustable shock absorber are adjusted for a first condition and thereafter allowed to further adjust based on the plurality of sensors. In a still further variation, the

damping characteristic of the first adjustable shock absorber and the damping characteristic of the second adjustable shock absorber are adjusted for a first condition and thereafter allowed to further adjust based on the plurality of sensors and the damping characteristic of the third adjustable shock absorber and the damping characteristic of the fourth adjustable shock absorber are adjusted for a second condition and thereafter allowed to further adjust based on the plurality of sensors. In a further variation, the first condition is a duration of a timer. In a still further variation, the second condition is a duration of a second timer.

(16) In yet another example, the at least one electronic controller adjusts a first damping characteristic of the first adjustable shock absorber in response to the snowmobile being airborne. In a variation thereof, the adjustment of the first damping characteristic of the first adjustable shock absorber is dependent on a length of time that the snowmobile has been airborne. In another variation thereof, the at least one electronic controller increases a compression damping characteristic of the first adjustable shock absorber in response to the snowmobile being airborne. In still a further variation, the at least one electronic controller continues to hold the increased compression damping characteristic of the first adjustable shock absorber for a first period of time after the snowmobile has landed. In a further still variation, the at least one electronic controller alters a rebound damping characteristic of the first adjustable shock absorber in response to the snowmobile being airborne. In yet another variation, the adjustment of the rebound damping characteristic of the first adjustable shock absorber is dependent on a length of time that the snowmobile has been airborne. In yet a further variation, the at least one electronic controller increases the rebound damping characteristic of the first adjustable shock absorber for a first post landing period of time after the snowmobile has landed. In a further variation, the at least one electronic controller adjusts a first damping characteristic of the first adjustable shock absorber and a first damping characteristic of the second adjustable shock absorber in response to the snowmobile being airborne. In another variation, the adjustment of the first damping characteristic of the first adjustable shock absorber and the first damping characteristic of the second adjustable shock absorber is dependent on a length of time that the snowmobile has been airborne. In a further variation, the at least one electronic controller increases a compression damping characteristic of the first adjustable shock absorber and increases a compression damping characteristic of the second adjustable shock absorber in response to the snowmobile being airborne. In yet a further variation, the at least one electronic controller continues to hold the increased compression damping characteristic of the first adjustable shock absorber and the increased compression damping characteristic of the second adjustable shock absorber for a first period of time after the snowmobile has landed. In yet a further variation, the at least one electronic controller alters a rebound damping characteristic of the first adjustable shock absorber and alters a rebound damping characteristic of the second adjustable shock absorber in response to the snowmobile being airborne. In another variation, the adjustment of the rebound damping characteristic of the first adjustable shock absorber and the adjustment of the rebound damping characteristic of the second adjustable shock absorber is dependent on a length of time that the snowmobile has been airborne. In a further variation, the at least one electronic controller increases the rebound damping characteristic of the first adjustable shock absorber and increases the rebound damping characteristic of the second adjustable shock absorber for a first post landing period of time after the snowmobile has landed. In yet another variation, the at least one electronic controller adjusts a first damping characteristic of the third adjustable shock absorber, a first damping characteristic of the fourth adjustable shock absorber, a first damping characteristic of the first adjustable shock absorber, and a first damping characteristic of the second adjustable shock absorber in response to the snowmobile being airborne. In yet another variation, the adjustment of at least one of the first damping characteristic of the third adjustable shock absorber, the first damping characteristic of the fourth adjustable shock absorber, the first damping characteristic of the first adjustable shock absorber, and the first damping characteristic of the second adjustable shock absorber is dependent on a length of time that the snowmobile has been airborne. In still another variation, the at least one electronic controller increases a compression damping characteristic of the third adjustable shock absorber, increases a compression damping characteristic of the fourth adjustable shock absorber, increases a compression damping characteristic of the first adjustable shock absorber, and increases a compression damping characteristic of the second adjustable shock absorber in response to the snowmobile being airborne. In yet still another embodiment, the at least one electronic controller continues to hold the increased

compression damping characteristic of the third adjustable shock absorber, the increased compression damping characteristic of the fourth adjustable shock absorber, the increased compression damping characteristic of the first adjustable shock absorber, and the increased compression damping characteristic of the second adjustable shock absorber for a first period of time after the snowmobile has landed. In a further variation, the at least one electronic controller alters a rebound damping characteristic of the third adjustable shock absorber, alters a rebound damping characteristic of the fourth adjustable shock absorber, alters a rebound damping characteristic of the first adjustable shock absorber, and alters a rebound damping characteristic of the second adjustable shock absorber in response to the snowmobile being airborne. In a further still variation, the adjustment of the rebound damping characteristic of the third adjustable shock absorber and the adjustment of the rebound damping of the fourth adjustable shock absorber is adjusted in a first configuration in response to the snowmobile being airborne for less than a first time duration and in a second configuration in response to the snowmobile being airborne for longer than the first time duration. In a further still variation, the at least one electronic controller increases the rebound damping characteristic of the third adjustable shock absorber and increases the rebound damping characteristic of the fourth adjustable shock for a first post landing period of time after the snowmobile has landed in the second configuration. In yet another variation, the at least one electronic controller one of maintains or alters the rebound damping characteristic of the third adjustable shock absorber and one of maintains or alters the rebound damping characteristic of the fourth adjustable shock absorber for a first post landing period of time after the snowmobile has landed in the first configuration. In another variation, the adjustment of the rebound damping characteristic of the first adjustable shock absorber and the adjustment of the rebound damping characteristic of the second adjustable shock absorber is dependent on a length of time that the snowmobile has been airborne. In yet another variation, the at least one electronic controller increases the rebound damping characteristic of the third adjustable shock absorber, increases the rebound damping characteristic of the fourth adjustable shock absorber, increases the rebound damping characteristic of the first adjustable shock absorber, and increases the rebound damping characteristic of the second adjustable shock absorber for a first post landing period of time after the snowmobile has landed.

(17) In still another example, the snowmobile further comprises a driver actuatable suspension adjust input, wherein the at least one electronic controller adjusts a damping characteristic of the first adjustable shock absorber in response to a first actuation of the driver actuatable suspension input. In a variation thereof, the at least one electronic controller increases the compression damping of the first adjustable shock absorber in response to the first actuation of the driver actuatable suspension input. In another variation thereof, the driver actuatable suspension adjust input is supported by the steering system. In a further variation thereof, the driver actuatable suspension adjust input is positioned on a left hand portion of a handlebar of the steering system. In a further still variation thereof, the driver actuatable suspension adjust input is moveable along a longitudinal axis of the left hand portion of the handlebar of the steering system. In still another variation thereof, a first actuation characteristic of the driver actuatable suspension adjust input results in a first type of damping characteristic of the first adjustable shock absorber and a second actuation characteristic of the driver actuatable suspension adjust input results in a second type of damping characteristic of the first adjustable shock absorber. In a further still variation thereof, the first actuation characteristic is a single depress of a first time duration. In yet a further variation thereof, the second actuation characteristic is a single depress of a second time duration longer than the first time duration. In still another variation thereof, the second actuation characteristic is a plurality of depresses within a first time period.

(18) In a further example thereof, the snowmobile further comprises at least one mode input supported by the snowmobile, the at least one electronic controller selecting at least one damping characteristic of the first adjustable shock absorber based on a mode selected with the at least one mode input. In a variation thereof, an operator may select a first mode from a plurality of available modes with the at least one mode input.

(19) In still a further example thereof, the plurality of sensors include an internal measurement unit. In a variation thereof, the internal measurement unit is located between a spindle of the left ski and a rear end of a fuel tank supported by the plurality of ground engaging members. In another variation thereof, the internal measurement unit is located laterally within the lateral width of the endless track. In still another

variation, the internal measurement unit is located laterally within the lateral width of an engine of the snowmobile. In yet another variation, the internal measurement unit is located between an engine and a rear end of a fuel tank both supported by the plurality of ground engaging members. In a further variation, the internal measurement unit is supported by a tunnel covering the endless track. In yet another variation, the internal measurement unit is located vertically in line with a steering post of the steering system. In yet a further variation thereof, the frame includes an over-structure positioned above an engine of the snowmobile and supporting a steering post of the steering system, wherein the internal measurement unit is located within an interior of the over-structure. In still a further variation, the internal measurement unit is mounted to a first portion of the snowmobile and is vibration isolated from the first portion of the snowmobile to reduce engine vibration. In yet still another variation thereof, the internal measurement unit is integrated into the at least one electronic controller. In a further still variation thereof, the internal measurement unit is spaced apart from the at least one electronic controller.

(20) In another exemplary embodiment of the present disclosure, a method of controlling ride characteristics of a snowmobile is provided. The method comprising the steps of monitoring with at least one electronic controller a plurality of sensors supported by the snowmobile while the snowmobile is moving; and adjusting with the at least one electronic controller at least one damping characteristic of an adjustable shock absorber while the vehicle is moving, the adjustable shock absorber being apart of a suspension of an endless track of the snowmobile.

(21) In an example thereof, the method further comprises the step of maintaining the at least one damping characteristic of the adjustable shock absorber when the vehicle is stationary.

(22) In another example thereof, the method further comprises the step of discontinuing adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber when the vehicle is stationary.

(23) In still another example thereof, the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic based on a longitudinal acceleration of the snowmobile. In a variation thereof, the longitudinal acceleration of the snowmobile is measured by at least one sensor. In another variation thereof, the longitudinal acceleration of the snowmobile is estimated by the at least one electronic controller. In still another variation thereof, the longitudinal acceleration of the snowmobile is predicted by the at least one electronic controller.

(24) In still another example thereof, the method further comprising the steps of determining the longitudinal acceleration of the snowmobile indicates an acceleration of the snowmobile; and changing a rebound damping characteristic of the adjustable shock absorber. In yet still another variation, the method further comprises the steps of determining the longitudinal acceleration of the snowmobile indicates an acceleration of the snowmobile; and changing a compression damping characteristic of the adjustable shock absorber.

(25) In another example, the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic based on a predicted pitch motion of the snowmobile. In a variation thereof, the method further comprising the steps of determining the predicted longitudinal pitch motion of the snowmobile indicates a rearward pitch of the snowmobile; and increasing a compression damping characteristic of the adjustable shock absorber. In another variation thereof, the method further comprising the steps of determining the predicted longitudinal pitch motion of the snowmobile indicates a forward pitch of the snowmobile; and changing a rebound damping characteristic of the adjustable shock absorber. In still another variation thereof, the method further comprising the steps of: determining the predicted pitch motion of the snowmobile indicates a forward pitch of the snowmobile; and changing a compression damping characteristic of the adjustable shock absorber.

(26) In a further example thereof, wherein the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic based on a turning of the snowmobile. In a variation thereof, the step of

adjusting the at least one damping characteristic based on the turning of the snowmobile includes the step of altering a compression damping characteristic of the adjustable shock absorber. In another variation thereof, the step of adjusting the at least one damping characteristic based on the turning of the snowmobile includes the step of decreasing a compression damping characteristic of the adjustable shock absorber. In a further variation thereof, the step of adjusting the at least one damping characteristic based on the turning of the snowmobile includes the step of altering a rebound damping characteristic of the adjustable shock absorber. In yet another variation thereof, the step of adjusting the at least one damping characteristic based on the turning of the snowmobile includes the step of increasing a rebound damping characteristic of the adjustable shock absorber. In yet a further variation thereof, the step of adjusting the at least one damping characteristic based on the turning of the snowmobile includes the steps of decreasing a compression damping characteristic of the adjustable shock absorber and increasing a rebound damping characteristic of the adjustable shock absorber.

(27) In still another example thereof, the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic based on a braking of the snowmobile. In a variation thereof, the step of adjusting the at least one damping characteristic based on the braking of the snowmobile includes the step of altering a compression damping characteristic of the adjustable shock absorber. In another variation thereof, the step of adjusting the at least one damping characteristic based on the braking of the snowmobile includes the step of decreasing a compression damping characteristic of the adjustable shock absorber. In a further variation thereof, the step of adjusting the at least one damping characteristic based on the braking of the snowmobile includes the step of altering a rebound damping characteristic of the adjustable shock absorber. In still a further variation thereof, the step of adjusting the at least one damping characteristic based on the braking of the snowmobile includes the step of increasing a rebound damping characteristic of the adjustable shock absorber. In yet still a further variation, the step of adjusting the at least one damping characteristic based on the braking of the snowmobile includes the steps of decreasing a compression damping characteristic of the adjustable shock absorber and increasing a rebound damping characteristic of the adjustable shock absorber.

(28) In a still further example, the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic to promote a lifting of the skis of the snowmobile. In a variation thereof, the step of adjusting the at least one damping characteristic to promote the lifting of the skis of the snowmobile includes the steps of decreasing a compression damping characteristic of the adjustable shock absorber. In another variation thereof, the step of adjusting the at least one damping characteristic to promote the lifting of the skis of the snowmobile includes the steps of increasing a rebound damping characteristic of a second adjustable shock absorber associated with the suspension of the endless track.

(29) In a further example thereof, the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic based on the snowmobile being airborne. In a variation thereof, the step of adjusting the at least one damping characteristic based on the snowmobile being airborne includes the steps of increasing a compression damping characteristic of the adjustable shock absorber. In another variation thereof, a magnitude of the increase of the compression damping characteristic of the adjustable shock absorber is dependent on a length of time that the snowmobile has been airborne. In a further variation thereof, the method further comprises the step of continuing to hold the increased compression damping characteristic of the adjustable shock absorber for a first period of time after the snowmobile has landed. In still a further variation thereof, the step of adjusting the at least one damping characteristic based on the snowmobile being airborne further includes the step of decreasing a rebound damping characteristic of the adjustable shock absorber. In still another variation thereof, the method further comprising the step of increasing the rebound damping characteristic of the adjustable shock absorber for a second period of time after the snowmobile has landed. In a further still variation, the step of adjusting the at least one damping characteristic based on the snowmobile being airborne includes the step of

decreasing a rebound damping characteristic of the adjustable shock absorber. In yet a further still variation, the method further comprising the step of increasing the rebound damping characteristic of the adjustable shock absorber for a second period of time after the snowmobile has landed.

(30) In a still further exemplary embodiment of the present disclosure, a method of controlling a damping characteristic of at least one adjustable shock absorber of a vehicle being operated by a driver is provided. The method comprising receiving with an electronic controller a plurality of inputs from a plurality of sensors supported by the vehicle; predictively determining a longitudinal acceleration of the vehicle; and adjusting the damping characteristic of the at least one adjustable shock absorber of the vehicle based on the predicted longitudinal acceleration of the vehicle.

(31) In an example thereof, the method further comprising the steps of predictively determining a longitudinal pitch motion of the vehicle; and adjusting the damping characteristic of the at least one adjustable shock absorber of the vehicle based on the predicted longitudinal pitch motion of the vehicle.

(32) In another example thereof, the predicted longitudinal acceleration is determined by the steps of: determining a predicted power for a prime mover of the snowmobile; determining an output power of the drivetrain based on the determined predicted power, the drivetrain including a CVT; determining a forward moving force of the snowmobile based on the determined output power of the drivetrain; determining a resultant forward moving force by subtracting at least one of a coast down force and an applied braking force from the determined forward moving force; and dividing the resultant forward moving force by a mass of the snowmobile to determine the predicted vehicle longitudinal acceleration.

(33) In a further still exemplary embodiment of the present disclosure, a method of controlling a damping characteristic of at least one adjustable shock absorber of a vehicle being operated by a driver is provided. The method comprising receiving with an electronic controller a plurality of inputs from a plurality of sensors supported by the vehicle; predictively determining a longitudinal pitch motion of the vehicle; and adjusting the damping characteristic of the at least one adjustable shock absorber of the vehicle based on the predicted longitudinal pitch motion of the vehicle.

(34) In yet still a further exemplary embodiment of the present disclosure, a snowmobile for propelled movement relative to the ground is provided. The snowmobile comprising a plurality of ground engaging members including an endless track positioned along a centerline vertical longitudinal plane of the snowmobile having a lateral width, a left front ski positioned on a left side of the centerline vertical longitudinal plane of the snowmobile, and a right front ski positioned on a right side of the centerline vertical longitudinal plane of the snowmobile; a frame supported by the plurality of ground engaging members; a steering system supported by the frame and operatively coupled to the left front ski and the right front ski to control a direction of travel of the snowmobile; a left ski suspension operatively coupling the left front ski to the frame; a right ski suspension operatively coupling the right front ski to the frame; a track suspension operatively coupling the endless track to the frame, the track suspension including a plurality of shock absorbers, the plurality of shock absorbers including a first adjustable shock absorber, the first adjustable shock absorber having at least one adjustable damping characteristic, the first adjustable shock absorber being laterally positioned within the lateral width of the endless track and being the forwardmost of the plurality of shock absorbers of the track suspension; a plurality of sensors supported by the ground engaging members; and at least one electronic controller operatively coupled to the first adjustable shock absorber, the at least one electronic controller based on inputs from the plurality of sensors alters at least one damping characteristic of the first adjustable shock absorber.

(35) In an example thereof, the plurality of shock absorbers of the track suspension includes a second shock absorber positioned within the lateral width of the endless track. In a variation thereof, the second shock absorber is an adjustable shock absorber and the electronic controller is operatively coupled to the second shock absorber.

(36) In another example thereof, the left ski suspension includes a third adjustable shock absorber and the right ski suspension includes a fourth adjustable shock absorber, the electronic controller is operatively coupled to the third adjustable shock absorber and the fourth adjustable shock absorber.

(37) Additional features of the present disclosure will become apparent to those skilled in the art upon consideration of the following detailed description of illustrative embodiments exemplifying the best mode of carrying out the invention as presently perceived.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The foregoing aspects and many additional features of the present system and method will become more readily appreciated and become better understood by reference to the following detailed description when taken in conjunction with the accompanying drawings.
- (2) FIG. 1 illustrates a left side view of an exemplary snowmobile;
- (3) FIG. 1A illustrates a left front perspective view of the exemplary snowmobile of FIG. 1 illustrating a yaw-axis, a pitch-axis, and a roll-axis for the snowmobile;
- (4) FIG. 1B illustrates a right front perspective view of another exemplary snowmobile having another exemplary shock setup relative to the endless track of the snowmobile;
- (5) FIG. 1C illustrates a left side view of the exemplary snowmobile of FIG. 1B;
- (6) FIG. 2 illustrates a right side view of the exemplary snowmobile of FIG. 1;
- (7) FIG. 3 illustrates the track suspension of the exemplary snowmobile of FIG. 1;
- (8) FIG. 4 illustrates a representative view of components of the exemplary snowmobile of FIG. 1 including a suspension with a plurality of continuous damping control shock absorbers, an operator interface, and a plurality of sensors integrated with a controller of the snowmobile;
- (9) FIG. 5 illustrates a partial left rear perspective view of the exemplary snowmobile of FIG. 1;
- (10) FIG. 6 illustrates a representative view of components of the exemplary snowmobile of FIG. 1 including a suspension with a plurality of continuous damping control shock absorbers, an operator interface, and a plurality of sensors integrated with a controller of the snowmobile;
- (11) FIG. 7 illustrates a right front perspective view of the exemplary snowmobile of FIG. 1 illustrating a tunnel covering an endless track ground engaging member and a pyramidal frame;
- (12) FIG. 8A illustrates a representative view of an exemplary shock damping logic of the electronic controller of FIG. 6;
- (13) FIG. 8B illustrates a representative view of another exemplary shock damping logic of the electronic controller of FIG. 6;
- (14) FIG. 8C illustrates a representative view of yet another exemplary shock damping logic of the electronic controller of FIG. 6;
- (15) FIGS. 9A-C illustrate an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6 for a continuous damping control shock absorber provided as part of the suspension of a left front ski of the exemplary snowmobile of FIG. 1;
- (16) FIGS. 10A-C illustrate an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6 for a continuous damping control shock absorber provided as part of the suspension of a right front ski of the exemplary snowmobile of FIG. 1;
- (17) FIGS. 11A and 11B illustrate an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6 for a continuous damping control shock absorber provided as part of the suspension for the endless track of the exemplary snowmobile of FIG. 1;
- (18) FIGS. 12A and 12B illustrate an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6 for a continuous damping control shock absorber provided as part of the suspension for the endless track of the exemplary snowmobile of FIG. 1;
- (19) FIG. 13 illustrates an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6 for detecting a g-out event or a chatter event;
- (20) FIG. 14 illustrates an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6 for detecting an exemplary brake event;
- (21) FIG. 15 illustrates an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6 for detecting an exemplary airborne event;
- (22) FIGS. 16A-C illustrates an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6 for detecting an exemplary anti-squat event;
- (23) FIGS. 17A-D illustrates an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6 for detecting an exemplary cornering event;
- (24) FIG. 18 illustrates an exemplary processing sequence of the shock damping logic of the electronic

controller of FIG. 6 for detecting an exemplary driver actuatable suspension adjust input event;
(25) FIGS. 19A and 19B illustrate an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6 for detecting an exemplary launch mode event;
(26) FIG. 20 illustrates an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6 for detecting an exemplary one ski event;
(27) FIG. 21 illustrates the exemplary snowmobile of FIG. 1 airborne;
(28) FIG. 22 illustrates a pitch of snowmobile 10 in deep snow without an adjustment of the damping characteristics of the adjustable shock absorbers;
(29) FIG. 23 illustrates a pitch of snowmobile 10 in deep snow with an adjustment of the damping characteristics of the adjustable shock absorbers;
(30) FIG. 24 illustrates a representative view of an exemplary shock damping logic of the electronic controller of FIG. 6;
(31) FIG. 25 illustrates an exemplary processing sequence of the shock damping logic of the electronic controller of FIG. 6;
(32) FIG. 26 illustrates a left, front, perspective view of a side-by-side off-road recreational vehicle;
(33) FIG. 27 illustrates a left side view of the side-by-side off-road recreational vehicle of FIG. 26;
(34) FIG. 28 illustrates a right side view of the side-by-side off-road recreational vehicle of FIG. 26.
(35) FIGS. 29A-C illustrate exemplary arrangements for inputs of exemplary operator interfaces; and
(36) FIG. 30 illustrates an exemplary input screen for adjusting a gain for various damping profiles.
(37) Corresponding reference characters indicate corresponding parts throughout the several views. Although the drawings represent embodiments of various features and components according to the present disclosure, the drawings are not necessarily to scale and certain features may be exaggerated in order to better illustrate and explain the present disclosure.

DETAILED DESCRIPTION OF THE DRAWINGS

(38) For the purposes of promoting an understanding of the principles of the present disclosure, reference will now be made to the embodiments illustrated in the drawings, which are described below. The embodiments disclosed below are not intended to be exhaustive or limited to the precise form disclosed in the following detailed description. Rather, the embodiments are chosen and described so that others skilled in the art may utilize their teachings.

(39) Referring now to FIGS. 1, 1A, 2-4, and 7, an illustrative embodiment of a snowmobile 10 is shown. Snowmobile 10 includes a chassis or frame 12 having a front frame portion 12a and a rear frame portion 12b. A body assembly 14 generally surrounds at least front frame portion 12a of frame 12. Front frame portion 12a is supported by front ground-engaging members, illustratively skis 16, and rear frame portion 12b is supported by a rear ground-engaging member, illustratively an endless track 18. The rider uses a steering assembly 20, which is operably coupled to at least skis 16 through a steering linkage 17 (see FIG. 7), when operating snowmobile 10. A seat assembly 22 is provided generally rearward of steering assembly 20 and is configured to support the rider.

(40) Front skis 16 are operably coupled to a front left suspension assembly 24 and a right front suspension assembly 24, and endless track 18 cooperates with a rear suspension assembly 26. A powertrain assembly is positioned generally intermediate front suspension assembly 24 and rear suspension assembly 26, and provides power to endless track 18 to move snowmobile 10. More particularly, the powertrain assembly 30 includes an engine (see prime mover 110, see FIG. 1C), a transmission, and a drive shaft. In one embodiment, the transmission includes a shiftable transmission and a continuously variable transmission (“CVT”) 111 (see FIG. 1C). In embodiments, the shiftable transmission includes a forward low gear, a forward high gear, a reverse gear, a neutral setting, and a park setting.

(41) As shown in FIG. 3, rear suspension assembly 26 includes a plurality of slide rails 32, a front track adjustable shock absorber 144 positioned inside of an interior of endless track 18, a rear track adjustable shock absorber 146 positioned inside of the interior of endless track 18, a plurality of torque arms 36 operably coupled to a forward, lower end of rear track adjustable shock absorber 146, and a link assembly 38 operably coupled to a rear, upper end of rear track adjustable shock absorber 146. In one embodiment, torque arms 36 may be comprised of forged aluminum, which may reduce the overall weight of snowmobile 10. Additionally, rear suspension assembly 26 may include front track adjustable shock absorber 144 positioned forward of rear track adjustable shock absorber 146 and operably coupled to

torque arms **36** and slide rails **32**.

(42) Rear suspension assembly **26** also includes a plurality of rear idler wheels **42** rotatably coupled to the rear end of slide rails **32** and a plurality of carrier wheels **44** laterally adjacent the rear, upper end of rear track adjustable shock absorber **146**. Rear idler wheels **42** and carrier wheels **44** are configured to maintain tension in endless track **18**. Additionally, the position of rear idler wheels **42** on slide rails **32** may be adjusted to adjust the tension in endless track **18**. As shown in FIGS. **1** and **2**, endless track **18** generally surrounds rear suspension assembly **26** and is supported on at least slide rails **32**, rear idler wheels **42**, and carrier wheels **44**. Rear suspension assembly **26** is configured to cooperate with endless track **18** when snowmobile **10** is operating. In particular, rear suspension assembly **26** is configured to move longitudinally and vertically during operation of snowmobile **10**, and the tension in endless track **18** is maintained throughout the movement of rear suspension assembly **26** by at least rear idler wheels **42**.

(43) Referring to FIGS. **1B** and **1C**, a snowmobile **10'** is shown having a different rear suspension **24'** than snowmobile **10**. Rear suspension **24'** positions front track adjustable shock absorber **144** inside the interior of the endless track **18** and rear track adjustable shock absorber **146** outside of the interior of endless track **18** and, in particular, above endless track **18**. As shown in FIG. **1A**, endless track **18** has a lateral width **W**. For each of snowmobile **10** and snowmobile **10'**, front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** are laterally positioned within the later width **W** of endless track **18**. Throughout the disclosure, snowmobile **10** should be interpreted to read snowmobile **10**, **10'** in discussing the damping characteristics of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**.

(44) Right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** are adjustable shock absorbers, the damping characteristics of which are continuously controlled by an electronic controller **100**. In embodiments, endless track **18** includes one adjustable shock absorbers and a standard shock absorber, such as a manually adjustable shock absorber. In embodiments, electronic controller **100** updates the damping characteristics of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** during movement of snowmobile **10**, **10'**. Electronic controller **100** continuously controls right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** by updating the desired damping characteristics of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based on monitored sensor values, received operator inputs, and/or other inputs at discrete instances of time. An exemplary time interval is about 1 milli-seconds to about 5 milliseconds. For example, electronic controller **100** updates targets for each of right front adjustable shock absorber **140**, **142**, front track adjustable shock absorber **144**, rear track adjustable shock absorber **146** about every 5 milliseconds and updates the current control loop about every milli-second.

(45) In embodiments, the damping characteristics of front track adjustable shock absorber **144** are controlled by electronic controller **100** while rear track adjustable shock absorber **146** is manually adjustable independent of electronic controller **100**. In embodiments, the damping characteristics of rear track adjustable shock absorber **146** are controlled by electronic controller **100** while front track adjustable shock absorber **144** is manually adjustable independent of electronic controller **100**. In embodiments, the arrangement and control of one or both of front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** of rear suspension **26** is applicable to single front ski vehicles, such as snowbikes. A snowbike may have one or more shocks associated with the front ski. These one or more shocks may be adjustable shock absorbers controlled by controller **100** in a similar manner as right front adjustable shock absorber **140** and left front adjustable shock absorber **142**.

(46) In embodiments, right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** include solenoid valves mounted at the base of the shock body or internal to a damper piston of the respective right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**. The stiffness of the shock absorber is

increased or decreased by introducing additional fluid to the interior of the shock absorber, removing fluid from the interior of the shock absorber, and/or increasing or decreasing the ease with which fluid can pass from a first side of a damping piston of the shock absorber to a second side of the damping piston of the shock absorber. In another embodiment, right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** include a magnetorheological fluid internal to the respective right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**. The stiffness of the shock is increased or decreased by altering a magnetic field experienced by the magnetorheological fluid. Additional details on exemplary adjustable shocks are provided in US Published Patent Application No. 2016/0059660, filed Nov. 6, 2015, titled VEHICLE HAVING SUSPENSION WITH CONTINUOUS DAMPING CONTROL, assigned to the present assignee, the entire disclosure of which is expressly incorporated by reference herein. In one embodiment, right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** each include a first controllable proportional valve to adjust compression damping and a second controllable proportional valve to adjust rebound damping. In another embodiment, right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** each include a combination proportional valve which controls both compression damping and rebound damping.

(47) Additional details of frame **12**, body assembly **14**, endless track **18**, front suspension assembly **24**, rear suspension assembly **26**, and the powertrain assembly for snowmobile **10**, **10'** and other exemplary snowmobiles are disclosed in U.S. Pat. Nos. 7,891,454, 8,590,654, 8,820,458, 8,944,204, 9,428,232, 9,540,072, 9,809,195, and 10,358,187, the complete disclosures of which are expressly incorporated by reference herein

(48) Referring to FIG. 4, electronic controller **100** includes at least one processor **104** and at least one non-transitory computer readable medium, memory **106**. In embodiments, electronic controller **100** is a single unit that controls the operation of various systems of snowmobile **10**. In embodiments, electronic controller **100** is a distributed system comprised of multiple controllers each of which control one or more systems of snowmobile **10** and may communicate with each other over one or more wired and/or wireless networks. For example, electronic controller **100** may include a suspension controller **200** (see FIG. 6) which controls the damping characteristics of each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** and an engine controller **204** which controls the operation of a prime mover **110** (see FIG. 4) of snowmobile **10**.

(49) Electronic controller **100** includes shock damping logic **150** which controls the damping characteristics of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**. The term "logic" as used herein includes software and/or firmware executing on one or more programmable processors, application-specific integrated circuits, field-programmable gate arrays, digital signal processors, hardwired logic, or combinations thereof. Therefore, in accordance with the embodiments, various logic may be implemented in any appropriate fashion and would remain in accordance with the embodiments herein disclosed. A non-transitory machine-readable medium comprising logic can additionally be considered to be embodied within any tangible form of a computer-readable carrier, such as solid-state memory, magnetic disk, and optical disk containing an appropriate set of computer instructions and data structures that would cause a processor to carry out the techniques described herein. This disclosure contemplates other embodiments in which electronic controller **100** is not microprocessor-based, but rather is configured to control operation of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based on one or more sets of hardwired instructions.

(50) Returning to FIG. 4, electronic controller **100** provides the electronic control of and/or monitors the various components of snowmobile **10**, illustratively prime mover **110**, a steering system **120**, and a braking system **122**. Exemplary prime movers include two-cycle combustion engines, four-cycle combustion engines, electric motors, and other suitable motive devices. Prime mover **110** is operatively

coupled to endless track **18** through a transmission. Exemplary transmissions include shiftable transmissions, continuously variable transmissions, and combinations thereof. An exemplary steering system **120** is shown in FIG. 7 including handlebars **124** attached to a steering post **126** which in turn is coupled to a steering linkage **128**. The steering linkage **128** is coupled to skis **16** to adjust an orientation of skis **16** relative to the ground.

(51) Further, electronic controller **100** is operatively coupled to a plurality of sensors **130** (see FIG. 4) which monitor various parameters of snowmobile **10** or the environment surrounding snowmobile **10**. Exemplary sensors **130** include a global positioning sensor (GPS) **131**, an inertial measurement unit (“IMU”) **132**, an engine speed sensor **133**, a brake switch **134**, a brake pressure sensor **135**, a steering angle sensor **136**, a transmission gear selection sensor **137**, a throttle position sensor **138**, a vehicle speed sensor **139**, an air pressure sensor **141**.

(52) GPS sensor **131** provides a location of snowmobile **10** on the surface of the earth. IMU **132** includes a three-axis accelerometer and a three-axis gyroscope. Referring to FIG. 1A, the three-axis accelerometer provides acceleration data of snowmobile **10** along axes **160**, **162**, and **164** and the three-axis gyroscope provides angular information regarding rotation about each of axes **160**, **162**, and **164**. IMU **132** is illustratively supported (see FIG. 7) on the chassis **150** of snowmobile **10** to provide an indication of acceleration forces of the vehicle during operation. In embodiments, IMU **132** is attached to a tunnel **154** of chassis **150** which covers track **18**. In embodiments, IMU **132** is attached to an over structure frame **156** of chassis **150**. In embodiments, IMU **132** is located within an interior of an over structure frame **156** of chassis **150**. In embodiments, IMU **132** is located vertically in line with a steering post **126** (see FIG. 7) of snowmobile **10** within an interior of an over structure frame **156** of chassis **150**. In embodiments, IMU **132** is mounted proximate to frame **156**, such as on a front side of a fuel tank **114** (see FIG. 1C) or integrated into a wall of the fuel tank. In embodiments, IMU **132** is located longitudinally between a fuel tank and a prime mover **110** of snowmobile **10**. In embodiments, IMU **132** is located between a spindle **116** (see FIG. 1C) of the left ski **16** and a rear end **118** of a fuel tank **114** supported by the plurality of ground engaging members. In embodiments, IMU **132** is located along a longitudinal centerline plane snowmobile **10**. In embodiments, IMU **132** is located at a center of gravity of snowmobile **10**. In embodiments, IMU **132** is offset from the center of gravity of snowmobile **10** and the readings of the three-axis gyroscope are used by electronic controller **100** to determine the acceleration values of snowmobile **10** at the center of gravity of snowmobile **10**. In one embodiment, IMU is integrated into electronic controller **100**, such as integrated into suspension controller **200**. In one embodiment, IMU is spaced apart from electronic controller **100**. In embodiments, IMU **132** is isolated from chassis **150** with isolation mounts, such as rubber mounts, to reduce the amount of engine vibration experienced by the IMU **132**.

(53) Engine speed sensor **133** monitors a crankshaft speed of the engine. In embodiments, the crankshaft speed is provided to controller **100** by the engine control module (“ECU”).

(54) Brake switch **134** monitors an actuation of an operator brake input, such as a foot actuated input or a hand actuated input. Steering angle sensor **136** monitors a rotation angle of steering post **126** (see FIG. 7). In embodiments, steering system **120** includes an electronic power steering unit. In embodiments, steering system does not include an electronic power steering unit. In the embodiments without an electronic power steering unit, steering angle sensor **136** is supported either in front of the engine below the exhaust ports of the engine or rearward of the engine and above the throttle bodies of the engine.

(55) Throttle position sensor **138** monitors an actuation of a throttle input, such as a foot actuated input or a hand actuated input. Vehicle speed sensor **139** monitors a ground speed of snowmobile **10**. In one example, a speed of endless track **18** is monitored by vehicle speed sensor **139** and used as an indication of the speed of snowmobile **10** relative to the ground. In embodiments, snowmobile **10** has a single vehicle speed sensor **139** which monitors a movement of endless track **18**.

(56) Brake pressure sensor **135** is a transducer that measures the pressure in applied by the operator in the brake lines of the braking system.

(57) Steering angle sensor **136** monitors a rotational movement of the steering column or monitors other movements of portions of the steering system.

(58) Transmission gear selection sensor **137** monitors an input from the engine control module of the gear selection for a shiftable transmission and/or a rotational direction of the crankshaft for forward and

reverse directions.

(59) Vehicle speed sensor **139** measures ground speed by monitoring a rotational speed of the track drive shaft or other measurements of rotational members of the drive line which are indicative of ground speed.

(60) Air pressure sensor **141** monitors one of ambient barometric pressure and/or the manifold air pressure in the engine intake system.

(61) Electronic controller **100** also interacts with an operator interface **180** (see FIGS. **4** and **5**) which includes at least one input device **182** and at least one output device **184**. Exemplary input devices **182** include levers, buttons, switches, soft keys, and other suitable input devices. Exemplary output devices **184** include lights, displays, audio devices, tactile devices, and other suitable output devices. In embodiments, operator interface **180** includes a display **190**, such as a touch screen display, and electronic controller **100** interprets various types of touches to the touch screen display as inputs and controls the content displayed on touch screen display.

(62) Referring to FIG. **5**, operator interface **180** may include one or more switches **192**, one or more inputs **194** supported by handlebars **124**, and one or more parts of an instrument cluster **196** which may include display **190**. In embodiments, referring to FIG. **6**, operator interface **180** includes a mode select input **170**, a driver actuatable suspension adjust input **172**, and a launch mode input **174**. The mode select input permits an operator to select between at least three setups of snowmobile **10**, each having predefined base damping characteristics for right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**.

(63) Exemplary modes selectable with mode select input **170** include a comfort mode, a handling mode, and a rough trail mode. In the comfort mode both compression and rebound damping of each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** are lower than the rough trail mode. In one example, the compression and rebound damping are generally constant for vehicle speed and longitudinal acceleration. In the rough trail mode, the compression damping of each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** are generally higher than the comfort mode and the handling mode based on vehicle speed and longitudinal acceleration. The rebound damping in the rough trail mode will be maintained or lowered the respective shock absorbers will be more prone to extend and therefore have more shock length to absorb compression events. In the handling mode, the compression damping of each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** is lower than the comfort mode and the rough handling mode based on vehicle speed and longitudinal acceleration and the rebound damping is higher than the comfort mode based on vehicle speed and longitudinal acceleration. The dynamic ride height for snowmobile **10** is lowest for the handling mode and highest for the rough trail mode. In embodiments, the selected mode provides base damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**. These base damping characteristics are updated by controller **200** based on the movement or predicted movement of snowmobile **10**. Exemplary updates for the damping characteristics are provided herein. In embodiments, for the predicted longitudinal acceleration of the snowmobile **10**, controller **200** actively reviews the engine torque and/or throttle position and adjusting the compression and rebound damping to counter predicted motion of snowmobile **10**, such as diving or squatting. In an example, snowmobile **10** is traveling 80 MPH and the operator drops the throttle to 0%. In response, controller **200** increases the compression damping in right front adjustable shock absorber **140** and left front adjustable shock absorber **142** to counter a front end dive of snowmobile **10** and increases the rebound damping in front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** to counter the lifting of the rear end.

(64) In embodiments, a longitudinal acceleration of snowmobile **10** is measured based on one or more inputs, such as IMU **132**, estimated based on one or more inputs, such as a monitored throttle position and/or a monitored engine rpm, or predicted based on one or more inputs as described herein.

(65) In embodiments, an operator may provide a gain coefficient to one or more damping profiles. Referring to FIG. **30**, an exemplary input screen **1200** for display **190** is shown. Input screen **1200** is a

custom suspension mode screen. An operator selects which mode to modify, by selecting one of comfort mode input **1202**, sport mode input **1204**, and firm mode input **1206**. Also shown in FIG. **30** are slider inputs, illustratively base gain input **1210**, braking gain input **1212**, acceleration gain input **1214**, and steering or cornering gain input **1216**. Each of base gain input **1210**, braking gain input **1212**, acceleration gain input **1214**, and steering post **126** have a respective slider **1220**, **1222**, **1224**, and **1226**. When a slider is centered, such as base gain slider **1220** of base gain input **1210**, no change is made to the standard base damping profile for the selected mode. Moving a respective slider to the left on input screen **1200** reduces the standard base damping profile for the selected mode while moving a respective slider to the right on steering system **120** increases the standard base damping profile for the selected mode. In embodiments, a first screen is provided for right front adjustable shock absorber **140** and left front adjustable shock absorber **142** and a second screen is provided for front track adjustable shock absorber **144** and rear track adjustable shock absorber **146**.

(66) In embodiments, input screen **1200** further includes inputs for selecting one passenger (driver only) or two passengers and for indicating cargo weight. In embodiments, one or more of the damping profiles are adjusted automatically based on an input of the operator, such as the recognition of the operator and their rider profile settings in a rider profile. The rider profile may be stored in the electronic controller of the snowmobile **10**, in a personal computing device (such as a mobile phone), a key fob, or retrieval from the cloud or remote computing device.

(67) Referring to FIG. **29A**, an exemplary embodiment **1100** of operator interface **180** is illustrated. FIG. **29A** illustrates a portion of the left handlebar **124** including a hand grip portion **1102** to be grasped by the left hand of the operator and an input housing **1104**. Hand grip portion **1102** includes a longitudinal axis **1103**. Input housing **1104** includes a plurality of actuatable inputs **1106A-C** on a front face **1108** of input housing **1104** facing the seat **22**. Exemplary inputs include a light input, heated grips input, and control inputs for display **190**. Inputs **1106A-C** may be any type of actuatable inputs including buttons, membrane switches, rockers, and other suitable inputs. Additional inputs are provided on a top face **1110** of input housing **1104**. In embodiments, mode selection inputs **170** (up and down buttons for cycling through modes) and driver actuatable suspension adjust input **172** are provided on top face **1110** of input housing **1104**. Inputs **170** and **172** may be any type of actuatable inputs including buttons, membrane switches, rockers, levers, triggers, and other suitable inputs. In embodiments, input **172** is positioned within a finger's or thumb's touch distance of a hand grip so that it may be actuated without requiring the operator to remove their hand from the grip. In embodiments, one or both of input **170** and input **172** may be positioned on front face **1108** and actuatable therefrom.

(68) Referring to FIG. **29B**, an exemplary embodiment **1130** of operator interface **180** is illustrated. FIG. **29B** illustrates a portion of the left handlebar **124** including a hand grip portion **1102** to be grasped by the left hand of the operator and an input housing **1104**. Hand grip portion **1102** includes a longitudinal axis **1103**. Input housing **1104** includes a plurality of actuatable inputs **1106A-C** on a front face **1108** of input housing **1104** facing the seat **22**. Exemplary inputs include a light input, heated grips input, and control inputs for display **190**. Inputs **1106A-C** may be any type of actuatable inputs including buttons, membrane switches, rockers, and other suitable inputs. Additional inputs are provided on a top face **1110** of input housing **1104**. In embodiments, mode selection inputs **170** (up and down buttons for cycling through modes) is provided on top face **1110** of input housing **1104**. Additional inputs are provided on a rear face **1134** of input housing **1104**, rear face **1134** being opposite of front face **1108**. In embodiments, driver actuatable suspension adjust input **172** is provided on rear face **1134** of input housing **1104**. Inputs **170** and **172** may be any type of actuatable inputs including buttons, membrane switches, rockers, levers, triggers, and other suitable inputs. Driver actuatable suspension adjust input **172** is depressed in direction **1132** towards front face **1108** to actuate driver actuatable suspension adjust input **172**. In embodiments, input **172** is a lever or trigger which is one of pulled toward the operator in actuation or pushed away from the operator in actuation.

(69) Referring to FIG. **29C**, an exemplary embodiment **1150** of operator interface **180** is illustrated. FIG. **29C** illustrates a portion of the left handlebar **124** including a hand grip portion **1102** to be grasped by the left hand of the operator and an input housing **1104**. Hand grip portion **1102** includes a longitudinal axis **1103**. Input housing **1104** includes a plurality of actuatable inputs **1106A-C** on a front face **1108** of input housing **1104** facing the seat **22**. Exemplary inputs include a light input, heated grips input, and control

inputs for display **190**. Inputs **1106A-C** may be any type of actuatable inputs including buttons, membrane switches, rockers, and other suitable inputs. Additional inputs are provided on a top face **1110** of input housing **1104**. In embodiments, mode selection inputs **170** (up and down buttons for cycling through modes) is provided on top face **1110** of input housing **1104**. Additional inputs are provided on a hand grip side face **1152** of input housing **1104**. In embodiments, driver actuatable suspension adjust input **172** is provided on hand grip side face **1152** of input housing **1104**. Inputs **170** and **172** may be any type of actuatable inputs including buttons, membrane switches, rockers, and other suitable inputs. Driver actuatable suspension adjust input **172** is depressed in direction **1154** along **1103** to actuate driver actuatable suspension adjust input **172**. In embodiments, the stroke of input **172** in direction **1154** is about 0.25 inches. In embodiments, input **172** includes tactile feedback to the operator of depression. In one example, input **172** and input housing **1104** cooperate to provide a “click” feel at the end of stroke of input **172** in direction **1154**. In embodiments an operator interface surface of input **172** is a half-moon shape and can be actuated from hand grip face **1152** or front face **1108**.

(70) Although FIGS. **29A-C**, illustrate exemplary placements for driver actuatable suspension adjust input **172**, other inputs may occupy the respective positions. In embodiments, launch mode input **174** replaces driver actuatable suspension adjust input **172**.

(71) In embodiments, input **172** may be provided as one input of a multi-functional input device. For example, the multi-functional input device may provide the functionality of input **172** in response to a first actuation characteristic(s) (such as a sequence) and another functionality, such as mode change, in response to a second actuation characteristic(s) (such as a sequence).

(72) The driver actuatable suspension adjust input **172** permits an operator to request a maximum stiffness for one or more of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**. Exemplary operation of a driver actuatable suspension adjust input is discussed in U.S. Pat. No. 10,406,884, assigned to the assignee of the present application, the entire disclosure of which is incorporated by reference herein. Electronic controller **100** controls the operation of output devices **184** and monitors the actuation of input devices **182**. Referring to FIG. **6**, in embodiments, display **190** is operatively coupled to electronic controller **100** (illustratively suspension controller **200**) over a network, illustratively a CAN network.

(73) Referring to FIG. **8A**, shock damping logic **150** includes one or more processing sequences **202** which control the damping characteristics of one or more of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**. In embodiments, shock damping logic **150** includes one or more functions which based on one or more inputs output a desired damping characteristic for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**.

(74) Referring to FIG. **8B**, shock damping logic **150** includes one or more processing sequences **202** which control the damping characteristics of one or more of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** and one or more look-up tables **204** which based on one or more inputs provides damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**.

(75) Referring to FIG. **8C**, shock damping logic **150** includes one or more processing sequences **202** which control the damping characteristics of one or more of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** and one or more look-up tables **204** which based on one or more inputs provides damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**. Exemplary look-up tables include airborne time event table **210**, driver actuatable suspension adjust input event table **212**, brake event table **214**, anti-dive event table **216**, one ski event table **218**, brake corner event table **220**, chatter corner event table **222**, g-out event table **224**, chatter event table **226**, corner event table **228**, base damping table **230**, launch mode event table **232**, anti-squat event table **234**, and a predictive longitudinal acceleration and predictive vehicle pitch table **236**. The use of look-up tables **204**

by processing sequences **202** are illustrated in the exemplary processing sequences of FIGS. **9-20** and **24**. In embodiments, electronic controller **200** executes the exemplary processing sequences generally continuously while monitoring for operator inputs and sensor values. In one embodiment, electronic controller **200** updates the damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** every about 1 to about 5 milliseconds. For example, electronic controller **100** updates targets for each of right front adjustable shock absorber **140**, **142**, front track adjustable shock absorber **144**, rear track adjustable shock absorber **146** about every 5 milliseconds and updates the current control loop about every 1 millisecond.

(76) Electronic controller **200** when executing processing sequences **202** arbitrates which damping characteristics to use for right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based on the sensed values from sensors **130** and inputs from operator interface **180**. In embodiments, the arbitration of electronic controller **200** for compression damping may be prioritized with airborne detection compression damping having the highest priority, followed by driver actuable suspension adjust input **172** compression damping having the next highest priority, followed by cornering detection compression damping, followed by braking detection compression damping, followed by the maximum of the base compression damping based on mode selection and acceleration based detection compression damping. In one example, wherein the predictive longitudinal acceleration and predictive vehicle pitch processing sequence is used, the braking detection damping is taken into account with the predictive acceleration and pitch and thus following cornering detection compression damping is the maximum of the base compression damping based on mode selection and the predictive longitudinal acceleration and predictive vehicle pitch based detection compression damping. In embodiments, the arbitration of electronic controller **200** for rebound damping may be prioritized with airborne detection rebound damping having the highest priority including post landing time, followed by cornering detection rebound damping, followed by braking detection rebound damping, followed by the maximum of the base rebound damping based on mode selection and acceleration based detection rebound damping. In one example, wherein the predictive longitudinal acceleration and predictive vehicle pitch processing sequence is used the braking detection rebound damping is taken into account with the predictive acceleration and pitch and thus following cornering detection rebound damping is the maximum of the base rebound damping based on mode selection and the predictive longitudinal acceleration and predictive vehicle pitch based detection rebound damping. The above are exemplary arbitration priorities and different processing sequences may include different arbitration priorities based on the event detection tables provided and the desired performance of the vehicle.

(77) Referring to FIG. **24**, predictive longitudinal acceleration and predictive pitch table **236** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based on one or both of a predicted longitudinal acceleration of snowmobile **10** and a predicted pitch of snowmobile **10**. Shock damping logic **150** based on a predicted vehicle longitudinal acceleration **240** and/or a predicted vehicle pitch **242** alters the damping characteristics of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**.

(78) When both the predicted longitudinal acceleration **240** and the predicted vehicle pitch **242** are taken into account, shock damping logic **150** is able to adjust right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** for acceleration of snowmobile **10** including minimizing vehicle squat during acceleration and minimizing vehicle dive during deceleration. In one example, a predicted increase in the longitudinal acceleration results in shock damping logic **150** altering, such as increasing, the compression damping of front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** to reduce the chance of skis **16** being lifted off of the snow and alters, such as increases the rebound damping of right front adjustable shock absorber **140** and left front adjustable shock absorber **142**. Further, the rebound damping may be increased on the front track adjustable shock absorber **144**. In another example, when the predicted vehicle pitch indicates the rear of snowmobile **10** is predicted to

drop and the predicted longitudinal acceleration is increasing, shock damping logic **150** increases the compression damping of right front adjustable shock absorber **140** and left front adjustable shock absorber **142** and decreases the rebound damping of right front adjustable shock absorber **140** and left front adjustable shock absorber **142** to promote a lifting of skis **16** off of the snow. In a further embodiment, when the predicted longitudinal acceleration is decreasing and the predicted vehicle pitch indicates the front of snowmobile **10** is predicted to drop, shock damping logic **150** increases the compression damping of right front adjustable shock absorber **140** and left front adjustable shock absorber **142** to reduce diving of the front of snowmobile **10** and, alter, such as increases or decreases the compression damping of front track adjustable shock absorber **144** to promote track **18** pressure on the snow and to absorb bumps.

(79) The predicted longitudinal acceleration **240** and the predicted vehicle pitch **242** are also applicable to other off-road recreational vehicles including side-by-side vehicles, such as vehicle **2000** shown in FIGS. **26-28**. Vehicle **2000** includes a pair of front wheels **2002** and a pair of rear wheels **2004** supporting a frame **2006**. Vehicle **2000** includes a driver seat **2010** and a passenger seat **2012** arranged in a side-by-side arrangement. Each of the front wheels **2002** are coupled to frame **2006** through front suspensions **2020** including shock absorbers **2022**, **2024** which may be adjustable shock absorbers as described herein. Each of the rear wheels **2004** are coupled to frame **2006** through rear suspensions **2030** including shock absorbers **2032**, **2034** which may be adjustable shock absorbers as described herein. Additional details regarding vehicle **2000** are provided in US Published Patent Application US2019/0210668, filed Jan. 10, 2019, titled VEHICLE, the entire disclosure of which is expressly incorporated by reference herein.

(80) Referring to FIG. **25**, an exemplary processing sequence **250** of suspension controller **200** for determining a predicted longitudinal acceleration **240** and a predicted vehicle pitch **242** of snowmobile **10** is illustrated. A predicted power for prime mover **110**, for example an internal combustion engine, is determined, as represented by block **252**. In one example, an engine torque is provided from an engine controller of the vehicle. The engine torque is multiplied by a measured engine speed measured by engine speed sensor **133** to determine a power output of the engine. In another example, a throttle position is measured and with a look-up table a corresponding engine torque is provided. Again, the engine torque is multiplied by an engine speed to obtain the output power of the engine. In embodiments, a value is measured by air pressure sensor **141** and the look-up table used to determine engine torque is multi-dimensional and includes torque values for different air pressures. In one example, air pressure sensor **141** measures an air pressure associated with an airbox of the snowmobile **10**. In another example, air pressure is measured indirectly by GPS sensor **131** which determines a location of snowmobile **10** and based on a look-up table provides an ambient air pressure reading for that elevation either actual from a third party service or typical based on a look-up table.

(81) The determined engine power is then multiplied by an efficiency factor for the transmission of snowmobile **10** to provide an output power for the drivetrain, as represented by block **254**. In one example, the efficiency factor accounts for losses associated with the CVT transmission. The output power of the drivetrain is converted to a forward moving force of the vehicle by dividing the output power of the drivetrain by the vehicle speed measured by vehicle speed sensor **139**, as represented by block **256**.

(82) A resultant or composite forward moving force is determined by subtracting from the determined forward moving force of block **256** a coast down force of the vehicle and a braking force, as represented by block **258**. The coast down force of the vehicle is determined through a look-up table as a function of a measured vehicle speed measured by vehicle speed sensor **139**. The braking force is determined through a look-up table of braking force as a function of a measured brake pressure measured by brake pressure sensor **135**.

(83) A predicted vehicle longitudinal acceleration is determined by dividing the resultant forward moving force by the mass the vehicle, as represented by block **260**. In one example, a standard mass of the vehicle is used.

(84) The predicted vehicle longitudinal acceleration is compared to tractive limits and set equal to the respective tractive limit (a negative tractive limit for a deceleration of snowmobile **10** and a positive tractive limit for an acceleration of snowmobile **10**) if the predicted longitudinal acceleration exceeds the respective tractive limit, as represented by block **262**.

(85) In embodiments, the predicted vehicle acceleration from block 262 is filtered, as represented by block 264, to provide a smoother response. The filtering is helpful to account for the time difference between a determined engine output power and an acceleration of snowmobile 10 and to account for different sampling rates of the various sensors.

(86) The filtered predicted vehicle longitudinal acceleration is used to determine a predicted pitch motion of snowmobile 10. A direction of travel of snowmobile 10 is determined, as represented block 266. Once a direction of travel is known, forward or reverse, the effect of the acceleration or deceleration on the front and rear of the vehicle can be considered. In one example, a gear selection sensor 137 is provided as part of the shiftable transmission of snowmobile 10 and provides an indication of whether the shiftable transmission is in a forward gear or a reverse gear. In another example, the gear selection sensor monitors in an electric reverse input (not shown) has been actuated. Upon actuation of the electric reverse input, the engine of snowmobile 10 is stalled and then fired in a reverse direction to change the rotation of the output shaft of the engine.

(87) The predicted magnitude of the pitch motion is determined by taking the derivative of the filtered predicted vehicle longitudinal acceleration, as represented by block 268. This predicted vehicle pitch motion value is filtered to provide a smoother result over time, as represented by block 270. The predicted vehicle pitch motion 242 and/or the predicted vehicle longitudinal acceleration 240 are used by shock damping logic 150 to adjust the damping characteristics of right front adjustable shock absorber 140, left front adjustable shock absorber 142, front track adjustable shock absorber 144, and rear track adjustable shock absorber 146, as represented by block 272.

(88) In embodiments, the predicted vehicle longitudinal acceleration and the predicted vehicle pitch motion are used to alter the base damping of right front adjustable shock absorber 140, left front adjustable shock absorber 142, front track adjustable shock absorber 144, and rear track adjustable shock absorber 146 which may be set by the selected vehicle mode (comfort, handling, and rough trail). The damping characteristic tables for compression of each of right front adjustable shock absorber 140, left front adjustable shock absorber 142, front track adjustable shock absorber 144, and rear track adjustable shock absorber 146 and the damping characteristics tables for rebound of each of right front adjustable shock absorber 140, left front adjustable shock absorber 142, front track adjustable shock absorber 144, and rear track adjustable shock absorber 146 may be two-dimensional (one input, one output damping characteristic), three-dimensional (two inputs, one output damping characteristic), or x dimensional (x-1 inputs, one output damping characteristic).

(89) In embodiments, the base damping tables are two-dimensional map for each of right front adjustable shock absorber 140, left front adjustable shock absorber 142, front track adjustable shock absorber 144, and rear track adjustable shock absorber 146 and each of compression damping characteristic and rebound characteristic (two inputs, one output). The two inputs are vehicle speed and predicted longitudinal vehicle acceleration and the output depending on the table is one of compression damping and rebound damping. In one example, vehicle speed is measured by vehicle speed sensor 139 and the predicted longitudinal vehicle acceleration is determined by processing sequence 250.

(90) Referring to FIG. 8C, predictive longitudinal acceleration and pitch motion table 236 provides damping characteristics for right front adjustable shock absorber 140, left front adjustable shock absorber 142, front track adjustable shock absorber 144, and rear track adjustable shock absorber 146 based on a predicted longitudinal vehicle acceleration and a predicted vehicle pitch motion. Assuming snowmobile 10 is traveling forward, for a predicted constant longitudinal acceleration (no or minimal predicted pitch motion) shock damping logic 150 increases the rebound damping characteristic for right front adjustable shock absorber 140 and left front adjustable shock absorber 142 and, optionally, reduce the compression damping characteristic for right front adjustable shock absorber 140 and left front adjustable shock absorber 142. For a predicted increase in the vehicle pitch motion (a rearward pitch) shock damping logic 150 further increases the rebound damping characteristic of right front adjustable shock absorber 140 and left front adjustable shock absorber 142 and increase the compression damping characteristic for front track adjustable shock absorber 144 and rear track adjustable shock absorber 146 for the duration of the predicted vehicle pitch motion.

(91) Assuming snowmobile 10 is traveling forward, for a predicted constant longitudinal deceleration (no or minimal pitch) shock damping logic 150 increases the rebound damping characteristic and decreases

the compression damping characteristic for right front adjustable shock absorber **140** and left front adjustable shock absorber **142** and, optionally, increases the rebound damping characteristic for front track adjustable shock absorber **144** and rear track adjustable shock absorber **146**. For a predicted decrease in the vehicle longitudinal pitch motion (a forward pitch) shock damping logic **150** further increases the compression damping characteristic of right front adjustable shock absorber **140** and left front adjustable shock absorber **142** and alters, such as increases, the rebound damping characteristic for front track adjustable shock absorber **144** and alters, such as increases, a rebound damping of the rear track adjustable shock absorber **146** for the duration of the predicted vehicle pitch motion. For a predicted increase in the vehicle longitudinal pitch motion (a rearward pitch) shock damping logic **150** alters, such as increases, the compression damping characteristic front track adjustable shock absorber **144** and alters, such as increases, a compression damping of the rear track adjustable shock absorber **146** for the duration of the predicted vehicle pitch motion. Further, for a predicted increase in the vehicle longitudinal pitch motion (a rearward pitch) shock damping logic **150** alters, such as increases, the rebound damping characteristic of the rear track adjustable shock absorber **146** for the duration of the predicted vehicle pitch motion. Additionally, for a predicted increase in the vehicle longitudinal pitch motion (a rearward pitch) shock damping logic **150** alters, such as increases, the rebound damping characteristic of the right front adjustable shock absorber **140** and the left front adjustable shock absorber **142** for the duration of the predicted vehicle pitch motion

(92) Returning to FIG. **8C**, airborne time table **210** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based on the elapsed time that snowmobile **10** has been airborne. An example of snowmobile **10** being airborne is illustrated in FIG. **21**. In embodiments, airborne time table **210** specifies a percentage of available damping range for compression damping only, for rebound damping only, or for both compression damping and rebound damping for one or more time period ranges of airborne detection. For example, a first percentage for a first time range of airborne elapsed time detection and a second percentage for a second time range of airborne elapsed time detection.

(93) In embodiments, upon detection of an airborne state, the compression damping characteristics for right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** provide an increased damping percentage over the base damping tables and continue to increase as the detected airborne time continues to increase. The increased compression damping is held after airborne event has concluded to make sure the added compression damping is used through the entire compression stroke of the respective shocks. In one example, the increased compression damping is held for about 300 milliseconds. The increased compression damping is stepped back down to the base damping level for normal operation of snowmobile **10** or is altered to another level if a different event is detected, such as acceleration, braking or cornering.

(94) In embodiments, upon detection of an airborne state, the rebound damping characteristics for right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** go to a minimal value, such as zero to promote shock extension. Once snowmobile **10** has landed, the rebound damping characteristic increases to stabilize the landing and reduce the occurrence of vehicle hops. The amount of rebound increase is based on airborne time (higher for longer airborne times). This provides different responses between small airborne events, like whoops, and larger airborne events so it can activate differently in whoops (medium size bumps on trail) versus big jumps which have longer air times. Rebound damping is held at the minimal level while snowmobile **10** is airborne and upon initial landing increased and held for a time period generally equal to the first extension stroke of the respective shock after compression. An advantage among others is that this keeps the track and skis in contact with the snow more for increased traction and stability.

(95) In embodiments, IMU **132** is used to detect when snowmobile **10** is airborne by monitoring acceleration along axis **164** (see FIG. **1A**). Exemplary detection of an airborne event is described in US Published Patent Application No. 2016/0059660, filed Nov. 6, 2015, titled VEHICLE HAVING SUSPENSION WITH CONTINUOUS DAMPING CONTROL, assigned to the present assignee, the

entire disclosure of which is expressly incorporated by reference herein. Additional exemplary detection methodologies for an airborne event are described in U.S. Pat. No. 9,381,810, filed Jun. 3, 2011, titled ELECTRONIC THROTTLE CONTROL, assigned to the present assignee, the entire disclosure of which is expressly incorporated by reference herein.

(96) Driver actuatable suspension adjust input event table **212** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** in response to an actuation of driver actuatable suspension adjust input event table **212** of snowmobile **10**. In embodiments, driver actuatable suspension adjust input event table **212** specifies a percentage of available damping range for compression damping only, for rebound damping only, or for both compression damping and rebound damping for an actuation of driver actuatable suspension adjust input event table **212**. In embodiments, actuation of driver actuatable suspension adjust input event table **212** results in the compression damping for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** is set at an increased level. In one example, the compression damping for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** are set at 100 percent. The driver actuatable suspension adjust input **172** is actuatable by an operator to increase the compression damping to absorb rough terrain that the operator views as upcoming.

(97) In embodiments, a second actuation of driver actuatable suspension adjust input **172** within a given time period is interpreted by electronic controller **100** to reduce compression damping for right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** to absorb chatter bumps (small bumps on trail).

(98) In embodiments, a second actuation of driver actuatable suspension adjust input **172** within a given time period is interpreted by electronic controller **100** to hold compression damping for right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** until a third actuation of driver actuatable suspension adjust input **172** is received or a driver mode (comfort, handling, rough trail) is changed.

(99) In embodiments, a continued actuation of driver actuatable suspension adjust input **172**, such as holding a button down, for a given time period is interpreted by electronic controller **100** to hold compression damping for right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** until a subsequent actuation of driver actuatable suspension adjust input **172** is received or a driver mode (comfort, handling, rough trail) is changed.

(100) In embodiments, driver actuatable suspension adjust input **172** is not a separate input, but is recognized as a characteristic of another driver input. In one example, a quick partial actuation of a brake lever for a short duration of time that is detected by brake switch **134** is interpreted by controller **100** as an input from driver actuatable suspension adjust input **172** while a longer actuation and/or a more complete actuation of the brake lever is interpreted by controller **100** as an actuation of the brakes of snowmobile **10**.

(101) Brake event table **214** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based on an actuation of a brake input of snowmobile **10** as monitored by brake switch **134** on the brake lever or based on a pressure value from brake pressure sensor **135** (actual pressure reading or pressure switch).

(102) In embodiments, upon detection of braking while snowmobile **10** is traveling forward, the compression damping characteristics for right front adjustable shock absorber **140** and left front adjustable shock absorber **142** are increased to minimize forward pitch of snowmobile **10** and bottoming out of right front adjustable shock absorber **140** and left front adjustable shock absorber **142**. For front track adjustable shock absorber **144**, the compression damping characteristic is decreased to increase the ability of snowmobile **10** to absorb trail bumps and to collect snow in front of endless track **18** to assist slowing snowmobile **10**. For rear track adjustable shock absorber **146**, the compression damping either

remains at a current level or is decreased to keep more weight of snowmobile **10** on endless track **18**.

(103) In embodiments, upon detection of braking while snowmobile **10** is traveling forward, the rebound damping characteristics for right front adjustable shock absorber **140** and left front adjustable shock absorber **142** either remains the same or is decreased to keep right front adjustable shock absorber **140** and left front adjustable shock absorber **142** extended as much as possible and thereby keep the front of snowmobile **10** higher. For front track adjustable shock absorber **144**, the rebound damping characteristic is increased to collect snow in front of endless track **18** to assist slowing snowmobile **10** and keep track weight. For rear track adjustable shock absorber **146**, the rebound damping is increased to reduce pitch motion of snowmobile **10** and keep more weight transferred to the rear of snowmobile **10**.

(104) In embodiments, a separate brake event table **214** is not provided due to the braking response being accounted for in predictive vehicle pitch table **236** when looking at a predicted deceleration of snowmobile **10**.

(105) Anti-dive event table **216** includes damping characteristics for each of right front adjustable shock absorber **140** and left front adjustable shock absorber **142** based on a deceleration rate of the vehicle from the accelerometer input or the vehicle speed input. In embodiments, anti-dive event table **216** specifies a percentage of available damping range for compression damping only, for rebound damping only, or for both compression damping and rebound damping based on an actuation of a brake input of snowmobile **10** as monitored by brake switch **134** or based on a pressure value from brake pressure sensor **135**. In embodiments, the compression damping characteristics for right front adjustable shock absorber **140** and left front adjustable shock absorber **142** are increased to minimize forward pitch of snowmobile **10** and bottoming out of right front adjustable shock absorber **140** and left front adjustable shock absorber **142**. For front track adjustable shock absorber **144**, the compression damping characteristic is decreased to increase the ability of snowmobile **10** to absorb trail bumps and to collect snow in front of endless track **18** to assist slowing snowmobile **10**. For rear track adjustable shock absorber **146**, the compression damping either remains at a current level or is decreased to keep more weight of snowmobile **10** on endless track **18**.

(106) In embodiments, upon detection of braking while snowmobile **10** is traveling forward, the rebound damping characteristics for right front adjustable shock absorber **140** and left front adjustable shock absorber **142** either remains the same or is decreased to keep right front adjustable shock absorber **140** and left front adjustable shock absorber **142** extended as much as possible and thereby keep the front of snowmobile **10** higher. For front track adjustable shock absorber **144**, the rebound damping characteristic is increased to collect snow in front of endless track **18** to assist slowing snowmobile **10** and keep track weight. For rear track adjustable shock absorber **146**, the rebound damping is increased to reduce pitch motion of snowmobile **10** and keep more weight transferred to the rear of snowmobile **10**.

(107) In embodiments, the compression damping characteristics for right front adjustable shock absorber **140** and left front adjustable shock absorber **142** are increased over level for a braking event **214**. Based on a level of the brake pressure applied, shock damping logic **150** selects between brake event table **214** and anti-dive event table **216** with anti-dive event table **216** being for higher levels of brake pressure. In one example, anti-dive event table **216** is used for an initial timeframe and then brake event table **214** thereafter because the vehicle speed has slowed.

(108) In embodiments, a separate anti-dive event table **216** is not provided. In embodiments, the braking and anti-dive response are accounted for in the predictive vehicle pitch table **236** when looking at a predicted deceleration of snowmobile **10** and at a predicted pitch forward of snowmobile **10**. In embodiments, the braking and anti-dive response is accounted for based on the degree of actuation of the brake level or on the level or monitored brake pressure.

(109) One ski event table **218** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based on a steering angle of the steering system and one or more outputs of IMU **132**, such as a lateral acceleration, a roll axis angle, and a roll rate. In embodiments, one ski event table **218** specifies a percentage of available damping range for compression damping only, for rebound damping only, or for both compression damping and rebound damping based on a roll angle detected by IMU **132**.

(110) In embodiments, if snowmobile **10** is rolling towards the right side the compression damping for

left front adjustable shock absorber **142** is increased to counteract the roll and the rebound damping for right front adjustable shock absorber **140** is decreased to extend right front adjustable shock absorber **140** to increase contact with the snow. If snowmobile **10** is rolling towards the left side the compression damping for right front adjustable shock absorber **140** is increased to counteract the roll and the rebound damping for left front adjustable shock absorber **142** is decreased to extend left front adjustable shock absorber **142** to increase contact with the snow. In embodiments, if snowmobile **10** is rolling towards the right then increase compression damping for the right shock and decrease rebound damping for the right shock. In embodiments, if snowmobile **10** is rolling towards left then increase compression damping for left shock and decrease compression damping for left shock.

(111) G-out event table **224** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based on a pitch motion of snowmobile **10**. In embodiments, G-out event table **224** specifies a percentage of available damping range for compression damping only, for rebound damping only, or for both compression damping and rebound damping. In embodiments, the compression damping characteristic for right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, and rear track adjustable shock absorber **146** is increased.

(112) Chatter event table **226** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based on based on a pitch motion of snowmobile **10**. In embodiments, chatter event table **226** specifies a percentage of available damping range for compression damping only, for rebound damping only, or for both compression damping and rebound damping. In embodiments, both the compression and rebound damping are decreased for all shock absorbers. In embodiments, chatter events are distinguished from whoops events based on a frequency analysis of the IMU output.

(113) Cornering event table **228** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, and front track adjustable shock absorber **144** based longitudinal acceleration of snowmobile **10** and at least one of steering angle sensor **136** or acceleration along axis **162** (lateral acceleration) for cornering. In embodiments, cornering event table **228** specifies a percentage of available damping range for compression damping only, for rebound damping only, or for both compression damping and rebound damping.

(114) In embodiments, upon detection of cornering while snowmobile **10** is traveling forward, the compression damping characteristics for the front outside shock (fp**140** if turning to left or left front adjustable shock absorber **142** if turning to the right) is increased minimize roll of snowmobile **10** and for the front inside shock (fp**142** if turning to left or right front adjustable shock absorber **140** if turning to the right) is decreased to absorb trail bumps more smoothly. The level of increase and decrease is dependent on the longitudinal acceleration of snowmobile **10** (larger increases and decreases for higher speeds) to control pitch motion for snowmobile **10**. Regardless of the direction of the turn, the compression damping characteristic for front track adjustable shock absorber **144** is decreased to add ski traction for improved cornering and for rear track adjustable shock absorber **146** the compression damping characteristic is updated to control longitudinal pitch motion and weight transfer throughout the cornering event. For example, at corner entry, the compression damping characteristic of rear track adjustable shock absorber **146** may remain unchanged or be decreased based on longitudinal acceleration, but at mid corner or at corner exit when the throttle is applied the compression damping characteristic of rear track adjustable shock absorber **146** may be increased to prevent lifting of the skis and losing traction on the front of snowmobile **10**.

(115) In embodiments, upon detection of cornering while snowmobile **10** is traveling forward, the rebound damping characteristics for the front inside shock (fp**142** if turning to left or right front adjustable shock absorber **140** if turning to the right) is increased to reduce roll of snowmobile **10**. The level of increase and decrease is dependent on the longitudinal acceleration of snowmobile **10**. In one example, the level of increase and decrease is also dependent on a lateral acceleration of snowmobile **10**. Regardless of the direction of the turn, the rebound damping characteristic for front track adjustable shock absorber **144** is increased to add ski traction for improved cornering and for rear track adjustable shock absorber **146** the rebound damping characteristic remains unchanged or is increased to control

longitudinal pitch motion, hold the rear end down, and control vehicle body motion throughout the cornering event.

(116) Brake corner event table **220** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based on snowmobile **10** both cornering and braking. In embodiments, shock damping logic **150** follows whichever of brake event table **214** and corner event table **228** has a higher priority. In one example, the cornering event has a higher priority than the braking event.

(117) Chatter corner event table **222** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based on snowmobile **10** both cornering and airborne detection. In embodiments, airborne events override cornering events. Further, a steering angle could be used to modify the airborne damping value increasing the damping of the outside front and/or rear shock. In embodiments, a separate chatter corner event table **222** is not provided, but rather shock damping logic **150** follows whichever of airborne time event table **210** and corner event table **228** has a higher priority.

(118) Base damping table **230** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** in the absence of detecting one or more of airborne time event table **210**, driver actuatable suspension adjust input event table **212**, brake event table **214**, anti-dive event table **216**, one ski event table **218**, brake corner event table **220**, chatter corner event table **222**, g-out event table **224**, chatter event table **226**, corner event table **228**, launch mode event table **232**, anti-squat event table **234**, and predictive vehicle pitch table **236**. In embodiments, base damping table **230** specifies a percentage of available damping range for compression damping only, for rebound damping only, or for both compression damping and rebound damping for detected vehicle speeds and/or throttle positions. As mentioned herein, each of the selectable modes (comfort, handling, and rough trail) have their own base damping table.

(119) Launch mode event table **232** includes damping characteristics for each of front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** based on an actuation of the launch mode input **174** or based on one or more sensor readings (such as vehicle speed is zero and throttle actuation above a first level). In embodiments, launch mode event table **232** specifies a percentage of available damping range for compression damping only, for rebound damping only, or for both compression damping and rebound damping. In response to an actuation of the launch mode input, different actions are taken based on the selected mode (Comfort, Handling, Rough Trail) of snowmobile **10** for the expected high acceleration of snowmobile **10**. For the Comfort and Handling modes, it is desired to keep skis **16** on the snow. To achieve this outcome, the compression damping characteristics for front track adjustable shock absorber **144** is maintained or decreased, the rebound damping characteristic for front track adjustable shock absorber **144** is increased, the compression damping characteristic for rear track adjustable shock absorber **146** is increased, and the rebound damping characteristic for rear track adjustable shock absorber **146** is maintained or decreased. These changes both promotes keeping the skis **16** on the snow and minimizing a rearward pitch motion. For the Rough Trail mode, it may be desirable to raise skis **16** off of the snow. To achieve this outcome, the compression damping characteristics for front track adjustable shock absorber **144** is increased, the rebound damping characteristic for front track adjustable shock absorber **144** is decreased, the compression damping characteristic for rear track adjustable shock absorber **146** is maintained or decreased, and the rebound damping characteristic for rear track adjustable shock absorber **146** is maintained or increased. These changes both promotes lifting the skis **16** and promoting a rearward pitch motion. Further, when starting from a stop or low speed, the changes to front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** may be further modified to promote snowmobile **10** raising the skis further off the ground to perform a wheelie.

(120) Anti-squat event table **234** includes damping characteristics for each of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based longitudinal acceleration of snowmobile **10** measured by IMU **132**, a pitch rate, and/or a pitch angle measured by IMU **132**. In embodiments, anti-squat event table **234** specifies a percentage of available damping range for compression damping only, for rebound damping

only, or both compression damping and rebound damping for one or more time period ranges of detection. For a measured pitch angle, shock damping logic **150** increases the rebound damping characteristic of right front adjustable shock absorber **140** and left front adjustable shock absorber **142** and increases the compression damping characteristic for front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** for the duration of the predicted vehicle pitch motion.

(121) Having right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** being adjustable is helpful for orienting snowmobile **10** in various environmental situations. Referring to FIG. **22**, snowmobile **10** is shown in deep snow. When the shock absorbers **144** and **146** are not adjustable, the rear of snowmobile **10** sinks in the snow up to the running boards of snowmobile **10**. By sensing the rearward pitch of snowmobile **10** with IMU **132**, the rebound damping characteristic of front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** can be automatically increased to promote extension of front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** and the compression damping characteristic of front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** can be decreased. This results in the rear end of the rear suspension to drop and keeps snowmobile **10** more level in the snow.

(122) Referring to FIGS. **9A-C**, an exemplary processing sequence **300** of the shock damping logic **150** of the electronic controller **200** of FIG. **6** for left front adjustable shock absorber **142** provided as part of the suspension **24** of a left front ski **16** of the exemplary snowmobile **10** of FIG. **1**. Referring to FIG. **9A**, processing sequence **300** determines if an airborne event is detected, as represented by block **302**. An exemplary process **700** for detecting an airborne event is illustrated in FIG. **15**. If an airborne event is detected, the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in airborne time table **210** of shock damping logic **150**, as represented by block **304** and processing sequence **300** is completed, as represented by block **306**.

(123) If an airborne event is not detected, shock damping logic **150** determines if a driver actuatable suspension adjust input event is detected, as represented by block **310**. If a driver actuatable suspension adjust input event is detected, the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in driver actuatable suspension adjust input table **212** of shock damping logic **150**, as represented by block **312** and processing sequence **300** is completed, as represented by block **306**.

(124) If a driver actuatable suspension adjust input event is not detected, shock damping logic **150** determines if a braking event is detected, as represented by block **314**. An exemplary process **650** for detecting a braking event is illustrated in FIG. **14**. If a braking event is detected, shock damping logic **150** determines if an anti-dive time threshold has elapsed, as represented by block **316**. If the anti-dive threshold has not elapsed, the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in anti-dive table **216** of shock damping logic **150**, as represented by block **318** and processing sequence **300** is completed, as represented by block **306**.

(125) If the anti-dive threshold has elapsed, the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in brake event table **214** of shock damping logic **150** based on a value of vehicle deceleration from IMU **132**. Shock damping logic **150** next determines if a cornering event is detected, as represented by block **322**. If a cornering event is not detected processing sequence **300** is completed, as represented by block **306**. If a cornering event is detected, shock damping logic **150** determines if the vehicle acceleration is to the left side of snowmobile **10**, as represented by block **324**. If the vehicle acceleration is to the left, left front adjustable shock absorber **142** is designated the outside shock, as represented by block **326**, and the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in brake corner event table **220** for the outside shock, as represented by block **328**, and processing sequence **300** is completed, as represented by block **306**. If the vehicle acceleration is not to the left, left front adjustable shock absorber **142** is designated the inside shock, as represented by block **330**, and the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in brake corner event table for the inside shock, as represented by block **328**, and processing sequence **300** is completed, as represented by block **306**.

(126) If a braking event is not detected, shock damping logic **150** determines if a one ski event is

detected, as represented by block **340**. An exemplary process **1000** for detecting a one ski event is illustrated in FIG. **20**. If a one ski event is detected, shock damping logic **150** determines the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in one ski event table **218** of shock damping logic **150**, as represented by block **342** and processing sequence **300** is completed, as represented by block **306**.

(127) If a one ski event is not detected, shock damping logic **150** determines if a G-out event is detected, as represented by block **350**. An exemplary process **600** for detecting a G-out event is illustrated in FIG. **13**. If a G-out event is detected, shock damping logic **150** determines the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in G-out event table **224** of shock damping logic **150**, as represented by block **352** and processing sequence **300** is completed, as represented by block **306**.

(128) If a G-out event is not detected, shock damping logic **150** determines if a chatter event is detected, as represented by block **354**. An exemplary process **600** for detecting a chatter event is illustrated in FIG. **13**. If a chatter event is detected, shock damping logic **150** determines the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in chatter event table **226** of shock damping logic **150**, as represented by block **356**. Shock damping logic **150** then determines if a cornering event is detected, as represented by block **358**. If a cornering event is not detected, processing sequence **300** is completed, as represented by block **306**. If a cornering event is detected, shock damping logic **150** determines if the vehicle acceleration is to the left side of snowmobile **10**, as represented by block **364**. If the vehicle acceleration is to the left, left front adjustable shock absorber **142** is designated the outside shock, as represented by block **366**, and the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in chatter corner event table **222** for the outside shock, as represented by block **368**, and processing sequence **300** is completed, as represented by block **306**. If the vehicle acceleration is not to the left, left front adjustable shock absorber **142** is designated the inside shock, as represented by block **370**, and the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in chatter corner event table **222** for the inside shock, as represented by block **368**, and processing sequence **300** is completed, as represented by block **306**.

(129) If a chatter event is not detected, shock damping logic **150** determines if a cornering event is detected, as represented by block **376**. An exemplary process **800** for detecting a cornering event is illustrated in FIGS. **17A-D**. If a cornering event is detected, shock damping logic **150** determines if the vehicle acceleration is to the left side of snowmobile **10**, as represented by block **378**. If the vehicle acceleration is to the left, left front adjustable shock absorber **142** is designated the outside shock, as represented by block **380**, and the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in the corner event table **228** for the outside shock, as represented by block **382**, and processing sequence **300** is completed, as represented by block **306**. If the vehicle acceleration is not to the left, left front adjustable shock absorber **142** is designated the inside shock, as represented by block **384**, and the damping characteristics for left front adjustable shock absorber **142** is set based on the damping value provided in the corner event table **228** for the inside shock, as represented by block **382**, and processing sequence **300** is completed, as represented by block **306**. In embodiments, shock damping logic **150** also monitors vehicle acceleration/deceleration along axis **160** and this acceleration/deceleration value is a further input to corner event table. By taking into account the vehicle acceleration/deceleration along axis **160**, shock damping logic **150** is able to adjust the damping characteristics for left front adjustable shock absorber **142** differently for when snowmobile **10** is entering a corner (deceleration) and when snowmobile **10** is exiting a corner (acceleration).

(130) If a cornering event is not detected, shock damping logic **150** determines a damping characteristic for left front adjustable shock absorber **142** based on the damping value provided in the base damping table **230**, as represented by block **390** and processing sequence **300** is completed, as represented by block **306**.

(131) Referring to FIGS. **10A-C**, an exemplary processing sequence **400** of the shock damping logic **150** of the electronic controller **200** of FIG. **6** for right front continuous damping control shock absorber **142** provided as part of the suspension **24** of a left front ski **16** of the exemplary snowmobile **10** of FIG. **1**. Referring to FIG. **9A**, processing sequence **400** determines if an airborne event is detected, as represented

by block **402**. An exemplary process **700** for detecting an airborne event is illustrated in FIG. **15**. If an airborne event is detected, the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in airborne time table **210** of shock damping logic **150**, as represented by block **404** and processing sequence **400** is completed, as represented by block **406**.

(132) If an airborne event is not detected, shock damping logic **150** determines if a driver actuatable suspension adjust input event is detected, as represented by block **410**. If a driver actuatable suspension adjust input event is detected, the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in driver actuatable suspension adjust input table **212** of shock damping logic **150**, as represented by block **412** and processing sequence **400** is completed, as represented by block **406**.

(133) If a driver actuatable suspension adjust input event is not detected, shock damping logic **150** determines if a braking event is detected, as represented by block **414**. An exemplary process **650** for detecting a braking event is illustrated in FIG. **14**. If a braking event is detected, shock damping logic **150** determines if an anti-dive time threshold has elapsed, as represented by block **416**. If the anti-time threshold has not elapsed, the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in anti-dive table **216** of shock damping logic **150**, as represented by block **418** and processing sequence **400** is completed, as represented by block **406**.

(134) If the anti-dive time threshold has elapsed, the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in brake event table **214** of shock damping logic **150** based on a value of vehicle deceleration from IMU **132**. Shock damping logic **150** next determines if a cornering event is detected, as represented by block **422**. If a cornering event is not detected processing sequence **400** is completed, as represented by block **406**. If a cornering event is detected, shock damping logic **150** determines if the vehicle acceleration is to the right side of snowmobile **10**, as represented by block **424**. If the vehicle acceleration is to the right, right front adjustable shock absorber **140** is designated the outside shock, as represented by block **426**, and the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in brake corner event table **220** for the outside shock, as represented by block **428**, and processing sequence **400** is completed, as represented by block **406**. If the vehicle acceleration is not to the left, right front adjustable shock absorber **140** is designated the inside shock, as represented by block **430**, and the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in brake corner event table for the inside shock, as represented by block **428**, and processing sequence **400** is completed, as represented by block **406**.

(135) If a braking event is not detected, shock damping logic **150** determines if a one ski event is detected, as represented by block **440**. An exemplary process **1000** for detecting a one ski event is illustrated in FIG. **20**. If a one ski event is detected, shock damping logic **150** determines the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in one ski event table **218** of shock damping logic **150**, as represented by block **442** and processing sequence **400** is completed, as represented by block **406**.

(136) If a one ski event is not detected, shock damping logic **150** determines if a G-out event is detected, as represented by block **450**. An exemplary process **600** for detecting a G-out event is illustrated in FIG. **13**. If a G-out event is detected, shock damping logic **150** determines the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in G-out event table **224** of shock damping logic **150**, as represented by block **452** and processing sequence **400** is completed, as represented by block **406**.

(137) If a G-out event is not detected, shock damping logic **150** determines if a chatter event is detected, as represented by block **454**. An exemplary process **600** for detecting a chatter event is illustrated in FIG. **13**. If a chatter event is detected, shock damping logic **150** determines the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in chatter event table **226** of shock damping logic **150**, as represented by block **456**. shock damping logic **150** then determines if a cornering event is detected, as represented by block **458**. If a cornering event is not detected, processing sequence **400** is completed, as represented by block **406**. If a cornering event is detected, shock damping logic **150** determines if the vehicle acceleration is to the right side of snowmobile **10**, as represented by block **464**. If the vehicle acceleration is to the right, right front adjustable shock absorber

140 is designated the outside shock, as represented by block **466**, and the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in chatter corner event table **222** for the outside shock, as represented by block **468**, and processing sequence **400** is completed, as represented by block **406**. If the vehicle acceleration is not to the left, right front adjustable shock absorber **140** is designated the inside shock, as represented by block **470**, and the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in chatter corner event table **222** for the inside shock, as represented by block **468**, and processing sequence **400** is completed, as represented by block **406**.

(138) If a chatter event is not detected, shock damping logic **150** determines if a cornering event is detected, as represented by block **476**. An exemplary process **800** for detecting a cornering event is illustrated in FIGS. **17A-D**. If a cornering event is detected, shock damping logic **150** determines if the vehicle acceleration is to the right side of snowmobile **10**, as represented by block **478**. If the vehicle acceleration is to the right, right front adjustable shock absorber **140** is designated the outside shock, as represented by block **480**, and the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in the corner event table **228** for the outside shock, as represented by block **482**, and processing sequence **400** is completed, as represented by block **406**. If the vehicle acceleration is not to the left, right front adjustable shock absorber **140** is designated the inside shock, as represented by block **484**, and the damping characteristics for right front adjustable shock absorber **140** is set based on the damping value provided in the corner event table **228** for the inside shock, as represented by block **482**, and processing sequence **400** is completed, as represented by block **406**. In embodiments, shock damping logic **150** also monitors vehicle acceleration/deceleration along axis **160** and this acceleration/deceleration value is a further input to corner event table. By taking into account the vehicle acceleration/deceleration along axis **160**, shock damping logic **150** is able to adjust the damping characteristics for right front adjustable shock absorber **140** differently for when snowmobile **10** is entering a corner (deceleration) and when snowmobile **10** is exiting a corner (acceleration).

(139) If a cornering event is not detected, shock damping logic **150** determines a damping characteristic for right front adjustable shock absorber **140** based on the damping value provided in the base damping table **230**, as represented by block **490** and processing sequence **400** is completed, as represented by block **406**.

(140) Referring to FIGS. **11A** and **11B** an exemplary processing sequence **500** of the shock damping logic **150** of the electronic controller **200** of FIG. **6** for first track continuous damping control shock absorber **144** provided as part of the suspension **26** of the exemplary snowmobile **10** of FIG. **1**.

(141) Shock damping logic **150** determines if a launch mode has been enabled, as represented by block **502**. An exemplary processing sequence **950** for determining if a launch mode has been enabled is provided in FIGS. **19A** and **19B**. If a launch mode has been enabled, shock damping logic **150** determines a damping characteristic for first track continuous damping control shock absorber **144** based on the damping value provided in the launch mode event table **232**, as represented by block **504** and processing sequence **500** is completed, as represented by block **506**.

(142) If a launch mode is not detected, shock damping logic **150** determines if an airborne event is detected, as represented by block **510**. If an airborne event is detected, shock damping logic **150** determines a damping characteristic for first track continuous damping control shock absorber **144** based on the damping value provided in the airborne event table **210**, as represented by block **512** and processing sequence **500** is completed, as represented by block **506**.

(143) If an airborne event is not detected, shock damping logic **150** determines if a driver actuatable suspension adjust input event is detected, as represented by block **514**. If a driver actuatable suspension adjust input event is detected, shock damping logic **150** determines a damping characteristic for first track continuous damping control shock absorber **144** based on the damping value provided in the driver actuatable suspension adjust input event table **212**, as represented by block **516** and processing sequence **500** is completed, as represented by block **506**.

(144) If a driver actuatable suspension adjust input event is not detected, shock damping logic **150** determines if a brake event is detected, as represented by block **518**. If a brake event is detected, shock damping logic **150** determines a damping characteristic for first track continuous damping control shock absorber **144** based on the damping value provided in the brake event table **214**, as represented by block

520 and processing sequence **500** is completed, as represented by block **506**.

(145) If a brake event is not detected, shock damping logic **150** determines if a one ski event is detected, as represented by block **522**. If a one ski event is detected, shock damping logic **150** determines a damping characteristic for first track continuous damping control shock absorber **144** based on the damping value provided in the one ski event table **218**, as represented by block **524** and processing sequence **500** is completed, as represented by block **506**.

(146) If a one ski event is not detected, shock damping logic **150** determines if a g-out event is detected, as represented by block **526**. If a g-out event is detected, shock damping logic **150** determines a damping characteristic for first track continuous damping control shock absorber **144** based on the damping value provided in the g-out event table **224**, as represented by block **528** and processing sequence **500** is completed, as represented by block **506**.

(147) If a G-out event is not detected, shock damping logic **150** determines if a chatter event is detected, as represented by block **530**. If a chatter event is detected, shock damping logic **150** determines a damping characteristic for first track continuous damping control shock absorber **144** based on the damping value provided in the chatter event table **226**, as represented by block **532** and processing sequence **500** is completed, as represented by block **506**.

(148) If a chatter event is not detected, shock damping logic **150** determines if an anti-squat event is detected, as represented by block **534**. If an anti-squat event is detected, shock damping logic **150** determines a damping characteristic for first track continuous damping control shock absorber **144** based on the damping value provided in the anti-squat event table **234**, as represented by block **536** and processing sequence **500** is completed, as represented by block **506**.

(149) If an anti-squat event is not detected, shock damping logic **150** determines if a cornering event is detected, as represented by block **538**. If a cornering event is detected, shock damping logic **150** determines a damping characteristic for first track continuous damping control shock absorber **144** based on the damping value provided in the cornering event table **228**, as represented by block **540** and processing sequence **500** is completed, as represented by block **506**. In embodiments, shock damping logic **150** also monitors vehicle acceleration/deceleration along axis **160** and this acceleration/deceleration value is a further input to corner event table. By taking into account the vehicle acceleration/deceleration along axis **160**, shock damping logic **150** is able to adjust the damping characteristics for front track adjustable shock absorber **144** differently for when snowmobile **10** is entering a corner (deceleration) and when snowmobile **10** is exiting a corner (acceleration).

(150) If a cornering event is not detected, shock damping logic **150** determines a damping characteristic for first track continuous damping control shock absorber **144** based on the damping value provided in the base damping table **230**, as represented by block **542** and processing sequence **500** is completed, as represented by block **506**.

(151) Referring to FIGS. **12A** and **12B** an exemplary processing sequence **550** of the shock damping logic **150** of the electronic controller **200** of FIG. **6** for second track continuous damping control shock absorber **146** provided as part of the suspension **26** of the exemplary snowmobile **10** of FIG. **1**.

(152) Shock damping logic **150** determines if a launch mode has been enabled, as represented by block **552**. An exemplary processing sequence for determining if a launch mode has been enabled is provided in FIGS. **19A** and **19B**. If a launch mode has been enabled, shock damping logic **150** determines a damping characteristic for second track continuous damping control shock absorber **146** based on the damping value provided in the launch mode event table **232**, as represented by block **554** and processing sequence **550** is completed, as represented by block **556**.

(153) If a launch mode is not detected, shock damping logic **150** determines if an airborne event is detected, as represented by block **558**. If an airborne event is detected, shock damping logic **150** determines a damping characteristic for second track continuous damping control shock absorber **146** based on the damping value provided in the airborne event table **210**, as represented by block **560** and processing sequence **550** is completed, as represented by block **556**.

(154) If an airborne event is not detected, shock damping logic **150** determines if a driver actuatable suspension adjust input event is detected, as represented by block **562**. If a driver actuatable suspension adjust input event is detected, shock damping logic **150** determines a damping characteristic for second track continuous damping control shock absorber **146** based on the damping value provided in the driver

actuatable suspension adjust input event table **212**, as represented by block **564** and processing sequence **550** is completed, as represented by block **556**.

(155) If a driver actuatable suspension adjust input event is not detected, shock damping logic **150** determines if a brake event is detected, as represented by block **566**. If a brake event is detected, shock damping logic **150** determines a damping characteristic for second track continuous damping control shock absorber **146** based on the damping value provided in the brake event table **214**, as represented by block **568** and processing sequence **550** is completed, as represented by block **556**.

(156) If a brake event is not detected, shock damping logic **150** determines if a one ski event is detected, as represented by block **570**. If a one ski event is detected, shock damping logic **150** determines a damping characteristic for second track continuous damping control shock absorber **146** based on the damping value provided in the one ski event table **218**, as represented by block **572** and processing sequence **550** is completed, as represented by block **556**.

(157) If a one ski event is not detected, shock damping logic **150** determines if a g-out event is detected, as represented by block **574**. If a g-out event is detected, shock damping logic **150** determines a damping characteristic for second track continuous damping control shock absorber **146** based on the damping value provided in the g-out event table **224**, as represented by block **576** and processing sequence **550** is completed, as represented by block **556**.

(158) If a g-out event is not detected, shock damping logic **150** determines if a chatter event is detected, as represented by block **578**. If a chatter event is detected, shock damping logic **150** determines a damping characteristic for second track continuous damping control shock absorber **146** based on the damping value provided in the chatter event table **226**, as represented by block **580** and processing sequence **550** is completed, as represented by block **556**.

(159) If a chatter event is not detected, shock damping logic **150** determines if an anti-squat event is detected, as represented by block **582**. If an anti-squat event is detected, shock damping logic **150** determines a damping characteristic for second track continuous damping control shock absorber **146** based on the damping value provided in the anti-squat event table **234**, as represented by block **584** and processing sequence **550** is completed, as represented by block **556**.

(160) If an anti-squat event is not detected, shock damping logic **150** determines a damping characteristic for second track continuous damping control shock absorber **146** based on the damping value provided in the base damping table **230**, as represented by block **586** and processing sequence **550** is completed, as represented by block **556**.

(161) Referring to FIG. **13**, an exemplary processing sequence **600** of the shock damping logic **150** of the electronic controller **200** of FIG. **6** for detecting a g-out event or a chatter event is illustrated. suspension controller **200** samples from IMU **132** a pitch of snowmobile **10** about axis **162** over a window of time, as represented by block **602**. The sampled values are input to a discrete Fourier transform (“DFT”), as represented by block **604**, to provide a frequency map of the changes in pitch of snowmobile **10**.

(162) The magnitude of the low frequency values, such as from 0 Hz to 3 Hz, are compared a low frequency threshold, as represented by block **606**. If the magnitude of the low frequency values do not satisfy the low frequency threshold, then no event is detected and the low frequency portion of processing sequence **600** ends, as represented by blocks **614** and **612**. If the magnitude of the low frequency values satisfy the low frequency threshold, then processing sequence **600** compares a pitch up rate from a gyroscope input from the IMU **132** to another threshold, as represented by block **608**. If the pitch-up rate does not satisfy the threshold, then no event is detected and the low frequency portion of processing sequence **600** ends, as represented by blocks **614** and **612**. If the pitch-up rate satisfies the threshold, then a g-out event is detected, as represented by block **610**. The detection of a g-out event as explained herein results in the damping characteristics for one or more of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** being selected based on g-out event table **224**. In general, the damping characteristics are increased stiffness of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, and rear track adjustable shock absorber **146**.

(163) The magnitude of the high frequency values, such as from 3 Hz to 10 Hz, are compared a high frequency threshold, as represented by block **616**. If the magnitude of the high frequency values does not satisfy the high frequency threshold, then no event is detected and the high frequency portion of

processing sequence **600** ends, as represented by blocks **614** and **612**. If the magnitude of the high frequency values satisfies the high frequency threshold, then a chatter event is detected, as represented by block **618**. The detection of a chatter event as explained herein results in the damping characteristics for one or more of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** being selected based on chatter event table **226**.

(164) Referring to FIG. **14**, an exemplary processing sequence **650** of the shock damping logic **150** of the electronic controller **200** of FIG. **6** for detecting an exemplary brake event is illustrated. shock damping logic **150** determines if a brake switch is activated, as represented by block **652**. In embodiments, a switch is closed when a brake input is actuated. If the brake switch is not activated, no brake event is detected, as represented by block **654**, and processing sequence **650** is completed. If the brake switch is activated, a brake event is detected, as represented by block **656**, and processing sequence **650** is completed.

(165) FIG. **15** illustrates an exemplary processing sequence **700** of the shock damping logic **150** of the electronic controller **200** of FIG. **6** for detecting an exemplary airborne event. shock damping logic **150** if an acceleration of snowmobile **10** along axis **164** detected by IMU **132** is below a threshold value, as represented by block **702**. If the detected acceleration is below the threshold value, an airborne event is detected, as represented by block **704** and processing sequence **700** is completed. If the detected acceleration is greater than the threshold, then shock damping logic **150** checks to see if the current status of snowmobile **10** is that an airborne event is active for snowmobile **10** meaning that snowmobile **10** was recently determined to be in and is still in an airborne event, as represented by block **708**. If an airborne event is not active, no change is made meaning snowmobile **10** is not found to now be in an airborne event, as represented by block **710**, and processing sequence **700** is completed. If an airborne event is active, shock damping logic **150** determines if the detected vertical acceleration exceeds the threshold value plus a hysteresis value of IMU **132**, as represented by block **712**. If not, no change is made meaning snowmobile **10** remains in an airborne event, as represented by block **710**, and processing sequence **700** is completed, as represented by block **706**. If the detected vertical acceleration does exceed the threshold value plus the hysteresis value of IMU **132**, shock damping logic **150** determines if the elapsed time from the determination that snowmobile **10** is in an airborne event exceeds a timeout value, as represented by block **714**. If the elapsed time does not exceed the timeout value, no change is made meaning snowmobile **10** remains in an airborne event, as represented by block **710**, and processing sequence **700** is completed, as represented by block **706**. If the elapsed time does exceed the timeout value, the status of snowmobile **10** is changed to airborne event not detected, as represented by block **716**, and processing sequence **700** is completed, as represented by block **706**.

(166) FIGS. **16A-C** illustrates an exemplary processing sequence **750** of the shock damping logic **150** of the electronic controller **200** of FIG. **6** for detecting an exemplary anti-squat event. shock damping logic **150** determines if a rate of change of the throttle input detected by throttle position sensor **138** exceeds an enable limit, as represented by block **752**. If so, then shock damping logic **150** determines that a throttle rate of change event is detected, as represented by block **754**. If not, shock damping logic **150** determines if a rate of change of the throttle input is less than a disable limit, as represented by block **756**. If the rate of change of the throttle input is less than the disable limit, shock damping logic **150** determines that a throttle rate of change event is not detected, as represented by block **758**. If the rate of change of the throttle input is not less than the disable limit, shock damping logic **150** determines if the detected throttle position is less than a throttle limit meaning that the operator has backed off on the throttle, as represented by block **760**. If the detected throttle position is less than the throttle limit, shock damping logic **150** determines that a throttle rate of change event is not detected, as represented by block **758**. If the detected throttle position is greater than the throttle limit, shock damping logic **150** determines if the elapsed time since a throttle rate of change event was detected exceeds a hold time threshold, as represented by block **762**. If the elapsed time since the throttle rate of change event was detected does not exceed the hold time threshold, no change is made to whether a throttle rate of change event is active or not, as represented by block **764**. If the elapsed time since the throttle rate of change event was detected does exceed the hold time threshold, shock damping logic **150** determines that a throttle rate of change event is not detected, as represented by block **758**.

(167) Turning to FIG. **16B**, shock damping logic **150** next determines if a linear acceleration of

snowmobile **10** along axis **160** exceeds a threshold, as represented by block **766**. If the linear acceleration of snowmobile **10** along axis **160** exceeds the threshold, then an acceleration event is detected, as represented by block **768**. If the linear acceleration of snowmobile **10** along axis **160** does not exceed the threshold, shock damping logic **150** determines if the linear acceleration of snowmobile **10** is less than the threshold minus a hysteresis of IMU **132**, as represented by block **770**. If so, an acceleration event is not detected, as represented by block **772**. If not, no change is made to the current status of whether an acceleration event is active or not for snowmobile **10**, as represented by block **774**.

(168) Turning to FIG. **16C**, shock damping logic **150** determines if one of a throttle rate of change event or an acceleration event is active for snowmobile **10**, as represented by block **780**. If either is active, an anti-squat event is determined, as represented by block **782**, and processing sequence **750** is completed, as represented by block **790**. If not, then shock damping logic **150** checks to verify both the throttle rate of change event and the acceleration event are not active, as represented by block **784**. If both are inactive, shock damping logic **150** disables an anti-squat event, as represented by block **786**, and processing sequence **750** is completed, as represented by block **790**. If one of the throttle rate of change event and the acceleration event are active, no change is made to the anti-squat status of snowmobile **10**, as represented by block **788**, and processing sequence **750** is completed, as represented by block **790**.

(169) FIGS. **17A-D** illustrates an exemplary processing sequence **800** of the shock damping logic **150** of the electronic controller **200** of FIG. **6** for detecting an exemplary cornering event. shock damping logic **150** determines if an absolute value of a detected steering angle detected by steering angle sensor **136** exceeds a threshold (a zero steering angle corresponds with the skis pointing directly forward along axis **160**), as represented by block **802**. If the absolute value of the detected steering angle detected by steering angle sensor **136** exceeds the threshold, a steering event is detected, as represented by block **804**. If not, the absolute value of the detected steering angle detected by steering angle sensor **136** is compared to the threshold minus a hysteresis value of the steering angle sensor **136**, as represented by block **806**. If the absolute value of the detected steering angle detected by steering angle sensor **136** is less than the threshold minus the hysteresis value of the steering angle sensor **136**, shock damping logic **150** determines that a steering event is not detected, as represented by block **808**. If the absolute value of the detected steering angle detected by steering angle sensor **136** is not less than the threshold minus the hysteresis value of the steering angle sensor **136**, shock damping logic **150** makes no change to the steering event status of snowmobile **10**, as represented by block **810**.

(170) Turning to FIG. **17B**, shock damping logic **150** determines if a lateral acceleration of snowmobile **10** along axis **162** exceeds a threshold value, as represented by block **812**. If the lateral acceleration of snowmobile **10** along axis **162** exceeds the threshold value, then a corner event is detected, as represented by block **814**. If not, the absolute value of the detected lateral acceleration of snowmobile **10** is compared to the threshold minus a hysteresis value of IMU **132**, as represented by block **816**. If the absolute value of the detected lateral acceleration of snowmobile **10** is less than the threshold minus the hysteresis value of IMU **132**, shock damping logic **150** determines that a cornering event is not detected, as represented by block **818**. If the absolute value of the detected lateral acceleration of snowmobile **10** is not less than the threshold minus the hysteresis value of IMU **132**, shock damping logic **150** makes no change to the corner event status of snowmobile **10**, as represented by block **820**.

(171) Turning to FIG. **17C**, shock damping logic **150** determines if an absolute value of yaw rate and/or angle about axis **164** exceeds a threshold value, as represented by block **830**. If the absolute value of yaw rate and/or angle about axis **164** exceeds the threshold value, then a yaw event is detected, as represented by block **832**. If not, the absolute value of yaw rate and/or angle about axis **164** is compared to the threshold minus a hysteresis value of IMU **132**, as represented by block **834**. If the absolute value of the absolute value of yaw rate and/or angle about axis **164** is not less than the threshold minus the hysteresis value of IMU **132**, shock damping logic **150** makes no change to the yaw status of snowmobile **10**, as represented by block **836**. If the absolute value of absolute value of yaw rate and/or angle about axis **164** is less than the threshold minus the hysteresis value of IMU **132**, shock damping logic **150** determines if a cornering event timeout time has elapsed, as represented by block **838**. If the cornering timeout time has not elapsed, shock damping logic **150** makes no change to the yaw status of snowmobile **10**, as represented by block **836**. If the cornering timeout time has elapsed, then a yaw event is detected, as represented by block **840**.

(172) Turning to FIG. 17D, shock damping logic **150** determines if a yaw event or a steering event was detected in processing sequence **800**, as represented by block **850**. If one of the yaw event and steering event was detected then a cornering event is detected and the cornering timeout timer is set to zero, as represented by block **852**, and processing sequence **800** is completed, as represented by block **854**. If one of the yaw event and steering event was not detected then shock damping logic **150** determines if both the yaw event and steering event not detected, as represented by block **856**. If not, then there is no change to the cornering event status as represented by block **858**, and processing sequence **800** exits, as represented by block **854**. If so, then shock damping logic **150** determines a cornering event is not detected as represented by block **860**, and processing sequence **800** exits, as represented by block **854**.

(173) FIG. 18 illustrates an exemplary processing sequence **900** of the shock damping logic **150** of the electronic controller **200** of FIG. 6 for detecting an exemplary driver actuatable suspension adjust input event. shock damping logic **150** monitors whether driver actuatable suspension adjust input **172** has been actuated, as represented by block **902**. If driver actuatable suspension adjust input **172** has been actuated, a driver actuatable suspension adjust input event is detected, as represented by block **904** and processing sequence **900** is completed. If driver actuatable suspension adjust input **172** has not been actuated, shock damping logic **150** checks to see if a driver actuatable suspension adjust input timeout counter is active and, if so, has it elapsed, as represented by block **908**. If the driver actuatable suspension adjust input timeout has elapsed, shock damping logic **150** determines that a driver actuatable suspension adjust input event has not been detected, as represented by block **910** and processing sequence **900** is complete. If the driver actuatable suspension adjust input timeout has not elapsed, shock damping logic **150** keeps the current state of the driver actuatable suspension adjust input event status, as represented by block **912**, and processing sequence **900** is complete.

(174) FIGS. 19A and 19B illustrate an exemplary processing sequence **950** of the shock damping logic **150** of the electronic controller **200** of FIG. 6 for detecting an exemplary launch mode event. Referring to FIG. 19A, shock damping logic **150** monitors to determine if a launch mode input **174** has been actuated, as represented by block **952**. If launch mode input **174** has not been actuated then no change is made to the launch mode event status, as represented by block **954**. If launch mode input **174** has been actuated, shock damping logic **150** determines if a launch mode is currently active, as represented by block **956**. If a launch mode is currently active, then the actuation of launch mode input **174** causes the launch mode to be disabled, as represented by block **958**. If a launch mode is not currently enabled, shock damping logic **150** based on vehicle speed sensor **139** determines if the speed of snowmobile **10** is zero, as represented by block **960**. If the vehicle speed is not zero, no change is made to the launch mode status, as represented by block **954**. If the vehicle speed is zero, shock damping logic **150** determines if the launch button **174** has been actuated for timeout, as represented by block **962**. If not, no change is made to the launch mode status, as represented by block **954**. If so, shock damping logic **150** enables the launch mode, as represented by block **964**.

(175) Referring to FIG. 19B, shock damping logic **150** determines if the launch mode is enabled, as represented by block **966**. If not, no change is made to the launch mode status, as represented by block **968**. If the launch mode is enabled, shock damping logic **150** determines based on vehicle speed sensor **139** if the vehicle speed is above a threshold, as represented by block **970**. If not, no change is made to the launch mode status, as represented by block **968**. If the vehicle speed is above the threshold then shock damping logic **150** determines if the linear acceleration of snowmobile **10** along axis **160** is less than a threshold, as represented by block **972**. If not, no change is made to the launch mode status, as represented by block **968**. If the linear acceleration of snowmobile **10** along axis **160** is less than the threshold, shock damping logic **150** disables the launch mode because snowmobile **10** is traveling closer to a constant speed than quickly accelerating, as represented by block **974**.

(176) FIG. 20 illustrates an exemplary processing sequence **1000** of the shock damping logic **150** of the electronic controller **200** of FIG. 6 for detecting an exemplary one ski event. shock damping logic **150** based on IMU **132** monitors if a roll rate and/or angle of snowmobile **10** about axis **160** is greater than a low threshold, as represented by block **1002**. If so, shock damping logic **150** then checks to see if the monitored roll rate and/or angle is less than a high roll rate and/or angle threshold, as represented by block **1004**. If the vehicle roll rate and/or angle is in the range between the low threshold and the high threshold, a one ski event is detected, as represented by block **1006**, and processing sequence **1000** is

completed, as represented by block **1008**. Returning back to block **1002**, if the vehicle roll rate and/or angle is not greater than the low threshold, shock damping logic **150** determines if the vehicle roll rate and/or angle is less than the low threshold minus the hysteresis of the IMU **132**, as represented by block **1010**. If not, no change is made by shock damping logic **150** to the one ski event status, as represented by block **1014**. If so, shock damping logic **150** determines that a one ski event is not detected, as represented by block **1012** and processing sequence **1000** is completed, as represented by block **1008**. Returning to block **1004**, if the vehicle roll rate and/or angle is not less than the high threshold, shock damping logic **150** determines that a one ski event is not detected, as represented by block **1012** and processing sequence **1000** is completed, as represented by block **1008**.

(177) In embodiments, power is provided to front track adjustable shock absorber **144** and/or rear track adjustable shock absorber **146** through a wired connection routed through the suspension components or entering an interior of the track from a lateral side. In embodiments, communication signals are provided to and/or sent by front track adjustable shock absorber **144** and/or rear track adjustable shock absorber **146** through a wired connection routed through the suspension components or entering an interior of the track from a lateral side. In embodiments, both communication signals and power are provided to/from front track adjustable shock absorber **144** and/or rear track adjustable shock absorber **146** through a wired connection routed through the suspension components or entering an interior of the track from a lateral side. In embodiments, at least one of front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** include a power source and/or receive/transmit communication signals to controller **100** wirelessly.

(178) In embodiments, snowmobile **10** includes a demo mode to illustrate the functionality of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**. In one embodiment, snowmobile **10** includes a battery and an operator input is provided to activate accessory power on snowmobile **10**. In this example, an operator is able to select different operating modes (comfort, handling, rough trail) and/or input adjustments to right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146**. In one example, an operator can select a left turn option and experience the change in the damping characteristics for right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** for a left turn. In another embodiment, snowmobile **10** does not include a battery. In this example, a power connection is provided on snowmobile **10** which allows for an external power source to be plugged into snowmobile **10** to power snowmobile **10** to operate in the demo mode.

(179) In embodiments, during operation of vehicle **10** or **10'**, the damping characteristics of at least one of front track adjustable shock absorber **144** and rear track adjustable shock absorber **146** may be further adjusted to alter handling. In examples, the base damping profile for a given mode (such as comfort or sport), predicted acceleration damping profile (longitudinal or lateral), braking damping profile, and cornering damping profile include adjustments to damping characteristics of at least one of front track adjustable shock absorber **144** and rear track adjustable shock absorber **146**.

(180) During normal straight line driving (no appreciable cornering or change in acceleration), the base damping characteristics of front track adjustable shock absorber **144** may be different from rear track adjustable shock absorber **146** or the same as rear track adjustable shock absorber **146**. Changes in driving, such as cornering or changes in acceleration may result in adjustments to the base damping profile.

(181) For example, in the comfort mode, during normal straight line driving, front track adjustable shock absorber **144** has a first setup relative to rear track adjustable shock absorber **146** in compression damping (stiffer or the same). This setup biases snowmobile **10** balance to have less ski pressure on the ground for skis **16** and generally less positive tracking of skis **16**. The compression damping of front track adjustable shock absorber **144** is still soft enough to not sacrifice ride comfort. When snowmobile **10** brakes, decelerates or corners or is predicted to do so; the compression damping of front track adjustable shock absorber **144** is increased relative to its previous state. This adjustment prevents weight transfer to skis **16** and makes the turning effort of snowmobile **10** less with sacrificed traction on skis **16**.

(182) In another example, in sport mode, during normal driving, front track adjustable shock absorber **144**

has a first setup relative to rear track adjustable shock absorber **146** in compression damping (softer or the same). This setup biases snowmobile **10** balance to have more ski pressure on the ground for skis **16** and generally more positive tracking of skis **16**. When snowmobile **10** brakes, decelerates or corners or is predicted to do so; the compression damping of front track adjustable shock absorber **144** is decreased relative to its previous state. This adjustment adds weight transfer to skis **16** and creates increased traction on skis **16** at the sacrifice of increased steering effort.

(183) In embodiments, electronic controller **100** monitors the outputs of IMU **132** (a three-axis accelerometer and a three-axis gyroscope) to evaluate terrain and/or driver aggressiveness. Driver aggressiveness may be monitored by the longitudinal acceleration and lateral acceleration experienced by vehicle **10**. Further, throttle position, brake pressure, and steering angle, and steering velocity may provide indicators. Electronic controller **100** may monitor these factors and adjust the damping characteristics of one or more of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** based thereon. Terrain type may be monitored by longitudinal acceleration, lateral acceleration, vertical acceleration, and all three angular rates of IMU **132**. In embodiments, the outputs are analyzed to determine the frequency response of each. The frequency responses may be determined through one or more bandpass filters, fast Fourier transform, or other methods. For example, the roll angular frequency response may be monitored with a bandpass filter for frequencies in a first range, such as 8-15 Hertz, to provide an indication of chatter. The monitored frequency response for one or more of the outputs are compared to stored ranges for different terrain types and the damping characteristics of one or more of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** are adjusted based thereon.

(184) In embodiments, electronic controller **100** also monitors GPS sensor **131**. A given location might indicate a first terrain type based on the frequency responses of the IMU **132** on a first day, such as fresh snow, and a second terrain type based on the frequency responses of the IMU **132** on a second day, such as hard snow. Based on those different terrain types and the historical data of the location, electronic controller may adjust the damping characteristics of one or more of right front adjustable shock absorber **140**, left front adjustable shock absorber **142**, front track adjustable shock absorber **144**, and rear track adjustable shock absorber **146** to make the hard snow of the second day feel more like the fresh snow of the first day. This provides the ability for snowmobile **10** to have the same feel for the same location on different days even if the terrain characteristics have changed.

(185) In embodiments, sensors **130** includes a sensor which monitors if rear suspension assembly **26** is in a coupled state or uncoupled state. An exemplary sensor is a position sensor, an angular sensor, a pressure sensor, or a contact sensor which monitors when the suspension arm contacts a coupling block of rear suspension assembly **26**. In embodiments, the damping characteristics (compression and/or rebound) of front track adjustable shock absorber **144** and/or rear track adjustable shock absorber **146** are adjusted based on whether rear suspension assembly **26** is in a coupled state or uncoupled state.

(186) While embodiments of the present disclosure have been described as having exemplary designs, the present invention may be further modified within the spirit and scope of this disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the disclosure using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this invention pertains.

Claims

1. A snowmobile for propelled movement relative to the ground, comprising a plurality of ground engaging members including an endless track positioned along a centerline vertical longitudinal plane of the snowmobile having a lateral width, a left front ski positioned on a left side of the centerline vertical longitudinal plane of the snowmobile, and a right front ski positioned on a right side of the centerline vertical longitudinal plane of the snowmobile; a frame supported by the plurality of ground engaging members; a steering system supported by the frame and operatively coupled to the left front ski and the right front ski to control a direction of travel of the snowmobile; a left ski suspension operatively coupling the left front ski to the frame; a right ski suspension operatively coupling the right front ski to the frame; a

track suspension operatively coupling the endless track to the frame, the track suspension including a first adjustable shock absorber, the first adjustable shock absorber having at least one adjustable damping characteristic, the first adjustable shock absorber being laterally positioned within the lateral width of the endless track; a plurality of sensors supported by the ground engaging members; and at least one electronic controller operatively coupled to the first adjustable shock absorber, the at least one electronic controller based on a sensor measurement from a sensor spaced apart from each of the left ski suspension, right ski suspension, and track suspension operable to determine an airborne condition, and in response to the airborne condition the electronic controller alters at least one damping characteristic of the first adjustable shock absorber, wherein the at least one damping characteristic includes a rebound damping characteristic and the controller is operable to alter the rebound damping characteristic based upon a length of time that the snowmobile has been airborne.

2. The snowmobile of claim 1, the first adjustable shock absorber of the first suspension is positioned within an interior bounded by the endless track.

3. The snowmobile of claim 1, the track suspension further comprises a second adjustable shock absorber having at least one adjustable damping characteristic, the second adjustable shock absorber being laterally positioned within the lateral width of the endless track, the first adjustable shock absorber is a front track adjustable shock absorber and the second adjustable shock absorber is a rear track adjustable shock absorber.

4. The snowmobile of claim 3, the second adjustable shock absorber of the track suspension is positioned within the interior bounded by the endless track.

5. The snowmobile of claim 3, the second adjustable shock absorber of the track suspension is positioned outside of the interior bounded by the endless track.

6. The snowmobile of claim 1, wherein the at least one electronic controller alters the at least one damping characteristic of the first adjustable shock absorber while the snowmobile is moving relative to the ground.

7. The snowmobile of claim 6, wherein the at least one electronic controller alters a compression damping characteristic of the first adjustable shock absorber.

8. The snowmobile of claim 1, further comprising a third adjustable shock absorber and a fourth adjustable shock absorber, the third adjustable shock absorber is part of the left ski suspension operatively coupling the left front ski to the frame and the fourth adjustable shock absorber is part of the right ski suspension operatively coupling the right front ski to the frame.

9. The snowmobile of claim 1, wherein a first damping characteristic of the first adjustable shock absorber is adjusted by the at least one electronic controller based on a longitudinal acceleration of the snowmobile.

10. The snowmobile of claim 1, wherein a first damping characteristic of the first adjustable shock absorber is adjusted by the at least one electronic controller based on a vehicle pitch motion of the snowmobile.

11. The snowmobile of claim 1, wherein the at least one electronic controller adjusts a compression damping characteristic of the first adjustable shock absorber in response to the snowmobile being airborne.

12. The snowmobile of claim 11, wherein the adjustment of the compression damping characteristic of the first adjustable shock absorber is dependent on the length of time that the snowmobile has been airborne.

13. A method of controlling ride characteristics of a snowmobile, the method comprising the steps of: monitoring with at least one electronic controller a plurality of sensors supported by the snowmobile while the snowmobile is moving; predictively determining a longitudinal acceleration of the snowmobile based on a current sensor value of at least one sensor of the plurality of sensors; and adjusting with the at least one electronic controller at least one damping characteristic of an adjustable shock absorber while the vehicle is moving, based on the predicted longitudinal acceleration of the vehicle, the adjustable shock absorber being apart of a suspension of an endless track of the snowmobile.

14. The method of claim 13, wherein the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic based on a longitudinal acceleration of the snowmobile.

15. The method of claim 14, wherein the longitudinal acceleration of the snowmobile is measured by at least one sensor.

16. The method of claim 15, further comprising the steps of: determining the longitudinal acceleration of the snowmobile indicates an acceleration of the snowmobile; and changing a rebound damping characteristic of the adjustable shock absorber.

17. The method of claim 15, further comprising the steps of: determining the longitudinal acceleration of the snowmobile indicates an acceleration of the snowmobile; and changing a compression damping characteristic of the adjustable shock absorber.

18. The method of claim 13, wherein the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic based on a predicted pitch motion of the snowmobile.

19. The method of claim 18, wherein the predicted pitch motion of the snowmobile is based on the predicted vehicle longitudinal acceleration.

20. The method of claim 18, wherein step of adjusting the at least one damping characteristic based on the predicted pitch motion of the snowmobile includes determining the predicted vehicle longitudinal acceleration and determining a direction of travel of the snowmobile.

21. The method of claim 13, wherein the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic based on a turning of the snowmobile.

22. The method of claim 13, wherein the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic based on a braking of the snowmobile.

23. The method of claim 13, wherein the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic based on the snowmobile being airborne.

24. The method of claim 13, wherein the step of adjusting with the at least one electronic controller the at least one damping characteristic of the adjustable shock absorber which is apart of the suspension of the endless track of the snowmobile while the vehicle is moving, includes the step of adjusting the at least one damping characteristic to promote a lifting of the skis of the snowmobile.

25. The method of claim 24, wherein the step of adjusting the at least one damping characteristic to promote the lifting of the skis of the snowmobile includes the steps of decreasing a compression damping characteristic of the adjustable shock absorber.

26. The method of claim 25, wherein the step of adjusting the at least one damping characteristic to promote the lifting of the skis of the snowmobile includes the steps of increasing a rebound damping characteristic of a second adjustable shock absorber associated with the suspension of the endless track.

27. A method of controlling a damping characteristic of at least one adjustable shock absorber of a vehicle being operated by a driver, the method comprising: receiving with an electronic controller a plurality of inputs from a plurality of sensors supported by the vehicle; predictively determining a longitudinal acceleration of the vehicle based on a current sensor value of at least one sensor of the plurality of sensors; and adjusting the damping characteristic of the at least one adjustable shock absorber of the vehicle based on the predicted longitudinal acceleration of the vehicle.

28. The method of claim 27, wherein the step of adjusting the damping characteristic of the at least one adjustable shock absorber of the vehicle based on the predicted longitudinal acceleration of the vehicle, includes the step of adjusting the at least one damping characteristic based on a predicted pitch motion of the snowmobile.

29. The method of claim 28, wherein the at least one adjustable shock absorber includes a left adjustable shock absorber and a right adjustable shock absorber, and in response to a predicted increase in vehicle pitch motion, altering a damping characteristic of the left adjustable shock absorber and a damping characteristic of the right adjustable shock absorber.

30. The method of claim 29, wherein the at least one adjustable shock absorber includes a rear adjustable shock absorber, and in response to a predicted increase in vehicle pitch motion, altering the damping characteristic of the rear adjustable shock absorber.

31. The method of claim 30, wherein each of the left adjustable shock absorber, right adjustable shock absorber, and rear adjustable shock absorber have a first damping characteristic and a second damping characteristic, the second damping characteristic being different than the first damping characteristic, and in response to a predicted increase in vehicle pitch motion, increasing the first damping characteristic of the left adjustable shock absorber and the right adjustable shock absorber and increasing the second damping characteristic of the rear adjustable shock absorber.

32. The method of claim 27, further comprising the steps of: predictively determining a longitudinal pitch motion of the vehicle; and adjusting the damping characteristic of the at least one adjustable shock absorber of the vehicle based on the predicted longitudinal pitch motion of the vehicle.

33. The method of claim 32, wherein the predicted longitudinal acceleration is determined by the steps of: determining a predicted power for a prime mover of the snowmobile; determining an output power of the drivetrain based on the determined predicted power, the drivetrain including a CVT; determining a forward moving force of the snowmobile based on the determined output power of the drivetrain; determining a resultant forward moving force by subtracting at least one of a coast down force and an applied braking force from the determined forward moving force; and dividing the resultant forward moving force by a mass of the snowmobile to determine the predicted vehicle longitudinal acceleration.
