

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398029
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Zahdeh; Akram et al.

Autonomous transport vehicle

Abstract

An autonomous transport vehicle includes a frame forming a transport payload area of the vehicle. The payload area includes a payload contact support surface that defines a payload support plane that supports the payload. The payload area further includes an articulated underpick end effector that engages and underpicks the payload with respect to the support plane, and extends and retracts with respect to the payload area effecting payload transfer. Payload registration facets are mounted to the frame to engage the payload. The registration facets are disposed to provide, upon engagement with the payload, at least two degrees of registration capturing and securing the payload in a predetermined position in the payload area, and are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with seating of the payload on the payload support plane of the payload area.

Inventors:	Zahdeh; Akram (Wilmington, MA), Kepple; Todd (Wilmington, MA)
Applicant:	Symbotic LLC (Wilmington, MA)
Family ID:	1000008779409
Assignee:	Symbotic LLC (Wilmington, MA)
Appl. No.:	17/664944
Filed:	May 25, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230069056 A1	Mar. 02, 2023

Related U.S. Application Data

us-provisional-application US 63236591 20210824

Publication Classification

Int. Cl.: B66F9/06 (20060101); B66F9/18 (20060101)

U.S. Cl.:

CPC B66F9/063 (20130101); B66F9/18 (20130101);

Field of Classification Search

CPC: B66F (9/063); B66F (9/18); B66F (9/10); B66F (9/143); B65G (1/0492)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2009/0074545	12/2008	Lert, Jr.	414/267	B65G 1/1378
2010/0316468	12/2009	Lert et al.	N/A	N/A
2014/0277692	12/2013	Buzan	700/218	B65G 1/0492
2019/0202635	12/2018	Conrad et al.	N/A	N/A
2019/0283239	12/2018	Skaaksrud et al.	N/A	N/A
2019/0359436	12/2018	Cyrulik et al.	N/A	N/A

Primary Examiner: Mehdizadeh; Navid Z.

Assistant Examiner: McCleary; Caitlin R

Attorney, Agent or Firm: Perman & Green, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a non-provisional of and claims the benefit of U.S. provisional patent application No. 63/236,591 filed on Aug. 24, 2021, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

1. Field

(1) The disclosed embodiment generally relates to material handling systems, and more particularly, to transports for automated storage and retrieval systems.

2. Brief Description of Related Developments

(2) Generally autonomous transport vehicles in logistics/warehouse facilities are manufactured to have a predetermined form factor for an assigned task in a given environment. These autonomous transport vehicles are constructed of a bespoke cast or machined chassis/frame. The other components (e.g., wheels, transfer arms, etc.), some of which may also be bespoke assemblies/components, are mounted to the frame and are carried with the frame as the autonomous transport vehicle traverses along a traverse surface. The transfer arms and payload bay of these autonomous transport vehicles may include numerous components and motor assemblies for transferring payloads to and from the autonomous transport vehicles as well as for justifying

payloads within the payload bay. The components and numerous motors of the transfer arms and payload bay may be complex and expensive to manufacture, increasing the cost and maintenance requirements of the autonomous transport vehicles.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The foregoing aspects and other features of the disclosed embodiment are explained in the following description, taken in connection with the accompanying drawings, wherein:
- (2) FIG. 1 is a block diagram of an exemplary automated storage and retrieval system incorporating aspects of the disclosed embodiment;
- (3) FIGS. 2A, 2B, and 2C are schematic perspective illustrations of an autonomous guided vehicle of the automated storage and retrieval system of FIG. 1 incorporating aspects of the disclosed embodiment;
- (4) FIG. 2D is a schematic plan illustration of a portion of the autonomous guided vehicle of FIGS. 2A-2C incorporating aspects of the disclosed embodiment;
- (5) FIG. 2E is an exemplary schematic side illustration of a portion of the autonomous guided vehicle of FIGS. 2A-2D incorporating aspects of the disclosed embodiment;
- (6) FIG. 2F is an exemplary perspective illustration of a portion of the autonomous guided vehicle of FIGS. 2A-2D incorporating aspects of the disclosed embodiment;
- (7) FIG. 3A is a schematic perspective illustration of a portion of the autonomous guided vehicle of FIGS. 2A-2D in accordance with aspects of the disclosed embodiment;
- (8) FIG. 3B is a plan view of a portion of the autonomous guided vehicle shown in FIG. 3A in accordance with aspects of the disclosed embodiment;
- (9) FIG. 4A is a schematic perspective illustration of a portion of the autonomous guided vehicle of FIGS. 2A-2D in accordance with aspects of the disclosed embodiment;
- (10) FIG. 4B is a plan view of a portion of the autonomous guided vehicle shown in FIG. 4A in accordance with aspects of the disclosed embodiment;
- (11) FIG. 4C is a plan view of a portion of the autonomous guided vehicle shown in FIG. 4A in accordance with aspects of the disclosed embodiment;
- (12) FIG. 5A is a schematic perspective illustration of a portion of the autonomous guided vehicle of FIGS. 2A-2D in accordance with aspects of the disclosed embodiment;
- (13) FIG. 5B is a plan view of a portion of the autonomous guided vehicle shown in FIG. 5A in accordance with aspects of the disclosed embodiment;
- (14) FIG. 5C is a plan view of a portion of the autonomous guided vehicle shown in FIG. 5A in accordance with aspects of the disclosed embodiment;
- (15) FIG. 6A is a schematic perspective illustration of a portion of the autonomous guided vehicle of FIGS. 2A-2D in accordance with aspects of the disclosed embodiment;
- (16) FIG. 6B is a plan view of a portion of the autonomous guided vehicle shown in FIG. 6A in accordance with aspects of the disclosed embodiment;
- (17) FIG. 6C is a plan view of a portion of the autonomous guided vehicle shown in FIGS. 6A and 6B in accordance with aspects of the disclosed embodiment;
- (18) FIG. 6D is a plan view of a portion of the autonomous guided vehicle shown in FIG. 6C in accordance with aspects of the disclosed embodiment;
- (19) FIG. 6E is a plan view of a portion of the autonomous guided vehicle shown in FIG. 6A in accordance with aspects of the disclosed embodiment;
- (20) FIG. 6F is a plan view of a portion of the autonomous guided vehicle shown in FIGS. 6A and 6E in accordance with aspects of the disclosed embodiment;
- (21) FIG. 6G is a plan view of a portion of the autonomous guided vehicle shown in FIG. 6F in

accordance with aspects of the disclosed embodiment;

(22) FIGS. 7A and 7B are schematic perspective illustrations of a portion of case handling assembly of the autonomous guided vehicle of FIGS. 2A-2D in accordance with aspects of the disclosed embodiment;

(23) FIGS. 8A, 8B, and 8C are schematic perspective illustrations of a transfer arm of the case handling assembly of FIGS. 7A and 7B in accordance with aspects of the disclosed embodiment;

(24) FIGS. 9A, 9B, and 9C are schematic perspective illustrations of a transfer arm of the case handling assembly of FIGS. 7A and 7B in accordance with aspects of the disclosed embodiment;

(25) FIGS. 10A, 10B, 10C, and 10D are schematic perspective illustrations of a transfer arm of the case handling assembly of FIGS. 7A and 7B in accordance with aspects of the disclosed embodiment;

(26) FIGS. 11A, 11B, and 11C are schematic perspective illustrations of portions of the case handling assembly of FIGS. 7A and 7B in accordance with aspects of the disclosed embodiment;

(27) FIGS. 12A, 12B, 12C, and 12D are schematic perspective illustrations of portions of the case handling assembly of FIGS. 7A and 7B in accordance with aspects of the disclosed embodiment;

(28) FIGS. 12E, 12F, 12G, and 12H are schematic perspective illustrations of portions of the case handling assembly of FIGS. 7A and 7B in accordance with aspects of the disclosed embodiment;

(29) FIGS. 13A, 13B, 13C, 13D, 13E, and 13F are schematic perspective illustrations of portions of the case handling assembly of FIGS. 7A and 7B in accordance with aspects of the disclosed embodiment;

(30) FIGS. 14A, 14B, 14C, 14D, 14E, 14F are schematic perspective illustrations of portions of the autonomous guided vehicle of FIGS. 2A-2D showing an exemplary case unit pick and justification sequence in accordance with aspects of the disclosed embodiment;

(31) FIG. 15 is an exemplary flow diagram for an exemplary method(s) in accordance with aspects of the disclosed embodiment;

(32) FIG. 16 is an exemplary schematic illustration of a portion of the storage and retrieval system of FIG. 1 in accordance with aspects of the disclosed embodiment;

(33) FIGS. 17A and 17B are schematic sectional illustrations of the autonomous transport vehicle of FIGS. 2A-2D with the payload bed in a lowered position in accordance with aspects of the disclosed embodiment;

(34) FIGS. 17C and 17D are schematic sectional illustrations of the autonomous transport vehicle of FIGS. 2A-2D with the payload bed in a raised position in accordance with aspects of the disclosed embodiment;

(35) FIG. 18 is an exemplary flow diagram for an exemplary method in accordance with aspects of the disclosed embodiment; and

(36) FIG. 19 is an exemplary flow diagram for an exemplary method in accordance with aspects of the disclosed embodiment.

DETAILED DESCRIPTION

(37) FIG. 1 illustrates an exemplary automated storage and retrieval system **100** in accordance with aspects of the disclosed embodiment. Although the aspects of the disclosed embodiment will be described with reference to the drawings, it should be understood that the aspects of the disclosed embodiment can be embodied in many forms. In addition, any suitable size, shape or type of elements or materials could be used.

(38) As described in greater detail herein, the aspects of the disclosed embodiment provide autonomous transport vehicles **110** of the automated storage and retrieval system **100** with a multiple degree of freedom payload/case handling assembly. The payload handling assembly secures the payload in six degrees of freedom while held by the autonomous transport vehicle **110** while providing a simplified case handling structure compared to conventional warehouse autonomous transport vehicles. The payload handling assembly reduces part count and costs of the autonomous transport vehicles **110** by employing universal/common interchangeable structures

(see, e.g., lift towers **211**, **122** described herein) that may be employed in one or more locations of the autonomous transport vehicles **110**. The payload handling assembly reduces part count and costs of the autonomous transport vehicles **110** by minimizing the number of actuators/motors that effect payload gripping and manipulation. As also described herein, the payload handling assembly is configured to adapt to and stably hold payloads of differing sizes by varying a distance between at least two adjacent payload supports of an underpick end effector or arm **210A** of the payload handling assembly reduces part count and costs of the autonomous transport vehicles **110**.

(39) The aspects of the disclosed embodiment also provide the autonomous transport vehicle **110** with registration facets disposed to provide, upon engagement with a payload, registration of the payload within a payload area or bay of the autonomous transport vehicle **110** with at least two degrees of registration capturing and securing the payload in a predetermined position in the payload area. As described herein, registration facets of the autonomous transport vehicle **110** are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with seating of the payload on the payload support plane of the payload area so as to pick (and place) and securely register a payload within the payload area in about 10 seconds or less.

(40) The automated storage and retrieval system **100** in FIG. 1, may be disposed in a retail distribution center or warehouse, for example, to fulfill orders received from retail stores for replenishment goods shipped in cases, packages, and or parcels. The terms case, package and parcel are used interchangeably herein and as noted before may be any container that may be used for shipping and may be filled with case or more product units by the producer. Case or cases as used herein means case, package or parcel units not stored in trays, on totes, etc. (e.g. uncontained). It is noted that the case units CU (also referred to herein as mixed cases, cases, and shipping units) may include cases of items/unit (e.g. case of soup cans, boxes of cereal, etc.) or individual item/units that are adapted to be taken off of or placed on a pallet. In accordance with the exemplary embodiments, shipping cases or case units (e.g. cartons, barrels, boxes, crates, jugs, shrink wrapped trays or groups or any other suitable device for holding case units) may have variable sizes and may be used to hold case units in shipping and may be configured so they are capable of being palletized for shipping. Case units may also include totes, boxes, and/or containers of one or more individual goods, unpacked/decommissioned (generally referred to as backpack goods) from original packaging and placed into the tote, boxes, and/or containers (collectively referred to as totes) with one or more other individual goods of mixed or common types at an order fill station. It is noted that when, for example, incoming bundles or pallets (e.g. from manufacturers or suppliers of case units arrive at the storage and retrieval system for replenishment of the automated storage and retrieval system **100**, the content of each pallet may be uniform (e.g. each pallet holds a predetermined number of the same item—one pallet holds soup and another pallet holds cereal). As may be realized, the cases of such pallet load may be substantially similar or in other words, homogenous cases (e.g. similar dimensions), and may have the same SKU (otherwise, as noted before the pallets may be “rainbow” pallets having layers formed of homogeneous cases). As pallets leave the storage and retrieval system, with cases or totes filling replenishment orders, the pallets may contain any suitable number and combination of different case units (e.g. each pallet may hold different types of case units—a pallet holds a combination of canned soup, cereal, beverage packs, cosmetics and household cleaners). The cases combined onto a single pallet may have different dimensions and/or different SKU's.

(41) The automated storage and retrieval system may be generally described as a storage and retrieval engine **190** coupled to a palletizer **162**. In greater detail now, and with reference still to FIG. 1, the storage and retrieval system **100** may be configured for installation in, for example, existing warehouse structures or adapted to new warehouse structures. As noted before the system **100** shown in FIG. 1 is representative and may include for example, in-feed and out-feed conveyors terminating on respective transfer stations **170**, **160**, lift module(s) **150A**, **150B**, a storage structure

130, and a number of autonomous transport vehicles **110** (also referred to herein as “bots”). It is noted that the storage and retrieval engine **190** is formed at least by the storage structure **130** and the bots **110** (and in some aspect the lift modules **150A**, **150B**; however in other aspects the lift modules **150A**, **150B** may form vertical sequencers in addition to the storage and retrieval engine **190** as described in U.S. patent application Ser. No. 17/091,265 filed on Nov. 6, 2020 and titled “Pallet Building System with Flexible Sequencing,” the disclosure of which is incorporated herein by reference in its entirety). In alternate aspects, the storage and retrieval system may also include robot or bot transfer stations (not shown) that may provide an interface between the bots **110** and the lift module(s) **150A**, **150B**. The storage structure **130** may include multiple (stacked) levels **130L1-130Ln** (see FIGS. **1** and **16**, generally referred to as storage level **130** or a storage level **130**, and where n is an integer that denotes an upper number of storage levels present in the storage and retrieval system **100**) of storage rack modules where each level **130L** includes respective picking aisles **130A**, and transfer decks **130B** for transferring case units between any of the storage areas of the storage structure **130** and a shelf of the lift module(s) **150A**, **150B**. The picking aisles **130A** are in one aspect configured to provide guided travel of the bots **110** (such as along rails **1600**—see FIG. **16**) while in other aspects the picking aisles are configured to provide unrestrained travel of the bot **110** (e.g., the picking aisles are open and undeterministic with respect to bot **110** guidance/travel). The transfer decks **130B** have open and undeterministic bot support travel surfaces along which the bots **110** travel under guidance and control provided by bot steering (as will be described herein). In one or more aspects, the transfer decks have multiple lanes between which the bots **110** freely transition for accessing the picking aisles **130A** and/or lift modules **150A**, **150B**. The picking aisles **130A**, and transfer decks **130B** also allow the bots **110** to place case units CU into picking stock and to retrieve ordered case units CU. In alternate aspects, each level **130L** may also include respective bot transfer stations **140**. The bots **110** may be configured to place case units, such as the above described retail merchandise, into picking stock in the one or more levels **130L** of the storage structure **130** and then selectively retrieve ordered case units for shipping the ordered case units to, for example, a store or other suitable location. The in-feed transfer stations **170** and out-feed transfer stations **160** may operate together with their respective lift module(s) **150A**, **150B** for bi-directionally transferring case units CU to and from one or more levels **130L** of the storage structure **130**. It is noted that while the lift modules **150A**, **150B** may be described as being dedicated inbound lift modules **150A** and outbound lift modules **150B**, in alternate aspects each of the lift modules **150A**, **150B** may be used for both inbound and outbound transfer of case units from the storage and retrieval system **100**. It is noted that while the aspects of the disclosed embodiment are described with respect to a multilevel storage array, the aspects of the disclosed embodiment may be equally applied to a single level storage array that is disposed on a facility floor or elevated above the facility floor.

(42) As may be realized, the storage and retrieval system **100** may include multiple in-feed and out-feed lift modules **150A**, **150B** that are accessible by, for example, bots **110** of the storage and retrieval system **100** so that one or more case unit(s), uncontained (e.g. case unit(s) are not held in trays), or contained (within a tray or tote) can be transferred from a lift module **150A**, **150B** to each storage space **130S** on a respective level **130L** (see FIG. **16**) and from each storage space **130S** to any one of the lift modules **150A**, **150B** on a respective level **130L**. The bots **110** may be configured to transfer the case units between the storage spaces **130S** (e.g., located in the picking aisles **130A** or other suitable storage space/case unit buffer disposed along the transfer deck **130B**) and the lift modules **150A**, **150B**. Generally, the lift modules **150A**, **150B** include at least one movable payload support that may move the case unit(s) between the in-feed and out-feed transfer stations **160**, **170** and the respective level **130L** of the storage space **130S** where the case unit(s) CU is stored and retrieved. The lift module(s) may have any suitable configuration, such as for example reciprocating lift, or any other suitable configuration. The lift module(s) **150A**, **150B** include any suitable controller (such as controller **120** or other suitable controller coupled to controller **120**,

warehouse management system **2500**, and/or palletizer controller **164**, **164'**) and may form a sequencer or sorter in a manner similar to that described in U.S. patent application Ser. No. 16/444,592 filed on Jun. 18, 2019 and titled “Vertical Sequencer for Product Order Fulfillment” (the disclosure of which is incorporated herein by reference in its entirety).

(43) The automated storage and retrieval system may include a control system, comprising for example one or more control servers **120** that are communicably connected to the in-feed and out-feed conveyors and transfer stations **170**, **160**, the lift modules **150A**, **150B**, and the bots **110** via a suitable communication and control network **180**. The communication and control network **180** may have any suitable architecture which, for example, may incorporate various programmable logic controllers (PLC) such as for commanding the operations of the in-feed and out-feed conveyors and transfer stations **170**, **160**, the lift modules **150A**, **150B**, and other suitable system automation. The control server **120** may include high level programming that effects a case management system (CMS) **120** managing the case flow system. The network **180** may further include suitable communication for effecting a bi-directional interface with the bots **110**. For example, the bots **110** may include an on-board processor/controller **1220**. The network **180** may include a suitable bi-directional communication suite enabling the bot controller **1220** to request or receive commands from the control server **120** for effecting desired transport (e.g. placing into storage locations or retrieving from storage locations) of case units and to send desired bot **110** information and data including bot **110** ephemeris, status and other desired data, to the control server **120**. As seen in FIG. 1, the control server **120** may be further connected to a warehouse management system **2500** for providing, for example, inventory management, and customer order fulfillment information to the CMS **120** level program. A suitable example of an automated storage and retrieval system arranged for holding and storing case units is described in U.S. Pat. No. 9,096,375, issued on Aug. 4, 2015 the disclosure of which is incorporated by reference herein in its entirety.

(44) Referring now to FIGS. 2A, 2B, 2C, and 2D, the autonomous transport vehicle or bot **110** (which may also be referred to herein as an autonomous guided vehicle) includes a frame **200F** having a front end **200E1** and a back end **200E2** that define a longitudinal axis LAX of the autonomous transport vehicle **110**. The frame **200** may be constructed of any suitable material (e.g., steel, aluminum, composites, etc.) and includes a case handling assembly **210** configured to handle cases/payloads transported by the autonomous transport vehicle **110**. The frame **200F** of the case handling assembly **210** forms a transport payload area (also referred to as a payload bed or area) **210B**. As described herein the payload bed **210B** includes a payload contact support surface **610** (e.g., formed by protrusions **620** of justification tray **600**) that defines a payload support plane **610P** (FIG. 14E) of the vehicle **110** that supports the payload (e.g., case unit CU) held in the payload bay **210B** with vehicle traverse.

(45) The autonomous transport vehicle also includes any suitable transfer arm **210A** (also referred to as an articulated underpick end effector). The arm **210A** is configured to engage and underpick a payload with respect to the payload support plane **610P** (FIG. 14E), and extend and retract with respect to the payload bay **210B** effecting payload transfer to and from the payload bay **210B** unloading and loading the payload bay **210B**. Here, “underpick” is a picking of a payload by the end effector or transfer arm **210A** where the arm **210A** is arranged/configured to engage an underside of the payload CU and pick up the payload CU therefrom (i.e., lift from the underside) effecting transfer of the payload CU, from at least one of, each predefined storage area **130S** of storage racks (formed by, e.g., a vertical array of storage shelves VAS—see FIG. 16) and each transfer shelf (such as of a lift **150**) of the input/output station **160**, **170**, to the vehicle **110**. In a similar but opposite manner, the underpick end effector or transfer arm **210A** deterministically underpicks (via bottom engagement) the payload/case unit CU so as to transport and transfer the payload CU on and from the payload bed **210B** and place the payload CU at a storage space **130S** of a storage rack/transfer shelf (such as of the vertical array of storage shelves VAS or other

suitable payload holding area of the storage and retrieval system). At a pick/place location/operation, the underpick exchange between the transfer arm **210A** and the storage rack supports **900S** (see, e.g., FIG. **9**) of the storage spaces **130S** engages the underside/bottom of the payload/case unit CU (allowing substantially free unencumbered latitude) of case units on the storage racks so that the case units on the storage racks have a closely packed spacing therebetween (i.e., a spacing along a length of the storage rack that extends substantially parallel with, for example, a picking aisle **130A** or travel lane of the transfer deck **130B**), where the closely packed spacing is independent of a distortion of the sides of the cases. The arm **210A** is configured to transfer payloads between the autonomous transport vehicle **110** and a payload holding location (such as any suitable payload storage location, a shelf of lift module **150A**, **150B**, and/or any other suitable payload holding location). The transfer arm **210A** may be configured to extend laterally in direction LAT and/or vertically in direction VER to transport payloads to and from the case handling assembly **210**. In the aspect illustrated in FIGS. **2A** and **2B** the case handling assembly **210** includes at least one lift tower **211**, **212** configured to move the transfer arm **210A** and/or payload bed **210B** vertically in the direction VER as will be described in greater detail herein; however, in other aspects, the case handling assembly **210** may not have the at least one lift tower **211**, **212**. Examples of suitable payload beds **210B** and transfer arms **210A** and/or autonomous transport vehicles to which the aspects of the disclosed embodiment may be applied can be found in United States pre-grant publication number 2012/0189416 published on Jul. 26, 2012 (U.S. patent application Ser. No. 13/326,952 filed on Dec. 15, 2011) and titled “Automated Bot with Transfer Arm”; U.S. Pat. No. 7,591,630 issued on Sep. 22, 2009 titled “Materials-Handling System Using Autonomous Transfer and Transport Vehicles”; U.S. Pat. No. 7,991,505 issued on Aug. 2, 2011 titled “Materials-Handling System Using Autonomous Transfer and Transport Vehicles”; U.S. Pat. No. 9,561,905 issued on Feb. 7, 2017 titled “Autonomous Transport Vehicle”; U.S. Pat. No. 9,082,112 issued on Jul. 14, 2015 titled “Autonomous Transport Vehicle Charging System”; U.S. Pat. No. 9,850,079 issued on Dec. 26, 2017 titled “Storage and Retrieval System Transport Vehicle”; U.S. Pat. No. 9,187,244 issued on Nov. 17, 2015 titled “Bot Payload Alignment and Sensing”; U.S. Pat. No. 9,499,338 issued on Nov. 22, 2016 titled “Automated Bot Transfer Arm Drive System”; U.S. Pat. No. 8,965,619 issued on Feb. 24, 2015 titled “Bot Having High Speed Stability”; U.S. Pat. No. 9,008,884 issued on Apr. 14, 2015 titled “Bot Position Sensing”; U.S. Pat. No. 8,425,173 issued on Apr. 23, 2013 titled “Autonomous Transports for Storage and Retrieval Systems”; and U.S. Pat. No. 8,696,010 issued on Apr. 15, 2014 titled “Suspension System for Autonomous Transports”, the disclosures of which are incorporated herein by reference in their entireties.

(46) The frame **200** includes one or more suitable idler wheels **250** disposed adjacent the front end **200E1**. The idler wheels **250** may be substantially similar to those described in U.S. provisional patent application No. 63/213,589 filed on Jun. 22, 2021 with the title “Autonomous Transport Vehicle with Suspension” and U.S. provisional patent application No. 63/193,188 filed on May 26, 2021 with the title “Autonomous Transport Vehicle with Steering,” the disclosures of which are incorporated by reference herein in their entireties. The frame also includes one or more drive wheels **260** disposed adjacent the back end **200E2**. The drive wheels **260** may be substantially similar to those described in U.S. provisional patent application No. 63/213,589 filed on Jun. 22, 2021,” the disclosure of which was previously incorporated by reference herein in its entirety. In other aspects, the position of the idler wheels **250** and drive wheels **260** may be reversed (e.g., the drive wheels **260** are disposed at the front end **200E1** and the idler wheels **250** are disposed at the back end **200E2**).

(47) It is noted that in some aspects, the autonomous transport vehicle **110** is configured to travel with the front end **200E1** leading the direction of travel or with the back end **200E2** leading the direction of travel. For exemplary purposes only, the idler wheels **250A**, **250B** (which are substantially similar to idler wheel **250** described herein) are located at respective front corners of

the frame **200** at the front end **200E1** and drive wheels **260A**, **260B** (which are substantially similar to drive wheel **260** described herein) are located at respective back corners of the frame **200** at the back end **200E2** (e.g., a support wheel is located at each of the four corners of the frame **200**) so that the autonomous transport vehicle **110** stably traverses the transfer deck(s) **130B** and picking aisles **130A** of the storage structure **130**. In other examples, the idler wheels **250A**, **250B** are located at respective back corners of the frame **200** at the back end **200E2** and drive wheels **260A**, **260B** (which are substantially similar to drive wheel **260** described herein) are located at respective front corners of the frame **200** at the front end **200E1**.

(48) Each drive wheel **260** comprises a drive unit **261** that is independently coupled to the frame **200** in any suitable manner such as by suspension system **280**, so that each drive wheel **260** is independently movable relative to the frame and any other drive wheel(s) **260** that is/are also coupled to the frame in a manner substantially similar to that described in U.S. provisional patent application No. 63/213,589 filed on Jun. 22, 2021 and titled “Autonomous Transport Vehicle with Suspension”, the disclosure of which was previously incorporated herein by reference in its entirety. It is noted that each drive unit **261** comprises any suitable drive motor **261M** and a wheel **261W**. The drive motor **261M** is coupled to and rotationally drives the wheels **261W** so as to propel the autonomous transport vehicle **110** in a travel direction. Here the motors **261M** of two drive wheels **260A**, **260B** may be operated at the same time and at substantially the same rotational speed to propel the autonomous transport vehicle **110** in a substantially straight line path of travel. In other aspects, the motors **261M** of the two drive wheels **260A**, **260B** may be operated at the same time (or at different times) and at different rotational speeds to propel the autonomous transport vehicle **110** along an arcuate path of travel or to pivot the autonomous transport vehicle in direction **294** about vehicle pivot axis **293**. The vehicle pivot axis **293** may be located about midway between the two drive wheels **260A**, **260B**. The differential operation of the motors **261M** of the respective drive wheels **260A**, **260B** that effects turning and/or pivoting of the autonomous guided vehicle **110** as described above is referred to herein as differential drive wheel steering.

(49) Referring still to FIGS. **2A** and **2B** as well as FIGS. **3A-5C** the case handling assembly **210** will be described. As noted above, the case handling assembly **210** includes the transfer arm **210A** and/or payload bed (or bay) **210B**. In this aspect, the payload bed **210B** is movably coupled to the at least one lift tower **211**, **212** for vertical movement in direction **VER** and the transfer arm **210A** is movably coupled to the payload bed **210B** for lateral movement in direction **LAT**. The payload bed **210B** includes a payload bed frame **210BF** that forms a payload area in which case units carried by the bot **110** are disposed for transport throughout the storage and retrieval system **100**. The payload bed frame **210BF** includes longitudinal ends **210BE1**, **210BE2** that are each coupled to a respective one of the at least one lift tower **211**, **212**. Here the at least one lift tower includes lift tower **211** disposed at or adjacent the front end **200E1** of the frame **200** and lift tower **212** disposed at or adjacent the back end **200E2** of the frame **200**. Here, each lift tower **211**, **212** includes a movable carriage or carrier **290** to which a respective one of the longitudinal ends **210BE1**, **210BE2** is fixedly coupled in any suitable manner such as mechanical or chemical fasteners (i.e., so that as the movable carrier **290** moves the payload bed frame **210BF** moves with the movable carrier **290**).

(50) Referring to FIGS. **3A** and **3B**, in one or more aspects, as noted above, the vehicle **110** includes at least one lift tower **211**, **212**. Each of the at least one lift tower **211**, **212** is substantially similar to each other of the at least one lift tower **211**, **212** such that only lift tower **211** and its carrier **290** will be described (i.e., the lift towers **211**, **212** are interchangeable/common with each other and may be placed adjacent either the front end **200E1** or back end **200E2** of the frame **200**). The lift tower **211** includes a tower frame **300F**. The tower frame **300F** includes a base **305**, vertical guides **306**, **307**, and a cross brace or brace **308**. The carrier or movable payload carriage **290** extends laterally between and is guided in vertical movement by the vertical guides **306**, **307** (e.g., the carrier **290** is configured to raise and lower the payload CU within the payload area **210B**. For

example, the lift tower **211** includes the vertical guides **306, 307**, each of which forms a guide rail **306R, 307R** that guides movement of the carrier **290**. An interface between the guide rail **306R, 307R** and the carrier **290** is undeterministic with respect to a torsional position of the carrier **290** relative to the guide rail **306R, 307R**. For example, vertical guides **306, 307** may comprise “C” shaped channels that form the guide rails **306R, 307R**. Here, the vertical guides **306, 307** are easily and inexpensively extruded (or stamped or near net shape cast) structures that reduce cost and facilitate easy assembly/disassembly of the lift tower **211, 212** to the frame **200F**. The carrier **290** includes ends **290E1, 290E2** that are received into a respective guide rail **306R, 307R**. The ends **290E1, 290E2** may include any suitable low cost lubricious bushing **290B** that is easily insert able to (and removed from) the respective guide rail **306R, 307R** so as to engage the respective guide rail **306R, 307R** and facilitate easy assembly and disassembly of the carrier **290** to the guide rails **306R, 307R**. The ends **290E1, 290E2** and the respective bushings **290B** engaged with the guide rail **306R, 307R** are configured to restrain movement of the carrier **290** in the longitudinal direction LON, while allowing the carrier **290** unrestrained movement in direction VER within the guide rails **306R, 307R** (i.e., the bushings **290B** have a running fit clearance with the guide rails **306R, 307R** such that the guide rails do not need to be manufactured with tight/small tolerances). The bushings **290B** provide a sacrificial material that may be easily replaced, where the bushings **290B** are coupled to the respective end **290E1, 290E2** with removable fasteners, snaps, clips, or any other suitable removable coupling. The guide rails **306R, 307R** provide for a smooth/fast motion of the carrier **290** in direction VER as the carrier **290** is raised/lowered relative to the frame **200F**, where, as described herein, torsional stiffness of the carrier **290** is provided by a flexible transmission **330** that facilitates the undeterministic interface between the ends **290E1, 290E2** and the guide rails **306R, 307R**.

(51) A drive section **390S** with at least one degree of freedom movement is coupled to the carrier **290** by a flexible transmission **330**. Here, the flexible transmission movably couples the carrier **290** to the at least one lift tower **211, 212** and the drive section **290S** is configured to move the carrier **290** relative to the at least one lift tower **211, 212**. For example, the carrier **290** moves vertically in direction VER between the base **305** and brace **308** under motive force of any suitable drive motor **390** of the drive section **390S**, where, for example, the drive motor **390** is coupled to the carrier **290** by the flexible transmission **330** (such as those described herein). In one aspect, the drive motor **390** is a rotary motor coupled to the carrier **290** through a flexible transmission **330** (e.g., belts, chains, and/or cables); while in other aspect the drive motor **390** may be a linear motor (e.g., any suitable electric, hydraulic, and/or pneumatic linear actuator) coupled to the carrier **290** for moving the carrier **290** in direction VER. In the aspect illustrated in FIG. 3A, the frame includes pulleys **320-325** (or sprockets in aspects where chains are employed) rotatably coupled thereto. Pulleys **320, 321** are coupled to the base **305** while pulleys **322-325** are coupled to the brace **308**. A serpentine flexible transmission member **330** extends around the pulleys **320-325** and is coupled to the carrier **290**. In the aspect illustrated, the flexible transmission member **330** is a toothed belt and the pulleys are toothed pulleys; however, as noted above, in other aspects the flexible transmission member **330** is any suitable cable, chain, or other transmission member capable of serpentine routing.

(52) The flexible transmission **330** is configured to effect torsional stability of the carrier **290**, and the payload CU held thereon (noting that the carrier **290** carries the payload bed **210B** and transfer arm **210A** as described herein), with respect to the frame **200F** and independent of each other interface between the carrier **290** and the at least one lift tower **211, 212** than the flexible transmission **330** coupling the carrier **290** to the at least one lift tower **211, 212**. For example, as described above, the interface between the ends **290E1, 290E2** and the guide rails **306R, 307R** is undeterministic such that a running clearance is provided therebetween allowing the ends **290E1, 290E2** to move freely in direction VER. The configuration of the flexible transmission **330** described herein restrains the ends **290E1, 290E2** in at least direction VER so as to effect torsional

stability of the carrier **290**. As may be realized, the flexible transmission **330** drives the carrier **290** in direction VER along the vertical guides **306**, **307** and is configured to effect torsional stability of the carrier **290** throughout an entire range of motion of the carrier **290** relative to the at least one lift tower **211**, **212**. The flexible transmission **330**, as described herein, is also configured to effect torsional stability of the carrier **290** throughout a range of motion of the carrier **290**, relative to the at least one lift tower **211**, **212**, that effects a payload transfer from the carrier **290** (e.g., the payload bed **210B** and transfer arm **210A** carried thereby) to a payload support shelf (such as in the vertical array of storage shelves VAS or any other payload holding area of the storage and retrieval system). Similarly, the flexible transmission **330** is configured to effect torsional stability of the carrier **290** throughout a range of motion of the carrier **290**, relative to the at least one lift tower **211**, **212**, that effects a payload transfer from a payload support shelf (such as in the vertical array of storage shelves VAS or any other payload holding area of the storage and retrieval system) to the carrier **290** (e.g., the payload bed **210B** and transfer arm **210A** carried thereby).

(53) As an example, the flexible transmission member **330** is endless or otherwise forms a closed loop transmission where the ends of the flexible transmission member **330** are fixed to or adjacent one another. The closed loop transmission is configured to provide torsional stability to the carrier **290** so that the carrier **290** and the payload bed **210B** and transfer arm **210A** coupled thereto and carried thereby remains in a predetermined spatial orientation relative to one or more of the frame **200F**, a travel surface upon which the autonomous guided vehicle **110** travels, and a case seating surface to and from which case units are transferred (e.g., so that the transfer arm **210A** and payload bed **210B** are substantially parallel with seating surfaces of case unit CU holding locations so as to effect picking and placing of the case units CU with the transfer arm **210A**). For example, extension of the transfer arm **210A** for picking or placing a case unit causes the center of mass of the transfer arm **210A** (and any case unit or object carried on the transfer arm **210A**) to move laterally in direction LAT relative to the frame **200F** (and the carriers **290** of the at least one lift tower **211**, **212**). This lateral movement of the center of mass of the transfer arm **210A** (and any object carried thereon) inducing torsional moments on at least the carriers **290** which torsional moments are resisted/countered by the closed loop transmission formed by the flexible transmission member (belt, chain, cable, etc.) **330**.

(54) An exemplary serpentine (closed loop) transmission path of the flexible transmission member **330** is illustrated in FIG. 3B where the flexible transmission member **330** is fixedly coupled to the carrier **290** (so that as the flexible transmission member **330** moves the carrier moves with the flexible transmission member **330**) at couplings **340**, **341** adjacent lateral ends of the carrier **290**. As may be realized, the further apart the couplings **340**, **341** the more resistant the carrier **290** is to torsion loads created by, for example, extension of the transfer arm **210A**. As described above, the drive motor **390** drives movement of the flexible transmission member **330** (and the carrier **290** coupled thereto).

(55) In the aspect illustrated in FIG. 3A, the motor **390** is mounted to the tower frame **300F** in any suitable manner, such as with mechanical or chemical fasteners. The pulleys **320**, **321** coupled to the base **305** are coupled to the base **305** such the axle PXL of the respective pulleys **320**, **321** is accessible through sides of the base **305** for coupling to with a drive coupling DC or driven pulley **350**. Here, the driven pulley **350** (or sprocket) is coupled to the axle PCL of pulley **320** (or pulley **321**) where the driven pulley **350** is coupled to a drive pulley **351** (or sprocket) of the motor **390** by a drive belt **352** (or chain or cable). In other aspects, a drive shaft of the motor **390** may be coupled substantially directly to the axle PXL of the pulley **320** (or pulley **321**). The axle PXL of pulley **320** is also coupled to a drive shaft **355** by a drive coupling DC, where one end of the drive shaft **355** is coupled to axle PXL of pulley **320** of lift tower by the drive coupling DC and the other end of the drive shaft **355** is coupled to axle PXL of pulley **321** of lift tower **312** by another drive coupling DC so that the respective flexible transmission members **330** of the lift towers **211**, **212** are driven by a common motor (i.e., motor **390** drives the flexible transmission members **330** of both lift towers

211, 212) and so that the carriers **290** (of lift towers **211, 212**), coupled to the respective flexible transmission members **330**, are synchronously moved in direction VER. Here the axle PXL of the pulleys **320, 321** are configured to mate with a corresponding recess of the driven pulley **350** and drive coupling DC in any suitable manner such as by forming a splined coupling, a hex drive coupling or any other suitable drive coupling so that driving force is transmitted to the axle PXL of the respective pulley **320, 321**. In other aspects, each lift tower **211, 212** has a respective motor (where the motors are synchronized in their movement in any suitable manner such as with suitable encoders, etc.) for driving movement of the respective belt (and carrier coupled thereto).

(56) Referring to FIGS. **4A, 4B**, and **4C**, in one or more aspects, the lift towers **211, 212** are substantially similar to those described above with respect to FIGS. **3A** and **3B**; however, carrier **290** of each lift tower **211, 212** is driven by a flexible transmission member **430** (substantially similar to flexible transmission member **330** described above) and stabilized against torsional forces by flexible stabilizing members **435, 436** (belts, chains, cables, etc.) that are separate and distinct from the flexible transmission member **430**. In this aspect, a pulley **421** is coupled to the base **305** in a manner substantially similar to pulleys **320, 321** described above, and a pulley **422** is coupled to the brace **308** in a manner substantially similar to pulleys **322-325** described above. The flexible transmission member **430** forms a continuous/endless loop around the pulleys **421, 422**. In one or more aspects, the flexible transmission member **430** is a toothed belt and the pulleys **421, 422** are toothed pulleys however, in other aspects any suitable belts, chains, cables, etc. and pulleys may be employed. The carrier **290** is coupled to one side of the continuous loop by coupling **340** as illustrated in FIG. **4C** so as to drive the carrier **290** in direction VER as the flexible transmission member **430** is driven around the pulleys by motor **390** in a manner substantially similar to that described above with respect to flexible transmission member **330** (in this aspect the motor **390** is illustrated as being coupled substantially directly to the axle PXL of pulley **421** by any suitable drive coupling similar to that described above, where pulleys **421** of lift tower **211** and lift tower **212** are coupled by drive shaft **355** in a manner substantially similar to that described above so that the flexible transmission members **430** and carriers **290** of the lift towers **211, 212** are synchronously moved in direction VER. In other aspects, the each lift tower **211, 212** may have a respective drive motor **390** for driving a respective flexible transmission member **430** where the rotation of the drive motors are synchronized in any suitable manner (such as described herein).

(57) As described above, the carrier **290** of each lift tower **211, 212** illustrated in FIGS. **4A-4C** is torsionally stabilized (e.g., against torsional forces induced by extension of the transfer arm **210A**) by a pair of flexible stabilizing members **435, 436** disposed adjacent or at the lateral ends of the respective carrier **290**. Each flexible stabilizing member **435, 436** has a terminal end **435E1, 436E1** fixedly coupled to the brace **308** (in any suitable manner such as by mechanical or chemical fasteners) and another terminal end **435E2, 436E2** fixedly coupled to the base **305** (in any suitable manner such as by mechanical or chemical fasteners). Each flexible stabilizing member **435, 436** follows a serpentine path (shown in FIG. **4B**) between the brace **308** and the base **305**, where the serpentine path is defined at least in part by a pair of offset pulleys **423A, 424A** and **423B, 423B** (or sprockets in the case a chain is employed) that are rotatably coupled to the carrier **290** adjacent or at lateral ends of the carrier **290** (as illustrated in FIG. **4A**). Here the pulleys **423A, 424A** are offset both vertically in direction VER and longitudinally in direction LON. Pulleys **423B, 424B** are also offset both vertically in direction VER and longitudinally in direction LON so that the pulleys **423A, 423B** are substantially in-line with each other in direction LAT (i.e., coaxial with each other) and pulleys **424A, 424B** are substantially in-line with each other in direction LAT (i.e., coaxial with each other) as illustrated in FIG. **4B**. As can be seen in FIGS. **4A** and **4B**, the flexible stabilizing member **435** forms a serpentine path around pulleys **423A, 424A** and flexible stabilizing member **436** forms a serpentine path around pulleys **423B, 424B**. The serpentine path of each flexible stabilizing member **435, 436** forms a substantial S shape around the respective pulleys **423A, 424A, 423B, 424B**. The pulley **424A** is rotationally fixed to pulley **424B** (i.e., as pulley

424A rotates the pulley **424B** rotates with pulley **424A**) by shaft **450** (or any other suitable mechanical coupling) so as to, in conjunction with the serpentine path of the flexible stabilizing members **435**, **436**, maintain the relative position of the carrier **290** with at least the frame **300F** to prevent a tilting or tipping of the carrier **290** under torsional loads induced on the carrier **290** by the extension of the transfer arm **210A** as described herein. In other aspects, the pulleys **423A**, **423B** are also rotationally fixed to each other in a manner similar to that described above with respect to pulleys **424A**, **424B**. In other aspects, the pulleys **423A**, **423B** are rotationally fixed to each other in lieu of the rotational fixing of pulleys **424A**, **424B**.

(58) Referring to FIGS. 5A, 5B, and 5C, in one or more aspects, the lift towers **211**, **212** are substantially similar to those described above with respect to FIGS. 4A, 4B, and 4C; however, the carrier **290** of each lift tower **211**, **212** is stabilized against torsional forces by opposing flexible stabilizing members **535**, **536** (illustrated as cables but in other aspects, chains, belts, etc.) that are separate and distinct from the flexible transmission member **430** and extend along the carrier **290** in at least the direction LAT. For example, the carrier **290** of each lift tower **211**, **212** includes pulleys **590**, **591** disposed on one side of the carrier **290** and pulleys **592**, **593** disposed on another side of the carrier **290** so that an axis of rotation SPX1, SPX2 of each of the pulleys extends in direction LON and the pulleys lie substantially parallel with a plane of the respective lift tower **211**, **212**. In other aspects, the pulleys **590-593** are located on the same/common side of the carrier **290**. The pulleys **591**, **593** at or adjacent one end of the carrier **290** are coaxially located along axis SPX2 and the pulleys at or adjacent the other end of the carrier **290** are coaxially located along axis SPX1; however in other aspects the pulley **591** may not be coaxially located with pulley **593** and the pulley **590** may not be coaxially located with pulley **592**.

(59) Flexible stabilizing member **535** is wrapped around pulleys **590**, **591** along a serpentine path (a substantially “S” shaped path as illustrated in FIG. 5B) so that one end **535E1** of the flexible stabilizing member **535** at or adjacent end **290E1** of the carrier **290** and extending from pulley **591** is fixedly coupled to the brace **308** and another end **535E2** of the flexible stabilizing member **535** at or adjacent the other end **290E2** of the carrier **290** and extending from pulley **590** is fixedly coupled to the base **305**. Flexible stabilizing member **536** is wrapped around pulleys **592**, **593** in a manner that opposes flexible stabilizing member **535**. For example, flexible stabilizing member **536** is wrapped around pulleys **590**, **591** along a serpentine path (a substantially “S” shaped path as illustrated in FIG. 5C) so that one end **536E1** of the flexible stabilizing member **536** at or adjacent end **290E1** of the carrier **290** and extending from pulley **593** is fixedly coupled to the base **305** (e.g., end **536E1** of flexible stabilizing member **536** opposes end **535E1** of flexible stabilizing member **535**) and another end **536E2** of the flexible stabilizing member **536** at or adjacent the other end **290E2** of the carrier **290** and extending from pulley **592** is fixedly coupled to the brace **308** (e.g., end **536E2** of flexible stabilizing member **536** opposes end **535E2** of flexible stabilizing member **535**). This opposing serpentine flexible stabilizing member arrangement illustrated in FIGS. 5A, 5B, and 5C maintains the relative position of the carrier **290** with at least the frame **300F** to prevent a tilting or tipping of the carrier **290** under torsional loads induced on the carrier **290** by the extension of the transfer arm **210A** as described herein.

(60) Referring again to FIGS. 2A and 2B as well as FIGS. 6A, 6B, 6C, 6D, 6E, 6F, and 6G, as described above, the payload bed frame **210BF** coupled to (e.g., via the carriers **290**) and extends between the lift towers **211**, **212**. In other aspects, the payload bed frame **210BF** is cantilevered from one lift tower or coupled to more than two lift towers. The payload bed frame **210BF** has mounted thereon a justification tray **600**. The justification tray **600** includes a base **630** and at least one case unit support surface **610** coupled to the base **630** (or integrally formed with the base **630**) in any suitable manner. The at least one case unit support surface **610** forms a case unit support plane **610P** along which case units CU carried by the bot **110** can be moved laterally and/or longitudinally to justify/reposition the case units CU on the payload bed **210B** as will be described herein. The at least one case unit support surface **610**, in one or more aspects, is/are one or more

protrusions **620** that extend from the base **630** where each protrusion **620** has an arcuate surface **621** upon which the case units are supported. In other aspects, the at least one case unit support surface **610** is/are one or more laterally extending rollers **620A** that extend in direction LAT; while in still other aspects the at least one case unit support surface **610** is formed by a plurality of ball bearings **620B** that form a ball transfer table; while in still other aspects the at least one case unit support surface **610** may be formed by a combination of protrusions, rollers, and ball bearings.

(61) Referring to FIGS. **6A** and **6E-6G**, the base **630** of the justification tray **600** is coupled to the payload bed frame **210BF** in any suitable manner so that as the payload bed frame **210BF** moves in direction VERT relative to the bot **110** frame **200F** the justification tray **600** moves with the payload bed frame **210BF**. For example, the payload bed frame **210BF** includes guide members **666P** (e.g., posts, rods, etc.) that hold the justification tray captive to the payload bed frame **210BF** and along which the justification tray slides in direction VERT. In one or more aspects, any suitable biasing member(s) **666** (e.g., springs, resilient/rubber bushings, etc.) are provided and bias (in direction VERL) the justification tray **600** away from the payload bed frame **210BF**; while in other aspects gravity and/or biasing members **666** may bias the justification tray **600** in direction VERL. With the justification tray **600** biased away from the payload bed frame **210BF** (see FIG. **6E**), case unit support surfaces **210AFS** of tines or fingers **210AF** of the transfer arm **210A** (as will be described herein) are disposed above the payload support plane **610P** of the justification tray **600**. With the justification tray **600** moved toward the payload bed frame **210BF** (e.g., against the biasing force of the biasing member(s) **666** and/or against the force of gravity—such as by contact of the justification tray **600** with the frame **200F**) the case unit support surfaces **210AFS** of tines or fingers **210AF** of the transfer arm **210A** are disposed below the payload support plan **610P** (see FIGS. **6F** and **6G**) so that case units CU are transferred from the case unit support surfaces **210AFS** of the fingers **210AF** to the support surface(s) **610** of the justification tray **600**.

(62) As illustrated in FIGS. **6A** and **6F**, at least a portion of the payload bed frame **210BF** and at least a portion the base **630** of the justification tray **600** are shaped and sized to fit within and be recessed into the frame **200F** of the bot **110**. The justification tray **600** is configured so that the protrusions **620** (or in the case of the rollers **620A** and ball bearings **620B** any suitable tabs or portion of the base **630**) extends over the frame **200F** (in the aspect illustrated in FIG. **6A** the protrusions extend laterally in direction LAT but in other aspects any suitable tabs may extend longitudinally in direction LON and/or laterally in direction LAT) so that as the portion of the payload bed frame **210BF** is lowered/recessed (e.g., by the lift towers **211**, **212**) in direction VERL into an opening **670** of the frame **200F** the protrusions **620** abut the frame **200F** (or any other suitable hard stop surface of the bot **110**) causing the justification tray **600** to be seated on the frame **200F** (or any other suitable hard stop surface of the bot **110**) and move toward the payload bed frame **210BF**. As the payload bed frame **210BF** continues to move in direction VERL (with the movement of the justification tray **600** in direction VERL stopped by the frame **200F**) the payload support plane **610P** is positioned above the case unit support surfaces **210AFS** of tines or fingers **210AF** to transfer case units CU from the fingers **210AF** to the justification tray **600** (e.g., support of the case units are transferred from the transfer arm **210A** to the justification tray **600** for justification/repositioning in directions LON, LAT). Any suitable resilient material (e.g., rubber (or other elastomeric/resilient material) bushings, pads, etc.) may be placed between the justification tray **600** and the frame **200F** to substantially dampen vibrations from the frame **200F** to the justification tray **600** and vice versa.

(63) With the case units justified/repositioned, the lift towers **211**, **212** move the payload bed **210B** in direction VERU so that the biasing members **666** and/or gravity bias (e.g. in direction VERL) the justification tray **600** away from the payload bed frame **210BF**. With continued movement of the payload bed **210B** in direction VERU the case unit support surfaces **210AFS** of the fingers **210AF** move past (e.g., above) the payload support plane **610P** of the justification tray **600** to transfer support of the case units CU from the justification tray **600** to the fingers **210AF**. As may

be realized, the case units CU can be transported by the bot **110** with the case units CU supported on the justification tray and/or supported on the fingers **210AF**. The justification tray **600** is also configured to retain, such as in troughs **665** (see FIGS. **6B** and **7B**) adjacent/between the case unit support surfaces **610**, any debris (e.g., liquids and/or solids) from the case units CU held/supported in the payload bed **210B** by the transfer arm **210A** or justification tray **600**. Retention of case unit debris by the justification tray **600** may prevent the debris from falling on, for example, the transfer deck **130B** (FIG. **1**) and picking aisles **130A** (FIG. **1**) where such fallen debris may decrease wheel traction between the bot **110** wheels and the travel/support surfaces of the transfer deck **130B** and picking aisles **130A**.

(64) Referring to FIGS. **6A** and **6B-6D**, in one or more alternate aspects, the base **630** of the justification tray **600** is coupled to the payload bed frame **210BF** in any suitable manner (such as with guide members **666P**) so that as the payload bed frame **210BF** moves in direction VERT relative to the bot **110** frame **200F** the justification tray **600** moves with the payload bed frame **210BF**. In one or more aspects, the justification tray **600** is coupled to the payload bed frame **210BF** by a biased coupling that provides relative movement of the justification tray **600** relative to the payload bed frame **210BF** in direction VERT while biasing the justification tray **600** against the payload bed frame **210BF** in direction VERT. For example, any suitable biasing member(s) **666** (e.g., springs, resilient/rubber bushings, etc.) bias the justification tray **600** in direction VERL towards the payload bed frame **210BF** (see FIG. **6A**) and provide for the relative movement between the justification tray **600** and the payload bed frame in direction VERT. With the justification tray **600** biased against the payload bed frame **210BF** (see FIG. **6B**), case unit support surfaces **210AFS** of tines or fingers **210AF** of the transfer arm **210A** (as will be described herein) are disposed above the payload support plane **610P** of the justification tray **600**. With the justification tray **600** moved away from the payload bed frame **210BF** (e.g., against the biasing force of the biasing member(s) **666**—such as by contact with the frame **200F**) the case unit support surfaces **210AFS** of tines or fingers **210AF** of the transfer arm **210A** are disposed below the payload support plane **610P** (see FIGS. **6C** and **6D**) so that case units CU are transferred from the case unit support surfaces **210AFS** of the fingers **210AF** to the support surface(s) **610** of the justification tray **600**.

(65) As illustrated in FIGS. **6A** and **6D**, at least a portion of the payload bed frame **210BF** and at least a portion the base **630** of the justification tray **600** are shaped and sized to fit within and be recessed into the frame **200F** of the bot **110**. The justification tray **600** is configured so that the protrusions **620** (or in the case of the rollers **620A** and ball bearings **620B** any suitable tabs or portion of the base **630**) extends over the frame **200F** (in the aspect illustrated in FIG. **6A** the protrusions extend laterally in direction LAT but in other aspects any suitable tabs may extend longitudinally in direction LON and/or laterally in direction LAT) so that as the portion of the payload bed frame **210BF** is lowered/recessed (e.g., by the lift towers **211**, **212**) in direction VERL into an opening **670** of the frame **200F** the protrusions **620** abut the frame **200F** (or any other suitable hard stop surface of the bot **110**) causing the justification tray **600** to be seated on the frame **200F** (or any other suitable hard stop surface of the bot **110**) and become spaced apart from the payload bed frame **210BF** (e.g., the movement of the justification tray **600** in direction VERL is stopped by the frame **200F** while the payload bed frame **210BF** continues to move in direction VERL). As the payload bed frame **210BF** continues to move in direction VERL the case unit support surfaces **210AFS** of the fingers **210AF** move past (e.g., beneath) the payload support plane **610P** of the justification tray **600** to transfer case units CU from the fingers **210AF** to the justification tray **600** (e.g., support of the case units are transferred from the transfer arm **210A** to the justification tray **600** for justification/repositioning in directions LON, LAT).

(66) With the case units justified/repositioned, the lift towers **211**, **212** move the payload bed **210B** in direction VERU so that the biasing members **666** bias (e.g. in direction VERL) the justification tray **600** against the payload bed frame **210BF**. With continued movement of the payload bed **210B**

in direction VERU the case unit support surfaces **210AFS** of the fingers **210AF** move past (e.g., above) the payload support plane **610P** of the justification tray **600** to transfer support of the case units CU from the justification tray **600** to the fingers **210AF**. As may be realized, the case units CU can be transported by the bot **110** with the case units CU supported on the justification tray and/or supported on the fingers **210AF**. The justification tray **600** is also configured to retain, such as in troughs **665** (see FIGS. **6B** and **7B**) adjacent/between the case unit support surfaces **610**, any debris (e.g., liquids and/or solids) from the case units CU held/supported in the payload bed **210B** by the transfer arm **210A** or justification tray **600**. Retention of case unit debris by the justification tray **600** may prevent the debris from falling on, for example, the transfer deck **130B** (FIG. **1**) and picking aisles **130A** (FIG. **1**) where such fallen debris may decrease wheel traction between the bot **110** wheels and the travel/support surfaces of the transfer deck **130B** and picking aisles **130A**.

(67) The justification tray **600** is positioned relative to the fingers **210AF** of the transfer arm **210A** so that, with the payload bed **210B** raised relative to the frame **200F** for picking and/or placing a case unit CU, the case unit support surface **210AFS** of the fingers **210AF** are located a distance (e.g., gap) CAG above the support surface **610** of the justification tray **600**. This gap CAG is sized (i.e., minimized) only to allow sufficient clearance between a case unit CU supported on the fingers **210AF** so that movement of the case unit CU above the support surface **610** (e.g., the arcuate support surfaces **621**) is without contact between the case unit CU and the support surface **610**. As will be described herein. The minimized gap CAG effects, with relative vertical movement between the fingers **210AF** and justification tray **600** (e.g., where the relative movement of the justification tray **600** effected by the frame **200F** or an actuator **666A**), seating of the case unit CU on the justification tray **600** substantially immediately proximate to the end effector **210A** positioning the underpick case unit CU within the payload bay **210B** loading the payload bay **210B**. For example, when a transfer arm **210A** retract movement into the payload bed **210B** is complete, the relative movement between the transfer arm **210A** and the justification tray **600** substantially coincident with and substantially immediately upon completion of retract movement transfers the case unit CU to justification tray **600**. The support surface **610** has a sufficient coefficient of friction to stably hold the case unit CU thereon so as to register the case unit CU in two degrees of registration (vertically in direction VER and planar in directions LON, LAT) to effect commencement of autonomous transport vehicle **110** traverse motion (without the case unit being gripped by the justification bars **222**, **223**, the pusher arms **1150**, or the case pullers) substantially coincident with completion of retract movement (e.g., the case unit is retracted into the payload bed **210B**, securely registered on the justification tray **600**, and the vehicle **110** traverse is commenced in about 10 seconds or less). As described herein, the justification tray **600** extends above the fingers through contact with the frame **200F**; however, the payload bay **210B** may include linear actuators **666A** (see FIGS. **6B** and **6E**) to raise or lower the justification tray **600** relative to the fingers **210A**. As an example, the actuators **666A** may be employed where the transfer arm **210A** and payload bed **210B** are raised (e.g., via the lift towers **211**, **212**) to pick case units CU from an upper shelf **900U** of an array of stacked shelves as described herein (see FIG. **16**).

(68) Referring to FIGS. **2A**, **2B**, **7A**, and **7B**, as described above, the transfer arm **210A** is movably coupled to the payload bed frame **210BF** in any suitable manner so that the fingers **210AF** of the transfer arm **210A** are spaced from the payload bed frame **210BF** in direction VER by any suitable distance **667** (FIG. **2B**). For example, the transfer arm **210A** includes an extension axis **270** that is coupled to the payload bed frame **210BF** and configured to provide movement of the fingers **210AF** relative to the payload bed frame **210BF** in direction LAT. Here the extension axis **270** includes a linear guide rail **271** coupled to the payload bed frame **210BF** at or adjacent end **210BE1** of the payload bed frame **210BF**, and another linear guide rail **272** coupled to the payload bed frame **210BF** at or adjacent end **210BE2** of the payload bed frame **210BF**. The fingers **210AF** are coupled to a finger support rail **273** of the transfer arm **210A**, where the finger support rail **273** spans between and is movably coupled to the linear guide rails **271**, **272** for reciprocating

movement (e.g., extension and retraction) along the linear guide rails **271**, **272** in direction LAT. The transfer arm **210A** includes any suitable motor **275** (e.g., rotary motor, linear motor, etc.) and transmission **276** (e.g., belts, gears, etc.) for driving the finger support rail **273** along the linear guide rails **271**, **272** to effect reciprocal movement of the fingers **210AF** in direction LAT. In the aspect illustrated in the figures the transfer arm **210A** extends and retracts from one lateral side of the bot **110** frame **200F** while in other aspects the transfer arm **210A** is configured for bidirectional extension (e.g., extends and retracts from both lateral sides of the bot **110** frame **200F**).

(69) In the aspects illustrated in FIGS. **2A**, **2B**, **7A**, and **7B** there are three fingers **210AF1**, **210AF2**, **210AF3** (see FIGS. **7A** and **7B**) coupled to the finger support rail **273**; however, in other aspects there are more than three or less than three fingers coupled to the finger support rail **273**. Here, one or more of the fingers **210AF1**, **210AF2**, **210AF3** are movably coupled to the finger support rail **273** so as to be movable along the finger support rail **273** in the direction LON to at least change/vary a pitch or distance between the fingers **210AF1**, **210AF2**, **210AF3**. In one or more aspects, one or more of what may be referred to as outboard fingers **210AF1**, **210AF3** are movable relative to one or more of what may be referred to as inboard fingers **210AF2**. For example, the finger **210AF2** is stationarily fixed at a predetermined location on the finger support rail (e.g., does not move relative to the finger support rail **273**) such as at or along a laterally extending centerline **777** of the payload bed **210B** or the finger **210AF2** may be driven in direction LON independently of one or more of the outboard fingers **210AF1**, **210AF3**.

(70) At least the fingers **210AF1**, **210AF3** are coupled to the finger support rail **273** so as to move relative to each other and the finger **210AF2** in direction LON; while in other aspects, each of the fingers **210AF1**, **210AF2**, **210AF3** are coupled to the finger support rail **273** so as to move relative to each other. The finger support rail **273** includes any suitable number of linear actuators **776** for effecting the movement of the fingers **210AF1**, **210AF3** or fingers **210AF1**, **210AF2**, **210AF3** in direction LON. The fingers **210AF1**, **210AF2**, **210AF3** may be movable in direction LON independent of each other, in a fixed relationship with one or more other fingers, or as a single unit. The linear actuator(s) is/are any suitable actuator(s), examples of which include but are not limited to, pneumatic cylinders, hydraulic cylinders, ball-screw drives, lead-screw drives, rack and pinion drives, rotary arm-linkage drives, belt drives, chain drives, or any other suitable drive configured to effect linear movement of the fingers along the finger support rail in direction LON.

(71) In one or more aspects, each finger **210AF1**, **210AF3** has a respective linear actuator **776** so that the fingers **210AF1**, **210AF3** move independent of each other in direction LON, while in other aspects there is a single linear actuator **776** that is common to each finger **210AF1**, **210AF3** so that the single actuator **776** moves each of the fingers **210AF1**, **210AF3** in the direction LON in a fixed relationship. As an example, the linear actuator **776** is common to both fingers **210AF1**, **210AF3** and includes a stepper motor **776M** (or other suitable motor) and a lead screw **776S** having a right handed lead screw portion **776R**, and a left handed lead screw portion **776L**, where the lead screw **776S** is coupled to the stepper motor. One of the fingers **210AF1**, **210AF3** is coupled to the right handed lead screw portion **776R** and the other of the fingers **210AF1**, **AF3** is coupled to the left handed lead screw portion **776L** so that as the stepper motor simultaneously rotates both the left and right handed lead screw portions **776L**, **776R** in a first rotation direction the fingers **210AF1**, **210AF2** move away from each other and away from the finger **210AF2** to increase the distance **760A**, **760B** between the fingers to any suitable increased distance **760A'**, **760B'**, **760A''**, **760B''**. As the stepper motor **776M** simultaneously rotates both the left and right handed lead screw portions **776L**, **776R** in a second rotation direction (opposite the first rotation direction) the fingers **210AF1**, **210AF2** move towards each other and towards the finger **210AF2** to decrease the distance **760A'**, **760B'** between fingers to distance **760A**, **760B** or decrease the distance **760A''**, **760B''** between the fingers to distance **760A'**, **760B'** or **760A**, **460B** or any other suitable distance. The distances **460A**, **760B**, **760A'**, **760B'**, **760A''**, **760B''** correspond with a size of a case unit to be picked/transferred (see FIGS. **8A-8C** where case units having a length/width of 6 inches, 14 inches

and 24 inches are illustrated but in other aspects the case units may have any suitable lengths/widths), a spacing between protrusions **620** of the justification tray **600** (FIGS. 7A and 7B), and/or a spacing between slats **900S** of case unit supports **900** (FIG. 9A) at a case unit holding location. As noted above, where a single actuator drives movement of the fingers **210AF1**, **210AF3** the distance **760A'** is substantially the same as distance **760B'** and the distance **760A''** is substantially the same as distance **760B''**; however, the distance **760A'** may be different than distance **760B'** and the distance **760A''** may be different than distance **760B''** where each finger **210AF1**, **210AF3** is driven by its own respective actuator. In some aspects, the finger **210AF2** may also be driven along the finger support rail **273** in direction LON.

(72) As may be realized, any suitable guide rails/slides **850** (FIG. 8A, 8B) are included with the linear actuator **776** along which the fingers **210AF1**, **210AF3** travel so that the fingers **210AF1**, **210AF3** are maintained in a predetermined orientation relative to the payload bed **210B** and the fingers **210AF2** so as to define, with the finger **210AF2**, a case unit support plane CUSP. The case unit support plane CUSP being substantially parallel/coplanar with a case unit support plane CUSPH defined by the case unit supports **900** at a case unit holding location (FIG. 9A).

(73) In one or more aspects, the actuator **776** and the finger **210AF2** are coupled to a carriage **773** so that the actuator **776** (and fingers **210AF1**, **210AF3** coupled thereto) and finger **210AF2** move in direction LON along rail(s) **774** under impetus of actuator **775** (e.g., actuator moves the fingers **210AF1**, **210AF2**, **210AF3** and the actuator **776** in direction LON). The actuator **775** may be substantially similar to actuator **776** described herein. Here, the fingers **210AF1**, **210AF2**, **210AF3** move as a unit in direction LON so as to be positioned underneath (so as to underpick) payloads CU and transport the payloads CU that have been justified in direction LON anywhere within the payload bed **210B** (such as by justification bars **222**, **223** as described herein). The carriage **773** is sized to provide for longitudinal movement of the fingers as described herein and so that the fingers can be positioned anywhere within the payload bed **210B** in direction LON and arranged relative to each other so as to pick any suitable size payload CU. In one or more aspects, the carriage **773** may be a telescoping carriage having telescoping sections **773TS** that extend and retract to provide the range of motion of the outboard fingers **210AF1**, **210AF3** described herein, while allowing the fingers **210AF1**, **210AF2**, **21AF3** to move together in direction LON as a single unit. In one aspect, the telescoping sections **773TS** of the carriage **773** may be extended and retracted in a manner substantially similar to that of the fingers illustrated in and described with respect to FIGS. 9A-10D; while in other aspects, the telescoping sections **773TS** may be extended and retracted in any suitable manner so as to provide the range of motion (described herein) of the outboard fingers of the transfer arm **210A**. Moving the fingers **210AF1**, **210AF2**, **210AF3** together as a unit (such as with carriage **773**) in direction LON or moving each finger **210AF1**, **210AF2**, **210AF3** independently in direction LON provides for a justified pick/placement of payloads CU (e.g., a center justification or off-center justification) in the manner described herein, where the payloads CU are justified by the justification bars **222**, **223**.

(74) In FIGS. 7A and 7B each finger **210AF1**, **210AF2**, **210AF3** includes a product support **710** and a coupling **711** that couples the product support to the finger support rail **273**. In FIGS. 7A and 7B the couplings **711** of the fingers **210AF1**, **210AF2**, **210AF3** are substantially parallel with each other, however in other aspects, the coupling **711** of one or more fingers **210AF1**, **210AF2**, **210AF3** is angled with respect to another coupling of another of the fingers **210AF1**, **210AF2**, **210AF3** as shown in FIGS. 8A-8C. In the example shown in FIGS. 8A-8C, the couplings **711G1**, **711F3** of the fingers **210AF1**, **201AF3** are angled towards each other and the coupling **711F2** of finger **210AF2**. This coupling configuration decreases the distance between the couplings at the connection between the fingers **210AF1**, **210AF2**, **210AF3** and the finger support rail **273**, which in turn provides for a more compact linear actuator **776** and reduced weight/cost associated with such linear actuator **776**. The movement of one or more of the fingers **210AF1**, **210AF2**, **210AF3** in direction LON also substantially prevents interference of the fingers **210AF1**, **210AF2**, **210AF3**

with case units CU held at locations adjacent (e.g., neighboring case units) at a predetermined case unit holding location to/from which a case unit is to be placed/picked by the bot **110**.

(75) Referring to FIGS. **9A-9C**, in one or more aspects the transfer arm **210A** includes reconfigurable finger segments **210S1-210S7** which are each substantially similar to fingers **210AF** described herein unless otherwise noted. The finger segments **210S1-210S7** are reconfigurable through operation of the linear actuator to change/reconfigure the number of fingers **210AF1-210AF7** the transfer arm **210A** has. For example, in the aspects illustrated in FIGS. **9A-9C** the finger segments **210S1-210S3** and **210S5-210S7** are movable in direction LON in a manner similar to that described above so as to increase or decrease the number of fingers. In FIG. **9A** the transfer arm **210A** is illustrated as having three fingers **210AF1-210AF3**. Here finger segments **210S1-210S7** are disposed in segment groups so as to form finger **210AF1** (formed by finger segments **210S1, 210S2**), finger **210AF2** (formed by finger segments **210S3, 210S4, 210S5**), and finger **210AF3** (formed by finger segments **210S6, 210S7**). In FIG. **9B** the transfer arm **210A** is illustrated as having five fingers **210AF1-210AF5** where finger segments **210S1-210S7** are disposed in segment groups so as to form finger **210AF1** (formed by finger segment **210S1**), finger **210AF2** (formed by finger segments **210S2**), finger **210AF3** (formed by finger segments **210S3, 210S4, 210S5**), finger **210AF4** (formed by finger segment **210S6**), and finger **210AF5** (formed by finger segments **210S7**). In FIG. **9C** the transfer arm **210A** is illustrated as having seven fingers **210AF1-210AF7** (although in other aspects more or less than seven fingers may be provided) where finger segments **210S1-210S7** are disposed so that each finger segment **210S1-210S7** forms a respective finger **210AF1-210AF7**.

(76) In a manner similar to that described above, the finger segment **210S4** is stationarily fixed at a predetermined location on the finger support rail **273** (e.g., does not move relative to the finger support rail **273**) such as at or along a laterally extending centerline **777** of the payload bed **210B**. The other finger segments **210S1-210S3, 210S5-210S7** are movable along the finger support rail **273** in direction LON so as to place fingers **210AF1-210AF3** in FIG. **9A**, fingers **210AF1-210AF5** in FIG. **9B**, and fingers **210AF1-210AF7** in FIG. **9C** at a respective distance **760A, 760B, 760A', 460B', 760A'', 760B''** relative to stationary finger segment **210S4**; however, in other aspects the distance between adjacent finger segments may be any suitable distance that places the finger segments in spaces between slats **900S** of the case unit supports **900** of a case unit holding location.

(77) The movement of the finger segments **210S1-210S7** is effected in a manner similar to that described above with respect to FIGS. **7A-8C** where finger segments **210S1** and **210S7** are coupled to, for example, a respective one of the left and right lead screws **776L, 776R**. The movement of the finger segments **210S2, 210S3** in direction LON is slaved to the movement of finger segment **210S1** and the movement of the finger segments **210S5, 210S6** in the direction LON is slaved to the movement of finger segment **210S7**. For example, finger segments **210S2, 210S3** are coupled to each other through a rigid link **920** so that the distance between the finger segments **210S2, 210S3** in direction LON is fixed (e.g., does not change). A slotted link **921** is coupled to the finger segment **210S2**, where the slotted link **921** includes a slot **921S** in which at least a portion of the finger segment **210S1** reciprocates in direction LON. Finger segments **210S5, 210S6** are coupled to each other through a rigid link **922** so that the distance between the finger segments **210S5, 210S6** in direction LON is fixed (e.g., does not change). A slotted link **923** is coupled to the finger segment **210S6**, where the slotted link **923** includes a slot **923S** in which at least a portion of the finger segment **210S7** reciprocates in direction LON. While links **920, 921** are described as being distinct links, in other aspects the links **920, 921** may be formed as a single one piece link that sets the distance between and couples finger segments **210S2, 210S3** and forms the slot **921S** along which finger segment **210S1** reciprocates. Similarly, while links **922, 923** are described as being distinct links, in other aspects the links **922, 923** may be formed as a single one piece link that sets the distance between and couples finger segments **210S5, 210S6** and forms the slot **923S** along which finger segment **210S7** reciprocates. As noted above, more than seven fingers can be

provided, such that any suitable number of slaved fingers may be included on the transfer arm **210A** and operate in a telescoping manner substantially similar to that describe herein.

(78) Referring to FIGS. **9A-9C** in sequence, FIG. **9A** illustrates the finger segments **210S1-210S7** in a contracted configuration where finger segment **210S1** substantially abuts against finger segment **210S2**, finger segments **210S3**, **210S5** each are substantially abutted against finger segment **210S4**, and finger segment **210S7** substantially abuts against finger segment **210S6**. Linear actuator **776** is operated to simultaneously move the finger segment **210S7** in direction LON towards end **210BE2** (see FIG. **7A**) of the payload bed **210B** and move finger segment **210S1** in direction LON towards end **210BE1** of the payload bed **210B**. As can be seen in FIG. **9B**, movement of finger segment **210S1** towards end **210BE1** causes finger segment **210S1** to travel along the slot **921S** until the finger segment **210S1** reaches distance **760A'** so that finger segments **210S1**, **210S2** are separated and reconfigured as fingers **210AF1**, **210AF2**. One or more of the rigid link **920**, finger segment **210S2**, and finger segment **210S3** is/are held in place by any suitable detent (e.g., biased ball and recess, etc.) or any suitable biasing member (e.g., spring) during movement of finger **210S1** to distance **760A'**. Movement of finger segment **210S7** towards end **210BE2** causes finger segment **210S7** to travel along the slot **923S** until the finger segment **210S7** reaches distance **760B'** so that finger segments **210S6** and **210S7** are separated and reconfigured as fingers **210AF4**, **210AF5**. One or more of the rigid link **922**, finger segment **210S5**, and finger segment **210S6** is/are held in place by any suitable detent (e.g., biased ball and recess, etc.) or any suitable biasing member (e.g., spring) during movement of finger **210S7** to distance **760B'**. It is noted that finger segments **210S3-210S5** are reconfigured as finger **210AF3**.

(79) As can be seen in FIG. **9C**, further movement of finger **210S1** towards end **210BE1** in direction LON causes finger **210S1** to engage end **921SE** of slot **921S**. As finger segment **210S1** continues to move towards end **210BE1**, while engaged with end **921SE**, the finger segment **210S1** pulls finger segments **210S2**, **210S3** towards end **210BE1** by virtue of the links **921**, **920** (e.g., movement of the finger segments **210S2**, **210S3** are slaved to the movement of finger segment **210S1**). Here finger segments **210S1-210S3** are respectively reconfigured as fingers **210AF1-210AF3** and located at distances **760"**, **760A'**, **760A**. Similarly, further movement of finger segment **210S7** towards end **210BE2** in direction LON causes finger **210S7** to engage end **923SE** of slot **923S**. As finger segment **210S7** continues to move towards end **210BE2**, while engaged with end **923SE**, the finger segment **210S7** pulls finger segments **210S5**, **210S6** towards end **210BE2** by virtue of the links **922**, **923** (e.g., movement of the finger segments **210S5**, **210S6** are slaved to the movement of finger segment **210S1**). Here finger segments **210S1-210S3** are respectively reconfigured as fingers **210AF5-210AF7** and located at distances **760B**, **760B'**, **760B"**. It is noted that finger segment **210S4** is reconfigured as finger **210AF4**. As may be realized, reconfiguration of the finger segments from fingers **210AF1-210AF7** to fingers **210AF1-210AF5** and from **210AF1-210AF5** to **210AF1-210AF3** occurs in a substantially reverse manner to that described above, where a retracted movement of finger segments **210S1**, **210S7** causes finger segment **210S1** to substantially abut finger segment **210S2** and push finger segments **210S2**, **210S3** towards finger segment **210S4** and causes finger segment **210S7** to substantially abut finger segment **210S6** and push finger segments **210S5**, **210S6** towards finger segment **210S4**.

(80) Referring to FIGS. **10A-10D** in sequence, FIG. **10A** illustrates the finger segments **210S1-210S7** in a contracted configuration substantially similar to that of FIG. **9A** where finger segment **210S1** substantially abuts against finger segment **210S2**, finger segments **210S3**, **210S5** each are substantially abutted against finger segment **210S4**, and finger segment **210S7** substantially abuts against finger segment **210S6**. However, in the aspect illustrated in FIGS. **10A-10C** the respective coupling between the finger segment **210S1** and finger segment **210S2** and between finger segment **210S6** and finger segment **210S7** is an articulated link coupling **1010A**, **1010B**. For example, finger segment **210S1** is coupled to a rail **273R** of the finger support rail **273** by slide **1021**. Finger segments **210S2**, **210S3** are coupled to the rail **273R** by slide **1020** so that finger segments **210S2**,

210S3 are spaced a predetermined distance from each other in a manner substantially similar to that described with respect to FIGS. **9A-9C**. Finger segment **210S7** is coupled to a rail **273R** of the finger support rail **273** by slide **1023**. Finger segments **210S5**, **210S6** are coupled to the rail **273R** by slide **1022** so that finger segments **210S5**, **210S6** are spaced a predetermined distance from each other in a manner substantially similar to that described with respect to FIGS. **9A-9C**. The articulated link coupling **1010A** includes a first link **1011** and a second link **1012**. The first link **1011** is pivotally coupled at a proximate end to slide **1020** about axis **1010X1** (See FIG. **10D** with respect to articulated link coupling **1010B** which is substantially similar to articulated link coupling **1010A**). A proximate end of the second link **1012** is pivotally coupled to a distal end of the first link **1011** at axis **1010X**. A distal end of the second link **1012** is pivotally coupled to the slide **1021** about axis **1010X2** (see FIG. **10D** with respect to slide **1023**). The axis **1010X** is guided in movement so as to fold in a direction opposite the slides **1020**, **1021** by guide channel **1010C**. For example, the axis **1010X** includes a post or pin **1099** (see FIG. **10D**) that extends within and follows the guide channel **1010C** so that when folded guidance of the axis **1010X** along the channel **1010C** substantially prevents binding/locking of the first link **1011** and the second link **1012** and positions the axis **1010X** so that the first link **1011** and the second link **1012** are in an opposing spatial relationship with the finger segments **210S1**, **210S2**.

(81) Similarly, the articulated link coupling **1010B** includes a first link **1011** and a second link **1012**. The first link **1011** is pivotally coupled at a proximate end to slide **1022** about axis **1010X1**. A proximate end of the second link **1012** is pivotally coupled to a distal end of the first link **1011** at axis **1010X**. A distal end of the second link **1012** is pivotally coupled to the slide **1023** about axis **1010X2**. The axis **1010X** is guided in movement so as to fold in a direction opposite the slides **1020**, **1021** by guide channel **1010C**. For example, the axis **1010X** includes a post or pin **1099** (FIG. **10D**) that extends within and follows the guide channel **1010C** so that when folded guidance of the axis **1010X** along the channel **1010C** substantially prevents binding/locking of the first link **1011** and the second link **1012** and positions the axis **1010X** so that the first link **1011** and the second link **1012** are in an opposing spatial relationship with the finger segments **210S6**, **210S7**.

(82) In a manner similar to that described above, the finger segments **210A1**, **210S7** are simultaneously opposingly driven along the finger support rail **273** in direction LON so as to move towards and away from each other. For example, linear actuator **776** is operated to simultaneously move the finger segment **210S7** in direction LON towards end **210BE2** (see FIG. **7A**) of the payload bed **210B** and move finger segment **210S1** in direction LON towards end **210BE1** of the payload bed **210B**. As can be seen in FIG. **10B**, movement of the finger segment **210S1** (and the slide **1021** to which the finger segment **210S1** coupled) towards end **210BE1** causes the finger segment **210S1** to travel along the rail **273** (e.g., unfolding the first link **1011** and the second link **1012**, of the articulated link coupling **1010A**, relative to each other) until the finger segment **210S1** reaches the distance **760A'** so that finger segments **210S1**, **210S2** are separated and reconfigured as fingers **210AF1**, **210AF2**. One or more of the slide **1020** to which finger segments **210S2**, **210S3** are coupled, finger segment **210S2**, and finger segment **210S3** is/are held in place by any suitable detent (e.g., biased ball and recess, etc.) during movement of finger segment **210S1** to distance **760A'**. Movement of finger segment **210S7** (and the slide **1023** to which it is coupled) towards end **210BE2** causes finger segment **210S7** to travel along the rail **273** (e.g., unfolding the first link **1011** and the second link **1012**, of the articulated link coupling **1010A**, relative to each other) until the finger segment **210S7** reaches distance **760B'** so that finger segments **210S6** and **210S7** are separated and reconfigured as fingers **210AF4**, **210AF5**. One or more of the slide **1022** to which the finger segments **210S5**, **210S6** are coupled, finger segment **210S5**, and finger segment **210S6** is/are held in place by any suitable detent (e.g., biased ball and recess, etc.) during movement of finger **210S7** to distance **760B'**. It is noted that finger segments **210S3-210S5** are reconfigured as finger **210AF3**.

(83) As can be seen in FIG. **10C**, further movement of finger **210S1** towards end **210BE1** in

direction LON causes finger **210S1**/slide **1021** to pull the slide **1020** (and finger segments **210S2**, **210S3** coupled thereto) towards end **210BE1** by virtue of the unfolded articulated link coupling **1010A** (e.g., movement of the finger segments **210S2**, **210S3** are slaved to the movement of finger segment **210S1**). Here finger segments **210S1-210S3** are respectively reconfigured as fingers **210AF1-210AF3** and located at distances **760"**, **760A'**, **760A**. Similarly, further movement of finger **210S7** towards end **210BE2** in direction LON causes finger segment **210S7**/slide **1023** towards end **210BE2** to pull slide **1022** (and finger segments **210S5**, **210S6** coupled thereto) towards end **210BE2** by virtue of the unfolded articulated link coupling **1010B** (e.g., movement of the finger segments **210S5**, **210S6** are slaved to the movement of finger segment **210S1**). Here finger segments **210S1-210S3** are respectively reconfigured as fingers **210AF5-210AF7** and located at distances **760B**, **760B'**, **760B"**. It is noted that finger segment **210S4** is reconfigured as finger **210AF4**. As may be realized, reconfiguration of the finger segments from fingers **210AF1-210AF7** to fingers **210AF1-210AF5** and from **210AF1-210AF5** to **210AF1-210AF3** occurs in a substantially reverse manner to that described above, where a retracted movement of finger segments **210S1**, **210S7** causes finger segment **210S1** to substantially abut finger segment **210S2** and push finger segments **210S2**, **210S3** towards finger segment **210S4** and causes finger segment **210S7** to substantially abut finger segment **210S6** and push finger segments **210S5**, **210S6** towards finger segment **210S4**.

(84) Referring to FIGS. 2A, 2B, 2E, 2F, 7A, and 7B, in one or more aspects the case handling assembly **210** includes case unit justification. Here at least one justification bar **222**, **223** is movably coupled to the payload bed frame **210B** in any suitable manner so that the at least one justification bar **222**, **223** moves in direction LON to position case unit CU in a predetermined location within the payload bed **210B** relative to the longitudinal axis LAX of the bot **110**. In the example illustrated there are two justification bars **222**, **223**, both of which move in the direction LON so as to at least move towards and away from each other; however, in other aspects one of the justification bars **222**, **223** is stationarily fixed in direction LON while the other justification bar **222**, **223** moves in direction LON towards and away from the stationarily fixed justification bar **222**, **223**. As described herein, the justification bars **222**, **223** may be independently driven. Independently driving each justification bar **222**, **223** provides for justification of case units at any position within the payload bay **210B**. The case unit CU can be positioned off center (e.g., relative to a centerline of the payload bed **210B** in direction LAT). Positioning a case unit CU off center in the payload bay **210B** provides for a continuous equal gap between cases units on a storage shelf, which improves storage density.

(85) In one or more aspects, the justification bars **222**, **223** are coupled to one or more linear guide rails **225** of the payload bed frame **210BF**. The justification bars **222**, **223** are coupled to any suitable drive motor(s) **226** and transmission(s) **227** which in one aspect is/are similar to the drive motor **275** and transmission **276** that drives the movable finger segments described herein. For example, in one or more aspects a single drive motor **226** drives movement of both the justification bars **222**, **223** where the drive motor **226** is a stepper motor or any other suitable motor coupled to a lead screw in a manner similar to that described above with respect to the finger segments. Here one end of the lead screw (e.g., transmission **227**) has right hand threads and the other end of the lead screw has left hand threads. Each justification bar **222**, **223** includes a nut that engages a respective one of the right hand threads and left hand threads of the lead screw so that as the drive motor **275** turns the lead screw in a first rotation direction the justification bars **222**, **223** move towards each other (and towards a longitudinal centerline CL of the payload bed **210B**) and as the drive motor **275** turns the lead screw in a second opposite rotation direction (i.e., opposite the first rotation direction) justification bars **222**, **223** move away from each other (e.g., justification bar **222** moves towards end **200BE1** of the payload bed **210B** and justification bar **223** moves towards end **200BE2** of the payload bed **210B**). Here both justification bars **222**, **223** are driven by the a single (i.e., the same) drive motor **226** and transmission **227** (the drive motor and transmission are

common to both justification bars **222, 223**); however, in other aspects, the bot **110** includes two drive motors **226** and at least one transmissions **227** (i.e., a transmission for each justification bar **222, 223** or a common (i.e., one) transmission for each justification bar **222, 223**) so each justification bar **222, 223** is driven by a respective motor and transmission to move in direction LON independent of movement of the other justification bar **222, 223** (here justification of cases unit is not limited to a “center justification” relative to the centerline CL of the payload bed, instead the case units can be justified to any location between the ends **210BE1, 210BE2** of the payload bed **210B**).

(86) FIGS. 2E and 2F illustrate an example of employing two drive motors **226** to independently move each justification bar **222, 223** in direction LON so as to justify payloads CU anywhere along direction LON within the payload bed **210B**. In this example, each justification bar **222, 223** includes a respective motor **226** that is coupled to a common stationary transmission **227**. Here the transmission **227** is a flexible transmission similar to flexible transmission **330** described herein. One end of the transmission **227** is fixedly coupled to the end **210BE1** of the frame **210BF** of the payload bed **210B** in any suitable manner (e.g., clamp, removable fastener, clip, etc.). The opposite end of the transmission **227** is fixedly coupled to the opposite end **210BE2** of the frame **210BF** of the payload bed **210B** in any suitable manner (e.g., clamp, removable fastener, clip, etc.). The justification bar **222** includes motor **226** that is mounted to and carried by the justification bar **222** in any suitable manner. The justification bar **222** also includes a drive pulley **226P3** that is coupled to and driven by the motor **226**. An idler pulley **226P4** is coupled to the justification bar **222** below the drive pulley **226P3** and is positioned relative to the justification tray **600** so as to at least partially extend below the payload support plane **610P** of the payload bay **210B**. The justification bar **223** is similarly configured such that justification bar **223** includes the motor **226** that is mounted to and carried by the justification bar **223** in any suitable manner, a drive pulley **226P1** is coupled to and driven by the motor **226**, and an idler pulley **226P2** is coupled to the justification bar **223** below the drive pulley **226P1** and is positioned relative to the justification tray **600** so as to at least partially extend below the payload support plane **610P** of the payload bay **210B**.

(87) The flexible transmission is wrapped around the pulleys **226P1, 226P2** and the pulleys **226P3, 226P4** in a serpentine manner so that a portion **227P** of the transmission **227** extends beneath the payload support plane **610P** of the payload bay **210B**. The serpentine arrangement of the transmission **227** around pulleys **226P1, 226P2** also provides for engagement of the drive pulley **226P1** with the transmission **227** so that as the motor **226** (of justification bar **223**) rotates the drive pulley **226P1** the justification bar **223** moves in direction LON independent of movement of justification bar **222**. Similarly, the serpentine arrangement of the transmission **227** around pulleys **226P3, 226P4** provides for engagement of the drive pulley **226P3** with the transmission **227** so that as the motor **226** (of justification bar **222**) rotates the drive pulley **226P3** the justification bar **222** moves in direction LON independent of movement of justification bar **223**.

(88) Justification of the case units CU on the payload bed **210B** in the direction LON provides for a known location of the case units CU on the bot **110** that effects placement of case units CU at predetermined locations at case unit holding locations. Justification of one or more case units CU is performed by the at least one justification bar **222, 223** with the one or more case units CU held on (supported by) the fingers **210AF** of the transfer arm **210A** or with the one or more case units CU held on (supported by) the justification tray **600**. In one or more aspects, the justification tray **600** includes channels **677, 678** that provide a running clearance in direction LON for the coupling between the at least one justification bar **222, 223** and the linear guide rail **225** (and transmission **276** coupling to the at least one justification bar **222, 223**). While the at least one linear guide rail **225** is illustrated as being substantially centered in the payload bed **210B** and extending in direction LON, in other aspects, the at least one linear guide rail **225** is positioned in any suitable location in the payload bed **210B** and/or on the transfer arm **210A** for providing movement of the justification

bars **222**, **223** in direction LON. In one or more aspects, at least a portion of the justification bars **222**, **223** is moveable in direction LAT so as to extend at least partially out of an area bounded by the payload bed **210B**.

(89) Here, the independent movement of the justification bars **222**, **223** provides for justification of payloads CU at any position along direction LON within the payload bed to, for example, provide for a continuous equal gap between cases units on a storage shelf, which improves storage density. As described above, the underpick end effector or transfer arm **210A** is employed with the justification bars **222**, **223** to transfer payloads CU to and from the payload bed **210B** at a justified (e.g., in direction LON) position. In one aspect the fingers **210AF** of the transfer arm **210A** may be retracted into the payload bed **210B** with a payload CU thereon so as to roughly position the payload CU in a predetermined justification position in direction LON. The retract movement of the fingers **210AF** and payload CU thereon may be a compound movement in both directions LON and LAT so that the payload CU may be registered in the two degrees of registration substantially coincident with seating of the payload CU in the payload bed **210B** and substantially coincident upon completion of the transfer arm **210A** retract movement (as described herein). In one or more aspects, the support surface **210AFS** of the fingers **210AF** form a support plane on which the payload CU is registered with two degrees of registration, where the justification bars **222**, **223**, pushers **1150**, and/or tabs **1250** with the fingers **210AF** effect the registration of the payload CU in the two degrees of registration. With the payload CU seated in the payload bed **210B** (e.g., seated on the fingers **210AF** or on the justification tray **600**) the justification bars **222**, **223** may be independently moved to fine tune the justification position of the payload relative to the fingers **210AF** and the storage locations **130S** or other holding location) so that upon placement of the payload CU by the vehicle **110** at a storage space **130S**, (or other holding location) a spacing between side by side payloads in the storage spaces **130S** may be maintained at a minimum (equal spacing to increase storage density as described herein).

(90) Referring to FIGS. **11A-11C** and **12A-12H** each justification bar **222**, **223** includes a case pusher assembly **1110** and a case puller assembly **1120**. The case pusher assembly **1110** and case puller assembly **1120** will be described with respect to justification bar **222** noting that the case pusher assembly **1110** and case puller assembly **1120** of justification bar **223** are substantially similar. Here the justification bar **222** includes slots **1130**, **1131** disposed one above the other and extending in direction LAT along the justification bar **222**. In FIG. **11A** the pusher assembly **1110** is associated with the slot **1130** and the puller assembly **1120** is associated with the slot **1131**; however, in other aspects, such as illustrated in FIG. **12A**, the pusher assembly **1110** is associated with the slot **1131** and the puller assembly **1120** is associated with the slot **1130**. The case pusher assembly **1110** and the case puller assembly **1120** are, in one or more aspects, used in combination to grip case units transported by the bot **110**. In one or more aspects, one or more of the case pusher assembly **1110** and the case puller assembly **1120** are employed for justification of case units CU in direction LAT where the case units are supported by the fingers **210AF** and/or justification tray **600**. The case puller assembly **1120** is employed for pulling case units CU into the payload bed **210B** to substantially prevent case unit overhang (e.g., a portion of a case unit extends outside of the payload bed **210B** through the transfer opening **1199** of the payload bed **210B**).

(91) The pusher assembly **1110** includes any suitable linear actuator **1210** (e.g., lead screw drive, belt drive, piston, etc. driven by any suitable actuator such as stepper motor, servo motor, pneumatics, hydraulics, etc.) (see FIGS. **12A**, **12B**), a slider **1211** (see FIGS. **12A**, **12B**) coupled to the linear actuator **1210**, and a pusher arm or tab **1150** coupled to the slider **1211** through the slot **1131** (or **1130** depending on whether the pusher assembly is associated with slot **1131** or slot **1130**). The linear actuator **1210** is configured to move the slider **1211** in direction LAT along the channel or slot **1131** in any suitable manner. The pusher arm **1150** is coupled to the slider **1211** with any suitable mechanical or chemical fasteners (or is integrally formed with the slider **1211**) and is configured with a case interface surface **1150S** that contacts a side of a case unit CU for pushing

the case unit towards a transfer opening **1199** of the payload bed **210B** through which case units CU pass for transfer to and from the payload bed **210B**.

(92) The puller assembly **1120** includes any suitable linear actuator **1225** (e.g., lead screw drive, belt drive, piston, etc. driven by any suitable actuator such as stepper motor, servo motor, pneumatics, hydraulics, etc.), a rotating slider assembly **1230** coupled to the linear actuator **1225**, and a pusher arm or tab **1250** coupled to the rotating slider assembly **1230**. The linear actuator **1210** is configured to move the rotating slider assembly **1230** in direction LAT along the slot **1131** in any suitable manner. The rotating slider assembly **1230** includes a non-rotating plug **1231** and a rotating carrier **1232**. A puller arm or tab **1250** is coupled to the rotating carrier **1232** as described herein. The non-rotating plug **1231** is configured to linearly slide in direction LAT, within a channel **1277** of the justification bar **222**, under impetus of the linear actuator **1225**. For example, the non-rotating plug **1231** includes a channel engagement portion **1233** that includes one or more riding surfaces **1233S** (four are shown for exemplary purposes but in other aspects there are more or less than four riding surfaces—such as one surface illustrated in FIG. **12E**) and an anti-rotation tab **1234** that is configured to extend at least partially through the slot **1130** (or slot **1131** depending on which slot **1130**, **1131** the rotating slider assembly **1230** is associated with). Engagement between the slot **1130** and the anti-rotation tab **1234** prevents rotation of the non-rotating plug **1231** within the channel **1277** in direction **1291** about rotation axis **1290**. The non-rotating plug **1231** also includes a carrier engagement portion **1235** configured to interface with the rotating carrier **1232** so as to effect rotation of the rotating carrier **1232** in direction **1291** and linear movement of the rotating carrier **1232** in direction LAT within the channel **1277**, where both the rotation and linear movement of the rotating carrier **1232** (and tab **1250** coupled thereto) is driven by a single motor/linear actuator **1225**. The non-rotating plug **1231** is coupled (e.g., with mechanical and/or chemical fasteners) to the linear actuator **1225** in any suitable manner (such as coupled to one side of a belt/chain loop of the linear actuator **1225**, coupled to an actuating rod/screw of the linear actuator, coupled to a magnetic driven member of the linear actuator **1225**, etc.) for reciprocating sliding movement in direction LAT along the channel **1277**.

(93) The rotating carrier **1232** includes a tab mount portion **1260** and a cam portion **1261** coupled to (or integrally formed therewith) the tab mount portion **1260**. The tab mount portion **1260** is shaped and sized to as to slide or otherwise pass within the channel **1277**. The tab **1250** is coupled to the tab mount portion **1260** at coupling **1262** so that the tab **1250** extends away from and is cantilevered from the tab mount portion **1260**. The cam portion **1261** is a cylindrical tube having an aperture **1263** into which the carrier engagement portion **1235** of the non-rotating plug **1231** is inserted for reciprocal movement within the aperture **1263**. While the cam portion **1260** is illustrated as having the aperture **1263** into which the carrier engagement portion **1235** of the non-rotating plug **1231** is inserted, in other aspects, the carrier engagement portion **1235** includes the aperture and the cam portion **1261** is inserted into the carrier engagement portion **1235**.

(94) In the aspect illustrated in FIG. **12D**, the surface of the aperture **1263** includes one or more protrusions **1263P** that extend radially inward (e.g., towards rotation axis **1290**). The protrusions **1263P** form cam surfaces that engage corresponding recesses **1235R** of the carrier engagement portion **1235**. Here protrusions spirally extend along the length of the aperture **1263** and around the rotation axis **1290**. The mating recesses **1235R** spirally extend around the carrier engagement portion **1235** and around the rotation axis **1290** so as to engage or otherwise mate with the protrusions **1263P**. The protrusions **1263P** and recesses **1235R** are configured so that movement of the non-rotating plug **1231** in direction LAT1 (so that a portion of the carrier engagement portion **1235** outside of the aperture **1263** increases) by a predetermined distance (e.g., with the non-rotating plug held from movement in direction LAT1) causes, via camming action of the engaged protrusions **1263P** and recesses **1235R**, rotation of the tab **1250** in direction **1291** about rotation axis **1290** by an angle α as illustrated by a comparison between FIGS. **12A** and **12B**. In one or more aspects the angle α is about 90° while in other aspects the angle α is more or less than about 90° . As

may be realized, the protrusions **1263P** and recesses **1235R** are configured so that movement of the non-rotating plug **1231** in opposite direction **LAT2** (so that a portion of the carrier engagement portion **1235** outside of the aperture **1263** decreases) by the predetermined distance (e.g., with the non-rotating plug held from movement in direction **LAT2**) causes, via camming action of the engaged protrusions **1263P** and recesses **1235R**, an opposite rotation of the tab **1250** in direction **1291** about rotation axis **1290** by the angle α .

(95) To effect rotation of the rotating carrier **1232** relative to the non-rotating plug **1231** (which is held from rotation by engagement of anti-rotation tab **1234** and slot **1130**), the rotating carrier **1232** is held stationary in direction **LAT** at least in part by stop surfaces **1260S1**, **1260S2** of the rotating carrier **1232**. The stop surfaces **1260S1**, **1260S2** extend from the rotating carrier **1232** so as to engage a respective one of stop surfaces **1268**, **1269** of the channel **1277**. For example, the channel **1277** includes a slot or aperture **1270** disposed adjacent an end **222E**, **223E** of the justification bar **222** (and **223**) closest the transfer opening **1199** of the payload bed **210B**. The slot **1270** intersects slot **1130**. Here, movement of the non-rotating plug **1231** in direction **LAT1** under impetus of linear actuator **1225** causes rotation the stop surfaces **1260S1**, **1260S2** (and tab **1250** of the rotating carrier **1232**) towards the slot **1130** in direction **1291A** (via camming engagement of the one or more protrusions **1263P** and the corresponding recesses **1235R**) where the rotating carrier **1232** is held from movement in direction **LAT1** by engagement of stop surface **1260S1** of the rotating carrier **1232** with stop surface **1269** of the channel **1277**. Continued rotation of the rotating carrier **1232** effected by movement of the non-rotating plug **1231** in direction **LAT1** causes disengagement of the stop surfaces **1260S1**, **1269** and alignment of stop surfaces **1260S1**, **1260S2** with slot **1130**. With the stop surfaces **1260S1**, **1260S2** aligned with slot **1130**, rotation of the rotating carrier **1232** is arrested (via abutting contact between stop surfaces **1260S1**, **1260S2** with side **1130S1** of slot **1130**) and the rotating carrier **1232** moves with the non-rotating plug **1231** in direction **LAT1**. It is noted that with the rotation of the rotating carrier **1232** arrested by the slot **1130** the cammed engagement between the one or more protrusions **1263P** and the corresponding recesses **1235R** become locked effecting movement of the non-rotating plug **1231** and the rotating carrier **1232** as a unit in direction **LAT**.

(96) To effect rotation of the stop surfaces **1260S1**, **1260S2** (and tab **1250** of the rotating carrier **1232**) in direction **1291B**, the linear actuator **1255** moves the non-rotating plug **1231** (and rotating carrier **1232**) in direction **LAT2** so that stop surfaces **1260S1**, **1260S2** move into the slot **1270** (and are disengaged from the sides **1130S1**, **1130S2** of the slot **1130**) and stop surface **1260S2** engages stop surface **1268** of the slot **1270**. Engagement of stop surfaces **1260S2**, **1268** stop movement of the rotating carrier **1232** in direction **LAT2** while disengagement of stop surfaces **1260S1**, **1260S2** from the side **1130S2** of the slot **1130** allows rotation of the rotating carrier **1232** in direction **1291B**. With the stop surfaces **1260S2**, **1268** engaged and with the disengagement of stop surfaces **1260S1**, **1260S2** from the sides **1130S2** of the slot **1130**, further movement of the non-rotating plug **1231** in direction **LAT2** under impetus of the linear actuator **1225** causes (via camming engagement of the one or more protrusions **1263P** and the corresponding recesses **1235R**) rotation of the stop surfaces **1260S1**, **1260S2** (and tab **1250** of the rotating carrier **1232**) away from the slot **1130** in direction **1291B** by the angle α . As will be described herein, rotation of the tab **1250** from what may referred to as a retracted position (shown in FIGS. 2B, 11A, 12A and 12E) to what may be referred to as an extended position (shown in FIGS. 2A, 11B, 12B, 12C, 12G, and 12H) orients the tabs **1250** of the justification bars **222**, **223** for case unit engagement for pulling case units held in the payload bed **210B** in direction **LAT1** (FIGS. 2A and 11A).

(97) Referring to FIGS. 12E-12H, a portion of the puller assembly **1120** is illustrated in accordance with an aspect of the disclosed embodiment. What is illustrated in FIGS. 12E-12H is substantially similar to that described above with respect to FIGS. 12A-12D except where noted. In FIGS. 12A-12D the rotating slider assembly **1230** is configured so that the retracted configuration of the tab **1250** is with the tab **1250** extending towards a vehicle riding surface **VRS** of the transfer deck

130B or picking aisle **130A** (e.g., in direction **VERB**) whereas the retracted configuration of the tab **1250** in FIGS. **12A-12D** is with the tab **1250** extending away from the vehicle riding surface **VRS** of the transfer deck **130B** or picking aisle **130A** (e.g., in direction **VERA**); however, in other aspects the rotating slider assembly **1230** is configured retracted position of the tab **1250** at any suitable position that provides for substantially unhindered passage of case units through the transfer opening **1199** (see, e.g., FIG. **11A**) and the tab **1250** is rotated through any suitable rotation angle α that orients the tab **1250** for engagement with case units **CU** as described herein.

(98) In FIGS. **12E-12H** at least one of the stop surfaces **1260S1**, **1260S2** is integrated into the tab **1250**. The stop surface **1260S1**, **1260S2** as well as the minor of the tab **1250** engage the surfaces **1268**, **1269**, and sides **1130S1**, **1130S2** of the slot **1130** in a manner similar to that described above, noting that the stop surfaces **1260S1**, **1260S2** include both the major surfaces of the tab **1250** for engaging surfaces **1268**, **1269** of slot **1270** as well as minor surfaces of the tab **1250** for engaging sides **1130S1**, **1130S2** of slot **1130**. In the aspect shown in FIGS. **12E-12H**, the configuration of the cammed engagement between the non-rotating plug **1231** and the rotating carrier **1232** is in the form of at least one slot **1286** and at least one pin or post **1287**. Here the cam portion **1261** includes at least one cammed slot **1286** and the carrier engagement portion **1235** includes at least one pin **1287** that engages the at least one slot **1286**. In the aspect illustrated there are two cammed slots **1286** and two respective pins **1287**; however, in other aspects there may be one or more than two respective sets of cammed slots **1286** and pins **1287**. As the non-rotating plug **1231** is moved in direction **LAT1** the rotating carrier **1232** is held from movement in direction **LAT1** by engagement of at least one of the stop surfaces **1260S1**, **1269** in a manner similar to that described above.

Movement of non-rotating plug **1231** in direction **LAT1** causes relative movement of the at least one pin **1287** relative to the at least one slot **1286** effecting rotation of the tab **1250** and rotating carrier **1232** in direction **1291** until rotation of the tab **1250** is arrested through engagement of one or more of the stop surfaces **1260S1**, **1260S2** with one or more of the sides **1130S1**, **1130S2** of the slot **1130** in a manner similar to that described above. When stop surfaces **1260S1**, **1260S2** are aligned with slot **1130** and rotation of the rotating carrier **1232** is arrested, the cammed engagement of the at least one pin **1287** and the at least one slot **1286** is locked and the rotating carrier **1232** and non-rotating plug **1231** move in direction **LAT1** as a unit under impetus of the linear actuator **1225**.

(99) In one or more aspects, the at least one slot **1286** is configured such that engagement of the at least one pin **1287** with an end **1286E** of the at least one slot **1286** locks cammed engagement of the at least one pin and slot and arrests rotation of the tab **1250** and rotating carrier **1232**. In still other aspects, at least one stop surface **1260S1'**, **1260S2'** for holding movement of the rotating carrier **1232** in direction **LAT** is integral with the cam portion **1261** and/or tab mount portion **1260**. For example, the tab mount portion **1260** includes a protrusion or stop surface **1260S1'** substantially in-line with the tab **1250** that extends past the perimeter of the channel **1277** and engages outer surface **1293** of the justification bar so as to hold the rotating carrier **1232** from movement in direction **LAT1** as the non-rotating plug **1231** moves in direction **LAT1** and tab **1250** rotates in direction **1291B**. When the stop surface **1260S1** (and tab **1250**) is aligned with the slot **1130** the rotating carrier **1232** moves in direction **LAT1** with the non-rotating plug **1231** as described herein (noting rotation between the rotating carrier **1232** and non-rotating plug **1231** locked by engagement of pin **1287** with end **1286E** of cammed slot **1286**). Stop surface **1260S2'** for holding movement of the rotating carrier **1232** in direction **LAT2** is integral with the cam portion **1261** and engages an interior surface of channel **1277** (e.g., such as an end cap **1293C** that forms surface **1293** that extends inward past the bounds of the channel **1277** (see FIG. **12H**) to keep the cam portion **1261** from moving out of the channel **1277** (though tab mount portion **1260** extends from the channel **1277**) in direction **LAT2**.

(100) In one or more aspects, the rotating carrier **1232** is held from movement in direction **LAT1** by a detent mechanism **1222** (e.g., biased ball or plate) that engages a portion of the rotating carrier **1232** (such as shoulder **1223**) where the engagement of the detent mechanism with the rotating

carrier **1232** provides for rotation of the rotating carrier **1232** about axis **1290** while substantially preventing linear movement of the rotating carrier **1232** with the non-rotating plug **1231** in direction **LAT1**. With locking of the cammed engagement of the at least one pin **1287** and at least one slot **1286** (or cammed engagement of the at least one protrusion **1263P** and at least one recess **1235R**) the linear actuator **1225** overcomes the bias force of the detent mechanism **1222** for moving the rotating carrier **1232** in direction **LAT1**.

(101) An exemplary illustration of the tab **1250** rotation and linear movement described above is illustrated in FIGS. **11A-11C**. The justification bars **222, 223** are moved towards each other in direction **LON** so as to substantially contact case unit(s) **CU** held at least partially within the payload bed **210B**. As can be seen in FIG. **11A** the tabs **1250** of each respective justification bar **222, 223** are rotated in direction **1291** (e.g., through relative movement between the non-rotating plug **1231** and rotating carrier **1232** effected by the respective linear actuator **1225**) about a respective rotation axis **1290** from the retracted position (FIG. **11A**) to the extended position (FIG. **11B**). The linear actuator **1225** of each respective justification bar **222, 223** continues to operate so that the non-rotating plug **1231** and rotating carrier **1232** (e.g., the rotating slider assembly **1230**) are moved as a unit in direction **LAT1** to pull case units into the payload bed **210B**. Movement of the rotating slider assembly in direction **LAT2** and rotation of the tabs **1250** from the extended position to the retracted position occurs in a substantially opposite manner.

(102) Referring to FIGS. **13A-13F**, in one or more aspects, the puller assembly **1120** is substantially similar to that describe above; however, instead of the rotating slider assembly **1230** the puller assembly includes sliding rack assembly **1320**. The sliding rack assembly **1320** will be described with respect to justification bar **222** but it should be understood that that justification bar **222** is similarly configured (however, in some aspects justification bar **222** includes the sliding rack assembly **1320** and justification bar **223** includes the rotating slider assembly **1230** or vice versa).

(103) The sliding rack assembly includes a sliding frame **1332** that is shaped and sized to reciprocate in direction **LAT** within the slot **1130** (or slot **1131**). In the aspect illustrated the sliding frame **1332** has a rectangular cross section (and the slot **1130** or **1131** has a mating cross section) but in other aspects the sliding frame **1332** and slot **1130** (or slot **1131**) have any suitable mating cross sections the provide for reciprocating movement of the sliding frame **1332** in direction **LAT**. The sliding frame **1332** includes a first end **1332E1** and a second end **1332E2**. The sliding frame **1332** includes a channel **1332C** (FIG. **13D**) that extends through at least a portion of the sliding frame **1332** and opens through the first end **1332E1**. A rack gear **1331** extends through the channel **1332C** so as to reciprocate in direction **LAT** within the channel, where the rack gear **1331** extends out of the channel **1332C** at the first end **1332E1** for coupling with the linear actuator **1225**. As can be seen in FIG. **13E** the rack gear **1331** includes a frame **1331F**, a gear portion **1331R** coupled to the frame **1331F**, and a stepped portion **1331P**.

(104) A rotating gear set **1378** is coupled to the sliding frame **1332** at or adjacent the second end **1332E2** about axis **1377**. The rotating gear set **1378** includes at least one pinion gear **1351, 1352, 1353** (see FIG. **13D**). In the example illustrated the at least one pinon gear **1351, 1352, 1353** is three pinion gears stacked one on the other (or integrally formed with each other). Here a lower pinion gear **1351**, a middle pinion gear **1353**, and an upper pinion gear **1352** are coupled about axis **1377** between tines **TN1, TN2** (FIG. **13D**) of the sliding frame **1332**. It is noted that the terms upper, lower, and middle are used here for convenience and any other spatial identifiers may be used in their place. The rack gear **1331** is aligned with the middle pinon gear **1353** so that the gear portion **1331R** meshes with the middle pinion **1353** so as to drivingly rotate the upper pinion gear **1352** and the lower pinion gear **1351**. The upper pinion gear **1352** and the lower pinion gear **1351** are aligned with and mesh with respective rack gears **1350R1, 1350R2** disposed on (or integral with) the tab **1350** as described herein.

(105) As can be seen best in FIGS. **13C** and **13D**, the tines **TN1, TN2** of the sliding frame and the rotating gear set **1378** form a channel in which the tab **1350** reciprocates in direction **LON**. For

example, the tab **1350** includes lateral sides **LS1**, **LS2** and longitudinal ends **LT1**, **LT2** (see FIG. **13C**). The tab **1350** includes a protrusion **1350P** that extends from the lateral side **LS1** and at least partially into a slot **TNS** formed by the tines **TN1**, **TN2** at the second end **1332E2** of the sliding frame **1332**. The slot **TNS** and protrusion **1350P** are sized relative to each other so that the slot **TNS** at least in part guides reciprocating movement of the tab **1350** in direction **LON**. The lateral side **LS2** includes at least one rack gear **1350R1**, **1350R2** that meshes with the at least one pinion gear **1351**, **1352**, **1353**. In the example, shown an upper rack gear **1350R1** meshes with the upper pinion gear **1352** and a lower rack gear **1350R2** meshes with the lower pinion gear **1351** so that rotation of the upper and lower pinion gears **1352**, **1351** causes movement of the tab **1350** in direction **LON**. The dual rack gears may **1350R1**, **1350R2** maintain alignment of the protrusion **1350P** within the slot **TNS**.

(106) In a manner similar to that described above, reciprocating movement of the tab **1350** in both directions **LON**, **LAT** is effected with a single linear actuator **1225**. For example, FIG. **13A** illustrates the tab **1350** in a retracted position and FIG. **13B** illustrates the tab **1350** in an extended position. FIG. **13C** illustrates the movement of the extended tab **1350** in direction **LAT**. Here, to extend the tab **1350** the linear actuator **1225** is operated to move the rack gear **1331** in direction **LAT1**. Movement of the rack gear **1331** in direction **LAT1** causes rotation of the rotating gear set in a first rotation direction **1377R1** about axis **1377**, where the rotation of the upper and lower pinion gears **1352**, **1351** in the first rotation direction **1377R1** causes movement of rack gears **1350R1**, **1350R2** (and the tab **1350**) in direction **LON1** to extend the tab **1350**. In a manner similar to that described above, the sliding frame **1332** is held from movement in direction **LAT1** so that the rack gear **1331** moves relative to the sliding frame **1332** effecting extension of the tab **1350**.

(107) The sliding frame **1332** is held from movement so that movement of the rack gear **1331** in direction **LAT1** causes extension of the tab **1350**. As described herein, extension of the tab **1350** releases the sliding frame **1332** for movement in direction **LAT1** and further movement of the rack gear **1331** in direction **LAT1** moves the rack gear **1331** and the sliding frame **1332** (and tab **1350**) as a single unit in direction **LAT1** (See FIG. **13C**). Here the sliding frame **1332** is held from movement in any suitable manner such as by one or more of a detent mechanism **1222** substantially similar to that described above and a hard stop (e.g., abutting) engagement between the tab **1350** and the justification bar **222** (noting that the justification bar **222** includes the shroud **222S** that at least partially surrounds the sliding rack assembly **1320** where the shroud **222S** forms a portion of the channel **1277**). In the example illustrated the shroud **222S** includes a stop surface **1366** (FIGS. **13C** and **13F**) that substantially abuts the lateral side **LS** of the tab **1350** with the tab **1350** in at least the retracted position. The stop surface **1366** includes a protrusion **1367** that extends into and along a length of the channel **1277**. As the tab **1350** is extended the lateral side **LS1** of the tab **1350** rides along the stop surface **1366** (so that the sliding frame **1322** is held from movement in direction **LAT1**) until the tab **1350** extends past the protrusion **1367** (as shown in FIG. **13F**). Extension of the tab **1350** past the protrusion **1367** of the stop surface **1366** frees the sliding frame **1322** (and tab **1350**) for movement in direction **LAT1**. As may be realized, the middle pinion gear **1353** has a diameter that prevents interference with a portion of the protrusion **1367** that extends along the channel **1277** (and the upper and lower pinion gears **1351**, **1352** are disposed respectively above and below the protrusion **1367**).

(108) In one or more aspects, the running clearance and/or lubricity between sliding frame **1332** and the channel **1277** is such that any friction between the sliding frame **1332** and the channel **1277** is insufficient to cause relative movement between the rack gear **1331** and the sliding frame **1332** (e.g., so that further extension of the tab **1350** is precluded). In one or more aspects, a clutch is provided in the rotating gear set **1378** and/or a detent mechanism (substantially similar to detent mechanism **1222**) is provided between the sliding frame **1332** and the rack gear **1331** so that a force required to effect relative movement between the sliding frame **1332** and the rack gear **1331** is greater than the friction forces between the sliding frame **1332** and the channel **1277**. In one or

more aspects, relative movement between the rack gear **1331** and the sliding frame **1332** is arrested by suitable hard (e.g., abutting) stops between a surface of the rack gear **1331** (e.g., such as protruding surface or stepped portion **1331P**) and a mating stop surface (e.g., such as a stepped surface **1332CS**—FIG. **13D**) within the channel **1332C**. In still other aspects, the above are combined in any suitable manner so that there is substantially no relative movement between the rack gear **1331** and the sliding frame **1332**.

(109) Movement of the tab **1350** from the extended position to the retracted position occurs in a manner substantially opposite to that described above. For example, the linear actuator operates to move the rack gear **1331** in direction **LAT2**. Abutment of the tab **1350** against the protrusion **1367** prevents movement of tab **1350** in direction **LON2** and substantially locks (e.g., prevents) relative movement between the rotating gear set **1378** and the rack gear **1331** so that the sliding frame **1332**, rack gear **1331**, rotating gear set **1378**, and tab **1350** (e.g., sliding rack assembly **1320**) move as a unit in direction **LAT2**. Here, the rack gear(s) **1350R1**, **1350R2** of the tab **1350** that are meshed with the pinion gears **1351**, **1352** of the rotating gear set **1378** prevent rotation of the rotating gear set **1378** and, via meshing of the rack gear **1331** with pinion gear **1353**, relative movement between the rack gear **1331** and rotating gear set **1378** is prevented. The sliding rack assembly **1320** continues to move in direction **LAT2** until the tab **1350** moves past the protrusion **1367** (and stop surface **1366**), at which point relative movement between the rack gears **1331**, **1350R1**, **1350R2** and the rotating gear set **1378** is released such that movement of the sliding frame **1332** in direction **LAT2** is arrested in any suitable manner and rack gear **1331** continues to move in direction **LAT2** relative to the sliding frame **1332**. Movement of the rack gear **1331** in direction **LAT2** relative to the sliding frame **1332** causes rotation of the rotating gear set **1378** in direction **1377R2**. Rotation of the rotating gear set **1378** in direction **1377R2** causes movement of the tab **1350** in direction **LON2** so that the tab **1350** is moved to the retracted position. Movement of the sliding frame **1332** in direction **LAT2** is in one or more aspects arrested by suitable hard (e.g., abutting) stops between a surface of the sliding frame **1332** and the channel **1277**, by the detent mechanism **1222** (FIG. **12H**), or in any other suitable manner. The retracted position of the tab **1350** is in one or more aspects set by an end of stroke of the linear actuator **1225** in direction **LAT2**, the end of stroke being defined by one or more of a hard stop (current sensor of the linear actuator may detect when the hard stop is reached), encoder position, switch, etc. where the linear actuator **1225** is controlled, such as by bot controller **1220** (FIG. **1**) in response to signals received from one or more sensors/switches indicated the end of stroke.

(110) Referring to FIGS. **2A-2D**, **9A**, **14A-14F**, and **16**, at least the case unit support surface **610**, the pusher arms **1150**, **1250**, and the justification bars **222**, **223** form payload registration facets that, as described herein, are mounted to the frame **200F** so as to engage the payload held in the payload bed **210B**. The registration facets are disposed to provide, upon engagement with the payload, at least two degrees of registration capturing and securing the payload in a predetermined position in the payload bay **210B**, and are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with seating of the payload on the payload support plane **610P** of the payload bay **210B**. In one or more aspects, the seating of the payload or case unit **CU**, on the payload support plane **610P**, is effected with a common seating motion between the end effector or arm **210A** and the payload support plane **610P** for each pick of the arm **210A** from each different support plane height **CUSH1**, **CUSH2** (see FIG. **16**) of the storage space **130S**. The common seating motion is effected, as described herein, by moving both the arm **210A** and payload support plane **610P** in a common direction **VER** (e.g., **VERU**, **VERL**) with the lift towers **211**, **212** (as described herein, where the motion of the justification tray is arrested by the frame **200F**). The common seating motion is a minimum or minimized motion (e.g., in direction **VER** that is only so much as to allow movement of the case unit **CU** above the arcuate support surfaces **621** of the justification tray **600** without contact) closing a (common) clearance air gap **CAG** (sized according to the minimized motion; see FIGS.

6B and **6E**) between the payload support plane **610P** and the underpick end effector **210A** at a payload pick height **PCKH1**, **PCKH2** of the underpick end effector **210A** for each different support plane height **CUSPH** of the storage space **130S**.

(111) As will be described herein, effecting the at least two degrees of registration of the case unit **CU** substantially coincident with loading the payload bay **21B** with the case unit **CU** enables initiation of vehicle **110** travel (transporting the loaded case unit **CU**) substantially coincident with loading the case unit on the vehicle **110** for each case unit **CU** loaded on the vehicle **110**. As an example, an exemplary case unit pick operation of the bot **110** within a picking aisle **130A** will be described in accordance with the aspects described herein. It should be understood that the case unit pick operation of the bot **110** on the transfer deck is substantially similar. As described herein, the picking aisles include rails **1600** (and/or solid decks) on which the bot **110** travels. Each level **130L** of the storage structure includes the rails **1600** providing the bots **110** on that level **130L** access to the storage locations **130S** of case unit supports **900** within the picking aisles **130A**. As can be seen in FIG. **16**, each level **130L** includes at least one level of case unit supports **900** that are accessible from the rails **1600** of the respective level. For example, level **130L1** includes a single level of case unit supports **900** accessible from rails **1600L1**, while level **130L2** includes two levels of case unit supports **900** accessible from common rails **1600L2** (i.e., the rails **1600L2** are common to both upper and lower case unit supports **900U**, **900L** of level **130L2** so that a bot **110** on the common rails **1600L2** can access both the upper and lower case unit supports **900U**, **900L**).

(112) The bot **110** on a predetermined level **130L** is commanded, such as by control server **120** or warehouse management system **2500**, to pick a predetermined case unit **CU**. The bot **110** travels along the transfer deck **130B** on the predetermined level **130L** to a picking aisle **130A** in which the case unit **CU** is located, where bot travel and bot picking/placing operations are under control of, for example, bot controller **1220** or other suitable controller in communication with the bot **110**. The bot **110** is configured as described herein so that the articulated underpick end effector or arm **210A** extends and retracts (e.g., in direction **LAT**) loading the payload or case unit **CU** at each predetermined pick height **PCKH1**, **PCKH2** (e.g., corresponding to a height **CUSH1**, **CUSH2** of a predetermined case unit support **900**, **900U**, **900L**) of the articulated underpick end effector **210A**. In one or more aspects, each pick height of the end effector **210A** is selectable from different predetermined pick heights, and the payload support plane **610P** is disposed so that seating of the payload **CU** is substantially constant and independent of the pick height **PCKH1**, **PCKH2** of the articulated underpick end effector **210A** loading the payload **CU**. In one or more aspects, each pick height **PCKH1**, **PCKH2** is selectable from different predetermined pick heights **PCKH1**, **PCKH2**, and the registration facets register the payload **CU** loaded (and deregister an unloading payload) independent or decoupled from the pick height **PCKH1**, **PCKH2** of the articulated underpick end effector **210A** loading (or unloading) the payload **CU**. As can be seen in FIG. **16**, the articulated underpick end effector **210A** extends and retracts loading the payload **CU** at each payload storage shelf height **CUSH1**, **CUSH2** in a vertical array of storage shelves **VAS** at different heights (from a base level **BLA** of the vertical array of storage shelves **VAS**), and the registration facets register the payload **CU** loaded (and deregister an unloading payload) independent or decoupled from the payload storage shelf height **CUSH1**, **CUSH2**. Here, the payload support plane **610P** is movable relative to the frame **200F** in at least one degree of freedom (e.g., at least in direction **VER**) commensurate with motion of the articulated underpick end effector **210A** with respect to the frame **200F** and/or the payload support plane **610P** is movable relative to a pick height **PCKH1**, **PCKH2** of the articulated underpick end effector **210A** (see, e.g., FIGS. **6A-6F**—such as where the movement of the justification tray **600** is arrested by the frame **200F** or moved in direction **VERT** by actuator **666A**).

(113) As an example of the above-mentioned picking/placing operations, bot **110** on level **130L1**, the bot **110** enters the picking aisle **130A** and with any suitable bot odometry and/or sensor guidance stops in the picking aisle **130A** at the location of the case unit **CU** (FIG. **18**, Block **1800**).

The distance between the fingers **210AF** (or finger segments **210S1-210S7**) is adjusted according to a size of the case unit in the manner described herein. The distance between the fingers **210AF** (or finger segments **210S1-210S7**) is adjusted on-the-fly as the bot **110** is in transit to the case unit CU storage location **130S** and/or when the bot **110** is stopped adjacent the case unit CU storage location **130S**. As can be seen in FIGS. **9A** and **14A**, the fingers **200AF** are aligned with slats **900S** of the picking aisle storage location **130S** so that the fingers **210AF** are moved/extended in direction **LAT2** and positioned underneath the case unit CU for picking the case unit CU (FIG. **18**, Block **1810**).

(114) In the manner described above, the fingers **210AF** are moved in direction **VERU** to a predetermined pick height **PCKH1**, **PCKH2** to pick (or place) the case unit CU from (or to) the storage location **130S**. Here, the fingers **210AF** are moved in direction **VERU** by lifting the payload bed **210B** (and the payload support plane **610P** thereof) with the lift towers **211**, **212**. With the case unit CU supported on the fingers **210AF** the fingers **210AF** are moved/retracted in direction **LAT1** to transfer the case unit CU into the payload bed **210B** (e.g., or move/extend in direction **LAT2** to transfer the case unit CU from the payload bed **210B**) as illustrated in FIGS. **14B** and **16**. Here, the registration facets are configured to effect payload or case unit CU engagement with the at least two degrees of registration (as described herein) registering the payload substantially coincident with the arm **210A** positioning the case unit CU on the payload contact support surface **610** loading the payload bay **210B**. For example, as described above, the distance or gap **CAG** between the case unit support surface **210AFS** of the fingers **210AF** and the arcuate support surface **621** of the justification tray **600** is only so much (i.e., minimized) as to allow movement of the case unit CU above the arcuate support surfaces **621** without contact. Here, seating of the case unit CU on the justification tray **600** is substantially immediately proximate to the end effector **210A** positioning the underpick case unit CU within the payload bay **210B** loading the payload bay **210B**. For example, required movement of the payload bed **210B** and fingers **210AF** carried thereby in direction **VERL** so that the arcuate support surfaces **621** protrudes above the case unit support surface **210AFS** of the fingers **210AF** is minimized such that the movement occurs (and is completed) substantially immediate upon the movement of the payload bed **210B** and fingers **210AF** in direction **VERL** (such as where the movement of justification tray is arrested by the frame **200F**); while in other aspects, the actuator **666A** causes movement of the arcuate support surfaces **621** protrudes above the case unit support surface **210AFS** of the fingers **210AF**. Here, seating of the case unit or payload CU on the arcuate support surfaces **621** of the support surface **610** (i.e., of the justification tray **600**) registers the payload CU in the two degrees of registration (e.g., vertically in direction **VER** and planar in directions **LON/LAT**) substantially coincident with a completed retraction of the fingers **210AF** into the payload bed **210B**. The arcuate support surfaces **621** are configured to stably hold the payload and allow the vehicle **110** to begin traverse movement (e.g., along the picking aisle **130A** or transfer deck **130B**) substantially coincident with seating of the payload on the justification tray **600**.

(115) With the case unit or payload CU seated on the justification tray **600**, and substantially coincident with placement of the case unit CU on the support surface **610** of the justification tray **600** (and with the vehicle already traversing along the picking aisle **130A** or transfer deck **130B**), the justification bars **222**, **223** are moved in direction **LON** so that the justification bars **222**, **223** are located adjacent to respective sides of the case unit CU. Movement of the justification bars **222**, **223** may begin in direction **LON** prior to or after the case unit is transferred to the payload bed **210B**. Where the justification bars **222**, **223** are moved in direction **LON** to be adjacent the respective sides of the case unit CU before the case unit CU is transferred into the payload bed **210B**, the justification bars **222**, **223** are moved base upon an expected size of the case unit to be picked.

(116) It is also noted that the tabs **1250** are also extended but in a retracted position (FIG. **18**, Block **1820**), such as in FIG. **14A**, to allow substantially unhindered transfer of the case unit CU into the

payload bed **210B** with the transfer arm **210A** in a manner similar to that described above (FIG. **18**, Block **1830**). Referring also to FIGS. **17A** and **17B**, with the case unit **CU** in the payload bed **210B**, and substantially coincident with placement of the case unit **CU** on the support surface **610**, the tabs **1250** are rotated in direction **1291** about the respective rotation axis **1290** so as to extend the tabs **1250** into a case unit engagement position as illustrated in FIG. **14B**. The tabs **1250** are moved in direction **LAT1** in the manner described above so that the case unit **CU** is pulled into the payload bed **210B**, as shown in FIG. **14C**, to remediate any case overhang condition (e.g., the case unit **CU** extends at least partially out of the payload bed **210B** past the payload bed frame **210BF** and/or cantilevered tips of the fingers **210AF**—see FIG. **17A**).

(117) A case overhang position may be present where the vehicle **110** picks a case unit **CU** from a “deep” pick position (the deep pick position may be a position on the storage shelf where the predetermined storage position of the case unit partially extends beyond the physical reach of the transfer arm **210A** but only so much that the case unit **CU** in the “deep” pick position can still be stably picked and placed by the transfer arm **210A**). The case overhang condition may be such that the case unit **CU** may contact the storage structure if the vehicle **110** were to traverse along the picking aisle **130A** or transfer deck **130B**. Here, as the case unit **CU** is being retracted into the payload bed **210B**, the tabs **1250** engage the case unit **CU** and pull the case unit into the payload bed **210B** so as to substantially eliminate the case overhang position (see FIG. **17B**) substantially coincident with the seating of the case unit **CU** on the support surface **610** so as to facilitate traverse movement of the vehicle **110**, as described herein, substantially simultaneously with the registration of the case unit **CU** on the support surface **610** in the two degrees of registration (FIG. **18**, Block **1840**). As may be realized, the tabs **1250** may pull the case unit (e.g., from the overhang condition) into the payload bed **210B** just enough to clear the storage and retrieval structure so that with the case unit **CU** seated in the payload bed **210B** with the two degrees of registration, the vehicle **110** commences traverse movement (FIG. **18**, Block **1850**) along the picking aisle **130A** or transfer deck **130B** substantially coincident with and immediately upon seating of the case unit in the payload bed **210B**.

(118) In one or more aspects, substantially coincident with placement of the case unit **CU** on the support surface **610**, the pusher arms **1150** are moved in direction **LAT2** to push the case unit against the tabs **1250** for gripping the case unit. Here, the case unit may be registered with at least two degrees of registration into the position illustrated in FIG. **14C**, from the skewed position illustrated in FIG. **2D**.

(119) As another example of the above-mentioned picking/placing operations, bot **110** on level **130L2** enters the picking aisle **130A** and stops in the picking aisle **130A** at the location of the case unit **CU** in a manner similar to that described above (FIG. **18**, Block **1800**). The distance between the fingers **210AF** (or finger segments **210S1-210S7**) is adjusted according to a size of the case unit in the manner described above. Also, in the manner described above, and with the bot **110** on the common rails **1600L2** the fingers **210AF** are moved in direction **VERU** to pick the case unit **CU** from the storage location **130S** of one or more of the upper case unit supports **900U** and the lower case unit supports **900L** of level **130L2** respectively disposed at heights **CUSH2**, **CUSH1** (FIG. **18**, Block **1810**). Here, the fingers **210AF** are moved in direction **VERU** to a predetermined one or more of pick heights **PCKH1**, **PCKH2** by lifting the payload bed **210B** (and the case unit support plane **610P** thereof) with the lift towers **211**, **212**. With the case unit **CU** supported on the fingers **210AF**, the fingers **210AF** are moved/retracted in direction **LAT1** to transfer the case unit into the payload bed **210B** (or moved/extended in direction **LAT2** to transfer the case unit from the payload bed **210B**) as illustrated in FIGS. **14B** and **16** (FIG. **18**, Block **1830**). Here, the registration facets are configured to effect payload or case unit **CU** engagement with the at least two degrees of registration registering the payload substantially coincident with the arm **210A** positioning the case unit **CU** on the payload contact support surface **610** loading the payload bay **210B**. Again, the distance or gap **CAG** between the case unit support surface **210AFS** of the fingers **210AF** and the

arcuate support surface **621** of the justification tray **600** is only so much (i.e., minimized) as to allow movement of the case unit CU above the arcuate support surfaces **621** without contact. Here, seating of the case unit CU on the justification tray **600** is substantially immediately proximate to the end effector **210A** positioning the underpick case unit CU within the payload bay **210B** loading the payload bay **210B** as described above. In this example, the actuator **666A** is employed to move the arcuate support surfaces **621** so the arcuate support surfaces **621** protrude above the case unit support surface **210AFS** of the fingers **210AF**. Here, seating of the case unit or payload CU on the arcuate support surfaces **621** of the support surface **610** (i.e., of the justification tray **600**) registers the payload CU in the two degrees of registration (e.g., vertically in direction VER and planar in directions LON/LAT) substantially coincident with and substantially immediately upon a completed retraction of the fingers **210AF** into the payload bed **210B**. As described above, the arcuate support surfaces **621** are configured to stably hold the payload and allow the vehicle **110** to begin traverse movement (e.g., along the picking aisle **130A** or transfer deck **130B**) substantially coincident with seating of the payload on the justification tray **600**.

(120) In a manner similar to that described above, substantially coincident with placement of the case unit CU on the support surface **610** the justification bars **222**, **223** are moved in direction LON so that the justification bars **222**, **223** are located adjacent to respective sides of the case unit CU. The justification bars **222**, **223** may be moved in direction LON prior to or after the case unit being transferred to the payload bed **210B**. Where the justification bars **222**, **223** are moved in direction LON to be adjacent the respective sides of the case unit CU before the case unit CU is transferred into the payload bed **210B**, the justification bars **222**, **223** are moved based upon an expected size of the case unit to be picked. As described above, the tabs **1250** are extended but in a retracted position with the case unit CU being transferred to the payload bed **210B** by the transfer arm **210A** (FIG. **18**, Block **1820**), such as in FIG. **14A**, to allow substantially unhindered transfer of the case unit CU into the payload bed **210B** (FIG. **18**, Block **1830**). With the case unit in the payload bed **210B**, and substantially coincident with placement of the case unit CU on the support surface **610**, the tabs **1250** are rotated in direction **1291** about the respective rotation axis **1290** so as to extend the tabs **1250** into a case unit engagement position as illustrated in FIG. **14B**. The tabs **1250** are moved in direction LAT1 in the manner described above so that the case unit CU is pulled into the payload bed **210B**, as shown in FIG. **14C**, to substantially remediate/eliminate any case overhang condition (e.g., the case unit CU extends at least partially out of the payload bed **210B** past the payload bed frame **210BF** and/or cantilevered tips of the fingers **210AF**—see FIGS. **17A** and **17B**) (FIG. **18**, Block **1840**). In one or more aspects, substantially coincident with placement of the case unit CU on the support surface **610**, the pusher arms **1150** are moved in direction LAT2 to push the case unit against the tabs **1250** for gripping the case unit. Here, the case unit may be registered with at least two degrees of registration into the position illustrated in FIG. **14C**, from the skewed position illustrated in FIG. **2D**.

(121) In one or more aspects, the justification bars **222**, **223** (e.g., of the bot **110** located on any of the levels **130L** illustrated in FIG. **16** and transferring a case unit) are moved in direction LON to grip and or justify the case unit CU within the payload bed **210B**. FIGS. **14C**, **14D**, and **14E** illustrate a center justification of the case unit where the case unit is positioned by the justification bars **222**, **223** substantially at or along a centerline CL of the payload bed. However, in other aspects, the case unit is justified to a location that is off-center relative to the centerline CL. As described above, the case unit CU is moved in direction LON, with the case unit CU held in the payload bed **210B**, with the case unit CU being supported by the fingers **210AF** and/or by the justification tray **600**. FIG. **14E** illustrates placement of the case unit CU onto the protrusions **620** of justification tray **600** for justification to a position off-center relative to centerline CL (see FIG. **14F**) where the off-center position still allows the case unit CU to be lifted with all of the fingers **210AF** substantially underneath the case unit CU. Placing a case unit from the justified location within the payload bed occurs in a manner substantially opposite to that described above.

(122) In accordance with the aspects of the disclosed embodiment, and as described herein, the at least two degrees of registration include registration on the support surface **610**, registration in direction LON and in direction LAT. For example, the arm **210A** seating the case unit CU on the payload support plane **610P** (e.g., on the justification tray **600**) effects registration of the case unit CU in the at least two degrees of registration relative to the bot frame **200F**. As described herein, the arm **210A** seating of the case unit CU on the payload support plane **610P** is substantially immediately proximate to the end effector positioning the underpick case unit CU within the payload bay **210B** loading the payload bay **210B**. It is noted that effecting at least two degrees of registration of the case unit CU substantially coincident with loading the payload bay **210B** with the case unit CU enables initiation of vehicle **110** travel (transporting the loaded case unit CU along a licking aisle **130A** or transfer deck **130B**) substantially coincident with loading the case unit on the vehicle **110** for each case unit CU loaded on the vehicle **110**, regardless of the case unit support plane CUSPH height CUSH1, CUSH2 relative to the bot frame **200F** or rails **1600** (i.e., regardless of whether the case unit CU is picked from an upper case unit support **900U** or a lower case unit support **900L** of a level **130L**) (FIG. **18**, Block **1850**).

(123) Placement of a case unit CU onto a support shelf (e.g., in a storage space **130S** or other suitable location of the storage and retrieval system) from the autonomous transport vehicle **110** may occur in a manner substantially opposite to that described above. For example, the vehicle **110** is positioned at a predetermined location adjacent a storage space **130S** (or other holding location) at which the case unit CU is to be placed (FIG. **19**, Block **1900**). With placement of a case unit CU to a storage location **130S** of one or more of the upper case unit supports **900U** of, for example, level **130L2** disposed at height CUSH2, the tab **1250** is employed to maintain the case unit CU in a “pulled back position” so that the case unit CU does not contact structure (e.g., shelving, etc.) of the storage and retrieval system **100** (see FIG. **17C**) as the case unit CU is lifted (with the payload bed **210B**) to the predetermined pick/place height PCKH2 (FIG. **19**, Block **1910**). Where the case unit CU is to be stored/placed at a “deep” storage space **130S**, the pusher arms **1150** move in direction LAT2 (e.g., with the payload bed **210B** and transfer arm **210A** at the predetermined pick/place height PCKH2) so as to place the case unit in an overhang position (see FIG. **17D**) (FIG. **19**, Block **1920**) to facilitate the placement of the case unit CU by the transfer arm **210A** in the “deep” storage location **130S** (FIG. **19**, Block **1930**).

(124) Also, in the manner described above, and with the bot **110** on the common rails **1600L2** the fingers **210AF** are moved in direction VERU to pick the case unit CU from the storage location **130S** of one or more of the upper case unit supports **900U** and the lower case unit supports **900L** of level **130L2** respectively disposed at heights CUSH2, CUSH1. Here, the fingers **210AF** are moved in direction VERU to a predetermined one or more of pick heights PCKH1, PCKH2 by lifting the payload bed **210B** (and the case unit support plane **610P** thereof) with the lift towers **211**, **212**. With the case unit CU supported on the fingers **210AF**, the fingers **210AF** are moved/retracted in direction LAT1 to transfer the case unit into the payload bed **210B** (or moved/extended in direction LAT2 to transfer the case unit from the payload bed **210B**) as illustrated in FIGS. **14B** and **16**.

(125) Still referring to FIG. **2C**, the autonomous transport vehicle **110** includes a vision system configured to effect case handling by verifying a correct size case is picked, verify the case dimensions, and to verify the case orientation and location. The vision system substantially continuously monitors case unit CU position in the payload bay **210B** and provides the controller **1220** with update case unit CU position data at any suitable time intervals. Here, the case handling assembly **210** includes one or more of case edge detection sensor(s) CED, case yaw detection sensor(s) CYD, case overhand sensor(s) COH, shelf sensor(s) SS, three-dimensional image sensor(s) IMF, and extension cameras EXT, each of which is communicably coupled to controller **1220** for informing the controller of case/shelf positions to effect pick and place of case units CU as described herein. It is noted that the term “camera” described herein is a still imaging or video imaging device that includes one or more of a two-dimensional camera, a two dimensional camera

with RGB (red, green, blue) pixels, a three-dimensional camera with XYZ+A definition (where XYZ is the three-dimensional reference frame of the camera and A is one of a radar return strength, a time of flight stamp, or other distance determination stamp/indicator), and an RGB/XYZ camera which includes both RGB and three-dimensional coordinate system information, non-limiting examples of which are provided herein.

(126) The case edge detection sensor(s) CED are any suitable sensors such as laser measurement sensors configured to scan the shelves of the storage and retrieval system to verify the shelves are clear for placing case units CU, or to verify the case unit size and position before picking the case unit CU. While, on case edge detection sensor CED illustrated on each side of the payload bay **210B** there may be more or less than two case edge detection sensors placed at any suitable locations on the vehicle **110** so that the vehicle **110** can traverse by and scan case units CU with the front end **200E1** leading a direction of vehicle travel or the rear/back end **200E2** leading the direction of vehicle travel.

(127) The case yaw detection sensor CYD are mounted to, for example, the inside of the payload bay **210B**. The case yaw detection sensors are any suitable sensors such as laser measurement sensors. The case yaw detection sensors CYD are positioned so as to be aimed or directed at a case unit CU being picked so as to measure the yaw or skew of the case unit CU (see FIG. 2D) and inform the controller **1220** of the orientation of the case unit CU.

(128) The case overhang sensor(s) COH are in one aspect a through beam sensor having an emitter and receiver located on opposite sides of the payload bay **210B** in an opposing manner; while in other aspects reflective sensors or other suitable detection/proximity sensor may be employed. The case overhang sensor(s) COH are positioned adjacent the transfer opening **1199** such as with the case overhang sensor(s) COH detecting a case unit CU/obstruction the controller **1120** is informed that a case unit is extending out of the payload bay **210B** through the transfer opening **1199**.

(129) The shelf sensors SS are disposed at any suitable location of the case handling assembly (such as one sensor located on each side of the payload bay **210B**) to sense a shelf and verify shelf hat positions (see FIG. 9A) for picking case units CU and placement of the fingers of the transfer arm **210A** between the shelf hats.

(130) The three-dimensional image sensor(s) IMF (e.g., time-of-flight cameras, imaging radar systems, light detection and ranging (LIDAR), etc.) are suitably positioned relative to the payload bay **210B** and are employed to measure the position and orientation of the case unit CU in the payload bay **210B**. While one three-dimensional image sensor(s) IMF is illustrated there may be more than one.

(131) The extension camera(s) EXT are positioned at the rear of the payload bay **210B** (opposite the transfer opening **1199**) and are positioned so that a field of view of the extension camera(s) EXT is within the payload bay **210B** to record case unit pick and places. The extension camera(s) EXT may be employed by the controller **1220** or operators of the storage and retrieval system for debugging and/or teaching (e.g., to automation of the storage and retrieval system) pick place operations.

(132) Referring to FIGS. 2A-2D, 9A, 14A-14F, and 15 an exemplary method will be described in accordance with aspects of the disclosed embodiment. Here, an autonomous transport vehicle **110** is provided (FIG. 15, Block **1500**). The autonomous transport vehicle has a frame **200F** forming a transport payload area or bay **210B** of the vehicle **110**, the payload bay **210B** includes a payload contact support surface **610** that defines a payload support plane **610P** (FIG. 14E) that supports the payload (e.g., case unit CU) held in the payload bay **210B** with vehicle **110** traverse. The payload bay **210B** further includes an (articulated) underpick end effector or arm **210A** configured to engage and underpick (as described herein) the payload CU with respect to the payload support plane **610P**, and extend and retract with respect to the payload bay **21B** effecting payload CU transfer to and from the payload bay **210B** unloading and loading the payload bay **21B**. Payload registration facets (as described herein) are also mounted to the frame **200F**. The payload CU held

in the payload area is engaged with the payload (FIG. 15, Block 1510) registration facets. The registration facets are disposed to provide, upon engagement with the payload CU, at least two degrees of registration capturing and securing the payload CU in a predetermined position in the payload bay 210B, and are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with seating of the payload on the payload support plane 610P of the payload bay 210B. In one or more aspects, as described herein, the seating of the payload or case unit CU, on the payload support plane 610P, is effected with a common seating motion between the end effector or arm 210A and the payload support plane 610P for each pick of the arm 210A from each different support plane height CUSH1, CUSH2 (see FIG. 16) of the storage space 130S.

(133) The method may further include effecting, with the registration facets, payload CU engagement with the at least two degrees of registration registering the payload CU substantially coincident with the end effector 210A positioning the payload CU on the payload contact support surface 610 loading the payload area 210B. The method may include effecting, with the end effector 210A seating the payload CU on the payload support plane 610P, registration of the payload CU and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload CU relative to the autonomous transport vehicle 110 frame 200F. The method may include effecting, with the end effector 210A seating the payload CU on the payload contact support surface 610, registration of the payload CU and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload CU relative to the autonomous transport vehicle 110 frame 200F. The end effector 210A seating of the payload CU on the payload support plane 610P is substantially immediately proximate to the end effector 210A positioning the payload CU within the payload area 210B loading the payload area 210B. Effecting at least two degrees of registration of the payload CU substantially coincident with loading the payload area 210B with the payload CU enables initiation of vehicle 110 travel substantially coincident with loading the payload CU on the vehicle 110 for each payload CU loaded on the vehicle 110.

(134) In accordance with one or more aspects of the disclosed embodiment an autonomous transport vehicle for transporting a payload comprises: a frame forming a transport payload area of the vehicle, the payload area includes a payload contact support surface that defines a payload support plane that supports the payload held in the payload area with vehicle traverse; the payload area further includes an articulated underpick end effector configured to engage and underpick the payload with respect to the support plane, and extend and retract with respect to the payload area effecting payload transfer to and from the payload area unloading and loading the payload area; and payload registration facets mounted to the frame so as to engage the payload held in the payload area; wherein the registration facets are disposed to provide, upon engagement with the payload, at least two degrees of registration capturing and securing the payload in a predetermined position in the payload area, and are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with seating of the payload on the payload support plane of the payload area.

(135) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector extends and retracts loading the payload at each predetermined pick height of the articulated underpick end effector, and each pick height is selectable from different predetermined pick heights, and the payload support plane is disposed so that seating of the payload is substantially constant and independent of the pick height of the articulated underpick end effector loading the payload.

(136) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector extends and retracts loading the payload at each predetermined pick height of the articulated underpick end effector, and each pick height is selectable from different predetermined pick heights, and the registration facets register the payload loaded (and deregister

an unloading payload) independent or decoupled from the pick height of the articulated underpick end effector loading (or unloading) the payload.

(137) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector extends and retracts loading the payload at each payload storage shelf height in a vertical array of storage shelves at different heights (from a base level of the vertical array of storage shelves), and the registration facets register the payload loaded (and deregister an unloading payload) independent or decoupled from the payload storage shelf height.

(138) In accordance with one or more aspects of the disclosed embodiment the payload support plane is movable relative to the frame in at least one degree of freedom commensurate with motion of the articulated underpick end effector with respect to the frame.

(139) In accordance with one or more aspects of the disclosed embodiment the payload support plane is movable relative to the frame in at least one degree of freedom and movable relative to a pick height of the articulated underpick end effector.

(140) In accordance with one or more aspects of the disclosed embodiment the registration facets are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with the end effector positioning the payload on the payload contact support surface loading the payload area.

(141) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector seating the payload on the payload support plane effects registration of the payload and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload relative to the frame.

(142) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector seating the payload on the payload contact support surface effects registration of the payload and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload relative to the frame.

(143) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector seating of the payload on the payload support plane is substantially immediately proximate to the articulated underpick end effector positioning the payload within the payload area loading the payload area.

(144) In accordance with one or more aspects of the disclosed embodiment effecting at least two degrees of registration of the payload substantially coincident with loading the payload area with the payload enables initiation of vehicle travel substantially coincident with loading the payload on the vehicle for each payload loaded on the vehicle.

(145) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector is configured to engage an underside of the payload and pick up the payload therefrom effecting transfer of the payload by the autonomous transport vehicle.

(146) In accordance with one or more aspects of the disclosed embodiment an autonomous transport vehicle for transporting a payload comprises: a frame forming a transport payload area of the vehicle, the payload area includes a payload contact support surface that defines a payload support plane of the vehicle that supports the payload held in the payload area with vehicle traverse; the payload area further includes an underpick end effector configured to engage and underpick the payload with respect to a support plane of a storage space and effect payload transfer to and from the support plane of the storage space unloading and loading the payload area; and payload registration facets mounted to the frame so as to engage the payload held in the payload area; wherein the registration facets are disposed to provide, upon engagement with the payload, at least two degrees of registration capturing and securing the payload in a predetermined position in the payload area, and are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with seating of the payload, on the payload support plane of the payload area, effected with a common seating motion between the underpick end effector and payload support plane for each pick of the end effector from each

different support plane height of the storage space.

(147) In accordance with one or more aspects of the disclosed embodiment the common seating motion is a minimum motion closing a (common) clearance air gap between the payload support plane and the underpick end effector at a payload pick height of the underpick end effector for each different support plane height of the storage space.

(148) In accordance with one or more aspects of the disclosed embodiment the underpick end effector extends and retracts loading the payload at each predetermined pick height of the underpick end effector, and each pick height is selectable from different predetermined pick heights, and the payload support plane is disposed so that seating of the payload is substantially constant and independent of the pick height of the underpick end effector loading the payload.

(149) In accordance with one or more aspects of the disclosed embodiment the underpick end effector extends and retracts loading the payload at each predetermined pick height of the underpick end effector, and each pick height is selectable from different predetermined pick heights, and the registration facets register the payload loaded (and deregister an unloading payload) independent or decoupled from the pick height of the underpick end effector loading (or unloading) the payload.

(150) In accordance with one or more aspects of the disclosed embodiment the underpick end effector extends and retracts loading the payload at each payload storage shelf height in a vertical array of storage shelves at different heights (from a base level of the vertical array of storage shelves), and the registration facets register the payload loaded (and deregister an unloading payload) independent or decoupled from the payload storage shelf height.

(151) In accordance with one or more aspects of the disclosed embodiment the payload support plane is movable relative to the frame in at least one degree of freedom commensurate with motion of the underpick end effector with respect to the frame.

(152) In accordance with one or more aspects of the disclosed embodiment the payload support plane is movable relative to the frame in at least one degree of freedom and movable relative to a pick height of the underpick end effector.

(153) In accordance with one or more aspects of the disclosed embodiment the registration facets are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with the end effector positioning the payload on the payload contact support surface loading the payload area.

(154) In accordance with one or more aspects of the disclosed embodiment the underpick end effector seating the payload on the payload support plane effects registration of the payload and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload relative to the frame.

(155) In accordance with one or more aspects of the disclosed embodiment the underpick end effector seating the payload on the payload contact support surface effects registration of the payload and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload relative to the frame.

(156) In accordance with one or more aspects of the disclosed embodiment the underpick end effector seating of the payload on the payload support plane is substantially immediately proximate to the underpick end effector positioning the payload within the payload area loading the payload area.

(157) In accordance with one or more aspects of the disclosed embodiment effecting at least two degrees of registration of the payload substantially coincident with loading the payload area with the payload enables initiation of vehicle travel substantially coincident with loading the payload on the vehicle for each payload loaded on the vehicle.

(158) In accordance with one or more aspects of the disclosed embodiment the underpick end effector is configured to engage an underside of the payload and pick up the payload therefrom effecting transfer of the payload by the autonomous transport vehicle.

(159) In accordance with one or more aspects of the disclosed embodiment a method comprises: providing an autonomous transport vehicle with: a frame forming a transport payload area of the vehicle, the payload area includes a payload contact support surface that defines a payload support plane that supports the payload held in the payload area with vehicle traverse, the payload area further includes an articulated underpick end effector configured to engage and underpick the payload with respect to the support plane, and extend and retract with respect to the payload area effecting payload transfer to and from the payload area unloading and loading the payload area, and payload registration facets mounted to the frame; and engaging the payload held in the payload area with the payload registration facets; wherein the registration facets are disposed to provide, upon engagement with the payload, at least two degrees of registration capturing and securing the payload in a predetermined position in the payload area, and are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with seating of the payload on the payload support plane of the payload area.

(160) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector extends and retracts loading the payload at each predetermined pick height of the articulated underpick end effector, and each pick height is selectable from different predetermined pick heights, and the payload support plane is disposed so that seating of the payload is substantially constant and independent of the pick height of the articulated underpick end effector loading the payload.

(161) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector extends and retracts loading the payload at each predetermined pick height of the articulated underpick end effector, and each pick height is selectable from different predetermined pick heights, and the registration facets register the payload loaded (and deregister an unloading payload) independent or decoupled from the pick height of the articulated underpick end effector loading (or unloading) the payload.

(162) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector extends and retracts loading the payload at each payload storage shelf height in a vertical array of storage shelves at different heights (from a base level of the vertical array of storage shelves), and the registration facets register (and deregister an unloading payload) the payload loaded independent or decoupled from the payload storage shelf height.

(163) In accordance with one or more aspects of the disclosed embodiment the payload support plane is movable relative to the frame in at least one degree of freedom commensurate with motion of the articulated underpick end effector with respect to the frame.

(164) In accordance with one or more aspects of the disclosed embodiment the payload support plane is movable relative to the frame in at least one degree of freedom and movable relative to a pick height of the articulated underpick end effector.

(165) In accordance with one or more aspects of the disclosed embodiment the method further comprises effecting, with the registration facets, payload engagement with the at least two degrees of registration registering the payload substantially coincident with the end effector positioning the payload on the payload contact support surface loading the payload area.

(166) In accordance with one or more aspects of the disclosed embodiment the method further comprises effecting, with the articulated underpick end effector seating the payload on the payload support plane, registration of the payload and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload relative to the frame.

(167) In accordance with one or more aspects of the disclosed embodiment the method further comprises effecting, with the articulated underpick end effector seating the payload on the payload contact support surface, registration of the payload and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload relative to the frame.

(168) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector seating of the payload on the payload support plane is substantially

immediately proximate to the articulated underpick end effector positioning the payload within the payload area loading the payload area.

(169) In accordance with one or more aspects of the disclosed embodiment effecting at least two degrees of registration of the payload substantially coincident with loading the payload area with the payload enables initiation of vehicle travel substantially coincident with loading the payload on the vehicle for each payload loaded on the vehicle.

(170) In accordance with one or more aspects of the disclosed embodiment the articulated underpick end effector engages an underside of the payload and pick up the payload therefrom effecting transfer of the payload by the autonomous transport vehicle.

(171) In accordance with one or more aspects of the disclosed embodiment a method comprises: providing an autonomous transport vehicle with: a frame forming a transport payload area of the vehicle, the payload area includes a payload contact support surface that defines a payload support plane of the vehicle that supports the payload held in the payload area with vehicle traverse, the payload area further includes an underpick end effector configured to engage and underpick the payload with respect to a support plane of a storage space and effect payload transfer to and from the support plane of the storage space payload area unloading and loading the payload area, and payload registration facets mounted to the frame; and engaging the payload held in the payload area with the payload registration facets; wherein the registration facets are disposed to provide, upon engagement with the payload, at least two degrees of registration capturing and securing the payload in a predetermined position in the payload area, and are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with seating of the payload, on the payload support plane of the payload area, effected with a common seating motion between the underpick end effector and payload support plane for each pick of the end effector from each different support plane height of the storage space.

(172) In accordance with one or more aspects of the disclosed embodiment the common seating motion is a minimum motion closing a (common) clearance air gap between the payload support plane and the underpick end effector at a payload pick height of the underpick end effector for each different support plane height of the storage space.

(173) In accordance with one or more aspects of the disclosed embodiment the underpick end effector extends and retracts loading the payload at each predetermined pick height of the underpick end effector, and each pick height is selectable from different predetermined pick heights, and the payload support plane is disposed so that seating of the payload is substantially constant and independent of the pick height of the underpick end effector loading the payload.

(174) In accordance with one or more aspects of the disclosed embodiment the underpick end effector extends and retracts loading the payload at each predetermined pick height of the underpick end effector, and each pick height is selectable from different predetermined pick heights, and the registration facets register the payload loaded (and deregister an unloading payload) independent or decoupled from the pick height of the underpick end effector loading (or unloading) the payload.

(175) In accordance with one or more aspects of the disclosed embodiment the underpick end effector extends and retracts loading the payload at each payload storage shelf height in a vertical array of storage shelves at different heights (from a base level of the vertical array of storage shelves), and the registration facets register the payload loaded (and deregister an unloading payload) independent or decoupled from the payload storage shelf height.

(176) In accordance with one or more aspects of the disclosed embodiment the payload support plane is movable relative to the frame in at least one degree of freedom commensurate with motion of the underpick end effector with respect to the frame.

(177) In accordance with one or more aspects of the disclosed embodiment the payload support plane is movable relative to the frame in at least one degree of freedom and movable relative to a pick height of the underpick end effector.

- (178) In accordance with one or more aspects of the disclosed embodiment the method further comprises effecting, with the registration facets, payload engagement with the at least two degrees of registration registering the payload substantially coincident with the end effector positioning the payload on the payload contact support surface loading the payload area.
- (179) In accordance with one or more aspects of the disclosed embodiment the method further comprises effecting, with the underpick end effector seating the payload on the payload support plane, registration of the payload and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload relative to the frame.
- (180) In accordance with one or more aspects of the disclosed embodiment the method further comprises effecting, with the underpick end effector seating the payload on the payload contact support surface, registration of the payload and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload relative to the frame.
- (181) In accordance with one or more aspects of the disclosed embodiment the underpick end effector seating of the payload on the payload support plane is substantially immediately proximate to the underpick end effector positioning the payload within the payload area loading the payload area.
- (182) In accordance with one or more aspects of the disclosed embodiment effecting at least two degrees of registration of the payload substantially coincident with loading the payload area with the payload enables initiation of vehicle travel substantially coincident with loading the payload on the vehicle for each payload loaded on the vehicle.
- (183) In accordance with one or more aspects of the disclosed embodiment the underpick end effector engages an underside of the payload and pick up the payload therefrom effecting transfer of the payload by the autonomous transport vehicle.
- (184) In accordance with one or more aspects of the disclosed embodiment an autonomous transport vehicle for transport a payload is provided. The autonomous transport vehicle comprises: a frame forming a transport payload area of the vehicle, the payload area includes a payload contact support surface that defines a payload support plane that supports the payload held in the payload area with vehicle traverse; at least one lift tower connected to the frame; a movable payload carriage that is movably mounted to the at least one lift tower and configured to raise and lower the payload within the payload area; and a drive section with at least one degree of freedom movement coupled to the movable payload carriage by a flexible transmission, where flexible transmission movably couples the movable payload carriage to the at least one lift tower and the drive section is configured to raise and lower the movable payload carriage relative to the at least one lift tower; wherein the flexible transmission is configured to effect torsional stability of the movable payload carriage, and the payload held thereon, with respect to the frame and independent of each other interface between the movable payload carriage and the at least one lift tower than the flexible transmission coupling the movable payload carriage to the at least one lift tower.
- (185) In accordance with one or more aspects of the disclosed embodiment the flexible transmission is configured to effect torsional stability of the movable payload carriage throughout an entire range of motion of the movable payload carriage relative to the at least one lift tower.
- (186) In accordance with one or more aspects of the disclosed embodiment the flexible transmission is configured to effect torsional stability of the movable payload carriage throughout a range of motion of the movable payload carriage, relative to the at least one lift tower, that effects a payload transfer from the movable payload carriage to a payload support shelf.
- (187) In accordance with one or more aspects of the disclosed embodiment the flexible transmission is configured to effect torsional stability of the movable payload carriage throughout a range of motion of the movable payload carriage, relative to the at least one lift tower, that effects a payload transfer from a payload support shelf to the movable payload carriage.
- (188) In accordance with one or more aspects of the disclosed embodiment the at least one lift tower comprises a guide rail that guides movement of the movable payload carriage and an

interface between the guide rail and the movable payload carriage is undeterministic with respect to a torsional position of the movable payload carriage relative to the guide rail.

(189) In accordance with one or more aspects of the disclosed embodiment the autonomous transport vehicle further comprises an end effector movably coupled to and carried by the movable payload carriage, the end effector being configured to extend and retract relative to the torsionally stable movable payload carriage.

(190) It should be understood that the foregoing description is only illustrative of the aspects of the disclosed embodiment. Various alternatives and modifications can be devised by those skilled in the art without departing from the aspects of the disclosed embodiment. Accordingly, the aspects of the disclosed embodiment are intended to embrace all such alternatives, modifications and variances that fall within the scope of any claims appended hereto. Further, the mere fact that different features are recited in mutually different dependent or independent claims does not indicate that a combination of these features cannot be advantageously used, such a combination remaining within the scope of the aspects of the disclosed embodiment.

Claims

1. An autonomous transport vehicle for transporting a payload comprising: a frame forming a transport payload area of the vehicle, the payload area includes a payload contact support surface that defines a payload support plane that supports the payload held in the payload area with vehicle traverse; the payload area further includes an articulated underpick end effector configured to engage and underpick the payload with respect to the payload support plane, and extend and retract with respect to the payload area effecting payload transfer to and from the payload area unloading and loading the payload area; and payload registration facets mounted to the frame so as to engage the payload held in the payload area; wherein the registration facets are disposed to provide, upon engagement with the payload, at least two degrees of registration capturing and securing the payload in a predetermined position in the payload area where the at least two degrees of registration are effected substantially coincident so that registration in each of the at least two degrees of registration is substantially coincident with registration in each other of the at least two degrees of registration, and the registration facets are configured to effect payload engagement with the effected at least two degrees of registration registering the payload substantially coincident with seating of the payload on the payload support plane of the payload area.
2. The autonomous transport vehicle of claim 1, wherein the articulated underpick end effector extends and retracts loading the payload at each predetermined pick height of the articulated underpick end effector, and each pick height is selectable from different predetermined pick heights, and the payload support plane is disposed so that seating of the payload is substantially constant and independent of the pick height of the articulated underpick end effector loading the payload.
3. The autonomous transport vehicle of claim 1, wherein the articulated underpick end effector extends and retracts loading the payload at each predetermined pick height of the articulated underpick end effector, and each pick height is selectable from different predetermined pick heights, and the registration facets register the payload loaded independent or decoupled from the pick height of the articulated underpick end effector loading the payload.
4. The autonomous transport vehicle of claim 1, wherein the articulated underpick end effector extends and retracts loading the payload at each payload storage shelf height in a vertical array of storage shelves at different heights, and the registration facets register the payload loaded independent or decoupled from the payload storage shelf height.
5. The autonomous transport vehicle of claim 1, wherein the payload support plane is movable relative to the frame in at least one degree of freedom commensurate with motion of the articulated underpick end effector with respect to the frame.

6. The autonomous transport vehicle of claim 1, wherein the payload support plane is movable relative to the frame in at least one degree of freedom and movable relative to a pick height, in a direction of the pick height, of the articulated underpick end effector.
7. The autonomous transport vehicle of claim 1, wherein the registration facets are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with the end effector positioning the payload on the payload contact support surface loading the payload area.
8. The autonomous transport vehicle of claim 1, wherein the articulated underpick end effector seating the payload on the payload support plane effects registration of the payload and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload relative to the frame.
9. The autonomous transport vehicle of claim 1, wherein the articulated underpick end effector seating the payload on the payload contact support surface effects registration of the payload and the registration facets in at least one degree of registration of the at least two degrees of registration of the payload relative to the frame.
10. The autonomous transport vehicle of claim 1, wherein the articulated underpick end effector seating of the payload on the payload support plane is substantially immediately proximate to the articulated underpick end effector positioning the payload within the payload area loading the payload area.
11. The autonomous transport vehicle of claim 1, wherein effecting at least two degrees of registration of the payload substantially coincident with loading the payload area with the payload enables initiation of vehicle travel substantially coincident with seating of the payload on the payload support plane of the vehicle for each payload loaded on the vehicle.
12. The autonomous transport vehicle of claim 1, wherein the articulated underpick end effector is configured to engage an underside of the payload and pick up the payload therefrom effecting transfer of the payload by the autonomous transport vehicle.
13. An autonomous transport vehicle for transporting a payload comprising: a frame forming a transport payload area of the vehicle, the payload area includes a payload contact support surface that defines a payload support plane of the vehicle that supports the payload held in the payload area with vehicle traverse; the payload area further includes an underpick end effector configured to engage and underpick the payload with respect to a support plane of a storage space and effect payload transfer to and from the support plane of the storage space unloading and loading the payload area; and payload registration facets mounted to the frame so as to engage the payload held in the payload area; wherein the registration facets are disposed to provide, upon engagement with the payload, at least two degrees of registration capturing and securing the payload in a predetermined position in the payload area where the at least two degrees of registration are effected substantially coincident so that registration in each of the at least two degrees of registration is substantially coincident with registration in each other of the at least two degrees of registration, and the registration facets are configured to effect payload engagement with the effected at least two degrees of registration registering the payload substantially coincident with seating of the payload, on the payload support plane of the payload area, effected with a common seating motion of and between the underpick end effector and payload support plane for each pick of the end effector from each different support plane height of the storage space.
14. The autonomous transport vehicle of claim 13, wherein the common seating motion is a minimum motion closing a clearance air gap between the payload support plane and the underpick end effector at a payload pick height of the underpick end effector for each different support plane height of the storage space.
15. The autonomous transport vehicle of claim 13, wherein the underpick end effector extends and retracts loading the payload at each predetermined pick height of the underpick end effector, and each pick height is selectable from different predetermined pick heights, and the payload support

plane is disposed so that seating of the payload is substantially constant and independent of the pick height of the underpick end effector loading the payload.

16. The autonomous transport vehicle of claim 13, wherein the underpick end effector extends and retracts loading the payload at each predetermined pick height of the underpick end effector, and each pick height is selectable from different predetermined pick heights, and the registration facets register the payload loaded independent or decoupled from the pick height of the underpick end effector loading the payload.

17. The autonomous transport vehicle of claim 13, wherein the underpick end effector extends and retracts loading the payload at each payload storage shelf height in a vertical array of storage shelves at different heights, and the registration facets register the payload loaded independent or decoupled from the payload storage shelf height.

18. The autonomous transport vehicle of claim 13, wherein the payload support plane is movable relative to the frame in at least one degree of freedom commensurate with motion of the underpick end effector with respect to the frame.

19. The autonomous transport vehicle of claim 13, wherein the payload support plane is movable relative to the frame in at least one degree of freedom and movable relative to a pick height, in a direction of the pick height, of the underpick end effector.

20. The autonomous transport vehicle of claim 13, wherein the registration facets are configured to effect payload engagement with the at least two degrees of registration registering the payload substantially coincident with the end effector positioning the payload on the payload contact support surface loading the payload area.
