

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281949

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Tippmann; Jesse

MULTIPURPOSE UNDERGROUND TOOL

Abstract

A multipurpose underground tool may be compact, universal, multi-purpose and/or reconfigurable. A variety of underground equipment in a variety of conditions at a variety of depths with a variety of operating interfaces may be remotely viewed, cleared of obstructions and controlled with one tool that may be reduced in size. A portable computer (e.g., cell phone) may power a lighted camera, display images of underground conditions to assist a user with operations (e.g., clear obstructions, maneuver, steer, attach to and operate underground equipment) and/or provide a user interface. Accessories may be adjusted, added or removed to accomplish a variety of tasks in a variety of conditions. Integrated, detachable, fixed or adjustable accessories may include a display holder, an ejector, a retriever, a debris deflector, a debris collector, a pressure tank, a pressure hose, actuators and/or other pole tips (e.g., with one or more accessories), pole sections, handles and/or accessory controls.

Inventors: Tippmann; Jesse (Piedmont, SD)

Applicant: Tippmann; Jesse (Piedmont, SD)

Family ID: 86898792

Appl. No.: 19/064613

Filed: February 26, 2025

Related U.S. Application Data

parent US continuation 17565362 20211229 parent-grant-document US 12263510 child US 19064613

Publication Classification

Int. Cl.: B08B9/043 (20060101); B08B9/032 (20060101); B08B13/00 (20060101); H04N7/18 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of and claims the benefit of U.S. patent application Ser. No. 17/565,362, filed Dec. 29, 2021, entitled “Multipurpose Underground Tool,” the disclosure of which is hereby incorporated herein by reference in its entirety.

BACKGROUND

[0002] Underground equipment, such as a curb stop valve, is accessible through a confined space, such as a small diameter pipe, leading (e.g., deep) underground to an (e.g., a relatively small) access box positioned around the equipment. An underground equipment worker may carry around multiple long tools to control each type of underground equipment, which may have different dimensions. Access to and operation of underground equipment may be difficult, for example, when access lids, pipes, and/or equipment are damaged and/or when the ground has shifted an access pipe or box relative to the equipment. Lids and pipes may be damaged for years before being discovered. These problems may lead to a variety of obstructions (e.g., dirt, rocks, foliage, paper, pipe, broken pieces of lid or pipe) falling into an access pipe or box. Obstructions, access pipe or box shifts or damage may interfere with underground work. A worker may be unable to observe underground equipment or perform work without the assistance of a cleaning truck or excavation, leading to additional costs and delays.

SUMMARY

[0003] This Summary is provided to introduce concepts in a simplified form. These concepts are described in greater detail below in the sections entitled Detailed Description, Brief Description of the Drawings, Claims, and in the figures. This Summary is not intended to identify key or essential features of the described or claimed subject matter, nor limit the scope thereof.

[0004] Systems, methods, and instrumentalities are disclosed for a multipurpose underground tool that may be compact, universal, multi-purpose and/or reconfigurable. A variety of underground equipment in a variety of conditions at a variety of depths with a variety of operating interfaces may be remotely viewed, cleared of obstructions and controlled with one tool that may be broken down and stored in a compact case. A portable computer (e.g., an operator's cell phone), which may be held by the tool, may be used to power a lighted camera recessed in an actuator (e.g., valve key) and to display images of underground conditions provided by the camera, which may assist a user with operations (e.g., clear obstructions, maneuver, steer, attach to and operate underground equipment). Accessories may be adjusted, deployed/retracted, added or removed to accomplish a variety of tasks in a variety of conditions. Integrated, detachable, fixed or adjustable accessories may include, for example, a display holder, an ejector, a retriever, a debris deflector, a debris collector, a pressure tank, a pressure hose, actuators and/or other pole tips (e.g., with one or more accessories), pole sections, handles and/or accessory controls. Controls may be manual and/or automated.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] The drawings, summary, detailed description and claims individually and collectively

present non-limiting examples. Each figure represents a different example with different numbering.

[0006] FIG. 1 shows an example of a multipurpose underground tool, according to an embodiment.

[0007] FIG. 2 shows an example of a multipurpose underground tool, according to an embodiment.

[0008] FIG. 3 shows an example of a multipurpose underground tool, according to an embodiment.

[0009] FIG. 4 shows an example of a multipurpose underground tool, according to an embodiment.

[0010] FIG. 5 shows an example of a retractable collector, according to an embodiment.

[0011] FIG. 6 shows an example of a removable and repositionable debris deflector, according to an embodiment.

[0012] FIGS. 7A-D shows examples of accessories relative to actuators, according to an embodiment.

[0013] FIG. 8 shows an example of compact storage of a disassembled underground tool, according to an embodiment.

[0014] FIG. 9 shows a block diagram of an example computing device that may be used to implement example embodiments.

DETAILED DESCRIPTION

[0015] A detailed description of illustrative embodiments will now be described with reference to the various Figures. Although this description provides examples of possible implementations, it should be noted that details provided in examples are intended to be exemplary and in no way limit the scope of the application. The present technology may be practiced without these specific details. The present technology is intended to cover alternatives, modifications, and equivalents, which may be included within the spirit and scope the various embodiments as defined herein, including by the appended claims. In addition, in the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the present technology. However, the present technology may be practiced without these specific details. In other instances, methods, procedures, components, circuits, etc. known to those of ordinary skill have not been described in detail as not to unnecessarily obscure aspects of the embodiments presented.

[0016] References in the specification to “embodiment,” “example embodiment,” or the like, indicate that the embodiment described may include a particular feature, structure, characteristic or step, but every embodiment may not necessarily include the particular feature, structure, characteristic or step. Moreover, such phrases are not necessarily referring to the same embodiment. Furthermore, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to implement such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described.

[0017] Certain terms are used throughout the following description and claims to refer to particular system components and configurations. As one skilled in the art will appreciate, various skilled artisans and companies may refer to a component by different names. The discussion of embodiments is not intended to distinguish between components that differ in name but not function. In the following discussion and in the claims, the terms “including” and “comprising” are used in an open-ended fashion, and thus should be interpreted to mean “including, but not limited to . . .” Also, the terms “attached” and “coupled” are intended to mean either an indirect or direct connection.

[0018] Systems, methods, and instrumentalities are disclosed for a multipurpose underground tool that may be compact, universal, multi-purpose and/or reconfigurable. A variety of underground equipment in a variety of conditions at a variety of depths with a variety of operating interfaces may be remotely viewed, cleared of obstructions and controlled with one tool that may be broken down and stored in a compact case. A portable computer (e.g., an operator's cell phone), which may be held by the tool, may be used to power a lighted camera recessed in an actuator (e.g., valve key) and to display images of underground conditions provided by the camera, which may assist a user

with operations (e.g., clear obstructions, maneuver, steer, attach to and operate underground equipment). Accessories may be adjusted, deployed/retracted, added or removed to accomplish a variety of tasks in a variety of conditions. Integrated, detachable, fixed or adjustable accessories may include, for example, a display holder, an ejector, a retriever, a debris deflector, a debris collector, a pressure tank, a pressure hose, actuators and/or other pole tips (e.g., with one or more accessories), pole sections, handles and/or accessory controls. Controls may be manual and/or automated.

[0019] FIG. 1 is an example of a multipurpose underground tool, in accordance with an embodiment. FIG. 1 shows a multipurpose underground tool that may be used, for example, to view conditions, eject obstructions, deflect debris, collect debris, retrieve magnetic and non-magnetic obstructions, steer an actuator to dock with and/or operate an underground component (e.g., configured as an interface to operate underground equipment). FIG. 1 shows an example of underground tool **100** inserted under surface **146** (e.g., sidewalk, lawn, road) in access pipe **149** down to access box **168** (e.g., curb stop box) to access an underground component (e.g., operable valve nut **169** on valve stem **170** of curb stop valve **172** controlling flow in pipe **174**). The cutaway view in FIG. 1 shows access box **168** with obstructions **164** obstructing valve nut **169** in order to describe features of underground tool **100**.

[0020] Access pipe **149** and access box **168** provide a confined area to access and perform operations on an operable component of underground equipment without excavation. Access pipe **149** may be covered by a lid (not shown). A lid (e.g., when intact) may be removed from the top of access pipe **149**. Dimensions of access pipe **149** and access box **168** may vary. In an example, an interior diameter of access pipe may be less than three inches. A lid, access pipe **149** and access box **168** may comprise any material. In an example, a lid, access pipe **149** and access box **168** may comprise iron or plastic.

[0021] Pipe **174** and curb stop valve **172** may provide a controllable conduit, for example, for a vapor (e.g., natural gas) or a liquid (e.g., water). Pipe **174** and curb stop valve **172** may have a wide variety of dimensions (e.g., diameters), for example, for compliance with a wide variety of flow and flow control specifications. Valve **172**, valve stem **170** and valve nut **169** may comprise any material. In an example, valve **172**, valve stem **170** and valve nut **169** may comprise brass. Valve stem **170** and valve nut **169** may have a variety of dimensions and shapes. Valve nuts (e.g., valve nut **169**) may be operated (e.g., turned) to control (e.g., open, close) valves (e.g., valve **172**), for example, by one or more variable and/or a variety of fixed actuators (e.g., actuator **162**). An actuator may comprise, for example, a fitting (e.g., key) that mates with a valve nut.

[0022] Underground tool **100** may comprise, for example, user interface **106**, pole **113** and actuator **162**, with or without one or more accessories, e.g., lighted camera **158**, display **104**, first control **108**, second control **110**, first tank **129**, second tank **130**, pressure ejector **166**, first deflector **132**, second deflector **142** and/or collector **156**. Each of a wide variety of implementations may comprise any number of these and/or other accessories or components.

[0023] User interface (e.g., handle) **106** may serve several functions, such as (e.g., manual) control of actuator **162**, as an accessory platform (e.g., user interface), as a pressure conduit, as a wire and cable conduit, protective shield, etc. Control of an actuator may comprise, for example, manually rotating handle **106** to rotate actuator **162** and underground component **169** and/or resisting rotation of handle **106** during automated control of an active (e.g., motorized) actuator **162**. Handle **106** may comprise any material suitable for forces exerted on, in or by handle **106** (e.g., pure or alloy materials, such as iron, steel, aluminum, carbon fiber). Handle **106** may be any length (e.g., 30 inches). Handle **106** may have any width or diameter. Handle **106** may have grips. Handle **106** may be fixed length or variable length. Handle **106** may be configured to telescope, fold and/or may be configured (e.g., with connectors or couplers) for one or more segments to be added and/or removed. Handle **106** may have one or more segments and none or more couplers configured to connect and disconnect (e.g., couple and decouple, lock and unlock) handle segments. Handle **106**

or one or more segments thereof may be completely or partially solid (e.g., bar) and/or hollow (e.g., pipe). Handle **106** may have any shape (e.g., elongated, uniform, irregular, flattened, rectangular, curved, dished or concave). In an example, handle **106** may be configured to provide multiple grips (e.g., to lift, push, turn and otherwise manipulate underground tool **100**).

[0024] User interface (e.g., handle) **106** may have any cross section shape (e.g., round, square, regular polygon, irregular polygon). In an example, handle **106** may have angled or perpendicular protrusions (e.g., grips), not shown, extending upward and/or downward (e.g., from the ends of handle **106**). Handle **106** may be fixed to or removable from pole **113**. In an example, handle **106** may be configured with a stem **106a** joined or configured to be joined to first pole coupler **118**, which may be used to assemble and disassemble handle **106** and pole **113**. In an example, handle **106** may be removed from pole **113**. Handle **106** may be tethered to pole **113**, for example, by a sheath, operable cable(s), tether cable(s) and/or wire(s), which may be inside and/or outside pole **113** and handle **106**. In an example, handle **106** may be swapped for other handles (not shown), such as longer handles to induce more torque or a handle that may be driven by a mechanical (e.g., rotational) device. In an example, handle **106** may comprise handle segments (e.g., right, left) that attach to the top of pole **113** (e.g., tee shaped top of pole **113**). Handle **106** may be segmented or separable from pole, for example, to support breakdown and compact storage or protection (e.g., as shown by example in FIG. 8).

[0025] One or more accessories may be integrated with or coupled to (e.g., inside and/or outside) handle **106** or handle segments. In an example (e.g., as shown in FIG. 1), handle **106** may be configured with display holder **102**, which may hold display **104** (e.g., computing device with a display, such as a cellular phone or tablet computer). Display holder **102** may be fixed or variable (e.g., adjustable, direction, tilt, rotation, slide to position or fit, removable). In an example, display holder **102** may comprise a recess or compartment integrated with or attached to handle **106** (e.g., a wide handle with a recessed center). Display holder **102** may have a lid/cover, for example, to protect a display left attached to underground tool **100**. Display holder **102** may be variable (e.g., adjustable). In an example, display holder **102** may slide, spin and/or rotate in one or more dimensions, for example, to orient display **104** for user viewing. Display holder **102** may hold display **104**, for example, by clamp and/or strap. Display holder **102** may comprise, for example, slide spring-loaded clamp jaws to adapt to various dimensions of displays. Display holder **102** may comprise, for example, a cell phone mount (e.g., to a bike), such as a JDIBest-Bike Phone Mount, a Vibrelli® Universal Bike Phone Mount, a RAM Mounts® Tough-Claw Mount M with Universal X-Grip® phone mount, etc.

[0026] Display **104** may be fixed to or removable from display holder **102**. Display **104** (e.g., a computer) may serve multiple purposes, such as to provide power, communication, processing, user interface, display and so on. For example, display **104** may be coupled to camera cable **120**, for example, to provide power to lighted camera **158** and to receive still or video images from lighted camera **158**. As shown by example in FIG. 9, the computer may execute an underground tool program (UTP). Display **104** may display a UTP graphical user interface (GUI). A UTP GUI may display camera images and/or a menu for a user to selectively control one or more of camera settings and operation, the display of images from the camera, settings and/or operation of the actuator, settings and/or operation of the ejector, settings and/or operation of the retriever, settings and/or operation of the collector, and/or settings and/or operation of pole and/or actuator steering.

[0027] Display holder **102** may be coupled to handle **106**, for example, by display mount **114**. Handle **106** may be configured with first control **108**. First control **108** (e.g., retriever control, steering control, collector control) may be coupled to handle **106**, for example, by first mount **111**. Handle **106** may be configured with second control **110**. Second control **110** (e.g., retriever control, steering control, collector control) may be coupled to handle **106**, for example, by second mount **116**. Mounts (e.g., display mount **114**, first mount **111**, second mount **116**) may be fixed or removable and may couple or mount to handle **106**, for example, by clamp, weld, friction fit,

adhesive, fastener(s) or other fixed or removable mounts. In an example, handle **106** or handle segments may be configured (e.g., inside and/or outside) with, for example, one or more handle and/or pole couplers, segment retention cables or chords (e.g., solid or hollow sheaths), pressure couplers (e.g., when handle provides pressure conduit for a pressure source), sheaths, control wires and/or cables (e.g., first and second cables **112**, **124**), wire and/or cable terminations, camera cables (e.g., camera video and power cable **120**).

[0028] Pole **113** may provide reach and mechanical force (e.g., torque) conveyance between handle **106** and actuator **162**. Pole **113** may comprise any material suitable for forces exerted on, in or by pole **113** (e.g., pure and/or alloy materials, such as iron, steel, aluminum or carbon fiber). Pole **113** may be any length (e.g., eight feet). Pole **113** may be fixed length or variable length. In an example, pole **113** may telescope (e.g., with one pole inside another) and/or the number and/or length of segments may be variable, e.g., by adding or removing segments. Pole **113** may have any width or diameter that fits inside one or more underground equipment access pipes. Pole **113** may have one or more segments (e.g., discrete or telescoping sections) and none or more couplers configured to connect and disconnect (e.g., assemble and disassemble or lock and unlock) pole segments. Pole **113** or one or more segments thereof may be completely or partially solid (e.g., bar), hollow (e.g., pipe), and/or may have a honeycomb or other structural fill. Pole **113** may have any cross section shape (e.g., round, square, regular polygon, irregular polygon). In an example (e.g., as shown in FIG. 1), pole **113** may be segmented, for example, to support breakdown and compact storage and protection (e.g., as shown by example in FIG. 8). In an example, pole **113** may comprise a pipe with first, second and third segments **133**, **147**, **155**, which may be coupled and decoupled (e.g., broken down), respectively, by second and third pole couplers **140**, **150**.

[0029] One or more accessories may be integrated with or coupled to (e.g., inside and/or outside) pole **113** or pole segments **133**, **147**, **155**. In an example, third pole segment **155** may comprise a rigid pipe section and/or flexible/steerable pipe section **155B** (e.g., as shown in example **100D**). In an example, pole **113** or first through third pole segments **133**, **147**, **155** may be configured with first through fourth pole couplers **118**, **140**, **150**, **160**, pressure couplers **125** and **126** (e.g., configured to couple to first and second tanks **129**, **130**, pressure hose and/or other pressure source), cable termination **122**, first deflector **132**, second deflector **142** (e.g., with or without vacuum **144**), sheath **154** and/or collector **156** (e.g., as retracted or undeployed collector **156** or deployed collector **156B**), actuator **162**, ejector **166**, and/or accessories that may be coupled to handle **106** or pole **113**. An accessory mountable to handle **106** may be (e.g., alternatively or additionally) mountable to pole **113**, for example, with or without an adaptor, positioning device or pole segment.

[0030] One or more accessories, wires, cables, sheaths, tubes or components may be coupled to or on (e.g., along) or confined by the exterior and/or interior of pole **113**, handle **106** or one or more segments thereof. In an example, an interior and/or exterior of pole **113** and/or handle **106** may comprise, for example, sheath **154**, power wire(s) or cable(s) (e.g., camera video and power cable **120**), communication wire(s) or cable(s) (e.g., camera video and power cable **120**), retrieve control wire(s) or cable(s) (e.g., first or second control cable **112**, **124**), steering control wire(s) or cable(s) (e.g., first or second control cable **112**, **124**), ejector pressure tube(s) and/or other wire(s), cable(s), tube(s) and/or component(s) (e.g., transceiver, power supply, steering servo, retriever piston, collector piston, actuator servo, ejector valve). A sheath (e.g., sheath **154**) may partially or completely shroud (e.g., encircle) one or more wires, cable and/or tubes (e.g., as shown by example in FIG. 5). A sheath may be inside pole **113** or may be coupled (e.g., clamped, banded, zip tied) to exterior of pole **113**, handle **106** or one or more segments thereof. In an example, accessories, wires, cables, sheaths, tubes or components may be flexible, removed, disconnected, etc., for example, to support compact storage.

[0031] Sheath **154** may serve multiple purposes, such as confinement and/or protection of wires, cables, springs, rods, etc., with or without (e.g., also) providing retention of pole segments and

handle when disassembled (e.g., as shown by example in FIG. 8). Sheath **154** may comprise, for example, an open, closed, closable (e.g., zippered) sleeve. Sheath **154** may comprise any material and construction suitable for rigidity, flexibility and/or other conditions for an implementation (e.g., fixed length pole, segmented pole). Sheath **154** may comprise, for example, fabric, braided or woven yarn, fiber or filament comprising, for example, stainless steel, Nylon, Ballistic Nylon, Polyester, Polyethylene Terephthalate (PET), Silica, Fiberglass, Basalt or Polyaramid Polymetaphenylene Isophthalamide. Sheath **154** may be mounted inside and/or outside handle **106**, pole **113** and actuator **162**. In an example, sheath **154** may shield one or more of power and/or communication wire(s) or cable(s), retrieve control wire(s) or cable(s), steering control wire(s) or cable(s) and/or one or more other control, power or communication wire(s) or cable(s). Sheath **154** may confine and/or protect, for example, first control cable **112**, second control cable **124**, lighted camera cable **120** and/or other control wires, cables, springs, rods, etc. There may be any number of cables, wires, linkages, etc. inside and/or outside sheath **154**. Sheath **154** and/or (e.g., alternatively) a cord, wire or cable may operate to keep disassembled first, second and third pole segments **133**, **147**, **155** together with or without handle **106**, for example, as shown by example in FIG. 8.

[0032] Actuator **162** may be configured or configurable to operate underground equipment, for example, by moving an underground component. An example of an underground component may be, for example, operable valve nut **169** on valve stem **170** of curb stop valve **172** controlling flow in pipe **174**. Valve nut **169** may be moved (e.g., rotated), for example, by actuator **162**, to control flow in pipe **174**. Force applied to actuator **162** may be manual and/or automated. Manual force may be applied, for example, by applying force to (e.g., turning) handle **106**, which, in turn, may apply (e.g., rotational) force to pole **113** and actuator **162**. Force may be automated, for example, by an electromechanical, hydraulic or pneumatic device coupled to actuator **162**, pole **113** and/or handle **106**. In an example, an electrical, hydraulic or pneumatic servo may be integrated in or coupled to actuator **162** and controlled by a user (e.g., by a servo control on handle **106**, pole **113** or elsewhere, such as a UTP GUI control). Actuator **162** may comprise, for example, a thread-on, pin lock, quick connect (QC) or other coupler to pole **113** and/or to fourth coupler **160**.

[0033] Actuator **162** may be fixed or variable, e.g., in terms of shape(s), size(s), pattern(s). In an example, an actuator may comprise a shape keyed to fit an underground component (e.g., a mated fit). For example, an underground component may comprise a raised (e.g., head or nut) portion while an actuator may comprise a slotted, socket or jaws portion that fits multiple sides of the raised portion, e.g., in order to fit and impart mechanical or other force. A variable actuator may be used, for example, to control multiple types of underground components that may vary in size, shape and/or pattern. An actuator may be varied, for example, by manually or automatically changing shape (e.g., narrowing or widening spacing of jaws). Actuator variation may be controlled, for example, by a control on a handle (e.g., a grip, dial or button controlling a mechanical linkage, pressure in a hydraulic tube or a signal on a wire inside pole **113** leading to a servo motor coupled to one or more actuator jaws). Actuator **162** may be permanently or temporarily/removably mounted to pole **113**. In an example, actuator **162** may be mounted to a coupler (e.g., fourth pole coupler **160**) that may be coupled to and decoupled from pole **113**. Fourth pole coupler **160** may permit actuator **162** to be removed, for example, for maintenance, replacement and/or to swap for a different actuator. Actuator **162** may comprise any material suitable for environment parameters (e.g., pressures, gases, liquids, applied forces, temperatures). In an example, actuator **162** may comprise, for example, stainless steel. Actuator **162** may comprise components, such as a body and a key, where multiple keys may be swappable onto the same body. Keys may comprise one or more cut outs or holes that align with one or more accessories, such as cameras, pressure ejector ports, retrievers and so on.

[0034] One or more accessories may be integrated with or coupled to (e.g., inside and/or outside) actuator **162**, for example, as shown and discussed with greater detail in FIGS. 7A-D. An actuator

may be configured, for example, for a coupler, light(s), camera(s), servo, ejector(s) (e.g., gas and/or liquid pressure port(s)), collector(s) and/or retriever(s). In an example, actuator **162** may be configured with coupler **160**, lighted camera **158**, ejector **166** (e.g., to view and eject obstructions as shown in call out **100A**), grab or stab retriever **176** (e.g., as shown by example in call out **100B**), magnetic retriever **178** (e.g., as shown by example in call out **100C**) and/or flexible or steerable portion (e.g., as shown by example in call out **100D**). An actuator and/or flexible portion of pole **113** (e.g., a pole tip) may be steerable (e.g., as shown in callout **100D**).

[0035] There may be a variety of accessories. Accessories may be integrated, detachable, fixed or adjustable. Accessories may include, for example, a display holder, an ejector, a retriever, a debris deflector, a debris collector, a pressure tank, a pressure hose, actuators and/or other pole tips (e.g., with one or more accessories), pole sections, handles, accessory controls, etc.

[0036] Couplers **118, 125, 126, 140, 150, 160** may serve multiple purposes, such as assembly and disassembly of one or more configurations of (e.g., additional, replaceable, swappable) components, compact storage, pressure conveyance, conduit path and so on. Couplers **118, 125, 126, 140, 150, 160** may be the same or different. Couplers may comprise any type of coupler. Couplers may have any size or shape. Couplers may comprise any material, e.g., stainless steel. Coupler components may or may not be linked together (e.g., by a retainer such as a hinge or cable). In an example, a coupler may comprise a quick coupler. A coupler may be, for example, a pneumatic or hydraulic coupler, which may have a pressure rating. Pressure ratings for conduit (e.g., pipe), coupler(s) and pressure port(s) (e.g., actuator port) may be suitable for a pressure that may be applied by a pressure source (e.g., first and/or second pressure tanks **129, 130**) to eject pressurized gas or liquid through one or more ports (e.g., in actuator **162**). In an example, handle **106**, each end of first, second and third pole segments **133, 147, 155**, other segments (e.g., as shown in FIG. **8**), actuator **162** and/or other actuators (e.g., as shown in FIG. **8**) may be coupled to a pressure-rated coupler, such as a Dual-Lock™ P-Series Thor Interchange pneumatic coupler manufactured by Dixon Valve & Coupling Company, Inc. In an example, first and second pressure couplers **125, 126** may comprise a quick coupler for a High pressure Air (HPA) source (e.g., tank via a hose or a direct-coupled tank filled with compressed Nitrogen or air), a Carbon Dioxide (CO₂) source (e.g., tank via a hose or a direct-coupled tank filled with compressed liquid CO₂) and/or other source. Couplers may couple and decouple handle **106**, pole **113** and actuator **162** and/or other components while supporting (or not interfering with) accessories they may be configured with (e.g., sheath or retention cord or cable, camera, pressure port, collector, retriever(s)).

[0037] Collars or clamps (e.g., as shown by examples in FIGS. **1, 6** and **8**) may be coupled to one or more portions (e.g., segments or sections) of pole **113**, for example, to stabilize, position, hold-release, couple-decouple, attach-detach, retain and/or permit movement of one or more accessories (e.g., first and second deflectors **132, 142**, collector **156**). Collars or clamps may be fixed or movable. Collars or clamps may be captured or retained (e.g., adjustable or fixedly attached to a pole segment) or may be removable in one or more steps. Collars or clamps may be quick release. Collars or clamps may slide (e.g., by releasing compression and/or friction fit to pole **113**). Collars or clamps may be multi-purpose or specific purpose (e.g., sized and/or shaped to fit and/or retain one or more accessories). In an example, a (e.g., removable or slidable) collar or clamp may be positioned on a pole segment above and below an accessory (e.g., second deflector **142**) (e.g., as shown by example in FIG. **6**). In an example, one or more collars or clamps may comprise one or more holding components (e.g., expandable jaws, flexible strap(s), clamps) that may hold one or more accessories (e.g., with a single collar or clamp). An accessory or other component may be added to pole **113**, for example, by positioning or relocating (e.g., sliding) one or more collars to hold the accessory or component. A collar or clamp may be configured, for example, to position an accessory, hold an accessory, retain an accessory while permitting it to move (e.g., rotate, spin, deploy, retract and so on).

[0038] Pressure source(s) may be coupled to underground tool **100**, for example, when underground tool **100** is configured with one or more pressure ejectors/ports. A pressure source may be coupled to a pressure ejector by pressure conduit. Underground tool **100** may comprise internal and/or external pressure conduit. In an example, pressure conduit (e.g., flexible pressure conduit) between pressure control and pressure ejector(s)/port(s) may be mounted inside and/or outside of one or more of handle **106**, pole **113** and/or ejector **162**. In an example, the inside walls of one or more of handle **106**, pole **113** actuator **162** and couplers (e.g., first through fourth pole couplers **118**, **140**, **150**, **160**) may be configured as pressure conduit to convey pressurized liquid or gas from a source to an ejector. First and second pressure couplers **125**, **126** may (e.g., each) be coupled, for example, indirectly to a pressure source such as a pressure hose leading to a pressure source (e.g., one or more tanks or compressors). First and second pressure couplers **125**, **126** may be coupled, for example, directly, to a pressure source. A pressure source may comprise pressure tank(s), such as first and second tanks **129**, **130**. First and second tanks **129** may be any size or shape. First and second tanks **129**, **130** may supply pressurized gas or may be an expansion tank (e.g., to assist with controlling application of pressure). In an example, first and/or second tanks **129**, **130** may (e.g., each) comprise a pressure bottle or tank, such as, for example, a High Pressure Air (HPA) container, which may be filled with compressed Nitrogen or air, or a Carbon Dioxide (CO₂) container, which may be filled with compressed liquid CO₂. In an example, first tank **129** may comprise a 13 to 125 cubic inch (CI), 3000 to 4500 psi HPA tank (e.g., manufactured by Tippmann®). Pressure ejector(s)/port(s) **166** may comprise, for example, one or more portions on or in actuator **162** (e.g., a port on either side of camera in recessed portion/channel of actuator **162**). Pressure control/activation may comprise, for example, a button, handle, lever (e.g., first and second pressure control **127**, **128**). Pressure ejection system may comprise one or more safety features, such as an auto lock to block activation. A safety lock may be deactivated, for example, by pressing or moving a safety to permit movement of first and/or second pressure control **127**, **128**.

[0039] Collector(s) may be deployed on pole **113** to collect debris in access pipe **149**, such as debris **152** ejected by ejector **166** and/or to catch items falling through an open access pipe **149**. Collectors may be fixed or variable (e.g., deployable, retractable, resizable). In an example, retracted collector **156** may be deployed (e.g., as deployed collector **156B**), for example, after ejecting pressurized gas or liquid through ejector **166** and/or while a user has underground tool **100** inserted in access pipe **149** (e.g., to catch anything that falls into access pipe **149**). Underground tool **100** may be withdrawn from access pipe **149** to empty the contents of collector **156**. Pole **113** may be fitted with any number of collectors. In an example, pole or one or more segments thereof, may be fitted with a series of collectors. A collector may have any shape (e.g., an inverted cup with solid or perforated/screen walls). A collector may comprise any material(s), such as flexible materials (e.g., rubber, plastic, fabric, carbon fiber) and/or rigid materials (e.g., metal, plastic). Collector(s) may be fixedly or removably attached to pole **113** or a segment thereof, for example, by one or more collars or clamps.

[0040] FIG. 5 is an example of a retractable collector, according to an embodiment. Collector **556** mount to pole **513** may be fixed or variable (e.g., removable, repositionable). Collector **556** may be deployed automatically or manually by a user interacting with a control. A control (e.g., button, knob, lever, UTP GUI) may be coupled (e.g., mechanically, electrically or electromechanically) to one or more collectors. In an example, collector **556** may be coupled to control rods **502**, **504**. A user may deploy and retract collector **556**, for example, by causing control rods **502**, **504** to push and pull (e.g., or vice versa) or rotate (e.g., twist) clockwise and counterclockwise (e.g., or vice versa). In an example, control rods **502**, **504** may be segmented with hinge points **506**, **508**. Lower segments **510**, **512** may have a retracted position and a deployed position (**510b**, **512b**). Lower segments **510**, **512** may cause collector **556** to deploy (**556b**) and retract as hinge points **506**, **508** are pushed down and pulled up. In some examples, a user may use a UTP GUI to control a piston or servo coupled to collector linkages to deploy and retract one or more collectors.

[0041] Deflectors may deflect or steer debris. One or more deflectors may be used to deflect or steer debris removed from an access pipe. Deflectors may mount to or may surround part or all of pole **513**. Deflectors may be fixed or variable (e.g., removable, repositionable). Deflectors may be fixed, variable, deployed automatically or manually by a user interacting with a control. A control (e.g., button, knob, lever, UTP GUI) may be coupled (e.g., mechanically, electrically or electromechanically) to one or more deflectors. In some examples, a user may use a UTP GUI to control a piston or servo coupled to deflector linkages to deploy and retract one or more deflectors. The example shown in FIG. 1 presents two examples, first deflector **132** and second deflector **142**.

[0042] First deflector **132** may be configured (e.g., shaped, sized), for example, to deflect or steer debris **136** that may be ejected from access pipe **168** by ejector **166**, for example, when pressurized air, gas or liquid is ejected in access pipe **149**. Deflector shape may be fixed or variable (e.g., deployable in one or more increments, retractable, resizable). First deflector **132** may be configured or shaped (e.g., as an inverted cone or other configuration/shape) to permit debris to continue traveling upward while directing, steering or deflecting debris away from a user operating underground tool **100**. First deflector **132** may be implemented with any material(s) suitable to its purpose (e.g., to deflect or steer ejected debris). In an example, first deflector **132** may comprise rubber, plastic, metal, nylon and/or other suitable rigid and/or flexible material(s) configured to absorb, dampen, steer or deflect exhaust and/or debris. Deflector size may be fixed or variable. In an example, cone angle and/or diameter may be increased and decreased (e.g., deployed and retracted for compact storage). Position, size (e.g., diameter) and/or shape (e.g., incremental deployment or retraction) changes may occur, for example, by (e.g., manual or automated) rotating, twisting, pulling, pushing or other action. In an example, twisting a deflector may change its diameter. In an example, first deflector **132** deflection angle and diameter may be adjusted, for example, by sliding a collar on pole **113** to open or close an inverted cone (e.g., similar to opening and closing an umbrella). First deflector **132** may be permanently or removably mounted to pole **113** or a segment thereof. First deflector **132** position on pole **113** or segment thereof may be fixed or variable, for example, to adjust a position of first deflector **132** above surface **146** for different lengths of pole **113** underground (e.g., for different depths of operable components). In an example, first deflector **132** or a collar, clamp or other deflector mount may slide up and down or otherwise move position on pole **113** or segment thereof. Moving a collar, clamp or other mount may operate to move (e.g., position, reposition), deploy, retract, resize and/or reshape first deflector **132**.

[0043] Second deflector **142** may be configured (e.g., shaped), for example, to deflect or steer debris **136** (e.g., ejected from access pipe **168** by ejector **166**, which may comprise one or more pressure ports). Deflector shape may be fixed or variable. Second deflector **142** may, for example, have a shape that steers debris in a general direction and/or in a confined area, which may support capturing debris (e.g., in a net or vacuum **144**). Second deflector **142** may be implemented with any material(s) suitable to its purpose (e.g., to deflect or steer ejected debris). In an example, first deflector **132** may comprise rubber, plastic, metal, nylon and/or other suitable rigid and/or flexible material(s) configured to absorb, dampen, steer or deflect exhaust and/or debris. Deflector size may be fixed or variable. In an example, a shape (e.g., deflection angle) and/or size (e.g., exhaust diameter) may be increased and decreased (e.g., deployed and retracted for compact storage). Position, size and/or shape changes may be implemented, for example, by (e.g., manual or automated) rotating, twisting, pulling, pushing or other action. In an example, second deflector **142** may be permanently or removably mounted to pole **113** or a segment thereof. Second deflector **142** position on pole **113** or segment thereof may be fixed or variable, for example, to adjust a position of second deflector **142** above surface **146** for different lengths of pole **113** underground (e.g., for different depths of operable components). In an example, second deflector **142** or a collar, clamp or other deflector mount may slide up and down or otherwise move position on pole **113** or segment thereof (e.g., as shown by example in FIG. 6). Second deflector **142** may be configured to seal to a surface (e.g., surface **146**) or otherwise minimize air or debris leakage outside of a configured

debris deflection path.

[0044] FIG. 6 is an example of a removable and repositionable debris deflector, according to an embodiment. Multi-part deflector **600** may comprise multiple pieces (e.g., first half **610** and second half **615**), which may be assembled and disassembled (e.g., separated and pressed together, such as around pole **113**). First and second halves **610**, **615** may have edges **605** that fit together (e.g., sinusoidal, square or rectangular protrusions and depressions aligned or keyed to fit together). First and second halves **610**, **615** may comprise upper and lower pole adapters **630**, **635** that fit to pole **113**. FIG. 6 shows side and top views of first and second halves **610**, **615** pressed together around pole **113**. Multi-part deflector **600** may fixedly or variably attach (e.g., clamped) to pole **113**. Collars, clamps, elastic bands, tethered snaps or other coupling devices may be used to hold first and second halves **610**, **615** of multi-part deflector **600** together (e.g., for storage or around pole **113** for use). For example, a buckle strap may be cinched around first and second halves **610**, **615** to press them together. In an example (e.g., as shown in FIG. 6), clamps may comprise first and second pinch clamps **620**, **625** that fit around upper and lower pipe adapters **630**, **635**. Moving a collar, clamp or other mount may operate to move (e.g., position, reposition), deploy, retract, resize and/or reshape multi-part deflector **600**. For example, a user may pinch first and second pinch clamps **620**, **625** to slide them up and down with or without also moving first and second halves **610**, **615** to attach, remove or reposition multi-part deflector **600** to, from or on pole **113**. In an (e.g., another) example, clamps (e.g., one or more fixed or removable buckle clamps) may be fixed to or removable from first and second pole adapters **630**, **635** or other portions of first and second halves **610**, **615** (e.g., at or above base and exhaust port).

[0045] Second deflector **142** may be utilized with or without a supporting device, such as vacuum **144**. Vacuum **144** may comprise a coupler (e.g., a fitting), such as vacuum tube **138**, that may be coupled to and decoupled from second deflector **142** to induce airflow (create a draft) from access pipe **149** through second deflector **142**. In an example, a user may control first or second pressure tanks **129**, **130** (e.g., by turning first or second pressure controls **127**, **128**) to eject pressurized gas or liquid through one or more ports of ejector **166** to displace obstructions **164** while vacuum **144** assists with debris extraction by sucking air (and rising debris **148** stirred up by ejector **166**) out of access pipe **149** and through second deflector **142**. Second deflector **142** may comprise a base (e.g., base **143**), for example, to rest on surface **146**. In an example, base **143** may be weighted, deformable and/or may comprise a gasket (e.g., to seal against surface **146**). In an example, base **143** may be flexible, for example, to maintain a seal or approximate seal to surface **146** when it may be uneven. In an example, base **143** may comprise a wide flange that may support a weight, such as a sandbag. Second deflector **142** may comprise a top and bottom gasket to seal to pole **113**.

[0046] Second deflector **142** may serve multiple purposes. Second deflector **142** may support the weight of underground tool **100**. In an example, second deflector **142** may operate as a stand, for example, to relieve a user from supporting the weight of underground tool **100** (e.g., while viewing conditions, ejecting obstructions, deflecting and/or collecting debris, retrieving obstructions). Second deflector **142** may, for example, rest on surface **146** with or without being attached to pole **113**. Pole **113** may be moved up and down with second deflector **142** in place (e.g., with or without a gasket to minimize airflow through a gap between pole **113** and the top of second deflector **142**). Second deflector **142** may comprise a spring-loaded, pivoting support for underground tool **100**, for example, to allow a user to press down (e.g., pulling a first set of springs), pull up on (e.g., pulling another set of springs) or move (e.g., rotate and/or angle) handle **106** and pole **113** (e.g., while base **143** remains in contact with surface **146**). In some examples, first and second pole adapters **630**, **635** may be enlarged flexible rubber boots with springs therein to allow pole **113** to move up, down and/or side to side (e.g., within multipart deflector **600**). Spring-loading and pivoting may permit a user to manipulate underground tool **100** with less stress and fatigue while performing various operations, such as, for example, mating actuator **162** to valve stem **170**, moving actuator around to view the access box **168** and/or obstructions **164**, selecting a different angle before ejecting

pressurized gas or liquid through ejector **166**, aiming pole tip towards an obstruction or debris to pick up (e.g., via magnet, grab or stab) and so on. In an (e.g., additional or alternative) example, an additional accessory base for underground tool **100** may comprise, for example, a pivoting, spring-loaded base (e.g., a tripod), configured to rest on surface **146**.

[0047] A camera may be implemented in and/or on underground tool **100** to support a variety of operations, such as viewing the state of access pipe **149**, access box **168**, access equipment (e.g., pipe **174**, valve **127**, valve stem **170**), viewing obstructions **164**, clearing obstructions **164**, maneuvering underground tool **100**, steering actuator **162**, attaching to and operating underground equipment, etc. A camera may be implemented with or without lighting. A camera may be powered by any energy source (e.g., battery, generator, inverter coupled to vehicle power plug, transformer coupled to AC outlet). A camera may comprise a CCD, CMOS, NMOS or other camera sensor that sense one or more light wavelengths with or without LED lights that emit one or more light wavelengths (e.g., visible, IR). A camera may communicate (e.g., still or video images, control) wirelessly and/or by wire, e.g., to a computer for processing and/or display. A camera may be mounted, for example, on or in pole **113** and/or on or in actuator **162**. In an example, lighted camera **158** may be mounted outside actuator **162**. Lighted camera cable **120** may connect lighted camera **158** to display **104**. Lighted camera cable **120** may comprise, for example, a USB cable. Lighted camera cable **120** may run inside and/or outside actuator **162**, pole **113** and handle **106**). Display **104** (e.g., user cell phone) may provide power and control signals (e.g., for lights and camera) to lighted camera **158** and receive still and/or video images from lighted camera **158** via lighted camera cable **120**. Camera and light control software may be stored on and executed by display **104**. In an example, lighted camera **158** may comprise, for example, an endoscope/borescope with software operable on an Android operating system (e.g., a known camera such as a Pancellent® USB endoscope/borescope with a software application for a smart phone or other computer operating system). A built-in controller may permit a user using display **104** (e.g., a smart phone with a touch screen display) to control light brightness, record video, take photos, etc. A camera and/or lighting may be controlled by a user, for example, using a camera application GUI for the camera executed by the computer and/or a UTP GUI with camera and/or lighting controls.

[0048] Example underground tool **100** is shown deployed in an access pipe **149** and access box **168** with an underground component (e.g., valve nut **169**) obstructed by obstruction(s) **164**.

Obstruction(s) **164** may comprise any type of debris, such as one or more pieces of metallic and/or non-metallic debris (e.g., dirt, rocks, foliage, paper, pipe, broken lid or pipe), liquid (e.g., water), etc. A person operating underground tool **100** may observe obstruction(s) **164**, for example, by attaching a cellular phone, tablet or other computing device with a display to underground tool **100**. In an example, a cell phone may be inserted into computer or display holder **102** and attached to lighted camera cable **120**. The cell phone may provide power to lighted camera **158** through lighted camera cable **120**. A person (e.g., user, operator) may open a software application on the phone to view and/or control lighted camera **158**. Lighted camera **158** may shine any type of light (e.g., visible, infrared) and may provide imagery for display by cell phone display **104**. A user may, for example, observe obstruction(s) **164** or unobstructed underground component (e.g., valve nut) **169**.

[0049] Example underground tool **100** shows an example use involving a release of pressurized gas **167** through ejector **166**. Pressure **167** may be released, for example, by turning first pressure control **127** and/or second pressure control **128**, or by using a UTP GUI control that causes the computer to signal a servo or valve for one or more (e.g., timed) ejections. Pressure may be released from first and/or second tanks **129**, **130** through pole **113** and/or through pressure conduit inside and/or outside pole **113** before being ejected through ejector **166** into access box **168** and/or access pipe **149**. Arrows above obstruction **164** illustrate pressurized gas **167** forcing part or all of obstruction(s) **164** upward from access box **168** into access pipe **149**. Example **100** shows rising debris **148** traveling upward in access pipe **149** before becoming ejected debris **136** upon exiting

access pipe **149**. Ejected debris **136** may be deflected (e.g., away from the upper body of one or more persons in the vicinity) by a deflector (e.g., first deflector **132**, second deflector **142** and/or any other type of deflector). Vacuum **144** may assist with extraction of rising debris **148**, for example, by providing suction through second deflector **142**. A portion (e.g., tube or lip) of vacuum **144** may be configured to fit inside and/or outside a portion (e.g., tube or lip) of second deflector **142**. Some rising debris may not become ejected debris **136** and may, instead, fall. Falling debris **152** may be captured or collected **172** (e.g., by one or more debris collectors, such as collector **156**), for example, before continuing to fall where it could re-obstruct valve nut **169**, valve stem **170** or valve. Collector **156** is shown as undeployed collector **156** and deployed collector **156B**. Collector **156** may remain undeployed, for example, until after pressurized gas **167** is emitted to permit debris to rise above collector **156**. Collector **156** may deploy **156B** (e.g., automatically) in response to pressure and/or a timer following pressurized ejection (e.g., selected using a UTP GUI) or may be deployed manually (e.g., by a person interacting with a collector control on handle **106** and/or pole **113**). Collected debris may be extracted, for example, by removing pole **113** from access pipe **149** and dumping out collector **156**. Example underground tool **100** may operate valve nut **169**, for example, after clearing obstruction(s) **164**.

[0050] Callout **100A** (e.g., as discussed above) shows an example of operation for viewing an ejecting obstructions. FIG. **1** shows other examples of operation, such as retrieving obstructions by gripping or piercing an obstruction in callout **100B**, retrieving an obstruction by magnetization in callout **100C**, and steering, docking and operating in callout **100D**. Additional examples of configurations and accessories that may be associated with downhole operations are shown in callouts **100B**, **100C**, **100D**, FIGS. **2-4** and FIGS. **7A-D**.

[0051] Callout **100B** shows an example of underground tool **100** configured to retrieve an obstruction, such as obstruction **165** that may be too large and/or too heavy to eject and deflect or to displace and capture (e.g., in deployed collector **156B**). Obstruction **165** may be metallic or non-metallic. An underground tool (e.g., underground tool **100**) may be equipped with a (e.g., retractable) retriever that may, for example, grab, pierce/stab or scoop an obstruction, which may be removed from access pipe **149** by removing the underground tool. A retriever may be mechanical or electromechanical. A retriever control may comprise, for example, first control **108** or second control **110**. A mechanical retriever control (e.g., joystick, squeeze handle) may be coupled by a mechanical connector or linkage (e.g., cable(s), rod(s), wire(s)) inside and/or outside pole **113** to a retriever (e.g., pincers, jaws, gripper, sharpened and/or serrated/barbed prong(s)) deployable at or near the tip of pole **113** and/or actuator **162**. A UTP GUI may provide automated control for operation of one or more retrievers (e.g., operated by a piston or servo signaled by the computer). A retriever may comprise any material and any configuration to retrieve debris. Retriever connector(s) may, for example, be inside sheath **154**. A controller (e.g., first control **108**) may control, for example, extension and retraction of one or more claws or prongs (e.g., spring steel) by (e.g., manual or automated) twisting, untwisting, pulling and/or pushing (e.g., increasing and/or decreasing tension in or displacing or moving) one or more retriever connectors that transfer energy to a retriever. In an example, multiple pre-bent (e.g., spring steel) prongs may be mounted to one or more spring-loaded hinges. Prongs may be pushed out, for example, by pressing on control **108** and may be retracted by releasing or pulling back on control **108**. In an example, a spring-loaded hinge may open up when pressed outside a confined area, causing prongs to spread open. In an example, pre-bent or pre-stressed spring steel prongs with or without a spring-loaded hinge may spread open when pressed outside a confined space. Prongs **176** may (e.g., when extended then retracted) grab and hold onto an object, e.g., obstruction **165**, for example, when retriever control **108** is released or pulled back, causing prongs to draw back together. One or more prongs **176** may (e.g., alternatively) be sharpened or pointed to pierce or stab debris. In an example, a connector may comprise a throttle cable coupled to a retriever (e.g., pincers, jaws, gripper, sharpened and/or serrated/barbed prong(s)) operated (e.g., by a retriever control) to grab, or

pierce/stab one or more obstructions (e.g., paper, leaves, plastic debris).

[0052] Callout **100C** shows an example of underground tool **100** configured to retrieve an obstruction, such as obstruction **165** that may be too large and/or too heavy to eject and deflect or to displace and capture (e.g., in deployed collector **156B**). Obstruction **165** may comprise a metallic material attracted to magnets. Access pipes and lids may be constructed from iron, for example. Pieces of damaged pipe and/or lids may fall into access pipe **168** and may obstruct access to underground component **169**. In an example, underground tool **100** may be equipped or configured with magnetized retriever **178** that may, for example, attract and hold magnetic obstruction **165**. In an example, one or more magnets may be embedded in or mounted to actuator **162** and/or one or more portions (e.g., tips) of actuator **162** may be magnetized (e.g., as shown by example in FIGS. 7A-D). Magnets may comprise, for example, fixed (e.g., always on) or permanent magnets, electrically switched magnets such as electromagnets, mechanically switched magnets (e.g., Magswitch®) and so on. Switchable magnets may be coupled to a user control (e.g., first control **108**, second control **110**) via electrical and/or mechanical connector(s) to convey control to switchable magnets. IN some examples, a user may use a UTP GUI to operate a magnet retriever. Obstruction **165** may be removed from access box **168** and access pipe **149** by withdrawing underground tool **100** while magnetized retriever **178** holds obstruction **165**.

[0053] Callout **100D** shows an example detail of underground tool **100** configured with a steerable pole section and/or steerable actuator. Access pipe **149** and/or access box **168** may be misplaced and/or may shift or even break, for example, due to improper packing, loading, freeze/thaw cycles or other ground shifting. Deformed (e.g., broken, shifted) access pipe **149B** and/or deformed access box **168B** may prevent access to and/or control of underground component **169** with a straight, inflexible pole and actuator. In an example, actuator **162** may be coupled (e.g., directly or indirectly) to flexible pole section **155B**, which may configure actuator **162** to be steerable in one or more directions. Steering may be manual and/or automated. In an example, one or more steering connectors (e.g., rods, wires, cables, spring steel) may be coupled between actuator **169** and/or to flexible pipe **155B** and one or more controls. In an example, one or more (e.g., one, two, three, four) steering connectors may be coupled to steering or other control (e.g., control **110** on mount **116** on handle **106** or pole **113**). In some examples, a steerable pole section and/or actuator may (e.g., only) move in one or two directions given that a user may physically move or rotate pole **113**. Steering connector(s), such as first or second control cables **112**, **124**, may, for example, be inside sheath **154**. In an example, second control **110** may control a flexible pole section (e.g., flexible pole section **155B**) and/or actuator **162**, for example, by twisting, untwisting, pulling and/or pushing (e.g., increasing and/or decreasing tension in or displacing or moving) one or more connectors, thereby steering actuator **162**. In some examples, a user may use a UTP GUI or a computerized joystick control to control one or more servos or pistons to steer flexible pole section **155B** and/or actuator **162**. A further example of steerable pole section and/or actuator is shown in FIG. 3.

[0054] FIGS. 1-4 show several of many possible configurations of underground tool **100**. There may be many different configurations for each component. Component types, shapes, functions, controls, locations, etc. may vary among many different implementations. FIGS. 1-4 show a few examples of many different configurations of user interface (e.g., handle) **106**, pole **113** (e.g., as fixed or flexible-steerable segments), actuator **162** (e.g., as fixed or steerable) and accessories (e.g., controls, couplers, tanks, etc.). There are many more implementations beyond examples shown, made evident to one of ordinary skill by examples and discussion herein. A brief discussion is provided for comparison of examples shown in FIGS. 1-4.

[0055] As shown in FIG. 1, first example underground tool **100** is shown with handle **106** comprising first and second (e.g., mechanical or electromechanical) controls **108**, **110** on first and second mounts **111**, **116** and display **104** on display holder/mount **102**. First and second control cables **112**, **124** and lighted camera cable **120** are shown in conduit, sheath or sleeve **154** in pole

113, for example, exiting pole **113** under first pole coupler **118** at cable termination **122**. Pole **113** is shown with first and second tanks **129**, **130** coupled to first and second pressure couplers **125**, **126**. [0056] As shown in FIG. 2, second example underground tool **200** is shown with handle **206** comprising first and second controls **208**, **210** mounted to handle **206** with first and second control cables **212**, **224** and lighted camera cable **220** remaining inside sheath or sleeve **254** in pole **213** and handle **206** before exiting handle **206**, respectively, near first and second controls **208**, **210** and display holder **202**. Handle **206** is shown with first tank **229** coupled to first pressure coupler **225** coupled to handle **206**, indicating handle **206** may form a portion of pressure conduit leading through pole **213** to actuator **262**. Pole **213** is shown with rigid segment **255** coupled to actuator **262**.

[0057] As shown in FIG. 3, third example underground tool **300** is shown with handle **306** comprising first control **308** and display mount/steering control **302** mounted to handle **306** with first control cable **312**, steering control cables **323** and lighted camera cable **320** remaining inside pole **313** and handle **306** before exiting handle **306**, respectively, near first control **308** and display mount/steering control **302**. In this example, display mount and steering control may be integrated together. A user may pull, tilt, twist or otherwise move display mount **302** to move one or more cables and thereby move one or both flexible pole segment **355** and/or actuator **362**, e.g., depending how each of multiple steering control cables **323** are terminated. In an example, display mount or holder **302** may comprise, for example, a ball and socket or plate tethered to steering control cables **323** attached to pole **313** and/or actuator **362**. A centered display mount **302** may permit a relatively straight, tightened connection without turning cables to controls right or left of center on handle **306**. In an (e.g., another) example, display holder **302** may be positioned elsewhere and a dedicated steering control may be mounted in line with pole **313**. Handle **306** is shown with first tank **329** coupled to first pressure coupler **325** coupled to handle **306**. Pole **313** is shown with flexible segment **355B** coupled to actuator **362**. Ejector operation (e.g., and/or operation of retriever, collector, actuator, and so on) may be automated. As shown by example in FIG. 3, a user may control pressure coupler **325** (e.g., a valve in pressure coupler **325**) using an underground tool program (UTP) graphical user interface (GUI) displayed by computing device (e.g., cell phone) **304**. A UTP GUI may provide a user with pressure burst selections (e.g., in terms of number of bursts, lengths of bursts, and so on). A control signal may be provided from a computer via control wire **301** to a valve (e.g., in pressure coupler **325**).

[0058] As shown in FIG. 4, fourth example underground tool **400** is shown with display holder **402** mounted to handle **406**. Lighted camera cable **420** may be inside sheath or sleeve **454** in pole **413** and handle **406** before exiting handle **406** near display holder **402**. Top of pole **413** is shown coupled to first and second angled pipes **431**, **435** capped by first and second controls **408**, **410**. First and second control cables **412**, **424** may be inside sheath or sleeve **454** in pole **413** and split, respectively, into first and second angle pipes **431**, **435** before connecting to first and second controls **408**, **410**. First tank **429** may be coupled to first pressure coupler **425**, which may be coupled toward top of pole **413**.

[0059] FIGS. 7A-D show examples of accessories relative to actuators, according to an embodiment. FIGS. 7A-D show four different examples of an actuator end of an underground tool **700A-D**. Actuator **705** may comprise, for example, a cylinder having a length and a diameter. Actuator **705** may have other shapes (e.g., square, rectangular, hexagonal and so on). Actuator **705** is shown with a valve key comprising center recess **725** (e.g., to accept valve stem) separating first and second jaws **710**, **715** (e.g., configured to fit or mate with a valve stem). First and second jaws **710**, **715** and recess **725** may be fixed (e.g., milled from a stainless steel bar or shape or welded) or variable (e.g., a jaw may be varied to widen or narrow the gap between jaws). Variable jaws may be adjusted manually or automatically, e.g., by sliding or incrementally stepping jaw width. First and second jaws **710**, **715** (or their integrated or attached tips) may be magnetized, for example, as discussed with respect to other examples, to pick up metallic fragments.

[0060] Actuator **705** is shown with three openings (e.g., first, second and third holes **730**, **735** and **755**) through recessed portion **725**. Actuator **705** may have any number of openings of one or more sizes or diameters. Actuator **705** may have a rear recess area **720** on the pole-facing side of actuator **705**, which may reduce the depth of first, second and third holes **730**, **735** and **755**. Holes may provide a pathway from user controls through the interior of a pole to controlled devices coupled to or housed by actuator **705**. Holes may be used, for example, to eject pressurized gas or embed, conceal, protect and/or house fixed, removable, retractable, and/or controllable devices (e.g., camera, lighting, or grab, stab, and/or magnetic retriever(s))). Actuator key pattern may vary (e.g., to control various underground equipment) and the location of holes and devices may vary accordingly.

[0061] In an example, an (e.g., endoscope/borescope) lighted camera **740** may be inserted in and protected by second hole **735** in actuator **705**. Lighted camera **740** may have, for example, LED lights **745** and camera **750**, which may be controlled and powered by, for example, a cellular phone, tablet or other portable computing device. A cellular telephone or other computing device may also display images received from lighted camera **750**. In an example, lighted camera **740** may be (e.g., slightly) recessed from the surface of center recess **725**, for example, to avoid contact with the top of valve stems, debris, etc.

[0062] In an example, one or more holes may comprise pressure ports that may be configured (e.g., may be used to) eject pressurized gas released into pole or to a pressure line coupled to holes. As shown in FIGS. **7A** and **7B**, first hole **730** may eject pressurized gas, which may be transmitted internally through a pole. As shown in FIGS. **7C** and **7D**, first and third holes **730** and **755** may be used to eject pressurized gas. Holes may or may not be fitted with ejection nozzles.

[0063] In an example, one or more holes may be used to house one or more retrievers. For example, as shown in FIG. **7A**, third hole **755** may house first retriever **760** with multiple prongs **765**. As shown in FIG. **7B**, third hole may house second retriever **770** with one prong **775**. As shown in FIG. **C**, first retriever **760** with multiple prongs **765** and second retriever **770** with single prong **775** may be mounted to the exterior of actuator **705**. FIG. **7C** shows an additional and/or alternative ejector **777** external to actuator. As shown in FIG. **7D**, a larger retriever (e.g., third retriever **780** with four prongs **785**) may fit around an actuator (e.g., external to actuator) or may be integrated with an actuator (e.g., at the outer perimeter of actuator). In an example, holes through actuator **705** may be used to connect four prongs **785** to linkage internal to a pole to user controls (e.g., as previously shown). Retrievers, cameras, lights, ejectors, etc. may be internal and/or external to actuators and/or poles.

[0064] In some examples, actuators (e.g., of varying sizes) may be swapped or replaced for other actuators with holes in the same place to adapt to one or more devices that may be housed within the holes. Various actuators may slip on and lock (e.g., pin lock) onto pole, for example, rather than thread on. In other examples, one or more devices may be mounted (e.g., and sealed) to or in holes in each of multiple actuators with connectors that connect to connectors coupled to control wires and/or cables inside a pole to link up to user controls. Holes may not or may not have the same configuration. Holes and/or devices may be different for each of multiple actuators (e.g., and/or other accessories attached to a pole), which may support allowing users to control different devices with the same user control(s) and wired or wireless control, cable or other linkage.

[0065] FIG. **8** shows an example of compact storage of a disassembled underground tool, according to an embodiment. In an example, disassembled (e.g., broken down) underground tool **800** is shown as a disassembled version of example underground tool **100** shown in FIG. **1**. Disassembled underground tool **800** is shown, along with additional accessories, in underground tool storage case **805**. Underground tool **100** may be disassembled, for example, at first, second, third and fourth pole couplers **118**, **140**, **150**, and/or **160**. Underground tool **100** or disassembled underground tool **800** may be foldable or folded together with pole segments and handle for compact storage anywhere, e.g., as opposed to storage only in the bed of a truck due to fixed long length. Sheath or

sleeve **154** may retain (e.g., guide or contain) and protect control wires, cables and/or other linkages to controllable devices while a tool is disassembled. First and second deflectors **132**, **142** may be removed (e.g., if configured to be removable) from pole **113** for storage. Each may be one or more pieces that separate. One or more clamps (e.g., **620**, **625**) may be (e.g., configured to be) removed or may remain on pole **113** to hold and release first and/or second deflectors **132**, **142**. Extra accessories, such as additional pole segments **861A**, **861B** and actuators **863A**, **863B** may be stored with disassembled underground tool **800**. Storage lid **810** may close over case **805**. Case **805** and lid **810** may be latched together by one or more latches **815**. Disassembled underground tool **800** and accessories may be stored, protected and transported in case **805** (e.g., with carrying handle **820**) and/or other compact forms.

[0066] FIG. **9** shows an exemplary implementation of a computing device **900** in which example embodiments may be implemented. Computing device **900** may be, for example, a cellular telephone, a personal digital assistant (PDA), a smartphone, a laptop, a netbook, a personal computer, an Internet of Things (IoT) device, a watch or other wearable device, a head-mounted display (HMD) such as goggles or glasses, etc. Computing device **900** is a non-limiting example for purposes of illustration. Example embodiments may be implemented in other types of computer systems. Control (e.g., processes) described above may be implemented in a computer program, software, and/or firmware incorporated in a computer-readable medium for execution by a computer and/or processor.

[0067] Computing device **900** may comprise, for example, an implementation of camera control, video control, actuator control, ejector control, retriever control, steering control, collector control, etc., as described with reference to FIGS. **1-8**. Examples of computer-readable media include, but are not limited to, electronic signals (transmitted over wired and/or wireless connections) and/or computer-readable storage media. Examples of computer-readable storage media include, but are not limited to, read only memory (ROM), random access memory (RAM), a register, cache memory, semiconductor memory devices, magnetic media such as, but not limited to, solid state drives (SSDs), hard disk drives (HDDs) and removable drives or disks, magneto-optical media, and/or optical media such as compact disc (CD)-ROM disks, and/or digital versatile disks (DVDs).

[0068] As shown in FIG. **9**, computing device **900** may include computing system **904**. Computing system **904** may include one or more processors (e.g., processor circuit **926**), system memory **906**, and a bus **932** that couples various system components, e.g., including system memory **906** to processor circuit **926**. Processor circuit **926** may be an electrical and/or optical circuit implemented in one or more physical hardware electrical circuit device elements and/or integrated circuit devices (e.g., semiconductor material chips or dies), such as a central processing unit (CPU), a microcontroller, a microprocessor, and/or other physical hardware processor circuit. Processor circuit **926** may execute program code stored in a computer readable medium, such as program code of operating system **936**, application programs **938**, other programs **940**, etc. Bus **932** may include one or more of any of several types of bus structures, e.g., including a memory bus or memory controller, a peripheral bus, an accelerated graphics port, and/or a processor or local bus using any of a variety of bus architectures. System memory **906** may include read only memory (ROM) **908** and random-access memory (RAM) **912**. A basic input/output system **910** (BIOS) may be stored in ROM **908**.

[0069] Computing system **904** may have one or more storage devices (e.g., a (removable) flash memory device, an SSD, an HDD for reading from and writing to a hard disk, a magnetic disk drive for reading from or writing to a removable magnetic disk, an optical disk drive for reading from or writing to a removable optical disk such as a CD ROM, DVD ROM, or other optical media). One or more storage devices may be connected to bus **932** by a respective interface. A storage device (e.g., and associated computer-readable media) may provide nonvolatile storage of computer-readable instructions, data structures, program modules and/or other data for computing system **904**. Other types of hardware-based computer-readable storage media can be used to store

data, such as flash memory cards, digital video disks, RAMS, ROMs, etc.

[0070] One or more program modules may be stored on computer-readable storage media. Programs may include operating system **914**, one or more application programs **916**, other programs **918**, and/or program data **920**. Application programs **916** or other programs **918** may include, for example, computer program logic (e.g., computer program code or instructions) for implementing control of any of the components shown in FIGS. **1-8**. An application program may be underground tool program (UTP) **936**. UTP **936** may include, for example, one or more of the following: a camera control that may (e.g., be used to) control one or more automated features of a camera, a video control that may (e.g., be used to) control one or more automated features of video, actuator control that may (e.g., be used to) control one or more automated features of an actuator (e.g., actuator servo that turns an actuator key), ejector control that may (e.g., be used to) control one or more features of ejector operation (e.g., ejector valve that opens and closes a valve to emit pressurize gas or liquid), retriever control that may (e.g., be used to) control one or more automated features of a retriever (e.g., retriever piston that projects and withdraws a retriever), steering control that may (e.g., be used to) control one or more automated features of steering (e.g., steering servo that rotates linkages to change a direction and/or angle of a portion of a pole and/or actuator), collector control that may (e.g., be used to) control one or more automated features of a collector (e.g., collector piston that opens and closes a collector).

[0071] Computing system **904** may include and/or may be coupled (e.g., via bus **932** and/or interfaces **924**) to one or more (e.g., peripheral) devices (not shown), such as a touch screen or touch pad, display **922** (e.g., displaying a virtual keyboard and pointer for the touch pad or touch screen), microphone, joystick, game pad, a voice recognition system to receive voice input, a gesture recognition system to receive gesture input, or the like, speakers, microphone, software and/or hardware modules that provide wired or wireless connectivity, an e-compass, a satellite transceiver, a digital camera (e.g., for photographs and/or video), a universal serial bus (USB) port, a vibration device, a television transceiver, a hands free headset, a Bluetooth® module, a frequency modulated (FM) radio unit, a digital music player, a media player, a video game player module, an Internet browser, an HMD (e.g., video glasses, virtual reality and/or Augmented Reality (VR/AR) device), an activity tracker, one or more sensors (e.g., gyroscope, accelerometer, hall effect sensor, magnetometer, orientation sensor, proximity sensor, temperature sensor, time sensor; geolocation sensor; altimeter, light sensor, touch sensor, magnetometer, barometer, gesture sensor, biometric sensor, humidity sensor).

[0072] A user may enter commands and information into computing system **904** through one or more input devices (e.g., a touch screen or touch pad keyboard and/or pointer). One or more communication (e.g., input and/or output) devices may be connected to processor circuit **926** through one or more interfaces **924** coupled to bus **932** (e.g., through one or more interface circuits **930**). For example, a touchscreen that a user may interact with based on images displayed by display **922** may be an interface and a touchscreen circuit may be a communication circuit that interfaces the touchscreen to bus **932** (e.g., and UTP **936** execute by processor circuit **926**. For example, an antenna that receives and transmits wireless signals may be an interface and a transceiver may be a communication circuit that interfaces the antenna to bus **932**. Interfaces may include, for example, a connector or port, such as a USB port (e.g., USB-A, USB-C), through which a user may connect compatible devices.

[0073] Display (e.g., visual screen) **922** may be connected to bus **932** via an interface, such as a video adapter **928**. Display **922** may be external to, or incorporated in computing device **900**. Display **922** may display information. Display **922** may be integrated with a user interface for receiving user commands and/or other information (e.g., a touch screen or touch pad interface detecting input by touch, finger gestures, virtual keyboard). Computing device **900**, computing system **904** and/or display **932** may be an HMD. As shown in FIG. **9**, display **922** may display UTP GUI **902** generated based on execution of UTP **936** by processor circuit **926**. UTP GUI **902** may

include, for example, a user interface for steering control (e.g., configured for the user to steer at least a portion of the pole or the actuator); actuator control (e.g., configured for the user to control the actuator); deflector control (e.g., configured for the user to control a deflector); a retriever control (e.g., configured for the user to control at least one retriever); ejector control (e.g., configured for the user to control the ejector); camera control (e.g., configured for the user to control the camera); and/or display control (e.g., configured for the user to control a display of the images). UTP GUI **902** may use or may be integrated with an imaging program. In some examples, display **922** may display images (e.g., based on camera sensor data) using an imaging program (e.g., an application or app) provided with the camera.

[0074] Computing system **904** may connect to (e.g., and communicate with) a network (e.g., the Internet) through one or more interfaces (e.g., interfaces **924**, such as a network interface). A network may include a wireless network (e.g., a mobile network, such as a cellular network).

[0075] Computer programs and modules (including application programs **932** and other programs **934**) may be stored on one or more computer readable storage devices and/or media. In some examples, computer programs, when executed or loaded by an application, may (e.g., be configured and/or used to) enable computing system **904** to implement (e.g., in part) one or more features (e.g., controls) of example embodiments described herein. Example embodiments are directed to computer program products comprising computer-executable code or instructions stored on any computer-readable medium (e.g., storage device).

[0076] Systems, methods, and instrumentalities are disclosed for an underground tool that may be (e.g., in various implementations) compact, universal, multi-purpose and/or reconfigurable. A variety of underground components in a variety of conditions may be remotely viewed, cleared of obstructions and controlled with one tool that may be broken down and stored in a compact case. A portable computer (e.g., an operator's cell phone), which may be attached to or held by the tool, may (e.g., be used to) power a lighted camera recessed in an actuator (e.g., valve key) to observe underground conditions and assist with operations (e.g., clear obstructions, maneuver, steer, attach to and operate underground equipment). Accessories may be adjusted, added or removed to accomplish a variety of tasks in a variety of conditions. Integrated, detachable, fixed or adjustable accessories may include, for example, a display holder, ejector, retriever, magnet, debris deflector, debris collector, pressure tank, pressure hose, actuators and other pole tips, pole sections, handles and accessory controls. Additional examples are provided.

[0077] In an example, an apparatus may be or may include an underground tool (e.g., a portable, hand-held underground tool). An underground tool may include, for example, an actuator, a user interface, a pole, a camera and/or an ejector. An actuator may be, for example, a coupler, a valve key, a socket, a plug (e.g., a nut), a bit, etc. Actuator operation may be manual, automatic, mechanical, electromechanical, hydraulic, pneumatic, electric, etc. An actuator may be configured or configurable to fit an underground component (e.g., a valve nut) configured as an interface for underground equipment (e.g., valve). An actuator may be used to control or operate (e.g., rotate, open, close, switch, activate, deactivate, engage, disengage) an underground component. An underground component may be or may provide an operational interface for a device. For example, operation of an underground component may open or close a valve. A user interface (e.g., a handle) may be configured or configurable for a user to control the apparatus. For example, a handle may be detachable from a pole, foldable, etc., such that it may be configured to operate one or more features of the apparatus. A pole may be coupled or configured to be coupled between the user interface and the actuator. A camera may be attached to the pole or actuator, recessed or configured to be recessed in the actuator, etc. For example, an actuator may have one or more openings (e.g., holes) for a camera, retriever, etc. retained by the pole to fit or slide into, allowing actuators to be removed and replaced. A camera may be configured to communicate images of underground conditions to a display viewed by the user. A user may use display images, for example, to observe underground conditions, move obstructions obstructing an underground component, position the

actuator on the underground component, etc. An ejector may be configured to emit pressurized gas or liquid through a port to dislodge (e.g., clean, eject, move) debris obstructing an underground component.

[0078] In some examples (e.g., example implementations), the pole may be a pipe. An interior of the pole (e.g., pipe) may be configured to convey the pressurized gas or liquid to the ejector (e.g., or to the actuator) through an interior of the pipe. In some examples, a pipe (e.g., a flexible pipe) may be attached to the pole to convey the pressurized gas or liquid to the ejector (e.g., coupled to the pole and/or actuator). In some examples, an interior of the actuator may be configured to convey the pressurized gas or liquid to the port. In some examples, an interior of the user interface (e.g., handle) may be configured to convey the pressurized gas or liquid (e.g., to the pipe).

[0079] In some examples, the pole (e.g., pipe) may include multiple segments, such as a first segment with a first connector and a second segment with a second connector configured to couple to and decouple from the first connector to assemble and disassemble the first and second segments of the pole. In some examples, the user interface (e.g., handle) and/or the actuator may have one or more connectors configured so that the user interface and/or actuator may be assembled to and disassembled from the pole. Disassembly may support compact storage, portability, protection, etc. for underground tools (e.g., in a fixed or portable container or case).

[0080] In some examples, the user interface may include at least one of the following: a steering control (e.g., configured for the user to steer at least a portion of the pole or the actuator); an actuator control (e.g., configured for the user to control the actuator); a deflector control (e.g., configured for the user to control a deflector); a retriever control (e.g., configured for the user to control at least one retriever); an ejector control (e.g., configured for the user to control the ejector); a camera control (e.g., configured for the user to control the camera); and/or a display control (e.g., configured for the user to control a display of the images).

[0081] In some examples, the apparatus may include at least one of the following: a retriever (e.g., configured to), a deflector, and/or a collector (e.g., configured to collect debris ejected by the ejector). One or more retrievers, one or more deflectors, and/or one or more collectors may be coupled or configured to be coupled to the pole and/or actuator. Examples may include one or more types of retriever (e.g., grip, stab, scoop, magnet). A retriever may be configured and/or used (e.g., deployed or deployable) to retrieve debris obstructing the underground component. A deflector may be configured and/or used (e.g., deployed or deployable) to deflect debris away from the user (e.g., debris ejected above ground by the ejector). A collector may be configured and/or used (e.g., deployed or deployable) to collect debris ejected by the ejector (e.g., to prevent the ejected debris from re-obstructing the underground component).

[0082] In an (e.g., another) example, an apparatus may be or may include an underground tool (e.g., a portable, hand-held underground tool). An underground tool may include, for example, a pole, a camera, an ejector and/or a retriever. A pole may be coupled or configured to be coupled between the user interface and the actuator. A camera may be attached to the pole or actuator, recessed or configured to be recessed in the actuator, etc. A camera may be configured to communicate images of underground conditions to a display viewed by the user. A user may use display images, for example, to observe underground conditions, move obstructions obstructing an underground component, position the actuator on the underground component, etc. An ejector may be configured to emit pressurized gas or liquid through a port to dislodge (e.g., clean, eject, move) debris obstructing an underground component. A retriever may be configured and/or used (e.g., deployed or deployable) to retrieve debris obstructing the underground component.

[0083] In some examples, the apparatus may comprise the actuator. The actuator may include, for example, the camera and/or the ejector. The camera may be recessed or configured to be recessed in the actuator. In some examples, a camera may be secured to the pole. One or more (e.g., removable) actuators may be configured (e.g., with a hole) to fit (e.g., slip over or adjacent to) the camera (e.g., and attach to the pole). In some examples, a camera may be coupled (e.g., epoxied) to

an actuator. One or more camera connectors may be attached and/or detached to one or more camera connectors coupled to a cable in or on the outside of the pole. The ejector may be implemented, for example, as one or more openings (e.g., orifices, holes or ports) in the actuator to convey and/or emit pressurized gas and/or liquid (e.g., received through the pole in the form of a pipe). In some examples, one or more ejectors and/or one or more cameras may be implemented adjacent and/or attached to the pole and/or actuator.

[0084] An actuator may (e.g., be used to) control or operate (e.g., rotate, open, close, switch, activate, deactivate, engage, disengage) an underground component. For example, operation of an underground component may open or close a valve. An actuator may be or may include, for example, a key or fitting (e.g., mechanical or electrical component) that fits or mates to a corresponding fitting (e.g., valve nut) for underground equipment (e.g., a valve). An underground component may be or may provide an operational interface for underground equipment. An actuator key may be or may include, for example, a coupler, a socket, a plug (e.g., a nut), a bit, etc. An actuator or a portion thereof may be configured or configurable (e.g., adjustable, deployable) to fit an operational interface of an underground component (e.g., a valve nut). For example, an actuator key may be a valve key (e.g., a valve socket) that, when mated to a corresponding fitting (e.g., an operational interface) of a valve (e.g., a valve nut) and moved/operated to move the corresponding valve fitting (e.g., valve nut), opens or closes the valve. Actuator operation may be manual, automatic, mechanical, electromechanical, hydraulic, pneumatic, electric, etc.

[0085] In some examples, the apparatus may comprise the user interface. A user interface (e.g., a handle) may be configured or configurable for a user to control the apparatus. A user interface may be configured to operate one or more features of the apparatus (e.g., camera, display, power, hydraulic or pneumatic pressure ejection, debris deflection, debris collection, downhole debris or item retrieval such as grip, stab, grab, magnetic pick-up). A user interface may be, for example, a handle and/or an attachment point for one or more other user interfaces. Interfaces may include, for example, mechanical controls, electromechanical controls, hydraulic controls, pneumatic controls, displays, touchscreen controls, camera controls, a display holder (e.g., cell phone holder), display controls, power controls, etc. In some examples, a user interface (e.g., handle) may be detachable from a pole, foldable, etc., for example, for compact storage and/or protection of sensitive items (e.g., connectors, cell phone holder, controls).

[0086] In some examples (e.g., example implementations), the pole may be a pipe. An interior of the pole (e.g., pipe) may be configured to convey the pressurized gas or liquid to the ejector (e.g., or to the actuator) and ejected through one or more ports by passing through an interior of the pipe. In some examples, a pipe (e.g., a flexible pipe) may be attached to the pole to convey the pressurized gas or liquid to the ejector (e.g., coupled to the pole and/or actuator). In some examples, an interior of the actuator may be configured to convey the pressurized gas or liquid to the port. In some examples, an interior of the user interface (e.g., handle) may be configured to convey the pressurized gas or liquid (e.g., to the pipe).

[0087] In some examples, the pole (e.g., pipe) may include multiple segments, such as a first segment with a first connector and a second segment with a second connector configured to couple to and decouple from the first connector to assemble and disassemble the first and second segments of the pole. In some examples, the user interface (e.g., handle) and/or the actuator may have one or more connectors configured so that the user interface and/or actuator may be assembled to and disassembled from the pole. Disassembly may support compact storage, portability, protection, etc. for underground tools (e.g., in a fixed or portable container or case).

[0088] In some examples, the user interface (e.g., handle) may comprise a pipe. An interior of the user interface (e.g., pipe) may be configured to convey the pressurized gas or liquid to the pole (e.g., pipe) from a source (e.g., a portable pressurized tank, a tank and pump). In some examples, a pipe (e.g., a flexible pipe) may be attached to the handle to convey the pressurized gas or liquid to the pole or a pipe along the pole.

[0089] In some examples, the user interface (e.g., pipe) and/or pole (e.g., pipe) may include multiple segments, such as a first segment with a first connector and a second segment with a second connector configured to couple to and decouple from the first connector to assemble and disassemble the first and second segments of the user interface and/or the user interface and the pole or one or more segments of the pole with one or more connectors. Connectors supporting assembly and disassembly may support compact storage, portability, protection, etc. for the user interface and/or the underground tool (e.g., in a fixed or portable container or case).

[0090] In some examples, connectors may be pressure couplers. A user interface, pole, and/or actuator may include a pressure coupler to couple one or more pressure sources to one or more ports outside (e.g., external to) and/or inside (e.g., through) the user interface, pole, and/or actuator (e.g., via a conduit internal or external to the user interface, pole, and/or actuator). In some examples, the user interface and/or the pole may be configured (e.g., may include) a pressure coupler configured to couple to and to (e.g., rigidly) hold or suspend a portable pressure tank and/or a pressure hose. A connector (e.g., pressure coupler) may comprise, for example, a pneumatic or a hydraulic quick coupler.

[0091] In some examples, segments (e.g., of a user interface, pole, and/or actuator) may be tethered together. A tether may be a flexible conduit (e.g., a Nylon sheath) through which one or more wires, cables, etc. may pass between user interface, pole, and/or actuator. In some examples, the interior of a user interface, pole, and/or actuator or a conduit in the pipe, such as a (e.g., flexible) tether may include one or more power cables, communication cables and/or control cables (e.g., a camera communication cable, an actuator communication cable, a camera power cable, an actuator power cable, a retriever control cable, an actuator control cable, and/or a steering control cable).

[0092] In some examples, an apparatus (e.g., underground tool) may include one or more deflectors. A deflector may be coupled or configured to be coupled to the pole. A deflector may be configured or configurable (e.g., deployable, retractable, attachable, detachable) to deflect debris ejected above ground by the ejector. A deflector may deflect debris away from a user. For example, a deflector may be fixed (e.g., deployed) or deployable (e.g., retractable). A deflector may be assembled and disassembled on and/or around a pole. A deflector may be clamped to a pole. A deflector may be angled, for example, to alter the direction of travel of debris away from a user. A deflector may be configured to cover (e.g., seal) an opening in the ground around the pole and redirect ejected obstruction debris. A deflector may be configured to confine debris, for example in a (e.g., an angled) pipe or conduit. Suction (e.g., by a vacuum) may be coupled to a deflector to support or assist debris extraction through a confined space (e.g., a debris conduit), for example, to prevent the ejected obstruction debris from re-obstructing the underground component. A deflector may additionally and/or alternatively be deployed while the pole is in the access pipe to deflect items away from the access pipe.

[0093] In some examples, an apparatus (e.g., underground tool) may include one or more collectors. A collector may be coupled or configured to be coupled to the pole and/or actuator. A collector may be configured or configurable (e.g., deployable, retractable, attachable, detachable) to collect, capture or trap debris ejected by the ejector. A (e.g., deployed) collector may be shaped like a cone, cup, upside down umbrella, and/or other debris-collecting shape. A collector may be rigid and/or flexible deployed and/or retracted. One or more collectors may be mounted on or near the actuator. A collector may be positioned underground (e.g., on a portion of the pole in an access pipe) to collect debris before it falls to the bottom of the access pipe, potentially re-obstructing the underground component. One or more collectors may be deployed (e.g., manually or automatically), for example, after triggering a pressurized ejection to force debris upward. A collector may be configured to deploy and press against underground walls (e.g., access pipe wall). Following collection of debris, a collector may be retracted and/or removed. A retracted (e.g., closed) collector may be reduced in size and/or shape compared to deployed size and/or shape, for example, to support insertion and/or removal from an access pipe. A collector may additionally

and/or alternatively be deployed while the pole is in the access pipe to capture anything that may fall down the access pipe. A user may manually operate (e.g., deploy, retract) a collector, for example, by pushing and pulling a collector control to open and close a collector, e.g., after operation of the ejector to capture falling obstruction debris.

[0094] In some examples, an apparatus (e.g., underground tool) may include one or more retrievers. A retriever may be coupled or configured to be coupled to the pole and/or actuator. A retriever may be configured or configurable (e.g., deployable, retractable, attachable, detachable) to retrieve debris (e.g., obstructions) and/or other items in an underground access pipe or equipment box. A retriever may be any type (e.g., grab or grip, stab or penetrate, scoop, magnetic pickup). For example, at least a portion of an actuator may be magnetized and/or may include at least one magnet to pick up debris. In some examples, one or more retrievers may be mounted to an exterior of the pole and/or actuator. A retriever may be (e.g., configured to be) coupled to and decoupled from at least one of the pipe and the actuator. In some examples, one or more retrievers may be mounted inside the pole and/or actuator. For example, a retriever may be controlled (e.g., by a user using a retriever control) to extend from and retract into at least one of the pipe and the actuator. Debris may, for example, be held by clenched jaws of a grab or grip retriever, pierced and held by a barbed stab retriever, held by a scoop or held by a magnet.

[0095] In some examples, an apparatus (e.g., underground tool) may include a portable computer mount. A computer mount may be coupled or configured to be coupled (e.g., fixedly or removably attached, such as by one or more retainers or clamps) to the user interface and/or the pole. A computer mount may hold a portable computer (e.g., cell phone, tablet) for interaction and/or viewing by a user. A computer (e.g., as shown by example in FIG. 9) may provide (e.g., perform) a user interface and/or perform functions, such as one or more of the following: supply power to the camera, process image data from the camera, and/or display the processed images to the user. In some examples, a user interface may include at least one of the following: a steering control (e.g., configured for a user to steer at least a portion of the pole or the actuator); a deflector control (e.g., configured for the user to control a deflector); a collector control (e.g., configured for the user to control a collector); an actuator control (e.g., configured for the user to control the actuator); a retriever control configured for the user to control at least one retriever; an ejector control configured for the user to control the ejector; a camera control configured for the user to control a camera; and a display control configured for the user to control a display.

[0096] In some examples, the actuator or a portion of pole coupled to an actuator may be configured to be coupled to and decoupled from the pole to swap the actuator for a replacement actuator or a different actuator configured or configurable to fit a different underground component. Actuator control may be manual and/or automated (e.g., by controlling power or a hydraulic or pneumatic valve to provide pressurized fluid or gas to an electric, hydraulic or pneumatic servo). For example, a user may use a display GUI or manually provide force to operate an actuator.

[0097] In some examples, an actuator (e.g., valve key) may include a fitting (e.g., a key) configured or configurable to fit an underground component (e.g., a valve nut) of underground equipment (e.g., valve). An actuator may include an ejector configured or configurable to emit pressurized gas or liquid from a port to dislodge (e.g., clean, eject, move) obstructions obstructing the underground component. An actuator may include a retriever (e.g., grip, stab, scoop, magnet) configured or configurable to retrieve obstructions obstructing the underground component. An actuator may include a collector configured or configurable to collect ejected debris. An ejector, retriever and/or camera may be in the interior and/or on the exterior of an actuator (e.g., as shown by examples herein). In some examples, a camera may be recessed or configured to be recessed in the actuator, configured to communicate (wirelessly or by wire) images of underground conditions to a display viewed by a user. In some examples, the actuator may be configured to receive the pressurized gas or liquid through the pole (e.g., if the pole is a pipe). In some examples, an actuator connector may be configured (e.g., with a connector, such as a quick couple) to couple to and decouple from a

pole. The pole may be coupled or configured to be coupled between the actuator and a user interface (e.g., handle).

[0098] While the disclosed technology has been described with respect to a limited number of examples, it should be understood that they have been presented by way of example only, and not limitation. It will be understood by those skilled in the relevant art(s) that the spirit and scope of the subject matter of the present application encompasses a wide variety of implementations, including various changes in form and details to disclosed examples. Embodiments are not limited to the functional blocks, detailed examples, steps, order or the entirety of subject matter presented in the examples. An embodiment of a device, apparatus or machine may comprise any one or more features described herein in any configuration. An embodiment of a method or process may comprise any process described herein, in any order, with any number of steps, using any modality. The appended claims encompass examples and features described herein, modifications and variations thereto as well as additional examples and features that fall within the true spirit and scope of the disclosed subject matter.

Claims

1. An apparatus comprising: a pole coupled or configured to be coupled between a user interface and an actuator configured or configurable to attach to an interface of an operable underground component for operation of the operable underground component; and at least one of the following components: (i) a camera configured to communicate images of underground conditions to a display; (ii) an ejector configured to emit pressurized gas or liquid through a port to dislodge debris obstructing the operable underground component; (iii) a retriever configured to retrieve debris obstructing the operable underground component; (iv) a collector configured or configurable to collect debris to avoid obstructing or re-obstructing the operable underground component; or (v) a deflector configured or configurable to deflect debris ejected from underground.
2. The apparatus of claim 1, further comprising: the actuator, wherein the actuator comprises at least one of the following: the camera, the ejector, or the retriever.
3. The apparatus of claim 1, the apparatus comprising the ejector, wherein at least one of the pole or the user interface comprises a pipe, and wherein an interior of the pipe is configured to convey the pressurized gas or liquid to the ejector.
4. The apparatus of claim 3, wherein the pipe comprises a first segment with a first connector and a second segment with a second connector configured to couple to and decouple from the first connector to assemble and disassemble the first and second segments of the pole.
5. The apparatus of claim 1, wherein the apparatus comprises the deflector, wherein the deflector is configured or configurable to be at least one of the following: attached to and removed from the pole, repositionable on the pole, or deployed and retracted while coupled to the pole.
6. The apparatus of claim 1, wherein the apparatus comprises the collector, wherein the collector is configured or configurable to be at least one of the following: attached to and removed from the pole, repositionable on the pole, or deployed and retracted while coupled to the pole.
7. The apparatus of claim 1, wherein the apparatus comprises the retriever, wherein the retriever is configured or configurable to be at least one of the following: attached to and removed from the pole or the actuator, repositionable on the pole or actuator, or deployed and retracted while coupled to the pole or actuator.
8. The apparatus of claim 1, further comprising: the user interface, the user interface comprising at least one of the following: a steering control configured to steer at least one of the pole or the actuator; a deflector user interface control to operate the deflector; a retriever user interface control to operate the retriever; or an ejector user interface control to operate the ejector.
9. An actuator comprising: a key configured or configurable to attach to an interface of an operable underground component for operation of the operable underground component; and at least one of

the following: (i) an ejector configured or configurable to emit pressurized gas or liquid from a port to dislodge obstructions obstructing the operable underground component; (ii) a retriever configured or configurable to retrieve obstructions obstructing the operable underground component; or (iii) a camera configured to communicate images of underground conditions to a display.

10. The actuator of claim 9, further comprising: an actuator connector configured to couple to and decouple from a pole coupled or configured to be coupled between the actuator and a user interface.

11. The actuator of claim 9, the actuator comprising the ejector, wherein the ejector is configured to be positioned in the actuator.

12. The actuator of claim 9, the actuator comprising the retriever, wherein the retriever is configured to be positioned in the actuator.

13. The actuator of claim 9, the actuator comprising the camera, wherein the camera is configured to be positioned in the actuator.

14. The actuator of claim 9, wherein at least one of the following is magnetized: the retriever or at least a portion of the actuator.

15. An apparatus comprising: a deflector configured to deflect debris ejected from an underground pipe by an ejector coupled to a pole inserted in the underground pipe.

16. The apparatus of claim 15, wherein the deflector is configured or configurable to be coupled to and decoupled from the pole.

17. The apparatus of claim 16, wherein the deflector is configured or configurable to be repositionable on the pole.

18. The apparatus of claim 15, wherein the deflector is configured to be deployed and retracted while coupled to the pole.

19. The apparatus of claim 15, wherein the deflector is configured or configurable to rest on a surface above the underground pipe.

20. The apparatus of claim 15, wherein the deflector comprises a plurality of pieces configured or configurable to fit together around the pole while the pole is inserted in the underground pipe.

21. The apparatus of claim 15, wherein the deflector is configured or configurable to couple to a vacuum to assist with deflection or extraction of the ejected debris.

22. The apparatus of claim 15, wherein the deflector comprises a stand configured to support a weight of the pole and to allow the pole to be maneuvered in the underground pipe while supported by the stand.
