

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286329

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

CHEN; YING-CHUNG et al.

Power Supply System and Electrical Connector Thereof

Abstract

A power supply system, which comprises: an electrical connector, an inserting conductive component, and a power supply module. The power supply module is capable of providing power. The electrical connector is capable of receiving power from the power supply module, and the electrical connector comprises: a trigger component. The inserting conductive component is capable of being inserted into the electrical connector. When the inserting conductive component is fully inserted into the electrical connector, the trigger component triggers the power supply module to provide electrical power to the inserting conductive component. This can solve technical problems such as the electrical connector providing power to the inserting conductive component before it is fully inserted, ensuring that the power supplied by the electrical connector to the inserting conductive component is stable, allowing the power supply system to meet the expected power supply requirements in various electronic devices.

Inventors: CHEN; YING-CHUNG (New Taipei City, TW), HUANG; MU-JUNG (New Taipei City, TW)

Applicant: Dongguan Tarng Yu Electronics Co., Ltd. (Dongguan City, CN); Tarng Yu Enterprise co., ltd. (New Taipei City, TW)

Family ID: 93260646

Appl. No.: 19/074494

Filed: March 10, 2025

Foreign Application Priority Data

TW

113202437

Mar. 11, 2024

Publication Classification

Int. Cl.: H01R13/703 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the priority of Republic of China Patent Application No. 113202437 filed on Mar. 11, 2024, in the State Intellectual Property Office of the R.O.C., the disclosure of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] This application relates to the technical field of electronic devices. More specifically, it concerns an electrical connector.

Descriptions of the Related Art

[0003] An electrical connector can be equipped with a power supply module and an inserting conductive component to form a power supply system capable of providing electrical power. In such a power supply system, the electrical connector can receive power from the power supply module and provide a connection for the inserting conductive component, thereby delivering electrical power to the inserting conductive component. As a result, in recent years, this power supply system comprises been widely used to provide electrical power to various electronic devices.

[0004] However, during practical implementation, the electrical connector may provide electrical power to the inserting conductive component before it is fully inserted, which leads to unstable power delivery to the inserting conductive component, thereby affecting the power supply of the system.

[0005] Therefore, addressing the technical issue of how to prevent the electrical connector from providing power to the inserting conductive component before it is fully inserted is an urgent challenge for those skilled in the art.

SUMMARY OF THE INVENTION

[0006] In view of the drawbacks of the prior art mentioned above, the present application provides an electrical connector, which is able to be equipped with a power supply module and can receive an electrical power from the power supply module, and the electrical connector is able to provide insertion for an inserting conductive component, thereby providing electrical power to the inserting conductive component, and the electrical connector comprises: a trigger component, which is electrically connected to the power supply module; an inserting terminal, which is electrically connected to the power supply module and comprises an inserting terminal body, a front terminal inserting arm, and a terminal trigger arm, and the inserting terminal body is electrically connected to the terminal trigger arm, and the inserting terminal body comprises a front terminal body extension section, and the front terminal body extension section is electrically connected to the front terminal inserting arm, wherein the front terminal inserting arm comprises a front terminal inserting arm inserting structure, and the terminal trigger arm comprises a terminal trigger arm inserting structure and a terminal trigger arm abutting structure; and an insulating core, which comprises a core abutting space, a core inserting space, and a core guiding structure, and the insulating core is respectively mated with the inserting terminal and the trigger component, such that the front terminal inserting arm inserting structure and the terminal trigger arm abutting structure are respectively located within the core inserting space, and the terminal trigger arm abutting structure and the trigger component are respectively located within the core abutting

space, and the core guiding structure provides guidance for the insertion of the inserting conductive component, allowing the inserting conductive component to enter the core inserting space and sequentially insert the front terminal inserting arm inserting structure and the terminal trigger arm inserting structure; wherein when the inserting conductive component inserts the front terminal inserting arm inserting structure, the inserting conductive component is electrically connected to the front terminal inserting arm inserting structure; and when the inserting conductive component inserts the terminal trigger arm inserting structure, the terminal trigger arm abutting structure is electrically abutted against the trigger component within the core abutting space, triggering the power supply module through the trigger component, thereby allowing the power supply module to provide electrical power to the inserting conductive component via the front terminal inserting arm inserting structure.

[0007] Preferably, the electrical connector said above, wherein the trigger component triggers the power supply module, and the power supply module can further provide electrical power to the inserting conductive component via the terminal trigger arm inserting structure.

[0008] Preferably, the electrical connector said above, wherein the inserting terminal further comprises a rear terminal inserting arm, and the inserting terminal body further comprises a rear terminal body extension section, and the rear terminal body extension section is electrically connected to the rear terminal inserting arm, wherein, the rear terminal inserting arm comprises a rear terminal inserting arm inserting structure and a rear terminal inserting arm supporting structure, and the rear terminal body extension section comprises a rear terminal body extension section supporting structure, and the rear terminal inserting arm is located behind the front terminal inserting arm, and the rear terminal body extension section is located behind the front terminal body extension section, such that the rear terminal inserting arm supporting structure provide support to the front terminal inserting arm, and the rear terminal body extension section supporting structure provide support to the front terminal body extension section; the rear terminal inserting arm inserting structure is located within the core inserting space, when the inserting conductive component enters the core inserting space, the inserting conductive component can insert the rear terminal inserting arm inserting structure, wherein the time when the inserting conductive component inserts the rear terminal inserting arm inserting structure is earlier than the time when the inserting conductive component inserts the terminal trigger arm inserting structure; and when the inserting conductive component inserts the terminal trigger arm inserting structure, the power supply module can further provide electrical power to the inserting conductive component via the rear terminal inserting arm inserting structure.

[0009] Preferably, the electrical connector said above, wherein the trigger component comprises a trigger component mating extension section, a trigger component abutting extension section, and a trigger component supporting extension section, and the insulating core is mated with the trigger component mating extension section, such that the trigger component abutting extension section is located in the core abutting space, when the inserting conductive component inserts the terminal trigger arm inserting structure, the terminal trigger arm abutting structure is electrically abutted against the trigger component abutting extension section in the core abutting space, and the trigger component supporting extension section abuts the insulating core, providing support to the trigger component abutting extension section.

[0010] Preferably, the electrical connector said above, wherein the insulating core further comprises a trigger component stop structure, providing support to the trigger component abutting extension section in the trigger component supporting extension section, and the trigger component stop structure provides stop to the trigger component supporting extension section to prevent the trigger component supporting extension section from leaving the insulating core.

[0011] Preferably, the electrical connector said above, wherein the trigger component supporting extension section comprises a trigger component supporting extension section elastic structure, and the trigger component supporting extension section elastic structure provides elastic support to the

trigger component abutting extension section, allowing the trigger component abutting extension section to be positioned in a predetermined location within the core abutting space.

[0012] Preferably, the electrical connector said above, wherein the trigger component supporting extension section elastic structure is a bent structure.

[0013] Preferably, the electrical connector said above, wherein the trigger component abutting extension section and the trigger component supporting extension section can be combined to form a bent structure.

[0014] Preferably, the electrical connector said above, wherein the terminal trigger arm comprises a terminal trigger arm mating extension section, a terminal trigger arm abutting extension section, and a terminal trigger arm elastic extension section, wherein the insulating core is mated with the terminal trigger arm mating extension section, such that the terminal trigger arm abutting extension section is located within the core abutting space, and allowing the terminal trigger arm elastic extension section to provide a terminal trigger arm elastic extension section thrust to push the terminal trigger arm abutting extension section away from the trigger component via the terminal trigger arm elastic extension section thrust; when the inserting conductive component inserts the terminal trigger arm inserting structure, the inserting conductive component provides an inserting conductive component thrust to the terminal trigger arm abutting extension section; and when the inserting conductive component thrust is greater than the terminal trigger arm elastic extension section thrust, the terminal trigger arm abutting extension section is moved and abuts against the trigger component.

[0015] Preferably, the electrical connector said above, wherein the insulating core further comprises a terminal trigger arm stop structure, and the terminal trigger arm elastic extension section thrust forces the terminal trigger arm abutting extension section to move away from the trigger component, and the terminal trigger arm stop structure provides stop to the terminal trigger arm abutting extension section to prevent the terminal trigger arm abutting extension section from leaving the core abutting space.

[0016] Preferably, the electrical connector said above, wherein the insulating core further comprises a terminal trigger arm restriction structure, wherein the inserting conductive component thrust is greater than the terminal trigger arm elastic extension section thrust, and the terminal trigger arm restriction structure provides limitation on the movement path of the pushed terminal trigger arm abutting extension section to prevent the abutting extension section of the terminal trigger arm from abutting the trigger component in an unexpected manner.

[0017] Preferably, the electrical connector said above, wherein the trigger component and the inserting terminal are conductive metal bodies.

[0018] Additionally, the present application further provides an electric power supply system, comprising: an inserting conductive component; a power supply module capable of providing electric power; and an electrical connector, comprising: a trigger component electrically connected to the power supply module; an inserting terminal electrically connected to the power supply module, the inserting terminal comprising an inserting terminal body, a front terminal inserting arm, and a terminal trigger arm, the inserting terminal body being electrically connected to the terminal trigger arm and the front terminal inserting arm, wherein the front terminal inserting arm comprises a front terminal inserting arm joining structure, and the terminal trigger arm comprises a terminal trigger arm joining structure and a terminal trigger arm abutting structure; and an insulating core, comprising a core abutting space, a core inserting space, and a core guiding structure, the insulating core joining the inserting terminal so that the front terminal inserting arm joining structure and the terminal trigger arm abutting structure are located within the core inserting space, and the terminal trigger arm abutting structure enters the core abutting space, the core guiding structure providing guidance for the insertion of the inserting conductive component, allowing the inserting conductive component to enter the core inserting space and sequentially insert the front terminal inserting arm joining structure and the terminal trigger arm joining

structure; wherein, when the inserting conductive component joins the front terminal inserting arm joining structure, the inserting conductive component is electrically connected to the front terminal inserting arm joining structure; and when the inserting conductive component joins the terminal trigger arm joining structure, the terminal trigger arm abutting structure electrically abuts the trigger component within the core abutting space, triggering the power supply module by transmitting a trigger signal via the trigger component, so that the power supply module provides electric power to the inserting conductive component via the front terminal inserting arm joining structure.

[0019] Preferably, the electric power supply system said above, wherein the trigger component triggers the power supply module, and the power supply module can further provide electric power to the inserting conductive component via the terminal trigger arm joining structure.

[0020] Preferably, the electric power supply system said above, wherein the power supply module is disposed on a circuit substrate.

[0021] Preferably, the electric power supply system said above, further comprising a trigger cable and an inserting cable, the trigger cable electrically connecting the trigger component and the power supply module, and the inserting cable electrically connecting the inserting terminal and the power supply module.

[0022] Preferably, the electric power supply system said above, wherein the trigger component comprises a trigger component cable-clamping structure, which clamps the trigger cable to electrically connect the trigger component; and the inserting terminal comprises an inserting terminal cable-clamping structure, and the inserting terminal cable-clamping structure clamps the inserting cable, enabling the inserting cable to electrically connect the inserting terminal.

[0023] Compared to the prior art, the present application provides a power supply system, which comprises: an electrical connector, an inserting conductive component, and a power supply module. The power supply module is capable of providing power. The electrical connector is capable of receiving power from the power supply module, and the electrical connector comprises: a trigger component. The inserting conductive component is capable of being inserted into the electrical connector. When the inserting conductive component is fully inserted into the electrical connector, the trigger component triggers the power supply module to provide electrical power to the inserting conductive component. This can solve technical problems such as the electrical connector providing power to the inserting conductive component before it is fully inserted, ensuring that the power supplied by the electrical connector to the inserting conductive component is stable, allowing the power supply system to meet the expected power supply requirements in various electronic devices.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] The above and other aspects, features and other advantages of the present invention will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

[0025] FIG. 1 is a three-dimensional diagram of the power supply system of the present application in one embodiment.

[0026] FIG. 2 is a three-dimensional diagram of the electrical connector of the present application in one embodiment.

[0027] FIG. 3 is a front view diagram of the electrical connector of the present application in one embodiment.

[0028] FIG. 4 is a cross-sectional diagram of a part of the electrical connector shown in FIG. 3, taken along line AA.

[0029] FIG. **5** is a cross-sectional diagram of a part of the electrical connector shown in FIG. **3**, taken along line A'A'.

[0030] FIG. **6** is a cross-sectional diagram of a part of the electrical connector shown in FIG. **3**, taken along line BB.

[0031] FIG. **7** is a cross-sectional diagram of a part of the electrical connector shown in FIG. **3**, taken along line B'B'.

[0032] FIG. **8** is a cross-sectional diagram of a part of the electrical connector shown in FIG. **3**, taken along line B''B''.

[0033] FIG. **9** is a three-dimensional diagram of the trigger component of the present application in one embodiment.

[0034] FIG. **10** is a right-side diagram of the electrical connector of the present application in one embodiment.

[0035] FIG. **11** is a cross-sectional diagram of a part of the electrical connector shown in FIG. **10**, taken along line CC.

[0036] FIG. **12** is a cross-sectional diagram of a part of the electrical connector shown in FIG. **10**, taken along line DD.

[0037] FIG. **13** is a three-dimensional diagram of a part of the electrical connector of the present application in one embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0038] Embodiments of the present invention will now be described in detail with reference to the accompanying drawings. The invention may, however, be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

[0039] This application provides a power supply system, which comprises: an electrical connector, an inserting conductive component, and a power supply module. The power supply module is capable of providing power. The electrical connector is capable of receiving power from the power supply module, and the electrical connector comprises: a trigger component. The inserting conductive component is capable of being inserted into the electrical connector. When the inserting conductive component is inserted into the electrical connector, the trigger component triggers the power supply module to provide electrical power to the inserting conductive component. This solves technical problems such as the electrical connector providing power to the inserting conductive component before it is fully inserted, ensuring stable power delivery from the electrical connector to the inserting conductive component and allowing the power supply system to meet the expected power supply requirements for various electronic devices.

[0040] For a detailed description of the embodiments disclosed in the present application, please refer to FIGS. **1** to **13**.

[0041] In the embodiments shown in FIGS. **1** to **13**, at least one power supply system **1** is provided, which may comprise: an electrical connector **11**, an inserting conductive component **12**, a power supply module **13**, a trigger cable **14**, and an inserting cable **15**. The power supply module **13** may optionally be arranged on a circuit substrate P to provide electrical power.

[0042] The electrical connector **11** comprises: a trigger component **111**, an inserting terminal **112**, and an insulating core **113**. Optionally, the trigger component **111** and the inserting terminal **112** are conductive metal bodies capable of transmitting electrical signals.

[0043] The trigger component **111** comprises a trigger component cable-clamping structure **1110**, a trigger component mating extension section **1111**, a trigger component abutting extension section **1112**, and a trigger component supporting extension section **1113**. The trigger component cable-clamping structure **1110** holds one end of the trigger cable **14**, while the other end of the trigger cable **14** is electrically connected to the power supply module **13**, allowing the trigger component **111** to electrically connect to the power supply module **13** via the trigger cable **14**.

[0044] The inserting terminal **112** comprises an inserting terminal cable-clamping structure **1120**, which holds one end of the inserting cable **15**, while the other end of the inserting cable **15** is electrically connected to the power supply module **13**, allowing the inserting terminal **112** to electrically connect to the power supply module **13** via the inserting cable **15**.

[0045] The inserting terminal **112** comprises an inserting terminal body **1121**, a front terminal inserting arm **1122**, a terminal trigger arm **1123**, and a rear terminal inserting arm **1124**. The inserting terminal body **1121** is electrically connected to the terminal trigger arm **1123** and comprises a front terminal body extension section **11211** and a rear terminal body extension section **11212**. The front terminal body extension section **11211** is electrically connected to the front terminal inserting arm **1122**, and the rear terminal body extension section **11212** is electrically connected to the rear terminal inserting arm **1124**. The rear terminal body extension section **11212** comprises a rear terminal body extension section supporting structure **112121**. The front terminal inserting arm **1122** comprises a front terminal inserting arm inserting structure **11221**.

[0046] As shown in FIGS. 2 and 6 to 7, the terminal trigger arm **1123** further comprises a terminal trigger arm inserting structure **11231**, a terminal trigger arm abutting structure **11232**, a terminal trigger arm mating extension section **11233**, a terminal trigger arm abutting extension section **11234**, and a terminal trigger arm elastic extension section **11235**. The terminal trigger arm abutting structure **11232** is located on the terminal trigger arm abutting extension section **11234**. The rear terminal inserting arm **1124** comprises a rear terminal inserting arm inserting structure **11241** and a rear terminal inserting arm supporting structure **11242**.

[0047] The insulating core **113** comprises a core abutting space **S1**, a core inserting space **S2**, a core guiding structure **1131**, a trigger component stop structure **1132**, a terminal trigger arm stop structure **1133**, and a terminal trigger arm restriction structure **1134**. The insulating core **113** is respectively mated with and positions the inserting terminal **112** (or the terminal trigger arm mating extension section **11233**) and the trigger component **111** (or the trigger component mating extension section **1111**), such that the front terminal inserting arm inserting structure **11221**, the terminal trigger arm abutting structure **11232**, and the rear terminal inserting arm inserting structure **11241** are respectively located in the core inserting space **S2**, and the terminal trigger arm abutting structure **11232** (or the terminal trigger arm abutting extension section **11234**) and the trigger component **111** (or the trigger component abutting extension section **1112**) are respectively located in the core abutting space **S1**. The core guiding structure **1131** provides guidance for the insertion of the inserting conductive component **12**, allowing the inserting conductive component **12** to enter the core inserting space **S2** and sequentially insert the front terminal inserting arm inserting structure **11221** (and/or the rear terminal inserting arm inserting structure **11241**) and the terminal trigger arm inserting structure **11231**. That is, the inserting conductive component **12** inserts the front terminal inserting arm inserting structure **11221** (and/or the rear terminal inserting arm inserting structure **11241**) before it inserts the terminal trigger arm inserting structure **11231**.

[0048] In the above embodiment, when the inserting conductive component **12** inserts the front terminal inserting arm inserting structure **11221**, it electrically connects to the front terminal inserting arm inserting structure **11221**. Furthermore, when the inserting conductive component **12** inserts the terminal trigger arm inserting structure **11231**, the terminal trigger arm abutting structure **11232** electrically abuts the trigger component **111** (or the trigger component abutting extension section **1112**) in the core abutting space **S1**, and the trigger component **111** transmits a trigger signal to trigger the power supply module **13**. This allows the power supply module **13** to provide electrical power to the inserting conductive component **12** through the front terminal inserting arm inserting structure **11221** (and/or the rear terminal inserting arm inserting structure **11241**) and the terminal trigger arm inserting structure **11231**. As a result, the trigger component **111** triggers the power supply module **13** to provide electrical power to the inserting conductive component **12** only when the inserting conductive component **12** is fully inserted into the electrical connector **11**. This solves technical problems such as the electrical connector **11** providing power to the inserting

conductive component **12** before it is fully inserted, ensuring that the electrical connector **11** provides stable power to the inserting conductive component **12** and enabling the power supply system **1** to meet the expected power supply requirements for various electronic devices.

[0049] In the above embodiment, as shown in figure *, the rear terminal inserting arm **1124** is located behind the front terminal inserting arm **1122**, and the rear terminal body extension section **11212** is located behind the front terminal body extension section **11211**, such that the rear terminal inserting arm supporting structure **11242** and the rear terminal body extension section supporting structure **112121** can respectively support the front terminal inserting arm **1122** and the front terminal body extension section **11211**, ensuring that the inserting conductive component **12** can be inserted into the front terminal inserting arm inserting structure **11221**. The trigger component supporting extension section **1113** abuts against the insulating core **113**, providing support for the trigger component abutting extension section **1112**, ensuring that the trigger component abutting extension section **1112** is positioned at the predetermined location of the core abutting space **S1**, so that the terminal trigger arm abutting structure **11232** can electrically abut the trigger component **111** (or the trigger component abutting extension section **1112**).

[0050] In the above embodiment, the terminal trigger arm elastic extension section **11235** provides a terminal trigger arm elastic extension section thrust to the terminal trigger arm abutting extension section **11234**, thereby driving the terminal trigger arm abutting extension section **11234** with the terminal trigger arm elastic extension section thrust, forcing the terminal trigger arm abutting extension section **11234** to move away from the trigger component **111**. Furthermore, the terminal trigger arm stop structure **1133** is, for example, a stop wall structure. When the terminal trigger arm elastic extension section thrust forces the terminal trigger arm abutting extension section **11234** to move away from the trigger component **111**, the terminal trigger arm stop structure **1133** provides a stop for the terminal trigger arm abutting extension section **11234** to prevent it from leaving the core abutting space **S1**.

[0051] It should be noted that when the inserting conductive component **12** is inserted into the terminal trigger arm inserting structure **11231**, the inserting conductive component **12** can provide an inserting conductive component thrust to the terminal trigger arm abutting extension section **11234**. When the inserting conductive component thrust is greater than the terminal trigger arm elastic extension section thrust, the terminal trigger arm abutting extension section **11234** can be pushed and cause the terminal trigger arm abutting extension section **11234** (or the terminal trigger arm abutting structure **11232**) to abut the trigger component **111**. Additionally, the terminal trigger arm limiting structure **1134** is, for example, a stop wall structure. When the inserting conductive component thrust exceeds the terminal trigger arm elastic extension section thrust, the terminal trigger arm limiting structure **1134** limits the movement path of the pushed terminal trigger arm abutting extension section **11234**, preventing the terminal trigger arm abutting extension section **11234** from abutting the trigger component **111** in an unexpected manner.

[0052] In the above embodiment, the trigger component supporting extension section **1113** comprises a trigger component supporting extension section elastic structure **11131**, which can provide elastic support for the trigger component abutting extension section **1112**.

[0053] Optionally, the trigger component supporting extension section elastic structure **11131** is a bent structure, so that the structural strength of the trigger component supporting extension section elastic structure **11131** meets expectations. Moreover, the trigger component abutting extension section **1112** and the trigger component supporting extension section **1113** can be combined to form a bent structure, ensuring that the structural strength of the trigger component abutting extension section **1112** and the trigger component supporting extension section **1113** meets expectations.

[0054] Additionally, the trigger component stop structure **1132** is, for example, a stop wall structure. When the trigger component supporting extension section **1113** provides support for the trigger component abutting extension section **1112**, the trigger component stop structure **1132** provides a stop for the trigger component supporting extension section **1113** to prevent it from

leaving the insulating core **113**.

[0055] It should be noted that the power supply system and its electrical connector described in this application can omit certain components and are not limited to the above embodiment.

[0056] For example, the power supply system described in this application may optionally comprise only: the power supply system comprises: the inserting conductive component, the power supply module, and the electrical connector. The power supply module can provide electrical power. The electrical connector comprises: the trigger component, the inserting terminal, and the insulating core. The trigger component electrically connects the power supply module. The inserting terminal electrically connects the power supply module, and the inserting terminal comprises the inserting terminal body, the front terminal inserting arm, and the terminal trigger arm. The inserting terminal body electrically connects the terminal trigger arm and the inserting terminal body electrically connects the front terminal inserting arm, wherein the front terminal inserting arm comprises the front terminal inserting arm inserting structure, and the terminal trigger arm comprises the terminal trigger arm inserting structure and the terminal trigger arm abutting structure. The insulating core comprises the core abutting space, the core inserting space, and the core guiding structure. The insulating core is mated with the inserting terminal, such that the front terminal inserting arm inserting structure and the terminal trigger arm abutting structure are respectively located in the core inserting space, and the terminal trigger arm abutting structure enters the core abutting space. The core guiding structure provides guidance for inserting the conductive component, allowing the inserting conductive component to enter the core inserting space and sequentially insert the front terminal inserting arm inserting structure and the terminal trigger arm inserting structure. When the inserting conductive component is inserted into the front terminal inserting arm inserting structure, the inserting conductive component electrically connects the front terminal inserting arm inserting structure; and when the inserting conductive component is inserted into the terminal trigger arm inserting structure, the terminal trigger arm abutting structure electrically abuts the trigger component in the core abutting space, triggering the power supply module via the trigger component, causing the power supply module to provide electrical power to the inserting conductive component through the front terminal inserting arm inserting structure.

[0057] Additionally, the electrical connector described in this application may optionally comprise only: the trigger component, the inserting terminal, and the insulating core. The trigger component electrically connects the power supply module. The inserting terminal electrically connects the power supply module, and the inserting terminal comprises the inserting terminal body, the front terminal inserting arm, and the terminal trigger arm. The inserting terminal body electrically connects the terminal trigger arm, and the inserting terminal body comprises the front terminal body extension section. The front terminal body extension section electrically connects the front terminal inserting arm, wherein the front terminal inserting arm comprises the front terminal inserting arm inserting structure, and the terminal trigger arm comprises the terminal trigger arm inserting structure and the terminal trigger arm abutting structure. The insulating core comprises the core abutting space, the core inserting space, and the core guiding structure. The insulating core is respectively mated with the inserting terminal and the trigger component, such that the front terminal inserting arm inserting structure and the terminal trigger arm abutting structure are respectively located in the core inserting space, and the terminal trigger arm abutting structure and the trigger component are respectively located in the core abutting space. The core guiding structure provides guidance for inserting the conductive component, allowing the inserting conductive component to enter the core inserting space and sequentially insert the front terminal inserting arm inserting structure and the terminal trigger arm inserting structure. When the inserting conductive component is inserted into the front terminal inserting arm inserting structure, the inserting conductive component electrically connects the front terminal inserting arm inserting structure; and when the inserting conductive component is inserted into the terminal trigger arm inserting structure, the terminal trigger arm abutting structure electrically abuts the trigger

component in the core abutting space, triggering the power supply module through the trigger component, causing the power supply module to provide electrical power to the inserting conductive component via the front terminal inserting arm inserting structure.

[0058] In summary, the present application provides a power supply system, which comprises: an electrical connector, an inserting conductive component, and a power supply module. The electrical connector is configured to connect the power supply module, the inserting conductive component, and the insulating core. The insulating core comprises a core abutting space, a core inserting space, and a core guiding structure. The insulating core is respectively mated with the inserting terminal, so that the front terminal inserting arm inserting structure and the terminal trigger arm abutting structure are respectively located in the core inserting space, and the terminal trigger arm abutting structure enters the core abutting space. The core guiding structure provides guidance for inserting the inserting conductive component, allowing the inserting conductive component to enter the core inserting space and sequentially connect with the front terminal inserting arm inserting structure and the terminal trigger arm inserting structure. When the inserting conductive component inserts the front terminal inserting arm inserting structure, the inserting conductive component is electrically connected to the front terminal inserting arm inserting structure; and when the inserting conductive component inserts the terminal trigger arm inserting structure, the terminal trigger arm abutting structure electrically abuts the trigger component in the core abutting space, triggering the power supply module via the trigger component. This causes the power supply module to provide electrical power to the inserting conductive component through the front terminal inserting arm inserting structure.

[0059] The examples above are only illustrative to explain principles and effects of the invention, but not to limit the invention. It will be apparent to those skilled in the art that modifications and variations can be made without departing from the spirit and scope of the invention. Therefore, the protection range of the rights of the invention should be as defined by the appended claims.

Claims

1. An electrical connector, which is able to be equipped with a power supply module and can receive an electrical power from the power supply module, and the electrical connector is able to provide insertion for an inserting conductive component, thereby providing electrical power to the inserting conductive component, and the electrical connector comprises: a trigger component, which is electrically connected to the power supply module; an inserting terminal, which is electrically connected to the power supply module and comprises an inserting terminal body, a front terminal inserting arm, and a terminal trigger arm, and the inserting terminal body is electrically connected to the terminal trigger arm, and the inserting terminal body comprises a front terminal body extension section, and the front terminal body extension section is electrically connected to the front terminal inserting arm, wherein the front terminal inserting arm comprises a front terminal inserting arm inserting structure, and the terminal trigger arm comprises a terminal trigger arm inserting structure and a terminal trigger arm abutting structure; and an insulating core, which comprises a core abutting space, a core inserting space, and a core guiding structure, and the insulating core is respectively mated with the inserting terminal and the trigger component, such that the front terminal inserting arm inserting structure and the terminal trigger arm abutting structure are respectively located within the core inserting space, and the terminal trigger arm abutting structure and the trigger component are respectively located within the core abutting space, and the core guiding structure provides guidance for the insertion of the inserting conductive component, allowing the inserting conductive component to enter the core inserting space and sequentially insert the front terminal inserting arm inserting structure and the terminal trigger arm inserting structure; wherein when the inserting conductive component inserts the front terminal inserting arm inserting structure, the inserting conductive component is electrically connected to

the front terminal inserting arm inserting structure; and when the inserting conductive component inserts the terminal trigger arm inserting structure, the terminal trigger arm abutting structure is electrically abutted against the trigger component within the core abutting space, triggering the power supply module through the trigger component, thereby allowing the power supply module to provide electrical power to the inserting conductive component via the front terminal inserting arm inserting structure.

2. The electrical connector of claim 1, wherein the trigger component triggers the power supply module, and the power supply module can further provide electrical power to the inserting conductive component via the terminal trigger arm inserting structure.

3. The electrical connector of claim 1, wherein the inserting terminal further comprises a rear terminal inserting arm, and the inserting terminal body further comprises a rear terminal body extension section, and the rear terminal body extension section is electrically connected to the rear terminal inserting arm, wherein, the rear terminal inserting arm comprises a rear terminal inserting arm inserting structure and a rear terminal inserting arm supporting structure, and the rear terminal body extension section comprises a rear terminal body extension section supporting structure, and the rear terminal inserting arm is located behind the front terminal inserting arm, and the rear terminal body extension section is located behind the front terminal body extension section, such that the rear terminal inserting arm supporting structure provide support to the front terminal inserting arm, and the rear terminal body extension section supporting structure provide support to the front terminal body extension section; the rear terminal inserting arm inserting structure is located within the core inserting space, when the inserting conductive component enters the core inserting space, the inserting conductive component can insert the rear terminal inserting arm inserting structure, wherein the time when the inserting conductive component inserts the rear terminal inserting arm inserting structure is earlier than the time when the inserting conductive component inserts the terminal trigger arm inserting structure; and when the inserting conductive component inserts the terminal trigger arm inserting structure, the power supply module can further provide electrical power to the inserting conductive component via the rear terminal inserting arm inserting structure.

4. The electrical connector of claim 1, wherein the trigger component comprises a trigger component mating extension section, a trigger component abutting extension section, and a trigger component supporting extension section, and the insulating core is mated with the trigger component mating extension section, such that the trigger component abutting extension section is located in the core abutting space, when the inserting conductive component inserts the terminal trigger arm inserting structure, the terminal trigger arm abutting structure is electrically abutted against the trigger component abutting extension section in the core abutting space, and the trigger component supporting extension section abuts the insulating core, providing support to the trigger component abutting extension section.

5. The electrical connector of claim 4, wherein the insulating core further comprises a trigger component stop structure, providing support to the trigger component abutting extension section in the trigger component supporting extension section, and the trigger component stop structure provides stop to the trigger component supporting extension section to prevent the trigger component supporting extension section from leaving the insulating core.

6. The electrical connector of claim 4, wherein the trigger component supporting extension section comprises a trigger component supporting extension section elastic structure, and the trigger component supporting extension section elastic structure provides elastic support to the trigger component abutting extension section, allowing the trigger component abutting extension section to be positioned in a predetermined location within the core abutting space.

7. The electrical connector of claim 6, wherein the trigger component supporting extension section elastic structure is a bent structure.

8. The electrical connector of claim 6, wherein the trigger component abutting extension section

and the trigger component supporting extension section can be combined to form a bent structure.

9. The electrical connector of claim 1, wherein the terminal trigger arm comprises a terminal trigger arm mating extension section, a terminal trigger arm abutting extension section, and a terminal trigger arm elastic extension section, wherein the insulating core is mated with the terminal trigger arm mating extension section, such that the terminal trigger arm abutting extension section is located within the core abutting space, and allowing the terminal trigger arm elastic extension section to provide a terminal trigger arm elastic extension section thrust to push the terminal trigger arm abutting extension section away from the trigger component via the terminal trigger arm elastic extension section thrust; when the inserting conductive component inserts the terminal trigger arm inserting structure, the inserting conductive component provides an inserting conductive component thrust to the terminal trigger arm abutting extension section; and when the inserting conductive component thrust is greater than the terminal trigger arm elastic extension section thrust, the terminal trigger arm abutting extension section is moved and abuts against the trigger component.

10. The electrical connector of claim 9, wherein the insulating core further comprises a terminal trigger arm stop structure, and the terminal trigger arm elastic extension section thrust forces the terminal trigger arm abutting extension section to move away from the trigger component, and the terminal trigger arm stop structure provides stop to the terminal trigger arm abutting extension section to prevent the terminal trigger arm abutting extension section from leaving the core abutting space.

11. The electrical connector of claim 9, wherein the insulating core further comprises a terminal trigger arm restriction structure, wherein the inserting conductive component thrust is greater than the terminal trigger arm elastic extension section thrust, and the terminal trigger arm restriction structure provides limitation on the movement path of the pushed terminal trigger arm abutting extension section to prevent the abutting extension section of the terminal trigger arm from abutting the trigger component in an unexpected manner.

12. The electrical connector of claim 1, wherein the trigger component and the inserting terminal are conductive metal bodies.

13. An electric power supply system, comprising: an inserting conductive component; a power supply module capable of providing electric power; and an electrical connector, comprising: a trigger component electrically connected to the power supply module; an inserting terminal electrically connected to the power supply module, the inserting terminal comprising an inserting terminal body, a front terminal inserting arm, and a terminal trigger arm, the inserting terminal body being electrically connected to the terminal trigger arm and the front terminal inserting arm, wherein the front terminal inserting arm comprises a front terminal inserting arm joining structure, and the terminal trigger arm comprises a terminal trigger arm joining structure and a terminal trigger arm abutting structure; and an insulating core, comprising a core abutting space, a core inserting space, and a core guiding structure, the insulating core joining the inserting terminal so that the front terminal inserting arm joining structure and the terminal trigger arm abutting structure are located within the core inserting space, and the terminal trigger arm abutting structure enters the core abutting space, the core guiding structure providing guidance for the insertion of the inserting conductive component, allowing the inserting conductive component to enter the core inserting space and sequentially insert the front terminal inserting arm joining structure and the terminal trigger arm joining structure; wherein, when the inserting conductive component joins the front terminal inserting arm joining structure, the inserting conductive component is electrically connected to the front terminal inserting arm joining structure; and when the inserting conductive component joins the terminal trigger arm joining structure, the terminal trigger arm abutting structure electrically abuts the trigger component within the core abutting space, triggering the power supply module by transmitting a trigger signal via the trigger component, so that the power supply module provides electric power to the inserting conductive component via the front terminal

inserting arm joining structure.

14. The electric power supply system of claim 13, wherein the trigger component triggers the power supply module, and the power supply module can further provide electric power to the inserting conductive component via the terminal trigger arm joining structure.

15. The electric power supply system of claim 13, wherein the power supply module is disposed on a circuit substrate.

16. The electric power supply system of claim 13, further comprising a trigger cable and an inserting cable, the trigger cable electrically connecting the trigger component and the power supply module, and the inserting cable electrically connecting the inserting terminal and the power supply module.

17. The electric power supply system of claim 16, wherein the trigger component comprises a trigger component cable-clamping structure, which clamps the trigger cable to electrically connect the trigger component; and the inserting terminal comprises an inserting terminal cable-clamping structure, and the inserting terminal cable-clamping structure clamps the inserting cable, enabling the inserting cable to electrically connect the inserting terminal.
