

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication	20250286365
Kind Code	A1
Publication Date	September 11, 2025
Inventor(s)	LI; Luo et al.

POWER CONVERSION APPARATUS

Abstract

A power conversion apparatus which includes a direct current end, a power conversion circuit, a direct current side protection circuit, a first alternating current side protection circuit, and an alternating current end. The direct current side protection circuit is connected between the direct current end and protective earthing (PE). A plurality of protection branches of the first alternating current side protection circuit are connected between the alternating current end and the PE, and are configured as: when an alternating current end voltage between the alternating current end and the PE is greater than a second threshold, at least one of the plurality of protection branches is in a conducted state, for the alternating current end voltage to be clamped at a second voltage value.

Inventors:	LI; Luo (Xi'an, CN), RU; Yi (Xi'an, CN), RAO; Sheng (Xi'an, CN)
Applicant:	Huawei Digital Power Technologies Co., Ltd. (Shenzhen, CN)
Family ID:	1000008494566
Assignee:	Huawei Digital Power Technologies Co., Ltd. (Shenzhen, CN)
Appl. No.:	19/063659
Filed:	February 26, 2025

Foreign Application Priority Data

CN	202410254873.9	Mar. 06, 2024
----	----------------	---------------

Publication Classification

Int. Cl.:	H02H9/04 (20060101)
U.S. Cl.:	
CPC	H02H9/045 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to Chinese Patent Application No. 202410254873.9, filed on Mar. 6, 2024, which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] The embodiments relate to the field of power supply technologies, and to a power conversion apparatus.

BACKGROUND

[0003] A lightning strike is a discharge phenomenon that occurs when charged clouds are close to each other or a charged cloud and the ground are close to each other. During this discharge, strong lightning and a loud sound are produced, accompanied by a large amount of energy transfer.

Outdoor devices such as photovoltaic inverters are equipped with lightning protection circuits to ensure safe operation.

[0004] Currently, a three-phase four-wire inverter uses a lightning protection circuit shown in FIG. 1. As shown in FIG. 1, the three-phase four-wire inverter includes a power conversion circuit, a direct current side lightning protection circuit, and an alternating current side lightning protection circuit. The direct current side lightning protection circuit includes a varistor RV1, a varistor RV2, and a varistor RV3, one end of the varistor RV1 and one end of the varistor RV2 are respectively connected to a direct current end PV+ and a direct current end PV- of the inverter, and the other end of the varistor RV1 is connected to the other end of the varistor RV2 and then is connected to protective earthing (PE) via the varistor RV3. The alternating current side lightning protection circuit includes a varistor RV4, a varistor RV5, a varistor RV6, a varistor RV7, and a gas discharge tube GDT 1. One end of the varistor RV4, one end of the varistor RV5, one end of the varistor RV6, and one end of the gas discharge tube GDT 1 are respectively connected to a live wire end L1, a live wire end L2, a live wire end L3, and a neutral wire end N of the inverter; and the other end of the varistor RV4, the other end of the varistor RV5, and the other end of the varistor RV6 are connected to the other end of the gas discharge tube GDT 1 and then connected to the PE via the varistor RV7. When a common-mode lightning current exists on a direct current side of the three-phase four-wire inverter, both a voltage between the direct current end PV+ and the PE and a voltage between the direct current end PV- and the PE are greater than a conduction voltage threshold of the direct current side lightning protection circuit, and the direct current side lightning protection circuit is in a conducted state. Therefore, a part of the common-mode lightning current is discharged via the direct current side lightning protection circuit. In addition, another part of the common-mode lightning current flows through the power conversion circuit and reaches the neutral wire end N, so that the gas discharge tube GDT 1 and the varistor RV7 are turned on for discharge.

[0005] Although the lightning protection circuit shown in FIG. 1 may discharge the common-mode lightning current, after the gas discharge tube GDT 1 and the varistor RV7 are turned on, a clamping voltage between the neutral wire end N and the PE is low. Consequently, a most part of the common-mode lightning current flows through the power conversion circuit, and a power component in the power conversion circuit is damaged. As a result, the inverter cannot work normally.

SUMMARY

[0006] The embodiments provide a power conversion apparatus to prevent a power component in a power conversion circuit from being damaged by a most part of a common-mode lightning current, and protect the power conversion apparatus, so as to improve stability of the power conversion apparatus.

[0007] According to a first aspect, the embodiments provide a power conversion apparatus. The

power conversion apparatus includes a direct current end, a power conversion circuit, a direct current side protection circuit, a first alternating current side protection circuit, and an alternating current end. The power conversion circuit is connected between the direct current end and the alternating current end, and is configured to implement electric energy conversion between the direct current end and the alternating current end. The direct current side protection circuit is connected between the direct current end and PE, and is configured to be in a conducted state when a direct current end voltage between the direct current end and the PE is greater than a first threshold, for the direct current end voltage to be clamped at a first voltage value. The first alternating current side protection circuit includes a plurality of protection branches. The plurality of protection branches are connected between the alternating current end and the PE, and are configured as: when an alternating current end voltage between the alternating current end and the PE is greater than a second threshold, at least one of the plurality of protection branches is in a conducted state, for the alternating current end voltage to be clamped at a second voltage value, where an absolute value of a difference between the first voltage value and the second voltage value is less than or equal to a safety error threshold.

[0008] In this implementation, when a common-mode lightning current exists at the direct current end of the power conversion apparatus, the power conversion apparatus may discharge the common-mode lightning current via the direct current side protection circuit and the at least one protection branch of the first alternating current side protection circuit that are in the conducted state, to quickly discharge the common-mode lightning current. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold (including 0), in a process of discharging the common-mode lightning current, a case in which a clamping voltage of the direct current side protection circuit is greater than a clamping voltage of the first alternating current side protection circuit and a most part of the common-mode lightning current flows through the power conversion circuit can be avoided. This avoids damage to a power component in the power conversion circuit, and protects the power conversion apparatus, to improve stability of the power conversion apparatus.

[0009] With reference to the first aspect, in a first possible implementation, the alternating current end includes a live wire end and a neutral wire end, and the plurality of protection branches include a live wire protection branch and a neutral wire protection branch. The live wire protection branch is connected between the live wire end and the PE, and is configured to be in a conducted state when a live wire end voltage between the live wire end and the PE is greater than the second threshold, for the live wire end voltage to be clamped at the second voltage value. The neutral wire protection branch is connected between the neutral wire end and the PE, and is configured to be in a conducted state when a neutral wire end voltage between the neutral wire end and the PE is greater than the second threshold, for the neutral wire end voltage to be clamped at the second voltage value.

[0010] In this implementation, when the common-mode lightning current exists at the direct current end of the power conversion apparatus, the power conversion apparatus may discharge the common-mode lightning current via the direct current side protection circuit, the live wire protection branch, and the neutral wire protection branch that are in the conducted state, to quickly discharge the common-mode lightning current, and increase a speed of discharging the common-mode lightning current. Because the clamping voltages of the live wire end and the neutral wire end are both the second voltage value, and an absolute value of a difference between the clamping voltage of each of the live wire end and the neutral wire end and the clamping voltage of the direct current end is less than or equal to the safety error threshold (including 0), a case in which a most part of the common-mode lightning currents flow through the power conversion circuit can be avoided. This avoids damage to the power component in the power conversion circuit, and protects the power conversion apparatus, to improve stability of the power conversion apparatus.

[0011] With reference to the first possible implementation of the first aspect, in a second possible

implementation, the live wire protection branch includes a first protection unit and a second protection unit, and the neutral wire protection branch includes a second protection unit and a third protection unit. One end of the first protection unit and one end of the third protection unit are respectively connected to the live wire end and the neutral wire end, and the other end of the first protection unit is connected to the other end of the third protection unit and then connected to the PE via the second protection unit. The first protection unit is configured to be in a turn-on state when the live wire end voltage is greater than the second threshold. The second protection unit is configured to be in a turn-on state when the live wire end voltage or the neutral wire end voltage is greater than the second threshold. The third protection unit is configured to be in a turn-on state when the neutral wire end voltage is greater than the second threshold.

[0012] In this implementation, the first alternating current side protection circuit can implement protection against the common-mode lightning current at the alternating current end, and implement protection against a differential-mode lightning current at the alternating current end. Therefore, applicability is high.

[0013] With reference to the second possible implementation of the first aspect, in a third possible implementation, each of the first protection unit, the second protection unit, and the third protection unit includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0014] In this implementation, a structure of a protection unit of the first alternating current side protection circuit and a type of a protection element of the protection unit are diversified, so that diversity of a structure of the power conversion apparatus can be improved, and flexibility is high.

[0015] With reference to the first aspect, in a fourth possible implementation, the alternating current end includes a first end and a second end, and the plurality of protection branches include a first protection branch and a second protection branch. The first protection branch is connected between the first end and the PE, and the second protection branch is connected between the second end and the PE. An impedance value of the second protection branch increases as a change rate of a current flowing through the second protection branch increases, for the second protection branch to be in a disconnected state and a first end voltage between the first end and the PE to be greater than the second threshold. The first protection branch is configured to be in a conducted state when the first end voltage is greater than the second threshold, for the first end voltage to be clamped at the second voltage value.

[0016] In this implementation, when the common-mode lightning current exists at the direct current end of the power conversion apparatus, the power conversion apparatus may discharge the common-mode lightning current via the direct current side protection circuit and the first protection branch that are in the conducted state, to quickly discharge the common-mode lightning current. Because the second protection branch is in the disconnected state, the clamping voltage of the first end is the second voltage value, and an absolute value of a difference between the clamping voltage of the first end and the clamping voltage of the direct current end is less than or equal to the safety error threshold (including 0), the case in which the most part of the common-mode lightning currents flow through the power conversion circuit can be avoided. This avoids damage to the power component in the power conversion circuit, and protects the power conversion apparatus, to improve stability of the power conversion apparatus.

[0017] With reference to the fourth possible implementation of the first aspect, in a fifth possible implementation, the first protection branch includes a first protection unit and a second protection unit, and the second protection branch includes a second protection unit and a third protection unit. One end of the first protection unit and one end of the third protection unit are respectively connected to the first end and the second end, and the other end of the first protection unit is connected to the other end of the third protection unit and then connected to the PE via the second protection unit. The first protection unit and the second protection unit are configured to be in the

turn-on state when the first end voltage is greater than the second threshold. An impedance value of the third protection unit increases as a change rate of a current flowing through the third protection unit increases, for the third protection unit to be in a turn-off state.

[0018] In this implementation, the first alternating current side protection circuit has a simple structure and is easy to implement.

[0019] With reference to the fifth possible implementation of the first aspect, in a sixth possible implementation, each of the first protection unit and the second protection unit includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode. The third protection unit includes an inductor.

[0020] In this implementation, structures of the first protection unit and the second protection unit, and types of protection elements of the first protection unit and the second protection unit are diversified, so that diversity of the structure of the power conversion apparatus can be improved, and flexibility is high.

[0021] With reference to any one of the fourth possible implementation of the first aspect to the sixth possible implementation of the first aspect, in a seventh possible implementation, the first end is the live wire end, the second end is the neutral wire end, the first protection branch is the live wire protection branch, the second protection branch is the neutral wire protection branch, and the first end voltage is the live wire end voltage. Alternatively, the first end is the neutral wire end, the second end is the live wire end, the first protection branch is the neutral wire protection branch, the second protection branch is the live wire protection branch, and the first end voltage is the neutral wire end voltage.

[0022] In this implementation, when the common-mode lightning current exists at the direct current end of the power conversion apparatus, the power conversion apparatus may discharge the common-mode lightning current via the direct current side protection circuit and the neutral wire protection branch or the live wire protection branch that are in the conducted state, to quickly discharge the common-mode lightning current. Because the live wire protection branch is in a disconnected state, the clamping voltage of the neutral wire end is the second voltage value, or because the neutral wire protection branch is in a disconnected state, the clamping voltage of the live wire end is the second voltage value. In addition, because an absolute value of a difference between the second voltage value and the clamping voltage of the direct current end is less than or equal to the safety error threshold (including 0), the case in which the most part of the common-mode lightning currents flow through the power conversion circuit can be avoided. This avoids damage to the power component in the power conversion circuit, and protects the power conversion apparatus, to improve stability of the power conversion apparatus.

[0023] With reference to any one of the first aspect to the seventh possible implementation of the first aspect, in an eighth possible implementation, the power conversion apparatus further includes a capacitor and a fourth protection unit. The capacitor is connected between the live wire end and the neutral wire end of the power conversion circuit. The fourth protection unit is connected to the capacitor in parallel, and is configured to be in a turn-on state when a voltage between two ends of the capacitor is greater than a third threshold.

[0024] In this implementation, in the power conversion apparatus, a protection unit is connected to the two ends of the capacitor in parallel, so that when a lightning current exists between the live wire end and the neutral wire end, the capacitor is short-circuited by the protection unit connected to the capacitor in parallel. In this way, when the lightning current flows through the inductor and the capacitor in the power conversion apparatus, the inductor and the capacitor cannot oscillate. This can avoid a failure caused by an excessively high voltage at the two ends of the capacitor, to improve stability of the power conversion apparatus.

[0025] With reference to the first aspect to the eighth possible implementation of the first aspect, in a ninth possible implementation, the power conversion apparatus further includes a first inductor, a

second inductor, a fifth protection unit, and a sixth protection unit, and the alternating current end includes a live wire end and a neutral wire end. The live wire end of the power conversion circuit is connected to the live wire end of the power conversion apparatus via the first inductor, and the neutral wire end of the power conversion circuit is connected to the neutral wire end of the power conversion apparatus via the second inductor. The fifth protection unit is connected to the first inductor in parallel, and is configured to be in a turn-on state when a voltage between two ends of the first inductor is greater than a fourth threshold. The sixth protection unit is connected to the second inductor in parallel, and is configured to be in a turn-on state when a voltage between two ends of the second inductor is greater than the fourth threshold.

[0026] In this implementation, in the power conversion apparatus, a protection unit is connected to two ends of the inductor in parallel, so that when a lightning current exists between the live wire end and the neutral wire end, the inductor is short-circuited by the protection unit connected to the inductor in parallel. In this way, when the lightning current flows through the inductor and the capacitor in the power conversion apparatus, the inductor and the capacitor cannot oscillate. This can avoid a failure caused by an excessively high voltage at the two ends of the capacitor, to improve stability of the power conversion apparatus.

[0027] With reference to the eighth possible implementation of the first aspect or the ninth possible implementation of the first aspect, in a tenth possible implementation, each of the fourth protection unit, the fifth protection unit, and the sixth protection unit includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0028] In this implementation, structures of the fourth protection unit, the fifth protection unit, and the sixth protection unit, and types of protection elements of the fourth protection unit, the fifth protection unit, and the sixth protection unit are diversified, so that diversity of the structure of the power conversion apparatus can be improved, and flexibility is high.

[0029] With reference to the second possible implementation of the first aspect or the third possible implementation of the first aspect, in an eleventh possible implementation, the power conversion apparatus further includes a second alternating current side protection circuit. The second alternating current side protection circuit is connected between the live wire end and the neutral wire end, and is configured to be in a conducted state when an alternating current end voltage between the live wire end and the neutral wire end is greater than a fifth threshold, for the alternating current end voltage to be clamped at a third voltage value. The first protection unit and the third protection unit are configured to be in the turn-on state when the alternating current end voltage is greater than a sixth threshold, for the alternating current end voltage to be clamped at a fourth voltage value, where the fourth voltage value is greater than the third voltage value, and the sixth threshold is greater than the fifth threshold.

[0030] In this implementation, because the sixth threshold is greater than the fifth threshold, when a differential-mode lightning current exists between the live wire end and the neutral wire end, the second alternating current side protection circuit is in the conducted state, and the first protection unit and the third protection unit are in a turn-off state. Because a clamping voltage (such as the third voltage value) of the second alternating current side protection circuit is less than clamping voltages (such as the fourth voltage value) of the first protection unit and the third protection unit, the clamping voltage of the alternating current end can be effectively reduced, and the voltage between the two ends of the capacitor can be reduced. This can avoid a failure caused by an excessively high voltage at the two ends of the capacitor, to improve stability of the power conversion apparatus.

[0031] With reference to the eleventh possible implementation of the first aspect, in a twelfth possible implementation, the second alternating current side protection circuit includes a seventh protection unit and an eighth protection unit that are connected in series. Each of the seventh protection unit and the eighth protection unit includes one protection element, or at least two

protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0032] In this implementation, structures of the seventh protection unit and the eighth protection unit, and types of protection elements of the seventh protection unit and the eighth protection unit are diversified, so that diversity of the structure of the power conversion apparatus can be improved, and flexibility is high.

[0033] With reference to the seventh possible implementation of the first aspect, in a thirteenth possible implementation, the power conversion apparatus further includes a second alternating current side protection circuit. The second alternating current side protection circuit is connected between the live wire end and the neutral wire end, and is configured to be in the conducted state when an alternating current end voltage between the live wire end and the neutral wire end is greater than a fifth threshold. The second alternating current side protection circuit includes a seventh protection unit and an eighth protection unit that are connected in series. One of the seventh protection unit and the eighth protection unit includes a gas discharge tube, and the other protection unit includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0034] In this implementation, because a clamping voltage of the gas discharge tube is very low and can be ignored, the power conversion apparatus can reduce the clamping voltage of the alternating current end by disposing the second alternating current side protection circuit including the gas discharge tube, to reduce a voltage between two ends of the capacitor. This can avoid a failure caused by an excessively high voltage at the two ends of the capacitor, to improve stability of the power conversion apparatus.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0035] FIG. 1 is a schematic of a topology of a three-phase four-wire inverter in a conventional technology;

[0036] FIG. 2 is a diagram of an application scenario of a power conversion apparatus according to the embodiments;

[0037] FIG. 3 is a schematic of a topology of a power conversion apparatus according to the embodiments;

[0038] FIG. 4a is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0039] FIG. 4b is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0040] FIG. 4c is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0041] FIG. 4d is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0042] FIG. 4e is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0043] FIG. 4f is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0044] FIG. 4g is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0045] FIG. 4h is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0046] FIG. 5 is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0047] FIG. 6a is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0048] FIG. 6b is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0049] FIG. 6c is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0050] FIG. 6d is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0051] FIG. 6e is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0052] FIG. 6f is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0053] FIG. 6g is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0054] FIG. 6h is a schematic of another topology of a power conversion apparatus according to the embodiments;

[0055] FIG. 6i is a schematic of another topology of a power conversion apparatus according to the embodiments; and

[0056] FIG. 6j is a schematic of another topology of a power conversion apparatus according to the embodiments.

DETAILED DESCRIPTION OF EMBODIMENTS

[0057] A power conversion apparatus provided in the embodiments is applicable to a plurality of application fields such as the energy storage and power generation field, the photovoltaic power generation field, the new energy smart microgrid field, and the power transmission and distribution field. The power conversion apparatus provided in the embodiments may be an inverter, a power conversion system (PCS), an uninterruptible power supply (UPS), or the like, and is applicable to different application scenarios, for example, a photovoltaic power supply scenario, an energy storage power supply scenario, a photovoltaic storage hybrid power supply scenario, and a UPS power supply scenario. The following uses the photovoltaic power supply scenario as an example for description.

[0058] FIG. 2 is a diagram of an application scenario of a power conversion apparatus according to the embodiments. In a photovoltaic power supply scenario, a power conversion apparatus provided in the embodiments is an inverter shown in FIG. 2. The inverter includes a direct current end, a power conversion circuit, a direct current side protection circuit, an alternating current side protection circuit, and an alternating current end. The power conversion circuit includes a DC/DC conversion circuit and an inverter circuit. The direct current end of the inverter is connected to a photovoltaic string, and the alternating current end is connected to an alternating current load (for example, an alternating current power grid or a household device). An input end of the DC/DC conversion circuit is connected to the direct current end of the inverter, an output end of the DC/DC conversion circuit is connected to an input end of the inverter circuit, and an output end of the inverter circuit is connected to the alternating current end of the inverter. The direct current side protection circuit is connected between the direct current end of the inverter and PE (such as a ground or a protection ground). The alternating current side protection circuit includes a plurality of protection branches, and the plurality of protection branches are connected between the alternating current end of the inverter and the protective earthing (PE).

[0059] After the inverter starts running, the DC/DC conversion circuit performs direct current conversion on a direct current generated by the photovoltaic string connected to the direct current end of the inverter, and then outputs a converted direct current to the inverter circuit. The inverter

circuit inverts, into an alternating current, the direct current that is input by an input end of the inverter circuit and that is obtained through direct current conversion, and outputs the alternating current to the alternating current end of the inverter, to supply power to a plurality of types of power consumption devices such as an alternating current power grid and an alternating current load. In addition, when a common-mode lightning current exists between the direct current end of the inverter and the PE, a direct current end voltage between the direct current end of the inverter and the PE is greater than a first threshold, so that the direct current side protection circuit is in a conducted state, for the direct current end voltage to be clamped at a first voltage value. In this way, a part of the common-mode lightning current is discharged to the PE via the direct current side protection circuit. In addition, when the common-mode lightning current exists between the direct current end of the inverter and the PE, another part of the common-mode lightning current sequentially flows through the DC/DC conversion circuit and the inverter circuit, and then reaches the alternating current end of the inverter. In this case, an alternating current end voltage between the alternating current end of the inverter and the PE is greater than a second threshold, so that at least one of the plurality of protection branches of the alternating current side protection circuit is in a conducted state, for the alternating current end voltage to be clamped at a second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the alternating current side protection circuit. An absolute value of a difference between the first voltage value and the second voltage value is less than or equal to a safety error threshold.

[0060] It may be understood that, when a common-mode lightning current exists at the direct current end of the inverter, the inverter may discharge the common-mode lightning current via the direct current side protection circuit and the at least one protection branch of the alternating current side protection circuit that are in the conducted state, to quickly discharge the common-mode lightning current. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold (including 0), in a process of discharging the common-mode lightning current, a case in which a clamping voltage of the direct current side protection circuit is greater than a clamping voltage of the alternating current side protection circuit and a most part of the common-mode lightning current flows through the power conversion circuit can be avoided. This avoids damage to a power component in the power conversion circuit and protects the inverter, to improve stability of the inverter.

[0061] The foregoing is merely an example of the application scenario of the power conversion apparatus provided in the embodiments, but is not exhaustive. The application scenario is not limited.

[0062] With reference to FIG. 3 to FIG. 6j, the following describes an example of a working principle of a power conversion apparatus provided in the embodiments.

[0063] FIG. 3 is a schematic of a topology of a power conversion apparatus according to the embodiments. As shown in FIG. 3, a power conversion apparatus 1 includes a direct current end, a power conversion circuit 11, a direct current side protection circuit 12, a first alternating current side protection circuit 13, and an alternating current end. The direct current end of the power conversion apparatus 1 includes a direct current end in11 and a direct current end in12. The direct current end in11 and the direct current end in12 are configured to respectively connect to a positive electrode and a negative electrode of a direct current power supply. The direct current power supply includes a photovoltaic module, a battery cluster, or the like. The alternating current end of the power conversion apparatus 1 includes a live wire end out11 and a neutral wire end out1N. The live wire end out11 and the neutral wire end out1N are configured to connect to an alternating current load. The alternating current load includes an alternating current power grid or an alternating current power consumption device. The power conversion circuit 11 is connected between the direct current end and the alternating current end of the power conversion apparatus 1. For example, a direct current end in111 and a direct current end in112 of the power conversion circuit 11 are respectively connected to the direct current end in11 and the direct current end in12 of the

power conversion apparatus **1**. An alternating current end (including a live wire end out**11** and a neutral wire end out**11N**) of the power conversion circuit **11** is connected to the live wire end out**11** and a neutral wire end out IN of the power conversion apparatus **1**. The power conversion circuit **11** is configured to implement electric energy conversion between the direct current end and the alternating current end. For example, the power conversion circuit **11** includes a DC/AC conversion circuit, or includes a DC/DC conversion circuit and a DC/AC conversion circuit. The direct current side protection circuit **12** is connected between the direct current end of the power conversion apparatus **1** and PE. The first alternating current side protection circuit **13** includes a plurality of protection branches, and the plurality of protection branches are connected between the alternating current end of the power conversion apparatus **1** and the PE. For example, the plurality of protection branches include a live wire protection branch **131** and a neutral wire protection branch **132**. The live wire protection branch **131** is connected between the live wire end out**11** of the power conversion apparatus **1** and the PE, and the neutral wire protection branch **132** is connected between the neutral wire end out IN of the power conversion apparatus **1** and the PE.

[0064] In an implementation, after the power conversion apparatus **1** works, the power conversion circuit **11** converts a direct current output by the direct current power supply into an alternating current, and outputs the alternating current to the alternating current load, to supply power to the alternating current load. In addition, when a common-mode lightning current exists between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, a direct current end voltage between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1** is greater than a first threshold, so that the direct current side protection circuit **12** is in a conducted state, for the direct current end voltage to be clamped at a first voltage value. In this way, a part of the common-mode lightning current is discharged to the PE via the direct current side protection circuit **12**. In addition, when the common-mode lightning current exists between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, another part of the common-mode lightning current flows through the power conversion circuit **11** and reaches the alternating current end of the power conversion apparatus **1**. In this case, an alternating current end voltage between the alternating current end of the power conversion apparatus **1** and the PE is greater than a second threshold, so that at least one of the live wire protection branch **131** and the neutral wire protection branch **132** is in a conducted state, for the alternating current end voltage to be clamped at a second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the first alternating current side protection circuit **13**. For example, the another part of the common-mode lightning current flows through the power conversion circuit **11** and reaches the live wire end out**11** and/or the neutral wire end out**11N** of the power conversion apparatus **1**. In this case, a live wire end voltage between the live wire end out**11** of the power conversion apparatus **1** and the PE and/or a neutral wire end voltage between the neutral wire end out**11N** of the power conversion apparatus **1** and the PE are/is greater than the second threshold, so that the live wire protection branch **131** and/or the neutral wire protection branch **132** are/is in the conducted state, for the live wire end voltage and/or the neutral wire end voltage to be clamped at the second voltage value. In this way, the another part of the common mode lightning current is discharged to the PE via the live wire protection branch **131** and/or the neutral wire protection branch **132**. An absolute value of a difference between the first voltage value and the second voltage value is less than or equal to a safety error threshold. The safety error threshold is generally a difference between an upper limit value of a clamping voltage error range of the direct current side protection circuit and a lower limit value of a clamping voltage error range of the first alternating current side protection circuit. The clamping voltage error ranges of the direct current side protection circuit and the first alternating current side protection circuit each are determined by a calibrated clamping voltage and a calibrated tolerance of a protection element in the protection circuit. The tolerance is an error range between the calibrated clamping voltage and an actual clamping voltage of the

protection element. For example, if the direct current side protection circuit includes a first varistor and a second varistor that are connected in series, the clamping voltage error range of the direct current side protection circuit is $[V1*(1-a1\%)+V2*(1-a2\%), V1*(1+a1\%)+V2*(1+a2\%)]$, where $V1$ and $V2$ are respectively calibrated clamping voltages of the first varistor and the second varistor, and $a1\%$ and $a2\%$ are respectively calibrated tolerances of the first varistor and the second varistor. The first threshold is an actuating voltage threshold in a case in which the direct current side protection circuit **12** switches from a disconnected state to the conducted state, and the second threshold is an actuating voltage threshold in a case in which the live wire protection branch **131** and the neutral wire protection branch **132** switch from a disconnected state to the conducted state. In addition, a clamping voltage of a circuit in the embodiments is a voltage value obtained after a lightning current passes through the circuit. In the embodiments, a voltage at one end is clamped at a voltage value, that is, a clamping voltage of one end is a voltage value. For example, the clamping voltage is a voltage value obtained after the lightning current passes through a circuit between one end and the reference earthing. For example, that a clamping voltage of the direct current side protection circuit **12** is the first voltage value and that the direct current end voltage is clamped at the first voltage value both mean that a voltage value obtained after the lightning current passes through the direct current side protection circuit **12** is the first voltage value.

[0065] In embodiments, when a common-mode lightning current exists at the direct current end of the power conversion apparatus **1**, the power conversion apparatus **1** may discharge the common-mode lightning current via the direct current side protection circuit **12** and the at least one protection branch of the first alternating current side protection circuit **13** that are in the conducted state, to quickly discharge the common-mode lightning current. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold, in a process of discharging the common-mode lightning current, a case in which the clamping voltage of the direct current side protection circuit **12** is greater than a clamping voltage of the first alternating current side protection circuit **13** and a most part of the common-mode lightning current flows through the power conversion circuit **11** can be avoided. This avoids damage to a power component in the power conversion circuit **11**, and protects the power conversion apparatus **1**, to improve stability of the power conversion apparatus **1**.

[0066] FIG. **4a** is a schematic of another topology of the power conversion apparatus according to the embodiments. As shown in FIG. **4a**, the live wire protection branch **131** in FIG. **3** includes a first protection unit **1311** and a second protection unit **1312**, and the neutral wire protection branch **132** in FIG. **3** includes a second protection unit **1312** and a third protection unit **1321**. One end of the first protection unit **1311** and one end of the third protection unit **1321** are respectively connected to the live wire end out₁₁ and the neutral wire end out_{1N} of the power conversion apparatus **1**. The other end of the first protection unit **1311** is connected to the other end of the third protection unit **1321** and then connected to the PE via the second protection unit **1312**. In addition, the direct current side protection circuit **12** includes a ninth protection unit **121**, a tenth protection unit **122**, and an eleventh protection unit **123**. One end of the ninth protection unit **121** and one end of the eleventh protection unit **123** are respectively connected to the direct current end in₁₁ and the direct current end in₁₂ of the power conversion apparatus **1**. The other end of the ninth protection unit **121** is connected to the other end of the eleventh protection unit **123** and then connected to the PE via the tenth protection unit **122**. Each protection unit of the direct current side protection circuit **12** includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0067] In addition, the power conversion apparatus **1** further includes a capacitor C.sub.Inv-1, a first inductor, and a second inductor. The capacitor C.sub.Inv-1 is connected between the live wire end out₁₁ and the neutral wire end out_{11N} of the power conversion circuit **11**. The first inductor includes an inductor L.sub.filter11 and/or an inductor L.sub.filter_com1, or the first inductor

includes an integrated inductor of the inductor L.sub.filter11 and the inductor L.sub.filter_com1. The second inductor includes an inductor L.sub.filter2 and/or an inductor L.sub.filter_com2, or the second inductor includes an integrated inductor of the inductor L.sub.filter2 and the inductor L.sub.filter_com2. For example, the first inductor is the inductor L.sub.filter11, and the second inductor is the inductor L.sub.filter2. The live wire end out111 of the power conversion circuit 11 is connected to the live wire end out11 of the power conversion apparatus 1 via the inductor L.sub.filter11, and the neutral wire end out11N of the power conversion circuit 11 is connected to the neutral wire end out1N of the power conversion apparatus 1 via the inductor L.sub.filter2. Optionally, the power conversion apparatus 1 further includes relays Relay11-12, and relays Relay21 and Relay22. The live wire end out111 of the power conversion circuit 11 is connected to the live wire end out11 of the power conversion apparatus 1 via the inductor L.sub.filter11, the relay Relay11, and the relay Relay21 in sequence, and the neutral wire end out11N of the power conversion circuit 11 is connected to the neutral wire end out1N of the power conversion apparatus 1 via the inductor L.sub.filter2, the relay Relay12, and the relay Relay22 in sequence.

[0068] In an optional implementation, when a common-mode lightning current exists between the PE, and the direct current end in11 and/or the direct current end in12 of the power conversion apparatus 1, a direct current end voltage between the PE, and the direct current end in11 and/or the direct current end in12 of the power conversion apparatus 1 is greater than a first threshold, so that the direct current side protection circuit 12 is in a conducted state, for the direct current end voltage to be clamped at a first voltage value. In this way, a part of the common-mode lightning current is discharged to the PE via the direct current side protection circuit 12. In addition, when the common-mode lightning current exists between the PE, and the direct current end in11 and/or the direct current end in12 of the power conversion apparatus 1, another part of the common-mode lightning current sequentially flows through the power conversion circuit 11, the inductor, and the relay and reaches the live wire end out11 of the power conversion apparatus 1, and flows through the power conversion circuit 11 and reaches the neutral wire end out1N of the power conversion apparatus 1. In this case, both a live wire end voltage between the live wire end out11 of the power conversion apparatus 1 and the PE and a neutral wire end voltage between the neutral wire end out1N of the power conversion apparatus 1 and the PE are greater than a second threshold, so that both the live wire protection branch 131 and the neutral wire protection branch 132 are in a conducted state, for the live wire end voltage and the neutral wire end voltage to be clamped at the second voltage value. In this way, the another part of the common mode lightning current is discharged to the PE via the live wire protection branch 131 and the neutral wire protection branch 132. An absolute value of a difference between the first voltage value and the second voltage value is less than or equal to a safety error threshold.

[0069] For example, when a common-mode lightning current exists at the direct current end in11 and/or the direct current end in12 of the power conversion apparatus 1, a direct current end voltage between the direct current end in11 of the power conversion apparatus 1 and the PE and/or a direct current end voltage between the direct current end in12 of the power conversion apparatus 1 and the PE are/is greater than the first threshold, and the ninth protection unit 121 and the tenth protection unit 122 are in a turn-on state, and/or the eleventh protection unit 123 and the tenth protection unit 122 are in a turn-on state, for the direct current end voltages to be clamped at the first voltage value. In this way, a part of the common-mode lightning current is discharged to the PE via the ninth protection unit 121 and the tenth protection unit 122, and/or is discharged to the PE via the eleventh protection unit 123 and the tenth protection unit 122. The first voltage value is a sum of a clamping voltage of the ninth protection unit 121 or the eleventh protection unit 123 and a clamping voltage of the tenth protection unit 122. In addition, when the common-mode lightning current exists at the direct current end in11 and/or the direct current end in12 of the power conversion apparatus 1, another part of the common-mode lightning current sequentially flows through the power conversion circuit 11, the inductor, and the relay and reaches the live wire end

out11 of the power conversion apparatus **1**, and flows through the power conversion circuit **11** and reaches the neutral wire end out1N of the power conversion apparatus **1**. In this case, both the live wire end voltage and the neutral wire end voltage are greater than the second threshold, so that the first protection unit **1311**, the second protection unit **1312**, and the third protection unit **1321** are all in a turn-on state, for the live wire end voltage and the neutral wire end voltage to be clamped at the second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the first protection unit **1311**, the second protection unit **1312**, and the third protection unit **1321**, to quickly discharge the common-mode lightning current. The second voltage value is a sum of a clamping voltage of the first protection unit **1311** or the third protection unit **1321** and a clamping voltage of the second protection unit **1312**. Each of the first protection unit **1311**, the second protection unit **1312**, and the third protection unit **1321** includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold, in a process of discharging the common-mode lightning current, a case in which the clamping voltage of the direct current side protection circuit **12** is greater than a clamping voltage of the first alternating current side protection circuit **13** and a most part of the common-mode lightning current flows through the power conversion circuit **11** can be avoided. This avoids damage to a power component in the power conversion circuit **11**, and protects the power conversion apparatus **1**, to improve stability of the power conversion apparatus **1**.

[0070] For example, each protection unit of the direct current side protection circuit **12** and the first alternating current side protection circuit **13** includes a varistor. For details, refer to the power conversion apparatus **1** shown in FIG. **4b**. As shown in FIG. **4b**, the first protection unit **1311** includes a varistor RV41, the second protection unit **1312** includes a varistor RV6, the third protection unit **1321** includes a varistor RV5, the ninth protection unit **121** includes a varistor RV1, the tenth protection unit **122** includes a varistor RV3, and the eleventh protection unit **123** includes a varistor RV2. Optionally, the first protection unit **1311** further includes a fuse Fa, and the fuse Fa is connected to the varistor RV41 in series. The third protection unit **1321** further includes a fuse Fn, and the fuse Fn is connected to the varistor RV6 in series.

[0071] In another optional implementation, when a common-mode lightning current exists between the PE, and the direct current end in11 and/or the direct current end in12 of the power conversion apparatus **1**, a direct current end voltage between the PE, and the direct current end in11 and/or the direct current end in12 of the power conversion apparatus **1** is greater than a first threshold, so that the direct current side protection circuit **12** is in a conducted state, for the direct current end voltage to be clamped at a first voltage value. In this way, a part of the common-mode lightning current is discharged to the PE via the direct current side protection circuit **12**. In addition, when the common-mode lightning current exists between the PE, and the direct current end in11 and/or the direct current end in12 of the power conversion apparatus **1**, another part of the common-mode lightning current sequentially flows through the power conversion circuit **11**, the inductor, and the relay and reaches the live wire end out11 and the neutral wire end out1N of the power conversion apparatus **1** (or passes through the power conversion circuit **11** and reaches the neutral wire end out1N). In this case, the neutral wire protection branch **132** is in a disconnected state, and a live wire end voltage between the live wire end out11 of the power conversion apparatus **1** and the PE is greater than a second threshold, so that the live wire protection branch **131** is in a conducted state, for the live wire end voltage to be clamped at a second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the live wire protection branch **131**. An absolute value of a difference between the first voltage value and the second voltage value is less than or equal to a safety error threshold.

[0072] For example, when a common-mode lightning current exists at the direct current end in11

and/or the direct current end in **12** of the power conversion apparatus **1**, a direct current end voltage between the direct current end in **11** of the power conversion apparatus **1** and the PE and/or a direct current end voltage between the direct current end in **12** of the power conversion apparatus **1** and the PE are/is greater than the first threshold, and the ninth protection unit **121** and the tenth protection unit **122** are in a turn-on state, and/or the eleventh protection unit **123** and the tenth protection unit **122** are in a turn-on state, for the direct current end voltages to be clamped at the first voltage value. In this way, a part of the common-mode lightning current is discharged to the PE via the ninth protection unit **121** and the tenth protection unit **122**, and/or is discharged to the PE via the eleventh protection unit **123** and the tenth protection unit **122**. In addition, when the common-mode lightning current exists at the direct current end in **11** and/or the direct current end in **12** of the power conversion apparatus **1**, another part of the common-mode lightning current sequentially flows through the power conversion circuit **11**, the inductor, and the relay and reaches the live wire end out **11** and the neutral wire end out **1N** of the power conversion apparatus **1** (or passes through the power conversion circuit **11** and reaches the neutral wire end out **1N**). Because a lightning current value (for example, thousands of A) is far greater than a normal operating current value (for example, dozens of A) of the power conversion apparatus **1**, when the common-mode lightning current flows through the neutral wire protection branch **132**, a change rate of a current flowing through the neutral wire protection branch **132** increases, so that an impedance value of the neutral wire protection branch **132** increases accordingly. In this case, the neutral wire protection branch **132** is in the disconnected state, and the live wire end voltage is greater than the second threshold. For example, when the common-mode lightning current flows through the third protection unit **1321**, a change rate of a current flowing through the third protection unit **1321** increases, so that an impedance value of the third protection unit **1321** increases accordingly. In this case, the third protection unit **1321** is in a turn-off state, so that the neutral wire protection branch **132** is in the disconnected state, and the live wire end voltage is greater than the second threshold. When the live wire end voltage is greater than the second threshold, both the first protection unit **1311** and the second protection unit **1312** are in a turn-on state, for the live wire end voltage to be clamped at the second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the first protection unit **1311** and the second protection unit **1312**, to quickly discharge the common-mode lightning current. Each of the first protection unit **1311** and the second protection unit **1312** includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode. The third protection unit **1321** includes an inductor. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold, in a process of discharging the common-mode lightning current, a case in which the clamping voltage of the direct current side protection circuit **12** is greater than a clamping voltage of the first alternating current side protection circuit **13** and a most part of the common-mode lightning current flows through the power conversion circuit **11** can be avoided. This avoids damage to a power component in the power conversion circuit **11**, and protects the power conversion apparatus **1**, to improve stability of the power conversion apparatus **1**.

[0073] For example, each of the direct current side protection circuit **12**, the first protection unit **1311**, and the second protection unit **1312** includes one varistor, and the third protection unit **1321** includes an inductor. For details, refer to the power conversion apparatus **1** shown in FIG. 4c. As shown in FIG. 4c, the first protection unit **1311** includes a varistor RV41, the second protection unit **1312** includes a varistor RV6, the third protection unit **1321** includes an inductor Ln, the ninth protection unit **121** includes a varistor RV1, the tenth protection unit **122** includes a varistor RV3, and the eleventh protection unit **123** includes a varistor RV2. Optionally, the first protection unit **1311** further includes a fuse Fa, and the fuse Fa is connected to the varistor RV41 in series. The third protection unit **1321** further includes a fuse Fn, and the fuse Fn is connected to the inductor

Ln in series.

[0074] In still another optional implementation, when a common-mode lightning current exists between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, a direct current end voltage between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1** is greater than a first threshold, so that the direct current side protection circuit **12** is in a conducted state, for the direct current end voltage to be clamped at a first voltage value. In this way, a part of the common-mode lightning current is discharged to the PE via the direct current side protection circuit **12**. In addition, when the common-mode lightning current exists between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, another part of the common-mode lightning current sequentially flows through the power conversion circuit **11**, the inductor, and the relay and reaches the live wire end out**11** and the neutral wire end out**1N** of the power conversion apparatus **1** (or passes through the power conversion circuit **11** and reaches the neutral wire end out**1N**). In this case, the live wire protection branch **131** is in a disconnected state, and a neutral wire end voltage between the neutral wire end out**1N** of the power conversion apparatus **1** and the PE is greater than a second threshold, so that the neutral wire protection branch **132** is in a conducted state, for the neutral wire end voltage to be clamped at a second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the neutral wire protection branch **132**. An absolute value of a difference between the first voltage value and the second voltage value is less than or equal to a safety error threshold.

[0075] In an example, when a common-mode lightning current exists at the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, a direct current end voltage between the direct current end in**11** of the power conversion apparatus **1** and the PE and/or a direct current end voltage between the direct current end in**12** of the power conversion apparatus **1** and the PE are/is greater than the first threshold, and the ninth protection unit **121** and the tenth protection unit **122** are in a turn-on state, and/or the eleventh protection unit **123** and the tenth protection unit **122** are in a turn-on state, for the direct current end voltages to be clamped at the first voltage value. In this way, a part of the common-mode lightning current is discharged to the PE via the ninth protection unit **121** and the tenth protection unit **122**, and/or is discharged to the PE via the eleventh protection unit **123** and the tenth protection unit **122**. In addition, when the common-mode lightning current exists at the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, another part of the common-mode lightning current sequentially flows through the power conversion circuit **11**, the inductor, and the relay and reaches the live wire end out**11** and the neutral wire end out IN of the power conversion apparatus **1** (or passes through the power conversion circuit **11** and reaches the neutral wire end out**1N**). Because a lightning current value (for example, thousands of A) is far greater than a normal operating current value (for example, dozens of A) of the power conversion apparatus **1**, when the common-mode lightning current flows through the live wire protection branch **131**, a change rate of a current flowing through the live wire protection branch **131** increases, so that an impedance value of the live wire protection branch **131** increases accordingly. In this case, the live wire protection branch **131** is in the disconnected state, and the neutral wire end voltage is greater than the second threshold. For this implementation, positions of the first protection unit **1311** and the third protection unit **1321** in FIG. 4a are exchanged. For example, when the common-mode lightning current flows through the third protection unit **1321**, a change rate of a current flowing through the third protection unit **1321** increases, so that an impedance value of the third protection unit **1321** increases accordingly. In this case, the third protection unit **1321** is in a turn-off state, so that the live wire protection branch **131** is in the disconnected state, and the neutral wire end voltage is greater than the second threshold. When the neutral wire end voltage is greater than the second threshold, both the first protection unit **1311** and the second protection unit **1312** are in a turn-on state, for the neutral wire end voltage to be clamped at the second voltage value. In this way, the

another part of the common-mode lightning current is discharged to the PE via the first protection unit **1311** and the second protection unit **1312**, to quickly discharge the common-mode lightning current. Each of the first protection unit **1311** and the second protection unit **1312** includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode, and the third protection unit **1321** includes an inductor. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold, in a process of discharging the common-mode lightning current, a case in which the clamping voltage of the direct current side protection circuit **12** is greater than a clamping voltage of the first alternating current side protection circuit **13** and a most part of the common-mode lightning current flows through the power conversion circuit **11** can be avoided. This avoids damage to a power component in the power conversion circuit **11**, and protects the power conversion apparatus **1**, to improve stability of the power conversion apparatus **1**.

[0076] For example, each of the direct current side protection circuit **12**, the first protection unit **1311**, and the second protection unit **1312** includes one varistor, and the third protection unit **1321** includes an inductor. For details, refer to the power conversion apparatus **1** shown in FIG. **4d**. As shown in FIG. **4d**, the first protection unit **1311** includes a varistor RV5, the second protection unit **1312** includes a varistor RV6, the third protection unit **1321** includes an inductor La, the ninth protection unit **121** includes a varistor RV1, the tenth protection unit **122** includes a varistor RV3, and the eleventh protection unit **123** includes a varistor RV2. Optionally, the third protection unit **1321** further includes a fuse Fa, and the fuse Fa is connected to the inductor La in series.

[0077] In addition, when a differential-mode lightning current exists between the live wire end out11 and the neutral wire end out1N of the power conversion apparatus **1**, a voltage between the live wire end out11 and the neutral wire end out1N of the power conversion apparatus **1** is greater than an actuating voltage threshold of the first protection unit **1311** and the third protection unit **1321**, and the first protection unit **1311** and the third protection unit **1321** are in a turn-on state. In this case, a differential-mode lightning current loop **1** in which the differential-mode lightning current flows out from the live wire end out11, sequentially flows through the first protection unit **1311** and the third protection unit **1321**, and then flows into the neutral wire end out1N is formed, and a differential-mode lightning current loop **2** in which the differential-mode lightning current flows out from the live wire end out11, sequentially flows through the inductor L.sub.filter_com1, the relay, the inductor L.sub.filter11, the capacitor C.sub.Inv-1, the inductor L.sub.filter2, the relay, and the inductor L.sub.filter_com2, and then flows into the neutral wire end out1N is formed. Because the inductor and the capacitor in the differential-mode lightning current loop **2** oscillate, a voltage borne by the capacitor is excessively high, and consequently the capacitor fails.

[0078] In view of this, in the power conversion apparatus **1**, protection units may further be connected to two ends of the capacitor or the inductor in parallel, so that when a lightning current exists between the live wire end out11 and the neutral wire end out1N of the power conversion apparatus **1**, the capacitor or the inductor is short-circuited by the protection unit connected to the capacitor or the inductor in parallel. Alternatively, a second alternating current protection circuit may be disposed between the live wire end out11 and the neutral wire end out1N of the power conversion apparatus **1**, so that a clamping voltage of the second alternating current protection circuit is low, to avoid a capacitor failure.

[0079] In an optional implementation, the power conversion apparatus **1** further includes a fourth protection unit **141**, and the fourth protection unit **141** is connected to the capacitor C.sub.Inv-1 in parallel. The fourth protection unit **141** includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0080] For example, when the differential-mode lightning current exists between the live wire end out11 and the neutral wire end out1N of the power conversion apparatus **1**, a voltage between two

ends of the capacitor C.sub.Inv-1 is greater than a third threshold. In this case, the fourth protection unit **141** is in a turn-on state, so that the capacitor C.sub.Inv-1 is short-circuited, and the inductor and the capacitor in the differential-mode lightning current loop **2** cannot oscillate. This can avoid a failure caused by an excessively high voltage between the two ends of the capacitor, to improve stability of the power conversion apparatus **1**.

[0081] For example, as shown in FIG. **4c**, the fourth protection unit **141** includes a varistor RV**71**. Optionally, the fourth protection unit **141** further includes a fuse Finv-**1**, and the fuse Finv-**1** is connected to the varistor RV**71** in series.

[0082] In another optional implementation, the power conversion apparatus **1** further includes a fifth protection unit **151** and a sixth protection unit **16**. The fifth protection unit **151** is connected to the first inductor in parallel, and the sixth protection unit **16** is connected to the second inductor in parallel. For example, the first inductor is the inductor L.sub.filter11, and the second inductor is the inductor L.sub.filter2. Each of the fifth protection unit **151** and the sixth protection unit **16** includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0083] For example, when the differential-mode lightning current exists between the live wire end out**11** and the neutral wire end out**1N** of the power conversion apparatus **1**, both a voltage between two ends of the inductor L.sub.filter11 and a voltage between two ends of the inductor L.sub.filter2 are greater than a fourth threshold. In this case, both the fifth protection unit **151** and the sixth protection unit **16** are in a turn-on state, so that both the inductor L.sub.filter11 and the inductor L.sub.filter2 are short-circuited, and the inductor and the capacitor in the differential-mode lightning current loop **2** cannot oscillate. This can avoid a failure caused by an excessively high voltage between the two ends of the capacitor, and further improve stability of the power conversion apparatus **1**.

[0084] For example, as shown in FIG. **4f**, the fifth protection unit **151** includes a gas discharge tube GDT **11**, and the sixth protection unit **16** includes a gas discharge tube GDT **2**.

[0085] In another optional implementation, the power conversion apparatus **1** further includes a second alternating current side protection circuit **171**, and the second alternating current side protection circuit **171** is connected between the live wire end out**11** and the neutral wire end out **IN** of the power conversion apparatus **1**, and is configured to be in a conducted state when an alternating current end voltage between the live wire end out**11** and the neutral wire end out**1N** of the power conversion apparatus **1** is greater than a fifth threshold, for the alternating current end voltage to be clamped at a third voltage value. The second alternating current side protection circuit **171** includes a seventh protection unit and an eighth protection unit that are connected in series, and each of the seventh protection unit and the eighth protection unit includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode. The first protection unit **1311** and the third protection unit **1321** are configured to be in a turn-on state when the alternating current end voltage is greater than a sixth threshold, for the alternating current end voltage to be clamped at a fourth voltage value, where the fourth voltage value is greater than the third voltage value, and the sixth threshold is greater than the fifth threshold.

[0086] In an example, when the differential-mode lightning current exists between the live wire end out**11** and the neutral wire end out**1N** of the power conversion apparatus **1**, the alternating current end voltage starts to increase. Because the fifth threshold is less than the sixth threshold, when the alternating current end voltage is greater than the fifth threshold, both the seventh protection unit and the eighth protection unit are in a turn-on state, so that the alternating current end voltage is clamped at the third voltage value, and the first protection unit **1311** and the third protection unit **1321** are short-circuited by the second alternating current side protection circuit **171** and are in a turn-off state. In this way, a part of the differential-mode lightning current is discharged

via the second alternating current side protection circuit **171**, and another part of the differential-mode lightning current is discharged via a loop in which the inductor and the capacitor between the live wire end out**11** and the neutral wire end out**1N** are located. In addition, if there is no second alternating current side protection circuit **171** in the power conversion apparatus **1**, when the differential-mode lightning current exists between the live wire end out**11** and the neutral wire end out**1N** of the power conversion apparatus **1**, the alternating current end voltage is greater than a sixth threshold, and both the first protection unit **1311** and the third protection unit **1321** are in the turn-on state, for the alternating current end voltage to be clamped at a fourth voltage value. In this way, a part of the differential-mode lightning current is discharged via the first protection unit **1311** and the third protection unit **1321**, and another part of the differential-mode lightning current is discharged via a loop in which the inductor and the capacitor between the live wire end out**11** and the neutral wire end out**1N** are located. Because the third voltage value is less than the fourth voltage value, the power conversion apparatus **1** may reduce a clamping voltage of the alternating current end by disposing the second alternating current side protection circuit **171**, to reduce a voltage between two ends of the capacitor. This can avoid a failure caused by an excessively high voltage at the two ends of the capacitor, to improve stability of the power conversion apparatus **1**. [0087] For example, as shown in FIG. **4g**, the first protection unit **1311** includes a varistor RV**41**, the third protection unit **1321** includes a varistor RV**5**, the seventh protection unit includes a varistor RV**81**, and the eighth protection unit includes a gas discharge tube GDT **31**. A sum of an actuating voltage threshold of the varistor RV**41** and an actuating voltage threshold of the varistor RV**5** is greater than a sum of an actuating voltage threshold of the varistor RV**81** and an actuating voltage threshold of the gas discharge tube GDT **31**, a sum of a clamping voltage of the varistor RV**41** and a clamping voltage of the varistor RV**5** is greater than a sum of a clamping voltage of the varistor RV**81** and a clamping voltage of the gas discharge tube GDT **31**.

[0088] In still another optional implementation, the power conversion apparatus **1** further includes a second alternating current side protection circuit **171**, and the second alternating current side protection circuit **171** is connected between the live wire end out**11** and the neutral wire end out**1N** of the power conversion apparatus **1**, and is configured to be in a conducted state when an alternating current end voltage between the live wire end out**11** and the neutral wire end out**1N** of the power conversion apparatus **1** is greater than a fifth threshold. The second alternating current side protection circuit **171** includes a seventh protection unit and an eighth protection unit that are connected in series. One of the seventh protection unit and the eighth protection unit includes a gas discharge tube, and the other protection unit includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0089] For example, as shown in FIG. **4h**, the first protection unit **1311** includes a varistor RV**41**, the third protection unit **1321** includes an inductor Ln, the seventh protection unit includes a varistor RV**81**, and the eighth protection unit includes a gas discharge tube GDT **31**. For example, when the differential-mode lightning current exists between the live wire end out**11** and the neutral wire end out **1N** of the power conversion apparatus **1**, a change rate of a current flowing through the inductor Ln increases, and an impedance value of the inductor Ln increases accordingly. In this way, a branch in which the inductor Ln and the varistor RV**41** are located is in a disconnected state. When the differential-mode lightning current exists between the live wire end out**11** and the neutral wire end out**1N** of the power conversion apparatus **1**, the alternating current end voltage is greater than a fifth threshold, and both the varistor RV**81** and the gas discharge tube GDT **31** are in a turn-on state. In this way, a part of the differential-mode lightning current is discharged via the second alternating current side protection circuit **171**, and another part of the differential mode lightning current is discharged via a loop in which the inductor and the capacitor between the live wire end out**11** and the neutral wire end out**1N** are located. Because a clamping voltage of the gas discharge tube is very low and can be ignored, the power conversion apparatus **1** can reduce the clamping

voltage of the alternating current end by disposing the second alternating current side protection circuit **171** including the gas discharge tube, to reduce a voltage between two ends of the capacitor. This can avoid a failure caused by an excessively high voltage at the two ends of the capacitor, to improve stability of the power conversion apparatus **1**.

[0090] It should be noted that, a manner of disposing the protection units at two ends of the capacitor or the inductor shown in FIG. **4e** and FIG. **4f** to avoid an excessively high voltage between the two ends of the capacitor is also applicable to the power conversion apparatus **1** shown in FIG. **4c** and FIG. **4d**. A manner of disposing the second alternating current side protection circuit **171** shown in FIG. **4h** to reduce the voltage between the two ends of the capacitor is also applicable to the power conversion apparatus **1** shown in FIG. **4d**.

[0091] In embodiments, when the common-mode lightning current exists at the direct current end of the power conversion apparatus **1**, the power conversion apparatus **1** may discharge the common-mode lightning current via the direct current side protection circuit **12**, and the live wire protection branch **131** and/or the neutral wire protection branch **132** that are in the conducted state, to quickly discharge the common-mode lightning current. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold, in a process of discharging the common-mode lightning current, a case in which the clamping voltage of the direct current side protection circuit **12** is greater than a clamping voltage of the first alternating current side protection circuit **13** and a most part of the common-mode lightning current flows through the power conversion circuit **11** can be avoided. This avoids damage to a power component in the power conversion circuit **11**, and protects the power conversion apparatus **1**, to improve stability of the power conversion apparatus **1**. In addition, when the differential-mode lightning current exists between the live wire end out**11** and the neutral wire end out**1N** of the power conversion apparatus **1**, a protection circuit is connected between the two ends of the capacitor or the inductor in parallel, so that the inductor and the capacitor cannot oscillate, or the second alternating current side protection circuit **171** with a low clamping voltage is disposed between the live wire end out**11** and the neutral wire end out**1N** of the power conversion apparatus **1**. This can avoid a failure caused by an excessively high voltage at the two ends of the capacitor, to improve stability of the power conversion apparatus **1**.

[0092] FIG. **5** is a schematic of another topology of the power conversion apparatus according to the embodiments. As shown in FIG. **5**, compared with the power conversion apparatus **1** shown in FIG. **3**, the alternating current end of the power conversion apparatus **1** further includes a live wire end out**12** and a live wire end out**13**, and the alternating current end of the power conversion circuit **11** further includes a live wire end out**112** and a live wire end out**113**. The live wire end out**112** and the live wire end out**113** of the power conversion circuit **11** are respectively connected to the live wire end out**12** and the live wire end out**13** of the power conversion apparatus **1**. In addition, the first alternating current side protection circuit **13** further includes a live wire protection branch **133** and a live wire protection branch **134**. The live wire protection branch **133** is connected between the live wire end out**12** of the power conversion apparatus **1** and the PE, and the live wire protection branch **134** is connected between the live wire end out**13** of the power conversion apparatus **1** and the PE.

[0093] In an implementation, after the power conversion apparatus **1** works, the power conversion circuit **11** converts a direct current output by the direct current power supply into an alternating current, and outputs the alternating current to the alternating current load, to supply power to the alternating current load. In addition, when a common-mode lightning current exists between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, a direct current end voltage between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1** is greater than a first threshold, so that the direct current side protection circuit **12** is in a conducted state, for the direct current end voltage to be clamped at a first voltage value. In this way, a part of the common-mode lightning current is

discharged to the PE via the direct current side protection circuit **12**. In addition, when the common-mode lightning current exists between the PE, and the direct current end in **11** and/or the direct current end in **12** of the power conversion apparatus **1**, another part of the common-mode lightning current flows through the power conversion circuit **11** and reaches the alternating current end of the power conversion apparatus **1**. In this case, an alternating current end voltage between the alternating current end of the power conversion apparatus **1** and the PE is greater than a second threshold, so that at least one of the live wire protection branch (including the live wire protection branch **131**, the live wire protection branch **133**, and the live wire protection branch **134**) and/or the neutral wire protection branch **132** of the first alternating current side protection circuit **13** is in a conducted state, for the alternating current end voltage to be clamped at a second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the first alternating current side protection circuit **13**. For example, the another part of the common-mode lightning current flows through the power conversion circuit **11** and reaches the live wire end (including the live wire ends out **11** to out **13**) and/or the neutral wire end out **1N** of the power conversion apparatus **1**. In this case, a live wire end voltage between the live wire end of the power conversion apparatus **1** and the PE and/or a neutral wire end voltage between the neutral wire end out **1N** of the power conversion apparatus **1** and the PE are/is greater than the second threshold, so that the live wire protection branch and/or the neutral wire protection branch **132** are/is in the conducted state, for the live wire end voltage and/or the neutral wire end voltage to be clamped at the second voltage value. In this way, the another part of the common mode lightning current is discharged to the PE via the live wire protection branch and/or the neutral wire protection branch **132**. An absolute value of a difference between the first voltage value and the second voltage value is less than or equal to a safety error threshold.

[0094] In embodiments, when a common-mode lightning current exists at the direct current end of the power conversion apparatus **1**, the power conversion apparatus **1** may discharge the common-mode lightning current via the direct current side protection circuit **12**, and the live wire protection branch and/or the neutral wire protection branch of the first alternating current side protection circuit **13** that are in the conducted state, to quickly discharge the common-mode lightning current. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold, in a process of discharging the common-mode lightning current, a case in which the clamping voltage of the direct current side protection circuit **12** is greater than a clamping voltage of the first alternating current side protection circuit **13** and a most part of the common-mode lightning current flows through the power conversion circuit **11** can be avoided. This avoids damage to a power component in the power conversion circuit **11**, and protects the power conversion apparatus **1**, to improve stability of the power conversion apparatus **1**. In addition, the power conversion apparatus **1** provided in the embodiments is not only applicable to a single-phase power conversion apparatus, but also applicable to a three-phase power conversion apparatus, and has high applicability.

[0095] FIG. **6a** is a schematic of another topology of the power conversion apparatus according to the embodiments. As shown in FIG. **6a**, the live wire protection branch **131** in FIG. **5** includes a first protection unit **1311** and a second protection unit **1312**, the live wire protection branch **133** in FIG. **5** includes a first protection unit **1331** and a second protection unit **1312**, the live wire protection branch **134** in FIG. **5** includes a first protection unit **1341** and a second protection unit **1312**, and the neutral wire protection branch **132** in FIG. **5** includes a third protection unit **1321** and a second protection unit **1312**. One end of the first protection unit **1311**, one end of the first protection unit **1331**, one end of the first protection unit **1341**, and one end of the third protection unit **1321** are respectively connected to the live wire end out **11**, the live wire end out **12**, the live wire end out **13**, and the neutral wire end out **1N** of the power conversion apparatus **1**. The other end of the first protection unit **1311**, the other end of the first protection unit **1331**, the other end of the first protection unit **1341**, and the other end of the third protection unit **1321** are connected and then

connected to the PE via the second protection unit **1312**.

[0096] In addition, the power conversion apparatus **1** further includes a capacitor C.sub.Inv-1, a capacitor C.sub.Inv-2, a capacitor C.sub.Inv-3, a first inductor, and a second inductor. The capacitor C.sub.Inv-1 is connected between the live wire end out**111** and the neutral wire end out**11N** of the power conversion circuit **11**. The capacitor C.sub.Inv-2 is connected between the live wire end out**112** and the neutral wire end out**11N** of the power conversion circuit **11**. The capacitor C.sub.Inv-3 is connected between the live wire end out**113** and the neutral wire end out**11N** of the power conversion circuit **11**. The first inductor includes inductors L.sub.filter11-13 and/or inductors L.sub.filter_com1-3, or the first inductor includes an integrated inductor of the inductor L.sub.filter11 and the inductor L.sub.filter_com1, an integrated inductor of the inductor L.sub.filter12 and the inductor L.sub.filter_com2, and an integrated inductor of the inductor L.sub.filter13 and the inductor L.sub.filter_com3. The second inductor includes an inductor L.sub.filter2 and/or an inductor L.sub.filter_com4, or the second inductor includes an integrated inductor of the inductor L.sub.filter2 and the inductor L.sub.filter_com4. For example, the first inductor is the inductors L.sub.filter11-13, and the second inductor is the inductor L.sub.filter2. The live wire end out**111** of the power conversion circuit **11** is connected to the live wire end out**11** of the power conversion apparatus **1** via the inductor L.sub.filter11, the live wire end out**112** of the power conversion circuit **11** is connected to the live wire end out**12** of the power conversion apparatus **1** via the inductor L.sub.filter12, the live wire end out**113** of the power conversion circuit **11** is connected to the live wire end out**13** of the power conversion apparatus **1** via the inductor L.sub.filter13, and the neutral wire end out**11N** of the power conversion circuit **11** is connected to the neutral wire end out**1N** of the power conversion apparatus **1** via the inductor L.sub.filter2. Optionally, the power conversion apparatus **1** further includes relays Relay**11** to Relay**14** and relays Relay**21** to Relay**24**. The live wire end out**111** of the power conversion circuit **11** is connected to the live wire end out**11** of the power conversion apparatus **1** via the inductor L.sub.filter11, the relay Relay**11**, and the relay Relay**21** in sequence. The live wire end out**112** of the power conversion circuit **11** is connected to the live wire end out**12** of the power conversion apparatus **1** via the inductor L.sub.filter12, the relay Relay**12**, and the relay Relay**22** in sequence. The live wire end out**113** of the power conversion circuit **11** is connected to the live wire end out**13** of the power conversion apparatus **1** via the inductor L.sub.filter13, the relay Relay**13**, and the relay Relay**23** in sequence. The neutral wire end out**11N** of the power conversion circuit **11** is connected to the neutral wire end out**1N** of the power conversion apparatus **1** via the inductor L.sub.filter2, the relay Relay**14**, and the relay Relay**24** in sequence.

[0097] In an optional implementation, when a common-mode lightning current exists between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, a direct current end voltage between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1** is greater than a first threshold, so that the direct current side protection circuit **12** is in a conducted state, for the direct current end voltage to be clamped at a first voltage value. In this way, a part of the common-mode lightning current is discharged to the PE via the direct current side protection circuit **12**. In addition, when the common-mode lightning current exists between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, another part of the common-mode lightning current sequentially flows through the power conversion circuit **11**, the inductor, and the relay and reaches the live wire end out**11**, the live wire end out**12**, the live wire end out**13**, and the neutral wire end out**1N** of the power conversion apparatus **1** (or passes through the power conversion circuit **11** and reaches the neutral wire end out**1N**). In this case, a live wire end voltage between the live wire end out**11** of the power conversion apparatus **1** and the PE, a live wire end voltage between the live wire end out**12** of the power conversion apparatus **1** and the PE, a live wire end voltage between the live wire end out**13** of the power conversion apparatus **1** and the PE, and a neutral wire end voltage between the neutral wire end out**1N** of the power conversion

apparatus **1** and the PE are all greater than a second threshold, so that the live wire protection branch **131**, the live wire protection branch **133**, the live wire protection branch **134**, and the neutral wire protection branch **132** are all in a conducted state, for the live wire end voltages and the neutral wire end voltage to clamp a second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the live wire protection branch **131**, the live wire protection branch **133**, the live wire protection branch **134**, and the neutral wire protection branch **132**. An absolute value of a difference between the first voltage value and the second voltage value is less than or equal to a safety error threshold.

[0098] For example, when a common-mode lightning current exists at the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, a direct current end voltage between the direct current end in**11** of the power conversion apparatus **1** and the PE and/or a direct current end voltage between the direct current end in**12** of the power conversion apparatus **1** and the PE are/is greater than the first threshold, and the ninth protection unit **121** and the tenth protection unit **122** are in a turn-on state, and/or the eleventh protection unit **123** and the tenth protection unit **122** are in a turn-on state. In this way, a part of the common-mode lightning current is discharged to the PE via the ninth protection unit **121** and the tenth protection unit **122**, and/or is discharged to the PE via the eleventh protection unit **123** and the tenth protection unit **122**. In addition, when the common-mode lightning current exists at the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, another part of the common-mode lightning current sequentially flows through the power conversion circuit **11**, the inductor, and the relay and reaches the live wire end out**11**, the live wire end out**12**, the live wire end out**13**, and the neutral wire end out**1N** of the power conversion apparatus **1** (or passes through the power conversion circuit **11** and reaches the neutral wire end out**1N**). In this case, a live wire end voltage and a neutral wire end voltage are both greater than the second threshold, so that the first protection unit **1311**, the first protection unit **1331**, the first protection unit **1341**, the second protection unit **1312**, and the third protection unit **1321** are all in a turn-on state, for the live wire end voltage and the neutral wire end voltage to be clamped at the second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the first protection unit **1311**, the first protection unit **1331**, the first protection unit **1341**, the second protection unit **1312**, and the third protection unit **1321**, to quickly discharge the common-mode lightning current. Each of the first protection unit **1311**, the first protection unit **1331**, the first protection unit **1341**, the second protection unit **1312**, and the third protection unit **1321** includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold, in a process of discharging the common-mode lightning current, a case in which the clamping voltage of the direct current side protection circuit **12** is greater than a clamping voltage of the first alternating current side protection circuit **13** and a most part of the common-mode lightning current flows through the power conversion circuit **11** can be avoided. This avoids damage to a power component in the power conversion circuit **11**, and protects the power conversion apparatus **1**, to improve stability of the power conversion apparatus **1**.

[0099] For example, each protection unit of the direct current side protection circuit **12** and the first alternating current side protection circuit **13** includes a varistor. For details, refer to the power conversion apparatus **1** shown in FIG. **6b**. As shown in FIG. **6b**, the first protection unit **1311** includes a varistor RV**41**, the first protection unit **1331** includes a varistor RV**42**, the first protection unit **1341** includes a varistor RV**43**, the second protection unit **1312** includes a varistor RV**6**, and the third protection unit **1321** includes a varistor RV**5**. Optionally, the first protection unit **1311** further includes a fuse Fa, and the fuse Fa is connected to the varistor RV**41** in series. The third protection unit **1321** further includes a fuse Fn, and the fuse Fn is connected to the varistor RV**6** in series. The ninth protection unit **121** includes a varistor RV**1**, the tenth protection unit **122** includes

a varistor RV3, and the eleventh protection unit **123** includes a varistor RV2.

[0100] In another optional implementation, when a common-mode lightning current exists between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, a direct current end voltage between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1** is greater than a first threshold, so that the direct current side protection circuit **12** is in a conducted state, for the direct current end voltage to be clamped at a first voltage value. In this way, a part of the common-mode lightning current is discharged to the PE via the direct current side protection circuit **12**. In addition, when the common-mode lightning current exists between the PE, and the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, another part of the common-mode lightning current sequentially flows through the power conversion circuit **11**, the inductor, and the relay and reaches the live wire end out**11**, the live wire end out**12**, the live wire end out**13**, and the neutral wire end out**1N** of the power conversion apparatus **1** (or passes through the power conversion circuit **11** and reaches the neutral wire end out**1N**), so that the neutral wire protection branch **132** is in a disconnected state. In this case, a live wire end voltage between the live wire end out**11** of the power conversion apparatus **1** and the PE, a live wire end voltage between the live wire end out**12** of the power conversion apparatus **1** and the PE, and a live wire end voltage between the live wire end out**13** of the power conversion apparatus **1** and the PE are all greater than a second threshold, so that the live wire protection branch **131**, the live wire protection branch **133**, and the live wire protection branch **134** are all in a conducted state, for the live wire end voltages to be clamped at a second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the live wire protection branch **131**, the live wire protection branch **133**, and the live wire protection branch **134**. An absolute value of a difference between the first voltage value and the second voltage value is less than or equal to a safety error threshold.

[0101] For example, when a common-mode lightning current exists at the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, a direct current end voltage between the direct current end in**11** of the power conversion apparatus **1** and the PE and/or a direct current end voltage between the direct current end in**12** of the power conversion apparatus **1** and the PE are/is greater than the first threshold, and the ninth protection unit **121** and the tenth protection unit **122** are in a turn-on state, and/or the eleventh protection unit **123** and the tenth protection unit **122** are in a turn-on state. In this way, a part of the common-mode lightning current is discharged to the PE via the ninth protection unit **121** and the tenth protection unit **122**, and/or is discharged to the PE via the eleventh protection unit **123** and the tenth protection unit **122**. In addition, when the common-mode lightning current exists at the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, another part of the common-mode lightning current sequentially flows through the power conversion circuit **11**, the inductor, and the relay and reaches the live wire end out**11**, the live wire end out**12**, the live wire end out**13**, and the neutral wire end out**1N** of the power conversion apparatus **1** (or passes through the power conversion circuit **11** and reaches the neutral wire end out**1N**). Because a lightning current value (for example, thousands of A) is far greater than a normal operating current value (for example, dozens of A) of the power conversion apparatus **1**, when the common-mode lightning current flows through the neutral wire protection branch **132**, a change rate of a current flowing through the neutral wire protection branch **132** increases, so that an impedance value of the neutral wire protection branch **132** increases accordingly. In this case, the neutral wire protection branch **132** is in the disconnected state, and the three live wire end voltages are all greater than the second threshold. For example, when the common-mode lightning current flows through the third protection unit **1321**, a change rate of a current flowing through the third protection unit **1321** increases, so that an impedance value of the third protection unit **1321** increases accordingly. In this case, the third protection unit **1321** is in a turn-off state, so that the neutral wire protection branch **132** is in the disconnected state, and the three live wire end voltages are all greater than the second

threshold. When the three live wire end voltages are all greater than the second threshold, the first protection unit **1311**, the first protection unit **1331**, the first protection unit **1341**, and the second protection unit **1312** are all in a turn-on state, for the three live wire end voltages to be clamped at the second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the first protection unit **1311**, the first protection unit **1331**, the first protection unit **1341**, and the second protection unit **1312**, to quickly discharge the common-mode lightning current. Each of the first protection unit **1311**, the first protection unit **1331**, the first protection unit **1341**, and the second protection unit **1312** includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode. The third protection unit **1321** includes an inductor. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold, in a process of discharging the common-mode lightning current, a case in which the clamping voltage of the direct current side protection circuit **12** is greater than a clamping voltage of the first alternating current side protection circuit **13** and a most part of the common-mode lightning current flows through the power conversion circuit **11** can be avoided. This avoids damage to a power component in the power conversion circuit **11**, and protects the power conversion apparatus **1**, to improve stability of the power conversion apparatus **1**.

[0102] For example, each of the direct current side protection circuit **12**, the first protection unit **1311**, the first protection unit **1331**, the first protection unit **1341**, and the second protection unit **1312** includes one varistor, and the third protection unit **1321** includes an inductor. For details, refer to the power conversion apparatus **1** shown in FIG. 6c. As shown in FIG. 6c, the first protection unit **1311** includes a varistor RV41, the first protection unit **1331** includes a varistor RV42, the first protection unit **1341** includes a varistor RV43, the second protection unit **1312** includes a varistor RV6, and the third protection unit **1321** includes an inductor Ln. Optionally, the first protection unit **1311** further includes a fuse Fa, and the fuse Fa is connected to the varistor RV41 in series. The first protection unit **1331** further includes a fuse Fb, and the fuse Fb is connected to the varistor RV42 in series. The first protection unit **1341** further includes a fuse Fc, and the fuse Fc is connected to the varistor RV43 in series. The third protection unit **1321** further includes a fuse Fn, and the fuse Fn is connected to the inductor Ln in series. The ninth protection unit **121** includes a varistor RV1, the tenth protection unit **122** includes a varistor RV3, and the eleventh protection unit **123** includes a varistor RV2.

[0103] In still another optional implementation, when a common-mode lightning current exists between the PE, and the direct current end in11 and/or the direct current end in12 of the power conversion apparatus **1**, a direct current end voltage between the PE, and the direct current end in11 and/or the direct current end in12 of the power conversion apparatus **1** is greater than a first threshold, so that the direct current side protection circuit **12** is in a conducted state, for the direct current end voltage to be clamped at a first voltage value. In this way, a part of the common-mode lightning current is discharged to the PE via the direct current side protection circuit **12**. In addition, when the common-mode lightning current exists between the PE, and the direct current end in11 and/or the direct current end in12 of the power conversion apparatus **1**, another part of the common-mode lightning current sequentially flows through the power conversion circuit **11**, the inductor, and the relay and reaches the live wire end out11, the live wire end out12, the live wire end out13, and the neutral wire end out1N of the power conversion apparatus **1** (or passes through the power conversion circuit **11** and reaches the neutral wire end out1N). In this case, the live wire protection branch **131**, the live wire protection branch **133**, and the live wire protection branch **134** are all in a disconnected state, and a neutral wire end voltage between the neutral wire end out1N of the power conversion apparatus **1** and the PE is greater than a second threshold, so that the neutral wire protection branch **132** is in a conducted state, for the neutral wire end voltage to be clamped at a second voltage value. In this way, the another part of the common-mode lightning

current is discharged to the PE via the neutral wire protection branch **132**. An absolute value of a difference between the first voltage value and the second voltage value is less than or equal to a safety error threshold.

[0104] For example, when a common-mode lightning current exists at the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, a direct current end voltage between the direct current end in**11** of the power conversion apparatus **1** and the PE and/or a direct current end voltage between the direct current end in**12** of the power conversion apparatus **1** and the PE are/is greater than the first threshold, and the ninth protection unit **121** and the tenth protection unit **122** are in a turn-on state, and/or the eleventh protection unit **123** and the tenth protection unit **122** are in a turn-on state. In this way, a part of the common-mode lightning current is discharged to the PE via the ninth protection unit **121** and the tenth protection unit **122**, and/or is discharged to the PE via the eleventh protection unit **123** and the tenth protection unit **122**. In addition, when the common-mode lightning current exists at the direct current end in**11** and/or the direct current end in**12** of the power conversion apparatus **1**, another part of the common-mode lightning current sequentially flows through the power conversion circuit **11**, the inductor, and the relay and reaches the live wire end out**11**, the live wire end out**12**, the live wire end out**13**, and the neutral wire end out**1N** of the power conversion apparatus **1** (or passes through the power conversion circuit **11** and reaches the neutral wire end out**1N**). Because a lightning current value (for example, thousands of A) is far greater than a normal operating current value (for example, dozens of A) of the power conversion apparatus **1**, when the common-mode lightning current flows through the live wire protection branch **131**, the live wire protection branch **133**, and the live wire protection branch **134**, a change rate of a current flowing through the three live wire protection branches increases, so that impedance values of the three live wire protection branches increase accordingly. In this case, the live wire protection branch **131**, the live wire protection branch **133**, and the live wire protection branch **134** are in the disconnected state, and the neutral wire end voltage is greater than the second threshold. In this implementation, positions of the first protection unit and the third protection unit in FIG. **6a** are exchanged. In other words, the three live wire protection branches include third protection units, and the neutral wire protection branch **132** includes the first protection unit. For example, when the common-mode lightning current flow passes through the third protection units in the three live wire protection branches, a change rate of a current flowing through the third protection units in the three live wire protection branches increases, so that impedance values of the third protection units in the three live wire protection branches increase accordingly. In this case, the third protection units in the three live wire protection branches are all in a disconnected state, so that the live wire protection branch **131**, the live wire protection branch **133**, and the live wire protection branch **134** are in the disconnected state, and the neutral wire end voltage is greater than the second threshold. When the neutral wire end voltage is greater than the second threshold, both the first protection unit and the second protection unit **1312** are in a turn-on state, for the neutral wire end voltage to be clamped at the second voltage value. In this way, the another part of the common-mode lightning current is discharged to the PE via the first protection unit and the second protection unit **1312**, to quickly discharge the common-mode lightning current. The third protection units in the three live wire protection branches each include an inductor, and each protection unit in the first protection unit and the second protection unit **1312** includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold, in a process of discharging the common-mode lightning current, a case in which the clamping voltage of the direct current side protection circuit **12** is greater than a clamping voltage of the first alternating current side protection circuit **13** and a most part of the common-mode lightning current flows through the power conversion circuit **11** can be avoided. This avoids

damage to a power component in the power conversion circuit **11**, and protects the power conversion apparatus **1**, to improve stability of the power conversion apparatus **1**.

[0105] For example, each of the direct current side protection circuit **12**, the first protection unit, and the second protection unit **1312** includes one varistor, and the third protection units in the three live wire protection branches each include an inductor. For details, refer to the power conversion apparatus **1** shown in FIG. **6d**. As shown in FIG. **6d**, the third protection units in the three live wire protection branches respectively include an inductor La, an inductor Lb, and an inductor Lc, the second protection unit **1312** includes a varistor RV6, and the first protection unit includes a varistor RV5. Optionally, the third protection units in the three live wire protection branches further respectively include a fuse Fa, a fuse Fb, and a fuse Fc. The fuse Fa is connected to the inductor La in series, the fuse Fb is connected to the inductor Lb in series, and the fuse Fc is connected to the inductor Lc in series. The ninth protection unit **121** includes a varistor RV1, the tenth protection unit **122** includes a varistor RV3, and the eleventh protection unit **123** includes a varistor RV2.

[0106] In addition, to avoid a problem that the inductor and the capacitor in the power conversion apparatus **1** oscillate due to a differential-mode lightning current between the neutral wire end out1N and at least one of the three live wire ends of the power conversion apparatus **1**, and consequently the capacitor fails due to an excessively high voltage at the two ends of the capacitor, in the power conversion apparatus **1**, a protection unit may further be connected to two ends of the capacitor or the inductor in parallel, or a second alternating current protection circuit is disposed between each of the three live wire ends of the power conversion apparatus **1** and the neutral wire end out1N. An implementation of avoiding a capacitor failure is applicable to any power conversion apparatus **1** shown in FIG. **6a** to FIG. **6d**. Therefore, for case of description, the following uses the power conversion apparatus **1** shown in FIG. **6b** as an example for description with reference to the power conversion apparatus **1** shown in FIG. **6e** to FIG. **6h**.

[0107] In an optional implementation, the power conversion apparatus **1** further includes a fourth protection unit **141**, a fourth protection unit **142**, and a fourth protection unit **143**. The fourth protection unit **141** is connected to a capacitor C.sub.Inv-1 in parallel, and the fourth protection unit **142** is connected to a capacitor C.sub.Inv-2 in parallel, and the fourth protection unit **143** is connected to a capacitor C.sub.Inv-3 in parallel. The fourth protection unit **141**, the fourth protection unit **142**, and the fourth protection unit **143** each include one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0108] For example, when a differential-mode lightning current exists between each of the three live wire ends and the neutral wire end out1N of the power conversion apparatus **1**, voltages at two ends of the capacitor C.sub.Inv-1, two ends of the capacitor C.sub.Inv-2, and two ends of the capacitor C.sub.Inv-3 are all greater than a third threshold. In this case, the fourth protection unit **141**, the fourth protection unit **142**, and the fourth protection unit **143** are all in a turn-on state, so that the capacitor C.sub.Inv-1, the capacitor C.sub.Inv-2, and the capacitor C.sub.Inv-3 are all short-circuited, and the inductor and the capacitor in the differential mode lightning current loop **2** cannot oscillate. This can avoid a failure caused by an excessively high voltage between the two ends of the capacitor, to improve stability of the power conversion apparatus **1**.

[0109] For example, as shown in FIG. **6e**, the fourth protection unit **141** includes a varistor RV71, the fourth protection unit **142** includes a varistor RV72, and the fourth protection unit **143** includes a varistor RV73. Optionally, the fourth protection unit **141** further includes a fuse Finv-1, and the fuse Finv-1 is connected to the varistor RV71 in series. The fourth protection unit **142** further includes a fuse Finv-2, and the fuse Finv-2 is connected to the varistor RV72 in series. The fourth protection unit **143** further includes a fuse Finv-3, and the fuse Finv-3 is connected to the varistor RV73 in series.

[0110] In another optional implementation, the power conversion apparatus **1** further includes a fifth protection unit **151**, a fifth protection unit **152**, a fifth protection unit **153**, and a sixth

protection unit **16**. The fifth protection unit **151**, the fifth protection unit **152**, and the fifth protection unit **153** are all connected to different first inductors in parallel, and the sixth protection unit **16** is connected to the second inductor in parallel. For example, the first inductors are inductors L.sub.filter11-13, and the second inductor is an inductor L.sub.filter2. Each of the fifth protection unit **151**, the fifth protection unit **152**, the fifth protection unit **153**, and the sixth protection unit **16** includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0111] For example, when a differential-mode lightning current exists between each of the three live wire ends and the neutral wire end out1N of the power conversion apparatus **1**, both a voltage between two ends of each of the inductors L.sub.filter11-13 and a voltage between two ends of the inductor L.sub.filter2 are greater than a fourth threshold. In this case, the fifth protection unit **151**, the fifth protection unit **152**, the fifth protection unit **153**, and the sixth protection unit **16** are all in a turn-on state, so that the inductors L.sub.filter11-13 and the inductor L.sub.filter2 are all short-circuited, and the inductor and the capacitor in the differential-mode lightning current loop **2** cannot oscillate. This can avoid a failure caused by an excessively high voltage between the two ends of the capacitor, to improve stability of the power conversion apparatus **1**.

[0112] For example, as shown in FIG. 6f, the fifth protection unit **151** includes a gas discharge tube GDT **11**, the fifth protection unit **152** includes a gas discharge tube GDT **12**, the fifth protection unit **153** includes a gas discharge tube GDT **13**, and the sixth protection unit **16** includes a gas discharge tube GDT **2**.

[0113] In another optional implementation, the power conversion apparatus **1** further includes a second alternating current side protection circuit **171**, a second alternating current side protection circuit **172**, and a second alternating current side protection circuit **173**. The second alternating current side protection circuit **171** is connected between the live wire end out11 and the neutral wire end out1N of the power conversion apparatus **1**, and is configured to be in a conducted state when an alternating current end voltage between the live wire end out11 and the neutral wire end out1N of the power conversion apparatus **1** is greater than a fifth threshold, for the alternating current end voltage between the live wire end out11 and the neutral wire end out1N to be clamped at a third voltage value. The second alternating current side protection circuit **172** is connected between the live wire end out12 and the neutral wire end out1N of the power conversion apparatus **1**, and is configured to be in a conducted state when an alternating current end voltage between the live wire end out12 and the neutral wire end out1N of the power conversion apparatus **1** is greater than the fifth threshold, for the alternating current end voltage between the live wire end out12 and the neutral wire end out IN to be clamped at the third voltage value. The second alternating current side protection circuit **173** is connected between the live wire end out13 and the neutral wire end out1N of the power conversion apparatus **1**, and is configured to be in a conducted state when an alternating current end voltage between the live wire end out13 and the neutral wire end out1N of the power conversion apparatus **1** is greater than the fifth threshold, for the alternating current end voltage between the live wire end out13 and the neutral wire end out1N to be clamped at the third voltage value. The second alternating current side protection circuit **171**, the second alternating current side protection circuit **172**, and the second alternating current side protection circuit **173** each include a seventh protection unit and an eighth protection unit that are connected in series, and each of the seventh protection unit and the eighth protection unit includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0114] The first protection unit **1311** and the third protection unit **1321** are configured to be in the turn-on state when the alternating current end voltage between the live wire end out11 and the neutral wire end out1N is greater than a sixth threshold, for the alternating current end voltage between the live wire end out11 and the neutral wire end out1N to be clamped at a fourth voltage

value. The first protection unit **1331** and the third protection unit **1321** are configured to be in the turn-on state when the alternating current end voltage between the live wire end out**12** and the neutral wire end out**1N** is greater than the sixth threshold, for the alternating current end voltage between the live wire end out**12** and the neutral wire end out**1N** to be clamped at the fourth voltage value. The first protection unit **1341** and the third protection unit **1321** are configured to be in the turn-on state when the alternating current end voltage between the live wire end out**13** and the neutral wire end out**1N** is greater than the sixth threshold, for the alternating current end voltage between the live wire end out**13** and the neutral wire end out**1N** to be clamped at the fourth voltage value. The fourth voltage value is greater than the third voltage value, and the sixth threshold is greater than the fifth threshold.

[0115] For example, when the differential-mode lightning current exists between each of the three live wire ends and the neutral wire end out**1N** of the power conversion apparatus **1**, an alternating current end voltage between each of the three live wire ends and the neutral wire end out**1N** starts to increase. Because the fifth threshold is less than the sixth threshold, when the alternating current end voltage between each of the three live wire ends and the neutral wire end out**1N** is greater than the fifth threshold, the seventh protection units and the eighth protection units in the second alternating current side protection circuit **171**, the second alternating current side protection circuit **172**, and the second alternating current side protection circuit **173** are all in the conducted state. In addition, the alternating current end voltage between each of the three live wire ends and the neutral wire end out**1N** is clamped at the third voltage value, the first protection unit **1311** and the third protection unit **1321** are short-circuited by the second alternating current side protection circuit **171** and are in a turn-off state, the first protection unit **1331** and the third protection unit **1321** are short-circuited by the second alternating current side protection circuit **172** and are in a turn-off state, and the first protection unit **1341** and the third protection unit **1321** are short-circuited by the second alternating current side protection circuit **173** and are in a turn-off state. In this case, a part of the differential-mode lightning current is discharged via the second alternating current side protection circuit **171**, the second alternating current side protection circuit **172**, and the second alternating current side protection circuit **173**, and another part of the differential-mode lightning current is discharged via a loop in which the inductor and capacitor between each of the three live wire ends and the neutral wire end out**1N** are located. In addition, if there is no second alternating current side protection circuit **171** to the second alternating current side protection circuit **173** in the power conversion apparatus **1**, when the differential-mode lightning current exists between each of the three live wire ends and the neutral wire end out**1N** of the power conversion apparatus **1**, the alternating current end voltage between each of the three live wire ends and the neutral wire end out**1N** is greater than the sixth threshold, the first protection unit **1311**, the first protection unit **1331**, the first protection unit **1341**, and the third protection unit **1321** are all in the turn-on state, and the alternating current end voltage between each of the three live wire ends and the neutral wire end out**1N** is clamped at the fourth voltage value. In this case, a part of the differential-mode lightning current is discharged via the first protection unit **1311**, the first protection unit **1331**, the first protection unit **1341**, and the third protection unit **1321**, and the another part of the differential-mode lightning current is discharged via the loop in which the inductor and the capacitor between each of the three live wire ends and the neutral wire end out**1N** are located. Because the third voltage value is less than the fourth voltage value, the power conversion apparatus **1** may reduce the clamping voltage of the alternating current end by disposing the second alternating current side protection circuit **171** to the second alternating current side protection circuit **173**, to reduce a voltage between two ends of the capacitor. This can avoid a failure caused by an excessively high voltage between the two ends of the capacitor, to improve stability of the power conversion apparatus **1**.

[0116] For example, as shown in FIG. **6g**, the first protection unit **1311** includes a varistor RV**41**, the first protection unit **1331** includes a varistor RV**42**, the first protection unit **1341** includes a

varistor RV43, and the third protection unit 1321 includes a varistor RV5. The seventh protection units in the second alternating current side protection circuit 171 to the second alternating current side protection circuit 173 respectively include a varistor RV81 to a varistor RV83. The eighth protection units in the second alternating current side protection circuit 171 to the second alternating current side protection circuit 173 respectively include a gas discharge tube GDT 31 to a gas discharge tube GDT 33. A sum of actuating voltage thresholds of the varistor RV41 and the varistor RV5 is greater than a sum of actuating voltage thresholds of the varistor RV81 and the gas discharge tube GDT 31. A sum of clamping voltages of the varistor RV41 and the varistor RV5 is greater than a sum of clamping voltages of the varistor RV81 and the gas discharge tube GDT 31. A sum of actuating voltage thresholds of the varistor RV42 and the varistor RV5 is greater than a sum of actuating voltage thresholds of the varistor RV82 and the gas discharge tube GDT 32. A sum of clamping voltages of the varistor RV42 and the varistor RV5 is greater than a sum of clamping voltages of the varistor RV82 and the gas discharge tube GDT 32. A sum of actuating voltage thresholds of the varistor RV43 and the varistor RV5 is greater than a sum of actuating voltage thresholds of the varistor RV83 and the gas discharge tube GDT 33. A sum of clamping voltages of the varistor RV43 and the varistor RV5 is greater than a sum of clamping voltages of the varistor RV83 and the gas discharge tube GDT 33.

[0117] Optionally, to reduce circuit costs, the three live wire ends and the neutral wire end out1N of the power conversion apparatus 1 may share one second alternating current side protection circuit. For details, refer to the second alternating current side protection circuit 171 shown in FIG. 6h.

[0118] In still another optional implementation, the power conversion apparatus 1 further includes a second alternating current side protection circuit 171, a second alternating current side protection circuit 172, and a second alternating current side protection circuit 173. The second alternating current side protection circuit 171 is connected between the live wire end out11 and the neutral wire end out1N of the power conversion apparatus 1, and is configured to be in a conducted state when an alternating current end voltage between the live wire end out11 and the neutral wire end out1N of the power conversion apparatus 1 is greater than a fifth threshold. The second alternating current side protection circuit 172 is connected between the live wire end out12 and the neutral wire end out1N of the power conversion apparatus 1, and is configured to be in a conducted state when an alternating current end voltage between the live wire end out12 and the neutral wire end out1N of the power conversion apparatus 1 is greater than the fifth threshold. The second alternating current side protection circuit 173 is connected between the live wire end out13 and the neutral wire end out1N of the power conversion apparatus 1, and is configured to be in a conducted state when an alternating current end voltage between the live wire end out13 and the neutral wire end out1N of the power conversion apparatus 1 is greater than the fifth threshold. The second alternating current side protection circuit 171, the second alternating current side protection circuit 172, and the second alternating current side protection circuit 173 each include a seventh protection unit and an eighth protection unit that are connected in series. One of the seventh protection unit and the eighth protection unit includes a gas discharge tube, and the other protection unit includes one protection element, or at least two protection elements that are connected in series or in parallel. The protection element includes a gas discharge tube, a varistor, or a transient suppression diode.

[0119] For example, as shown in FIG. 6i, the first protection unit 1311 includes a varistor RV41, the first protection unit 1331 includes a varistor RV42, the first protection unit 1341 includes a varistor RV43, and the third protection unit 1321 includes an inductor Ln. The seventh protection units in the second alternating current side protection circuit 171 to the second alternating current side protection circuit 173 respectively include a varistor RV81 to a varistor RV83. The eighth protection units in the second alternating current side protection circuit 171 to the second alternating current side protection circuit 173 respectively include a gas discharge tube GDT 31 to a gas discharge tube GDT 33. For example, when a differential-mode lightning current exists

between each of the three live wire ends and the neutral wire end out1N of the power conversion apparatus 1, a change rate of a current flowing through the inductor L_n increases, and an impedance value of the inductor L_n increases accordingly. In this way, a branch in which the inductor L_n and each of the varistor RV41 to the varistor RV43 are located is in a disconnected state. When the differential-mode lightning current exists between each of the three live wire ends and the neutral wire end out1N of the power conversion apparatus 1, an alternating current end voltage between each of the three live wire ends and the neutral wire end out1N is greater than the fifth threshold, and the varistor RV81 to the varistor RV83 and the gas discharge tube GDT 31 to the gas discharge tube GDT 33 are all in a turn-on state. In this way, a part of the differential-mode lightning current is discharged via the second alternating current side protection circuit 171 to the second alternating current side protection circuit 173, and another part of the differential-mode lightning current is discharged via a loop in which the inductor and the capacitor between each of the three live wire ends and the neutral wire end out1N are located. Because a clamping voltage of the gas discharge tube is very low and can be ignored, the power conversion apparatus 1 can reduce the clamping voltage of the alternating current end by disposing the second alternating current side protection circuit 171 to the second alternating current side protection circuit 173 including gas discharge tubes, to reduce a voltage between two ends of the capacitor. This can avoid a failure caused by an excessively high voltage between the two ends of the capacitor, to improve stability of the power conversion apparatus 1.

[0120] Optionally, to reduce circuit costs, the three live wire ends and the neutral wire end out1N of the power conversion apparatus 1 may share one second alternating current side protection circuit. For details, refer to the second alternating current side protection circuit 171 shown in FIG. 6j.

[0121] It should be noted that a manner of disposing the protection units at two ends of the capacitor or the inductor shown in FIG. 6e and FIG. 6f to avoid an excessively high voltage between the two ends of the capacitor is also applicable to the power conversion apparatus 1 shown in FIG. 6c and FIG. 6d. Manners of disposing the second alternating current side protection circuit shown in FIG. 6i and FIG. 6j to reduce the voltage between the two ends of the capacitor is also applicable to the power conversion apparatus 1 shown in FIG. 6d.

[0122] In embodiments, when the common-mode lightning current exists at the direct current end of the power conversion apparatus 1, the power conversion apparatus 1 may discharge the common-mode lightning current via the direct current side protection circuit 12, and the live wire protection branch and/or the neutral wire protection branch that are in the conducted state, to quickly discharge the common-mode lightning current. Because the absolute value of the difference between the first voltage value and the second voltage value is less than or equal to the safety error threshold, in a process of discharging the common-mode lightning current, a case in which the clamping voltage of the direct current side protection circuit 12 is greater than a clamping voltage of the first alternating current side protection circuit 13 and a most part of the common-mode lightning current flows through the power conversion circuit 11 can be avoided. This avoids damage to a power component in the power conversion circuit 11, and protects the power conversion apparatus 1, to improve stability of the power conversion apparatus 1. In addition, when the differential-mode lightning current exists between each of the three live wire ends and the neutral wire end out1N of the power conversion apparatus 1, a protection circuit is connected between the two ends of the capacitor or the inductor in parallel, so that the inductor and the capacitor cannot oscillate, or the second alternating current side protection circuit with a low clamping voltage is disposed between each of the three live wire ends and the neutral wire end out1N of the power conversion apparatus 1. This can avoid a failure caused by an excessively high voltage between the two ends of the capacitor, to improve stability of the power conversion apparatus 1.

[0123] The foregoing descriptions are merely specific implementations of the embodiments, but are

not intended to limit their protection scope. Any variation or replacement readily figured out by a person skilled in the art shall fall within the scope of the embodiments.

Claims

1. A power conversion apparatus comprising: a direct current end; an alternating current end; a protective earthing (PE); a power conversion circuit, wherein the power conversion circuit is connected between the direct current end and the alternating current end and configured to implement electric energy conversion between the direct current end and the alternating current end; a direct current side protection circuit, wherein the direct current side protection circuit is connected between the direct current end and the PE and configured, when a direct current end voltage between the direct current end and the PE is greater than a first threshold, to be in a conducting state to clamp a direct current end voltage at a first voltage value; and a first alternating current side protection circuit comprising a plurality of protection branches connected between the alternating current end and the PE and configured to: when an alternating current end voltage between the alternating current end and the PE is greater than a second threshold, set at least one of the plurality of protection branches is in a conducting state to clamp the alternating current end voltage at a second voltage value, wherein an absolute value of a difference between the first voltage value and the second voltage value is less than or equal to a safety error threshold.
2. The power conversion apparatus according to claim 1, wherein the alternating current end further comprises: a live wire end and a neutral wire end, and the plurality of protection branches further comprise: a live wire protection branch, wherein the live wire protection branch is connected between the live wire end and the PE and configured, when a live wire end voltage between the live wire end and the PE is greater than the second threshold, to be in a conducting state, to clamp the live wire end voltage at the second voltage value; and a neutral wire protection branch connected between the neutral wire end and the PE and configured, when a neutral wire end voltage between the neutral wire end and the PE is greater than the second threshold, to be in a conducting state to clamp the neutral wire end voltage at the second voltage value.
3. The power conversion apparatus according to claim 2, wherein the live wire protection branch further comprises: a first protection unit and a second protection unit, and the neutral wire protection branch further comprises: the second protection unit and a third protection unit, wherein a first end of the first protection unit and a first end of the third protection unit are respectively connected to the live wire end and the neutral wire end, and a second end of the first protection unit is connected to a second end of the third protection unit and then connected to the PE via the second protection unit; the first protection unit is configured, when the live wire end voltage is greater than the second threshold, to be in a turn-on state; the second protection unit is configured, when either the live wire end voltage or the neutral wire end voltage is greater than the second threshold, to be in a turn-on state; and the third protection unit is configured, when the neutral wire end voltage is greater than the second threshold, to be in a turn-on state.
4. The power conversion apparatus according to claim 3, wherein each of the first protection unit, the second protection unit, and the third protection unit comprises one protection element, or at least two protection elements that are connected in series or in parallel, the protection element comprises a gas discharge tube, a varistor, or a transient suppression diode.
5. The power conversion apparatus according to claim 1, wherein the alternating current end further comprises: a first end and a second end, and the plurality of protection branches further comprise: a first protection branch, wherein the first protection branch is connected between the first end and the PE; and a second protection branch, wherein the second protection branch is connected between the second end and the PE; an impedance value of the second protection branch increases as a change rate of a current flowing through the second protection branch increases, and the second protection branch is configured, when a first end voltage between the first end and the PE to be

greater than the second threshold, to be in a disconnected state; and the first protection branch is configured, when the first end voltage is greater than the second threshold, to be in a conducting state to clamp the first end voltage at the second voltage value.

6. The power conversion apparatus according to claim 5, wherein the first protection branch further comprises: a first protection unit and a second protection unit, and the second protection branch further comprises: the second protection unit and a third protection unit, wherein a first end of the first protection unit and a first end of the third protection unit are respectively connected to the first end and the second end, and a second end of the first protection unit is connected to a second end of the third protection unit and then connected to the PE via the second protection unit; the first protection unit and the second protection unit are configured, when the first end voltage is greater than the second threshold, to be in a turn-on state; and an impedance value of the third protection unit increases as a change rate of a current flowing through the third protection unit increases, and the third protection unit is configured to be in a turn-off state.

7. The power conversion apparatus according to claim 6, wherein each of the first protection unit and the second protection unit comprises one protection element, or at least two protection elements that are connected in series or in parallel, the protection element comprises a gas discharge tube, a varistor, or a transient suppression diode, and the third protection unit comprises an inductor.

8. The power conversion apparatus according to claim 5, wherein the first end is a live wire end, the second end is a neutral wire end, the first protection branch is a live wire protection branch, the second protection branch is a neutral wire protection branch, and the first end voltage is a live wire end voltage; or the first end is a neutral wire end, the second end is a live wire end, the first protection branch is a neutral wire protection branch, the second protection branch is a live wire protection branch, and the first end voltage is a neutral wire end voltage.

9. The power conversion apparatus according to claim 6, wherein the first end is a live wire end, the second end is a neutral wire end, the first protection branch is a live wire protection branch, the second protection branch is a neutral wire protection branch, and the first end voltage is a live wire end voltage; or the first end is a neutral wire end, the second end is a live wire end, the first protection branch is a neutral wire protection branch, the second protection branch is a live wire protection branch, and the first end voltage is a neutral wire end voltage.

10. The power conversion apparatus according to claim 7, wherein the first end is a live wire end, the second end is a neutral wire end, the first protection branch is a live wire protection branch, the second protection branch is a neutral wire protection branch, and the first end voltage is a live wire end voltage; or the first end is a neutral wire end, the second end is a live wire end, the first protection branch is a neutral wire protection branch, the second protection branch is a live wire protection branch, and the first end voltage is a neutral wire end voltage.

11. The power conversion apparatus according to claim 1, further comprising: a capacitor is connected between a live wire end and a neutral wire end of the power conversion circuit; and a fourth protection unit connected to the capacitor in parallel and is configured, when a voltage between two ends of the capacitor is greater than a third threshold, to be in a turn-on state.

12. The power conversion apparatus according to claim 1, further comprising: a first inductor, a second inductor, a fifth protection unit, and a sixth protection unit, wherein the alternating current end comprises the live wire end and the neutral wire end, a live wire end of the power conversion circuit is connected to a live wire end of the power conversion apparatus via the first inductor, a neutral wire end of the power conversion circuit is connected to a neutral wire end of the power conversion apparatus via the second inductor; the fifth protection unit is connected to the first inductor in parallel, and is configured, when a voltage between two ends of the first inductor is greater than a fourth threshold, to be in a turn-on state; and the sixth protection unit is connected to the second inductor in parallel and is configured, when a voltage between two ends of the second inductor is greater than the fourth threshold, to be in a turn-on state.

13. The power conversion apparatus according to claim 9, wherein each of the fourth protection unit, the fifth protection unit, and the sixth protection unit comprises one protection element, or at least two protection elements that are connected in series or in parallel, the protection element comprises a gas discharge tube, a varistor, or a transient suppression diode.

14. The power conversion apparatus according to claim 10, wherein each of the fourth protection unit, the fifth protection unit, and the sixth protection unit comprises one protection element, or at least two protection elements that are connected in series or in parallel, the protection element comprises a gas discharge tube, a varistor, or a transient suppression diode.

15. The power conversion apparatus according to claim 3, further comprising: a second alternating current side protection circuit, wherein the second alternating current side protection circuit is connected between the live wire end and the neutral wire end and is configured, when an alternating current end voltage between the live wire end and the neutral wire end is greater than a fifth threshold, to be in a conducting state to clamp the alternating current end voltage at a third voltage value; and the first protection unit and the third protection unit are configured, when the alternating current end voltage is greater than a sixth threshold, to be in a conducting state to clamp the alternating current end voltage at a fourth voltage value, wherein the fourth voltage value is greater than the third voltage value and the sixth threshold is greater than the fifth threshold.

16. The power conversion apparatus according to claim 4, further comprising: a second alternating current side protection circuit connected between the live wire end and the neutral wire end and configured, when an alternating current end voltage between the live wire end and the neutral wire end is greater than a fifth threshold, to be in a conducting state to clamp the alternating current end voltage at a third voltage value; and the first protection unit and the third protection unit are configured, when the alternating current end voltage is greater than a sixth threshold, to be in a conducting state to clamp the alternating current end voltage at a fourth voltage value, wherein the fourth voltage value is greater than the third voltage value and the sixth threshold is greater than the fifth threshold.

17. The power conversion apparatus according to claim 15, wherein the second alternating current side protection circuit further comprises: a seventh protection unit and an eighth protection unit that are connected in series, wherein each of the seventh protection unit and the eighth protection unit comprises one protection element, or at least two protection elements that are connected in series or in parallel, and the protection element comprises a gas discharge tube, a varistor, or a transient suppression diode.

18. The power conversion apparatus according to claim 16, wherein the second alternating current side protection circuit further comprises: a seventh protection unit and an eighth protection unit that are connected in series, wherein each of the seventh protection unit and the eighth protection unit comprises one protection element, or at least two protection elements that are connected in series or in parallel, and the protection element comprises a gas discharge tube, a varistor, or a transient suppression diode.

19. The power conversion apparatus according to claim 8, further comprising: a second alternating current side protection circuit, wherein the second alternating current side protection circuit is connected between the live wire end and the neutral wire end and is configured, when an alternating current end voltage between the live wire end and the neutral wire end is greater than a fifth threshold, to be in a conducting state; and the second alternating current side protection circuit further comprises: a seventh protection unit and an eighth protection unit that are connected in series, a first unit of the seventh protection unit and the eighth protection unit comprises a gas discharge tube, a second comprises one protection element, or at least two protection elements that are connected in series or in parallel, and the protection element comprises a gas discharge tube, a varistor, or a transient suppression diode.

20. The power conversion apparatus according to claim 9, further comprising: a second alternating current side protection circuit connected between the live wire end and the neutral wire end and

configured, when an alternating current end voltage between the live wire end and the neutral wire end is greater than a fifth threshold, to be in a conducting state and the second alternating current side protection circuit further comprises a seventh protection unit and an eighth protection unit that are connected in series, a first unit of the seventh protection unit and the eighth protection unit comprises a gas discharge tube, a second unit comprises one protection element, or at least two protection elements that are connected in series or in parallel, and the protection element comprises a gas discharge tube, a varistor, or a transient suppression diode.
