

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403019
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Wu; Zhu et al.

Systems and methods for surgical registration

Abstract

A system for surgical registration. The system may include at least one computing device in communication with a surgical navigation system and the surgical device. The at least one computing device: a) receiving external bone registration data corresponding to locations on the exterior surface of the femur; b) calculating a first registration transform based on the external bone registration data; c) transforming a first bone removal plan of a surgical plan to the operative coordinate system based on the first registration transform; d) receiving internal bone canal registration data corresponding to at least one of location or orientation data from the inner canal of the femur; e) calculating a second registration transform based on both of the external and internal bone canal bone registration data; and f) transforming a second bone removal plan of the surgical plan to the operative coordinate system based on the second registration transform.

Inventors: Wu; Zhu (Weston, FL), Thompson; Matthew (Fort Lauderdale, FL), Mittelstadt; Brent (Fort Lauderdale, FL), Elbanna; Jamil (Fort Lauderdale, FL)

Applicant: MAKO Surgical Corp. (Weston, FL)

Family ID: 72336719

Assignee: MAKO Surgical Corp. (N/A, N/A)

Appl. No.: 18/380488

Filed: October 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240041613 A1	Feb. 08, 2024

Related U.S. Application Data

continuation parent-doc US 16810283 20200305 US 11839551 child-doc US 18380488

Publication Classification

Int. Cl.: **A61F2/46** (20060101); **A61B34/10** (20160101); **A61F2/32** (20060101); A61B34/20 (20160101); A61F2/30 (20060101)

U.S. Cl.:

CPC **A61F2/46** (20130101); **A61B34/10** (20160201); **A61F2/32** (20130101); **A61F2/4607** (20130101); A61B2034/102 (20160201); A61B2034/105 (20160201); A61B2034/2068 (20160201); A61F2002/30943 (20130101); A61F2002/4633 (20130101); A61F2002/4667 (20130101)

Field of Classification Search

CPC: A61F (2/46); A61F (2/32); A61F (2/4607); A61F (2002/30943); A61F (2002/4633); A61F (2002/4667); A61F (2002/4632); A61F (2/461); A61B (34/10); A61B (2034/102); A61B (2034/105); A61B (2034/2068); A61B (17/3403); A61B (2017/3411); A61B (34/74); A61B (34/76); A61B (90/50); A61B (2034/108); A61B (2034/2048); A61B (2034/2051); A61B (2034/2055); A61B (2034/2059); A61B (2034/252); A61B (2034/254); A61B (2090/3916); A61B (2090/3983); A61B (34/20); A61B (34/30); A61B (34/25); A61B (17/162); A61B (17/1659); A61B (17/1675); A61B (17/1735); A61B (17/1764); A61B (2034/107); A61B (2034/2065); A61B (17/175); G16H (20/40); G16H (50/50)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5806518	12/1997	Mittelstadt	N/A	N/A
11071594	12/2020	Kostrzewski et al.	N/A	N/A
2008/0010706	12/2007	Moses et al.	N/A	N/A
2013/0169423	12/2012	Iorgulescu et al.	N/A	N/A
2015/0328004	12/2014	Mofhouz	N/A	N/A
2016/0157751	12/2015	Mahfouz	N/A	N/A
2017/0258526	12/2016	Lang	N/A	N/A
2018/0021097	12/2017	Quaid et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2018-158104	12/2017	JP	N/A
WO 2018/013848	12/2017	WO	N/A
WO 2018/045086	12/2017	WO	N/A
WO 2018/231775	12/2017	WO	N/A

OTHER PUBLICATIONS

Australian Examination Report, AU 2020232318, dated May 10, 2022, 5 pgs. cited by applicant
EP Search Report, EP 20766825.2, dated Oct. 26, 2022, 10 pgs. cited by applicant
International Search Report and Written Opinion, PCT/US2020/021173, dated Jul. 8, 2020, 19 pgs. cited by applicant

Primary Examiner: Lamprecht; Joel

Attorney, Agent or Firm: Polsinelli PC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/810,283, filed Mar. 5, 2020, which application claims the benefit of U.S. Provisional Application No. 62/814,057, filed Mar. 5, 2019. Each application referenced above is hereby incorporated by reference in its entirety into the present application.

TECHNICAL FIELD

(1) The present disclosure relates generally to surgical systems for orthopedic joint replacement surgery and, more particularly, to methods of surgical registration.

BACKGROUND

(2) Robotic systems are often used in applications that require a high degree of accuracy and/or precision, such as surgical procedures or other complex tasks. Such systems may include various types of robots, such as autonomous, teleoperated, and interactive.

(3) Interactive robotic systems may be preferred for some types of surgery, such as joint replacement surgery, because they enable a surgeon to maintain direct, hands-on control of the surgical procedure while still achieving a high degree of accuracy and/or precision. For example, in knee replacement surgery, a surgeon can use an interactive, haptically guided robotic arm in a passive manner to sculpt bone to receive a joint implant, such as a knee implant. To sculpt bone, the surgeon manually grasps and manipulates the robotic arm to move a cutting tool (e.g., a rotating burr) that is coupled to the robotic arm to cut a pocket in the bone. As long as the surgeon maintains a tip of the burr within a predefined virtual cutting boundary or haptic boundary defined, for example, by a haptic object, the robotic arm moves freely with low friction and low inertia such that the surgeon perceives the robotic arm as essentially weightless and can move the robotic arm as desired. If the surgeon attempts to move the tip of the burr to cut outside the virtual cutting boundary, however, the robotic arm provides haptic feedback (e.g., forced resistance) that prevents or inhibits the surgeon from moving the tip of the burr beyond the virtual cutting boundary. In this manner, the robotic arm enables highly accurate, repeatable bone cuts. When the surgeon manually implants a knee implant (e.g., a patellofemoral component) on a corresponding bone cut the implant will generally be accurately aligned due to the configuration of and interface between the cut bone and the knee implant.

(4) The above-described interactive robotic system may also be used in hip replacement surgery, which may require the use of multiple surgical tools having different functions (e.g., reaming, impacting), different configurations (e.g., straight, offset), and different weights. A system designed to accommodate a variety of tools is described in U.S. patent application Ser. No. 12/894,071, filed Sep. 29, 2010, entitled “SURGICAL SYSTEM FOR POSITIONING PROSTHETIC COMPONENT AND/OR FOR CONSTRAINING MOVEMENT OF SURGICAL TOOL”, which is hereby incorporated by reference in its entirety.

(5) During a hip replacement surgery, as well as other robotically assisted or fully autonomous surgical procedures, the patient bones including the pelvis and the femur are intra-operatively

registered with corresponding virtual or computer bone models to correlate the pose (i.e., position and rotational orientation) of the actual, physical bone with the virtual bone models. The patient bone (physical space) is also tracked relative to the surgical robot, haptic device, or surgical tool, which may include at least one degree of freedom (e.g., rotating burr). In this way, the virtual cutting or haptic boundaries controlled and defined on the virtual bone model via a computer can be applied to the patient bone (physical space) such that the haptic device is constrained in its physical movement (e.g., burring) when working on the patient bone (physical space).

(6) Intra-operative registration of the pelvis and femur can be challenging. And while certain systems and methods exist in the art for registration of a patient pelvis and femur, there is need in the art for registration methods that increase accuracy while decreasing registration time.

SUMMARY

(7) Aspects of the present disclosure may include a system for registering a surgical device and a femur of a patient. The femur may include an exterior surface and an inner canal. The femur of the patient and the surgical device may be in an operative coordinate system. The system may include at least one computing device in communication with a surgical navigation system and the surgical device. The surgical navigation system may track the surgical device. The at least one computing device storing a surgical plan in a virtual coordinate space. The at least one computing device is configured for the following steps. The at least one computing device may receive external bone registration data corresponding to locations on the exterior surface of the femur. The at least one computing device may calculate a first registration transform based on the external bone registration data. The at least one computing device may transform a first bone removal plan of the surgical plan to the operative coordinate system based on the first registration transform. The at least one computing device may receive internal bone canal registration data corresponding to at least one of location or orientation data from the inner canal of the femur. The at least one computing device may calculate a second registration transform based on both of the external bone registration data and the internal bone canal registration data. The at least one computing device may transform a second bone removal plan of the surgical plan to the operative coordinate system based on the second registration transform.

(8) In certain instances, the first bone removal plan may be defined in the virtual coordinate space and may include first coordinate locations for a first portion of bone removal from a virtual inner canal that may be representative of the inner canal of the femur of the patient.

(9) In certain instances, the second bone removal plan may be defined in the virtual coordinate space and may include second coordinate locations for a second portion of bone removal from the virtual inner canal that may be representative of the inner canal of the femur of the patient.

(10) In certain instances, the first portion of bone removal from the first bone removal plan includes less bone removal from the virtual canal than the first and second bone removal plans combined. In certain instances, the first bone removal plan includes only a partial femur canal preparation plan that may be less than a full canal preparation needed for implantation of a stem of a femoral implant. In certain instances, the first portion of bone removal from the first bone removal plan and the second portion of bone removal from the second bone removal plan collectively amount to a full canal preparation plan.

(11) In certain instances, the second bone removal plan includes a robotic bone removal portion and a manual bone removal portion.

(12) In certain instances, the manual bone removal portion may be planned for a broach.

(13) In certain instances, the second coordinate locations for the second portion of bone removal includes the first coordinate locations for the first portion of bone removal.

(14) In certain instances, the second coordinate locations for the second portion of bone removal from the second bone removal plan encompasses the first coordinate locations for the first portion of bone removal from the first bone removal plan.

(15) In certain instances, the surgical navigation system may include a tracking device and at least

one tool configured to be tracked in its movement by the tracking device.

(16) In certain instances, the surgical plan further may include a position and orientation for a femoral neck etch, the at least one computing device configured for receiving femoral neck etch data corresponding to physical marks on the femoral neck, the marks being less than a complete resection of the femoral neck.

(17) In certain instances, the at least one computing device is further configured for comparing the first registration transform to the second registration transform, and proceeding with one of the first registration transform or the second registration transform based on the comparison.

(18) Aspects of the present disclosure may include a computer implemented method of registration of a surgical device and a femur of a patient. The femur includes an exterior surface and an inner canal. The surgical device and the femur of the patient are in an operative coordinate system. The computer implemented method may include the following steps. The method may include the step of receiving external bone registration data corresponding to locations on the exterior surface of the femur. The method may include the step of calculating a first registration transform based on the external bone registration data. The method may include the step of transforming a first bone removal plan of a surgical plan to the operative coordinate system based on the first registration transform, the first bone removal plan including a partial femoral canal preparation plan that may be less than a full canal preparation plan needed for receiving a stem of a femoral implant. The method may include the step of receiving internal bone canal registration data corresponding to at least one of location or orientation data from the inner canal of the femur. The method may include the step of calculating a second registration transform based on both of the external bone registration data and the internal bone canal registration data. And the method may include the step of transforming a second bone removal plan of the surgical plan to the operative coordinate system based on the second registration transform.

(19) In certain instances, the method may further include: determining a planned implant placement of an implant model relative to a femoral bone model, the femoral bone model being representative of the femur of the patient.

(20) In certain instances, the method may further include: determining a surgical plan in order to achieve the planned implant placement, the surgical plan may include the first bone removal plan and the second bone removal plan.

(21) In certain instances, the first bone removal plan may be planned in a virtual coordinate system relative to a femoral bone model representative of the femur, the virtual coordinate system being different than the operative coordinate system. And, transforming the first bone removal plan to the operative coordinate system based on the first registration transform may include mapping the first bone removal plan to the femur in the operative coordinate system in the same position and orientation that the first bone removal plan may be relative to the femoral bone model in the virtual coordinate system.

(22) In certain instances, the second bone removal plan may be planned in a virtual coordinate system relative a femoral bone model representative of the femur, the virtual coordinate system being different than the operative coordinate system. And, transforming the second bone removal plan to the operative coordinate system based on the second registration transform may include mapping the second bone removal plan to the femur in the operative coordinate system in the same position and orientation that the second bone removal plan may be relative to the femoral bone model in the virtual coordinate system.

(23) In certain instances, the second bone removal plan includes removal of bone from the inner canal of the femur, and the second bone removal plan encompasses the bone removal from the first bone removal plan. In certain instances, second bone removal plan includes removal of additional bone beyond the bone in the first bone removal plan.

(24) Aspects of the present disclosure may include a system for registering patient data of a first bone in a first coordinate system with a surgical plan associated with the first bone in a second

coordinate system that may be different than the first coordinate system. The first bone may include a head portion and a shaft portion extending from the head portion. The system may include at least one computing device in communication with a surgical navigation system that may include a tracking device and at least one tool configured to be tracked in its movement by the tracking device. The at least one computing device storing the surgical plan in the second coordinate system. The surgical plan may include a virtual bone model representative of the first bone, a first bone removal plan associated with the virtual bone model, and a second bone removal plan associated with the virtual bone model. The at least one computing device configured for receiving a first point-cloud of data associated with the first bone, the first point-cloud of data may include first data associated with the head portion of the first bone. The at least one computing device configured for calculating a first registration transform from the first point-cloud of data. The at least one computing device configured for, using the first registration transform, transforming the first bone removal plan of the surgical plan to the first coordinate system in a position and orientation relative to the first bone as the first bone removal plan existed in the second coordinate system relative to the virtual bone model. The at least one computing device configured for receiving a second point-cloud of data associated with the first bone, the second point-cloud of data may include second data associated with an internal portion of the shaft portion of the first bone. The at least one computing device configured for calculating a second registration transform from both of the first and second point-clouds of data. And, the at least one computing device configured for, using the second registration transform, transforming the second bone removal plan of the surgical plan to the first coordinate system in a position and orientation relative to the first bone as the second bone removal plan existed in the second coordinate system relative to the virtual bone model.

(25) In certain instances, the first and second point-cloud of data may be gathered intra-operatively via a surgical device that may be tracked in its movement by the tracking device of the surgical navigation system.

(26) In certain instances, the first bone removal plan includes a first plan for partial removal of bone from a virtual canal of the virtual bone model.

(27) In certain instances, the second bone removal plan includes a second plan for full removal of bone from the virtual canal of the virtual bone model, the first and second bone removal plans being for preparation of implantation of a stem of a femoral implant.

(28) Aspects of the present disclosure may include one or more tangible computer-readable storage media storing computer-executable instructions for performing a computer process on a computing system. The computer process may include the following steps. The computer process may include the step of receiving a plurality of image scans of a patient pelvis. The computer process may include the step of generating a three-dimensional bone model of the patient pelvis from the plurality of image scans. The computer process may include the step of identifying a scan axis associated with the plurality of image scans, the scan axis defined along a long axis of a scanning table of an imaging machine. The computer process may include the step of identifying a bone axis associated with the three-dimensional bone model of the patient pelvis. The computer process may include the step of determining an angular offset between the scan axis and the bone axis. The computer process may include the step of determining a virtual center of rotation of at least one virtual bone relative to a three-dimensional bone model of the patient pelvis. The computer process may include the step of using the angular offset and the virtual center of rotation as constraints in a registration transform to be employed in a surgical registration procedure.

(29) Aspects of the present disclosure may include one or more tangible computer-readable storage media storing computer-executable instructions for performing a computer process on a computing system. The computer process may include the following steps. The computer process may include the step of receiving a point-cloud of data from at least one tool of a surgical navigation system, the at least one tool tracked in its movement by a tracking device of the surgical navigation system. The at least one tool may be configured to store data points in the point-cloud data. The point-cloud

of data may include first data and second data in a common coordinate system. The first data may include a pair of points located on or proximate a surgical table. The second data may include a plurality of points corresponding to a concave portion of a joint surface of between a first bone may include the concave portion and a second bone may include a convex portion. The computer process may include the step of determining a vector between the pair of points of the first data. The computer process may include the step of determining a center of rotation from the second data, the center of rotation being of the second bone relative to the first bone. The computer process may include the step of employing a registration transform that registers the point-cloud of data with a three-dimensional computer model of at least the first bone, the vector and the center of rotation being constraints in the registration transform.

(30) Aspects of the present disclosure may include a computer-implemented method for surgical registration including the following steps. The method may include the step of receiving a point-cloud of data from at least one tool of a surgical navigation system, the at least one tool tracked in its movement by a tracking device of a surgical navigation system. The at least one tool configured to store data points in the point-cloud data based on its position relative to the tracking device. The point-cloud of data may include first data and second data in a first coordinate system. The first data may include first and second coordinate points located on or proximate a surgical table. The second data may include one or more coordinate points corresponding to a center-of-rotation of a joint formed between a pair of bones. The method may include the step of employing a registration transform that registers the point-cloud of data with a plurality of coordinate points associated with a three-dimensional computer model of or approximating the pair of bones and the joint. The plurality of coordinate points may include one or more coordinate points corresponding to a center-of-rotation of the joint. The plurality of coordinate points in a second coordinate system.

(31) In certain instances, the first and second coordinate points located on or proximate the surgical table are aligned parallel with a long axis of the surgical table.

(32) In certain instances, the first data may include a third coordinate point located on or proximate the surgical table, the third coordinate point may be located on an opposite side of the surgical table from the first and second coordinate points.

(33) In certain instances, the three-dimensional computer model of or approximating the pair of bones and the joint may be generated from pre-operative image scans of the pair of bones and the joint.

(34) In certain instances, the three-dimensional computer model of or approximating the pair of bones and the joint may include a generic bone model approximating the pair of bones and the joint.

(35) In certain instances, the three-dimensional computer model of or approximating the pair of bones and the joint may include a statistical bone model approximating the pair of bones and the joint.

(36) Aspects of the present disclosure may include a surgical registration system including the following. A registration needle that may include a distal tip and a proximal light emitting diode (LED) optical marker, the proximal LED optical marker configured to be tracked by a tracking device of a surgical navigation system. A needle template that may include a template block having a plurality of through-holes extending therethrough, the plurality of through-holes are spaced-apart from each other on the template block, and each of the plurality of through-holes are configured to guide the registration needle along a trajectory. And an optical localization tracker coupled to the needle template, the optical localization tracker configured to be tracked by the tracking device of the surgical navigation system.

(37) Aspects of the present disclosure may include a system for registering patient data gathered intra-operatively of a vertebra with a computer model of the vertebra in a coordinate system. The vertebra may include a cortical bone shell having an outer surface and an inner surface, and cancellous bone interior of the cortical bone shell. The vertebra may define a spinal cord canal

bounded by the cortical bone shell. The system may include a surgical navigation system including a tracking device and at least one tool configured to be tracked in its movement by the tracking device, the at least one tool may include an end effector having a cutting element at a distal end thereof, and a load cell configured to sense a load on the cutting element. The system may also include at least one computing device in communication with the surgical navigation system, the at least one computing device storing the computer model of the vertebra in the coordinate system. The at least one computing device configured for receiving load data associated with a load experienced by the cutting element at the distal end of the end effector when the cutting element contacts the cortical bone shell and the cancellous bone. The at least one computing device configured for identifying, based on the load data, when the cutting element contacts the inner surface of the cortical bone shell. The at least one computing device configured for receiving a point-cloud of data associated with the vertebra, the point-cloud of data may include coordinate locations on the inner surface of the cortical bone shell, the point-cloud of data collected via the cutting element at the distal end of the end effector. The at least one computing device configured for at least one of running or updating a transform to register the point-cloud of data associated with the vertebra to the computer model of the vertebra in a common coordinate system.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a perspective view of a femur and a pelvis.
- (2) FIG. 1B is a perspective view of a hip joint formed by the femur and pelvis of FIG. 1A.
- (3) FIG. 2A is an exploded perspective view of a femoral component and an acetabular component for a total hip replacement procedure.
- (4) FIG. 2B is a perspective view illustrating placement of the femoral component and acetabular component of FIG. 2A in relation to the femur and pelvis of FIG. 1A, respectively.
- (5) FIG. 3A is a perspective view of an embodiment of a surgical system.
- (6) FIG. 3B is a perspective view of an embodiment of a robotic arm of the surgical system of FIG. 3A.
- (7) FIG. 4 illustrates an embodiment of a computer display for use during a surgical procedure.
- (8) FIG. 5 illustrates an embodiment of steps of a hip replacement procedure.
- (9) FIGS. 6 and 7 illustrate an embodiment of a pelvic registration method shown on a display screen.
- (10) FIG. 8 illustrates steps of a femoral registration method.
- (11) FIG. 9A depicts a pre-operative image of a proximal femur undergoing segmentation.
- (12) FIG. 9B depicts a proximal femur with the canal partially resected.
- (13) FIG. 9C depicts a proximal femur being probed internally along the femoral canal.
- (14) FIG. 9D depicts a proximal femur fully resected along the femoral canal.
- (15) FIG. 10 illustrates steps of a femoral registration method.
- (16) FIG. 11A depicts a pre-operative image of a proximal femur undergoing segmentation.
- (17) FIG. 11B depicts a proximal femur with the femoral canal partially resected.
- (18) FIG. 11C depicts a proximal femur with the femoral canal partially resected, and with the internal surfaces of the femur being probed with a burr of an end effector.
- (19) FIG. 11D depicts a proximal femur with the femoral canal fully resected.
- (20) FIG. 12 illustrates steps of a femoral registration method.
- (21) FIG. 13A depicts a pre-operative image of a proximal femur undergoing segmentation.
- (22) FIG. 13B depicts a proximal femur with the femoral canal partially resected, and with a registration tool extending into the femoral canal.
- (23) FIG. 13C depicts a proximal femur with the femoral canal partially resected, and with the

registration tool extended into the femoral canal, and with the tool expanded to the internal bone surfaces.

(24) FIG. 13D depicts a proximal femur with the femoral canal fully resected.

(25) FIG. 13E depicts an exemplary flowchart for planning and performing a surgical procedure on a proximal femur.

(26) FIG. 13F depicts an exemplary flowchart for planning and performing a surgical procedure on a proximal femur.

(27) FIG. 14A illustrates pre-operative steps of a registration method utilizing information from a patient's orientation on an imaging table.

(28) FIG. 14B illustrates intra-operative steps of a registration method utilizing information from a patient's orientation on an imaging table.

(29) FIG. 14C illustrates pre-operative and intra-operative steps of a registration method.

(30) FIG. 14D illustrates pre-operative and intra-operative steps of a registration method.

(31) FIG. 15A depicts an overhead view of a patient on an imaging table.

(32) FIG. 15B depicts an overhead view of a patient on an operating room table.

(33) FIG. 15C depicts an angular offset between a vector determined in the operating room and a pelvic axis determined from the patient's orientation on the imaging table.

(34) FIG. 15D depicts an overhead view of a patient on an imaging table.

(35) FIG. 15E depicts an overhead view of a patient on an operating room table.

(36) FIG. 15F depicts an overhead view of a patient on an imaging table.

(37) FIG. 15G depicts an overhead view of a patient on an operating room table.

(38) FIG. 16A depicts needles of various lengths and diameters, and a needle template.

(39) FIG. 16B depicts an anterior view of a femur with a first embodiment of a needle-based registration system.

(40) FIG. 16C depicts an anterior view of a femur with a second embodiment of a needle-based registration system.

(41) FIGS. 17A and 17B depict a needle-based registration system used on a mid-distal portion of a femur.

(42) FIG. 17C depicts the needle-based registration system used on a mid-distal portion of a tibia.

(43) FIG. 18 depicts a side view of an ilium with the needle-based registration system utilized on the iliac crest.

(44) FIGS. 19A and 19B depict, respectively, a side view and a cross-sectional axial view of the needle-based registration system utilized on the spine.

(45) FIG. 20A (prior art) is an axial cross-section image of a vertebra with a bone anchor positioned within the pedicle.

(46) FIG. 20B is an axial cross-section image of a vertebra with a burr positioned within a neck region of the pedicle.

(47) FIG. 20C is an axial cross-section image of a vertebra with a burr positioned within a neck region of the pedicle.

(48) FIG. 20D is an axial cross-section image of a vertebra with a burr positioned through a neck region of the pedicle to a far inner cortical wall.

(49) FIG. 21 is an example computing system having one or more computing units that may implement various systems and methods discussed herein is provided.

DETAILED DESCRIPTION

(50) The present application incorporates by reference the following applications in their entireties: International Application PCT/US2017/049466, filed Aug. 30, 2017, entitled "SYSTEMS AND METHODS FOR INTRA-OPERATIVE PELVIC REGISTRATION"; U.S. patent application Ser. No. 12/894,071, filed Sep. 29, 2010, entitled "SURGICAL SYSTEM FOR POSITIONING PROSTHETIC COMPONENT AND/OR FOR CONSTRAINING MOVEMENT OF SURGICAL TOOL"; U.S. patent application Ser. No. 13/234,190, filed Sep. 16, 2011, entitled "SYSTEMS

AND METHOD FOR MEASURING PARAMETERS IN JOINT REPLACEMENT SURGERY”; U.S. patent application Ser. No. 11/357,197, filed Feb. 21, 2006, entitled “HAPTIC GUIDANCE SYSTEM AND METHOD”; U.S. patent application Ser. No. 12/654,519, filed Dec. 22, 2009, entitled “TRANSMISSION WITH FIRST AND SECOND TRANSMISSION ELEMENTS”; U.S. patent application Ser. No. 12/644,964, filed Dec. 22, 2009, entitled “DEVICE THAT CAN BE ASSEMBLED BY COUPLING”; and U.S. patent application Ser. No. 11/750,807, filed May 18, 2007, entitled “SYSTEM AND METHOD FOR VERIFYING CALIBRATION OF A SURGICAL DEVICE”.

I. Overview

(51) The hip joint is the joint between the femur and the pelvis and primarily functions to support the weight of the body in static (e.g., standing) and dynamic (e.g., walking) postures. FIG. 1A illustrates the bones of an operative side of a hip joint **10**, which include a left pelvis or ilium **12** and a proximal end of a left femur **14**. While a right pelvis and proximal end of a right femur is not shown in FIG. 1A, such a discussion herein is applicable to both the right and the left femur and pelvis without limitation. Continuing on, the proximal end of the femur **14** includes a femoral head **16** disposed on a femoral neck **18**. The femoral neck **18** connects the femoral head **16** to a femoral shaft **20**. As shown in FIG. 1B, the femoral head **16** fits into a concave socket in the pelvis **12** called the acetabulum **22**, thereby forming the hip joint **10**. The acetabulum **22** and femoral head **16** are both covered by articular cartilage that absorbs shock and promotes articulation of the joint **10**.

(52) Over time, the hip joint **10** may degenerate (e.g., due to osteoarthritis) resulting in pain and diminished functionality. As a result, a hip replacement procedure, such as total hip arthroplasty or hip resurfacing, may be necessary. During hip replacement, a surgeon replaces portions of a patient's hip joint **10** with artificial components. In total hip arthroplasty, the surgeon removes the femoral head **16** and neck **18** and replaces the native bone with a prosthetic femoral component **26** comprising a head **26a**, a neck **26b**, and a stem **26c** (shown in FIG. 2A). As shown in FIG. 2B, the stem **26c** of the femoral component **26** is anchored in a cavity the surgeon creates in the intramedullary canal of the femur **14**. Alternatively, if disease is confined to the surface of the femoral head **16**, the surgeon may opt for a less invasive approach in which the femoral head is resurfaced (e.g., using a cylindrical reamer) and then mated with a prosthetic femoral head cup (not shown). Similarly, if the natural acetabulum **22** of the pelvis **12** is worn or diseased, the surgeon resurfaces the acetabulum **22** using a reamer and replaces the natural surface with a prosthetic acetabular component **28** comprising a hemispherical shaped cup **28a** (shown in FIG. 2A) that may include a liner **28b**. To install the acetabular component **28**, the surgeon connects the cup **28a** to a distal end of an impactor tool and implants the cup **28a** into the reamed acetabulum **22** by repeatedly striking a proximal end of the impactor tool with a mallet. If the acetabular component **28** includes a liner **28b**, the surgeon snaps the liner **28b** into the cup **28a** after implanting the cup **28a**. Depending on the position in which the surgeon places the patient for surgery, the surgeon may use a straight or offset reamer to ream the acetabulum **22** and a straight or offset impactor to implant the acetabular cup **28a**. For example, a surgeon that uses a postero-lateral approach may prefer straight reaming and impaction whereas a surgeon that uses an antero-lateral approach may prefer offset reaming and impaction.

II. Exemplary Robotic System

(53) A surgical system described herein may be utilized to perform hip replacement, as well as other surgical procedures. As shown in FIG. 3A, an embodiment of a surgical system **5** for surgical applications according to the present disclosure includes a computer assisted navigation system **7**, a tracking device **8**, a computer **15**, a display device **9** (or multiple display devices **9**), and a robotic arm **30**.

(54) The robotic arm **30** can be used in an interactive manner by a surgeon to perform a surgical procedure on a patient, such as a hip replacement procedure. As shown in FIG. 3B, the robotic arm **30** includes a base **32**, an articulated arm **34**, a force system (not shown), and a controller (not

shown). A surgical tool **58** (e.g., a rotary burring device as seen in FIG. 3A, an end effector **40** having an operating member as seen in FIG. 3B) is coupled to an end of the articulated arm **34**, and the surgeon manipulates the surgical tool **58** by grasping and manually moving the articulated arm **34** and/or the surgical tool.

(55) The force system and controller are configured to provide control or guidance to the surgeon during manipulation of the surgical tool. The force system is configured to provide at least some force to the surgical tool via the articulated arm **34**, and the controller is programmed to generate control signals for controlling the force system. In one embodiment, the force system includes actuators and a backdriveable transmission that provide haptic (or force) feedback to constrain or inhibit the surgeon from manually moving the surgical tool beyond predefined virtual boundaries defined by haptic objects as described, for example, in U.S. patent application Ser. No. 11/357,197 (Pub. No. US 2006/0142657), filed Feb. 21, 2006, and/or U.S. patent application Ser. No. 12/654,519, filed Dec. 22, 2009, each of which is hereby incorporated by reference herein in its entirety. In a certain embodiment the surgical system is the RIO™. Robotic Arm Interactive Orthopedic System manufactured by MAKO Surgical Corp. of Weston, Fla. The force system and controller may be housed within the robotic arm **30**, or may be part of an autonomous or handheld unit. Generally, the method of surgical registration may be done with a robotic arm of a surgical robot operating autonomously, or being guided by a surgeon under haptic controls. Similarly, the method of surgical registration may be done via a handheld unit operating within a permissible zone of operation.

(56) The tracking device **8** is configured to track the relative locations of the surgical tool **58** (coupled to the robotic arm **30**) and the patient's anatomy. The surgical tool **58** can be tracked directly by the tracking device **8**. Alternatively, the pose of the surgical tool can be determined by tracking the location of the base **32** of the robotic arm **30** and calculating the pose of the surgical tool **58** based on joint encoder data from joints of the robotic arm **30** and a known geometric relationship between the surgical tool and the robotic arm **30**. In particular, the tracking device **8** (e.g., an optical, mechanical, electromagnetic, or other known tracking system) tracks (or enables determination of) the pose (i.e., position and orientation) of the surgical tool and the patient's anatomy so the navigation system **7** knows the relative relationship between the tool and the anatomy.

(57) In operation, a user (e.g., a surgeon) manually moves the robotic arm **30** to manipulate the surgical tool **58** (e.g., the rotary burring device, the end effector **40** having an operating member) to perform a surgical task on the patient, such as bone cutting or implant installation. As the surgeon manipulates the tool **58**, the tracking device **8** tracks the location of the surgical tool and the robotic arm **30** provides haptic (or force) feedback to limit the surgeon's ability to move the tool **58** beyond a predefined virtual boundary that is registered (or mapped) to the patient's anatomy, which results in highly accurate and repeatable bone cuts and/or implant placement. The robotic arm **30** operates in a passive manner and provides haptic feedback when the surgeon attempts to move the surgical tool **58** beyond the virtual boundary. The haptic feedback is generated by one or more actuators (e.g., motors) in the robotic arm **30** and transmitted to the surgeon via a flexible transmission, such as a cable drive transmission. When the robotic arm **30** is not providing haptic feedback, the robotic arm **30** is freely moveable by the surgeon and preferably includes a virtual brake that can be activated as desired by the surgeon. During the surgical procedure, the navigation system **7** displays images related to the surgical procedure on one or both of the display devices **9**.

(58) To aid in tracking the various pieces of equipment within the system, the robotic arm **30** may include a device marker **48** to track a global or gross position of the robotic arm **30**, a tool end marker **54** to track the distal end of the articulating arm **34**, and a free-hand navigation probe **56** for use in the registration process. Each of these markers **48**, **54**, **56** (among others such as navigation markers positioned in the patient's bone) is trackable by the tracking device **8** with optical cameras, for example.

(59) The computer **15** may include a display and an input device (e.g., keyboard, mouse) and is configured to communicate with the navigation system **7**, the tracking device **8**, the various display devices **9** in the system, and the robotic arm **30**. Furthermore, the computer **15** may receive information related to a particular surgical procedure and perform various functions related to performance of the surgical procedure. For example, the computer **15** may have software as necessary to perform functions related to image analysis, surgical planning, registration, navigation, image guidance, and haptic guidance. A more detailed analysis of an example computing system having one or more computing units that may implement various systems and methods discussed herein, is described subsequently in reference to FIG. **14**.

(60) FIG. **3B** depicts an end effector **40** particularly suited for use in robotic assisted hip arthroplasty. The end effector **40** is configured to be mounted to an end of the robotic arm **30**. The end effector **40** includes a mounting portion **50**, a housing, a coupling device, and a release member. The end effector **40** is configured to individually and interchangeably support and accurately position multiple operating members relative to the robotic arm **30**. As seen in FIG. **3B**, the end effector **40** is coupled to an operating member **100**. The end effector **40** and related tools, systems, and methods are described in U.S. patent application Ser. No. 12/894,071, filed Sep. 29, 2010, which is hereby incorporated by reference in its entirety.

(61) The mounting portion (or mount) **50** preferably couples the end effector **40** to the robotic arm **30**. In particular, the mounting portion **50** extends from the housing and is configured to couple the end effector **40** to a corresponding mounting portion **35** of the robotic arm **30** using, for example, mechanical fasteners, such that the mounting portions are fixed relative to one another. The mounting portion **50** can be attached to the housing or formed integrally with the housing and is configured to accurately and repeatedly position the end effector **40** relative to the robotic arm **30**. In one embodiment, the mounting portion **50** is a semi-kinematic mount as described in U.S. patent application Ser. No. 12/644,964, filed Dec. 22, 2009, and hereby incorporated by reference herein in its entirety.

(62) The end effector **40** in FIG. **3B** is one example of a surgical tool that can be tracked and used by the surgical robotic arm **30**. Other tools (e.g., drills, burrs) as known in the art can be attached to the robotic arm for a given surgical procedure.

III. Pre-operative Planning a Surgical Procedure

(63) Prior to the surgical procedure, a preoperative CT (computed tomography) scan of the patient's pelvis **12** and femur **14** is generated with a medical imaging device. While the discussion will focus on CT scans, other imaging modalities (e.g., MRI) may be similarly be employed. Additionally, and alternatively, X-ray images derived from the CT scan and/or the three-dimensional models **512**, **514** can be used for surgical planning, which may be helpful to surgeons who are accustomed to planning implant placement using actual X-ray images as opposed to CT based models.

Additionally, a generic model of the bone or a statistical model of the bone could be used. The models could be morphed to the patient's bone during the registration process. Additionally, or alternatively, patient specific bone models may also be generated using a combination of two-dimensional X-ray images either with or without patient data collected during registration (e.g., 2D to 3D models).

(64) The CT scan may be performed by the surgeon or at an independent imaging facility. Additionally, or alternatively, intra-operative imaging methods may be employed to generate a patient model of the bone. For example, various boney surfaces of interest may be probed with a tracked probe to generate a surface profile of the surface of interest. The surface profile may be used as the patient bone model. Accordingly, the present disclosure is applicable to all methods of generating a patient bone model or a portion thereof.

(65) As shown in FIG. **4**, the CT scan or data from the CT scan is segmented and to obtain a three-dimensional model **512** of the pelvis **12** and a three-dimensional model **514** of the femur **14**. The three-dimensional models **512**, **514** are used by the surgeon to construct a surgical plan. The

surgeon generates a surgical plan by designating a desired pose (i.e., position and orientation) of the acetabular component and the femoral component relative to the models **512**, **514** of the patient's anatomy. For example, a planned pose **500** of the acetabular cup can be designated and displayed on a computer display, such as the display device **9**. During the surgical procedure, motion of the patient's anatomy and the surgical tool in physical space are tracked by the tracking device **8**, and these tracked objects are registered to corresponding models in the navigation system **7** (image space). As a result, objects in physical space are correlated to corresponding models in image space. Therefore, the surgical system **5** knows the actual position of the surgical tool relative to the patient's anatomy and the planned pose **500**, and this information is graphically displayed on the display device **9** during the surgical procedure.

(66) In certain embodiments, the models **512**, **514** may be of the full bone surfaces **12**, **14** respectively. In certain embodiments, the models **512**, **514** may be trimmed three dimensional models providing only critical regions of interest such as the acetabulum **22** and femoral head **16**. That is, the trimmed three-dimensional models represent only a portion of the full bone models **512**, **514**. In certain embodiments, the models **512**, **514** may be the combination of multiple models. For example, model **512** may be the combination of individual three-dimensional models of the operative pelvis, non-operative pelvis, and spine.

IV. Intra-operative Procedures

(67) A.

(68) FIG. 5 illustrates an embodiment of intra-operative steps of performing a total hip replacement. In this embodiment, steps **S1-S7**, **S9**, **S11**, and **S12** can be performed with or without robotic assistance. In other embodiments, **S1-S2** may not be required, **S3-S5** could be done before **S1-S2**, and **S7** could be done at any point before **S8**. Steps **S8** and **S10** are preferably performed using the robotic arm **30**. For example, step **S8** (reaming) can be performed using the robotic arm **30** of FIG. 3 with the end effector **40** coupled to the operating member **100**, and step **S10** (impacting) can be performed using the robotic arm **30** with the end effector **40** coupled to another operating member.

(69) B. Tracking and Registration of Femur

(70) In step **S1** of the surgical procedure, a tracking array is attached to the femur **14** to enable the tracking device **8** to track motion of the femur **14**. In step **S2**, the femur **14** is registered to correlate the pose of the femur **14** (physical space) with the three-dimensional model **514** of the femur **14** in the navigation system **7** (image space). Additionally, the femur checkpoint may be attached. In step **S3**, the femur is prepared for surgery.

(71) The following description provides exemplary methods of preparing and registering the femur in a surgical procedure on a patient's hip. In certain instances, methods of femoral preparation and registration will be described with reference to FIGS. **8-13**. Additionally, certain steps of the preoperative planning of the femur implant and femur preparation will be described as well.

(72) To begin, reference is made to FIGS. **8** and **9A-9D**. In certain instances, the registration method **800** may include picking points on both an exterior surface of a proximal portion of the femur, and an interior bone surface such as, for example, along the medullary cavity, which is to be prepared for the implantation of a stem of a femoral implant component. In this way, the registration transform may include internal and external bone information to increase the accuracy of the transform. As seen in FIG. **8**, the registration method **800** may include segmenting or modeling the outer and inner bone surfaces of the femur at **802**. A single medical image **900** of the proximal femur **902** is shown in FIG. **9A**, where both the outer bone surface **904** and the inner bone surface **906** are identified for segmentation. While only a single medical image **900** is shown, the registration method **800** may include segmenting a plurality of medical images encompassing the full bone. Thus, the inner and outer bone surfaces of each of the plurality of medical images may be segmented.

(73) The registration method **800**, at **802** of FIG. **8**, may additionally include identifying a point-

cloud at the proximal femur. As seen in FIG. 9A, a series of points **908** and their respective locations are identified and stored in the point-cloud. As seen in the figure, the series of points **908** are located on femoral neck, femoral head, and greater trochanter.

(74) While step **802** of the registration method **800** takes place prior to the surgical procedure, steps **804** through **808** take place intra-operatively. The registration method **800**, at **804** of FIG. 8, may include resecting the proximal femur by a burr end-effector within a smaller than planned haptic volume to clear the bone cavity for point picking. As seen in FIG. 9B, the proximal femur **902** has been resected within a volume **910** that is smaller than a volume **912** for subsequent resection for placement of the stem of an implant.

(75) Referring back to FIG. 8, the registration method **800**, at **806**, may include the surgeon picking, logging, or capturing points on an interior bone surface along the medullary canal. As seen in FIG. 9C, a tracked probe **914** having a pointed tip may be used to capture points on an interior bone surface along the medullary canal of the proximal femur **902**. The probe tip may extend through the undercut volume **910** and into the stem volume **912** to the points **916** for capture. The registration method **800**, at **806**, may also include running an optimization method such as, for example, an iterative closest point (ICP) transform with combined new and existing point-cloud data, and the registration transform may be updated.

(76) At step **808** of the registration method **800**, preparation of the femur may be finished to the planned volume (i.e., using the burr end-effector) for subsequent implantation of the stem of the femoral component. As seen in FIG. 9D, the full volume **912** has been resected for the implantation of the stem of the femoral component.

(77) Another femur registration method **1000** is shown in FIGS. 10 and 11A-11D. As seen in FIG. 10, the registration method **1000** may include segmenting an outer and an inner bone surface of the femur, at step **1002**. Step **1002** additionally includes picking a point-cloud at the proximal femur for bone registration. FIG. 11A depicts a medical image **1100** of a proximal femur **1102** where both the outer bone surface **1104** and the inner bone surface **1106** are identified for segmentation. The medical image **1100** also includes a series of points **1108** stored in the point-cloud. As seen in the figure, the series of points **1108** are located on femoral neck, femoral head, and greater trochanter.

(78) While step **1002** of the registration method **1000** takes place prior to the surgical procedure, steps **1004** through **1008** take place intra-operatively. Step **1004** of FIG. 10 includes resecting the proximal femur with a burr of an end-effector within a smaller volume than ultimately planned for the implantation of a stem of a femoral implant component. This smaller volume clears the internal femoral cavity for point picking. As seen in FIG. 11B, a burr **1114** of an end effector resects a volume **1110** within an interior part of the proximal end of the femur **1102**. Generally, the burr **1114** may resect with a distal or downward trajectory though the femoral neck and greater trochanter. In certain instances, the femoral head may remain un-resected at this point of the procedure. The resected volume **1110**, as seen in FIG. 11B, is within the confines of a larger, final preparation volume **1112** that will be resected later in the procedure.

(79) Step **1006** of FIG. 10 includes moving the burr of the end effector (or other tool attached to the end of the end effector) down (distally) the femoral canal and picking, logging, or capturing points on intact bone surfaces on the inner portion of the bone. The bone surface may also be detected automatically by monitoring the state of the motors in the system to determine when contact with a hard surface is made. Then, the iterative closest point (ICP) calculation is run with combined new and existing point-cloud data. The registration transform is then updated. As seen in FIG. 11C, the surgeon extends the burr **1114** through the undercut haptic volume **1110** till the burr **1114** contacts the inner bone surface **1106**. The surgeon captures, logs, or picks points **1116** on the inner bone surface **1106**. The location of these points is used to update the registration transform. Additionally, or alternatively, the system may automatically detect the burr TCP contacting the inner intact cortical bone surface, or it may be measured using a force/torque sensor (or other type of sensor) attached to the burr end effector.

(80) Step **1008** of FIG. **10** includes finishing the resection of the femoral canal to the planned resection volume or haptic volume for the placement of the stem of the femoral implant component using the updated bone registration transform. As seen in FIG. **11D**, the femoral canal is fully resected to the full resection volume **1112** accord to the surgical plan.

(81) Another femur registration method **1200** is shown in FIGS. **12** and **13A-13D**. As seen in FIG. **12**, the registration method **1200** may include, at step **1202**, segmenting an outer bone surface of the proximal femur, and determining the femoral canal axis or the femoral anatomic Z-axis of the femur canal in a bone model constructed from medical images of the proximal femur. Additionally, step **1202** may include picking a point-cloud on the proximal femur outer surface for bone registration. This particular femur registration method **1200** does not include segmentation of the inner bone surface. As seen in FIG. **13A**, a medical image **1300** of a plurality of medical images are taken of a patient's proximal femur **1302**. The outer bone surfaces **1304** of the proximal femur **1302** in the medical images **1300** are segmented, and a femoral anatomic Z-axis **1306** of the femur canal is determined from the plurality of medical images. The figure also shows a plurality of points **1308** of a point-cloud on the proximal femur **1302**. The plurality of points **1308** are spaced along portions of the femoral head, femoral neck, and greater trochanter.

(82) While step **1202** of the registration method **1200** takes place preoperatively, steps **1204** through **1208** take place intra-operatively. Step **1204** of FIG. **12** includes resecting the proximal femur with a burr of an end-effector within a smaller volume than the fully resected haptic volume for the implantation of the stem of a femoral implant component. The smaller volume of the resection of step **1204** is intended to clear the cavity for point picking. Additionally, at step **1204**, a surgeon may insert a tracker mechanism into the medullar canal. As seen in FIG. **13B**, an initial volume **1310** within the femoral canal is resected via a burr of an end-effector. The initial volume **1310** is less than the full resection volume **1312** that will be used for the implantation of the stem of the femoral implant component. After the initial volume **1310** is resected, a tracker mechanism or tool **1314** is inserted into the femoral canal. As seen in FIG. **13B**, the tracker mechanism **1314** includes a distal expansion mechanism, a shaft extending proximally from the distal positioning mechanism, and a tracker at a proximal end of the tracker mechanism. The tracker mechanism **1314** may be inserted into the femoral canal such that the distal positioning mechanism extends past the initial volume **1310** and into the bone of the femoral canal.

(83) Step **1206** of FIG. **12** may include aligning the tracker mechanism **1314** with the cortical bone surface on the interior side of the femur. Reference is made to FIG. **13C**, which shows the tracker mechanism **1314** in a laterally expanded orientation within the femoral canal such that the shaft is generally parallel with the femoral anatomic Z-axis **1306**. As seen in the figure, the distal positioning mechanism **1314** may include a plurality of members extending longitudinally (parallel with the shaft) that are configured to expand radially outward so as to contact the inner cortical bone surfaces of the femur **1302**. The plurality of members may have a plurality of markers capable of being seen under medical imaging to verify the plurality of members are contacting the cortical bone surfaces of the femur. As seen in the figure, when the plurality of members contacts the cortical bone surface, the shaft extending proximally from the distal positioning mechanism is parallel to the femoral anatomic Z-axis **1306**. In certain instances, the location of the bone contact points may be tracked inside the tracker mechanism **1314**. The mechanism **1314** may include two, three, or more contact points capable of centering the tool in the canal so as to register the center point at any given position. In such an instance, a tool axis may not be needed. In certain instances, the contact points on the tracker mechanism **1314** could be spring expandable, and actively track and map the internal walls of the bone as the tool is inserted into the canal.

(84) Turning back to FIG. **12**, the registration method **1200** at step **1206** may also include running an iterative closest point (ICP) calculation with the existing point-cloud and the femoral anatomic Z-axis determination, and the registration transform may be updated accordingly.

(85) Step **1208** of FIG. **12** may include finishing the bone preparation by removing the tracker

mechanism **1314** and resecting the remaining portion of the femoral canal to the final resection volume, which may have been updated based on the registration transform. As seen in FIG. **13D**, the proximal femur **1302** may be fully resected to the final resection volume **1316** for the implantation of the stem of the femoral implant component.

(86) Another femur registration method **1330** is shown in FIG. **13E**. As seen in FIG. **13E**, the registration method **1330** may include the following operations or steps. In certain instances, the method **1330** may include planning the placement of an implant relative to a computer model of a patient bone in an imaging coordinate system (1). The implant plan in (1) may provide the planned initial femur canal preparation (2a) (to be used in canal registration) and the planned full preparation (2b) (to receive an implant stem) in the imaging coordinate system since the two planned preparations of the femoral canal may be related to the overall implant plan. A difference (e.g., volume difference) between the full (2b) and canal (2a) preparation can also be calculated in the imaging space (2c).

(87) Continuing on with the method **1330** in FIG. **13E**, after the implant planning (otherwise known as preoperative planning) (1), the surgeon may register the proximal femur (3) using any known registration method. From the proximal femur registration (3), the proximal registration transform to bone coordinate system (Bone CS A) is calculated (4). Using the proximal registration transform from (4), the planned femur canal preparation from (2) is transformed to the Bone CS A (5). Knowing the femur canal preparation plan in Bone CS A from (5), the system can then prepare the canal in Bone CS A (6) by physically burring out the proximal canal of the femur according to the planned canal preparation determined in (2a).

(88) With the proximal femoral canal burred-out or otherwise prepared, the surgeon may then register the inner bone (7) which is now exposed by the burring. The proximal registration in (3) may be combined with the inner bone registration in (7), to calculate a full bone registration transformation to Bone CS B (8). With the full bone transformation from (8), the full bone preparation plan from (2a) is transformed to Bone CS B (9).

(89) The decision box in **10** defines where the design may be split between full preparation or remaining preparation only.

(90) In instance #1: Prepare full bone preparation (ignoring previously prepared canal). Knowing the full preparation plan in Bone CS B from (9), the system can then prepare the proximal femur according to the full preparation plan in Bone CS B (11) by physically burring out the proximal femoral canal according to the full preparation plan from (2b). Registration and preparation of the bone is complete in this first instance.

(91) Instance #2 or #3 will now be described.

(92) The decision box in (16) defines where the design may be split between preparing remaining bone with or without correction for the transform between the proximal registration (Bone CS A) and full registration (Bone CS B).

(93) Instance #2: Preparing remaining bone with transform correction. The difference between Bone CS A from (4) and Bone CS B from (8) is calculated. Knowing the transform difference above, the femur canal prep in Bone CS A (5) can be transformed to Bone CS B (13). The remaining bone in Bone CS B (14) may be calculated by subtracting the canal prep in Bone CS B (13) from the full planned preparation in Bone CS B (9). Knowing the remaining bone in Bone CS B, the system can then prepare the remaining bone in Bone CS B (15) by burring the remaining bone in the proximal femur canal according to the full preparation plan. Registration and preparation of the bone is complete in this second instance.

(94) Instance #3: Preparing remaining bone without transform correction. The planned remaining bone from (2c) is transformed into Bone CS B knowing the transform from (8). The system can then prepare the assumed remaining bone in Bone CS B (17) with the assumption that the differences between Bone CS A and Bone CS B are minimal and any unprepared bone due to the difference will be floating and removable from the canal. Registration and preparation of the bone

is complete in this third instance.

(95) Another femur registration method **1340** is shown in FIG. **13F**. The first step **1342** of the method **1340** is preoperative planning the arthroplasty procedure such as a total hip replacement, for example. More particular, the step **1342** may include planning the implant placement of a femoral implant relative to the patient's femur in a preoperative coordinate system. This may include selection of implant size, shape, type, and manufacturer, among other variables. Additionally, the preoperative planning of the implant may include virtually positioning and orienting an implant model (e.g., virtual three-dimensional implant model representative of a physical implant provided by the manufacturer) relative to a patient bone model (e.g., virtual three-dimensional bone model representative of the patient's physical femur). The implant model may be provided by the manufacturer. The patient bone model may be generated from preoperative scans of the patient's leg. The patient bone model may be generated from a statistical model, a generic model, or other type of model that represents or approximates the shape, size, and configuration of the patient's physical bone.

(96) Once a final implant position and orientation is determined to achieve a particular surgical outcome, a surgical plan can be determined to achieve the final implant position and orientation. For instance, the final implant position and orientation will determine the corresponding position and orientation of bone to be removed from the canal of the femur so the stem of the femoral implant can be accurately positioned therein in order to achieve the desired or planned final implant position and orientation.

(97) As part of the preoperative planning step **1342**, the method **1340** may also include planning or determining an initial canal preparation plan, at step **1344**. The initial canal preparation plan may be also be called a first bone removal plan of the surgical plan. In the actual, physical surgery, the femoral canal will be prepared by, for example, being bored longitudinally in the place where the stem of the femoral implant will eventually be positioned. As described herein, the femoral canal will be prepared in at least two steps: initial canal preparation for registration purposes; and final canal preparation for implantation of the femoral implant. The step **1344** of determining an initial canal preparation plan may include determining coordinate locations for a partial bone removal of the femoral canal. The step **1344** may also include determining a cut path for a surgical device to facilitate removal of the bone from the femoral canal. The coordinate locations and the cut path may be defined in a coordinate system relative to preoperative bone model used for planning the final implant position and orientation. As described herein, the initial canal preparation plan may only include a partial canal preparation that includes less bone removal (e.g., less depth, less diameter) than a full canal preparation needed for implantation of the stem of the femoral implant.

(98) One reason for the initial canal preparation plan to be a partial bone removal from the femoral canal as opposed to a full preparation of the femoral canal is that partial bone removal allows for an additional registration step involving data from the femoral canal that takes place prior to the full preparation of the femoral canal. This additional registration of the internal femoral canal may lead to a more accurate registration process and thus a more accurate full preparation of the femoral canal. For at least these reasons, the preoperative planning of the bone removal may be split into at least a first bone removal plan including a plan for partial removal of bone from the femoral canal (for registration purposes), and a second bone removal plan including a plan for full removal of bone from the femoral canal to achieve the final implant position and orientation that was preoperatively planned.

(99) The next step **1346** of the method **1340** may include planning or determining a final canal preparation plan. The final canal preparation plan may be also be called a second bone removal plan of the surgical plan. Alternatively, the final canal preparation plan may be called a post-registration canal preparation plan. This step **136** of the method **1340** includes a plan for the preparation of the femoral canal beyond the initial canal preparation from step **1344**. In certain instances, this step **1346** includes the plan for preparation of the femoral canal so the canal is

sufficiently bored out to receive the stem of the femoral implant.

(100) The step **1346** may include a number of sub-steps such as the following: planning a broachless femoral preparation plan, at step **1348**; planning a single broach preparation plan, at step **1350**; planning an entire canal preparation plan, at step **1352**; and planning only a bone remainder canal preparation plan, at step **1354**. Each of these sub-steps will be described in turn.

(101) In determining the final canal preparation plan, at step **1346**, the method may include a broachless preparation plan, at step **1348**. In this step **1348**, the femoral canal is planned to be prepared fully robotically without manual broaching by a surgeon. In this way, no portion of the bone is left for manual preparation by the surgeon; stated differently, the entire final preparation plan (whether entire canal prep or bone remainder canal prep only) is robotically prepared.

(102) As an alternative to a broachless preparation plan, the final canal preparation plan may include a single broach preparation plan, at step **1350**. In this step **1350**, the femoral canal is planned to be prepared partially by robotic control, with a final broach performed manually by a surgeon. In this way, a small portion of bone removal needed to implant the implant is left off of the final canal preparation plan so that the surgeon can manually perform a final broach. In traditional (non-robotic) surgery, a surgeon may use a series of broaches of increasing size to prepare the femoral canal. In this case, a final (single) broach may be utilized since the final canal preparation plan was performed robotically without the need for broaches. Permitting the surgeon to perform a final broach of the femoral canal enables the surgeon to make any final adjustments to implant fit, and may also lessen the chance of removal of too much bone from the canal via robotic preparation since the surgeon could trial the implant fit while broaching.

(103) Separate from determine whether the final canal preparation plan will include a broachless plan, at step **1348**, or a single broach plan, at step **1350**, the final canal preparation plan **1346** may also include a determination of whether to plan the preparation of the entire femoral canal (including bone removal from the area of the initial canal preparation), at step **1352**, or whether to plan the preparation of only the bone remainder of the bone canal (bone that was not removed by the initial canal preparation), at step **1354**.

(104) At step **1352**, the final canal preparation plan may include planning the preparation of the entire femoral canal. This may include preparation of the femoral canal that was previously prepared by the initial canal preparation plan. The difference being that a second registration will have taken place that includes more registration data as compared to the first registration (e.g., registration data from both the inner canal and exterior surface of femur), possibly increasing the accuracy of the mapping of the surgical plan from the preoperative coordinate system including the second bone removal plan to the operative coordinate system. Thus, there may be improvements to the accuracy of the locations of bone removal following the second registration. Therefore, planning preparation of the entire femoral canal would benefit by re-milling or re-removing the portions of the bone that were initially planned to be removed in the initial canal preparation plan.

(105) In addition to re-removing the portions of bone that were initially planned to be removed in the initial canal preparation plan, at step **1344**, the planning for the preparation of the entire femoral canal, at step **1352**, may include planning coordinate locations for bone removal of the remaining portions of bone sufficient for implantation of the stem of the femoral implant. It is noted that a final canal preparation plan that includes the preparation of the entire femoral canal according to step **1352** may include a broachless preparation plan according to step **1348** or a single broach preparation plan according to step **1350**.

(106) At step **1354**, the final canal preparation plan may include planning the preparation of only the bone remainder of the femoral canal. This may include preparation of the femoral canal that was not previously prepared by the initial canal preparation plan. In certain instances, there may not be significant accuracy improvement from the second registration; therefore, the increased time it takes to re-prepare the bone as done in the entire canal preparation plan, at step **1352**, may not be worth marginal increase in accuracy. If there was, however, a substantial increase in accuracy

improvement from the second registration, this may indicate that preparation of the entire canal is beneficial.

(107) The planning for the preparation of only the bone remainder of the femoral canal, at step **1354**, may include planning coordinate locations for bone removal of the remaining portions of bone sufficient for implantation of the stem of the femoral implant. It is noted that a final canal preparation plan that includes the preparation of only the bone remainder of the femoral canal according to step **1354** may include a broachless preparation plan according to step **1348** or a single broach preparation plan according to step **1350**.

(108) In one instance, the final canal preparation plan may include a plan to prepare the entire femoral canal, according to step **1352**, and with a broachless preparation plan, according to step **1348**. In one instance, the final canal preparation plan may include a plan to prepare the entire femoral canal, according to step **1352**, and with a single broach preparation plan, according to step **1350**. In one instance, the final canal preparation plan may include a plan to prepare only the bone remainder of the femoral canal, according to step **1354**, and with a broachless preparation plan, according to step **1348**. In one instance, the final canal preparation plan may include a plan to prepare only the bone remainder of the femoral canal, according to step **1354**, and with a single broach preparation plan, according to step **1350**.

(109) After the preoperative planning, at step **1342**, is complete, the surgery may commence. As part of the surgery, a femoral track may be installed or coupled to the patient bone, at step **1356**. The femoral tracker provides a reference to the surgical navigation system so that the surgical robot is spatially aware of the proximity of the patient's bone in the operative coordinate system.

(110) Once the tracker is installed, the proximal bone of the femur is registered (assuming it is already dislocated from the hip), at step **1358**. More particularly, the femoral head may be registered by collecting, logging, capturing points with a surgical device (e.g., tracked pointer, end effector of robotic arm) on the exterior surface of the femoral head. The captured points (also known as registration data) may be stored in a point-cloud of data, and may be spatially oriented relative to each other according to their locations on the exterior surface of the femoral head. A sufficient number of points are collected in order to approximate the shape of the surface to be registered.

(111) The surgical navigation system is capable of spatially locating the captured points relative to the femoral tracker. The internal canal preparation plan, from step **1344**, is defined relative to the preoperative bone model that represents the patient's femur. Thus, the goal of registration is to accurately transform or map the preoperative surgical plan (e.g., internal canal preparation plan) to the operative coordinate space relative to the actual femur in the same position and orientation that the surgical plan was in relation to the preoperative bone model. In this way, the surgical robotic arm and the surgical plan will be in the same coordinate system, and the robotic arm can be operated to perform the surgical plan on the actual patient bone so as to accomplish the preparation of the femur as planned preoperatively at step **1342**.

(112) Once the points are captured on the proximal femur, the computer of the system calculates a registration transform based on the captured points on the proximal femur, at step **1360**. The registration transform is a mathematical algorithm mapping the coordinate points associated with the initial canal preparation plan from the preoperative coordinate system to the captured points on the physical femur in the operative coordinate system. From the registration transform, the surgical plan including the initial canal preparation plan, from step **1344**, is transformed or mapped to the operative coordinate system, at step **1362**.

(113) With the initial canal preparation plan defined in the operative coordinate system, the method **1340** now includes preparing the initial canal in the proximal femur according to the initial canal preparation plan, at step **1364**. As described with reference to step **1344**, the initial canal preparation plan may include a partial preparation of the femoral canal that is less than full preparation of the femoral canal for implantation of the stem of an implant. For example, the

robotic arm of the surgical robot may be used to bore or mill through the greater trochanter and into the central canal (i.e., femoral canal). The bone may be, for example, milled distally until the inner surfaces of the cortical bone are reached. The cortical bone is much harder than the spongy bone leading to the cortical bone; thus, it is easily identified during the procedure. The inner cortical bone is also easily identified in the preoperative bone model. Therefore, the inner cortical bone provides areas for registration that can be combined with the registration points on the proximal femur. The combined points may be advantageous for producing a more accurate registration transform since the points are spaced apart from each other, and are on different surfaces of the bone (inner and outer). Registration of the proximal femur and central canal is possible since the femoral head is still intact (i.e., not yet resected).

(114) After the initial, partial preparation of the central canal, the method **1340** may include registering the inner canal, at step **1366**. The inner canal may be registered in any number of ways. As an example, a surgical device (e.g., tracked probe, end effector of surgical arm, any of the devices previously described) may be used to collect, log, or capture points on the internal cortical bone surface of the femoral canal. As another example, a surgical device (e.g., tracked probe, end effector of surgical arm, any of the devices previously described) may be used to collect, log, or capture orientation data associated with the femoral canal. Orientation data may be an axis, such as a longitudinal axis of the femoral canal. The captured points and/or the orientation data may be defined as registration data. The registration data may be stored as a point-cloud of data in a computer.

(115) Once the inner bone is registered, the method **1340** may include calculating a registration transform using the registration data from the femoral canal (e.g., captured points) and the registration data from the exterior surface of the proximal femur (e.g., captured points and/or orientation data). Since the second registration transform, at step **1368**, includes additional data from the inner canal, as compared to the first registration, at step **1360**, the registration transform may have improved accuracy as compared with the first registration transform.

(116) At step **1370**, the method **1340** may include transforming or mapping the final canal preparation plan, from step **1346**, to the operative coordinate system based on the calculated registration transform of step **1368**. This step maps the coordinate locations and/or instructions for bone removal for the final canal preparation plan from the preoperative coordinate system to the operative coordinate system in the same position and orientation as the surgical plan was oriented and positioned relative to the preoperative bone model. In this way, the final canal preparation plan is in the operative coordinate system with the patient's femur and the surgical robot.

(117) Following transforming the final canal preparation plan to the operative coordinate system, the method **1340** may include, at step **1372**, preparing the femur according to the final canal preparation plan. How the femur is prepared depends on the parameters of the final canal preparation plan as preoperatively defined at step **1346**. For a preoperatively planned preparation of the entire canal, at step **1352**, the physical preparation of the entire canal will take place at step **1374**. In this step, the entire femoral canal may be milled or otherwise removed. This includes milling the previous portion of the bone that was previously removed at step **1364**, as well as preparing the bone remainder that was not previously removed. As described previously, the initial canal preparation, at step **1364**, was only a partial preparation of the femoral canal for the purpose of registration of the bone surfaces or axes associated with the canal. The final preparation of the femur canal is to remove sufficient bone to receive the stem of the femoral implant. As described previously, the entire canal preparation may take advantage of the second registration that involves data from the exterior and interior portions of the femur. Thus, the entire femur preparation may still remove bone from the initially prepared portion of the femur since the coordinates may have changed due to the subsequent registration.

(118) For a preoperatively planned preparation of only the bone remainder of the femoral canal, at step **1354**, the physical preparation of the bone remainder will take place at step **1376**. In this step,

the bone remainder or portion of the femoral canal that was not previously removed is prepared (i.e., removed) in order to make way for the stem of the femoral implant. This may include milling down into the femoral canal only the portions of bone that were not previously removed. This step may include a sub-step **1378** of deciding whether to use the first registration transform that was calculated with points on the exterior of the proximal femur, or the second registration transform that was calculated with points on the exterior of the proximal femur and femoral canal data taken from the femoral canal.

(119) Following the physical preparation of the femoral canal, and prior to the resection of the femoral head, the method **1340** may include, at step **1380**, marking the femoral neck in preparation for a manual resection of the neck. In a robotic hip surgery, the femoral tracker may be coupled to the femoral head. And thus robotic navigation will cease to function when the femoral head is resected as the tracker will no longer be able to correctly identify the location of the remaining portion of the femur. For at least this reason, the femoral neck is marked (e.g., etched) via robotically controlled and navigated guidance to provide guidance to the surgeon when manually resecting the neck. The femoral neck mark may be an etch or burr into the bone along the planned resection plane. The etch or burr may be a cut into the bone that does not fully resect the bone. That is, the cut into the bone may not extend through the cortical bone. Instead, the cut provides a visible mark for the surgeon to use or verify correct placement of a saw blade.

(120) The manual preparation of the femur is shown at step **1382**. The neck resection is shown at step **1384** and may include the surgeon using a bone saw with or without additional guides or jigs to manually resect the femoral head at the neck. If the final canal preparation included a single broach preparation plan, at step **1350**, the surgeon may then broach the femoral canal at step **1386**. Since the navigated robot prepared the rest of the femoral canal preparation, the only remaining part of the manual preparation of the canal prior to implant trialing and implant fitting is for the surgeon to use a single broach to remove the last remaining portions of the bone. This provides the surgeon with an opportunity to make minor adjustments to the femoral canal and/or trial the implant as he or she broaches to provide an accurate implant fit.

(121) The following is a description of an exemplary system implementing the method **1340** of FIG. **13F**. The system may register a surgical device, such as a surgical robot, and a bone of a patient, such as a femur. The femur may include an exterior surface such as the femoral head, neck, and greater trochanter. The femur may also include an inner canal or femoral canal. The surgical device and the femur are in the same operative coordinate system (e.g., operating room). The system may include at least one computing device in communication with a surgical navigation system and the surgical device. The surgical navigation system may include a tracking device and at least one tool (e.g., tracked probe, tracking arrays positioned on surgical robot and/or patient) configured to be tracked in its movement by the tracking device. The surgical navigation system is also configured to track the surgical device and/or a tracking array on the surgical device. The at least one computing device stores a surgical plan in a virtual coordinate space. The surgical plan may include data from the preoperative planning of the implant placement from step **1342** of the method **1340** of FIG. **13F**. The surgical plan may also include the initial canal preparation plan, also known as the first bone removal plan, at step **1344** of the method **1340** of FIG. **13F**. The surgical plan may also include the final canal preparation plan, also known as the second bone removal plan, at step **1346** of the method **1340** of FIG. **13F**. The second bone removal plan may include the plans for a broachless preparation plan at step **1348**, a single broach preparation plan at step **1350**, an entire canal preparation plan at step **1352**, and/or the bone remainder preparation plan at step **1354**, among other steps, such as the neck etch plan.

(122) The at least one computing device is configured to do the following: a) receive external bone registration data corresponding to locations on the exterior surface of the femur. This bone registration data may correspond to the registration of the proximal bone from step **1358** of the method **1340** of FIG. **13F**. For instance, the surgeon may capture, collect, or log points on the

patient's proximal femur (e.g., head, neck) using a tracked probe that is tracked by the surgical navigation system in the operative coordinate system. Next, the at least one computing device is configured to: b) calculate a first registration transform based on the external bone registration data. This step may correspond to step **1360** of the method **1340** of FIG. **13F**. The at least one computing device may then: c) transform the first bone removal plan of the surgical plan to the operative coordinate system based on the first registration transform. This step may correspond to step **1362** of the method **1340** of FIG. **13F**. The at least one computing device may also: d) receive internal bone canal registration data corresponding to at least one of location or orientation data from the inner canal of the femur. This step may correspond to step **1366** of the method **1340** of FIG. **13F**. For instance, the surgeon may capture, collect, or log points on the patient's inner femoral canal that was partially prepared for the purpose of accessing and registering to provide additional registration data that can be used for the final preparation of the femur canal.

(123) The at least one computing device may also: e) calculate a second registration transform based on both the external bone registration data and the internal bone registration data. This step may correspond to the step **1368** of the method **1340** of FIG. **13F**. And the at least one computing device may also: f) transform the second bone removal plan of the surgical plan to the operative coordinate system based on the second registration transform. This step may correspond to step **1370** of the method **1340** of FIG. **13F**.

(124) The exemplary system described in the previous paragraphs may be additionally or alternatively described as a computer implemented method of registration of a surgical device and a patient bone (e.g. femur). The computer implemented method may include the steps described by the at least one computer in steps a) through f), among others.

(125) The exemplary system described in the previous paragraphs may also be additionally or alternatively described as one or more tangible computer-readable storage media storing computer-executable instructions for performing a computer process on a computing system, such as the at least one computing device described in the previous paragraphs. The computer process may include the steps a) through f), among others, described with reference to the at least one computing device.

(126) C. Tracking and Registration of Pelvis

(127) 1. Overview

(128) In step **S4** of FIG. **5**, an acetabular tracking array is attached to the pelvis **12** to enable the tracking device **8** to track motion of the pelvis **12**. In step **S5**, a checkpoint may be attached to the pelvis **12** for use during the surgical procedure to verify that the acetabular tracking array has not moved in relation to the pelvis **12**. The checkpoint can be, for example, a checkpoint as described in U.S. patent application Ser. No. 11/750,807 (Pub. No. US 2008/0004633), filed May 18, 2007, and hereby incorporated by reference herein in its entirety.

(129) In step **S6**, the pelvis **12** is registered to correlate the pose of the pelvis **12** (physical space) with the three-dimensional model **512** of the pelvis **12** in the navigation system **7** (image space). In certain embodiments, as shown in FIG. **6**, registration is accomplished using the tracked navigation probe **56** to collect points on the pelvis **12** (physical space) that are then matched to corresponding points on the three-dimensional model **512** of the pelvis **12** (image space). In certain embodiments, registration may be accomplished using a tool that is coupled to the end effector **40** of the robotic arm **30**. In certain embodiments, registration may be accomplished with any tool or device that is tracked with the navigation system **7**. Two methods of registering the three-dimensional model **512** of the pelvis (image space) and the pelvis **12** (physical space) are described in the subsequent sections of this application.

(130) 2. Pelvic Registration Method

(131) As shown in FIG. **6**, the display device **9** may show the representation **512** of the pelvis **12**, including one or more registration points **516**. The registration points **516** help the surgeon understand where on the actual anatomy to collect points with the tracked probe. The registration

points **516** can be color coded to further aid the surgeon. For example, a registration point **516** on the pelvis **12** to be collected next with the tracked probe can be colored yellow, while registration points **516** that have already been collected can be colored green and registration points **516** that will be subsequently collected can be colored red. After registration, the display device **9** can show the surgeon how well the registration algorithm fit the physically collected points to the representation **512** of the pelvis **12**.

(132) For example, as shown in FIG. 7, error points **518** can be displayed to illustrate how much error exists in the registration between the surface of the representation **512** and the corresponding surface of the physical pelvis **12**. In one embodiment, the error points **518** can be color coded, for example, with error points **518** representing minimal error displayed in green and error points **518** representing increasing amounts of error displayed in blue, yellow, and red. As an alternative to color coding, error points **518** representing different degrees of error could have different shapes or sizes. Verification points **519** can also be displayed. The verification points **519** illustrate to the surgeon where to collect points with the tracked probe to verify the registration. When a registration point **519** is collected, the software of the navigation system **7** displays the error (e.g., numerically in millimeters) between the actual point collected on the anatomy and the registered location of the representation **512** in physical space. If the registration error is too high, the surgeon re-registers the pelvis **12** by repeating the registration process of step **S6**.

(133) This type of registration method requires the surgeon to continually switch his or her focus from the display device **9** showing the representation **512** of the pelvis **12**, including one or more registration points **516**, to the patient's physical pelvis **12** in order to collect accurate points. Switching focus takes time, and accurately estimating where the registration points **516** are on the patient's physical pelvis **12** takes even more time. In such a registration method described in this section, it may take at least forty-three points to complete an accurate registration.

(134) Additional pelvic registrations methods **S6** involving determining a center of rotation of the acetabulum based on pre-operative images and intra-operative point collection are described in related application PCT/US2017/049466, filed Aug. 30, 2017, which is hereby incorporated by reference in its entirety into the present application. The methods described may reduce the total number of collected points as compared with the previously described registration method. For example, with the method described in this section, a surgeon may complete an accurate registration with thirty-two points or less. Additionally, much of the registration described in this section is a region-based point collection, as opposed to a point-based point collection. In a region-based point collection, the surgeon is permitted to collect points within a region of the patient's bone, as opposed to an exact point as identified on the three-dimensional bone model **512**. This permits the surgeon to focus on the patient's anatomy, and collect points within the permitted region on the bone without having to switch his or her focus to the display screen **9** and back to the patient's physical pelvis **12**. Collecting points within a permitted region increases accuracy as it is easier for the surgeon to collect points within a region encompassing many possible locations of permissible points, as compared with a single permissible point.

(135) 3. Pelvic Registration Method Utilizing a Z-Axis of an Imaging Table and a Z-Axis of an Operating Table.

(136) Reference is made to FIGS. **14A-14B** and **15A-15C**, which illustrates a pelvic registration method **1400** utilizing acetabular center of rotation data and patient positioning data from the patient during a pre-operative image scan (e.g., CT, MRI) and while in the operating room. More particularly, the registration method **1400** assumes an orientation of a patient lying, for example, supine on an imaging table for a pre-operative image scan (e.g., CT, MRI) is the same or similar to an orientation of the same patient lying in the same position (e.g., supine in this example) on an operating room table. This patient orientation data or patient positioning data may be used in conjunction with acetabular center of rotation data, among other data, that may be determined from the pre-operative image scans and from capturing points on the patient's acetabulum intra-

operatively in registering a three-dimensional bone model of the patient's pelvis with the patient's physical pelvis in the operating room.

(137) To begin, reference is made to FIGS. **14A** and **14B**, which illustrate exemplary steps of the registration method **1400**. At step **1402** of FIG. **14A**, the registration method **1400** may include generating pre-operative image scans of a patient. The image scans may be generated via a variety of imaging modalities including computed tomography (CT), magnetic resonance imaging (MRI), and X-ray, among others. To generate the image scans, a patient **1500** lying supine on an imaging table **1502** may be imaged via an imaging arm **1504** of an imaging machine **1506**, as seen in FIG. **15A**. At step **1404** of the registration method **1400** of FIG. **14A**, the image scans may be segmented along the bone contour lines of the images. Once all the image scans are segmented, a three-dimensional bone model of the diseased area (e.g., ilium and femur) may be generated from the segmented image scans, at step **1406** of FIG. **14A**. As an alternative to generating a three-dimensional bone model from the segmented image scans, a generic 3D bone model or statistical 3D bone model being representative of the patient bone may be generated.

(138) At this point, the pre-operative steps of the registration method **1400** may diverge. Steps **1408**, **1410**, and **1412** may refer to the patient positioning data portion of the registration method **1400**, whereas step **1414** may refer to the center of rotation calculation portion of the method **1400**.

(139) At step **1408** of FIG. **14A**, the Z-axis, long axis, or superior-inferior axis may be identified from the scanned images or from the three-dimensional bone model. As seen in FIG. **15A**, the Z-axis **1508** extends longitudinally down the table and from the patient's **1500** head to toes. The Z-axis **1508** may be identified in the scanned images as the axis the imaging table **1502** extends relative to the imaging arm **1504**. For example, in a CT scan, the imaging table **1502** may be motorized so as to translate the table **1502** and patient **1500** positioned thereon along the Z-axis **1508** through an opening or through-way **1510** of the imaging arm **1504**. In this orientation, the scans may be oriented perpendicular to the Z-axis **1508**. The Z-axis **1508** may be identified in a coordinate system with the bone model.

(140) At step **1410** of FIG. **14A**, the registration method **1400** may include determining a pelvic axis **1512** (or a reference vector) of the patient **1500** from the scanned images or the bone model. The pelvic axis **1512** may be an axis bisecting the patient's pelvis between the pubic symphysis and generally equidistant between the pair of anterior superior iliac spines on the opposing ilium. Various methods described herein or known in the art may be used to determine the pelvic axis **1512**.

(141) At step **1412** of FIG. **14A**, the registration method **1400** may include determining an angular offset between the Z-axis **1508** and the pelvic axis **1512**. The angular offset **1514** may be seen in FIG. **15C**, which will be discussed subsequently.

(142) At step **1414** of FIG. **14A**, the registration method **1400** may include determining a center of rotation of the acetabulum from the bone model. Determining the center of rotation may be done by any method described herein or any method known in the art. An example method of determining a center of rotation of a patient's acetabulum in a bone model generated from pre-operative images is described in PCT/US2017/049466, filed Aug. 30, 2017, which is hereby incorporated by reference in its entirety into the present application. Another example method of determining a center of rotation of a patient's acetabulum is via a kinematic analysis or motion analysis of the patient's femur relative to the pelvis.

(143) Reference is made to FIGS. **14B** and **15B**, which illustrate the steps of the registration method **1400** that may occur intra-operatively. At step **1416** of FIG. **14B**, the registration method **1400** may include installing a tracker on the patient's pelvis. As seen in FIG. **15B**, the patient **1500** is in an operating room, lying supine on an operating room table **1520**. The patient **1500** may also lay in a lateral decubitus position on the table **1520**, and it can reasonably be assumed that going from supine to lateral decubitus is approximately a pure rotation about the long axis of the patient **1500**. A robotic arm **1518** may be situated proximate the operating room table **1520**. As seen in the

figure, the tracker **1516** may be installed on the diseased side of the pelvis.

(144) At step **1418** of FIG. **14B**, the registration method **1400** may include positioning or aligning the patient **1500** on the operating room table **1520**, as seen in FIG. **15B**, in the same orientation as the patient was lying on the imaging table **1502**. At step **1420**, the registration method **1400** may include collecting two points **1522** on the operating room table **1520** along the long edge **1524** of the table **1520**. A vector **1526** may be calculated between the two points **1522**, at step **1422** of the method **1400**. This vector **1526** may be analogous to the Z-axis **1508** of the scanned images in that the patient **1500** is lying in a supine position in likely the same orientation on the imaging table **1502** and the operating room table **1520**. The vector **1526** may be determined and saved by the system in a common coordinate system with the positioning data for the tracker **1516**. Additionally, or alternatively, a pointer or tracked probe may be used to identify the table axis. For instance, the pointer may be positioned in space so it is aligned with the long edge **1524** of the table **1520**, and the system may capture the axis of the pointer. Additionally, or alternatively, the pointer could be aligned with the patient by, for example, placing the pointer along the midline of the patient with the pointed tip facing the patient's head. This method would also work with the patient lying on his or her side.

(145) Step **1424** of the registration method **1400** of FIG. **14B** may include defining a registration constraint that the patient's pelvis, on the operating room table **1520**, is angled relative to the vector **1526** (or the long axis of the OR table **1520**) by the angular offset **1514** as shown in FIG. **15C**. The angular offset **1514** may be defined as an angle between the Z-axis **1508** and the pelvic axis **1512**, or the angular offset **1514** may be defined as an angle between the vector **1526** on the OR table **1520** and the pelvic axis **1512** (assuming the vector **1526** and the pelvic axis **1512** are in a common coordinate system).

(146) At step **1426** of FIG. **14B**, the registration method **1400** may include determining a center of rotation of the patient's pelvis. The center of rotation **1528** is shown in FIG. **15B**. This step **1426** may be accomplished via any method known in the art, and may be accomplished via the method described in PCT/US2017/049466, filed Aug. 30, 2017, which is hereby incorporated by reference in its entirety into the present application. In the aforementioned PCT application, the method describes picking points on the patient's acetabulum and forming a sphere based on the points. From the sphere, a center of rotation can be determined.

(147) Once the center of rotation is found, at step **1426**, and the registration constraint correlating to the angular offset is found, at step **1424**, the registration transform may be employed at step **1428** of FIG. **14B**. The registration transform merges the bone model (determined from pre-operative image scans of the patient's body) with the patient's physical body on the operating room table **1520** such that the robotic arm **1518** of FIG. **15C** may be used to operate on the patient's body in a controlled manner and according to a pre-determined plan.

(148) Knowing the center of rotation of the patient's pelvis, at step **1426**, effectively locks the position of the pelvis in a coordinate system during the registration transform. Knowing only a single fixed point (center of rotation), however, means that the pelvis is unconstrained from rotating along three axes in this coordinate system. Thus, more information is needed to merge the bone model and the physical pelvis. The registration transform may use the registration constraint, of step **1428**, by locking the orientation of the patient's pelvis relative to the vector **1526** during registration. Since the vector **1526** includes coordinates in three directions (x,y,z), the orientation of the pelvis may be determined when combining the information from the vector **1526** and the center of rotation **1528**.

(149) Additionally, or alternatively, the surgical registration method may be as illustrated in FIGS. **14C** and **15D-15E**. FIG. **14C** illustrates a flowchart showing exemplary steps in a surgical registration method **1440**. FIG. **15D** illustrates an overhead view of a patient **1500** on an imaging table **1502** about to undergo an imaging event (e.g., CT, MRI). FIG. **15E** illustrates the patient **1500** on an operating room table **1520** about to undergo a surgical procedure. The registration method

1440 takes information about the pre-operative position and orientation of the patient **1500** on the imaging table **1502** and assumes certain information about the position and orientation of the patient will be consistent when the patient lies on the operating room table **1520**.

(150) Referring to FIG. **14C**, at step **1442**, image scans of the patient **1500** are generated. The image scans may be CT, X-ray, or MRI, among other imaging modalities. At step **1444**, the acetabulum center of rotation (COR) may be determined relative to the imaging coordinate system. The image device may include its own coordinate system (x, y, z) based on the translational movements of the imaging table **1502**, for example (as seen in FIG. **15D**, the table **1502** lies in the xz plane). That is, the table **1502** may translate in the z-direction in order to move the patient and table within the opening **1510** of the imaging arm **1504** of the imaging device **1506**. The table **1502** may additionally translate in the x-direction and y-direction to center the patient and table within the opening **1510** of the arm **1504**.

(151) The COR of the acetabulum may be identified by a user selecting the COR within the image scans, for example, by selecting the COR in multiple coordinate views (e.g., coronal, sagittal, axial). Additionally, or alternatively, the method **1440** may include generating a three-dimensional bone model of the patient bone either from the image scans, a statistical bone model, or generic bone model, among others. And, any method known in the art or described herein may be used to identify the COR from the bone model within the imaging coordinate system. It is noted, the COR may be a three-dimensional location (x, y, z) of one or more points relative to an origin (0, 0, 0) of the imaging coordinate system.

(152) Moving to the intra-operative portion of the method **1440**, at step **1446** of FIG. **14C**, and as also seen in FIG. **15E**, the patient **1500** is positioned on the OR table **1520**. At step **1448**, a pelvic tracking device (anatomy tracker) **1516** is attached to the patient's diseased pelvis.

(153) At step **1450**, the XYZ coordinates of the operating room table **1520** are identified. More particularly, at least three points **1530**, **1532**, **1534** are identified on the table **1520**, where two points **1530**, **1532** are located on the same side of the table (e.g., edge of the table so as to be at the same point on the x-axis), and one point **1534** is located on the opposite side of the table **1520**. The two points **1530**, **1532** may be oriented or aligned with the OR table axis or Z-axis, as shown in FIG. **15E**. All points **1530**, **1532**, and **1534** may be positioned at the same position along the y-axis. Stated differently, the three points **1530**, **1532**, **1534** may be positioned at the same height relative to a plane defined by the top of the OR table **1520**. The three points **1530**, **1532**, **1534** may be captured or logged with a tracked pointer of the system, and may be identified relative to the position of the pelvic tracking device **1516** in the intra-operative coordinate system. As an alternative to collecting points **1530**, **1532**, **1534** on the OR table **1520**, the table axes (x, y, z) may be determined by translating the table in order along the corresponding axes to ascertain the applicable vectors. In certain instances, it may be advantageous to determine the points **1530**, **1532** prior to extensive leg manipulation to ensure the patient has not moved (e.g., before femoral dislocation).

(154) At step **1452**, the XYZ coordinates of the acetabulum center point (COR) may be determined in the intra-operative coordinate system (relative to the anatomical tracker **1516**, or another point. The COR may be determined based on any method described herein or known in the art. In certain instances, the COR may be determined from a range of motion analysis. In certain instances, the COR may be determined based on a point-picking approach after the femoral head is dislocated from the acetabulum.

(155) At this point, at least the following points are identified within the intra-operative coordinate system: points **1530**, **1532**, and **1534** located on the OR table **1520**, and the COR of the patient's acetabulum. And at least the following points are identified within the pre-operative imaging coordinate system: COR of the acetabulum, as well as the coordinate axes (x, y, z), which correlate to the translational movement of the imaging table **1502**.

(156) Next, at step **1454** of FIG. **14C**, a six degree-of-freedom (DOF) transform is computed

between the imaging coordinate points and the intra-operative coordinate points so as to register the pre-operative images to the intra-operative position of the patient **1500**. In this way, a robotic arm or handheld surgical device of an autonomous or haptic-driven device may be able to identify the position and orientation of patient for performance of a surgical procedure.

(157) Additionally, or alternatively, the surgical registration method may be as illustrated in FIGS. **14D** and **15F-15G**. FIG. **14D** illustrates a flowchart showing exemplary steps in a surgical registration method **1460**. FIG. **15F** illustrates an overhead view of a patient **1500** on an imaging table **1502** about to undergo an imaging event (e.g., CT, MRI). FIG. **15G** illustrates the patient **1500** on an operating room table **1520** about to undergo a surgical procedure. The registration method **1460** takes information about the pre-operative position and orientation of the patient **1500** on the imaging table **1502** and assumes certain information about the position and orientation of the patient will be consistent when the patient lies on the operating room table **1520**.

(158) Referring to FIG. **14D**, at step **1462**, image scans of the patient **1500** are generated. The image scans may be CT, X-ray, or MRI, among other imaging modalities. At step **1464**, the acetabulum center of rotation (COR) may be determined relative to the imaging coordinate system. The imaging device may include its own coordinate system (x, y, z) based on the translational movements of the imaging table **1502**, for example (as seen in FIG. **15F**, the table **1502** lies in the xz plane). That is, the table **1502** may translate in the z-direction in order to move the patient and table within the opening **1510** of the imaging arm **1504** of the imaging device **1506**. The table **1502** may additionally translate in the x-direction and y-direction to center the patient and table within the opening **1510** of the arm **1504**.

(159) The COR of the acetabulum may be identified by a user selecting the COR within the image scans, for example, by selecting the COR in multiple coordinate views (e.g., coronal, sagittal, axial). Additionally, or alternatively, the method **1460** may include generating a three-dimensional bone model of the patient bone either from the image scans, a statistical bone model, or generic bone model, among others. And, any method known in the art or described herein may be used to identify the COR from the bone model within the imaging coordinate system. It is noted, the COR may be a three-dimensional location (x, y, z) of one or more points relative to an origin (0, 0, 0) of the imaging coordinate system.

(160) Moving to the intra-operative portion of the method **1460**, at step **1466** of FIG. **14D**, and as also seen in FIG. **15G**, the patient **1500** is positioned on the OR table **1520**. At step **1468**, a pelvic tracking device (anatomy tracker) **1516** is attached to the patient's diseased pelvis.

(161) At step **1470**, the XYZ coordinates of the operating room table **1520** are identified. More particularly, at least three points **1530**, **1532** are identified on the table **1520**, where the two points **1530**, **1532** are located on the same side of the table **1520** (e.g., edge of the table so as to be at the same point on the x-axis). The two points **1530**, **1532** may be oriented or aligned with the OR table axis or Z-axis, as shown in FIG. **15G**. The points **1530**, **1532** may be positioned at the same position along the y-axis. Stated differently, the two points **1530**, **1532** may be positioned at the same height relative to a plane defined by the top of the OR table **1520**. The two points **1530**, **1532** may be captured or logged with a tracked pointer of the system, and may be identified relative to the position of the pelvic tracking device **1516** in the intra-operative coordinate system. As an alternative to collecting points **1530**, **1532** on the OR table **1520**, the table axes (x, y, z) may be determined by translating the table in order along the corresponding axes to ascertain the applicable vectors. In certain instances, it may be advantageous to determine the points **1530**, **1532** prior to extensive leg manipulation to ensure the patient has not moved (e.g., before femoral dislocation).

(162) At step **1472**, the XYZ coordinates of the acetabulum center point (COR) may be determined in the intra-operative coordinate system (relative to the anatomical tracker **1516**, or another point). The COR may be determined based on any method described herein or known in the art. In certain instances, the COR may be determined from a range of motion analysis. In certain instances, the COR may be determined based on a point-picking approach after the femoral head is dislocated

from the acetabulum.

(163) At this point, at least the following points are identified within the intra-operative coordinate system: points **1530**, **1532** located on the OR table **1520**, and the COR of the patient's acetabulum. And at least the following points are identified within the pre-operative imaging coordinate system: COR of the acetabulum, as well as the coordinate axes (x, y, z), which correlate to the translational movement of the imaging table **1502**.

(164) Next, at step **1474** of FIG. **14D**, a six degree-of-freedom (DOF) transform is computed between the imaging coordinate points and the intra-operative coordinate points so as to register the pre-operative images to the intra-operative position of the patient **1500**. In this way, a robotic arm or handheld surgical device of an autonomous or haptic-driven device may be able to identify the position and orientation of patient for performance of a surgical procedure.

(165) D. Registering of Robotic Arm

(166) Referring back to FIG. **5**, after registering the pelvis at step **S6**, the robotic arm **30** may be registered at step **S7**. In this step, the robotic arm **30** is registered to correlate the pose of the robotic arm **30** (physical space) with the navigation system **7** (image space). The robotic arm **30** can be registered, for example, as described in U.S. patent application Ser. No. 11/357,197 (Pub. No. US 2006/0142657), filed Feb. 21, 2006, and hereby incorporated by reference herein in its entirety.

(167) E. Preparation of the Acetabulum and Performance of the Surgical Procedure

(168) In operation, the surgeon can use the robotic arm **30** of FIG. **3B** to facilitate a joint replacement procedure, such as reaming bone and implanting an acetabular cup for a total hip replacement or hip resurfacing procedure. As explained above, the robotic arm **30** includes a surgical tool configured to be coupled to a cutting element (for reaming) and to engage a prosthetic component (for impacting). For example, as seen in FIG. **3B**, for reaming, the end effector **40** can couple to the operating member **100**, which couples to a cutting element. Similarly, for impacting, the end effector **40** can couple to another operating member, which engages the prosthetic component. The robotic arm **30** can be used to ensure proper positioning during reaming and impacting.

(169) In step **S8** of FIG. **5**, the surgeon resurfaces the acetabulum **22** using a reamer, such as the operating member **100**, coupled to the robotic arm **30** of FIG. **3B**. As described above in connection with the operating member **100**, the surgeon couples the appropriate operating member (e.g., a straight or offset reamer) to the end effector **40**, connects the cutting element to the received operating member, and manually manipulates the robotic arm **30** to ream the acetabulum **22**. During reaming, the robotic arm **30** provides haptic (force feedback) guidance to the surgeon. The haptic guidance constrains the surgeon's ability to manually move the surgical tool to ensure that the actual bone cuts correspond in shape and location to planned bone cuts (i.e., cuts consistent with the surgical plan). In certain instances, an autonomous or hand held system may work within a defined virtual boundary without haptic feedback or guidance.

(170) In step **S9** of FIG. **5**, the surgeon verifies that the registration (i.e., the geometric relationship) between the acetabular tracking array and the pelvis **12** is still valid by contacting the pelvis checkpoint with a tracked probe as described, for example, in U.S. patent application Ser. No. 11/750,807 (Pub. No. US 2008/0004633), filed May 18, 2007, and hereby incorporated by reference herein in its entirety. If registration has degraded (e.g., because the acetabular tracking array was bumped during reaming), the pelvis **12** is re-registered. Registration verification can be performed any time the surgeon wants to check the integrity of the acetabular registration.

(171) In step **S10** of FIG. **5**, the prosthetic component **316** is implanted on the reamed acetabulum **22** using an impactor tool. In a manner identical to that described above in connection with step **S8** (reaming), during the impaction step **S10**, the display device **9** can show the planned pose **500**, the activation region **510**, the representations **512**, **514** of the anatomy, and a representation of the surgical tool, as seen in FIG. **4**. Also as described above in connection with step **S8**, if the surgeon moves the end effector **40** to override the haptic feedback, the controller can initiate automatic

control of the surgical tool to substantially align at least one aspect of the actual pose with the corresponding desired aspect of the target pose.

(172) In step **S11** of FIG. **5**, the surgeon installs the femoral component on the femur **14**, and in step **S12**, the surgeon determines leg length and femoral offset. At any time during the surgical procedure, the display device **9** can show data related to progress and/or outcome. For example, after reaming in step **S8** and/or impacting in step **S10**, data relating to the actual position of the reamed acetabulum **22** (or the implanted acetabular cup) can include, for example, numerical data representing error between the actual and planned locations in the three orthogonal planes of the patient's anatomy (i.e., medial/lateral, superior/inferior, and anterior/posterior).

V. Tools and Methods for Bone Registration of Femur, Pelvis, and Vertebrae, Among Other Bones

(173) Point-picking based bone registration is one method of registration in navigated and robotic assisted orthopedic surgeries. During a surgical procedure, an incision is made at the surgical site (e.g., hip, knee). A localization pointer or tracked probe is utilized to pick a digitized point-cloud (a set of data points in a coordinate system representing a surface contour) on boney areas of the patient's body that are accessible through the incision. By using point-pair and iterative closest point (ICP) algorithms, the patient point-cloud data in "tracker space" (coordinate system with position data corresponding to trackers on the patient body and the point-cloud of patient collected points) is transformed to the three-dimensional bone model of the patient's bone formed from segmented medical images, or otherwise. An accurate registration transform is determined as the minimum root-mean-square of the point-cloud fitting.

(174) In the context of point-picking based registration (femoral, pelvic, or otherwise), intra-operatively picking points on the bone surface with a probe generally requires the surgeon to have access to the bones through the initial incision at the surgical site. Due to small incision areas, especially in minimally invasive surgeries, it can be difficult to ensure six degrees of freedom accuracy in registration when relying on point-cloud data collected only within the surgical incision. To increase accuracy of such registrations, points can be added to the point-cloud that are far from the surgical site. For example, in a total hip arthroplasty procedure, a surgeon may capture points on the patient's acetabulum, and additionally capture points on the iliac crest surface of the patient's ilium to increase registration accuracy. Still in the context of a total hip arthroplasty, a surgeon may pick points on the proximal femur (e.g., femoral head), and may additionally capture points on a distal or mid-distal femur surface to increase the registration accuracy. The iliac crest and distal femur are, however, not within the initial surgical incision.

(175) In order to pick such distant points on the iliac crest and distal femur (i.e., that are not within the initial surgical incision), the surgeon may need to make an additional incision (e.g., stab incision) remote from the initial incision for the sole purpose of contacting a tracked probe or localization pointer against the patient's bone(s). Making additional incisions into the patient's body may not be ideal as there is an increased chance of infection, pain, scarring, and time associated with such a method.

(176) Described herein in reference to FIGS. **16A-16C** are registration tools and methods for use in zones of the patient's body that are remote from the surgical site (i.e., outside the surgical incision) and that do not involve additional incisions in the patient's skin. As seen in FIG. **16A**, needles **1** of varying lengths and diameters, such as an acupuncture needle or a syringe needle, may be used to digitize points on hard bone surface without incision through the patient's skin. The needle **1** diameter may be small enough to easily penetrate patient skin, the soft tissue, and the cartilage of the patient with no side effect on patient satisfaction. Using needles **1**, bone registration points can be picked in anatomic regions which are normally not accessible through in-wound point picking method, especially in MIS.

(177) As seen in FIG. **16B**, which is an anterior view of a femur **6** in accordance with the present disclosure, one or more needles **1a** may be inserted into soft tissue **7** through one of a plurality of holes of a needle fixture or template **2**. The needle fixture **2** may guide the needles **1a** through the

skin, and the needles **1a** may stop at the hard bone surface of the femur **6**. A passive or active localization marker may be attached to the needles **1a** so as to navigate the position of the needle-top via one or more cameras **10** (e.g., optical camera). A needle tracker **3a** may be coupled to the needle fixture **2**. However, a needle tracker **3a** may not be needed if the needle tips are tracked. The fixture **2** may have multiple functions, including: (1) compressing the soft tissue; (2) guiding insertion of the needles **1a**; and (3) measuring the position of the needle tip relative to the needle tracker **3a** via a transform **8a**.

(178) Still referring to FIG. **16B**, a bone tracker **4** may be rigidly attached to a hard bone surface of the femur **6** by a clamp and bone pin **5**. A needle tip position in bone tracker **4** space may be determined through a transform **9a**. The needle fixture **2**, together with needle tracker **3a**, can be freely moved to different anatomical locations of the bone to digitize multiple points on bone surface **6**, and add those points to the point-cloud. The camera **10** may track the position of the bone tracker **4** and the needle tracker **3a**.

(179) As seen in FIG. **16C**, which is an anterior view of a femur **6** in accordance with the present disclosure, a proximal end of a needle **1b** is attached to a mechanical tracker **3b** so as to navigate the position of needle tip (distal end of needle) in mechanical tracker **3b** space through transform **8b**. The mechanical tracker **3b** may be attached to the bone clamp **5** or another reference position. The mechanical tracker **3b** may be registered to an optical tracker **4** by transform **9b**. Mechanical tracker **3b** may indicate the position of each joint—such as via encoders, or fiber optic trackers. A camera (e.g., optical camera) may track the movement of the optical tracker **4**. And, a needle tip position in bone tracker **4** space is further determined through transform **9b**. The needle fixture **2** and tip-center point (TCP) of mechanical tracker **3b** can be freely moved to different anatomical locations of the bone to digitize multiple points on the bone surfaces **6**, and add those points to the point-cloud.

(180) In certain instances, a registration system **1700** may be utilized as seen in FIGS. **17A-17C**. FIG. **17A** shows an anterior view of a femur **4** being registered with the registration system **1700** in a total hip arthroplasty context, FIG. **17B** shows an anterior view of the femur **4** being registered with the registration system **1700** in a total knee arthroplasty context, and FIG. **17C** shows an anterior view of a tibia **5** being registered with the registration system **1700** in a total knee arthroplasty context.

(181) As seen in FIG. **17A**, the proximal end of the femur **4** may be subject to point-picking via a tracked pointer through the incision in the patient at the surgical site (e.g., hip region). In the case of a total hip arthroplasty, the femoral head may be exposed and easily accessible for point-picking via the tracked pointer for developing a point-cloud of data to be used in the registration process. To increase accuracy of the registration transform, the registration system **1700** including a needle template **2** including a plurality of through-holes, a needle tracker **3**, and a tracking needle **1a** are used on the shaft of the femur **4** approximately midway between the proximal femoral head and the distal femoral condyles. The needle template **2** may be pressed against the patient's skin, and the needle template **2** may be used to guide one or more needles **1a** into the patient's skin until it contacts the bone surface of the femur. The optical camera (not shown) may sense the position of the needle template **2**, and the corresponding position of the needle within one of the through-holes of the template **2**.

(182) Thus, when the registration transform is ran, the system may use point-cloud data associated with surface points on the femoral head and on a mid-distal femoral bone surface to increase the accuracy of the process.

(183) As seen in FIG. **17B**, the distal end of the femur **4** may be subject to point-picking via a tracked pointer through the incision in the patient at the surgical site (e.g., knee region). In the case of a total knee arthroplasty, the femoral condyles may be exposed and easily accessible for point-picking via the tracked pointer for developing a point-cloud of data to be used in the registration process. To increase accuracy of the registration transform, the registration system **1700** including a

needle template **2** including a plurality of through-holes, a needle tracker **3**, and a tracking needle **1a** are used on the shaft of the femur **4** approximately midway between the proximal femoral head and the distal femoral condyles. The needle template **2** may be pressed against the patient's skin, and the needle template **2** may be used to guide the needle **1a** into the patient's skin until it contacts the bone surface of the femur. The optical camera (not shown) may sense the position of the needle template **2**, and the corresponding position of the needle within one of the through-holes of the template **2**.

(184) Thus, when the registration transform is ran, the system may use point-cloud data associated with surface points on the femoral condyles and on a mid-distal femoral bone surface to increase the accuracy of the process.

(185) As seen in FIG. **17C**, the proximal end of the tibia **5** may be subject to point-picking via a tracked pointer through the incision in the patient at the surgical site (e.g., knee region). In the case of a total knee arthroplasty, the proximal tibia (e.g., tibial plateau) may be exposed and easily accessible for point-picking via the tracked pointer for developing a point-cloud of data to be used in the registration process. To increase accuracy of the registration transform, the registration system **1700** including a needle template **2** including a plurality of through-holes, a needle tracker **3**, and a tracking needle **1a** are used on the shaft of the tibia **5** approximately midway between the proximal tibia and the distal tibia. The needle template **2** may be pressed against the patient's skin, and the needle template **2** may be used to guide the needle **1a** into the patient's skin until it contacts the bone surface of the tibia. The optical camera (not shown) may sense the position of the needle template **2**, and the corresponding position of the needle within one of the through-holes of the template **2**.

(186) Thus, when the registration transform is ran, the system may use point-cloud data associated with surface points on the proximal tibia and on a mid-distal tibial bone surface to increase the accuracy of the process.

(187) The registration system **1700** described with reference to FIGS. **17A-17C** may be employed on the ilium, as seen in FIG. **18**. More particularly, the acetabular rim **2** and acetabular articular surface **1** may be accessible in a hip arthroplasty procedure, but, the iliac crest **4**, and an area just inferior to the lip of the iliac crest (i.e., the portion of the dorsus ossis ilium between the iliac crest **4** and the anterior gluteal line) is generally not within the surgical incision for conventional hip arthroplasty procedures. As seen in FIG. **18**, the articular surface **1** and the rim **2** of the acetabular may be point-picked via a tracked pointer through the incision in the hip region. From the articular surface **1** and the rim **2**, the system may determine a center of rotation COR by, for example, the method described in PCT/US2017/049466, filed Aug. 30, 2017, which is hereby incorporated by reference in its entirety into the present application. To increase the accuracy of the registration transform, the registration system **1700** including a needle template **2** including a plurality of through-holes, a needle tracker **3**, and a tracking needle **1a** are used on the iliac crest proximate the anterior superior iliac spine. The needle template **2** may be pressed against the patient's skin, and the needle template **2** may be used to guide the needle **1a** into the patient's skin until it contacts the bone surface of the ilium. The optical camera (not shown) may sense the position of the needle template **2**, and the corresponding position of the needle within one of the through-holes of the template **2**.

(188) Thus, when the registration transform is ran, the system may use point-cloud data associated with surface points on the acetabular region of the ilium and on the iliac crest surface to increase the accuracy of the process.

(189) The registration system **1700** may additionally or alternatively be used on other parts of the patient's body that may be segmented, such as the spine (L1, L2, L3, L4, L5). As seen in FIG. **19A**, which is a side view of an ilium and a spinal column, a tracking array may be positioned on the patient's ilium. Additionally, the registration system **1700** including a needle template **2** including a plurality of through-holes, a needle tracker **3**, and a tracking needle **1a** may be used on the boney

portions of the posterior aspect of the vertebrae of the spine. The needle template **2** may be pressed against the patient's skin, and the needle template **2** may be used to guide the needle **1a** into the patient's skin until it contacts the bone surface of the vertebrae. The optical camera (not shown) may sense the position of the needle template **2**, and the corresponding position of the needle within one of the through-holes of the template **2**.

(190) Thus, when the registration transform is run, the system may use point-cloud data associated with the vertebrae, along with another registration area, to increase the accuracy of the process. The method described herein may be utilized on any bone, and is not limited to bones of the legs and vertebrae. The needle-based registration method may be used on bones of the arms, hands, feet, upper body, and head, without limitation.

(191) Reference is made to FIGS. **20A-20D**, which depict, respectively, an axial cross-section image of a vertebra **2000** and a bone anchor **2002** positioned therein, an axial cross-section image of a vertebra **2000** with a rotating burr **2004** positioned partially within the vertebra **2000**, another axial cross-section image of a vertebra **2000** with a rotating burr **2004** positioned partially within the vertebra **2000**, and an axial cross-section image of a burr **2004** extending through a vertebra **2000** to a far inner wall of the cortical bone **2006**.

(192) Accuracy in spinal registration can be challenging. Conventionally, a tracker device is placed in the pelvis of the patient so the vertebrae (which is the subject of a surgical procedure) could be several non-rigid joints away from the tracker. Thus, when the patient is positioned in a prone position (i.e., on the stomach), among other positions, there may be a significant soft tissue pushing against the vertebrae that could alter the position of the vertebrae. Additionally, working on adjacent vertebral segments may move the spine slightly.

(193) A goal of the tools, systems, and methods described subsequently is to confirm and improve registration by identifying contact with the internal cortical bone of the vertebra **2000** after initial penetration of the outer surface of the vertebra **2000**. To that end, FIG. **20A** shows an axial cross-section image of a vertebra **2000** with a bone anchor **2002** positioned therein. As seen in the figure, a shank **2008** of the bone anchor **2002** extends through a pedicle **2010** of the vertebra **2000** while avoiding contact with the spinal cord **2012**. The vertebra **2000** includes cortical bone **2006**

(compact bone) on outer portions or outer shell including a cortical rim **2014** surrounding the vertebral body, and cancellous bone **2016** (spongy or trabecular bone) interior of the cortical bone **2006**. The cortical bone **2006** is harder and denser than the cancellous bone **2016**, which is porous, weaker, and easier to fracture than cortical bone **2006**. Cancellous bone **2016** makes up the shafts of long bones (e.g., femur, tibia). Cortical bone **2006** surrounds and protects the spinal cord **2012**.

(194) When inserting a bone anchor **2002** into a vertebra **2000**, as seen in FIG. **20A**, the surgeon attempts to position the anchor **2002** as shown in the figure where the shank **2008** remains within the vertebra **2000** (i.e., does not exit either side of the cortical bone **2006**). That is, the shank **2008** remains within the cancellous bone **2016** once it initially penetrates through the cortical bone **2006**. Conventional ways to ensure placement of the shank **2008** within the interior of the vertebra **2000** is for a surgeon to drill through the outer cortical layer of the vertebra **2000** in the vicinity of the pedicle **2010** and attempt to identify an inner surface of the cortical surface or wall by the “feel” of the tip of the drill bit contacting the inner cortical surface. Once the surgeon senses contact with the inner wall of the cortical bone **2006**, the surgeon knows not to extend the drill any farther.

(195) During a registration procedure, once cortical contact is achieved, the point of contact between the bone and the burr **2004** may be used to update the registration of the bone position. The surgeon may also update the screw insertion plan if needed. Registration improvement may be optimized by the load cell **2020** detecting the direction of the contact of the burr **2004** with the bone. The system may identify an error by comparing the contact position with the anticipated contact based upon the surgical navigation system tracking the position of the burr **2004** with respect to the registered position of the patient. If there is a difference, the registration could be updated using the contact point as an internal registration point.

(196) FIGS. 20B-20D illustrate a system and method of registering a vertebra **2000** using a burr **2004** of an end effector **2018** of surgical robotic system (not shown in FIGS. 20B-20D, but as shown and described in this application). Generally, the burr **2004** may be used to create a pathway into the pedicle **2010**. Once inside the bone, the burr **2004** may be shut off so as to cease rotating. The surgeon may advance the burr **2004** through the cancellous bone **2016**. A load cell **2020** on the end effector **2018** would be able to indicate if the burr **2004** contacts cortical bone **2006**. The load cell **2020** may be configured so as to identify and distinguish cancellous bone **2016** from cortical bone **2006** as each bone type has a different stiffness. The load cell **2020** may audibly or otherwise (visually, haptic) signal the burr's **2004** contact with the cortical bone **2006**. With a haptic setting, the surgical robotic system may prevent the surgeon from extending the burr **2004** further in a direction of the cortical bone **2006** once a certain stiffness value is reached.

(197) As seen in FIG. 20B, the surgeon may insert the burr **2004** into the pedicle **2010** into the smallest neck region between the cortical bone **2006** around the spinal cord **2012** and the cortical canal **2022** around the exterior of the vertebra **2000**. The burr **2004** may be moved from side-to-side (as indicated by the arrows in FIG. 20B) to intentionally contact the cortical walls **2006** and register the internal features thereof. The burr **2004** may be pivoted about the entry point in order to minimize any disruption of screw thread purchase areas.

(198) As seen in FIG. 20C, the surgeon may insert the burr **2004** into the pedicle **2010** into the smallest neck region between the cortical bone **2006** around the spinal cord **2012** and the cortical con around the exterior of the vertebra **2000**. The burr **2004** may be moved (as indicated by the arrows in FIG. 20C) over the internal surface of the cortical canal **2022** to map out or create a registration surface thereon. The identified surface on the cortical con may then be compared with the model to improve or adjust registration.

(199) As seen in FIG. 20D, the surgeon may insert the burr **2004** through the pedicle **2010** and through the cancellous bone **2016** until the burr **2004** contacts a far inner surface of the cortical rim **2014**. If there were no contacts with the burr **2004** against the cortical bone **2006** of the neck region of the pedicle **2012**, contact with the inner surface of the cortical rim **2014** would be confirmed. When the load cell **2020** detects the far cortex, then the system may indicate such contact and the registration may be updated or improved accordingly.

(200) In addition to the system detecting when the burr **2004** contacts the cortical bone **2006**, the system may also detect potential breaches of the cortical bone **2006**. For example, once the burr **2004** contacts the cortical bone **2006**, as determined by the load experienced by the load cell **2020** of the end effector **2018**, any loads experienced at that boundary wall that vary from the previous loads (e.g., a sudden decrease in resistance/stiffness indicating a break through of the cortical wall) may be considered potential breaches of the cortical surface **2006**.

(201) In certain instances, a system and method of surgical registration may be as follows. A system may register patient data gathered intra-operatively of a vertebra **2000** with a computer model of the vertebra in a coordinate system. The vertebra **2000** may include a cortical bone shell **2006** having an outer surface and an inner surface, and cancellous bone interior **2016** of the cortical bone shell **2006**. The vertebra **2000** may define a spinal cord canal **2022** bounded by the cortical bone shell **2006**. In certain instances, the system may include a surgical navigation system, and at least one computing device. The surgical navigation system may include a tracking device and at least one tool **2018** that is tracked by the tracking device. The at least one tool may include an end effector **2018** having a cutting element **2004** at a distal end thereof, and a load cell **2018** to sense a load on the cutting element **2004**. The computing device may be in communication with the surgical navigation system. And the at least one computing device may store the computer model of the vertebra in the coordinate system.

(202) In certain instances, the at least one computing device may receive load data associated with a load experienced by the cutting element **2004** at the distal end of the end effector **2018** when the cutting element **2004** contacts the cortical bone shell **2006** and the cancellous bone **2016**. The at

least one computing device may also identify, based on the load data, when the cutting element **2004** contacts the inner surface of the cortical bone shell **2006**. The at least one computing device may also receive a point-cloud of data associated with the vertebra **2000**. The point-cloud of data may include coordinate locations on the inner surface of the cortical bone shell **2006** that are collected via the cutting element **2004**. The at least one computing device may also run or update a transform to register the point-cloud of data associated with the vertebra **2000** to the computer model of the vertebra in a common coordinate system.

VI. Example Computing System

(203) Referring to FIG. **21**, a detailed description of an example computing system **3000** having one or more computing units that may implement various systems and methods discussed herein is provided. The computing system **3000** may be applicable to any of the computers or systems utilized in the preoperative or intra-operative planning of the arthroplasty procedure (e.g., registration), and other computing or network devices. It will be appreciated that specific implementations of these devices may be of differing possible specific computing architectures not all of which are specifically discussed herein but will be understood by those of ordinary skill in the art.

(204) The computer system **3000** may be a computing system that is capable of executing a computer program product to execute a computer process. Data and program files may be input to the computer system **3000**, which reads the files and executes the programs therein. Some of the elements of the computer system **3000** are shown in FIG. **21**, including one or more hardware processors **3002**, one or more data storage devices **3004**, one or more memory devices **3008**, and/or one or more ports **3008-3010**. Additionally, other elements that will be recognized by those skilled in the art may be included in the computing system **3000** but are not explicitly depicted in FIG. **21** or discussed further herein. Various elements of the computer system **3000** may communicate with one another by way of one or more communication buses, point-to-point communication paths, or other communication means not explicitly depicted in FIG. **21**.

(205) The processor **3002** may include, for example, a central processing unit (CPU), a microprocessor, a microcontroller, a digital signal processor (DSP), and/or one or more internal levels of cache. There may be one or more processors **3002**, such that the processor **3002** comprises a single central-processing unit, or a plurality of processing units capable of executing instructions and performing operations in parallel with each other, commonly referred to as a parallel processing environment.

(206) The computer system **3000** may be a conventional computer, a distributed computer, or any other type of computer, such as one or more external computers made available via a cloud computing architecture. The presently described technology is optionally implemented in software stored on the data stored device(s) **3004**, stored on the memory device(s) **3006**, and/or communicated via one or more of the ports **3008-3010**, thereby transforming the computer system **3000** in FIG. **21** to a special purpose machine for implementing the operations described herein. Examples of the computer system **3000** include personal computers, terminals, workstations, mobile phones, tablets, laptops, personal computers, multimedia consoles, gaming consoles, set top boxes, and the like.

(207) The one or more data storage devices **3004** may include any non-volatile data storage device capable of storing data generated or employed within the computing system **3000**, such as computer executable instructions for performing a computer process, which may include instructions of both application programs and an operating system (OS) that manages the various components of the computing system **3000**. The data storage devices **3004** may include, without limitation, magnetic disk drives, optical disk drives, solid state drives (SSDs), flash drives, and the like. The data storage devices **3004** may include removable data storage media, non-removable data storage media, and/or external storage devices made available via a wired or wireless network architecture with such computer program products, including one or more database management

products, web server products, application server products, and/or other additional software components. Examples of removable data storage media include Compact Disc Read-Only Memory (CD-ROM), Digital Versatile Disc Read-Only Memory (DVD-ROM), magneto-optical disks, flash drives, and the like. Examples of non-removable data storage media include internal magnetic hard disks, SSDs, and the like. The one or more memory devices **3006** may include volatile memory (e.g., dynamic random access memory (DRAM), static random access memory (SRAM), etc.) and/or non-volatile memory (e.g., read-only memory (ROM), flash memory, etc.). (208) Computer program products containing mechanisms to effectuate the systems and methods in accordance with the presently described technology may reside in the data storage devices **3004** and/or the memory devices **3006**, which may be referred to as machine-readable media. It will be appreciated that machine-readable media may include any tangible non-transitory medium that is capable of storing or encoding instructions to perform any one or more of the operations of the present disclosure for execution by a machine or that is capable of storing or encoding data structures and/or modules utilized by or associated with such instructions. Machine-readable media may include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more executable instructions or data structures. (209) In some implementations, the computer system **3000** includes one or more ports, such as an input/output (I/O) port **3008** and a communication port **3010**, for communicating with other computing, network, navigation, or robotic devices. It will be appreciated that the ports **3008-3010** may be combined or separate and that more or fewer ports may be included in the computer system **3000**.

(210) The I/O port **3008** may be connected to an I/O device, or other device, by which information is input to or output from the computing system **3000**. Such I/O devices may include, without limitation, one or more input devices, or output devices, such as, for example, robotic arms, and navigation and tracking systems.

(211) In one implementation, the input devices convert a human-generated signal, such as, human voice, physical movement, physical touch or pressure, and/or the like, into electrical signals as input data into the computing system **3000** via the I/O port **3008**. Similarly, the output devices may convert electrical signals received from computing system **3000** via the I/O port **3008** into signals that may be sensed as output by a human, such as sound, light, and/or touch. The input device may be an alphanumeric input device, including alphanumeric and other keys for communicating information and/or command selections to the processor **3002** via the I/O port **3008**. The input device may be another type of user input device including, but not limited to: direction and selection control devices, such as a mouse, a trackball, cursor direction keys, a joystick, and/or a wheel; one or more sensors, such as a camera, a microphone, a positional sensor, an orientation sensor, a gravitational sensor, an inertial sensor, and/or an accelerometer; and/or a touch-sensitive display screen ("touchscreen"), and/or tracking/probe devices associated with the navigation and tracking systems. The output devices may include, without limitation, a display, a touchscreen, a speaker, a tactile and/or haptic output device, and/or the like. In some implementations, the input device and the output device may be the same device, for example, in the case of a touchscreen.

(212) In one implementation, a communication port **3010** is connected to a network by way of which the computer system **3000** may receive network data useful in executing the methods and systems set out herein as well as transmitting information and network configuration changes determined thereby. Stated differently, the communication port **3010** connects the computer system **3000** to one or more communication interface devices configured to transmit and/or receive information between the computing system **3000** and other devices by way of one or more wired or wireless communication networks or connections. Examples of such networks or connections include, without limitation, Universal Serial Bus (USB), Ethernet, Wi-Fi, Bluetooth®, Near Field Communication (NFC), Long-Term Evolution (LTE), and so on. One or more such communication interface devices may be utilized via the communication port **3010** to communicate one or more

other machines, either directly over a point-to-point communication path, over a wide area network (WAN) (e.g., the Internet), over a local area network (LAN), over a cellular (e.g., third generation (3G) or fourth generation (4G)) network, or over another communication means. Further, the communication port **3010** may communicate with an antenna or other link for electromagnetic signal transmission and/or reception.

(213) In an example implementation, patient data, bone models (e.g., generic, patient specific), transformation software, tracking and navigation software, registration software, and other software and other modules and services may be embodied by instructions stored on the data storage devices **3004** and/or the memory devices **3006** and executed by the processor **3002**. The computer system **3000** may be integrated with or otherwise form part of the surgical system **100**. The system may be configured for registering patient data gathered intra-operatively from a first bone with a computer model of the first bone in a common coordinate system. The first bone may joint a second bone to form a joint such as, for example, a hip joint, a knee joint, a shoulder joint, an elbow joint, or ankle joint, among others. The system may include a surgical navigations system including a tracking device and a tool (e.g., navigation probe, end of a surgical robotic arm) to be tracked in its movement by the tracking device. Additionally, the system may include a computing device (one or more) in communication with the navigation system. The computing device may perform the following steps: 1) receive first data points of the patient data from first intra-operatively collected points on an articular surface of the concave portion of the bone. The first data points may be collected using the at least one tool. The first data points may correspond in location to a first articular region on the computer model. 2) receive a second data point from a second intra-operatively collected point on the first bone. The second data point may be collected using the at least one tool. The second data point may correspond in location to a second virtual data point on the computer model. 3) determine an intra-operative center of rotation from the first data points. The intra-operative center of rotation may correspond to a physical center of rotation of the second bone relative to the first bone. 4) compare a first distance between the virtual center of rotation and the second virtual data point and a second distance between the intra-operative center of rotation and the second data point. And, 5) run a transformation with the patient data and the computer model so as to have them correspond with respect to position and orientation.

(214) The system set forth in FIG. **21** is but one possible example of a computer system that may employ or be configured in accordance with aspects of the present disclosure. It will be appreciated that other non-transitory tangible computer-readable storage media storing computer-executable instructions for implementing the presently disclosed technology on a computing system may be utilized.

(215) In the present disclosure, the methods disclosed herein, for example, those shown in FIG. **5**, among others, may be implemented as sets of instructions or software readable by a device. Further, it is understood that the specific order or hierarchy of steps in the methods disclosed are instances of example approaches. Based upon design preferences, it is understood that the specific order or hierarchy of steps in the method can be rearranged while remaining within the disclosed subject matter. The accompanying method claims present elements of the various steps in a sample order, and are not necessarily meant to be limited to the specific order or hierarchy presented.

(216) The described disclosure including any of the methods described herein may be provided as a computer program product, software, or computerized method that may include a non-transitory machine-readable medium having stored thereon instructions, which may be used to program a computer system (or other electronic devices) to perform a process according to the present disclosure. A machine-readable medium includes any mechanism for storing information in a form (e.g., software, processing application) readable by a machine (e.g., a computer). The machine-readable medium may include, but is not limited to, magnetic storage medium, optical storage medium; magneto-optical storage medium, read only memory (ROM); random access memory (RAM); erasable programmable memory (e.g., EPROM and EEPROM); flash memory; or other

types of medium suitable for storing electronic instructions.

(217) While the present disclosure has been described with reference to various implementations, it will be understood that these implementations are illustrative and that the scope of the present disclosure is not limited to them. Many variations, modifications, additions, and improvements are possible. More generally, embodiments in accordance with the present disclosure have been described in the context of particular implementations. Functionality may be separated or combined in blocks differently in various embodiments of the disclosure or described with different terminology. These and other variations, modifications, additions, and improvements may fall within the scope of the disclosure as defined in the claims that follow. For example, while the description discusses methods involving the hip, the disclosure is similarly applicable to other joints including the shoulder, ankle, and spine, among others.

(218) In general, while the embodiments described herein have been described with reference to particular embodiments, modifications can be made thereto without departing from the spirit and scope of the disclosure. Note also that the term “including” as used herein is intended to be inclusive, i.e. “including but not limited to.”

(219) The construction and arrangement of the systems and methods as shown in the various exemplary embodiments are illustrative only. Although only a few embodiments have been described in detail in this disclosure, many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.). For example, the position of elements may be reversed or otherwise varied and the nature or number of discrete elements or positions may be altered or varied. Accordingly, all such modifications are intended to be included within the scope of the present disclosure. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions and arrangement of the exemplary embodiments without departing from the scope of the present disclosure.

Claims

1. A system for registering patient data gathered intra-operatively of a vertebra with a computer model of the vertebra in a coordinate system, the vertebra comprising a cortical bone shell, the cortical bone shell having an outer surface and an inner surface, and a cancellous bone interior, the system comprising: a) a surgical navigation system comprising a tracking device and at least one tool configured to be tracked in its movement by the tracking device, the at least one tool comprising an end effector having a cutting element at a distal end thereof, and a load cell configured to sense a load on the cutting element; and b) at least one computing device in communication with the surgical navigation system, the at least one computing device storing the computer model of the vertebra in the coordinate system, the at least one computing device: i) receiving load data associated with the load on the cutting element at the distal end of the end effector when the cutting element is within the cancellous bone interior of the cortical bone shell; ii) identifying, based on the load data, when the cutting element contacts the inner surface of the cortical bone shell; iii) receiving a point-cloud of data associated with the vertebra, the point-cloud of data comprising coordinate locations on the inner surface of the cortical bone shell, the point-cloud of data being collected via the cutting element at the distal end of the end effector; and iv) at least one of running or updating a transform to register the point-cloud of data associated with the vertebra to the computer model of the vertebra in a common coordinate system.
2. The system of claim 1, wherein the surgical navigation system is configured to provide a signal based on the load data.
3. The system of claim 2, wherein the signal comprises one or more of an audible signal, a visual

signal, and a haptic signal.

4. The system of claim 1, wherein the at least one computing device is further configured for identifying, based on the load data, a potential breach of the cortical bone shell.

5. The system of claim 4, wherein the potential breach is identified when the load on the cutting element along the inner surface of the cortical bone shell varies from previous loads along the inner surface of the cortical bone shell.

6. The system of claim 1, wherein the cutting element is configured to cut the outer surface of the cortical bone shell.

7. The system of claim 6, wherein the at least one computing device is further configured for receiving additional load data associated with the load on the cutting element when the cutting element is cutting the outer surface of the cortical bone shell.

8. The system of claim 7, wherein the at least one computing device is further configured for identifying, based on the additional load data, when the cutting element contacts the cancellous bone interior.

9. The system of claim 8, wherein the at least one computing device is further configured for shutting off the cutting element when the cutting element contacts the cancellous bone interior.

10. The system of claim 1, wherein the at least one computing device is further configured for receiving additional load data associated with the load on the cutting element.

11. The system of claim 10, wherein the at least one computing device is further configured for identifying, based on the additional load data, a stiffness of a bone in contact with the cutting element.

12. The system of claim 11, wherein the at least one computing device is further configured for determining when the stiffness of the bone in contact with the cutting element meets or exceeds a threshold stiffness.

13. The system of claim 1, wherein the point-cloud of data is collected by the cutting element along a path.

14. The system of claim 13, wherein the path includes a side-to-side path within the cortical bone shell, a linear path within the cortical bone shell, and/or a pivoting path within the cortical bone shell.

15. The system of claim 10, wherein the cutting element comprises a burr.

16. The system of claim 1, wherein the load data is collected while the cutting element is in operation.

17. The system of claim 1, wherein the load data is collected while the cutting element is not in operation.
