

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403207
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kim; Jong Rack et al.

Sterilizing apparatus

Abstract

A sterilizing apparatus is disclosed. A sterilizing apparatus according to one embodiment comprises: a cover main body unit having an accommodation space formed therein so as to accommodate a device to be sterilized, wherein the accommodation space is open toward a bottom surface on which the device to be sterilized is disposed; an ultraviolet light emitting diode provided on a surface facing the bottom surface of the cover main body unit, and turned on so as to emit ultraviolet rays toward the accommodation space; a power supply unit for supplying power to the ultraviolet light emitting diode so as to turn on the ultraviolet light emitting diode; and a control unit for controlling an operation of the power supply unit.

Inventors: Kim; Jong Rack (Ansan-si, KR), Jung; Hee Cheul (Ansan-si, KR), Jung; Sang Wook (Ansan-si, KR), Bae; Hee Ho (Ansan-si, KR), Kim; Seong Heon (Ansan-si, KR)

Applicant: SEOUL VIOSYS CO., LTD. (Ansan-si, KR)

Family ID: 57585256

Assignee: SEOUL VIOSYS CO., LTD. (Ansan-si, KR)

Appl. No.: 18/615576

Filed: March 25, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240261451 A1	Aug. 08, 2024

Foreign Application Priority Data

KR	10-2015-0091036	Jun. 26, 2015
KR	10-2015-0093744	Jun. 30, 2015
KR	10-2016-0025592	Mar. 03, 2016

Related U.S. Application Data

continuation parent-doc US 17243290 20210428 US 11938239 child-doc US 18615576
continuation parent-doc US 16734929 20200106 US 11027033 20210608 child-doc US 17243290
continuation parent-doc US 15854647 20171226 US 10525153 20200107 child-doc US 16734929
continuation parent-doc WO PCT/KR2016/006386 20160616 PENDING child-doc US 15854647

Publication Classification

Int. Cl.: **A61L2/10** (20060101); **A61L2/26** (20060101); **E03C1/126** (20060101); **G01B5/24** (20060101); **G01B11/02** (20060101)

U.S. Cl.:

CPC **A61L2/10** (20130101); **A61L2/26** (20130101); **E03C1/126** (20130101); **G01B5/24** (20130101); **G01B11/02** (20130101); A61L2202/11 (20130101); A61L2202/121 (20130101); A61L2202/122 (20130101); A61L2202/14 (20130101); A61L2202/17 (20130101)

Field of Classification Search

CPC: A61L (2/10); A61L (2/26); A61L (2202/11); A61L (2202/121); A61L (2202/122); A61L (2202/14); A61L (2202/17); E03C (1/126); G01B (5/24); G01B (11/02)

USPC: 250/453.11; 250/454.11; 250/455.11

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3998590	12/1975	Glorieux	N/A	N/A
6585392	12/2002	Shiau et al.	N/A	N/A
6753537	12/2003	Woo	N/A	N/A
9022035	12/2014	Asada et al.	N/A	N/A
9279746	12/2015	Wynn	N/A	N/A
9518720	12/2015	Kim	N/A	N/A
9758953	12/2016	Bayley et al.	N/A	N/A
10525153	12/2019	Kim	N/A	G01B 5/24
11027033	12/2020	Kim	N/A	A61L 2/10
11938239	12/2023	Kim	N/A	G01B 5/24
2011/0306213	12/2010	Wang et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102216826	12/2010	CN	N/A
102824652	12/2011	CN	N/A
204387867	12/2014	CN	N/A
2003-501148	12/2002	JP	N/A
2004-41222	12/2003	JP	N/A

2010-275748	12/2009	JP	N/A
2013110411	12/2009	JP	N/A
2014133007	12/2013	JP	N/A
20-0335685	12/2002	KR	N/A
20-0335685	12/2002	KR	N/A
10-0825568	12/2007	KR	N/A
10-2010-0042334	12/2009	KR	N/A
10-2011-0085294	12/2010	KR	N/A
10-1145418	12/2011	KR	N/A
10-2012-0092465	12/2011	KR	N/A
10-1262661	12/2012	KR	N/A
20-2013-0002604	12/2012	KR	N/A

OTHER PUBLICATIONS

Supplementary European Search Report from related European Patent Application No.

EP16814619 dated Jan. 18, 2019 (12 pages). cited by applicant

English translation of Japanese Office Action from related Japanese Patent Application No. 2017-566777 dated Apr. 21, 2020 (7 pages). cited by applicant

English translation of Chinese Office Action(s) from related Chinese Patent Application No. 201680037592.1 (Aug. 2020) (23 pages). cited by applicant

English translation of European Office Action(s) from related European Patent Application No. 16814619.9 dated May 24, 2022 (6 pages). cited by applicant

English translation of Korean Office Action from Korean Application No. 10-2015-0093744 dated Dec. 16, 2021 (7 pages). cited by applicant

English translation of Office Action from related Japanese Patent Application No. 2022-109315 dated Jul. 11, 2023 (8 pages). cited by applicant

Primary Examiner: Ippolito; Nicole M

Attorney, Agent or Firm: Perkins Coie LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/243,290, filed on Apr. 28, 2021, which is a continuation of U.S. patent application Ser. No. 16/734,929, filed on Jan. 6, 2020, which is a continuation of U.S. patent application Ser. No. 15/854,647, filed on Dec. 26, 2017, which is a continuation of International Application No. PCT/KR2016/006386, filed on Jun. 16, 2016, which claims priority to and the benefit of Korean Patent Application No. 10-2015-0091036, filed on Jun. 26, 2015, and Korean Patent Application No. 10-2015-0093744, filed on Jun. 30, 2015, and Korean Patent Application No. 10-2016-0025592, filed on Mar. 3, 2016, all of which are hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND

Technical Field

(1) The present invention relates to a sterilizing apparatus using a UV light emitting diode to perform sterilization by emitting UV light towards a sterilization target region.

Discussion of the Background

(2) Generally, since various kinds of small devices used in contact with the human body, such as

earphones, nail clippers, razors, and mobile phones, are stored in various places for user convenience, such as pockets, bags, the interior of vehicles, and the like, such small devices are likely to contact many kinds of bacteria living in such places and are always exposed to air and an environment into which bacteria floating in the air can be easily introduced.

(3) Therefore, although it is necessary to remove bacteria present in such small devices used in contact with the human body, it is very troublesome and, often, impossible to clean such small devices every time using a detergent.

(4) In addition, a sink drain provides a good environment for bacteria and microorganisms to reproduce. Therefore, if food is not frequently removed from the sink drain and disinfection of the bacteria and microorganisms is not frequently performed, the bacteria and microorganisms will soon reproduce.

(5) Although chemicals capable of suppressing propagation of bacteria and microorganisms have been released in the art in order to prevent an unclean environment of the sink drain, such chemicals cause environmental pollution. Moreover, since the chemicals are frequently washed off by water, it is necessary to frequently replace or replenish the chemicals.

SUMMARY

(6) Exemplary embodiments of the present invention provide a sterilizing apparatus capable of easily and quickly removing bacteria on various kinds of small devices, such as earphones, nail clippers, razors, and mobile phones, at home.

(7) Exemplary embodiments of the present invention provide a drain cap capable of easily and quickly removing bacteria from a drain basin and a filter in a kitchen sink at home and having an ultraviolet sterilizing function.

(8) Exemplary embodiments of the present invention provide a sterilizing apparatus having a simple and reliable waterproof structure and a UV-transmissive window protection structure.

(9) Exemplary embodiments of the present invention provide a sterilizing apparatus capable of securing a sterilization region as much as possible and having high sterilizing power.

(10) Exemplary embodiments of the present invention provide a sterilizing apparatus provided with a safety apparatus which prevents UV light from reaching any other space outside a sterilizing region in any case.

(11) Exemplary embodiments of the present invention provide a sterilizing apparatus which can facilitate sterilization for various purposes.

(12) An exemplary embodiment of the present invention provides a sterilizing apparatus including: a cover body having an accommodation space defined therein to receive a sterilization target device, the accommodation space being open towards a bottom surface on which the sterilization target device is placed; a UV light emitting diode disposed at a side of the cover body facing the bottom surface and emitting UV light towards the accommodation space; a power supply supplying power to the UV light emitting diode to turn on the UV light emitting diode; and a controller controlling the power supply.

(13) The sterilizing apparatus may further include a detection unit detecting movement of the cover body, wherein the controller controls the power supply based on a detection result of the detection unit as to movement of the cover body.

(14) The detection unit may include a gyro sensor sensing a location of the cover body, and the controller may determine whether the cover body is moved based on a detection result of the detection unit as to the location of the cover body and may control the power supply to stop power supply to the UV light emitting diode when the cover body is moved away from the bottom surface on which the sterilization target device is placed.

(15) The detection unit may include a photosensor disposed inside the cover body and sensing light, and the controller may determine whether the cover body is moved based on a detection result of the detection unit as to light detection and may control the power supply to stop power supply to the UV light emitting diode when the cover body is moved away from the bottom surface

on which the sterilization target device is placed.

(16) The sterilizing apparatus may further include a switch for manipulating operation of the power supply, wherein the controller controls the power supply in response to manipulation of the switch.

(17) The cover body may include a cover plate having a plate shape and a sidewall extending downward from a lower edge of the cover plate facing the bottom surface, and the UV light emitting diode may be disposed on a lower surface of the cover plate to be placed in an interior region of the cover body surrounded by the lower surface of the cover plate and the sidewall.

(18) The sterilizing apparatus may further include a reflector formed on the cover body and reflecting UV light emitted from the UV light emitting diode towards the accommodation space.

(19) The reflector may be formed by coating aluminum onto the interior region of the cover body surrounded by the lower surface of the cover plate and the sidewall.

(20) The sterilizing apparatus may further include a timer for inputting a time for which the power supply supplies power to the UV light emitting diode, wherein the controller may control a power supply time of the power supply depending on a time set by the timer.

(21) The UV light emitting diode may emit UV light having a peak wavelength of 250 nm to 280 nm.

(22) The sterilizing apparatus may further include a visible light emitting diode provided to the cover body and emitting visible light.

(23) The visible light emitting diode may be turned on in association with turning on of the UV light emitting diode.

(24) An exemplary embodiment of the present invention provides a sterilizing apparatus including: a cover body opening or closing a drain hole in which a drain basin and a filter are disposed; a UV light emitting diode disposed at a side of the cover body facing the drain basin and the filter and emitting UV light towards the drain basin and the filter; a power supply supplying power to the UV light emitting diode to turn on the UV light emitting diode; and a controller controlling the power supply.

(25) The sterilizing apparatus may further include a detection unit detecting whether the drain hole is open or closed by the cover body, wherein the controller may control the power supply based on a detection result of the detection unit as to whether the drain hole is open or closed by the cover body.

(26) The detection unit may include a gyro sensor sensing a location of the cover body, and the controller may determine whether the drain hole is open or closed by the cover body based on a detection result of the detection unit as to the location of the cover body and may control the power supply to stop power supply to the UV light emitting diode when the cover body is placed to open the drain hole.

(27) The detection unit may include a photosensor disposed inside the drain hole and sensing light, and the controller may determine whether the drain hole is open or closed by the cover body based on a detection result of the detection unit as to light detection and may control the power supply to stop power supply to the UV light emitting diode when the cover body is placed to open the drain hole.

(28) The sterilizing apparatus may further include a magnet member embedded in the cover body, wherein the detection unit includes a sensor for sensing a magnetic flux of the magnet member, and the controller may determine whether the drain hole is open or closed by the cover body based on a detection result of the detection unit as to the magnetic flux of the magnet member and may control the power supply to stop power supply to the UV light emitting diode when the cover body is placed to open the drain hole.

(29) The sterilizing apparatus may further include a switch for manipulating operation of the power supply, wherein the controller controls the power supply in response to manipulation of the switch.

(30) The sterilizing apparatus may further include a handle for a user to grip the cover body, wherein the switch is disposed on the handle.

- (31) The cover body may include a cover plate having a plate shape corresponding to a shape of the drain hole and a sidewall extending downward from a lower edge of the cover plate facing the drain basin and the filter, and the UV light emitting diode may be disposed on a lower surface of the cover plate to be placed in an interior region of the cover body surrounded by the lower surface of the cover plate and the sidewall.
- (32) The sterilizing apparatus may further include a reflector formed on the cover body and reflecting UV light emitted from the UV light emitting diode towards the drain basin and the filter.
- (33) The reflector may be formed by coating aluminum onto the interior region of the cover body surrounded by the lower surface of the cover plate and the sidewall.
- (34) At least one of the cover body and the sidewall may be formed with an air flow hole through which the interior region of the cover body surrounded by the lower surface and the side wall of the cover plate communicates with an outside of the drain hole.
- (35) The sterilizing apparatus may further include a timer for inputting a time for which the power supply supplies power to the UV light emitting diode, wherein the controller may control a power supply time of the power supply depending on a time set by the timer.
- (36) The UV light emitting diode may emit UV light having a peak wavelength of 250 nm to 280 nm.
- (37) The sterilizing apparatus may further include a visible light emitting diode provided to the cover body and emitting visible light.
- (38) The visible light emitting diode may be turned on in association with turning on of the UV light emitting diode.
- (39) An exemplary embodiment of the present invention provides a sterilizing apparatus including: a housing having an outer surface facing a sterilization target region; a cover body coupled to the housing to define a space inside the housing; an irradiation opening formed in the housing; a window member receiving portion disposed on an inner surface of the housing around the irradiation opening; a window member provided to the window member receiving portion; a step portion disposed at an edge of the window member receiving portion; a first O-ring disposed on a portion of the window member and the step portion; a compression member secured to the housing to press the first O-ring and having a hole concentrically aligned with the irradiation opening; and a substrate on which a UV light emitting diode is mounted, the UV light emitting diode being disposed inside the housing and emitting UV light through the hole of the compression member and the irradiation opening.
- (40) The step portion may have substantially the same height as the window member received in the window member receiving portion.
- (41) The irradiation opening may have an irradiation opening-enlarged portion having a cross-section gradually widening from the inner surface of the housing to an outer surface thereof.
- (42) The irradiation opening may have a circular shape and the first O-ring may have an annular shape.
- (43) The window member may have a square shape.
- (44) The housing may include a first jaw formed on the inner surface thereof and supporting an outer circumferential surface of the first O-ring.
- (45) The compression member may be provided with a protruding jaw supporting an inner circumferential surface of the first O-ring.
- (46) A leading end of the protruding jaw may be separated from the window member by a predetermined distance.
- (47) The first O-ring may be formed of a ductile silicone material having a hardness of less than 30 with reference to a hardness of 0 to 100 and the compression member may have higher hardness than the first O-ring.
- (48) The sterilizing apparatus may further include an additional elastic member interposed between the window member and the window member receiving portion.

- (49) The sterilizing apparatus may further include a second O-ring fitted into a second O-ring receiving groove disposed outside the first jaw with respect to the irradiation opening, wherein the second O-ring may be pressed by the compression member.
- (50) The second O-ring receiving groove may be disposed between the first jaw and a second jaw disposed outside the first jaw with respect to the irradiation opening.
- (51) The substrate may be secured to the compression member.
- (52) The UV light emitting diode may emit UV light having a peak wavelength of 260 nm to 280 nm.
- (53) The sterilizing apparatus may further include a detection unit detecting a location or posture of the sterilizing apparatus.
- (54) The detection unit may be placed at a location on the substrate exposed through the irradiation opening and the hole of the compression member and may include an illuminance sensor.
- (55) The detection unit may be placed at a location on the substrate exposed through the irradiation opening and the hole of the compression member and may include a distance sensor.
- (56) According to exemplary embodiments of the present invention, the sterilizing apparatus can easily, quickly, and effectively remove bacteria present in various types of small devices and sinks through simple on/off operation.
- (57) In addition, the sterilizing apparatus according to the exemplary embodiments can be manufactured in a small size and can easily sterilize a small device simply by covering the device placed on a bottom surface to secure easy carriage and use convenience.
- (58) Further, the sterilizing apparatus according to the exemplary embodiments allows UV irradiation only when all safety conditions are satisfied, thereby further improving operation efficiency while effectively reducing a risk of occurrence of accidents and UV light leakage.
- (59) Further, the sterilizing apparatus according to the exemplary embodiments can realize reliable waterproofing and a breakage prevention function of a fragile part even with a simple structure.
- (60) Further, the sterilizing apparatus according to the exemplary embodiments can further improve sterilization efficiency and can enlarge a sterilization area.
- (61) Further, the sterilizing apparatus according to the exemplary embodiments can reduce UV exposure to the human body as much as possible.
- (62) Further, the sterilizing apparatus according to the exemplary embodiments can be used for various purposes and allow convenient sterilization.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a sectional view of a multipurpose sterilizing apparatus according to one embodiment of the present invention.
- (2) FIG. 2 is a block diagram of the sterilizing apparatus according to the embodiment of the present invention.
- (3) FIG. 3 is a sectional view illustrating one example of use of the portable multipurpose sterilizing apparatus according to the embodiment of the present invention.
- (4) FIG. 4 and FIG. 5 are graphs depicting inactivation levels of *E. coli* depending upon UV irradiation time and irradiation amount of the portable multipurpose sterilizing apparatus according to the embodiment of the present invention.
- (5) FIG. 6 and FIG. 7 are graphs depicting inactivation levels of *Staphylococcus aureus* depending upon UV irradiation time and irradiation amount of the portable multipurpose sterilizing apparatus according to the embodiment of the present invention.
- (6) FIG. 8 is a view showing an installation state of a drain cap having a UV sterilizing function according to one embodiment of the present invention.

- (7) FIG. 9 is a cross-sectional view of the drain cap having a UV sterilizing function according to the embodiment of the present invention.
- (8) FIG. 10 is a block diagram of the drain cap having a UV sterilizing function according to the embodiment of the present invention.
- (9) FIG. 11 is a view illustrating one example of use of the drain cap having a UV sterilizing function according to the embodiment of the present invention.
- (10) FIG. 12 is a view illustrating another example of use of the drain cap having a UV sterilizing function according to the embodiment of the present invention.
- (11) FIG. 13 and FIG. 14 are graphs depicting inactivation levels of *E. coli* depending upon UV irradiation time and irradiation amount of the drain cap having a UV sterilizing function according to the embodiment of the present invention.
- (12) FIG. 15 and FIG. 16 are graphs depicting inactivation levels of *Staphylococcus aureus* depending upon UV irradiation time and irradiation amount of the drain cap having a UV sterilizing function according to the embodiment of the present invention.
- (13) FIG. 17 is an exploded perspective view of a sterilizing apparatus according to another embodiment of the present invention.
- (14) FIG. 18 is an exploded perspective view illustrating an assembled state of a window member, a battery and a charging terminal in FIG. 17.
- (15) FIG. 19 is an exploded perspective view illustrating an assembled state of a first O-ring and a second O-ring in FIG. 18.
- (16) FIG. 20 is an exploded perspective view illustrating an assembled state of a compression member in FIG. 19.
- (17) FIG. 21 is an exploded perspective view illustrating an assembled state of a substrate and a housing O-ring in FIG. 20.
- (18) FIG. 22 is an exploded perspective view illustrating an assembled state of the sterilizer of FIG. 17, viewed from a different direction.
- (19) FIG. 23 shows an embodiment of a sterilizing apparatus.
- (20) FIG. 24 is a cross-sectional view taken along line A-A' of FIG. 21.
- (21) FIGS. 25A and 25B are enlarged views of Part C of FIG. 24.
- (22) FIG. 26 is a plan view showing a state in which the window member is placed on the first O-ring.
- (23) FIG. 27 is a front view showing a state in which the sterilizing apparatus according to the embodiment of the present invention is operable.
- (24) FIG. 28 is a graph showing a relationship between UV irradiation dose and sterilization rate after mixing *E. coli* O157:H7 (ATCC 43894) with water and irradiating the mixture with UV light at different wavelengths.
- (25) FIG. 29 is a graph showing a relationship between UV irradiation dose and sterilization rate after mixing *B. subtilis* spores (ATCC 6633) with water and irradiating the mixture with UV light at different wavelengths.
- (26) FIG. 30 is a graph showing a relationship between UV irradiation dose and sterilization rate after mixing B. MS2 phage (ATCC 15597-B1) with water and irradiating the mixture with UV light at different wavelengths.
- (27) FIG. 31 and FIG. 32 are views illustrating other examples of use of the sterilizing apparatus according to the embodiment of the present invention.
- (28) FIG. 33 is a flowchart illustrating operation of the sterilizing apparatus according to the embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(29) Hereinafter, exemplary embodiments of the present invention will be described in detail with reference to the accompanying drawings. It should be noted that the drawings are not to precise scale and may be exaggerated in thickness of lines or size of components for descriptive

convenience and clarity only. In addition, the terms used herein are defined by taking functions of the present invention into account and can be changed according to user or operator custom or intention. Therefore, definition of the terms should be made according to the overall disclosure set forth herein.

(30) FIG. 1 is a sectional view of a sterilizing apparatus according to one embodiment of the present invention and FIG. 2 is a block diagram of the sterilizing apparatus according to the embodiment of the present invention.

(31) Referring to FIGS. 1 and 2, the sterilizing apparatus **100** according to this embodiment may include a cover body **110**, a UV light emitting diode **120**, a power supply **130**, a detection unit **140**, and a controller **150**.

(32) The cover body **110** constitutes a main body of the sterilizing apparatus **100** and has an accommodation space for a sterilization target **1** (see FIG. 3) therein.

(33) The cover body **110** is formed such that the accommodation space is open toward a bottom surface B on which the sterilization target **1** is placed, and includes a cover plate **111** and a sidewall **113**.

(34) The cover plate **111** has a plate shape. Although the cover plate **111** is shown as a rectangular plate in this embodiment, it should be understood that the present invention is not limited thereto and the cover plate **111** may have various shapes such as circular, triangular, and polygonal shapes depending on application thereof.

(35) The sidewall **113** extends downward from an edge of a lower surface of the cover plate **111** facing the bottom surface B.

(36) Thus, the cover body **110** including the cover plate **111** and the sidewall **113** may be placed on the bottom surface B to provide an accommodation space for the sterilization target **1** (FIG. 3) that is optically isolated from the outside.

(37) The UV light emitting diode (LED) **120** is disposed at a side of the cover body **110** facing the bottom surface B and emits UV light toward the accommodation space and the sterilization target **1** received in the accommodation space.

(38) In this embodiment, the UV light emitting diode **120** is disposed on the lower surface of the cover plate **111** to be placed in an interior region of the cover body **110** surrounded by the lower surface of the cover plate **111** and the sidewall **113**.

(39) The UV light emitting diode **120** emits UV light having a peak wavelength of 270 nm to 280 nm toward the accommodation space and the sterilization target **1** received in the accommodation space and may include a plurality of UV light emitting diodes such that a surface of the sterilization target **1** received in the accommodation space can be evenly irradiated with UV light.

(40) UV light having a peak wavelength of 270 nm to 280 nm, particularly UV light having a peak wavelength of 275 nm, has high sterilization efficacy.

(41) In this embodiment, the UV light emitting diode **120** is configured to emit UV light having a peak wavelength of 275 nm, thereby enabling active sterilizing action to occur in the accommodation space.

(42) However, in order to provide an efficient level of sterilization, UV light having a peak wavelength in the UVC region, particularly UV light having a peak wavelength of about 250 nm to 280 nm, may be used.

(43) The sterilizing apparatus **100** according to this embodiment may further include a reflector **160**.

(44) The reflector **160** is formed on the cover body **110** to reflect UV light from the UV light emitting diode **120** toward the accommodation space and the sterilization target **1** received in the accommodation space.

(45) The reflector **160** may be formed by coating aluminum, which has high UV reflectance, onto an inner surface of the sidewall **113** of the cover body **110** and the lower surface of the cover plate **111** to surround the accommodation space. It should be understood that the reflector **160** may be

formed of any suitable material having high UV reflectance as well as aluminum.

(46) Thus, the reflector **160** serves to reflect UV light from the UV light emitting diode **120** toward the accommodation space and the sterilization target **1** received in the accommodation space to focus the UV light on the sterilization target **1** such that the sterilization target **1** can be more effectively sterilized by the UV light.

(47) The power supply **130** supplies electric power to the UV light emitting diode **120** to turn on the UV light emitting diode **120**.

(48) The power supply **130** may be realized by a battery disposed inside the cover body **110**.

Alternatively, the power supply **130** may be realized by an external power source.

(49) The detection unit **140** serves to detect movement of the cover body **110**.

(50) If the accommodation space is open to the outside or is not properly closed by the cover body **110**, UV light emitted from the UV light emitting diode **120** can escape to the outside of the cover body **110**. In order to prevent UV light emitted from the UV light emitting diode **120** from escaping to the outside of the cover body **110**, it is necessary to check whether the cover body **110** properly closes the accommodation space.

(51) For this purpose, the detection unit **140** is configured to obtain information about the location of the cover body **110** to check whether the cover body **110** properly closes the accommodation space.

(52) In one example, the detection unit **140** may include a gyro sensor for detecting the location, posture and the like of the cover body **110**, without being limited thereto.

(53) In another example, the detection unit **140** may include a photosensor disposed inside the cover body **110**. When the cover body **110** covers the bottom surface B such that the accommodation space is surrounded and closed by the cover body **110** and the bottom surface B, the inside of the cover body **110** is darkened. As a result, the detection unit **140** can check whether the cover body **110** properly closes the accommodation space by detecting whether the inside of the cover body **110** is shielded from light.

(54) In a further example, the detection unit **140** may include a plurality of trigger switches protruding from at least two portions of a lower surface of the sidewall **113** to determine closure of the accommodation space inside the cover body **110** depending upon whether the trigger switches are depressed.

(55) In addition, the detection unit **140** may include a combination of the aforementioned examples. For example, in a dark room, the location, posture and the like of the cover body **110** cannot be detected by the photosensor; on an inclined bottom surface, whether the cover body **110** closes the accommodation space cannot be accurately determined using the gyro sensor; and, on an uneven bottom surface, the trigger switches cannot function properly. In order to overcome these problems, the detection unit **140** may include a combination of various sensors as set forth above.

(56) The controller **150** controls operation of the power supply **130** to turn on/off the UV light emitting diode **120**. In addition, the controller **150** controls the power supply **130** to be operated depending upon the detection result of the detection unit **140** detecting whether the cover body **110** properly closes the accommodation space.

(57) For example, the controller **150** may determine whether the cover body **110** properly closes the accommodation space based on information about the location and posture of the cover body **110** detected by the detection unit **140**. If the cover body **110** is placed to open the accommodation space, the controller **150** may control the power supply **130** such that power supply to the UV light emitting diode **120** can be stopped.

(58) That is, the controller **150** may control the power supply **130** to supply power to the UV light emitting diode **120** so as to turn on the UV light emitting diode **120**. In this operation, the controller **150** determines whether the cover body **110** is open or closed based on the information about the location and posture of the cover body **110** detected by the detection unit **140**. If it is determined that the cover body **110** opens or does not properly closes the accommodation space, the controller

150 can stop irradiation with UV light through the UV light emitting diode **120** by controlling the power supply **130** to stop power supply to the UV light emitting diode **120**.

(59) The sterilizing apparatus **100** according to this embodiment may further include a switch **170**.

(60) The switch **170** is provided to control the power supply **130**. In this embodiment, the switch **170** is disposed at an upper portion of the cover body **110**, more specifically, on an upper surface of the cover plate **111**, in order to allow easy manipulation of the switch **170** by a user.

(61) Such a switch **170** may be provided to manipulate on/off operation of the power supply **130** and the controller **150** controls the power supply **130** to be turned on or turned off through manipulation of the switch **170**.

(62) The sterilizing apparatus **100** according to this embodiment may further include a timer **180**.

(63) The timer **180** is provided as a means for inputting a period of time for which the power supply **130** supplies power to the UV light emitting diode **120**, and the controller **150** can control a power supply time of the power supply **130** according to the period of time adjusted by the timer **180**.

(64) For example, if the period of time input through the timer **180** is set to 10 minutes, the controller **150** controls the power supply **130** to supply power to the UV light emitting diode **120** such that the UV light emitting diode **120** can be turned off after the UV light emitting diode **120** is turned on to emit UV light for 10 minutes.

(65) The sterilizing apparatus **100** according to this embodiment may further include a visible light emitting diode **190**.

(66) The visible light emitting diode **190** is disposed near the UV light emitting diode **120** inside the cover body **110**, more specifically in an interior region of the cover body **110** surrounded by the lower surface of the cover plate **111** and the sidewall **113**.

(67) With this structure, the visible light emitting diode **190** emits light in the visible range at a location near the UV light emitting diode **120** when the UV light emitting diode **120** is turned on, and is operated in conjunction with the UV light emitting diode **120**.

(68) Specifically, the visible light emitting diode **190** is turned on to emit light in the visible range when the UV light emitting diode **120** is turned on to emit UV light, thereby providing a function of displaying UV irradiation through the UV light emitting diode **120**.

(69) With such operation of the visible light emitting diode **190**, a user can easily recognize that UV light is emitted through the UV light emitting diode **120** and thus can be prevented from being continuously exposed to UV light not perceived by the user during irradiation with the UV light emitted from the UV light emitting diode **120**.

(70) FIG. 3 is a sectional view illustrating one example of use of the portable multipurpose sterilizing apparatus according to the embodiment of the present invention; FIG. 4 and FIG. 5 are graphs depicting inactivation levels of *E. coli* depending upon UV irradiation time and irradiation amount of the portable multipurpose sterilizing apparatus according to the embodiment of the present invention; and FIG. 6 and FIG. 7 are graphs depicting inactivation levels of *Staphylococcus aureus* depending upon UV irradiation time and irradiation amount of the portable multipurpose sterilizing apparatus according to the embodiment of the present invention.

(71) Next, operation and advantageous effects of the sterilizing apparatus according to this embodiment will be described with reference to FIG. 2 to FIG. 7.

(72) Referring to FIG. 2 and FIG. 3, the sterilizing apparatus **100** according to this embodiment sterilizes a sterilizing target device, for example, a small device such as an earphone, a nail clipper, a mobile phone, and the like, disposed on the bottom surface B, with the cover body **110** covering the sterilizing target device so as to be received in the accommodation space thereof, and the sterilizing operation of the sterilizing apparatus **100** is controlled by the controller **150**.

(73) The operation of the sterilizing apparatus **100** for sterilizing of the sterilization target device received in the accommodation space can be started by manipulating the switch **170** disposed on the upper surface of the cover body **110**.

(74) For example, when the sterilizing target device placed on the bottom surface B is covered with the cover body **110** to be received in the accommodation space and an operation signal is input through the switch **170**, the signal is transmitted to the controller **150**, which in turn starts to control the power supply **130** in response to the signal.

(75) The detection unit **140** senses the location of the cover body **110** and obtains information about the location and posture of the cover body **110**, and the controller **150** determines whether the accommodation space is open or closed by cover body **110**, based on the information about the location and posture of the cover body **110**.

(76) As a result, if it is determined that the accommodation space is closed by the cover body **110**, the controller **150** controls the power supply **130** to supply power to the UV light emitting diode **120**, and if it is determined that the accommodation space is open or is not properly closed by the cover body **110**, the controller **150** controls the power supply **130** such that power is not supplied to the UV light emitting diode **120**.

(77) As such, the operation of the UV light emitting diode **120** is controlled only when the accommodation space is closed by the cover body **110**, thereby preventing inefficient operation of the sterilizing apparatus **100**, reducing accident risk, and preventing UV light emitted from the UV light emitting diode **120** from leaking to the outside of the cover body **110** and providing a harmful effect on the human body.

(78) In this way, when power is supplied to the UV light emitting diode **120** through operation control of the controller **150**, the UV light emitting diode **120** is turned on to emit ultraviolet light toward the sterilization target device.

(79) Here, the UV light emitting diode **120** emits UV light exhibiting strong sterilizing properties, for example, UV light having a peak wavelength in the range of 270 nm to 280 nm, more preferably UV light having a peak wavelength of 275 nm.

(80) In this way, operation of the detection unit **140** is continued during operation of the UV light emitting diode **120**, and during this operation, if it is determined that the accommodation space is open or is not properly closed by the cover body **110**, based on the information about the location and posture of the cover body **110** obtained by the detection unit **140**, the controller **150** controls the power supply **130** to stop power supply to the UV light emitting diode **120**, whereby the UV light emitting diode **120** can be turned off to stop UV irradiation.

(81) In addition, the UV light emitting diode **120** may be turned off when the power supply time of the power supply **130** set by the timer **180** has elapsed, and whether the UV light emitting diode **120** is turned on or off can be determined based on whether the visible light emitting diode **190** is turned on or off.

(82) That is, in the sterilizing apparatus **100** according to this embodiment, UV irradiation can be performed only when the operation signal is input through the switch **170** in the state that the accommodation space is closed by the cover body **110**; power supply can be automatically interrupted to stop UV irradiation when there is a risk of UV light leakage due to instability of the cover body **110** during operation of the cover body **110** or when a preset period of time has elapsed; and whether the UV light emitting diode **120** is turned on to emit UV light can be determined based on whether the visible light emitting diode **190** is turned on.

(83) The sterilizing apparatus **100** according to this embodiment allows UV irradiation only when the safety conditions described above are satisfied, thereby further improving operation efficiency while effectively reducing accident risk and leakage of UV light.

(84) On the other hand, UV light emitted from the UV light emitting diode **120** is directed to the sterilization target device received in the accommodation space, thereby enabling sterilization on the surface of the sterilizing target device.

(85) According to this embodiment, a plurality of UV light emitting diodes **120** is provided to the sterilizing apparatus such that the entire region of the sterilization target device can be irradiated with UV light, and the reflector **160** is disposed to reflect UV light emitted from the UV light

emitting diodes **120** towards the accommodation space and the sterilization target device received in the accommodation space so as to focus the UV light on the sterilization target device, thereby enabling active sterilization over the entire region of the sterilization target device.

(86) As sterilization effects through sterilization using the sterilizing apparatus **100** according to this embodiment described above, it can be seen that inactivation of *E. coli* approached 99.9% on the sterilization target device upon UV irradiation at a dose of about 5 mJ/cm^{sup.2} for about 15 minutes and most of *E. coli* remaining on the surface of the sterilization target device was sterilized during sterilization through UV irradiation (see FIG. 4 and FIG. 5).

(87) In addition, it can be seen that inactivation of *Staphylococcus aureus* approached 99.9% on the sterilization target device upon UV irradiation at a dose of about 7 mJ/cm^{sup.2} for about 20 minutes and most of *Staphylococcus aureus* remaining on the surface of the sterilization target device was sterilized during sterilization through UV irradiation (see FIG. 6 and FIG. 7).

(88) The sterilizing apparatus **100** according to this embodiment allows automatic UV sterilization with respect to various kinds of small devices, such as earphones, nail clippers, mobile phones, and the like, through simple on/off operation, so that various bacteria remaining on such small sterilization target devices can be removed with high efficiency, thereby enabling easy, rapid and effective removal of bacteria present on various types of small devices at home.

(89) In addition, since the sterilizing apparatus **100** according to this embodiment can be manufactured in a small size, the sterilizing apparatus **100** according to this embodiment is convenient to carry and provides use convenience through easy sterilization of a small device simply by covering the small device placed on the bottom surface.

(90) Further, the sterilizing apparatus **100** according to this embodiment allows UV irradiation only when various safety conditions, such as operation of the switch **170**, detection of the closed state of the accommodation space through the detection unit **140**, and operation time setting through the timer **180**, are satisfied, thereby further improving operation efficiency of the sterilizing apparatus while effectively reducing accident risk and leakage of UV light.

(91) FIG. 8 is a view showing an installation state of a sterilizing apparatus according to another embodiment of the present invention, FIG. 9 is a cross-sectional view of the drain cap having a UV sterilizing function according to the embodiment of the present invention, and FIG. 10 is a block diagram of the drain cap having a UV sterilizing function according to the embodiment of the present invention.

(92) Referring to FIG. 8 to FIG. 10, a sterilizing apparatus **200** according to another embodiment is provided to a bottom of a wash basin **211** of a sink **210** to open or close a drain hole **212** formed at the bottom of the wash basin **211**.

(93) In the drain hole **212**, a drain basin **214** is disposed to connect the drain hole **212** to a drainage pipe **213** and is provided with a filter **215** that filters food residues or foreign substances remaining in the sewage discharged through the drain hole **212**.

(94) The sterilizing apparatus **200** according to this embodiment is detachably provided to the wash basin **211** to open or close the drain hole **212** above the drain basin **214** and the filter **215**, and may include light emitting diodes **120**, a power supply **130**, a detection unit **140**, and a controller **150**.

(95) The cover body **110** constitutes a main body of the sterilizing apparatus **200** according to the present embodiment, and opens or closes the drain hole **212**, which is provided therein with the drain basin **214** and the filter **215**. The cover body **110** includes a cover plate **111** and a sidewall **113**.

(96) The cover plate **111** is formed in a plate shape corresponding to the shape of the drain hole **212**. In this embodiment, the drain hole **212** has a circular shape and the cover plate **111** has a disk shape corresponding to the shape of the drain hole **212**.

(97) The sidewall **113** extends downward from a bottom edge of the cover plate **111** facing the drain basin **214** and the filter **215**.

(98) In the cover body **110** including the cover plate **111** and the sidewall **113**, the sidewall **113** may

be inserted into the drain hole **212**, and the cover plate **111** may be coupled to the wash basin **211** to close the drain hole **212** by covering the drain hole **212** and may be separated from the wash basin **211** to open the drain hole **212**.

(99) However, the sidewall **113** is not necessarily inserted into the drain hole **212** and may be disposed such that a lower surface of the sidewall **113** is placed on the bottom surface of the wash basin **211**.

(100) The sterilizing apparatus **200** according to this embodiment may further include a handle **115**.

(101) The handle **115** may protrude from an upper surface of the cover body **110**, that is, an upper surface of the cover plate **111**, such that a user can grip the cover body **110**. Thus, a user can easily open or close the drain hole **212** by grasping the handle **115**.

(102) The UV light emitting diodes (LEDs) **120** are disposed at a side of the cover body **110** facing the drain basin **214** and the filter **215**, and is turned on to emit UV light towards at least one of the drain basin **214** and the filter **215**.

(103) In this embodiment, the UV light emitting diode **120** is disposed on a lower surface of the cover plate **111** so as to be placed inside the cover body **110** surrounded by the lower surface of the cover plate **111** and the sidewall **113**.

(104) An air flow hole (not shown) may be formed in at least one of the cover plate **111** and the sidewall **113**.

(105) The air flow hole forms a flow channel, through which the interior of the cover body **110** surrounded by the lower surface of the cover plate **111** and the sidewall **113** communicate with the outside of the drain hole **212**, such that moisture can be discharged from the drain hole **212** therethrough, thereby suppressing influence of the moisture remaining in the drain basin **214** and the filter **215** on the UV light emitting diode **120**.

(106) The UV light emitting diode **120** is disposed to emit UV light having a peak wavelength of 270 nm to 280 nm towards the drain basin **214** and the filter **215**, and a plurality of such UV light emitting diodes **120** is arranged at constant intervals to uniformly emit UV light to the entirety of the drain basin **214** and the filter **215**.

(107) Among UV light, ultraviolet light having a peak wavelength of 270 nm to 280 nm, particularly UV light having a peak wavelengths of 275 nm, has an excellent sterilizing effect.

(108) In this embodiment, the UV light emitting diode **120** is configured to emit UV light having a peak wavelength of 275 nm and sterilization can be actively performed inside the drainage pipe **213** through operation of the UV light emitting diode **120**.

(109) However, in order to obtain an effective level of sterilization effect, UV light in the UVC range, particularly, UV light having a peak wavelength of about 950 nm to 280 nm, may be used.

(110) The sterilizing apparatus **200** according to this embodiment may further include a reflector **160**.

(111) The reflector **160** is formed on the cover body **110** to reflect UV light emitted from the UV light emitting diode **120** toward the drain basin **214** and the filter **215**.

(112) The reflector **160** may be formed by coating the interior region of the cover body **110** surrounded by the lower surface of the cover plate **111** and the sidewall **113** with aluminum or other coating materials having high reflectivity with respect to UV light.

(113) The reflector **160** reflects UV light emitted from the UV light emitting diode **120** toward the drain basin **214** and the filter **215** to focus UV irradiation on the drain basin **214** and the filter **215**, thereby enabling more effective sterilization of the drain basin **214** and the filter **215**.

(114) The power supply **130** supplies power to the UV light emitting diode **120** to turn on the UV light emitting diode **120**.

(115) The power supply **130** may be realized by a battery disposed inside the cover body **110** to supply power to the UV light emitting diode **120**, or may be realized by an external power source that supplies power to the UV light emitting diode **120** through the power supply **130**.

(116) The detection unit **140** is disposed to detect whether the drain hole **212** of the cover body **110**

is open or closed.

(117) If the cover body **110** opens or does not properly close the drain hole **212**, UV light emitted from the UV light emitting diode **120** can leak through the drain hole **212**. Thus, in order to prevent UV light emitted from the UV light emitting diode **120** from leaking through the drain hole **212**, it is necessary to determine whether the cover body **110** properly closes the drain hole **212**.

(118) To this end, the detection unit **140** can obtain information about the location of the cover body **110** in order to determine whether the cover body **110** properly closes the drain hole **212**.

(119) In one example, the detection unit **140** may include a gyro-sensor that senses the location, posture, and the like of the cover body **110**, without being limited thereto.

(120) In another example, the detection unit **140** may include a photosensitive sensor disposed inside the drain hole **212**. When the drain hole **212** is covered by the cover body **110**, the interior of the drain hole **212** is darkened. Thus, the detection unit **140** can determine whether the cover body **110** properly closes the drain hole **212** by sensing whether light is blocked inside the drain hole **212**.

(121) In a further example, the detection unit **140** may be realized by a magnet member disposed inside the cover body **110** and a sensor disposed inside the drain hole **212** to sense a magnetic flux of the magnet member, or by a sensor provided with a switch that can be pressed when the cover body **110** is covered.

(122) In yet another example, the detection unit **140** may be realized by at least two triggers (not shown) protruding from the lower surface of the sidewall **113** so as to determine whether the drain hole **212** of the cover body **110** is closed depending upon whether the trigger switches are pressed.

(123) The controller **150** controls the power supply **130** such that the UV light emitting diode **120** can be turned on or off. The controller **150** controls the power supply **130** depending upon a detection result of the detection unit **140** as to whether the drain hole **212** of the cover body **110** is open or closed.

(124) By way of example, the controller **150** may determine whether the drain hole **212** of the cover body **110** is open or closed based on information about the location and posture of the cover body **110** detected by the detection unit **140**. If the cover body **110** is placed to open the drain hole **212**, the controller **150** may control the power supply **130** such that power supply to the UV light emitting diode **120** can be stopped.

(125) That is, the controller **150** may control the power supply **130** to supply power to the UV light emitting diode **120** so as to turn on the UV light emitting diode **120**. In this operation, the controller **150** determines whether the drain hole **212** of the cover body **110** is open or closed based on the information about the location and posture of the cover body **110** detected by the detection unit **140**. If it is determined that the cover body **110** opens or does not properly close the drain hole **212**, the controller **150** can stop irradiation with UV light through the UV light emitting diode **120** by controlling the power supply **130** to stop power supply to the UV light emitting diode **120**.

(126) The sterilizing apparatus **200** according to this embodiment may further include a switch **170**.

(127) The switch **170** is provided to control the power supply **130**. In this embodiment, the switch **170** is provided to the handle **115** in order to allow easy manipulation of the switch **170** by a user.

(128) Such a switch **170** may be provided to manipulate on/off operation of the power supply **130** and the controller **150** controls the power supply **130** to be turned on or turned off through manipulation of the switch **170**.

(129) The sterilizing apparatus **200** according to this embodiment may further include a timer **180**.

(130) The timer **180** is provided as a means for inputting a period of time for which the power supply **130** supplies power to the UV light emitting diode **120**, and the controller **150** can control a power supply time of the power supply **130** according to the period of time adjusted by the timer **180**.

(131) For example, if the period of time input through the timer **180** is set to 10 minutes, the controller **150** controls the power supply **130** to supply power to the UV light emitting diode **120**

such that the UV light emitting diode **120** can be turned off after the UV light emitting diode **120** is turned on to emit UV light for 10 minutes.

(132) The sterilizing apparatus **200** according to this embodiment may further include a visible light emitting diode **190**.

(133) The visible light emitting diode **190** is disposed near the UV light emitting diode **120** inside the cover body **110**, more specifically in an interior region of the cover body **110** surrounded by the lower surface of the cover plate **111** and the sidewall **113**.

(134) With this structure, the visible light emitting diode **190** emits light in the visible range at a location near the UV light emitting diode **120** when the UV light emitting diode **120** is turned on, and is operated in conjunction with the UV light emitting diode **120**.

(135) Specifically, the visible light emitting diode **190** is turned on to emit light in the visible range when the UV light emitting diode **120** is turned on to emit UV light, thereby providing a function of displaying UV irradiation through the UV light emitting diode **120**.

(136) With such operation of the visible light emitting diode **190**, a user can easily recognize that UV light is emitted through the UV light emitting diode **120** and thus can be prevented from being continuously exposed to UV light not perceived by the user during irradiation with the UV light emitted from the UV light emitting diode **120**.

(137) FIG. **11** is a sectional view illustrating one example of use of the sterilizing apparatus according to this embodiment and FIG. **12** is a sectional view illustrating another example of use of the sterilizing apparatus according to this embodiment. In addition, FIG. **13** and FIG. **14** are graphs depicting inactivation levels of *E. coli* depending upon UV irradiation time and irradiation amount of the sterilizing apparatus according to this embodiment, and FIG. **15** and FIG. **16** are graphs depicting inactivation levels of *Staphylococcus aureus* depending upon UV irradiation time and irradiation amount of the sterilizing apparatus according to this embodiment.

(138) Next, operation and advantageous effects of the sterilizing apparatus according to this embodiment will be described with reference to FIG. **10** to FIG. **16**.

(139) Referring to FIG. **10** and FIG. **11**, the sterilizing apparatus **200** according to this embodiment is disposed to open or close the drain hole **212** at the bottom of the wash basin **211** and sterilizes the drain basin **214** and the filter **215** inside the drain hole **212** in a closed state, and the sterilizing operation of the sterilizing apparatus **200** is controlled by the controller **150**.

(140) The operation of the sterilizing apparatus **200** for sterilizing the drain basin **214** and the filter **215** inside the drain hole **212** can be started by manipulating the switch **170** disposed on the handle **115**.

(141) For example, when the drain hole **212** is closed by the cover body **110** using the handle **115** and an operation signal is input through the switch **170**, the signal is transmitted to the controller **150**, which in turn starts to control the power supply **130** in response to the signal.

(142) The detection unit **140** senses the location of the cover body **110** and obtains information about the location and posture of the cover body **110**, and the controller **150** determines whether the drain hole **212** is open or closed by the cover body **110**, based on the information about the location and posture of the cover body **110**.

(143) As a result, if it is determined that the drain hole **212** is closed by the cover body **110**, the controller **150** controls the power supply **130** to supply power to the UV light emitting diode **120**, and if it is determined that the drain hole **212** is open or is not properly closed by the cover body **110**, the controller **150** controls the power supply **130** such that power is not supplied to the UV light emitting diode **120**.

(144) As such, the operation of the UV light emitting diode **120** is controlled only when the drain hole **212** is closed by the cover body **110**, thereby preventing inefficient operation of the sterilizing apparatus **200**, reducing accident risk, and preventing UV light emitted from the UV light emitting diode **120** from leaking to the outside of the cover body **110** and providing a harmful effect on the human body.

(145) In this way, when power is supplied to the UV light emitting diode **120** through operation control of the controller **150**, the UV light emitting diode **120** is turned on to emit ultraviolet light toward the drain basin **214** and the filter **215**.

(146) Here, the UV light emitting diode **120** emits UV light exhibiting strong sterilizing properties, for example, UV light having a peak wavelength in the range of 270 nm to 280 nm, more preferably UV light having a peak wavelength of 275 nm.

(147) In this way, operation of the detection unit **140** is continued during operation of the UV light emitting diode **120**, and during this operation, if it is determined that the drain hole **212** is open or is not properly closed by the cover body **110**, based on the information about the location and posture of the cover body **110** obtained by the detection unit **140**, the controller **150** controls the power supply **130** to stop power supply to the UV light emitting diode **120**, whereby the UV light emitting diode **120** can be turned off to stop UV irradiation.

(148) In addition, the UV light emitting diode **120** may be turned off when the power supply time of the power supply **130** set by the timer **180** has elapsed, and whether the UV light emitting diode **120** is turned on or off can be determined based on whether the visible light emitting diode **190** is turned on or off.

(149) That is, in the sterilizing apparatus **200** according to this embodiment, UV irradiation can be performed only when the operation signal is input through the switch **170** in the state that the drain hole **212** is closed by the cover body **110**; power supply can be automatically interrupted to stop UV irradiation when there is a risk of UV light leakage due to instability of the cover body **110** during operation of the cover body **110** or when a preset period of time has elapsed; and whether the UV light emitting diode **120** is turned on to emit UV light can be determined based on whether the visible light emitting diode **190** is turned on.

(150) The sterilizing apparatus **200** according to this embodiment allows UV irradiation only when the safety conditions described above are satisfied, thereby further improving operation efficiency while effectively reducing accident risk and leakage of UV light.

(151) On the other hand, UV light emitted from the UV light emitting diode **120** is directed to the drain basin **214** and the filter **215**, thereby enabling sterilization of the drain basin **214** and the filter **215**.

(152) According to this embodiment, a plurality of UV light emitting diodes **120** is provided to the sterilizing apparatus such that the entire region of the drain basin **214** and the filter **215** can be irradiated with UV light, and the reflector **160** is disposed to reflect UV light emitted from the UV light emitting diodes **120** towards the drain basin **214** and the filter **215** so as to focus the UV light on the drain basin **214** and the filter **215**, thereby enabling active sterilization over the entire region of the drain basin **214** and the filter **215**.

(153) In another example, with the filter **215** removed from the drain basin **214**, UV light may be emitted towards the drain basin **214** to perform more active sterilization with respect to the drain basin **214** (see FIG. 12).

(154) As sterilization effects through sterilization using the sterilizing apparatus **200** according to this embodiment described above, it can be seen that inactivation of *E. coli* approached 99.9% on the drain basin **214** and the filter **215** upon UV irradiation at a dose of about 5 mJ/cm² for about 15 minutes and most of *E. coli* remaining on the drain basin **214** and the filter **215** was sterilized during sterilization through UV irradiation (see FIG. 13 and FIG. 14).

(155) In addition, it can be seen that inactivation of *Staphylococcus aureus* approached 99.9% on the drain basin **214** and the filter **215** upon UV irradiation at a dose of about 7 mJ/cm² for about 20 minutes and most of *Staphylococcus aureus* remaining on the drain basin **214** and the filter **215** was sterilized during sterilization through UV irradiation (see FIG. 15 and FIG. 16).

(156) The sterilizing apparatus **200** according to this embodiment allows automatic UV sterilization with respect to the drain basin **214** and the filter **215** disposed inside the drain hole **212** through simple on/off operation, so that various bacteria remaining on the drain basin **214** and the filter **215**

can be removed with high efficiency, thereby enabling easy, rapid and effective removal of bacteria present on the drain basin **214** and the filter **215** of the sink **210** at home.

(157) In addition, the sterilizing apparatus **100** according to this embodiment allows UV irradiation only when various safety conditions, such as operation of the switch **170**, detection of the closed state of the drain hole **212** through the detection unit **140**, and operation time setting through the timer **180**, are satisfied, thereby further improving operation efficiency of the sterilizing apparatus while effectively reducing accident risk and leakage of UV light.

(158) FIG. **17** is an exploded perspective view of a sterilizing apparatus according to another embodiment of the present invention, FIG. **18** is an exploded perspective view illustrating an assembled state of a window member, a battery and a charging terminal in FIG. **17**, FIG. **19** is an exploded perspective view illustrating an assembled state of a first O-ring and a second O-ring in FIG. **18**, FIG. **20** is an exploded perspective view illustrating an assembled state of a compression member in FIG. **19**, FIG. **21** is an exploded perspective view illustrating an assembled state of a substrate and a housing O-ring in FIG. **20**, FIG. **22** is an exploded perspective view illustrating an assembled state of the sterilizer of FIG. **17**, viewed in a different direction, FIG. **24** is a cross-sectional view taken along line A-A' of FIG. **21**, FIGS. **25A** and **25B** are enlarged views of Part C of FIG. **24**, FIG. **26** is a plan view showing a state in which the window member is placed on the first O-ring, and FIG. **27** is a front view showing a state in which the sterilizing apparatus according to the embodiment of the present invention is operable.

(159) Referring to FIG. **22** and FIG. **23**, the sterilizing apparatus according to this embodiment includes a housing **10** which receives various components for sterilization; a cover body **110**; and a holder **30** which holds the sterilizing apparatus. Four legs **32** of the holder **30** are placed on a flat floor, and the housing **10** and the cover body **110** are placed on the holder **30** to be secured thereto.

(160) Referring to FIG. **17** and FIG. **27**, in the sterilizing apparatus, the housing **10** is a flat portion and has a circular shape, and the cover body **110** has a curved shape and covers an upper portion of the housing **10**. A bottom surface (see FIG. **27**) is an outer surface of the housing **10** and faces a sterilizing target region. The housing **10** is provided at a central portion thereof with an irradiation opening **11**, through which UV light emitted from a light source inside the cover body **110** is emitted. The cover body **110** is provided with a switch **170** for operating the sterilizing apparatus and a visible light emitting diode **190** for determining whether the sterilizing apparatus is operating.

(161) First, a watertight structure and a window member protection structure disposed around the irradiation opening **11** of the housing **10** will be described. Referring to FIG. **17**, FIG. **18** and FIG. **24**, a square-shaped window member receiving portion **12** is formed on an inner surface of the housing **10** to enclose the irradiation opening **11** having a circular shape. A step portion **13** is formed around the window member receiving portion **12** to prevent a window member **40** fitted into the window member receiving portion **12** from moving to one side. The step portion **13** has substantially the same height as the window member **40** in a state that the window member **40** is received in the window member receiving portion **12**. When the heights of the step portion and the window member are substantially the same, a step is not formed between upper surfaces of the window member **40** and the step portion **13**, whereby sealing therebetween can be easily realized by placing a sealing member (first O-ring described below) between the window member and the step portion to be brought into close contact therewith.

(162) The window member **40** may be quartz or fused silica, which is a material through which deep UV light emitted from a UV light emitting diode described below can be transmitted.

(163) Referring to FIG. **18**, FIG. **19** and FIG. **24**, a first O-ring **50** is placed on the step portion **13** and the window member **40** fitted into the window member receiving portion **12** to cover at least a gap between the window member and the step portion. The first O-ring **50** has an annular shape, in which an outer circumferential surface **51** of the first O-ring **50** has a larger diameter than an outer circumference of the window member **40** and/or an inner circumference of the step portion and an inner circumferential surface **52** of the first O-ring has a smaller diameter than the window member

40 (see FIG. 26). Thus, when the first O-ring **50** is placed on the step portion **13** and the window member **40** fitted into the window member receiving portion **12**, the gap between the window member and the step portion is shielded by the first O-ring **50**.

(164) As shown in the drawings, a first jaw **14** is formed outside a region in which the first O-ring **50** is placed, and regulates the location of the first O-ring **50**. In addition, a second O-ring receiving groove **16** into which a second O-ring **56** is fitted is formed outside the first jaw **14** and a second jaw **15** having substantially the same height as the first jaw **14** is formed outside the second O-ring receiving groove **16**. The second O-ring receiving groove **16** receives the second O-ring described later. In this way, according to this embodiment, the sterilizing apparatus has a double-sealing structure in a path where water penetration is likely to occur, thereby securing waterproof characteristics. In particular, when the two jaws **14**, **15** have the same height, the second O-ring can be more easily received and can be uniformly expanded without uneven distribution of compressive force when the second O-ring is pressed by a compression member described below.

(165) Referring to FIG. 19, FIG. 20 and FIG. 24, the compression member **60** is formed in a shape of an annular flat plate, and includes a circular hole **62** formed at the center thereof, a rib **61** formed at an outer circumference thereof to reinforce the compression member **60**, and three fastening portions **66** formed at the outer circumference thereof and arranged at intervals of 120 degrees. A fastening screw (not shown) penetrates each of the fastening portions **66** and is screwed to an inner surface of the housing such that the compression member **60** is strongly pressed and secured to the inner surface of the housing **10**.

(166) Such a compressive force is transmitted to the first O-ring **50** and the second O-ring **56** such that an upper surface of the first O-ring is brought into close contact with the compression member **60** and a lower surface of the first O-ring is brought into close contact with the upper surfaces of the window member **40** and the step portion **13**. When the first O-ring **50** is pressed, the first O-ring **50** is pushed by the pressure such that the outer circumferential surface **51** of the first O-ring **50** expands in a direction of increasing the diameter thereof and the inner circumferential surface **52** thereof expands in a direction of decreasing the diameter thereof. The outer circumferential surface **51** of the first O-ring is prevented from expanding by the first jaw **14** and brought into close contact with the first jaw **14**. On the other hand, the inner circumferential surface of the first O-ring is prevented from expanding by a protruding jaw **64** protruding in the direction of the window member, that is, downward, around the hole **62** of the compression member **60**. At this time, a lower end of the protruding jaw **64** does not contact the window member **40** and is separated a certain distance from the window member to have a gap therebetween. Since the window member **40** can be damaged due to intensive pressure from the protruding jaw **64** when the protruding jaw **64** is brought into contact with the window member **40**, a predetermined gap is required between the window member and the protruding jaw. On the other hand, since the inner circumferential surface of the first O-ring can freely expand inwards in a structure wherein the compression member **60** does not include the protruding jaw **64**, adherence between the inner circumferential surface of the first O-ring, the compression member and the window member can be deteriorated. Accordingly, the protruding jaw **64** may be formed to have a sufficient height to be uniformly pressed between the window member and the first O-ring without applying intensive pressure to the window member in consideration of the material of the first O-ring and the like. In other words, as the height of the protruding jaw is lowered, the possibility of applying the intensive pressure to the window member becomes higher, whereas uniformity of the pressure applied between the window member and the first O-ring is lowered. As the height of the protruding jaw is increased, the possibility of applying the intensive pressure to the window member increases, whereas it is more advantageous to secure uniformity of the pressure applied between the window member and the first O-ring. An optimal height of the protruding jaw may be determined so as to satisfy the above conditions in consideration of the material of the first O-ring and the gap between the protruding jaw and the window member.

(167) A cross-sectional area of the second O-ring **56** is set to be slightly larger than a cross-sectional area defined by the second O-ring receiving groove **16**, the first jaw **14**, the second jaw **15** and the compression member. Thus, when the second O-ring is pressed by the compression member, an outer surface of the second O-ring is brought into contact with the second O-ring receiving groove **16**, the first jaw **14**, the second jaw **15** and the compression member under uniform pressure.

(168) Among materials theoretically having a hardness of 0 to 100, the first O-ring **50** is formed of a ductile silicone material having a hardness of less than 30. If the hardness is greater than 30, there is a high possibility that the intensive pressure is applied to a certain portion of the window member **40** to be damaged when the first O-ring is pressed by the compression member. It should be understood that the compression member may be formed of a material having a higher hardness than the first O-ring, such as ABS resins.

(169) As shown in FIG. **25B**, the compression member may further include an additional elastic material **59** interposed between the window member **40** and the window member receiving portion **12**. The elastic material **59** has an effect of eliminating a possibility of pressure concentration at a specific portion between the window member and the window member receiving portion while improving a watertight effect through adherence of the elastic member.

(170) On the other hand, the hole **62** of the compression member **60** is concentrically aligned with the irradiation opening **11** of the housing **10**. Both the hole **62** of the compression member and the irradiation opening **11** of the housing **10** have a circular shape. The inner circumferential surface of the first O-ring also coincides with the center of these holes and has a circular shape. This structure is provided in consideration of an irradiation pattern of the light emitting diode which emits light in the form of diffusing the light in a conical shape from a spot light source, and can cause the compressive force between the compression member **60** and the housing **10** to be uniformly distributed between the first O-ring **50** and the window member **40** and can minimize an exposed area of the window member while securing as large a UV irradiation area as possible.

(171) Alternatively, the window member **40** may have a square shape. With this structure, the window member can be easily manufactured and prevented from laterally moving or rotating in place when the location of the window member is restricted by the step portion **13**. The shapes of the window member **40** and the first O-ring **50** have been described above with reference to FIG. **26**.

(172) Next, referring to FIG. **20**, FIG. **21**, FIG. **24** and FIGS. **25A** and **25B**, a substrate **70** is secured to an upper surface of the compression member **60**. The substrate **70** is provided with fixing portions **76** at two locations opposite to each other with respect to the center of the substrate and a fastening screw is screwed to a fixing portion **68** of the compression member **60** through each of the fixing portions **76**. The locations of the fixing portions **68** may be determined so as not to overlap the locations of the fastening portions **66** of the compression member described above.

(173) On the substrate **70**, the UV light emitting diode **120** is mounted at a location concentrically aligned with the irradiation opening **11** and the hole **62** while facing the irradiation opening **11** and the hole **62**. By way of example, the UV light emitting diode **120** may have an irradiation angle of 120 degrees. UV light emitted from the UV light emitting diode **120** is emitted to the outside after passing through the window member **40** and the irradiation opening **11**. As a result, a sterilization region facing the housing **10** is exposed to UV light. For example, the irradiation opening **11** may have a smaller diameter, such that at least 50% of the amount of UV light emitted from the UV light emitting diode **120** can pass therethrough.

(174) In order to secure the irradiation angle of the UV light emitting diode as much as possible, the irradiation opening **11** may include an irradiation opening-enlarged portion **321**, which has a cross section gradually widened toward the outside (see FIGS. **25A** and **25B**). The irradiation opening-enlarged portion **321** may have a curved shape as shown in FIG. **25A** or may have a tapered shape as shown in FIG. **25B**. With any shape, the irradiation opening-enlarged portion **11**

secures an irradiation area (a) corresponding as much as possible to the irradiation angle of UV light emitted from the UV light emitting diode, while securing an area for supporting the window member **40** as much as possible. For example, in a structure wherein the irradiation opening **11** does not include the irradiation opening-enlarged portion **11**, the diameter of the irradiation opening **11** must be increased so as to increase the irradiation area by a, thereby causing reduction in the area of the window member receiving portion that supports the window member. In addition, since the diameter of the hole **62** of the compression member **60** must be increased corresponding to increase in the diameter of the irradiation opening **11** (when the hole of the compression member has a smaller diameter than the irradiation opening, pressure is unevenly applied to the upper and lower surfaces of the window member, thereby increasing a possibility of damage to the window member), the unsupported area of the upper and lower surfaces of the window member **40** is increased, thereby increasing the possibility of damage to the window member **40**. However, according to this embodiment, the irradiation opening **11** is formed with the irradiation opening-enlarged portion **11**, thereby reducing the possibility of damage to the window member **40** while securing the irradiation region of UV light as much as possible.

(175) By way of example, the UV light emitting diode **120** emits deep UV light having a peak wavelength of 275 nm.

(176) The UV light source used in the present invention is the UV light emitting diode **120**, which has high directionality in one direction. The UV light emitting diode allows fine adjustment of the peak wavelength of light emitted therefrom depending upon the proportion of components thereof. Therefore, efficiency of UV light can be increased through use of a UV light emitting diode configured to emit light having a peak wavelength most efficient for UV sterilization.

(177) Generally, UV having a peak wavelength of 253 nm is known to have the highest sterilizing power. However, as a result of actual experiments, it was confirmed that the most germicidal wavelength was 270 nm in sterilization of bacteria contained in water.

(178) FIG. **28** is a graph showing a relationship between UV irradiation dose and sterilization rate after mixing *E. coli* O157:H7 (ATCC 43894) with water and irradiating the mixture with UV light at different wavelengths. An initial concentration of bacteria contained in water was 1.9 to 3.0×10^5 cfu/mL. Experiments were performed under the same conditions excluding the wavelength of UV light.

(179) Experimental results showed a sterilization rate of 99% upon irradiation with UV light having a wavelength of 270 nm at a dose of 1.4 mJ/cm^2 , which was much superior to UV light of other wavelengths.

(180) FIG. **29** is a graph showing a relationship between UV irradiation dose and sterilization rate after mixing *B. subtilis* spores (ATCC 6633) with water and irradiating the mixture with UV light at different wavelengths.

(181) Experimental results showed a sterilization rate of 99% upon irradiation with UV light having a wavelength of 270 nm at a dose of 22 mJ/cm^2 , which was much superior to UV light of other wavelengths.

(182) FIG. **30** is a graph showing a relationship between UV irradiation dose and sterilization rate after mixing B. MS2 phage (ATCC 15597-B1) with water and irradiating the mixture with UV light at different wavelengths.

(183) Experimental results showed a sterilization rate of 99% upon irradiation with UV light having a wavelength of 270 nm at a dose of 42 mJ/cm^2 , which was much superior to UV light of other wavelengths.

(184) As a result of analysis of the experimental results, it was concluded that DNA or RNA of bacteria or viruses contained in water could be more sensitive to UV light having a wavelength of 270 nm. Since most of bacteria and viruses entering the body through food consumed by a person depend on moisture of the food and a sink drain also has an environment rich in food waste and water, it can be concluded that the above experiments were performed under conditions sufficiently

reflecting an actual region to be sterilized.

(185) Consequently, it was confirmed that sterilization efficiency was decreased with increasing or decreasing wavelength from 270 nm. Accordingly, in the present invention, the UV light emitting diode configured to emit UV light having a peak wavelength within the range of about 10 nm from 270 nm is used to improve sterilization efficiency with respect to bacteria or microorganisms.

(186) Although the sterilizing apparatus according to the embodiments employs the UV light emitting diode **120** configured to emit UV light having a peak wavelength in a wavelength band slightly deviating from a wavelength of 253 nm, which is the best absorption wavelength for human DNA, UV light emitted from the UV light emitting diode **120** is still detrimental to humans. Therefore, there is a need for a safety device for allowing UV irradiation of the sterilizing apparatus only in the case of sterilization.

(187) As shown in FIG. **24**, the sterilizing apparatus according to the present invention is provided with a plurality of detection units detecting different factors. Since the sterilizing apparatus according to the embodiments can employ deep UV light, the sterilizing apparatus requires a safety device which allows operation of the sterilizing apparatus for UV irradiation only when all environments measured by the plurality of detection units satisfy all conditions for use of the sterilizing apparatus.

(188) For example, since the sterilizing apparatus according to the embodiments acts as a lid for covering the drain hole of the sink to block external light (visible light), it can be defined that a region where sterilization is performed is in a dark state. In addition, upon sterilization, the drain hole of the sink is placed to allow the outer surface of the housing to face in the direction of gravity. Further, upon sterilization of the drain hole, a front side of the sterilizing apparatus is not separated a distance of 20 cm or more (depth of the drain hole) from the outer surface of the housing.

(189) For measurement under such an environment, in the sterilizing apparatus according to the present invention, the detection unit **140** may be placed near the UV light emitting diode **120** mounted on the substrate **70**. The detection unit **140** includes an illuminance sensor for detecting visible light entering the housing through the irradiation opening **11**. The illuminance sensor is provided to check whether the environment for use of the sterilizing apparatus is a dark environment.

(190) However, this structure alone has limitations in guaranteeing a suitable environment for use of the sterilizing apparatus. For example, if the dark environment is obtained by turning off all lights in a room, the illumination sensor alone cannot guarantee the suitable environment for use of the sterilizing apparatus.

(191) Therefore, in the sterilizing apparatus according to the present invention, the detection unit **140** disposed on the substrate **70** may further include a distance sensor (for example, an IR sensor). The distance sensor of the detection unit measures a distance of an object in front of the outer surface of the housing through the irradiation opening **11**. If the measured distance is greater than a reference distance (the distance that the object is placed in front of the housing upon normal sterilization), it can be determined that the sterilizing apparatus is not in an environment suitable for use.

(192) In addition, the sterilizing apparatus according to the present invention may further include a posture sensor (for example, a gyro sensor or a tilt sensor). Since the sterilizing apparatus according to the present invention is used in the form of a lid, the housing of the sterilizing apparatus faces the floor under normal use conditions (see FIG. **27**) Therefore, if it is detected that the sterilizing apparatus does not face the floor, it can be determined that the sterilizing apparatus is not in the environment suitable for use.

(193) According to the present invention, the substrate **70** may have a control circuit that enables power supply to the UV light emitting diode only when all of conditions measured by the plurality of sensors for measuring such various environments satisfy safety standards.

(194) It should be noted that operation of turning on or off the UV light emitting diode **120** is primarily controlled by the switch **170** and, even when the switch **170** is switched on, power supply to the UV light emitting diode **120** is interrupted in the case where all of the conditions measured by the plurality of sensors do not satisfy the safety standards.

(195) The sterilizing apparatus according to the present invention further includes a visible light emitting diode **190** which is disposed near the switch **170** and is connected in series to the UV light emitting diode to be turned on or off together with the UV light emitting diode. The visible light emitting diode may be used to confirm, by the naked eye, whether the UV light emitting diode is turned on. In this way, when the visible light emitting diode is connected in series to the UV light emitting diode, the visible light emitting diode **190** and the UV light emitting diode **120** are turned on or off at the same time. Accordingly, a user can conveniently determine whether the sterilizing apparatus is operated by checking with the naked eye whether the visible light emitting diode is turned on or off. In the structure wherein the visible light emitting diode is connected in series to the UV light emitting diode, if either the UV light emitting diode or the visible light emitting diode fails, both the UV light emitting diode and the visible light emitting diode do not operate when the visible light emitting diode is not turned on due to failure of the visible light emitting diode. Therefore, it can be ensured that the UV light emitting diode also does not operate if the visible light emitting diode is not turned on.

(196) Sterilization may be performed by UV light or by removing moisture to create a dry environment. In the present invention, a far infrared light source may be further disposed on the substrate **70** to realize both UV irradiation and a drying function. The far infrared light source can further increase the sterilizing effect by drying a sterilization region by emitting far infrared rays to the sterilization region through the irradiation opening **11**.

(197) Referring to FIG. **20** to FIG. **23**, a housing O-ring **58** is press-fitted into a housing O-ring receiving groove **18** formed along a contact portion between the housing **10** and the cover body **110** facing each other when the housing **10** and the cover body **110** are fastened to each other. As described above, water tightness can be secured not only around the irradiation opening **11** but also at the contact portion between the housing **10** and the cover body **110**, thereby ensuring waterproofing of the interior space in the housing **10** and the cover body **110** fastened to each other. The sterilizing apparatus according to the present invention requires a sufficient degree of waterproofing to prevent water from entering the sterilizing apparatus, for example, when tap water is accidentally supplied to the sink.

(198) In order to fasten the housing **10** to the cover body **110**, a fastening screw (not shown) is fitted from the outer surface of the housing **10** into the cover body **110**, as shown in the drawings. Then, the fastening screw is screwed to the cover body through a fastening hole **380** of the housing. In addition, a support member **80** is provided to the outer surface of the housing **10** on which the fastening hole **380** is formed. The support member **80** is formed of, for example, a rubber-like elastic material that can achieve both a slipping prevention effect and a sealing effect, thereby prevent water from penetrating through the fastening hole **380** and allowing the sterilizing apparatus to be maintained in place without slipping on a surface on which the sterilizing apparatus is placed.

(199) In the present invention, a power source for operating the UV light emitting diode may be supplied from the power supply **130** embedded in the sterilizing apparatus. For example, the power supply **130** is a secondary battery. The power supply **130**, the substrate **70**, and the switch **170** are electrically connected to one another inside the cover body **110** and the housing **10**. In addition, the power supply **130** is electrically connected to a charging terminal **97**. Here, the charging terminal **97** is a path through which power is supplied from an external power source to charge the power supply **130**. An inlet of the charging terminal **97** is exposed to the outside of the cover body **110** and the housing **10** and a watertight cap is detachably fitted to the inlet of the charging terminal **97**. Thus, during charge of the power supply **130**, the charging terminal **97** may be connected to an

external power source after removing the watertight cap from the inlet thereof. According to this embodiment of the present invention, the sterilizing apparatus has the structure wherein the charging terminal is secured outside the housing O-ring **58** in order to secure additional water tightness with respect to the interior region between the cover body **110** and the housing **10** and a portion to be protected from water on the charging terminal is covered by silicone, as shown in the drawings. With this structure, when water permeates towards the charging terminal not covered by the watertight cap, the water is prevented from entering the interior region between the cover body **110** and the housing **10**. Thus, there is no need to dry other components except the charging terminal.

(200) The sterilizing apparatus according to the present invention may be used in sterilization of various objects. For example, even the drain hole of the sink may have different specifications (diameters). In consideration of this point, the sterilizing apparatus according to the present invention includes an alignment protrusion **390** formed on the outer surface of the housing **10**, as shown in FIG. **27**. The sterilizing apparatus may include a plurality of alignment protrusions **390** concentrically arranged on the outer surface of the housing **10** at locations of different diameters **r1**, **r2** with respect to the irradiation opening. The alignment protrusions may be provided in the form of an annular ring centered on the UV irradiation opening, a part of the annular ring, or a set of points located on the annular ring. These diameters **r1** and **r2** can be determined corresponding to the diameter of a drain hole of available sinks.

(201) The sterilizing apparatus according to the present invention may also be used to sterilize the interior of each of various containers after being placed on a lid of the corresponding container. For example, sterilization may be performed after placing the sterilizing apparatus at an entrance of a cup or tumbler that is too deep for the hand of a user to reach into.

(202) The sterilizing apparatus according to the present invention may further include a holder **30**, as shown in the drawings. The holder has a hollow cylindrical shape having a low height and blocked at a side surface thereof, and includes a vent hole **31** formed in a bottom surface and a plurality of legs **32** extending below the bottom surface to allow smooth communication with external air through the vent hole.

(203) In order to dry and sterilize a scrubber after dish washing, the scrubber may be sterilized using the sterilizing apparatus after placing the sterilizing apparatus on the holder **30**, with the scrubber placed inside the holder **30**. In addition, not only kitchen utensils such as scrubbers but also objects having a size to be received in the holder can be sterilized using the sterilizing apparatus.

(204) The sterilizing apparatus according to the present invention may also be used for sterilization not only of the drain hole of the sink but also various other objects. For example, in sterilization of a tumbler **35** or a pot **38** which requires internal sterilization, the tumbler **35** or the pot **38** is covered by the sterilizing apparatus instead of a lid, as shown in FIG. **31** and FIG. **32**.

(205) Next, operation of the sterilizing apparatus according to the present invention will be described.

(206) A user places the sterilizing apparatus on the holder **30** or puts it on the floor and charges the power supply **130** by connecting an external power source thereto through the charging terminal **97**. The degree of charge is indicated by a color of the visible light emitting diode **190**. After charging the power supply, the sterilizing apparatus with the watertight cap fitted into the charging terminal **97** is placed on a drain hole of a sink. At this time, the center of the sterilizing apparatus can be efficiently aligned with the center of the drain hole by the alignment protrusions **390** protruding toward the floor, and the sterilizing apparatus is fixed in place by the support member **80** without slipping.

(207) FIG. **33** is a flowchart illustrating operation of the sterilizing apparatus according to the embodiment of the present invention.

(208) When a user presses the switch **170**, the control circuit on the substrate **70** checks

environmental measurement results of various sensors. That is, under conditions wherein illuminance of visible light measured by the illuminance sensor is lower than a reference value, an object is detected within a predetermined distance from the irradiation opening by the distance sensor, and the sterilizing apparatus emits UV light in the downward direction (that is, the sterilizing apparatus is horizontally well placed), power is supplied to the UV light emitting diode **120** by the control circuit. When there is no abnormal operation of both the UV light emitting diode **120** and the visible light emitting diode **190**, the visible light emitting diode **190** is also turned on together with the UV light emitting diode **120**, whereby a user can confirm whether the sterilizing apparatus is operating.

(209) The sterilizing apparatus operates as a timer. For example, after power is supplied to the UV light emitting diode for a sufficient period of time for sterilization, the power source is interrupted again to turn off the sterilizing apparatus. Experimental results showed that the sterilizing apparatus according to the embodiment of the present invention secured 259.9% of sterilization even when the sterilizing apparatus was operated for about 30 to 40 minutes. When a time set by the timer has elapsed, the visible light emitting diode **190** blinks. The visible light emitting diode may be turned off after blinking several times, or may continue to blink until a user confirms that the time set by the timer has elapsed.

(210) If the sterilizing apparatus is inadvertently struck or raised before the time set by the timer elapses, at least one of the sensors detects that the use environment is out of safety conditions and power supply is immediately shut off. Of course, even in the case where the time set by the timer time has not elapsed, the power supplied to the UV light emitting diode is immediately shut off when a user switches off the sterilizing apparatus.

(211) In this way, the sterilizing apparatus can improve quality of life through sterilization around the drain hole of the sink by inhibiting reproduction of bacteria or fungi while removing odors. In addition, sterilization of other products can also be performed using the holder and the like by the method as described above.

(212) Although some exemplary embodiments have been described herein, it should be understood by those skilled in the art that these embodiments are given by way of illustration only, and that various modifications, variations, and alterations can be made without departing from the spirit and scope of the present invention. In addition, although advantageous effects provided by a certain configuration are not clearly described in description of the exemplary embodiments, it should be noted that expectable effects of the corresponding configuration should be acknowledged.

Claims

1. A light emitting apparatus, comprising; a housing comprising an outer surface facing a target and an inner surface opposite to the outer surface; a light source disposed on a substrate in the housing and configured to emit light toward the target, an irradiation opening configured to pass the light emitted from the light source; and a power supply configured to supply power to the light source, wherein the light source includes a first light emitter configured to emit having a peak wavelength in UV light range, wherein the first light emitter is disposed on the substrate and aligned with the irradiation opening while facing the irradiation opening, and wherein the irradiation opening has a diameter allowing at least 50% of light emitted from the first light emitter to pass therethrough.
2. The light emitting apparatus of claim 1, wherein the light source further comprises a light transmissive window including a material through which deep UV light emitted from the light source is transmitted.
3. The light emitting apparatus of claim 1, further comprising; a reflector disposed on the housing and including a material having a reflectivity to reflect the light emitted from the first light emitter.
4. A light emitting apparatus, comprising; a housing comprising an outer surface facing a target and an inner surface opposite to the outer surface; a light source disposed on a substrate in the housing

and configured to emit light toward the target, an irradiation opening configured to pass the light emitted from the light source; and a power supply configured to supply power to the light source, wherein the light source includes a first light emitter configured to emit light to inactivate a pathogen, wherein the first light emitter is disposed on the substrate and aligned with the irradiation opening while facing the irradiation opening, and wherein the irradiation opening has a diameter allowing at least 50% of light emitted from the first light emitter to pass therethrough.

5. The light emitting apparatus of claim 4, wherein the light source further comprises a light transmissive window including a material through which deep UV light emitted from the light source is transmitted.

6. The light emitting apparatus of claim 4, further comprising a reflector disposed on the housing and including a material having a reflectivity to reflect the light emitted from the first light emitter.

7. A light emitting apparatus comprising; a housing comprising an outer surface facing a target and an inner surface opposite to the outer surface; a light source disposed on the housing and configured to emit toward the target, an irradiation opening configured to pass the light emitted from the light source; and a power supply configured to supply power to the light source, wherein the light source includes a first light emitter configured to emit light, wherein the first light emitter is disposed on a substrate of the housing and aligned with the irradiation opening while facing the irradiation opening, and wherein the irradiation opening has a diameter allowing at least 50% of the light emitted from the first light emitter to pass therethrough.

8. The light emitting apparatus of claim 7, wherein the light source further comprises a light transmissive window including a material through which UV light emitted from the light source is transmitted.

9. The light emitting apparatus of claim 1, wherein the light source further includes a second light emitter configured to emit light having a different peak wavelength from the peak wavelength of the first light emitter.

10. The light emitting apparatus of claim 9, wherein the second light emitter is configured to be turned on simultaneously with the first light emitter such that the first light emitter and the second light emitter operate together.

11. The light emitting apparatus of claim 1, wherein the irradiation opening has an irradiation opening-enlarged portion having a cross-section gradually widening along a direction away from the light source.

12. The light emitting apparatus of claim 1, wherein the first light emitter is configured to emit the light at a dose between 5 mJ/cm.^{sup.2} and 20 mJ/cm.^{sup.2} to inactivate a pathogen including *E. coli* that is included in the target.

13. The light emitting apparatus of claim 1, wherein the first light emitter is configured to emit the light at a dose between 7 mJ/cm.^{sup.2} and 20 mJ/cm.^{sup.2} to inactivate a pathogen including *Staphylococcus aureus* that is included in the target.

14. The light emitting apparatus of claim 4, wherein the irradiation opening has an irradiation opening-enlarged portion having a cross-section gradually widening along a direction away from the light source.

15. The light emitting apparatus of claim 4, wherein the first light emitter is configured to emit the light at a dose between 5 mJ/cm.^{sup.2} and 20 mJ/cm.^{sup.2} to inactivate a pathogen including *E. coli* that is included in the target.

16. The light emitting apparatus of claim 4, wherein the first light emitter is configured to emit the light at a dose between 7 mJ/cm.^{sup.2} and 20 mJ/cm.^{sup.2} to inactivate a pathogen including *Staphylococcus aureus* that is included in the target.

17. The light emitting apparatus of claim 4, wherein light source further includes a second light emitter configured to emit light having a different peak wavelength from a peak wavelength of the first light emitter.

18. The light emitting apparatus of claim 7, wherein light source further includes a second light

emitter and the second light emitter emits light having a different peak wavelength from a peak wavelength of the first light emitter.

19. The light emitting apparatus of claim 18, wherein the second light emitter is configured to be turned on simultaneously with the first light emitter such that the first light emitter and the second light emitter operate together.

20. The light emitting apparatus of claim 7, wherein the irradiation opening has an irradiation opening-enlarged portion having a cross-section gradually widening along a direction away from the light source.
