

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403247
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Yang; Cuijun

Drug infusion device

Abstract

This invention discloses a drug infusion device, including: a drug storage unit; a piston and a driving wheel respectively connected with a screw, the driving wheel drives the screw to move by rotation, the piston is arranged in the drug storage unit, the screw advances the piston to move; a driving unit cooperating with the driving wheel, the driving unit includes more than two driving arms, the driving unit, through the multiple pivoting movement modes, drives driving arms to perform tooth number adjustable driving on the driving wheel for increment-adjustable infusion; and a power unit connected to the driving unit, the power unit exerts a force on the driving unit to lead the driving unit to perform a plurality of pivot steps. More than two driving arms are stalled on the driving unit, thereby achieving multi-level engagement on the driving wheel, and finally achieving the purpose of increment-adjustable infusion.

Inventors:	Yang; Cuijun (Shanghai, CN)
Applicant:	MEDTRUM TECHNOLOGIES INC. (Shanghai, CN)
Family ID:	73336493
Assignee:	MEDTRUM TECHNOLOGIES INC. (Shanghai, CN)
Appl. No.:	17/432096
Filed (or PCT Filed):	May 17, 2019
PCT No.:	PCT/CN2019/087342
PCT Pub. No.:	WO2020/232565
PCT Pub. Date:	November 26, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220339763 A1	Oct. 27, 2022

Publication Classification

Int. Cl.: A61M5/142 (20060101); A61B5/00 (20060101); A61M5/145 (20060101); A61M5/158 (20060101); A61M5/168 (20060101); A61M5/172 (20060101); A61M5/36 (20060101); B25B13/46 (20060101); B25B21/00 (20060101); B25B23/00 (20060101)

U.S. Cl.:

CPC A61M5/14248 (20130101); A61B5/4839 (20130101); A61M5/14216 (20130101); A61M5/1452 (20130101); A61M5/158 (20130101); A61M5/1684 (20130101); A61M5/16877 (20130101); A61M5/172 (20130101); A61M5/36 (20130101); B25B13/463 (20130101); B25B21/005 (20130101); A61B2560/0209 (20130101); A61B2562/043 (20130101); A61M2005/14208 (20130101); A61M2005/14252 (20130101); A61M2005/14268 (20130101); A61M2005/14533 (20130101); A61M2205/3317 (20130101); A61M2205/3576 (20130101); A61M2205/50 (20130101); B25B23/0078 (20130101)

Field of Classification Search

CPC: A61M (2005/14533); A61M (5/3156); A61M (2005/14506); A61M (5/31561); A61M (5/31548); A61M (5/31556); B25B (21/005); B25B (23/0078)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2003/0199824	12/2002	Mahoney	604/155	A61M 5/1452
2003/0236498	12/2002	Gross	604/141	A61M 5/14216
2004/0153032	12/2003	Garribotto et al.	N/A	N/A
2005/0238507	12/2004	Dilanni	417/415	F04B 9/08
2019/0117881	12/2018	Yang	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101208515	12/2007	CN	N/A
102600526	12/2011	CN	N/A
106999670	12/2016	CN	N/A
207627685	12/2017	CN	N/A
208049137	12/2017	CN	N/A
108939203	12/2017	CN	N/A
2014166889	12/2013	WO	N/A

OTHER PUBLICATIONS

“Search Report of Europe Counterpart Application”, issued on Nov. 10, 2022, pp. 1-8. cited by applicant

“International Search Report (Form PCT/ISA/210) of PCT/CN2019/087342,” mailed on Sep. 2, 2019 , with English translation thereof, pp. 1-4. cited by applicant

Primary Examiner: Fredrickson; Courtney B

Assistant Examiner: Turkowski; Kayla M.

Attorney, Agent or Firm: JCIP GLOBAL INC.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application is a 371 of international application of PCT application serial no. PCT/CN2019/087342, filed on May 17, 2019. The entirety of the above mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

(2) The present invention mainly relates to the field of medical instruments, in particular to a drug infusion device.

Description of Related Art

(3) A drug infusion device is a medical device that achieves treatment of a patient's physiological condition by continuously injecting a drug into a patient. Drug infusion devices are widely used for the treatment of diabetes, allowing required doses of insulin to be continuously infused into the subcutaneous tissue of the patient's body, thereby simulating the secretion function of the pancreas, thereby keeping the patient's blood sugar stable. The drug fluid is usually stored inside the infusion pump. The existing drug infusion device usually attaches the pump body directly to the patient's body through a medical adhesive tape, and the patient operates a remote device to control infusion.

(4) In the case of drug infusion, the current infusion devices can only operate with one level of increment, the infusion process cannot be flexibly controlled, and the infusion efficiency is relatively low. Moreover, the minimum dose that can be infused each time is relatively large, which can cause the concentration of some substance(s) in a patient's body fluid to fluctuate greatly under the control of the infused drug, and cannot achieve the purpose of more accurately controlling the concentration of that substance(s).

(5) Therefore, there is a need in the prior art for a drug infusion device that can flexibly control a drug infusion process and improve drug infusion efficiency.

SUMMARY

(6) The embodiment of the invention discloses a drug infusion device, which is provided with more than two driving arms on the driving unit, thereby realizing tooth number adjustable driving on the driving wheel, and finally achieving the purpose of increment-adjustable infusion and more flexible control. The multi-mode driving improves the efficiency of the infusion.

(7) The invention discloses a drug infusion device, including: a drug storage unit; a piston and a driving wheel respectively connected with a screw, the driving wheel drives the screw movement by rotation, the piston is arranged in the drug storage unit, the screw advances the piston to move; a driving unit cooperating with the driving wheel, the driving unit includes more than two driving arms, the driving unit, through the its own adjustable movement, drives driving arms to rotate the driving wheel by an optional number of gear teeth, resulting in increment-adjustable infusion; and a power unit connected to the driving unit, the power unit exerts a force on the driving unit to lead the driving unit to perform adjustable pivoting movements.

(8) According to an aspect of the invention, the adjustable pivoting movements of the driving unit includes: after pivoting by an optional number of degrees in one direction in a single time, the driving unit starts pivoting by an optional number of degrees in another direction until the end of

the pivoting in this direction, the driving unit completes pivoting in both directions to drive the driving wheels to rotate by an optional number of gear teeth.

(9) According to an aspect of the invention, the driving wheel includes a plurality of sub-wheels, the circumferential surface of the sub-wheel being provided with gear teeth, and the driving arms drive the driving wheel by engaging gear teeth.

(10) According to an aspect of the invention, a plurality of driving arms are respectively installed on both sides of the driving unit.

(11) According to an aspect of the invention, when driving arms on one side of the driving unit engage the gear teeth, the lines representing the engaging directions of the plurality of driving arms on this side intersect each other.

(12) According to an aspect of the invention, two driving arms are installed on each side of the driving unit, and two driving arms on the same side of the driving unit are installed up and down, or are installed left and right.

(13) According to an aspect of the invention, the two driving arms on the same side of the driving unit are installed up and down, and when driving arms on one side of the driving unit engage the gear teeth, the angle between the two driving arms on the driving direction is α , $0^\circ \leq \alpha \leq 7^\circ$.

(14) According to an aspect of the invention, $3.1^\circ \leq \alpha \leq 4.1^\circ$.

(15) According to an aspect of the invention, $\alpha = 3.5^\circ$.

(16) According to an aspect of the invention, the horizontal distance between the driving ends of the two driving arms on one side of the driving unit is h , the pitch of the gear teeth is s , $0.1 s \leq h \leq 2.5 s$.

(17) According to an aspect of the invention, $0.5 s \leq h \leq 1.5 s$.

(18) According to an aspect of the invention, the gear teeth are ratchet teeth, and during the whole process of the driving unit pivoting in one direction, the driving unit alternately pivots and stalls in an adjustable way to drive driving arms to alternately engage and stop engaging the ratchet teeth, so that the driving wheel alternately rotates and stops rotation to realize tooth number adjustable rotation.

(19) According to an aspect of the invention, when the driving unit drives the driving wheel, at least one of the driving arms on the side on which the driving force is applied engages the gear teeth, and the driving arms on the other side of the driving unit does not apply a force to the gear teeth to rotate the driving wheel.

(20) According to an aspect of the invention, the plurality of movement modes of the driving unit include a large movement mode and a small movement mode, and when the infusion is performed, the driving unit can switch between the large movement mode and the small movement mode to realize increment-adjustable infusion.

(21) According to an aspect of the invention, the plurality of movement modes of the driving unit further include one or more intermediate movement modes, wherein the intermediate movement mode is between the large movement mode and the small movement mode, and the driving unit can switch among the large movement mode, the intermediate movement mode and the small movement mode to achieve increment-adjustable infusion.

(22) Compared with the prior art, the technical solution of the present invention has the following advantages:

(23) In the drug infusion device disclosed by the present invention, the driving unit includes more than two driving arms, the driving unit, through the adjustable pivoting movements, drives driving arms to perform tooth number adjustable driving on the driving wheel for increment-adjustable infusion. When more than two driving arms are installed on the driving unit, the driving unit cooperates with the driving wheel to realize adjustable rotation: the driving arm driving the driving wheel to rotate by an optional number of teeth, thereby realizing increment-adjustable infusion of drug, which makes the infusion process more flexible and controllable and significantly improves the efficiency of drug infusion. At the same time, it also reduces the minimum drug infusion

amount, accurately controls the process of the drug infusion, effectively avoids large fluctuations of concentration of some substance(s) in patient's body fluid and enables the patients to control and manage their physiological condition more precisely.

(24) Furthermore, adjustable pivoting movements of the driving unit includes: after pivoting by an optional number of degrees in one direction in single time, the driving unit starts pivoting by an optional number of degrees in another direction until the end of the pivoting in this direction, the driving unit completes an alternate pivot in both directions. When a plurality of pivot modes are available, one of the pivot modes can be selected for the driving unit according to actual needs, driving the driving wheel to rotate by an optional number of teeth, thereby realizing the increment-adjustable infusion of the device, and allowing the patient to control the infusion process more flexibly.

(25) Furthermore, a plurality of driving arms are installed on each side of the driving unit. Multiple driving arms on both sides can better achieve adjustable pivot of the driving unit.

(26) Furthermore, in the solution of the present invention, when driving arms on one side of the driving unit engage the teeth, the plurality of driving arms on this side intersect in a line in which the engaging direction is located. Since the circumferential surface of the driving wheel has a circular arc shape as a whole, the engaged tooth faces of the adjacent gear teeth are not parallel to each other, and the intersection of the plurality of driving arms on one side in engaging direction can ensure the engaging direction is perpendicular to the tooth engaging surface, which improves the efficiency of engaging.

(27) Furthermore, in the solution of the present invention, the teeth are ratchet teeth. Using of ratchet teeth can effectively prevent the driving wheel from being reversed cooperating with the driving arms. In addition, during the whole process of the driving unit pivoting in one direction, the driving unit alternately pivots and stops in an adjustable way to drive the driving arms to alternately engage and stop engaging the ratchet teeth, so that the driving wheel alternately rotates and stops rotation to perform tooth number adjustable driving on the driving wheel. In a single rotation in one direction, the driving unit's adjustable pivoting helps delivering the infused drug in several steps by means of a pivot-stop-pivot-stop- . . . alternating method to achieve accurate infusion.

(28) Furthermore, multiple-gear positions of the driving unit include large gear position and small gear position. Patients can freely choose and switch large gear position or small gear position infusion according to the actual infusion volume and infusion rate requirements, making the infusion process more flexible and controllable, greatly improving the infusion efficiency.

(29) Furthermore, a plurality of movement modes of the driving unit further include one or more intermediate movement modes. Setting intermediate movement modes provides more infusion options for the patient and the patient's control of the infusion process is more flexible.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a top view showing structure of a drug storage unit, a piston, a screw, a driving unit, a power unit, and a driving wheel in a drug infusion device according to an embodiment of the present invention.

(2) FIG. 2a-FIG. 2c are respectively a perspective view of a three-dimensional structure, a side view and a top view of a driving unit in a drug infusion device according to an embodiment of the present invention.

(3) FIG. 3a-FIG. 3b are a schematic perspective view of a driving unit of a drug infusion device according to another embodiment of the present invention.

(4) FIG. 4 is a perspective view showing the structure of a driving unit in a drug infusion device

according to another embodiment of the present invention.

(5) FIG. 5 is a perspective view showing the structure of a driving unit in a drug infusion device according to another embodiment of the present invention.

(6) FIG. 6 is a partial structural view of a driving wheel in a drug infusion device according to an embodiment of the present invention.

(7) FIG. 7 is a schematic structural view of a driving unit pushing a driving wheel in a drug infusion device according to an embodiment of the present invention.

(8) FIG. 8 is a schematic structural view showing a pivoting position of different movement modes of a driving unit in a drug infusion device according to an embodiment of the present invention.

DESCRIPTION OF THE EMBODIMENTS

(9) As previously mentioned, prior art infusion devices have only one un-adjustable infusion mode and do not have the flexibility to control the infusion process.

(10) It has been found through research that the above mentioned problems are caused by the fact that the prior art drug infusion device can only drive the driving wheel to rotate in an unadjustable way, and cannot repeat the rotate-stop process for multiple times in a single period, which results in a relatively simple control of the infusion process in the prior art.

(11) In order to solve this problem, the present invention provides a drug infusion device in which a driving unit is pivoted in an adjustable way to perform tooth-number adjustable driving on the driving wheel. The different options of increment allow patients to flexibly control the drug infusion process. At the same time, the minimum drug infusion amount of the infusion device is effectively reduced, and the fluctuation of concentration of some substance(s) in patient's body fluid is mitigated.

(12) Various exemplary embodiments of the present invention will now be described in detail with reference to the drawings. The relative arrangement of the components and the steps, numerical expressions and numerical values set forth in the embodiments are not to be construed as limiting the scope of the invention.

(13) In addition, it should be understood that, for ease of description, the dimensions of the various components shown in the figures are not necessarily drawn in the actual scale relationship, for example, the thickness, width, length or distance of certain units may be exaggerated relative to other structures.

(14) The following description of the exemplary embodiments is merely illustrative, and is not intended to be in any way limiting the invention and its application or use. The techniques, methods and devices that are known to those of ordinary skill in the art may not be discussed in detail, but such techniques, methods and devices should be considered as part of the specification.

(15) It should be noted that similar reference numerals and letters indicate similar items in the following figures. Therefore, once an item is defined or illustrated in a drawing, it will not be discussed further in the following description of the drawings.

(16) FIG. 1 is a top view showing the structure of a drug infusion device according to an embodiment of the present invention. The drug infusion device includes a driving unit **100**, a driving wheel **130**, a drug storage unit **150**, a piston **160**, a screw **170**, and a power unit **180**.

(17) The screw **170** is coupled to the piston **160** and the driving wheel **130**, respectively. In the embodiment of the present invention, the driving wheel **130** is movably mounted on the device base (not shown), and the driving wheel **130** moves the driving screw **170** through rotation to advance the piston **160** disposed in the drug storage unit **150** to move forward for the purpose of injecting drugs.

(18) The driving unit **100** is used to drive the driving wheel **130** to rotate. The driving unit **100** is movably connected to the device base through the pivot shaft **120**. The power unit **180** is used to apply a force to the driving unit **100** to lead the driving unit **100** pivot. In the embodiment of the present invention, the power unit **180** is fixedly connected at the top position of the driving unit **100**, thereby dividing the power unit **180** into two left and right portions, such as the A' direction

portion and the B' direction portion in FIG. 1. The driving unit **100** is alternately led to pivot in the A' direction or the B' direction through the pivot shaft **120**. Specifically, in the embodiment of the present invention, when the power unit **180** leads the driving unit **100** in the A' direction, the driving unit **100** pivots in the A direction through the pivot shaft **120**. When the power unit **180** leads the driving unit **100** in the B' direction, the driving unit **100** pivots in the B direction through the pivot shaft **120**. By alternately leading the driving unit **100** in the A' direction and the B' direction, the driving unit **100** can be alternately pivoted through the pivot shaft **120** in the A direction and the B direction.

(19) Specifically, in the embodiment of the present invention, the power unit **180** is a shape memory alloy. The A' direction portion and the B' direction portion of the shape memory alloy are alternately powered on and off, and a leading force is applied to the driving unit **100** by a change in the length of the power unit **180** thereof. The power unit **180** may be composed of one piece of shape memory alloy, or may be composed of left and right segments (such as the A' direction segment and the B' direction segment) of shape memory alloy, and is not specifically limited herein, as long as the force can be applied to lead the driving unit **100** pivot.

(20) Here, it should be noted that the power unit **180** includes but is not limited to a shape memory alloy. In other embodiments of the present invention, the power unit **180** may also be other structures, and the location where the power unit **180** applies force to the driving unit **100** is also not limited to the top position **140**, as long as the action of applying a force to the driving unit **100** can be satisfied to cause the driving unit **100** to alternately pivot left and right.

(21) Referring to the perspective view of the driving unit **100** shown in FIG. 2a, the driving unit **100** further includes more than two driving arms **110**. The driving wheel **130** includes a plurality of sub-wheels, and the circumferential surface of the sub-wheels is provided with gear teeth **131** (as shown in FIG. 6 and FIG. 7 below). Referring to the structure shown in FIG. 1 and FIG. 2a, when a plurality of driving arms **110** are installed on one side of the driving unit **100**, the driving unit **100** can drive the driving arms **110** to engage the gear teeth **131** through adjustable pivoting to rotate the driving wheel **130** by an optional number of teeth. Thus, in an embodiment of the invention, driving unit **100** and driving wheel **130** are designed to work compatibly, which means that the position of the driving wheel **130** and the number of the sub-wheels need to be compatible with the working principle of the driving unit **100** and the number, position and structure of the driving arms **110**.

(22) As shown in FIG. 1 and FIG. 2a, in the embodiment of the present invention, a plurality of driving arms **110** are installed on each side of the driving unit **100**. Therefore, a plurality of sub-wheels are also installed on both sides of the driving unit **100** to cooperate with the driving arms **110**. Specifically, in the embodiment of the present invention, the driving unit **100** includes four driving arms **110**, which are **110a**, **110b**, **110c**, and **110d**, respectively. **110a**, **110b** are installed on one side of the driving unit **100**, while **110c**, **110d** are installed on the other side of the driving unit **100**. The driving wheel **130** includes two sub-wheels, one of which cooperates with **110a**, **110b** and the other of which cooperates with **110c**, **110d**.

(23) It should be noted that the driving wheel **130** may further include more than two sub-wheels. For example, according to the design of the position and structure of the plurality of driving arms **110**, two adjacent sub-wheels may be set on one side of the driving unit **100** to cooperate with different positions, numbers of driving arms **110** on this side of the driving unit **100**.

(24) FIG. 2a, FIG. 2b, and FIG. 2c are respectively a schematic view of a three-dimensional, a side view, and a top view of the driving unit **100**, and the top view direction of FIG. 2c is the direction indicated by the arrow in FIG. 2b, while the side view direction of FIG. 2b is the direction shown by the arrow in FIG. 2c.

(25) In the embodiment of the present invention, the two driving arms **110** on one side of the driving unit **100** are installed up and down. Here, the up and down settings refer to the up and down positional relationship representations shown in FIG. 2b. Specifically, the two driving arms **110**

(such as **110a** and **110b**) on the side of the driving unit **100** can be seen in the side view FIG. **2b**, and in the top view FIGS. **2c**, **110b** and **110d** are blocked by **110a** and **110c**, respectively, wherein **110b** and **110d** are indicated by dotted lines in FIG. **2c**.

(26) In the embodiment of the present invention, since the driving wheel **130** is circular, the surfaces on which the adjacent teeth are applied with the engaging force are not parallel. Therefore, in order to keep the angle between the driving arms **110** and the teeth engaging surface 90 degree during engaging, thereby improving the engaging efficiency of the driving arms **110**, when the driving arms **110** on one side of the driving unit **100** engage the gear teeth **131**, the lines representing the engaging directions of the two driving arms **110** intersect each other. Specifically, as shown in FIG. **2b**, when the gear teeth **131** are engaged by **110a** and/or **110b**, the straight line where **110a** is located is 11, the straight line where **110b** is located is 12, wherein the angle between 11 and 12 is α , $3.1^{\circ} \leq \alpha \leq 4.1^{\circ}$. Specifically, in the embodiment of the present invention, $\alpha = 3.5^{\circ}$. In another embodiment of the invention, $\alpha = 3.3^{\circ}$. In still another embodiment of the invention, $\alpha = 3.9^{\circ}$.

(27) It should be noted that, in other embodiments of the present invention, according to different structural designs, when the driving arms **110** on one side of the driving unit **100** engage the gear teeth **131**, the lines representing the engaging directions of these two driving arms **110** can also be parallel ($\alpha = 0^{\circ}$) or skew with a structure also able to drive the driving wheel **130** to rotate to achieve the purpose of drug infusion. In this case, the angle α between 11 and 12 may be set according to the actual structure, such as according to the diameter, number of the driving wheels **130**, the number of the gear teeth **131**, the pitch of the screw **170**, the positional relationship and the number of the driving arms **110**. For example, α may be between $0^{\circ} \sim 3.1^{\circ}$ or $4.1^{\circ} \leq \alpha \leq 7^{\circ}$, and is not specifically limited herein.

(28) As shown in the dotted portion **10** of FIG. **2a** and FIG. **2b**, in the embodiment of the present invention, the two driving arms **110** on one side of the driving unit **100** are formed by folding at the dotted circle **10**. In other embodiments of the present invention, the two driving arms **110** on one side of the driving unit **100** may also be formed by other means. As shown in the perspective view of the driving unit **200**, **300** shown in FIG. **3a** and FIG. **3b**, the up position **210a**, **210c**, **310a**, **310c** and the down position **210b**, **210d**, **310b**, **310d** are respectively set in different structural subunits. As in FIG. **3a**, the two structural subunits are secured together by welding or other means of attachment to form one single structure. And as shown in FIG. **3b**, the two structural subunits are connected at the top position **340** of the driving unit **300**, and then the top position **340** of the driving unit **300** is folded over to form the structure of the driving arms **310** in the embodiment of the present invention. In addition, the driving units **200**, **300** pivot around the pivot shafts **220**, **320**, respectively.

(29) It should be noted that, in other embodiments of the present invention, the driving arms may be formed by other means, as long as the arms are able to drive the driving wheel to rotate, and is not specifically limited herein.

(30) Please refer to FIG. **4**, which is a top view of a driving unit **400** according to another embodiment of the present invention. In addition, the driving unit **400** pivots around pivot shaft **420**.

(31) The angles of view of FIG. **4** and FIG. **2c** are the same. According to FIG. **2a**, FIG. **2b**, FIG. **2c** and FIG. **4**, it is apparent that the two driving arms on one side of the driving unit **400** are slightly offset from left and right, such as **410a**, **410b** and **410c**, **410d**. Specifically, in one embodiment of the invention, **410a** and **410c** are offset to the right and **410b** and **410d** are offset to the left.

(32) It should be noted that, in other embodiments of the present invention, the left and right offset degree of the two driving arms on the same side and the direction in which the two are offset relative to each other need to be determined according to the actual structural design, and are not limited specifically described herein. Furthermore, in an embodiment of the invention, the two driving arms on one side of the driving unit can also be installed left and right. Here, the left and

right installing mean that from the perspective of FIG. 4 (top view), two complete driving arms on one side of the driving unit can be seen, while from the perspective of FIG. 2b (side view), the driving arms close to the main body of the driving unit is completely or partially blocked by the driving arms away from driving unit's main body. In this case, the lines presenting the engaging directions of driving arms on the same side of driving unit is coplanar or skew. At the same time, there is no particular limitation on the length or the length relationship among different driving arms.

(33) Please refer to FIG. 5, which is a schematic perspective view of a driving unit **500** according to still another embodiment of the present invention. In addition, the driving unit **500** pivots around pivot shaft **520**.

(34) Specifically, the driving unit **500** includes six driving arms **510**, each three of which are installed on one side of the driving unit **500**. Specifically, **510a**, **510b**, and **510c** are installed on one side, and **510d**, **510e**, and **510f** are installed on the other side. As described above, the lengths, the length relationships and the positional settings of the driving arms **510** on the same side are designed according to the specific structure and working principle, and are not specifically limited herein. Specifically, in the embodiment of the present invention, the positional relationship of the three driving arms **510** on the same side of the driving unit **500** is similar to that in FIG. 2a, FIG. 2b and FIG. 2c, that is, the three driving arms **510** on the same side of the driving unit **500** are installed up and down.

(35) It should be noted that, in other embodiments of the present invention, the total number of driving arms may also be an odd number, such as three, five or more, that is, the numbers of driving arms on both sides of the driving unit are not equal. Moreover, the structural relationship between the different driving arms can be similar to that described above, and no specific restrictions are imposed here.

(36) Referring to FIG. 6 and FIG. 2c together, FIG. 6 is a partial structural diagram of the driving wheel **130**, and gear teeth **131**.

(37) In the perspective of FIG. 2c, the horizontal distance between the driving ends of the two driving arms on one side of the driving unit **100** is h , and the pitch of the gear teeth **131** is s , then $0.5s \leq h \leq 1.5s$. Specifically, in the embodiment of the present invention, $h=0.8s$. In another embodiment of the invention, $h=1.2s$. In still another embodiment of the invention, $h=s$. Here, the driving end of the driving arms **110** refers to the end of the driving arms **110** that directly contacts the gear teeth **131** when engaged. The horizontal distance refers to the plane distance between the driving ends of the two driving arms **110** on the same side of the driving unit **100** when viewed in an angle as shown in FIG. 2c.

(38) It should be noted that in other embodiments of the present invention, $0.1s \leq h \leq 0.5s$ or $1.5s < h \leq 2.5s$ may be used, and the effects of the present invention may be also achieved, and also are not specifically limited herein.

(39) As shown in FIG. 6, in the embodiment of the present invention, the driving wheel **130** is a ratchet, and the gear teeth **131** are ratchet teeth. The use of a ratchet can prevent the driving wheel **130** from rotating reversely. Each ratchet tooth surface includes a gentle surface and a steep surface, as shown in FIG. 6. Moreover, in the embodiment of the present invention, the driving arms **110** of the driving unit **100** include a portion that drives the driving wheel **130** to rotate and a portion that does not drive the driving wheel **130** to rotate during the entire pivot of the driving unit **100** in one direction. The portion that drives the driving wheel **130** to rotate applies the engaging force on the steep surface of the ratchet teeth, in order to drive the driving wheel **130** to rotate in the C direction.

(40) Please refer to FIG. 7, which is a schematic perspective view of the driving unit **100** and the driving wheel **130**.

(41) With reference to FIG. 7, FIG. 1, FIG. 2b and FIG. 2c, in the embodiment of the present invention, under the action of the power unit **180**, the driving unit **100** pivots around the pivot shaft

120, thereby driving the plurality of driving arms **110** on both sides of the driving unit **100** to engage the gear teeth **131** for rotation of the driving wheel **130**.

(42) Referring to FIG. 7 and FIG. 8 together, FIG. 8 is a schematic structural diagram of the adjustable pivoting movements of the driving unit **100**.

(43) As described above, the driving unit **100** has a certain distance h between the driving ends of the driving arms **110** on the same side, and there is a certain angle α between the lines representing the driving directions when the arms are engaged. And therefore, the driving unit **100** pivots in one direction in a single time throughout the process, as shown in FIG. 7 in a single pivot in the direction A, **110a** and/or **110b** engage the gear teeth **131** to drive the driving wheel **130**, while **110c** and **110d** can slide on the gear teeth **131** (as on the gentle surface of the ratchet teeth, but not exert a force for driving the driving wheel **130** to rotate). And obviously, **110c** slides to the next adjacent tooth first and makes a “click” sound. At this time, the driving end of **110c** acts on the steep surface of the ratchet teeth to prevent the driving wheel **130** from being rotated reversely. At this time, the driving unit **100** stops pivoting and the driving arms **110a** and/or **110b** stop engaging the gear teeth **131**, and the driving wheel **130** stops rotating. Thus the driving unit **100** completes one step of pivot. Referring to FIG. 8, the driving unit **100** pivots in the A direction to reach the A1 position. The next moment the driving unit **100** continues to pivot in the A direction, **110d** will slide to the next adjacent tooth and will make another “click” sound. Similarly, the driving end of **110d** also acts on the steep surface of the ratchet teeth to prevent the driving wheel **130** from rotating reversely. Thus the driving unit **100** completes a second step of pivot. Referring to FIG. 8, the driving unit **100** pivots to reach the A2 position. At this time, **110c** and **110d** respectively complete the sliding between adjacent gear teeth **131**, and the driving unit **100** completes the whole process of single pivot in the A direction, reaching A1 and A2 positions respectively, thereby driving the driving wheel **130** to rotate by two steps, realizing two-step infusion of the drug device.

(44) It should be noted that, in the above pivoting process, **110d** may first slide to the next gear tooth **131**, and then **110c** slide to the next gear tooth **131**, which is not specifically limited herein. Similarly, when the driving unit **100** pivots in the B direction, it can reach B1 and B2 positions respectively.

(45) Obviously, in the whole process of the above-mentioned single pivot in the A direction, the driving unit **100** undergoes an alternate action of pivot and stop, and the driving arms **110** alternately engage and stop engaging gear teeth **131** to drive the driving wheel **130** to rotate and stop rotating, realizing two-step rotation of the driving wheel, and finally achieves two-level increment-adjustable drug infusion.

(46) Specifically, when the driving unit **100** has two driving arms **110** on one side, the driving unit **100** undergoes two-step movement of the pivot-stop-pivot-stop during the single pivot in the A direction, in order to drive driving wheel **130** for two-step rotation. When the driving unit **100** has three driving arms **110** on one side, the driving unit **100** performs the pivot-stop-pivot-stop-pivot-stop three-step motion in the whole process of single pivot in the A direction, realizing three-step rotation of the driving wheel **130** to achieve three-level increment-adjustable drug infusion. By analogy, when there are more driving arms **110** on one side of the driving unit **100**, the driving unit **100** realizes multiple-step driving of the driving wheel **130** by the multiple-step actions of the pivot-stop-pivot-stop-pivot- . . . -pivot-stop, completing multi-level increment-adjustable drug infusion.

(47) With continued reference to FIG. 7, in combination with the above, in the embodiment of the present invention, when the driving unit **100** drives the driving wheel **130** to rotate, at least one of the driving arms **110** on the driving force side applies an engaging force to the gear teeth **131**. While one or both of the driving arms **110** on the other side are in contact with the gear teeth **131** without applying any force to the gear teeth **131** to drive the driving wheel **130** to rotate, only applying a force if necessary for preventing the driving wheel **130** from being reversed. Therefore, there is a case in the embodiment of the present invention that only one of the driving arms **110** of

the driving unit **100** applies a force to the gear teeth **131** to push the driving wheel **130** to rotate, and the other driving arms **110** are in contact with the driving wheel **130** without applying any force to the gear teeth **131** to drive the rotation of the driving wheel **130**. At this time, the driving arm **110** that slides on the teeth on the other side applies a force to the gear teeth **131** to prevent the driving wheel **130** from being reversed.

(48) It should be noted that, in the embodiment of the present invention having three or more driving arms **110** on one side of the driving unit **100**, when the driving unit **100** is in operation, the above-mentioned similar situation may also occur. When there are an odd number of driving arms, the numbers of driving arms on both sides of the driving unit are not equal, and the same process as above is also performed in the whole process of the driving unit rotating in a certain direction.

(49) Referring to FIG. **8** again, in another embodiment of the present invention, when the driving unit **100** has two driving arms **110** on one side, the driving unit **100** pivots one step in the A direction, that is, reaching the A1 position, and then pivots one or two steps in the B direction, that is, reaching the B1 or B2 position until the pivot in the B direction stops. This process completes the alternate pivot of the driving unit **100** in two directions, so that the driving wheel **130** can be rotated in multiple steps. Therefore, in the embodiment of the present invention, the driving unit **100** can alternately switch modes among A1-B1 or A1-B1-B2 or B1-A1-A2, so as to achieve the purpose of switching among different increments of infusion.

(50) With continued reference to FIG. **8**, in another embodiment of the present invention, the driving unit **100** can also be pivoted directly to the A2 position without passing through the A1 position, then directly pivoted to the B2 position without passing through the B1 position, that is, the driving unit **100** alternately pivots between the A2-B2 positions. As described above, the driving unit **100** can also alternately pivot between the A1-B1 positions. Obviously, in a unit time, the dose of infused drug when the driving unit **100** alternately pivots between the A2-B2 positions is greater than the dose of infused drug when it alternately pivots between the A1-B1 positions. If the minimum dose of infused drug driven by the driving unit is the minimum increment of the infusion device, the drug infusion device using the embodiment of the present invention can reduce the minimum increment of drug dose and achieve more precise control of the drug infusion. When the patient needs to infuse more drugs, the large A2-B2 mode can be selected to speed up the infusion rate. When a small amount of drug needs to be infused, the patient can select the small A1-B1 mode to reduce the drug infusion rate and achieve precise control of the drug infusion.

(51) In a drug infusion system, only one driving arm is set on each side of the driving unit, and only one-step rotation of the driving wheel can be performed in the whole process of rotating in one direction, that is, driving unit alternately moving between A2-B2 as shown in FIG. **8**. This one-level driving method does not provide flexibility in controlling drug dose and infusion rate. At the same time, the minimum dose of infused drug is large, and it is hard to accurately control the drug infusion, which will eventually lead to a large fluctuation in the concentration of some substance(s) in a patient's body fluid. And it is also a waste of drugs and increasing the cost for patients.

(52) Compared with the device with increment-unadjustable infusion, the drug infusion device of the embodiment of the invention realizes driving degree-adjustable rotation of the driving wheel by setting more than two driving arms on the driving unit, thereby achieving increment-adjustable drug delivery. With the drug infusion device of the embodiment of the invention, the patient can freely and flexibly switch between different increments of infusion according to the actual drug dose and the demand of the infusion rate, thereby improving the infusion efficiency. At the same time, intermediate A1-B1-B2 mode or B1-A1-A2 mode and the small A1-B1 mode are set along with the large A2-B2 mode. And the drug infusion device can reduce the minimum dose of infused drug in order to achieve the goal of precise control of the infusion.

(53) As with the drug infusion device of the embodiment of the present invention, when the infusion is started, the amount of drug required is relatively large, and the patient can select the large A2-B2 position shown in FIG. **8** for infusion. After a period of infusion, the intermediate A1-

B1-B2 mode or B1-A1-A2 mode can be used to reduce the rate of drug infusion. When the drug infusion is about to be completed, the patient can switch to the small A1-B1 mode to further reduce the infusion rate and achieve precise control of the drug infusion. Of course, the patient can also choose one or several of the modes for infusion, and there are no specific restrictions.

(54) In other embodiments of the present invention, when more than two driving arms **110** are installed on one side of the driving unit **100**, the drug infusion device can have more and more elaborate infusion modes, and the patient can further flexibly control the infusion to make the infusion process more precisely.

(55) In summary, the present invention discloses a drug infusion device, in which more than two driving arms are installed on a driving unit, and the driving unit drives the driving wheel to rotate by an optional number of teeth through different pivoting movement modes, thereby realizing increment-adjustable drug infusion, increasing the patient's flexibility in controlling the infusion process and improving the efficiency of drug infusion. At the same time, the drug infusion device also reduces the minimum dose of infused drug, from which the patients can accurately control the drug infusion and precisely manage their own physiological condition.

(56) While the invention has been described in detail with reference to the specific embodiments of the present invention, it should be understood that it will be appreciated by those skilled in the art that the above embodiments may be modified without departing from the scope and spirit of the invention. The scope of the invention is defined by the appended claims.

Claims

1. An infusion device, comprising: a drug storage unit; a screw, a piston and a driving wheel respectively connected with the screw, the driving wheel drives the screw to move by rotation, the piston is arranged in the drug storage unit, the screw advances the piston to move; a driving unit cooperating with the driving wheel, the driving unit comprises more than two driving arms which drive the driving wheel to rotate, the driving unit, through multiple-mode pivot, drives the driving arms to perform a driving mechanism that uses any number of teeth and is adjustable on the driving wheel for increment-adjustable infusion; and a power unit connected to the driving unit, the power unit exerts a force on the driving unit to lead the driving unit to perform multiple-mode pivot, wherein the driving arms are respectively installed on two sides of the driving unit, each of the two sides of the driving unit is installed with two driving arms of the driving arms, distances between the two driving arms on each side of the driving unit become smaller along a direction towards two driving ends of the two driving arms, wherein the two driving ends of the two driving arms contact the driving wheel, wherein the multiple-mode pivot of the driving unit includes: after pivoting one or more steps in one direction in a single time, the driving unit starts pivoting one or more steps in another direction until an end of the pivot in this direction, the driving unit completes an alternating pivot in both directions to perform multiple-mode driving on the driving wheel.
2. The drug infusion device according to claim 1, wherein the driving wheel includes: a plurality of sub-wheels, a circumferential surface of each of the plurality of sub-wheels is provided with gear teeth, and the driving arms drive the driving wheel by engaging the gear teeth.
3. The drug infusion device according to claim 2, wherein when the driving arms on one side of the two sides of the driving unit engage the gear teeth of the driving wheel, lines representing engaging directions of the driving arms each occurring on the one side of the two sides intersect each other, and the engaging directions are directions that the two driving arms are oriented in when engaged with the gear teeth, respectively.
4. The drug infusion device according to claim 3, wherein the two driving arms on each of the two sides of the driving unit are oriented along a first direction, or are oriented along a second direction, the first direction is not parallel to the second direction.
5. The drug infusion device according to claim 4, wherein the two driving arms on each of the two

sides of the driving unit are oriented along the first direction, and when the two driving arms on each of the two sides of the driving unit engage the gear teeth of the driving wheel, an angle between the lines representing driving directions of the two driving arms is α , $0^\circ \leq \alpha \leq 7^\circ$, the driving directions are directions that the driving arms are oriented in when driving the gear teeth, respectively.

6. The drug infusion device according to claim 5, wherein $3.1^\circ \leq \alpha \leq 4.1^\circ$.

7. The drug infusion device according to claim 6, wherein $\alpha = 3.5^\circ$.

8. The drug infusion device according to claim 4, wherein a horizontal distance between driving ends of the two driving arms on the one side of the two sides of the driving unit is h , a pitch of the gear teeth of the driving wheel is s , $0.1s \leq h \leq 2.5s$.

9. The drug infusion device according to claim 8, wherein $0.5s \leq h \leq 1.5s$.

10. The drug infusion device according to claim 2, wherein the gear teeth of the driving wheel are ratchet teeth, and during a whole process of the driving unit pivoting in either of the one direction or the another direction, the driving unit alternately pivots and stops multiple times to drive the driving arms to alternately engage and stop engaging the ratchet teeth, so that the driving wheel alternately rotates and stops rotation to perform the driving mechanism.

11. The drug infusion device according to claim 10, wherein when the driving unit drives the driving wheel, at least one of the driving arms on one side of the two sides on which a driving force is applied engages the ratchet teeth of the driving wheel, and the driving arms on the other side of the two sides of the driving unit do not apply a force to the ratchet teeth of the driving wheel to rotate the driving wheel.

12. The drug infusion device according to claim 1, wherein the multiple-mode pivot of the driving unit comprises: a large movement mode and a small movement mode, and when an infusion is performed, the driving unit switches between the large movement mode and the small movement mode to realize the increment-adjustable infusion.

13. The drug infusion device according to claim 12, wherein the multiple-mode pivot of the driving unit further comprises: at least one intermediate movement mode, wherein the at least one intermediate movement mode is between the large movement mode and the small movement mode, and the driving unit switches among the large movement mode, the at least one intermediate movement mode and the small movement mode to achieve the increment-adjustable infusion.
