

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12404686
B2
September 02, 2025
Mikic; Erzad

Scaffolding crossbar, scaffolding and method for constructing scaffolding

Abstract

A scaffolding crossbar having at least two, in particular at least three crossbar coupling elements at one end. The crossbar coupling elements can be designed to be the same. The crossbar coupling elements are designed preferably in the form of receiving openings. The crossbar coupling elements serve to detachably secure diagonal piece coupling elements. The scaffolding according to the invention, having a scaffolding crossbar of this type, has a diagonal scaffolding piece with a first diagonal piece coupling element at one end and a second diagonal piece coupling element at the other end. The first diagonal piece coupling element can be designed differently from the second diagonal piece coupling element, wherein the crossbar coupling elements are designed preferably for connecting both diagonal piece coupling elements. The scaffolding can thereby be designed such that it is optionally partially or completely particularly torsion resistant.

Inventors:	Mikic; Erzad (Karlsruhe, DE)
Applicant:	PERI SE (Weissenhorn, DE)
Family ID:	63713580
Assignee:	PERI SE (Weissenhorn, DE)
Appl. No.:	16/647861
Filed (or PCT Filed):	September 12, 2018
PCT No.:	PCT/DE2018/100774
PCT Pub. No.:	WO2019/052604
PCT Pub. Date:	March 21, 2019

Prior Publication Data

Document Identifier

US 20200217090 A1

Publication Date

Jul. 09, 2020

Foreign Application Priority Data

DE

10 2017 216 255.4

Sep. 14, 2017

Publication Classification

Int. Cl.: E04G5/16 (20060101); E04G1/04 (20060101); E04G5/00 (20060101)

U.S. Cl.:

CPC E04G5/16 (20130101); E04G1/04 (20130101); E04G5/007 (20130101);

Field of Classification Search

CPC: E04G (5/16); E04G (5/007); E04G (5/001); E04G (5/067); E04G (1/04); E04G (1/20); E04G (1/152); E04G (11/48); E04G (7/302); E04G (7/301); E04G (17/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1330290	12/1919	Westman	249/210	E04G 11/48
1498665	12/1923	MacIvor	249/210	E04G 11/48
1552333	12/1924	Mosher	52/651.1	E04G 5/16
2018338	12/1934	Abdelnour	15/250.33	B60S 1/4003
2195906	12/1939	Uecker	52/651.1	E04G 1/14
2575461	12/1950	North	52/646	E04G 1/24
2794558	12/1956	Miles	414/12	E04G 5/007
3367080	12/1967	McClelland	52/645	E04G 5/16
3409266	12/1967	Jennings	248/165	E04G 17/04
3564803	12/1970	Breeze et al.	52/651.1	E04G 11/48
3693309	12/1971	Kutchai	52/646	E04G 11/48
3807120	12/1973	Viandon	52/646	E04G 5/00
3835612	12/1973	Beziat	52/646	E04G 1/14
6220392	12/2000	Schwoerer	182/186.7	E04G 7/305
6296077	12/2000	Wood	403/49	E04G 7/307
10059055	12/2017	Riffel	N/A	E04G 5/16
10995504	12/2020	Cook	N/A	E04G 7/22
2002/0014371	12/2001	Krause	403/49	E04G 7/304
2002/0129567	12/2001	Olsen	52/651.01	E04H 12/185
2002/0141811	12/2001	Shih	403/49	E04G 25/061
2003/0061779	12/2002	Wyse	52/651.1	E04G 5/16
2004/0211623	12/2003	Weston	182/152	E04G 5/16

2007/0274771	12/2006	Chang	403/187	E04G 11/48
2008/0128205	12/2007	Berlin	182/186.7	E04G 7/22
2009/0223743	12/2008	Jejina	248/235	E04G 1/38
2010/0000822	12/2009	Wall	182/128	E04G 1/12
2010/0071299	12/2009	Daas	52/646	E04C 3/005
2011/0047910	12/2010	Hartmann	52/302.1	E04G 11/48
2011/0308189	12/2010	Daas	52/646	E04H 12/10
2012/0112376	12/2011	Khoo	264/33	E04G 11/48
2012/0298449	12/2011	Kreller	182/113	E04G 5/147
2013/0126270	12/2012	Darby	256/65.01	E04G 5/14
2013/0180801	12/2012	Vogels	182/113	E04G 7/02
2014/0020982	12/2013	Hayman	29/428	E04G 5/007
2014/0262619	12/2013	Bains	248/351	E04G 7/34
2015/0197949	12/2014	Rosati	249/219.1	E04G 25/061
2015/0267422	12/2014	Tan	249/188	E04G 19/003
2015/0292263	12/2014	Hierl	182/128	E04G 5/007
2019/0010718	12/2018	Ubiñana Felix	N/A	E04G 5/007
2019/0078340	12/2018	Faresin	N/A	E04G 1/30
2019/0078341	12/2018	Li	N/A	E04G 5/16
2019/0145115	12/2018	Bacon	52/127.2	E04G 25/08
2020/0002954	12/2019	Carmody	N/A	E04G 1/24
2020/0284061	12/2019	Pezzola	N/A	E04G 23/04
2021/0054638	12/2020	Steck	N/A	E04G 1/14
2021/0062580	12/2020	Smith	N/A	E04G 1/20
2021/0254351	12/2020	Tubbs	N/A	E04G 5/14

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2910467	12/1978	DE	N/A
8117020	12/1980	DE	N/A
8117020	12/1980	DE	N/A
3600245	12/1985	DE	N/A
102016109972	12/2016	DE	N/A
2062945	12/1993	ES	N/A
2062945	12/1993	ES	N/A
2018338	12/1978	GB	N/A
2136908	12/1983	GB	N/A
56159432	12/1980	JP	N/A
2014237930	12/2013	JP	N/A
200175311	12/1999	KR	N/A
20010037634	12/2000	KR	N/A

OTHER PUBLICATIONS

PERI GmbH: PERI UP Rosett Stützturm, Aufbau- und Verwendungsanleitung für die Regelausführung. Apr. 2014. 89259 Weißenhorn, 2012. S. 1, 5, 20, 27, 28.—Firmenschrift. cited by applicant

Primary Examiner: Laux; Jessica L

Assistant Examiner: McFarland; Kathleen M.

Background/Summary

FIELD OF THE INVENTION

(1) The invention relates to a scaffolding crossbar for the horizontal reinforcement of a scaffolding between two scaffolding posts of the scaffolding, wherein the scaffolding post comprises a first crossbar coupling part in its first longitudinal end region for connecting a diagonal coupling part of a first scaffolding diagonal scaffolding piece. The invention furthermore relates to a scaffolding with such a scaffolding crossbar and a method for constructing a scaffolding.

BACKGROUND OF THE INVENTION

(2) It is common practice to use scaffolding posts when constructing scaffolding in lightweight construction in order to transfer vertical loads. The scaffolding posts are, either indirectly or directly, connected by means of horizontal scaffolding crossbars. These may be designed to be flexible or rigid. The scaffolding is primarily reinforced by the diagonal scaffolding piece, wherein two scaffolding crossbars are connected with a single diagonal scaffolding piece. A unit consisting of two scaffolding crossbars that are vertically arranged above each other and that are connected with a diagonal scaffolding piece is referred to as a “lift height.” In prior art, therefore, one diagonal scaffolding piece is installed per lift height. The bracing this achieves, however, is not very significant. This limits the applications of known scaffoldings in lightweight construction.

SUMMARY OF THE INVENTION

(3) It is therefore the object of the invention to provide a scaffolding crossbar that makes constructing a significantly better reinforced scaffolding possible and easier. It is furthermore the object of the invention to provide a scaffolding with such a scaffolding crossbar and a method for constructing a significantly better reinforced scaffolding.

(4) The object according to the invention is solved by a scaffolding crossbar, a scaffolding, and a method.

(5) The object according to the invention is therefore solved by a scaffolding crossbar. The scaffolding crossbar is preferably designed in the form of a modular scaffolding crossbar. The scaffolding crossbar is designed to horizontally reinforce a scaffolding between two scaffolding posts of the scaffolding. The scaffolding crossbar can, in particular, be arranged on connection plates, preferably in the form of perforated disks, of the scaffolding posts. The scaffolding crossbar extends in the direction of its longitudinal axis and comprises at its one end, i.e., in its longitudinally extending first end region, a first crossbar coupling part of a first diagonal scaffolding piece of the scaffolding. In addition, the scaffolding crossbar comprises in the same longitudinally extending end region a second crossbar coupling part for the connection of a diagonal piece coupling part of a second diagonal scaffolding piece of the scaffolding.

(6) The second crossbar coupling part in the area of the first crossbar coupling part offers a simple way to arrange a second diagonal scaffolding piece per lift height. This significantly increases the rigidity and the load-bearing capacity of the scaffolding. It is not absolutely necessary to arrange a second diagonal scaffolding piece in every lift height. Rather, depending on the load on individual scaffolding parts, a second diagonal scaffolding piece may be arranged or not when the scaffolding is constructed. In other words, the scaffolding may, even after it has been constructed, be reinforced with a further diagonal scaffolding piece at particularly load-bearing points without having to significantly increase the total number of the scaffolding components or having to use a scaffolding generally designed for higher loads.

(7) The scaffolding crossbar may comprise a third scaffolding coupling part in its first longitudinal end region for connecting a diagonal piece coupling part of a third diagonal scaffolding piece of the

scaffolding. The third crossbar coupling part therefore makes it possible to further reinforce a lift height of a scaffolding by means of a third diagonal scaffolding piece. In doing so, the scaffolding is able to bear particular loads in some areas.

(8) At least two crossbar coupling parts (30a-30c) may be arranged on the same horizontal plane, and preferably all crossbar coupling parts (30a-30c) may be arranged on the same horizontal plane.

(9) To simplify the connection of the diagonal scaffolding piece, a plurality of crossbar coupling parts, preferably all crossbar coupling parts, may be formed equally.

(10) If at least three crossbar coupling parts are arranged or formed on the scaffolding post, the part in the center of the three crossbar coupling parts is preferably evenly spaced from its two adjacent crossbar coupling parts.

(11) A crossbar coupling part may have the form of a projection. Preferably, a plurality, preferably all, crossbar coupling parts have the form of a projection.

(12) In a particularly preferred embodiment of the invention, a crossbar coupling part has the form of a through-recess. A diagonal piece coupling part may, in this case, have the form of a projection, which can, at least partially, be placed into the through-recess. In a further preferred embodiment, a plurality, preferably all, crossbar coupling parts have the form of a through-recess.

(13) To be able to not have to pay a lot of attention to the orientation of the scaffolding crossbar when constructing the scaffolding, the scaffolding crossbar is preferably formed symmetrically to a symmetry plane. The symmetry plane may run vertically to the longitudinal axis of the scaffolding crossbar.

(14) The object according to the invention is furthermore solved by a scaffolding with a first scaffolding crossbar as described above, a first diagonal scaffolding piece, whose diagonal piece coupling part is connected with the first crossbar coupling part of the first scaffolding crossbar, and a second diagonal scaffolding piece, whose diagonal piece coupling part is connected with the second crossbar coupling part of the first scaffolding crossbar. The scaffolding is preferably a modular scaffolding.

(15) The scaffolding may furthermore comprise the following: a. A first scaffolding post and a second scaffolding post, wherein the first scaffolding crossbar connects, either indirectly or directly, the first scaffolding post with the second scaffolding post; b. a previously described second scaffolding crossbar, which, either indirectly or directly, connects the first scaffolding post with the second scaffolding post; wherein the first diagonal scaffolding piece comprises, at one end, the first diagonal piece coupling part and, at the other end, a second diagonal piece coupling part, wherein the second diagonal piece coupling part is connected to a crossbar coupling part of the second scaffolding crossbar; and wherein the second diagonal scaffolding piece comprises, at one end, the first diagonal piece coupling part and, at the other end, a second diagonal piece coupling part, wherein the second diagonal piece coupling part is connected with a crossbar coupling part of the second scaffolding crossbar.

(16) The scaffolding may comprise a third diagonal scaffolding piece, which, at one end, comprises a first diagonal piece coupling part and, at the other end, a second diagonal piece coupling part, wherein the third diagonal scaffolding piece connects the two scaffolding crossbars. This makes the lift height of a scaffolding particularly well reinforced.

(17) The first diagonal piece coupling part of the third diagonal scaffolding piece may be connected with a crossbar coupling part of the first scaffolding crossbar, and the second diagonal piece coupling part of the third diagonal scaffolding piece may be connected with a crossbar coupling part of the second scaffolding.

(18) To be able to arrange the first diagonal scaffolding piece to the scaffolding crossbars in a particularly easy and fast but still reliable manner, the first diagonal piece coupling part is preferably formed so that it does not fully penetrate the scaffolding crossbar. The second diagonal piece coupling part of the first diagonal scaffolding piece is preferably formed so that it fully penetrates the scaffolding crossbar.

(19) It is furthermore preferred that the first diagonal piece coupling part has the form of a rigid hook. The second diagonal piece coupling part preferably comprises a pin. The pin may be a movable element to ensure the engagement of the pin. This allows for a fast hooking into the first diagonal piece coupling part and a reliable arrangement of the diagonal scaffolding piece with the, in particular, secured pin.

(20) The first diagonal scaffolding piece is preferably the same as the second diagonal scaffolding piece and in particular the same as the third diagonal scaffolding piece.

(21) The object according to the invention is furthermore solved by a method for constructing a scaffolding, in particular a scaffolding as described above, with the following method steps: A) Fastening of a first diagonal scaffolding piece between a first scaffolding crossbar and a second scaffolding crossbar; B) Fastening of a first diagonal scaffolding piece between the first scaffolding crossbar and the second scaffolding crossbar.

(22) The method may furthermore comprise the following method step: C) Fastening of a third diagonal scaffolding piece between the first scaffolding crossbar and the second scaffolding crossbar.

(23) Prior to, after and/or between the method steps A), B) and/or C), a further process step or further process steps may be performed.

(24) In the present invention, the terms “top,” “bottom,” “vertical,” “horizontal,” etc. refer to the scaffolding in its assembled state.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Further features and advantages of the invention are described in the following detailed description of several exemplary embodiments of the invention and the claims as well as the figures of the drawing, which shows details that are essential to the invention. The different features may be realized in variants of the invention either individually or in any combination. The features shown in the drawing are shown in such a way that the particulars of the invention can be clearly demonstrated.

(2) FIG. 1 shows a schematic side view of a scaffolding according to prior art with a diagonal scaffolding piece between two scaffolding crossbars;

(3) FIG. 2 shows a schematic side view of a scaffolding, wherein two diagonal scaffolding pieces are arranged between two scaffolding crossbars each at the lowermost lift height and the top lift height;

(4) FIG. 3 shows a schematic side view of a scaffolding, wherein four diagonal scaffolding pieces are arranged between two scaffolding crossbars each at the lowest lift height and at the highest lift height and wherein two diagonal scaffolding pieces are arranged between two scaffolding crossbars each in the lift height between them;

(5) FIG. 4a shows a side view of a scaffolding with two scaffolding posts, two scaffolding crossbars connecting the scaffolding posts and two diagonal scaffolding pieces reinforcing the scaffolding crossbars;

(6) FIG. 4b shows an enlarged side view of the scaffolding according to the dot-dashed area in FIG. 4a, wherein FIG. 4b shows two crossbar coupling parts formed on the scaffolding crossbar;

(7) FIG. 4c shows an enlarged isometric view of the scaffolding according to the dotted area in FIG. 4a, wherein FIG. 4c shows the pending arrangement of a third diagonal scaffolding piece;

(8) FIG. 4d shows an isometric view of the scaffolding according to FIG. 4c after the third diagonal scaffolding piece has been arranged;

(9) FIG. 4e shows an enlarged isometric partial view of the scaffolding according to the dot-dashed area in FIG. 4d;

(10) FIG. 5 shows an isometric partial view of the scaffolding according to FIG. 4e but with a different fastening variant of the third diagonal scaffolding piece.

DETAILED DESCRIPTION

(11) FIG. 1 shows a scaffolding **10** according to prior art. The scaffolding **10** comprises a plurality of lift heights **12a**, **12b**, **12c**, **12d**. The lift heights **12a-12d** each comprise two scaffolding crossbars **14a**, **14b**, **14c**, **14d**, **14e**. A diagonal scaffolding piece **16a**, **16b**, **16c**, **16d** is arranged between two scaffolding crossbars **14a-14e** each. One diagonal scaffolding piece **16a-16d** is therefore provided for each lift height **12a-12d**. For many applications, however, the scaffolding **10** is not reinforced enough. The object of the present invention is therefore to provide a scaffolding **10** that is significantly more reinforced.

(12) FIG. 2 shows a scaffolding **10** according to the invention with lift heights **12a-12d** and scaffolding crossbars **14a-14e**. The scaffolding **10** comprises, however, diagonal scaffolding pieces **16e**, **16f** in addition to the diagonal scaffolding pieces **16a-16d**. The lift heights **12a** and **12d** are particularly rigid due to the additional diagonal scaffolding pieces **16e**, **16f**. It was found that the stability of the lowermost lift heights is what matters most when increasing the overall stability of the scaffolding **10**. The scaffolding **10** according to FIG. 2 is thus formed so that it is particularly effective in bearing high loads because only the critical areas in the form of the lift heights **12a** and **12d** are reinforced by at least one additional diagonal scaffolding piece **16e**, **16f**.

(13) FIG. 3 shows an embodiment of a scaffolding **10**, which is even more reinforced than the scaffolding **10** in FIG. 2. The scaffolding **10** in FIG. 3 comprises, in each lift height **12a-12d**, at least two diagonal scaffolding pieces **16a-16f**, **16g**, **16h**, **16i**, **16j**, **16k**, **16l**. The diagonal scaffolding pieces **16a-16l** are therefore preferably arranged above the cross so that they are offset against each other. The lowermost lift height **12a** and the top lift height **12d** may be, as shown, especially reinforced.

(14) FIG. 4a shows a part of a scaffolding **10** with vertically oriented scaffolding posts **18a**, **18b**. The scaffolding posts **18a**, **18b** each comprise connection plates **20a**, **20b**, **20c**, **20d**, here in the form of perforated plates, especially in the form of rosettes. Scaffolding crossbars **22a**, **22b** are arranged on, in particular inserted into, the connection plates **20a**, **20b**. The front sides scaffolding crossbars **22a**, **22b** may lie against the scaffolding posts **18a**, **18b** to create a particularly stable embodiment of the scaffolding **10**.

(15) The scaffolding crossbar **22a** is formed so that it is symmetrical to a symmetry plane **24**. The symmetry plane **24** runs vertical to the longitudinal axis **26** of the scaffolding crossbar **22a**.

(16) The scaffolding crossbars **22a**, **22b** are designed to be the same.

(17) Diagonal scaffolding pieces **16a**, **16b** are arranged between the scaffolding crossbars **22a**, **22b**. Seen in the direction of the longitudinal axis **26**, the scaffolding crossbar **22a** has a first end region **28a** and a second end region **28b**. A plurality of diagonal scaffolding pieces **16a**, **16b** can be arranged on at least one end region **28a**, **28b**.

(18) FIG. 4b shows the scaffolding **10** according to the area in the dot-dashed frame in FIG. 4a. FIG. 4b shows that the scaffolding crossbar **22a** comprises a first crossbar coupling part **30a**, a second crossbar coupling part **30b** and a third crossbar coupling part **30c** in the first end region **28a**. The crossbar coupling parts **30a-30c** are each configured in the form of a through-recess. At least one through-recess may be formed by both side walls of the scaffolding crossbar **22a**. Preferably, a plurality of through-recesses, more preferably all through-recesses, are formed by both side walls of the scaffolding crossbar **22a**. At least one through-recess, preferably a plurality of through-recesses, in particular all through-recesses, can have a same diameter D , in particular of $22\text{ mm} \pm 20\text{ mm}$, preferably of $22\text{ mm} \pm 10\text{ mm}$, particularly preferably of $22\text{ mm} \pm 5\text{ mm}$. The crossbar coupling parts **30a-30c** may have the same distance A from each other. The distance A is preferably $40\text{ mm} \pm 20\text{ mm}$, in particular $40\text{ mm} \pm 10\text{ mm}$, most preferably $40\text{ mm} \pm 5\text{ mm}$.

(19) FIG. 4c shows the scaffolding **10** according to the area in the dashed frame in FIG. 4a. According to FIG. 4c, two diagonal scaffolding pieces **16a**, **16b** are already fastened to the

scaffolding crossbar 22a. A third diagonal scaffolding piece 16c is to be arranged on the scaffolding crossbar 22a in addition. The third diagonal scaffolding piece 16c comprises a first diagonal piece coupling part 32. The first diagonal piece coupling part 32 is configured in the form of a hook, which is preferably formed to engage with a single side wall of the scaffolding crossbar 22a of a crossbar coupling part 30a, 30b, 30c.

(20) FIG. 4d shows the scaffolding 10 with three diagonal scaffolding pieces 16a, 16b, 16c between the scaffolding crossbars 22a, 22b. The diagonal scaffolding pieces 16a-16c are preferably arranged on both sides of the scaffolding crossbar 22a, 22b; in the present case, the diagonal scaffolding pieces 16a, 16b are arranged on one side of the scaffolding crossbars 22a, 22b, and the diagonal scaffolding piece 16c is arranged on the other side of the scaffolding crossbars 22a, 22b.

(21) FIG. 4e shows the scaffolding 10 according to the area in the dot-dashed frame in FIG. 4d. FIG. 4e makes clear that the scaffolding crossbar 22b, in particular both side walls of the scaffolding crossbar 22b, are penetrated by two diagonal piece coupling parts 34. The diagonal piece coupling parts 36 each have a pin, which is secured by a movable element 38.

(22) FIG. 5 shows a scaffolding 10, wherein diagonal scaffolding pieces 16a, 16b are arranged parallel to each other at the first end 28a of the scaffolding crossbar 22b and extend downward. A third diagonal scaffolding piece 16c is arranged also at the first end 28a of the scaffolding crossbar 22b, preferably between the scaffolding crossbars 16a, 16b, and extends upward.

(23) Combining all the figures of the drawing, the invention relates, in summary, to a scaffolding crossbar 22a, 22b, which, at one end, comprises at least two, preferably in particular three, crossbar coupling elements 30a-30c. The crossbar coupling elements 30a-30c can be designed to be the same. The crossbar coupling elements 30a-30c are preferably in the form of receiving openings. The crossbar coupling elements 30a-30c serve to detachably secure the diagonal piece coupling elements 32, 34. A scaffolding 10 according to the invention, having a scaffolding crossbar 22a, 22b of this type, has diagonal scaffolding piece 16a-16c with a first diagonal piece coupling element 32 at one end and a second diagonal piece coupling element 34 at the other end. The first diagonal piece coupling element 32 can be designed differently from the second diagonal piece coupling element 34, wherein the crossbar coupling elements 30a-30c are designed preferably for connecting both diagonal piece coupling elements 32, 34. The scaffolding 10 can therefore be designed such that it is optionally partially or completely torsion-resistant.

Claims

1. A scaffolding, comprising: a first scaffolding crossbar having a first longitudinal axis defined along a length of the first scaffolding crossbar, the first scaffolding crossbar configured for horizontal reinforcement of the scaffolding between two scaffolding posts of the scaffolding, the first scaffolding crossbar having a first crossbar coupling part in its longitudinally sided first end region for connecting a first diagonal piece coupling part of a first diagonal scaffolding piece of the scaffolding, the first scaffolding crossbar having a second crossbar coupling part in its longitudinally sided first end region for connecting a second diagonal piece coupling part of a second diagonal scaffolding piece of the scaffolding, wherein the first crossbar coupling part and the second crossbar coupling part are arranged at a first distance from one another along the longitudinal axis of the first scaffolding crossbar; a second scaffolding crossbar having a second longitudinal axis defined along a length of the second scaffolding crossbar, the second scaffolding crossbar configured for horizontal reinforcement of the scaffolding between the two scaffolding posts of the scaffolding, the second scaffolding crossbar having a third crossbar coupling part in its longitudinally sided second end region for connecting a third diagonal piece coupling part of the first diagonal scaffolding piece of the scaffolding, the second scaffolding crossbar having a fourth crossbar coupling part in its longitudinally sided second end region for connecting a fourth diagonal piece coupling part of the second diagonal scaffolding piece of the scaffolding, wherein

the third crossbar coupling part and the fourth crossbar coupling part are arranged at the first distance from one another along the second longitudinal axis of the second scaffolding crossbar, the first diagonal scaffolding piece having the first diagonal piece coupling part connected with the first crossbar coupling part of the first scaffolding crossbar and having the third diagonal piece coupling part connected with the third crossbar coupling part of the second scaffolding crossbar; and the second diagonal scaffolding piece having the second diagonal piece coupling part connected with the second crossbar coupling part of the first scaffolding crossbar and having the fourth diagonal piece coupling part connected with the fourth crossbar coupling part of the second scaffolding crossbar, wherein the first diagonal scaffolding piece and the second diagonal scaffolding piece are arranged parallel to each other at the first end region of the first scaffolding crossbar and at the second end region of the second scaffolding crossbar, are offset from each other along both the first longitudinal axis of the first scaffolding crossbar and the second longitudinal axis of the second scaffolding crossbar by the first distance, and extend downward, wherein the first diagonal piece coupling part and the second diagonal piece coupling part do not penetrate the first scaffolding crossbar and wherein the third diagonal piece coupling part and the fourth diagonal piece coupling part penetrate the second scaffolding crossbar.

2. The scaffolding according to claim 1, wherein the first scaffolding crossbar comprises an additional crossbar coupling part in its longitudinally sided first end region for connecting an additional diagonal piece coupling part of a third diagonal scaffolding piece of the scaffolding, wherein at least the three crossbar coupling parts have a same distance from their adjacent crossbar coupling part.

3. The scaffolding according to claim 1, wherein at least the first crossbar coupling part and the second crossbar coupling part are designed to be the same.

4. The scaffolding according to claim 1, wherein at least one of the first crossbar coupling part or the second crossbar coupling part: i) is designed in the form of a through-recess, or ii) is designed in the form of a projection.

5. The scaffolding according to claim 1, wherein the first scaffolding crossbar is formed symmetrical to a symmetry plane that runs vertical to the longitudinal axis of the first scaffolding crossbar.

6. The scaffolding according to claim 1, further comprising: a first scaffolding post of the two scaffolding posts and a second scaffolding post of the two scaffolding posts; the first scaffolding crossbar, which, either indirectly or directly, connects the first scaffolding post with the second scaffolding post; and a second scaffolding crossbar, which, either indirectly or directly, connects the first scaffolding post with the second scaffolding post.

7. The scaffolding according to claim 6, wherein the scaffolding comprises a third diagonal scaffolding piece, which, at one end, comprises a fifth diagonal piece coupling part and, at the other end, a sixth diagonal piece coupling part, wherein the fifth diagonal piece coupling part is connected with the first crossbar coupling part of the first scaffolding crossbar and the sixth diagonal piece coupling part is connected with the crossbar coupling part of the second scaffolding crossbar.

8. The scaffolding according to claim 6, wherein the first and second diagonal piece coupling parts are designed in the form of a stiff hook and wherein the third and fourth diagonal piece coupling parts comprises a pin, with a movable element for securing the engagement of the pin.

9. A method for constructing a scaffolding according to claim 6, comprising: arranging the first diagonal scaffolding piece between the first scaffolding crossbar and the second scaffolding crossbar; arranging the second diagonal scaffolding piece between the first scaffolding crossbar and the second scaffolding crossbar.

10. The method according to claim 9, wherein the method comprises: arranging a third diagonal scaffolding piece between the first scaffolding crossbar and the second scaffolding crossbar.

11. A scaffolding, comprising: a first scaffolding crossbar having a first longitudinal axis defined

along a length of the first scaffolding crossbar, the first scaffolding crossbar having a first crossbar coupling part at a first end of the first scaffolding crossbar and having a second crossbar coupling part at the first end of the first scaffolding crossbar, wherein the first crossbar coupling part and the second crossbar coupling part are arranged at a first distance from one another along the longitudinal axis of the first scaffolding crossbar; a second scaffolding crossbar having a second longitudinal axis defined along a length of the second scaffolding crossbar, the second scaffolding crossbar having a third crossbar coupling part at a second end of the second scaffolding crossbar and having a fourth crossbar coupling part at the second end of the second scaffolding crossbar, wherein the third crossbar coupling part and the fourth crossbar coupling part are arranged at the first distance from one another along the second longitudinal axis of the second scaffolding crossbar a first diagonal scaffolding piece having a first diagonal scaffolding piece coupling part connected with the first crossbar coupling part of the first scaffolding crossbar and having a third diagonal scaffolding piece coupling part connected with the third crossbar coupling part of the second scaffolding crossbar; and a second diagonal scaffolding piece having a second diagonal scaffolding piece coupling part connected with the second crossbar coupling part of the first scaffolding crossbar and having a fourth diagonal scaffolding piece coupling part connected with the fourth crossbar coupling part of the second scaffolding crossbar, wherein the first diagonal scaffolding piece and the second diagonal scaffolding piece are arranged parallel to each other at both the first end region of the first scaffolding crossbar and the second end region of the second scaffolding crossbar and are offset from each other along both the first longitudinal axis of the first scaffolding crossbar and the second longitudinal axis of the second scaffolding crossbar by the first distance, wherein the first diagonal piece coupling part and the second diagonal piece coupling part do not penetrate the first scaffolding crossbar and wherein the third diagonal piece coupling part and the fourth diagonal piece coupling part penetrate the second scaffolding crossbar.

12. The scaffolding according to claim 11, wherein the first diagonal scaffolding piece and the second diagonal scaffolding piece extend downward.
