

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404695
Kind Code	B1
Date of Patent	September 02, 2025
Inventor(s)	Hillis; Logan

Portable privacy screen

Abstract

The portable privacy screen includes one or more barrier sections, a plurality of guylines, and a plurality of stakes. The portable privacy screen may be a visual barrier that may be adapted to be erected at an accident scene to provide privacy for an accident victim. An individual barrier section selected from the one or more barrier sections may be collapsed for storage within an emergency vehicle when not in use. The individual barrier section may be secured in place by a plurality of aprons located at the bottom of the individual barrier section, by the plurality of guylines, by the plurality of stakes, or by any combination thereof. The one or more barrier sections may be coupled end-to-end to lengthen the visual barrier.

Inventors:	Hillis; Logan (Houston, TX)
Applicant:	Hillis; Logan (Houston, TX)
Family ID:	-1000007200250
Appl. No.:	18/208956
Filed:	June 13, 2023

Publication Classification

Int. Cl.: E01F13/00 (20060101); **E04H15/48** (20060101); E04H15/32 (20060101)

U.S. Cl.:

CPC **E04H15/48** (20130101); **E01F13/00** (20130101); E04H2015/328 (20130101)

Field of Classification Search

CPC: E04H (15/48); E04H (2015/328); E04H (15/003); E04H (15/005); E01F (15/06); E01F (15/065); E01F (15/10); E01F (7/00); E01F (7/02); E01F (7/025); E01F (7/04); E01F (7/045); E01F (7/06)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2652845	12/1952	O'Neill	135/90	E04H 15/003
4124196	12/1977	Hipskind	N/A	N/A
4134439	12/1978	Scott	N/A	N/A
4186912	12/1979	Byrd	N/A	N/A
4529173	12/1984	Kramer	256/12.5	E01F 7/02
4533122	12/1984	Bannister	N/A	N/A
5269623	12/1992	Hanson	N/A	N/A
5371982	12/1993	Douglas	52/64	E01F 7/00
5373863	12/1993	Prizio	135/117	E04H 15/001
5379786	12/1994	Lynam	160/135	E04H 15/003
5553648	12/1995	Goharjou	160/237	E01F 7/00
5595230	12/1996	Guerra	N/A	N/A
5732935	12/1997	Codario, Jr.	256/31	E01F 7/025
6036249	12/1999	Kuntz	N/A	N/A
6360761	12/2001	Zheng	220/9.3	A63B 9/00
D486529	12/2003	Valenzuela	N/A	N/A
6733204	12/2003	Paniccia	N/A	N/A
6969185	12/2004	Adair	362/486	G09F 7/00
7252106	12/2006	Conforti	135/117	B60J 1/2091
7600554	12/2008	Wright	N/A	N/A
8579007	12/2012	Pottmeyer	160/351	A01M 31/025
D707599	12/2013	Pifer, III	D12/183	N/A
8915258	12/2013	Beam	135/117	E04H 15/001
8973645	12/2014	Cannova	160/351	E01F 7/00
9629470	12/2016	Bussell	N/A	A47C 7/666
10697141	12/2019	Hillis	N/A	N/A
11199021	12/2020	Cox	N/A	E04H 15/60
11486159	12/2021	Shull	N/A	E04H 15/005
11758900	12/2022	Sharp	160/351	A01M 29/30
2006/0060310	12/2005	Haugen	160/135	G09F 7/18
2006/0213628	12/2005	McLoughlin	160/351	E01F 7/00
2008/0054038	12/2007	Tonkin	224/575	A45C 15/00
2008/0251775	12/2007	Haslem	256/12.5	E01F 7/025

2010/0288450	12/2009	Bruck	248/176.1	F16M 11/242
2013/0008617	12/2012	Rivera	160/127	G09F 15/0025
2013/0048044	12/2012	Hope	135/144	E04H 15/005
2013/0233365	12/2012	Loos	135/114	E04H 15/005
2016/0143453	12/2015	Shapiro	256/25	A47D 13/063
2020/0256083	12/2019	Xu	N/A	E04H 15/34
2022/0395115	12/2021	Le	N/A	A47G 5/00

Primary Examiner: Shablack; Johnnie A.

Background/Summary

CROSS REFERENCES TO RELATED APPLICATIONS

(1) Not Applicable

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH

(2) Not Applicable

REFERENCE TO APPENDIX

(3) Not Applicable

BACKGROUND OF THE INVENTION

Field of the Invention

(4) The present invention relates to the fields of emergency equipment and privacy barriers, more specifically, a portable privacy screen.

SUMMARY OF INVENTION

(5) The portable privacy screen comprises one or more barrier sections, a plurality of guylines, and a plurality of stakes. The portable privacy screen may be a visual barrier that may be adapted to be erected at an accident scene to provide privacy for an accident victim. An individual barrier section selected from the one or more barrier sections may be collapsed for storage within an emergency vehicle when not in use. The individual barrier section may be secured in place by a plurality of aprons located at the bottom of the individual barrier section, by the plurality of guylines, by the plurality of stakes, or by any combination thereof. The one or more barrier sections may be coupled end-to-end to lengthen the visual barrier.

(6) An object of the invention is to provide a visual barrier that may erected at an accident scene to provide privacy for an accident victim.

(7) Another object of the invention is to provide one or more barrier sections that may be secured in a vertical orientation by a plurality of aprons, a plurality of guylines, a plurality of stakes, or any combination thereof.

(8) A further object of the invention is to a plurality of buckle clips are both ends of individual barrier sections such that the visual barrier may be extended in length.

(9) Yet another object of the invention is to collapse an individual barrier section and store the individual barrier section in a storage bag when not in use.

(10) These together with additional objects, features and advantages of the portable privacy screen will be readily apparent to those of ordinary skill in the art upon reading the following detailed description of the presently preferred, but nonetheless illustrative, embodiments when taken in conjunction with the accompanying drawings.

(11) In this respect, before explaining the current embodiments of the portable privacy screen in detail, it is to be understood that the portable privacy screen is not limited in its applications to the details of construction and arrangements of the components set forth in the following description or illustration. Those skilled in the art will appreciate that the concept of this disclosure may be

readily utilized as a basis for the design of other structures, methods, and systems for carrying out the several purposes of the portable privacy screen.

(12) It is therefore important that the claims be regarded as including such equivalent construction insofar as they do not depart from the spirit and scope of the portable privacy screen. It is also to be understood that the phraseology and terminology employed herein are for purposes of description and should not be regarded as limiting.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The accompanying drawings, which are included to provide a further understanding of the invention are incorporated in and constitute a part of this specification, illustrate an embodiment of the invention and together with the description serve to explain the principles of the invention. They are meant to be exemplary illustrations provided to enable persons skilled in the art to practice the disclosure and are not intended to limit the scope of the appended claims.

(2) FIG. 1 is an isometric view of an embodiment of the disclosure.

(3) FIG. 2 is an isometric in-use view of an embodiment of the disclosure.

(4) FIG. 3 is a front view of an embodiment of the disclosure.

(5) FIG. 4 is a rear view of an embodiment of the disclosure.

(6) FIG. 5 is a side view of an embodiment of the disclosure.

(7) FIG. 6 is a front detail view of an embodiment of the disclosure.

(8) FIG. 7 is a front detail view of an embodiment of the disclosure, illustrating storage of an individual barrier section.

(9) FIG. 8 is an in-use view of an embodiment of the disclosure, illustrating storage of the invention on an emergency vehicle.

(10) FIG. 9 is an in-use view of an embodiment of the disclosure, illustrating the invention erected at an accident scene.

DETAILED DESCRIPTION OF THE EMBODIMENT

(11) The following detailed description is merely exemplary in nature and is not intended to limit the described embodiments of the application and uses of the described embodiments. As used herein, the word “exemplary” or “illustrative” means “serving as an example, instance, or illustration.” Any implementation described herein as “exemplary” or “illustrative” is not necessarily to be construed as preferred or advantageous over other implementations. All of the implementations described below are exemplary implementations provided to enable persons skilled in the art to practice the disclosure and are not intended to limit the scope of the appended claims. Furthermore, there is no intention to be bound by any expressed or implied theory presented in the preceding technical field, background, brief summary or the following detailed description. As used herein, the word “or” is intended to be inclusive.

(12) Detailed reference will now be made to a first potential embodiment of the disclosure, which is illustrated in FIGS. 1 through 9.

(13) The portable privacy screen **100** (hereinafter invention) comprises one or more barrier sections **200**, a plurality of guylines, and a plurality of stakes **270**. The invention **100** may be a visual barrier that may be adapted to be erected at an accident scene to provide privacy for an accident victim **920**. An individual barrier section **210** selected from the one or more barrier sections **200** may be collapsed for storage within an emergency vehicle **900** when not in use. The individual barrier section **210** may be secured in place by a plurality of aprons located at the bottom of the individual barrier section **210**, by the plurality of guylines, by the plurality of stakes **270**, or by any combination thereof. The one or more barrier sections **200** may be coupled end-to-end to lengthen the visual barrier.

(14) The individual barrier section **210** may comprise a plurality of barrier panels and the plurality of aprons. An individual barrier panel selected from the plurality of barrier panels May be an opaque rectangular panel erected in a vertical orientation to block a sight line. As a non-limiting example, the individual barrier panel may block the sight line between the accident victim **920** and a motorist passing by the accident scene. The plurality of aprons may be flexible extensions coupled to the bottom of one or more of the plurality of barrier panels that may be operable to retain the bottom of the individual barrier panel in place.

(15) In a preferred embodiment, the individual barrier section may comprise three barrier panels and two aprons. The three barrier panels may comprise a left barrier panel **220**, a center barrier panel **230**, and a right barrier panel **240**. The two aprons may comprise a left apron **212** that may be coupled to the bottom of the left barrier panel **220** and a right apron **214** that may be coupled to the bottom of the right barrier panel **240**. The plurality of barrier panels may be hingedly coupled such that the left barrier panel **220** and the right barrier panel **240** May fold back by 180 degrees to a position that is adjacent to the center barrier panel **230**.

(16) The left barrier panel **220** may comprise an upper pair of left panel buckle clips **222** and a lower pair of left panel buckle clips **224**. The right barrier panel **240** may comprise an upper pair of right panel buckle clips **242** and a lower pair of right panel buckle clips **244**. The upper pair of left panel buckle clips **222** and the lower pair of left panel buckle clips **224** on a first barrier section **202** may detachably couple to the upper pair of right panel buckle clips **242** and the lower pair of right panel buckle clips **244** on a second barrier section **204** such that the first barrier section **202** may be detachably coupled to the second barrier section **204** to lengthen the visual barrier.

(17) The individual barrier panel selected from the left barrier panel **220**, the center barrier panel **230**, and the right barrier panel **240** may comprise a wire frame **232**, a fabric center **234**, and a guyline loop **236**. The fabric center **234** may be coupled to the wire frame **232**. The wire frame **232** may support the fabric center **234** when the visual barrier is erected. The fabric center may be a piece of flexible and opaque material that may be stretched by the wire frame **232**. As a non-limiting example, the fabric center **234** may be made of a lightweight material such as nylon to enhance the portability of the individual barrier section **210**.

(18) The guyline loop **236** may be a loop of material coupled to the top center of the individual barrier panel. The guyline loop **236** may be operable to secure an individual guyline **272** to the individual barrier panel in order to support the top of the individual barrier panel.

(19) An individual apron may be operable to anchor the bottom of the individual barrier panel when the visual barrier is erected. The individual apron selected from the left apron **212** and the right apron **214** may comprise a front apron half **250** and a rear apron half **252**. The front apron half **250** may be coupled to the bottom front of the individual barrier panel and the rear apron half **252** may be coupled to the bottom rear of the individual barrier panel. Both the front apron half **250** and the rear apron half **252** may hang down below the bottom of the individual barrier panel. The front apron half **250** may be pulled to the front of the individual barrier panel and the rear apron half **252** may be pulled to the rear of the individual barrier panel.

(20) An individual apron half selected from the front apron half **250** and the rear apron half **252** may comprise a plurality of stake apertures **254**. The individual apron may anchor the bottom of the individual barrier panel by driving the plurality of stakes **270** through the plurality of stake apertures **254**. Alternatively, the individual apron may anchor the individual barrier panel by placing one or more objects on the front apron half **250** and/or the rear apron half **252**. As a non-limiting example, the one or more objects may comprise a medical bag **910**, tool box, and/or other equipment from the emergency vehicle **900**.

(21) An individual pair of buckle clips selected from the upper pair of left panel buckle clips **222**, the lower pair of left panel buckle clips **224**, the upper pair of right panel buckle clips **242**, and the lower pair of right panel buckle clips **244** may comprise a male buckle half **262** and a female buckle half **264** coupled to the individual barrier panel separately and used independently. By

presenting both the male buckle half **262** and the female buckle half **264**, the individual pair of buckle clips on the first barrier section **202** may couple to the individual pair of buckle clips on the second barrier section **204** without the possibility that the second barrier section **204** may require rotation by 1180 degrees because of a gender mismatch between the individual pairs of buckle clips.

(22) The plurality of guylines may be operable to support the tops of the plurality of barrier panels. The center of the **8** individual guyline **272** selected from the plurality of guylines may be coupled to the guyline loop **236** at the top center of the individual barrier panel. The ends of the individual guyline **272** may be pulled to ground level in front of the individual barrier panel and behind the individual barrier panel and both ends may be secured using individual stakes **274** or by some other means. The individual guyline **272** may prevent the individual barrier panel from leaning forward or rearward.

(23) In some embodiments, the invention **100** may further comprise a storage bag **280** that the individual barrier section **210** may be stored within when the individual barrier section **210** is collapsed.

(24) To collapse the individual barrier section **210**, the left barrier panel **220** and the right barrier panel **240** may first be folded back 180 degrees to positions that place the left barrier panel **220** and the right barrier panel **240** adjacent to the center barrier panel **230** on opposite sides of the center barrier panel **230**. The wire frames **232** of the left barrier panel **220**, the center barrier panel **230**, and the right barrier panel **240** may then be treated as a single wire frame. The single wire frame may be adapted to be grasped by both hands and twisted to fold the single wire frame into a smaller size. The individual barrier section **210**, thus folded, may be placed into the storage bag **280**. To deploy the individual barrier section **210**, the individual barrier section **210** may be removed from the storage bag **280**, untwisted to restore the single wire frame to full size, and unfolded to reveal the left barrier panel **220**, the center barrier panel **230**, and the right barrier panel **240**.

(25) In use, the individual barrier section **210** may be removed from the storage bag **280** and expanded to the unfolded state by a user. As a non-limiting example, the user may be a first responder **952**. The individual barrier section **210** may be positioned to block sight lines between the accident victim **920** and motorists. The bottom of the individual barrier section **210** may be secured using the plurality of aprons. Specifically, the plurality of aprons may be staked, weights may be placed upon the plurality of aprons, or both. The top of the individual barrier section **210** may be secured using the plurality of guylines. Specifically, the individual guylines **272** may be coupled to the guyline loops **236** located at the top of the individual barrier sections **210** and the ends of the individual guylines **272** may be staked.

(26) A first barrier section **202** may be detachably coupled to a second barrier section **204** to lengthen the visual barrier by coupling the upper pair of left panel buckle clips **222** on the first barrier section **202** to the upper pair of right panel buckle clips **242** on the second barrier section **204** and by coupling the lower pair of left panel buckle clips **224** on the first barrier section **202** to the lower pair of right panel buckle clips **244** on the second barrier section **204**. At each coupling of the upper pair of left panel buckle clips **222** to the upper pair of right panel buckle clips **242** or the lower pair of left panel buckle clips **224** to the lower pair of right panel buckle clips **244**, the male buckle half **262** on the first barrier section **202** may be coupled to the female buckle half **264** on the second barrier section **204** or the female buckle half **264** on the first barrier section **202** may be coupled to the male buckle half on the second barrier section **204** with regard for the orientation of the first barrier section **202** relative to the second barrier section **204**.

Definitions

(27) Unless otherwise stated, the words “up”, “down”, “top”, “bottom”, “upper”, and “lower” should be interpreted within a gravitational framework. “Down” is the direction that gravity would pull an object. “Up” is the opposite of “down”. “Bottom” is the part of an object that is down farther than any other part of the object. “Top” is the part of an object that is up farther than any

other part of the object. “Upper” may refer to top and “lower” may refer to the bottom. As a non-limiting example, the upper end of a vertical shaft is the top end of the vertical shaft.

(28) As used in this disclosure, an “anchor” may be a device that holds an object in place. When used as a verb, “anchor” may refer to holding an object firmly or securely.

(29) As used in this disclosure, an “aperture” may be an opening in a surface or object. Aperture may be synonymous with hole, slit, crack, gap, slot, or opening.

(30) As used in this disclosure, the word “buckle” may refer to any fastener that is used for joining a first loose end of a strap to a second loose end of the same strap or to a loose end of a different strap.

(31) As used herein, the words “couple”, “couples”, “coupled” or “coupling”, may refer to connecting, either directly or indirectly, and does not necessarily imply a mechanical connection.

(32) As used herein, “deploy” may refer to configuring a device to place the device into service or to make the device ready for service. As non-limiting examples, “deployed” may be synonymous with extended, unfolded, inflated, erected, or activated. As non-limiting examples, a device that is not deployed may be referred to as retracted, folded, deflated, withdrawn, collapsed, stowed, or deactivated.

(33) As used in this disclosure, “flexible” may refer to an object or material which will deform when a force is applied to it, which will not return to its original shape when the deforming force is removed, and which may not retain the deformed shape caused by the deforming force.

(34) As used herein, “front” may indicate the side of an object that is closest to a forward direction of travel under normal use of the object or the side or part of an object that normally presents itself to view or that is normally used first. “Rear” or “back” may refer to the side that is opposite the front.

(35) Unless noted otherwise, “ground” may refer to any surface which may support items and individuals. As non-limiting examples, ground may refer to an earthen surface whether covered by vegetation or not, a floor, a tarmac, a driveway, a road, a deck, bedrock, or a stage. The phrase “from the ground” may refer to performing an activity while standing on such a surface as opposed to climbing a ladder.

(36) As used in this disclosure, “orientation” may refer to the positioning and/or angular alignment of a first object relative to a second object or relative to a reference position or reference direction.

(37) As used herein, “rectangle” and “rectangular” may refer to a closed figure comprising four straight lines joined by four right angles. The opposing sides of a rectangle have equal length. A square is considered to be a special type of rectangle where all four sides are the same length. An object may still be considered to have a generally rectangular shape even if corners of the object are rounded off as long as two sets of opposing, straight-line, perpendicular sides are apparent.

(38) As used herein, “sightline” may refer to an imaginary line between an observer's eye(s) and a subject of interest. A sightline may also be referred to as a “line of sight”. As used in this disclosure, a “stake” may be a shaft that is driven into a horizontal surface, such as the ground, to serve as an anchor point.

(39) As used in this disclosure, “vertical” may refer to a direction that is parallel to the local force of gravity. Unless specifically noted in this disclosure, the vertical direction is always perpendicular to horizontal.

(40) With respect to the above description, it is to be realized that the optimum dimensional relationship for the various components of the invention described above and in FIGS. 1 through 9, include variations in size, materials, shape, form, function, and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by the invention.

(41) It shall be noted that those skilled in the art will readily recognize numerous adaptations and modifications which can be made to the various embodiments of the present invention which will

result in an improved invention, yet all of which will fall within the spirit and scope of the present invention as defined in the following claims. Accordingly, the invention is to be limited only by the scope of the following claims and their equivalents.

Claims

1. A portable privacy screen comprising: one or more barrier sections, a plurality of guylines, and a plurality of stakes; wherein the portable privacy screen is a visual barrier that is adapted to be erected at an accident scene to provide privacy for an accident victim; wherein an individual barrier section selected from the one or more barrier sections is collapsible for storage within an emergency vehicle; wherein a selected individual barrier section is coupled end-to-end to another selected individual barrier section in order to lengthen the visual barrier; wherein the individual barrier section comprises a plurality of barrier panels a plurality of aprons; wherein an individual barrier panel selected from the plurality of barrier panels is an opaque rectangular panel erected in a vertical orientation to block a sight line; wherein the plurality of aprons are flexible extensions coupled to the bottom of one or more of the plurality of barrier panels that are operable to retain the bottom of the individual barrier panel in place; wherein the plurality of barrier panels are hingedly coupled such that a left barrier panel and a right barrier panel fold back by 180 degrees to a position that is adjacent to the center barrier panel; wherein the individual barrier panel selected from the left barrier panel, a center barrier panel, and the right barrier panel comprises a wire frame, a fabric center, and a guyline loop; wherein the guyline loop is operable to secure an individual guyline to the individual barrier panel in order to support the top of the individual barrier panel.
2. The portable privacy screen according to claim 1 wherein the individual barrier section is secured in place by the plurality of aprons located at the bottom of the individual barrier section, by the plurality of guylines, by the plurality of stakes, or by any combination thereof.
3. The portable privacy screen according to claim 2 wherein the individual barrier section comprises three barrier panels and two aprons; wherein the three barrier panels comprises the left barrier panel, the center barrier panel, and the right barrier panel; wherein the two aprons comprises a left apron that is coupled to the bottom of the left barrier panel and a right apron that is coupled to the bottom of the right barrier panel.
4. The portable privacy screen according to claim 3 wherein the left barrier panel comprises an upper pair of left panel buckle clips and a lower pair of left panel buckle clips; wherein the right barrier panel comprises an upper pair of right panel buckle clips and a lower pair of right panel buckle clips; wherein the upper pair of left panel buckle clips and the lower pair of left panel buckle clips on a first barrier section detachably couple to the upper pair of right panel buckle clips and the lower pair of right panel buckle clips on a second barrier section such that the first barrier section detachably couples to the second barrier section to lengthen the visual barrier.
5. The portable privacy screen according to claim 4 wherein the fabric center is coupled to the wire frame; wherein the wire frame supports the fabric center.
6. The portable privacy screen according to claim 5 wherein the fabric center is a piece of flexible and opaque material that is stretched by the wire frame.
7. The portable privacy screen according to claim 6 wherein the fabric center is made of nylon.
8. The portable privacy screen according to claim 6 wherein the guyline loop is a loop of material coupled to the top center of the individual barrier panel.
9. The portable privacy screen according to claim 8 wherein an individual apron is operable to anchor the bottom of the individual barrier panel when the visual barrier is erected; wherein the individual apron selected from the left apron and the right apron comprises a front apron half and a rear apron half; wherein the front apron half is coupled to the bottom front of the individual barrier panel and the rear apron half is coupled to the bottom rear of the individual barrier panel; wherein

both the front apron half and the rear apron half hang down below the bottom of the individual barrier panel; wherein the front apron half is pulled to the front of the individual barrier panel and the rear apron half is pulled to the rear of the individual barrier panel.

10. The portable privacy screen according to claim 9 wherein an individual apron half selected from the front apron half and the rear apron half comprises a plurality of stake apertures; wherein the individual apron anchors the bottom of the individual barrier panel by driving the plurality of stakes through the plurality of stake apertures.

11. The portable privacy screen according to claim 9 wherein the individual apron anchors the individual barrier panel by placing one or more objects on the front apron half and/or the rear apron half.

12. The portable privacy screen according to claim 9 wherein an individual pair of buckle clips selected from the upper pair of left panel buckle clips, the lower pair of left panel buckle clips, the upper pair of right panel buckle clips, and the lower pair of right panel buckle clips comprises a male buckle half and a female buckle half coupled to the individual barrier panel separately and usable independently.

13. The portable privacy screen according to claim 12 wherein the plurality of guylines are operable to support the tops of the plurality of barrier panels; wherein the center of the individual guyline selected from the plurality of guylines is coupled to the guyline loop at the top center of the individual barrier panel.

14. The portable privacy screen according to claim 13 wherein the ends of the individual guyline are pulled to ground level in front of the individual barrier panel and behind the individual barrier panel and both ends are secured using individual stakes; wherein the individual guyline prevents the individual barrier panel from leaning forward or rearward.

15. The portable privacy screen according to claim 14 wherein the portable privacy screen further comprises a storage bag that the individual barrier section is stored within when the individual barrier section is collapsed.

16. The portable privacy screen according to claim 15 wherein to collapse the individual barrier section, the left barrier panel and the right barrier panel are first folded back 180 degrees to positions that place the left barrier panel and the right barrier panel adjacent to the center barrier panel on opposites sides of the center barrier panel; wherein the wire frames of the left barrier panel, the center barrier panel, and the right barrier panel are then treated as a single wire frame; wherein the single wire frame is adapted to be grasped by both hands and twisted to fold the single wire frame into a smaller size; wherein the individual barrier section, thus folded, is placed into the storage bag; wherein to deploy the individual barrier section, the individual barrier section is removed from the storage bag, untwisted to restore the single wire frame to full size, and unfolded to reveal the left barrier panel, the center barrier panel, and the right barrier panel.

17. A portable privacy screen comprising: one or more barrier sections; wherein the portable privacy screen is a visual barrier that is adapted to be erected at an accident scene to provide privacy for an accident victim; wherein an individual barrier section selected from the one or more barrier sections is collapsible for storage within an emergency vehicle; wherein a selected individual barrier section is coupled end-to-end to another selected individual barrier section in order to lengthen the visual barrier; a plurality of guylines, and a plurality of stakes; wherein the individual barrier section is secured in place by a plurality of aprons located at the bottom of the individual barrier section, by the plurality of guylines, by the plurality of stakes, or by any combination thereof; wherein the individual barrier section comprises a plurality of barrier panels and the plurality of aprons; wherein an individual barrier panel selected from the plurality of barrier panels is an opaque rectangular panel erected in a vertical orientation to block a sight line; wherein the plurality of aprons are flexible extensions coupled to the bottom of one or more of the plurality of barrier panels that are operable to retain the bottom of the individual barrier panel in place;

wherein the plurality of barrier panels are hingedly coupled such that the left barrier panel and the right barrier panel fold back by 180 degrees to a position that is adjacent to the center barrier panel.
