

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406106
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Ye; Tao et al.

Interpreter framework for a computer file

Abstract

A method for an interpreter framework is described. The method includes an interpreter module of a computing system receiving a first data file that includes multiple data sections. The interpreter module identifies each of the data sections of the first data file. Each data section includes data representing a real-world entity. For each respective data section of the first data file, the interpreter module parses information about the real-world entity represented by the data included in the data section. The interpreter module generates a second data file based on the parsed information for each of the data sections. The second data file includes encoded data for rendering a digital geographic structure using information about the real-world entity.

Inventors: Ye; Tao (Garfield, NJ), Yadav; Tejas (West Haven, CT), Rizvi; Asim (Howell, NJ)

Applicant: Nuvolo Technologies Corporation (Paramus, NJ)

Family ID: 67139485

Assignee: NUVOLO TECHNOLOGIES CORPORATION (Davidson, NC)

Appl. No.: 18/236444

Filed: August 22, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230409768 A1	Dec. 21, 2023

Related U.S. Application Data

continuation parent-doc US 17855509 20220630 US 11741272 child-doc US 18236444
continuation parent-doc US 17008029 20200831 US 11514205 20221129 child-doc US 17855509
continuation parent-doc US 16166885 20181022 US 10762250 20200901 child-doc US 17008029

Publication Classification

Int. Cl.: **G06F8/51** (20180101); **G06F8/41** (20180101); **G06F8/75** (20180101); **G06F16/2455** (20190101); **G06F16/29** (20190101); **G06F30/00** (20200101); **G06F30/13** (20200101)

U.S. Cl.:

CPC **G06F30/13** (20200101); **G06F8/427** (20130101); **G06F8/51** (20130101); **G06F8/75** (20130101); **G06F16/2455** (20190101); **G06F16/29** (20190101); **G06F30/00** (20200101);

Field of Classification Search

CPC: G06F (8/51); G06F (8/61); G06F (8/65); G06F (8/75); G06F (16/29); G06F (16/2455)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7542886	12/2008	Storms et al.	N/A	N/A
7869981	12/2010	Pendyala et al.	N/A	N/A
8484556	12/2012	Mcmillan et al.	N/A	N/A
8577905	12/2012	Gan et al.	N/A	N/A
9177418	12/2014	Bawden et al.	N/A	N/A
9275173	12/2015	Loomis et al.	N/A	N/A
9384308	12/2015	Snyder et al.	N/A	N/A
9459600	12/2015	Huffine	N/A	N/A
10628616	12/2019	Yadav et al.	N/A	N/A
10762250	12/2019	Ye et al.	N/A	N/A
11222148	12/2021	Yadav et al.	N/A	N/A
11514205	12/2021	Ye et al.	N/A	N/A
2002/0188622	12/2001	Wallen et al.	N/A	N/A
2004/0153824	12/2003	Devarajan et al.	N/A	N/A
2005/0071135	12/2004	Vredenburgh et al.	N/A	N/A
2005/0081161	12/2004	Macinnes et al.	N/A	N/A
2006/0041842	12/2005	Loberg	N/A	N/A
2008/0125892	12/2007	Hoguet	N/A	N/A
2010/0268513	12/2009	Loberg	N/A	N/A
2011/0087662	12/2010	Darby, Jr.	707/812	G06Q 50/08
2012/0290429	12/2011	Ostroff	N/A	N/A
2016/0140771	12/2015	Chang et al.	N/A	N/A
2017/0092012	12/2016	Palanivelu et al.	N/A	N/A
2019/0057110	12/2018	Albrecht et al.	N/A	N/A
2019/0212991	12/2018	Ye et al.	N/A	N/A
2019/0213287	12/2018	Ye et al.	N/A	N/A
2020/0334392	12/2019	Yadav et al.	N/A	N/A

2020/0394344	12/2019	Ye et al.	N/A	N/A
2022/0171895	12/2021	Yadav et al.	N/A	N/A
2022/0335174	12/2021	Ye et al.	N/A	N/A

OTHER PUBLICATIONS

(Sep. 11, 2015) Stack Exchange, “How to Extract Style Data from DXF when Converting to GeoJSON”, 3 pages. cited by applicant

Primary Examiner: Nguyen; Duy Khuong T

Attorney, Agent or Firm: Womble Bond Dickinson (US) LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation and claims priority to U.S. application Ser. No. 17/855,509 filed Jun. 30, 2022 and entitled “INTERPRETER FRAMEWORK FOR A COMPUTER FILE”, which is a continuation of U.S. application Ser. No. 17/008,029 filed on Aug. 31, 2020 and entitled “INTERPRETER FRAMEWORK FOR A COMPUTER FILE,” which is a continuation of U.S. application Ser. No. 16/166,885 filed on Oct. 22, 2018 and entitled “INTERPRETER FRAMEWORK FOR A COMPUTER FILE,” which claims the benefit of U.S. Provisional Application 62/614,857 filed on Jan. 8, 2018 and entitled “INTERPRETER FRAMEWORK FOR A COMPUTER FILE” and claims the benefit of U.S. Provisional Application 62/614,870 filed on Jan. 8, 2018 and entitled “SPACE PROFILE INTERPRETER FRAMEWORK FOR A COMPUTER FILE,” the disclosures of which are incorporated by reference herein in their entirety.

BACKGROUND

(1) This application relates to computing processes for converting electronic files.
(2) DXF files are generated by a computer-aided design (CAD) program (e.g., commercial CAD programs or drafting software applications) and encode data representations of real-world constructs. For example, the data representations can be two dimensional floorplans for a building, where the floorplans include different outlines for each room of a floor. Data representations of real-world constructs in separate DXF files can be encoded and arranged differently based on preferences and design choices used in the CAD program. Because data representations can be encoded in DXF files in a variety of ways, interpreting DXF files can be challenging.

SUMMARY

(3) A DXF drawing file can be converted to a GeoJSON file by parsing and extracting data from sections of the DXF drawing file. The extracted data is converted to GeoJSON format and aggregated to create a GeoJSON file for viewing and modifying representations of real-world constructs. A computer application can interpret DXF files irrespective of the different ways in which data defining the representations is arranged within the files. For example, the computer application incorporates a standard method for identifying certain sections of the DXF files, extracting relevant information from the sections, converting the extracted information, and aggregating or rendering the information to produce the GeoJSON file.
(4) One aspect of the subject matter described in this specification can be embodied in a computer-implemented method. The method includes, receiving, at an interpreter module of a computing system, a first electronic data file comprising multiple respective data sections; identifying, by the interpreter module, each of the respective data sections of the first electronic data file, each data section comprising data representing a real-world entity of the first electronic data file. For each of

the respective data sections, the method includes, parsing, by the interpreter module, information about the real-world entity represented by the data included in the data section. The method further includes, generating, by the interpreter module and based on each of the respective data sections, a second electronic data file comprising encoded data for rendering at least one digital geographic structure using information about the real-world entity represented by the data included in the data section.

(5) These and other implementations can each optionally include one or more of the following features. For example, in some implementations, parsing the information about the real-world entity includes: extracting dimensional coordinates for the real-world entity, the dimensional coordinates defining characteristics of the real-world entity; and in response to extracting, digitally rendering the at least one geographic structure using the dimensional coordinates.

(6) In some implementations, generating the second electronic data file includes: converting, to a geospatial data format, the extracted dimensional coordinates for the real-world entity, wherein the geospatial data format includes at least one dataset comprising geometry or physical attribute information about the real-world entity; translating the digital geographic structure by aggregating the converted dimensional coordinates that have the geospatial data format; and generating the second electronic data file based on the rendered digital geographic structure.

(7) In some implementations, the information about the real-world entity represented by the data included in each of the respective data sections at least one of: i) defines an outline of the real-world entity, or ii) is descriptive of the real-world entity. In some implementations, the first electronic data file defines multiple layers, each layer representing a feature of a digitally rendered geographic structure; and each of the respective data sections corresponds to a particular layer of the multiple layers defined by the first electronic file.

(8) In some implementations, the real-world entity defines a virtual boundary of the feature of the digitally rendered geographic structure, and the layer corresponds to a floorplan of a physical space renderable as a digital geographic structure and the feature corresponds to a shape of at least a portion of the floorplan. In some implementations, the interpreter module is configured to communicate with an enterprise system that manages one or more assets and the method further includes: associating, by a mapping module of the computing system, at least one asset managed by the enterprise system with at least one feature of the digitally rendered geographic structure based on a location hierarchy for the geographic structure.

(9) In some implementations, the first electronic data file: i) is a drawing file generated by a particular application program; ii) includes data for encoding one or more graphical objects; and iii) that has a first file format for enabling interoperability between the drawing file generated by the particular application program and one or more other application programs. In some implementations, the particular application program is a computer-aided design (CAD) application program; and the first file format corresponds to a drawing exchange format (DXF).

(10) In some implementations, the second electronic data file has a second file format that corresponds to a geospatial data interchange format for encoding one or more geographic data structures. In some implementations, the second electronic data file comprises encoded data for rendering multiple respective digital geographic structures, and each respective digital geographic structure corresponds to a particular real-world entity of multiple real-world entities represented by the data included in the data section.

(11) Other implementations of this and other aspects include corresponding systems, apparatus, and computer programs, configured to perform the actions of the methods, encoded on computer storage devices. A computing system of one or more computers or hardware circuits can be so configured by virtue of software, firmware, hardware, or a combination of them installed on the system that in operation cause the system to perform the actions. One or more computer programs can be so configured by virtue of having instructions that, when executed by a data processing apparatus, cause the apparatus to perform the actions.

(12) The subject matter described in this specification can be implemented to realize one or more of the following advantages. DXF files can be interpreted irrespective of the different ways in which data is arranged within the files. The described standardized framework can be implemented to efficiently identify sections of DXF files, parse entity data for the sections, and to extract relevant entity records from the sections. Processes are described for extracting coordinate data of the entity records and converting the extracted data from a raw DXF drawing file format to a GeoJSON geospatial data file format.

(13) The details of one or more implementations of the subject matter described in this specification are set forth in the accompanying drawings and the description below. Other potential features, aspects, and advantages of the subject matter will become apparent from the description, the drawings, and the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates an example computing system for executing an interpreter framework to convert one or more files.

(2) FIG. 2 illustrates an interpreter module of the example computing system of FIG. 1.

(3) FIG. 3 illustrates an example floorplan represented by a DXF file.

(4) FIG. 4 is a process flow chart for executing an interpreter framework to convert one or more files.

(5) FIG. 5 is a block diagram of a computing system that can be used in connection with methods described in this specification.

(6) Like reference numbers and designations in the various drawings indicate like elements.

DETAILED DESCRIPTION

(7) This document describes techniques for interpreting DXF files irrespective of the different data arrangements within the files. For example, the described techniques include a file interpreter framework for converting DXF files to GeoJSON files. Drawing files that have a DXF file format are often formatted to include multiple data sections. The described interpreter framework can be represented by a computer application that receives the drawing file and uses an interpreter module of the computer application to identify the different data sections of the drawing file. For example, the drawing file may be used to view renderings of a building floorplan and each data section of the file can include information about a layer of the floorplan. A layer of a floorplan can correspond to electrical lines of the floorplan or plumbing lines of the floorplan.

(8) Each data section can include objects that contain information about the section. For example, objects can be entity records containing graphical information defining shapes and outlines of objects in the floorplan. The computer application parses and extracts object information of the drawing file and converts the extracted object information to a renderable format. For example, the application can convert extracted dimensional coordinates of a DXF file to a geoJSON format for rendering geographic data structures. The application program then generates a geoJSON file that can be used to graphically render the floorplan of the DXF file.

(9) The DXF file format provides a file structure that includes the following types of data sections: i) a HEADER section that includes general information about the drawing; ii) a CLASSES section that holds the information for application-defined classes; iii) a TABLES section that contains definitions of named items; iv) a BLOCKS section that contains Block Definition entities describing the entities in the drawing; v) an ENTITIES section that contains the drawing entities, including any Block section references; vi) an OBJECTS section that contains data that applies to non-graphical objects; and vii) a THUMBNAILIMAGE section that contains the preview image for the DXF file.

(10) The GeoJSON file format is a format for encoding a variety of geographic data structures (e.g., encoded data). In general, the GeoJSON file format is a geospatial data interchange format based on JavaScript Object Notation (JSON) and is designed for representing geographical features, along with their non-spatial attributes. An object of a GeoJSON file may represent a geometry, a feature, or a collection of features. The features can include points (e.g., addresses and locations), line strings (e.g., streets, highways and boundaries), polygons (e.g., countries, provinces, tracts of land), and multi-part collections of these types. In some implementations, GeoJSON features can represent non-physical real-world entities. For example, mobile routing and navigation applications might describe signal coverage areas using the GeoJSON format.

(11) As used in this document, the interpreter framework can represent a specific set of computer-implemented rules for a standardized method of converting a DXF file to a geoJSON file. The interpreter framework enables the automation of specific computer-related DXF file interpretation and conversion tasks that previously could not be performed by computer systems in an efficient manner. The framework improves computer-based file conversion processes by enabling different arrangements of data representations in a DXF file to be automatically converted and rendered for viewing in a geoJSON format. Also, the described techniques provide a repeatable automated process that involves minimal human intervention and does not require manual execution of data parsing, extraction, or conversion functions. As such, the techniques enable computing systems to perform operations that the systems were previously unable to automatically perform due to the challenges of developing standardized methods for interpreting DXF files.

(12) FIG. 1 illustrates an example computing system **100** for executing an interpreter framework to convert one or more files. The system **100** generally includes a client system **102**, a computing server **104**, a cloud computing platform **112**, a client device **114**, and an enterprise asset management (EAM) system **116**. EAM is the management of the physical (and virtual) assets of an organization or business enterprise. Asset management can cover concepts including the design, construction, commissioning, operations, maintenance, decommissioning, or replacement of assets such as electronic devices, mechanical equipment, or facilities. An example EAM system can execute software programs that provide asset managers with computer-based options for holistically viewing and managing a variety of different company-owned resources.

(13) In general, the platform **112** can correspond to an example cloud-based computing system. For example, the platform **112** can enable access to certain application programs and code scripts for performing various data processing operations. In addition, the platform **112** can facilitate or enable the sharing of data communications between client and server devices of system **100**.

(14) The client system **102** can generally include one or more client devices **114**. Any of the client devices **114** can be a desktop computer, a laptop computer, a tablet device, a smart computer device, or one of other related electronic devices that are configured to execute example design application programs. The client system **102** executes a computer-aided design application **106** for generating one or more electronic data files **108**. In some implementations, the application **106** is an example computer-aided design (CAD) program (e.g., commercial CAD programs or drafting software applications) and the electronic data files **108** are DXF files generated by the CAD program. As described in further detail below, the DXF files are drawing files that encode data representations of real-world constructs.

(15) The computing server **104** includes a data interpreter module **110** and is generally configured to exchange data, including electronic data files, with the client system **102**. The server **104** is configured to access, implement, and/or execute the data interpreter module **110**. For example, the server **104** can obtain or receive one or more data files **108** from the client system **102**. As described in more detail below, the server **104** can cause the interpreter module **110** to execute specific computing processes for an interpreter framework. Using the interpreter module **110**, the server **104** can convert a first data file **108** in order to generate a corresponding new second data file **128**. For example, the server **104** uses the interpreter module **104** to execute specific computing

rules to interpret and convert data files **108** in order to generate the new data files **128**. The new second data files **128** may have file characteristics that are different than file characteristics of the first data files **108**.

(16) For example, a data file **108** can be a drawing file generated by a particular type of application **106** (e.g., a CAD program) and can include data for encoding one or more graphical objects. The data files **108** can have a file format for enabling interoperability between drawing files generated by the application **106** and one or more other application programs. In particular, the file format can be a drawing exchange format (DXF) which indicates file characteristics of the data files **108**. Using processes described in this document, a user can leverage the interoperability afforded by the DXF file format to interpret and convert a data file **108**, e.g., a DXF drawing file, to generate a corresponding data file **128**. The data file **128** has a geospatial data interchange format, e.g., GeoJSON format, for encoding one or more geographic data structures.

(17) While in typical implementations, the interpreter module **110** is encoded on computer-readable media, in some implementations, the interpreter module **110** is included within the server **104** as a sub-system of hardware circuits that includes one or more processing devices or processor microchips. In general, the server **104** can include processors, memory, and data storage devices that collectively form modules and computer systems of the server **104**. Processors of the computer systems process instructions for execution by the server **104**, including instructions stored in the memory or on the data storage device to display graphical information for output at an example display monitor of system **100**.

(18) Execution of the stored instructions can cause one or more of the actions described herein to be performed by the server **104** or the interpreter module **110**. In other implementations, multiple processors may be used, as appropriate, along with multiple memories and types of memory. For example, the server **104** may be connected with multiple other computing devices, with each device (e.g., a server bank, groups of servers, modules, or a multi-processor system) performing portions of the actions, operations, or logical flows described in this specification.

(19) The data interpreter module **110** executes a file interpreter framework for converting DXF files to GeoJSON files. The data interpreter module **110** processes programed instructions for executing a file importer **120**, a data extractor **122**, a data converter **124**, and a data translator **126**. As described in more detail below with reference to FIG. 2, the module **110** uses the importer **120** to receive or obtain the data file **108** from the client system **102**. The data file **108** can be a DXF drawing file that is formatted to include multiple data sections. Using the programmed instructions, the data interpreter module **110** executes a file interpreter framework for converting DXF files to GeoJSON files.

(20) For example, a DXF drawing file can be converted to a GeoJSON file by using importer **120** to receive and identify certain sections of the DXF file and then using data extractor **122** to parse and extract data from the identified sections of the DXF drawing file. Converter **124** interprets the extracted data and uses coded scripts to convert the data to a GeoJSON format. The data translator **126** is used to process and aggregate the converted data in order to create a GeoJSON file which corresponds to data file **128**. The data file **128** can be a GeoJSON file that is used by the EAM system **116** to view and modify existing representations of real-world constructs. In some implementations, the client device **114** is used to interface with the EAM system **116** to manage existing location hierarchies or to create new hierarchies based on information included in the GeoJSON data files **128**.

(21) FIG. 2 illustrates the interpreter module **110** of the computing system **100** described above with reference to FIG. 1. In particular, FIG. 2 shows an interpreter framework **200** used by the interpreter module **110** to convert a DXF file **204** to a GeoJSON file **218**. Framework **200** includes the interpreter module **110** receiving a DXF drawing file **204**. The interpreter module **110** imports or receives file **204** using the server **104**. In some implementations, the server **104** uses computing services enabled by the cloud computing platform **112** to access the file **204** from the client system

102 and to access the interpreter module **110**.

(22) For example, the interpreter module **110** can reside on a software service device of the cloud computing platform **112** and use the platform **112** to import the file **204**. In some implementations, the cloud computing platform **112** is a ServiceNow platform. In other implementations, computing logic for the file importing functions of identifier **120** are integrated with client system **102**. For example, file **204** can be stored on a file server of client system **102** and the interpreter module **110** can use the integrated importer function to retrieve the file **204**. Interpreter module **110** can be configured to support a variety of file retrieval methods, such as a file attachment upload method or methods involving the file transfer protocol (FTP).

(23) The server **104** can include an example management, instrumentation, and discovery (MID) server that is a Java-based application executed within an operating system of the server **104**. For example, a MID server can facilitate communication and movement of data between the cloud computing platform **112** and other application programs (e.g., external applications), data sources, and services. The server **104** can use the MID server application features to execute code scripts (e.g., JavaScript) as well as create or import additional script libraries for implementing features of the interpreter module **110** and the framework **200**.

(24) In some implementations, an application file that communicates with the MID server is installed on the client system **102** to allow the MID server and/or the server **104** to access network resources (e.g., DXF drawing files) stored at the client system **102**. The application file can be configured to facilitate streamlined access to the client system **102**. For example, the application file can be used by the client system **102** to provision data access permissions to the MID server and the server **104**. The permissions can facilitate direct access to data files and resources of the client system **102** irrespective of access restrictions imposed by firewalls or other network boundary devices of the client system.

(25) To perform the framework **200**, the interpreter module **110** receives the DXF file **204** (e.g., a drawing file) from client system **102**. The file **204** includes multiple respective data sections that can represent layers or other aspects of a DXF drawing file. Individual layers of a drawing file correspond to physical features or other characteristics of real-world constructs, such as plumbing or electrical lines of a building. In addition to the layers, the file **204** can include various types of data that can represent real-world entities. Data representing a real-world entity can be described at least as a data record or a data object of the DXF drawing file. An example data object can represent a graphical data structure for depicting lines and boundaries that define physical features of real-world constructs.

(26) The interpreter module **110** identifies each data section **206** of the DXF file **204**. For example, based on features of the server **104** and/or the MID server, the interpreter module **110** uses the identifier **120** to perform data processing and streaming operations for identifying data sections **206** of file **204**. In some implementations, data for the various data sections of file **204** are streamed to the compute blocks of the interpreter module **110** and processed in real-time. In other implementations, each compute block consumes an entire file **204** by storing the file in memory and then processing the file **204** to perform a particular operation for interpreting data contents of the file.

(27) The interpreter module **110** parses and extracts objects and/or information **208** about real-world entities from the file layers that correspond to the identified data sections **206**. As used herein, real-world entities represent actual physical and non-physical items/things of the real-world that can be graphically rendered and displayed at a computer system display monitor as a computer-generated object. Examples of a real-world entity include a layout of a floor of a building, a campus location, buildings at the campus, rooms of the building, a computing device positioned in a room, a detectable wireless signal range of the computing device, or plumbing lines of the building.

(28) For clarity, data representing real-world entities relates to electronic data for producing the

computer-generated objects that can be graphically displayed at a display monitor of a computer system. Hence, data representing real-world entities is different than the actual physical (and non-physical) items that correspond to the real world entities. In some implementations, real-world entities can indicate signal coverage ranges, sprinkler system ranges, or physical attributes and dimensions of real-world construct. For example, the information **208** about real-world entities extracted from the file layers can: i) define an outline of the real-world entity, e.g., size or shape of the entity, or ii) is descriptive of the real-world entity, e.g., indicates a Wi-Fi signal range or identifies a type of electrical line.

(29) The DXF file **204** can define multiple layers that each include information about features of a digitally renderable real-world entity (e.g., a geographic structure or location). In some implementations, each layer includes data that defines a virtual boundary of the feature of the digitally rendered real-world entity. For example, a layer can correspond to a physical building, a floorplan, or campus location floorplan, and the feature can correspond to a shape of at least a portion of the particular real-world entities for that layer.

(30) The interpreter module **110** uses the data extractor **122** to parse data for a layer and forms sets of individual entity records based on the parsed data. Using the sets of individual entity records, the data extractor **122** extracts dimensional coordinates and/or descriptive information **210** for the real-world entity. For example, each entity record can correspond to a shape or feature of the real-world entity and can include dimensional coordinates that define an outline and other characteristics of the real-world entity. Extracted dimensional coordinates **210** can define the lines and boundaries of a real-world entity.

(31) The interpreter module **110** uses the converter **124** to convert the extracted dimensional coordinates **210** to a GeoJSON file format **212**. For example, the converter **124** processes raw numerical line data, e.g., for the dimensional coordinates **210**, in the native DXF file format to generate new GeoJSON data structures. The generated GeoJSON data **212** includes geometry or physical attribute information about real-world entities of the DXF file **204**. The interpreter module **110** uses the data translator **126** to translate and digitally render geographic structures **214** using the GeoJSON data **212** that are based the converted dimensional coordinates **210**. As used in this document, translating and rendering relates to using extracted DXF file coordinates **210** that have been converted to the GeoJSON file format **212** to reconstruct (e.g., render) a particular shape or outline of a real-world entity. The data translator **126** renders a digital geographic structure **214** by aggregating converted dimensional coordinates **210** that have the geospatial data format **212**. A digital geographic structure depicts a real-world entity (or multiple real-world entities) and is computer-generated for graphical rendering and display using a computer system. The aggregated dimensional coordinates **210** represent rendered geographic data structures **214** and are used to generate GeoJSON file **218**.

(32) The interpreter module **110** can communicate with the EAM system **116** that manages assets for at least one location hierarchy **220**. The EAM system **116** uses the GeoJSON file **218** to obtain entity meta data about the real-world entities represented by data in the DXF file **204**. For example, the entity meta data can include descriptions of physical assets associated with a real-world entity or space profile information indicating a size or dimension of a real-world entity, such as a size of room in a building.

(33) The EAM system **116** can modify existing representations, or create new representations, of real-world entities and buildings using the entity metadata included in the GeoJSON file **218**. In some implementations, the EAM system **116** uses a mapping module **222** of the system **100** to associate assets managed by the enterprise system with features of a real-world entity represented in the DXF file **204**. For example, the module **222** can associate the assets of a location hierarchy **220** with real-world entities based on a relationship between the assets and the real world entities.

(34) For example, the mapping module **222** can be a data processor (e.g., a software module that processes data) that uses programmed instructions to scan an existing asset database for information

about assets (e.g., real-entities) of a location hierarchy **220**. The module **222** can also analyze information about real-world entities identified in the file **218**. Based on the scanning and analysis, the module **222** can determine relationships between the assets of the database and the real-world entities included in the file **218**. For example, a relationship between the asset and the real-world entity can be defined based on the asset and the entity associated with the same virtual floorplan or layer of the location hierarchy **220**. In some implementations, the location hierarchy **220** includes existing feature locations and floor plan details of the multiple real-world entities that are identified and included in file geoJSON file **218**.

(35) FIG. **3** illustrates a diagram **300** of real-world entities that can be represented by the DXF file **204**. The diagram **300** can include data representations of real-world entities for at least a floorplan layer of the DXF file **204**. For example, the data representations can be two dimensional renderings of floorplans for a building, where the floorplans include different outlines **302** for each room of a floor in the building. Data representations of other real-world entities associated with a layer of the file **204** include an example Wi-Fi or cellular signal coverage range **306** and/or a plumbing fixture **304** (e.g., a pump).

(36) FIG. **4** is a flow chart of a process **400** for executing an interpreter framework to convert one or more files. The process **400** can be performed or executed using systems **100** and **200** described above. In some implementations, described actions of process **400** are enabled by programmed software instructions that are executable by at least one processing device and memory of computing systems described in this document.

(37) The process **400** includes the interpreter module **110** of the system **100** receiving a first electronic data file (**402**). For example, the interpreter module **110** can import or receive a DXF drawing file that includes multiple respective data sections. The respective data sections can represent layers of a DXF drawing file. In some implementations, individual layers of a drawing file correspond to physical features or other characteristics of real-world constructs. For example, one layer can correspond to plumbing lines and related plumbing features of a real-world building construct or electrical lines and wiring features included in the building construct.

(38) The interpreter module **110** uses the identifier **120** to identify each of the respective data sections of the first electronic data file **108**, e.g., the DXF drawing file (**404**). Each data section or layer of the drawing file includes data representing a real-world entity of the drawing file. In some implementations, real-world entities can include Wi-Fi zones of a building or location, sprinkler range for a sprinkler system of a building, or various other entities and attributes of one or more real-world construct. In some implementations, data representing a real-world entity can be described as one or more data objects of the DXF drawing file, such as graphical structures for depicting lines and boundaries. The lines and boundaries may define a floorplan of the real-world building construct or physical items associated with the floorplan.

(39) For each of the respective data sections or layers of the DXF drawing file, the interpreter module **110** uses the data extractor **122** to parse information about the real-world entities represented by the data for the layer (**406**). In some implementations, parsing the information about the real-world entity includes data extractor **122** extracting dimensional coordinates for the real-world entity. The dimensional coordinates define characteristics of the real-world entity. For example, extracted dimensional coordinates can define the lines and boundaries for a floorplan of the real-world building construct and/or define the lines and boundaries for physical items associated with the floorplan.

(40) The interpreter module **110** uses the converter **124** to convert the extracted dimensional coordinates (**408**) to a geospatial data format, e.g., a GeoJSON file format. In some implementations, converting the extracted dimensional coordinates to the GeoJSON file format includes the module **110** generating at least one dataset that includes geometry or physical attribute information about one or more real-world entities represented by data in the drawing file. In response to extracting and converting the dimensional coordinates to the GeoJSON file format, the

module **110** can use the data translator **126** to translate and digitally render at least one geographic structure using the dimensional coordinates (**408**).

(41) For example, the interpreter module **110** can translate and digitally render the digital geographic structure by aggregating converted dimensional coordinates that have the geospatial data format. The aggregated dimensional coordinates can represent rendered data for generating a geospatial data file, e.g., a GeoJSON file. The interpreter module **110** then generates a second electronic data file **128** based on the rendered data associated with each of the respective data sections of the DXF drawing file (**410**). The second electronic file **128** is a GeoJSON data file that encodes data for rendering digital geographic structures using information about the real-world entity represented by the data for the respective layers of the drawing file. In some implementations, the digital geographic structures represent physical or other features of the real-world building constructs.

(42) FIG. 5 is a block diagram of computing devices **500**, **550** that may be used to implement the systems and methods described in this document, as either a client or as a server or plurality of servers. Computing device **500** is intended to represent various forms of digital computers, such as laptops, desktops, workstations, personal digital assistants, servers, blade servers, mainframes, and other appropriate computers. Computing device **550** is intended to represent various forms of mobile devices, such as personal digital assistants, cellular telephones, smartphones, smartwatches, head-worn devices, and other similar computing devices. The components shown here, their connections and relationships, and their functions, are meant to be exemplary only, and are not meant to limit implementations described and/or claimed in this document.

(43) Computing device **500** includes a processor **502**, memory **504**, a storage device **506**, a high-speed interface **508** connecting to memory **504** and high-speed expansion ports **510**, and a low speed interface **512** connecting to low speed bus **514** and storage device **506**. Each of the components **502**, **504**, **506**, **508**, **510**, and **512**, are interconnected using various busses, and may be mounted on a common motherboard or in other manners as appropriate. The processor **502** can process instructions for execution within the computing device **500**, including instructions stored in the memory **504** or on the storage device **506** to display graphical information for a GUI on an external input/output device, such as display **516** coupled to high speed interface **508**. In other implementations, multiple processors and/or multiple buses may be used, as appropriate, along with multiple memories and types of memory. Also, multiple computing devices **500** may be connected, with each device providing portions of the necessary operations, e.g., as a server bank, a group of blade servers, or a multi-processor system.

(44) The memory **504** stores information within the computing device **500**. In one implementation, the memory **504** is a computer-readable medium. In one implementation, the memory **504** is a volatile memory unit or units. In another implementation, the memory **504** is a non-volatile memory unit or units.

(45) The storage device **506** is capable of providing mass storage for the computing device **500**. In one implementation, the storage device **506** is a computer-readable medium. In various different implementations, the storage device **506** may be a floppy disk device, a hard disk device, an optical disk device, or a tape device, a flash memory or other similar solid state memory device, or an array of devices, including devices in a storage area network or other configurations. In one implementation, a computer program product is tangibly embodied in an information carrier. The computer program product contains instructions that, when executed, perform one or more methods, such as those described above. The information carrier is a computer- or machine-readable medium, such as the memory **504**, the storage device **506**, or memory on processor **502**.

(46) The high speed controller **508** manages bandwidth-intensive operations for the computing device **500**, while the low speed controller **512** manages lower bandwidth-intensive operations. Such allocation of duties is exemplary only. In one implementation, the high-speed controller **508** is coupled to memory **504**, display **516**, e.g., through a graphics processor or accelerator, and to

high-speed expansion ports **510**, which may accept various expansion cards (not shown). In the implementation, low-speed controller **512** is coupled to storage device **506** and low-speed expansion port **514**. The low-speed expansion port, which may include various communication ports, e.g., USB, Bluetooth, Ethernet, wireless Ethernet, may be coupled to one or more input/output devices, such as a keyboard, a pointing device, a scanner, or a networking device such as a switch or router, e.g., through a network adapter.

(47) The computing device **500** may be implemented in a number of different forms, as shown in the figure. For example, it may be implemented as a standard server **520**, or multiple times in a group of such servers. It may also be implemented as part of a rack server system **524**. In addition, it may be implemented in a personal computer such as a laptop computer **522**. Alternatively, components from computing device **500** may be combined with other components in a mobile device (not shown), such as device **550**. Each of such devices may contain one or more of computing device **500**, **550**, and an entire system may be made up of multiple computing devices **500**, **550** communicating with each other.

(48) Computing device **550** includes a processor **552**, memory **564**, an input/output device such as a display **554**, a communication interface **566**, and a transceiver **568**, among other components. The device **550** may also be provided with a storage device, such as a microdrive or other device, to provide additional storage. Each of the components **550**, **552**, **564**, **554**, **566**, and **568**, are interconnected using various buses, and several of the components may be mounted on a common motherboard or in other manners as appropriate.

(49) The processor **552** can process instructions for execution within the computing device **550**, including instructions stored in the memory **564**. The processor may also include separate analog and digital processors. The processor may provide, for example, for coordination of the other components of the device **550**, such as control of user interfaces, applications run by device **550**, and wireless communication by device **550**.

(50) Processor **552** may communicate with a user through control interface **558** and display interface **556** coupled to a display **554**. The display **554** may be, for example, a TFT LCD display or an OLED display, or other appropriate display technology. The display interface **556** may include appropriate circuitry for driving the display **554** to present graphical and other information to a user. The control interface **558** may receive commands from a user and convert them for submission to the processor **552**. In addition, an external interface **562** may be provided in communication with processor **552**, so as to enable near area communication of device **550** with other devices. External interface **562** may provide, for example, for wired communication, e.g., via a docking procedure, or for wireless communication, e.g., via Bluetooth or other such technologies.

(51) The memory **564** stores information within the computing device **550**. In one implementation, the memory **564** is a computer-readable medium. In one implementation, the memory **564** is a volatile memory unit or units. In another implementation, the memory **564** is a non-volatile memory unit or units. Expansion memory **574** may also be provided and connected to device **550** through expansion interface **572**, which may include, for example, a SIMM card interface. Such expansion memory **574** may provide extra storage space for device **550**, or may also store applications or other information for device **550**. Specifically, expansion memory **574** may include instructions to carry out or supplement the processes described above, and may include secure information also. Thus, for example, expansion memory **574** may be provided as a security module for device **550**, and may be programmed with instructions that permit secure use of device **550**. In addition, secure applications may be provided via the SIMM cards, along with additional information, such as placing identifying information on the SIMM card in a non-hackable manner.

(52) The memory may include for example, flash memory and/or MRAM memory, as discussed below. In one implementation, a computer program product is tangibly embodied in an information carrier. The computer program product contains instructions that, when executed, perform one or more methods, such as those described above. The information carrier is a computer- or machine-

readable medium, such as the memory 564, expansion memory 574, or memory on processor 552.

(53) Device 550 may communicate wirelessly through communication interface 566, which may include digital signal processing circuitry where necessary. Communication interface 566 may provide for communications under various modes or protocols, such as GSM voice calls, SMS, EMS, or MMS messaging, CDMA, TDMA, PDC, WCDMA, CDMA2000, or GPRS, among others. Such communication may occur, for example, through radio-frequency transceiver 568. In addition, short-range communication may occur, such as using a Bluetooth, WiFi, or other such transceiver (not shown). In addition, GPS receiver module 570 may provide additional wireless data to device 550, which may be used as appropriate by applications running on device 550.

(54) Device 550 may also communicate audibly using audio codec 560, which may receive spoken information from a user and convert it to usable digital information. Audio codec 560 may likewise generate audible sound for a user, such as through a speaker, e.g., in a handset of device 550. Such sound may include sound from voice telephone calls, may include recorded sound, e.g., voice messages, music files, etc., and may also include sound generated by applications operating on device 550.

(55) The computing device 550 may be implemented in a number of different forms, as shown in the figure. For example, it may be implemented as a cellular telephone 580. It may also be implemented as part of a smartphone 582, personal digital assistant, or other similar mobile device.

(56) Various implementations of the systems and techniques described here can be realized in digital electronic circuitry, integrated circuitry, specially designed ASICs, computer hardware, firmware, software, and/or combinations thereof. These various implementations can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which may be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device.

(57) These computer programs, also known as programs, software, software applications or code, include machine instructions for a programmable processor, and can be implemented in a high-level procedural and/or object-oriented programming language, and/or in assembly/machine language. As used herein, the terms “machine-readable medium” “computer-readable medium” refers to any computer program product, apparatus and/or device, e.g., magnetic discs, optical disks, memory, Programmable Logic Devices (PLDs) used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term “machine-readable signal” refers to any signal used to provide machine instructions and/or data to a programmable processor.

(58) To provide for interaction with a user, the systems and techniques described here can be implemented on a computer having a display device, e.g., a CRT (cathode ray tube) or LCD (liquid crystal display) monitor, for displaying information to the user and a keyboard and a pointing device, e.g., a mouse or a trackball, by which the user can provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback, e.g., visual feedback, auditory feedback, or tactile feedback; and input from the user can be received in any form, including acoustic, speech, or tactile input.

(59) The systems and techniques described here can be implemented in a computing system that includes a back-end component, e.g., as a data server, or that includes a middleware component such as an application server, or that includes a front-end component such as a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of the systems and techniques described here, or any combination of such back-end, middleware, or front-end components. The components of the system can be interconnected by any form or medium of digital data communication such as, a communication network.

Examples of communication networks include a local area network (“LAN”), a wide area network

("WAN"), and the Internet.

(60) The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

(61) As used in this specification, the term "module" is intended to include, but is not limited to, one or more computers configured to execute one or more software programs that include program code that causes a processing unit(s)/device(s) of the computer to execute one or more functions. The term "computer" is intended to include any data processing or computing devices/systems, such as a desktop computer, a laptop computer, a mainframe computer, a personal digital assistant, a server, a handheld device, a smartphone, a tablet computer, an electronic reader, or any other electronic device able to process data.

(62) A number of embodiments have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the invention. Accordingly, other embodiments are within the scope of the following claims. While this specification contains many specific implementation details, these should not be construed as limitations on the scope of what may be claimed, but rather as descriptions of features that may be specific to particular embodiments. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment.

(63) Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

(64) Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system modules and components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

(65) Particular embodiments of the subject matter have been described. Other embodiments are within the scope of the following claims. For example, the actions recited in the claims can be performed in a different order and still achieve desirable results. As one example, some processes depicted in the accompanying figures do not necessarily require the particular order shown, or sequential order, to achieve desirable results.

Claims

1. A method implemented using a system comprising an interpreter module configured to execute an interpreter framework for generating geospatial data files, the method comprising: obtaining a drawing file comprising a plurality of layers, each layer representing a feature of a digitally rendered geographic structure; interpreting data values of a first layer of the drawing file, comprising: extracting each data value that represents a dimensional coordinate of an entity record that corresponds to a physical item of the first layer; for each of the data values that represents the dimensional coordinate, converting the data value to a geospatial file format to obtain a set of geospatial values; and automatically interpreting the data values irrespective of a manner in which data structures are arranged within the drawing file, wherein the data structures use the data values

to define representations of physical items of the first layer; and generating, based on the set of geospatial values, a geospatial data file having the geospatial file format, wherein the geospatial data file is configured to digitally render the physical item using the set of geospatial values, wherein generating the geospatial data file comprises a geospatial JavaScript Object Notation (geoJSON) drawing file configured to graphically render a floorplan of a DXF file, and wherein the physical item is included in the floorplan of the DXF.

2. The method of claim 1, further comprising: interpreting the data values of each of the plurality of layers in the drawing file, comprising: for each layer: extracting each of the data values that represents a dimensional coordinate of an entity record that corresponds to each physical item of the layer; and converting each of the data values that are extracted to the geospatial file format to obtain the set of geospatial values for the layer; wherein the drawing file is a drawing exchange format (DXF) file; wherein the geospatial data file comprises a geospatial JavaScript Object Notation (geoJSON) drawing file configured to graphically render a floorplan of a DXF file, and wherein the physical item is included in the floorplan of the DXF file; wherein each of the plurality of layers comprising data values are used to digitally render physical items; and wherein the geospatial data file is configured to digitally render the physical item using the set of geospatial values.

3. The method of claim 2, wherein generating the geospatial data file having the geospatial file format comprises generating the geospatial data file based on the set of geospatial values for each of the plurality of layers of the drawing file.

4. The method of claim 1, wherein: the interpreter framework executed by the interpreter module is a computer-based file conversion process that enables different arrangements of data representations in a first drawing file to be automatically converted and rendered for viewing in a geoJSON format; and wherein the data structures use the data values to define representations of physical items of the first layer.

5. The method of claim 1, wherein the generating of the geospatial data file comprises: converting dimensional coordinates of the first layer to the geospatial file format; aggregating the dimensional coordinates that are converted, which have the geospatial file format; and generating the set of geospatial values based on the dimensional coordinates that are converted, which have the geospatial file format.

6. The method of claim 5, wherein the geospatial file format is a geospatial data interchange format that is based on JavaScript Object Notation (JSON) and the geospatial file format is for representing geographical features of the drawing file, along with a respective non-spatial attribute of each geographical feature.

7. The method of claim 1, further comprising: automatically processing, using the interpreter module, contents of the drawing file after storing the drawing file in a memory, wherein the interpreter module processes a first drawing file independent of an application interface used to generate the first drawing file.

8. A system configured to execute an interpreter framework for generating geospatial data files, the system comprising a computer system including a processing device and a non-transitory machine-readable storage device storing instructions that are executable by the processing device to cause performance of operations comprising: obtaining a drawing file comprising a plurality of layers, each layer representing a feature of a digitally rendered geographic structure; interpreting data values of a first layer of the drawing file, comprising: extracting each data value that represents a dimensional coordinate of an entity record that corresponds to a physical item of the first layer; for each of the data values that represents the dimensional coordinate, converting each of the data values to a geospatial file format to obtain a set of geospatial values; automatically interpreting the data values irrespective of a manner in which data structures are arranged within the drawing file, wherein the data structures use the data values to define representations of physical items of the first layer; and generating, based on the set of geospatial values, a geospatial data file having the

geospatial file format, wherein the geospatial data file is configured to digitally render the physical item using the set of geospatial values, wherein generating the geospatial data file comprises a geospatial JavaScript Object Notation (geoJSON) drawing file configured to graphically render a floorplan of a DXF file, and wherein the physical item is included in the floorplan of the DXF.

9. The system of claim 8, wherein the operations further comprise: interpreting the data values of each of the plurality of layers in the drawing file, comprising: for each layer: extracting each of the data values that represents a dimensional coordinate of an entity record that corresponds to each physical item of the layer; and converting each of the data values that are extracted to the geospatial file format to obtain the set of geospatial values for the layer; wherein the drawing file is a drawing exchange format (DXF) file; and wherein the geospatial data file is configured to digitally render the physical item using the set of geospatial values, wherein generating the geospatial data file comprises a geospatial JavaScript Object Notation (geoJSON) drawing file configured to graphically render a floorplan of a DXF file, and wherein the physical item is included in the floorplan of the DXF file; wherein each of the plurality of layers comprising data values are used to digitally render physical items; and wherein the geospatial data file is configured to digitally render the physical item using the set of geospatial values.

10. The system of claim 9, wherein generating the geospatial data file having the geospatial file format comprises: generating the geospatial data file based on the set of geospatial values for each of the plurality of layers of the drawing file.

11. The system of claim 8, wherein: the interpreter framework executed by the interpreter module is a computer-based file conversion process that enables different arrangements of data representations in a first drawing file to be automatically converted and rendered for viewing in a geoJSON format; and wherein the data structures use the data values to define representations of physical items of the first layer.

12. The system of claim 8, wherein generating the geospatial data file converting dimensional coordinates of the first layer to the geospatial file format; comprises: aggregating the dimensional coordinates that are converted, which have the geospatial file format; and generating the set of geospatial values based on the dimensional coordinates that are converted, which have the geospatial file format.

13. The system of claim 12, wherein the geospatial file format is a geospatial data interchange format that is based on JavaScript Object Notation (JSON) and the geospatial file format is for representing geographical features of the drawing file, along with a respective non-spatial attribute of each geographical feature.

14. A non-transitory machine-readable storage device storing instructions for generating geospatial data files using an interpreter module, the instructions being executable by a processing device to cause operations comprising: obtaining a drawing file comprising a plurality of layers, each layer representing a feature of a digital rendered geographic structure; interpreting data values of a first layer of the drawing file, comprising: extracting each data value that represents a dimensional coordinate of an entity record that corresponds to a physical item of the first layer; for each of the data values that represents the dimensional coordinate, converting the data value to a geospatial file format to obtain a set of geospatial values; and automatically interpreting the data values irrespective of a manner in which data structures are arranged within the drawing file, wherein the data structures use the data values to define representations of physical items of the first layer; and generating, based on the set of geospatial values, a geospatial data file having the geospatial file format, wherein the geospatial data file is configured to digitally render the physical item using the set of geospatial values, wherein generating the geospatial data file comprises a geospatial JavaScript Object Notation (geoJSON) drawing file configured to graphically render a floorplan of a DXF file, and wherein the physical item is included in the floorplan of the DXF file.

15. The non-transitory machine-readable storage device of claim 14, wherein the operations further comprise: the interpreting data values of each of the plurality of layers in the drawing file

comprises: for each layer: extracting each of the data values that represents a dimensional coordinate of an entity record that corresponds to each physical item of the layer; and converting each of the data values that are extracted to the geospatial file format to obtain the set of geospatial values for the layer; wherein the drawing file is a drawing exchange format (DXF) file; and wherein the geospatial data file is configured to digitally render the physical item using the set of geospatial values.

16. The non-transitory machine-readable storage device of claim 15, wherein the geospatial data file comprises a geospatial JavaScript Object Notation (geoJSON) drawing file configured to graphically render the floorplan of the DXF file, and wherein the physical item is included in the floorplan of the DXF file.

17. The non-transitory machine-readable storage device of claim 15, wherein an interpreter framework executed by the interpreter module is a computer-based file conversion process that enables different arrangements of data representations in a first drawing file to be automatically converted and rendered for viewing in a geoJSON format.

18. The non-transitory machine-readable storage device of claim 15, wherein generating the geospatial data file comprises: converting dimensional coordinates of the first layer to the geospatial file format; aggregating the dimensional coordinates that are converted, which have the geospatial file format; and generating the set of geospatial values based on the dimensional coordinates that are converted, which have the geospatial file format.

19. The non-transitory machine-readable storage device of claim 18, wherein the geospatial file format is a geospatial data interchange format that is based on JavaScript Object Notation (JSON).

20. The non-transitory machine-readable storage device of claim 19, wherein the geospatial file format is for representing geographical features of the drawing file, along with a respective non-spatial attribute of each geographical feature.
