

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276812

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Zalger; Jonathan et al.

RAPID PART ASSESSMENT WITH TESTING AND MACHINE LEARNING BRANCHES

Abstract

A method includes the steps of manufacturing and generating data at each of a plurality of locations on the component. Passing the data to a testing branch which performs tests and reaches a conclusion as to whether the component is functionally tolerant at each of the plurality of locations. The data is also passed to a machine learning branch wherein it is compared to training data to determine whether the component is of a functionally tolerant dimension at each of the plurality of locations. The manufactured component accepts should both the testing branch and the machine learning branch determine the component is of functionally tolerant dimensions at the plurality of locations, and rejects the component if either of the testing branch or the machine learning branch determines the component fails to be functionally tolerant dimensions, respectively. A system is also disclosed.

Inventors: Zalger; Jonathan (Toronto, CA), Soukhostavets; Egor (Longueuil, CA), Ruoti; Christopher A. (Eagle Mountain, UT), Merabet; Reda (L'Assomption, CA), Fudge; Daniel (Vaughan, CA), Brewer; Steven (Charlottesville, VA), Ben Amor; Nesrine (Toronto, CA)

Applicant: Pratt & Whitney Canada Corp. (Longueuil, CA)

Family ID: 94870191

Appl. No.: 18/594778

Filed: March 04, 2024

Publication Classification

Int. Cl.: B64F5/60 (20170101); G01M15/14 (20060101); G06N20/20 (20190101)

U.S. Cl.:

Background/Summary

BACKGROUND

[0001] This application relates to assessing the quality of a manufactured component using both a testing branch and a machine learning branch.

[0002] Gas turbine engines are known, and typically include a propulsor delivering air into a compressor section. The compressed air is delivered into a combustor where it is mixed with fuel and ignited. Products of this combustion pass downstream over turbine rotors, driving them to rotate.

[0003] As known, the propulsor, the compressor, and the turbine all have a rotating disk carrying a plurality of vanes formed with an airfoil shape. As an example, one type of rotor and blades is a so called integrally bladed rotor (“IBR”).

[0004] It is typical that some physical testing of a manufactured gas turbine engine component is performed to ensure that the component is within tolerance range. To date this has primarily been manual inspection of dimensions.

SUMMARY

[0005] A method of assessing the quality of a manufactured component includes the steps of manufacturing a component and generating data at each of a plurality of locations on the component. The generated data is passed to a testing branch which performs tests on the generated data at each of the plurality of locations, and reaches a conclusion as to whether the component is functionally tolerant at each of the plurality of locations. The generated data is also passed to a machine learning branch wherein the generated data is compared to training data at each of the plurality of locations to determine whether the component is of a functionally tolerant dimension at each of the plurality of locations. The manufactured component accepts should both the testing branch and the machine learning branch determine the component is of functionally tolerant dimensions at the plurality of locations, and rejects the component if either of the testing branch or the machine learning branch determines the component fails to be functionally tolerant dimensions, respectively, at the plurality of sections.

[0006] A system for component assessment includes processing circuitry operable to assess the quality of a manufactured component by receiving generated data from a component at each of a plurality of locations through the component and also operable to provide the generated data to a testing branch which performs tests on the generated data at each of the plurality of locations, and reaches a conclusion as to whether the component is functionally tolerant at each of the plurality of locations. The system is also operable to provide the generated data to a machine learning branch. The generated data is compared to training data at each of the plurality of locations to determine whether the component is a functionally tolerant dimension at each of the plurality of locations. The system is operable to make a decision to accept the component should both the testing branch and the machine learning branch determine the component is within functionally tolerant dimensions at the plurality of locations and rejecting the component if either the testing branch or the machine learning branch determines the component is not within functionally tolerant dimensions at the plurality of locations.

[0007] These and other features will be best understood from the following drawings and specification, the following is a brief description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. **1** schematically shows a gas turbine engine.

[0009] FIG. **2** shows a testing regime for a manufactured component.

[0010] FIG. **3** is another view of the FIG. **2** testing regime.

[0011] FIG. **4** shows a portion of the FIG. **3** regime.

[0012] FIG. **5** shows another portion of the FIGS. **2** and **3** regime.

[0013] FIG. **6** shows a K-fold analysis.

[0014] FIG. **7** is a flow chart of a machine learning system assessment regime.

[0015] FIG. **8** shows detail of how the FIG. **7** machine learning regime functions.

DETAILED DESCRIPTION

[0016] FIG. **1** schematically illustrates a gas turbine engine **10**. The example gas turbine engine **10** is a turbofan that generally incorporates a fan section **11**, a compressor section **12**, a combustor section **13** and a turbine section **14**. The fan section **11** drives air along a bypass flow path B in a bypass duct defined within a nacelle **15**. The turbine engine **10** also intakes air along a core flow path C into the compressor section **12** for compression and communication into the combustor section **13**. In the combustor section **13**, the compressed air is mixed with fuel from a fuel system **16** and ignited to generate an exhaust gas flow that expands through the turbine section **14** and is exhausted through exhaust nozzle **17**. Although depicted as a turbofan turbine engine in the disclosed non-limiting embodiment, it should be understood that the concepts described herein are not limited to use with turbofans as the teachings may be applied to other types of turbine engines. As one example, rather than having the propulsor be an enclosed fan, the propulsor may be an open propeller. This embodiment can also be applied to industrial gas turbine engine as well.

[0017] FIG. **2** shows a testing system **20** for parts **22** that may be used in the engine **10**. As known, components containing airfoils such as parts **22** must be assessed to determine whether they are acceptable for use. System **20** is a dual branch assessment regime that includes both physical testing **25** and the use of machine learning **35**. Components as manufactured **22** include airfoils. In one embodiment, the component **22** may be an integrally bladed rotor wherein a disk **23** is formed integrally with blades **27** being the airfoil.

[0018] The part is evaluated by initially taking a number of sections through the airfoil. As example, twelve sections may be taken. In more detail, the part is measured/scanned along its surfaces and then broken down into sections. However, the broader teachings of this disclosure would extend to analyzing part surfaces, and is not limited to taking sections. Broadly, the method looks at a plurality of locations. This then generates data at process **24** which then passes into a first branch **25** for physical testing. An initial step is a cold mesh morphing at step **26** from nominal dimensions to inspected dimensions. The cold mesh is then subjected to dynamic testing at step **28** and stress and dynamic testing at step **30**. After step **30** hot mesh morphing **32** is applied to inspect the mesh at operating conditions.

[0019] At step **34** there is then a geometric analysis performed which will either indicate the part should be rejected or accepted. Outputs of the decision from steps **28** and **34** are sent to step **38** to be part of a final report.

[0020] Steps **28** and **30** both inherit from step **26**, i.e. a numerical mesh representing the as-manufactured geometry of the part **22**. Step **28** consists of multiple solid mechanics simulations for different dynamical and vibratory load cases applied on the mesh of step **26**. Similarly, step **30** uses the same mesh defined at step **26** to simulate multiple solid mechanics steady stress analyses on the part **22**. These 2 steps, e.g. **28** and **30**, are examples and different parts may not need both steps, whereas other parts could involve other type of analysis such as flow-field/aerodynamical or contact analysis to name a few.

[0021] In parallel to the branch **25**, a machine learning branch **35** moves to an aero and dynamic leading edge/trailing edge model or machine learning step **36**. As will be explained below, this

model determines the acceptability of the part **22** and also reports to the step **38** to be part of a final report.

[0022] In an embodiment, a component must pass both the machine learning branch **35**, and the testing branch **25** to be found acceptable.

[0023] As shown in FIG. **3**, a part definition is defined by drawings and/or 3D models of the part. Inspection data from manufacturing is supplied at **42** to a rapid part assessment app **26**. This data at **26** is then subjected to stress and dynamic evaluation at steps **30** and **28**.

[0024] As shown graphically at **44**, the nominal dimensions define a boundary **46**. In the prior art the nominal dimensions have been relied upon to indicate the acceptability of a part. However, relying solely on geometric tolerances identifies a number of parts as being unacceptable, when in fact they may actually be functionally tolerant part. As shown graphically, the boundaries of the functionally tolerant part **48** extend far beyond the nominal drawing limits **46**.

[0025] It should be understood that the graphical representation **44** is just that, and does not form any portion of the method disclosed here. That is, the graph is not prepared, but is instead simply utilized to convey the concept.

[0026] The FIGS. **2** and **3** processes may be performed on cloud based infrastructure. The result will be increased evaluation speed.

[0027] FIG. **4** shows detail of testing branch **25**. A network **52** receives a part assessment from an operator or inspector **54**. That data is delivered to a cloud function **57**. Network **52** may include computing devices that includes one or more computer processors, memory, storage means, network devices, input and/or output devices, and/or interfaces. The computing devices may be operable to execute one or more software programs. The computing devices may be operable to communicate with one or more networks established by one or more computing devices. The memory may include UVROM, EEPROM, FLASH, RAM, ROM, DVD, CD, a hard drive, or other computer readable medium which may store data and/or the functionality of this description. The computing devices may be a desktop computer, laptop computer, smart phone, tablet, or any other computer device. Input devices may include a keyboard, mouse, touchscreen, etc. Output devices may include a monitor, speakers, printers, etc. Each of the computing devices may include one or more processors coupled to the memory. The computing devices may be coupled to each other by one or more connections **40**. The connection **40** may be a wired and/or wireless connection. The connection **40** may be established over one or more networks and/or other computing systems.

[0028] The cloud function has a rapid part assessment core **58** which receives raw data. Although disclosed on the cloud, this disclosure could be ran elsewhere. At **60** a workflow is used for each type assessed part. The workflow would be directed to a particular component that is being evaluated. Thus, step **60** may well include workflows A, B, C for each of a plurality of distinct parts.

[0029] The stored workflows contain nominal geometry, functional and geometric limits, nominal mesh and loads to apply for functional analysis, as well as the general ordering and orchestration of information of the individual steps contained in the workflow. In fact, the stored workflow could be a core set of functionalities that are valid for any type of part to be analyzed by this system.

[0030] After this step the results of the workflow are stored at step **64** for long term storage, and also for status update and reporting. From step **60** an email report **62** may be sent back to the inspector **54**.

[0031] Moving to FIG. **5**, the machine learning branch **35** initially verifies the data in machine learning module **36** at step **66**. The curvature and profile at each of a plurality of section cuts are then extracted at step **68**. As an example, there may be on the order of three dozen section cuts in each airfoil. As mentioned above, the broader aspects of this disclosure extend beyond looking at sections.

[0032] There is a scope check **70**, a labeling task **72**, and a labeling app **74**. This is then sent to data

storage **76**, and a platform **78**. Task **72** is a task-generation function that assigns new tasks for human experts to evaluate and label a specific data item generated through this method. In this case, the data items being evaluated are airfoil shapes represented by profile and curvature plots. App **74** is a labeling application that allows expert humans to visualize the data-items and records the expert's label/evaluation. The app **74** stores the labels in a database **76**. Platform **78** is another platform that may access data base **76** in order to process the new labels, monitor the performance of machine learning predictions against expert labels, and re-training the machine learning models. [0033] As shown, the scope check **70** may identify a particular part as being an outlier at **80**. If so, the result is communicated to task **72**. At model **82**, a final determination for the component is indicated as an outlier at **84**.

[0034] Assuming the scope check does not identify the component as being an outlier, it then moves to the infer step **86** and an inference is made based on the profile and curvature of the several sections at **88**. At step **90** there is post processing. After that the component is identified with a percentage of likelihood between zero (clearly bad) at **92**; one (maybe bad) at step **94**; two (maybe good) at step; and three (clearly good) at step **98**. Of course, these number are examples and other quantities may be used. A percentage chance for each of these four likelihoods is then stored in data storage at **100**.

[0035] There is then a component review at **102** that has a step **104** that identifies whether to accept **108** or reject **106** the component based upon the analysis.

[0036] The identification of a part of as “clearly bad” is made when a section clearly exhibits defects. The “maybe bad” is reached if a section may possibly exhibit defects that highly impact the part quality. The “maybe good” finding is made for a section that may possible exhibit defects, but the defects do not impact the part quality. The finding of “clearly good” is reached for a section that exhibits no flaws. Of course, methods and systems coming under this disclosure may use other terms than clearly bad, maybe bad, maybe good, and clearly good. However, when interpreting the claims for this application it should be understood that these are classifications that are relative to each other, and not absolute findings.

[0037] The “good” findings can be equated to the part being acceptable at the particular section or location, while “bad” can be equated to the part being rejected at the particular section or location.

[0038] At **110** there is a graphical showing of the results for a number of evaluated components based upon the determined dimension and assessment results.

[0039] Details of the above aspects of this disclosure are disclosed and claimed in copending patent application Ser. No. _____, entitled “RAPID PART ASSESSMENT WITH TESTING AND MACHINE LEARNING BRANCHES,” filed on even date herewith and owned by the assignee of this application.

[0040] A The K-fold splits separate a data set **114** into K equal folds. All folds must have comparable data distribution.

[0041] Each of the five folds **128**, **130**, **132**, **134** and **136** for each of the splits are trained on data **112**. The data in each of the folds is distinct. In each of the splits **118**, **120**, **122**, **124**, and **126**, the training data folds are split differently between training and validation samples. Thus, each split represents a distinct training data sample on which a distinct machine learning model is trained and validated. Only the training data **114** is split between the folds.

[0042] As shown in FIG. **6**, K models are trained on distinct datasets from each of the K splits, but all models are tested on a common test dataset.

[0043] An example test will be explained. At the start, you have 100% of data, that you split into two sets: training validation set of 80% and test set of 20%. You set the test set aside. The remaining 80% of data is then split into 5 folds, each containing 16% of the original data set. Data from the same blade is ensured to be only contained in a single fold of 16% (to avoid contamination). The machine learning model is then trained 5 times as follows. Choose 4 out of 5 sets, and call them train data, and use the remaining set as validation data. Train a model. Verify

performance using test data set that was originally put aside (20%). Repeat the process 4 other times, by continuously taking 4 out of 5 folds at a time and using 1 remaining fold as validation. After 5 iterations, you ensured that each of the folds had a chance to be used as validation.

[0044] Details of the above aspect of this disclosure are disclosed and claimed in copending patent application Ser. No. _____, entitled “RAPID PART ASSESSMENT WITH K-FOLD EVALUATION” filed on even date herewith and owned by the assignee of this application.

[0045] The training data within the folds for each of the splits are also distinct sets. Thus, the training data utilizes information from different inspected parts in each of the folds. Each part in each of the folds would be used in all of the splits for that fold. Any data from one part should not be split between the folds and must be grouped in one single fold.

[0046] Each of the plural folds may receive training data for each of the plurality of splits from a common part and the training data for the common part used with one of the plural folds is not used with others of the plural folds.

[0047] Each of the plural folds receive training data for each of the plurality of splits, but does not receive test data for each of the plurality of splits.

[0048] Details of the above aspect of this disclosure are disclosed and claimed in copending patent application Ser. No. _____, entitled “RAPID PART ASSESSMENT WITH K-FOLD EVALUATION USING HISTORIC DATA AND TEST DATA” filed on even date herewith and owned by the assignee of this application.

[0049] FIG. 7 is a flow chart **120** of a system then evaluates the results of the machine learning prediction. A component is manufactured and inspected. There is section processing. Then, there is a shape check and an FEA/CFD check. The machine learning model then makes a disposition at step **102**. The shape-check component **120** in FIG. 7 represents the same machine learning component in FIG. 2. In fact, FIG. 7 is a more generic version of the process shown in FIG. 2.

[0050] As shown in FIG. 8, the machine learning will develop a profile image at **122** and curvature data at **124**. A plurality of models **130** look to the profile image **122** at model **126** to reach a decision on outcomes **92/94/96/98**. The machine learning system is composed of a plurality of Deep Neural Network architectures. Different architectures are trained on different data inputs **122** and **124**. One architecture is an image recognition model trained to evaluate airfoil quality based on profile images **126**. The second architecture is multi-layer perceptron trained on engineered features to evaluate the quality based on curvature data **128**. Both model types are supervised machine learning classification models. A plurality of models are trained using each architecture at **130** and **132**. During the evaluation of a new part, data types **122** and **124** are processed into images **126** and curvature features **128**, then respectively evaluated using the plurality of models in **130** and **132** to reach a edge quality evaluation at **102**.

[0051] Although neural networks are disclosed, other machine learning algorithms may be utilized.

[0052] The assessments are shown in **126** for two different parts, and with distinct clearly good and clearly bad results. There is also a machine learning process classifier on the curvature data at **128** using a plurality of machine learning process models at step **132**.

[0053] This then reaches a conservative answer for the disposition **102**. For each part and each section there would be an average between zero and three based upon the percentages assigned to each of outcome **92/94/96/98**. Thus, there would tend to be a likelihood of a single result for each part between zero and three. This lets the percentage evaluation of step **126** be reached.

[0054] However, due to the conservative evaluation the method does not simply look to what is the highest probability. Rather, the method conservatively will reject the part if its “clearly bad” or “maybe bad” numbers exceed a pre-defined percentage limit.

[0055] Stated another way, for a part to be accepted its clearly good number does not need to just be higher than its “clearly bad” number, but in addition the clearly bad number cannot exceed a predetermined maximum. In one example, the clearly bad percentage maximum limit may be 20%, but of course this is simply an example. The point is that the clearly bad maximum does not need to

be the highest likelihood percentage determined across the part for a part to be rejected.

[0056] The use of a probability identifier of whether the part is good or bad, and weighting the final determination in a conservative manner is disclosed and claimed in copending patent application Ser. No. _____, entitled "RAPID PART ASSESSMENT DEVELOPING GOOD/BAD PERCENTAGE LIKELIHOOD" filed on even date herewith and owned by the assignee of this application.

[0057] While an integrally bladed rotor is disclosed, other components having airfoils, such as separate blades or stators would come within the scope of this disclosure. In fact, other components such as castings would come within the scope of this disclosure.

[0058] In a featured embodiment, a method of assessing the quality of a manufactured component includes the steps of manufacturing a component and generating data at each of a plurality of locations on the component. The generated data is passed to a testing branch which performs tests on the generated data at each of the plurality of locations, and reaches a conclusion as to whether the component is functionally tolerant at each of the plurality of locations. The generated data is also passed to a machine learning branch wherein the generated data is compared to training data at each of the plurality of locations to determine whether the component is of a functionally tolerant dimension at each of the plurality of locations. The manufactured component accepts should both the testing branch and the machine learning branch determine the component is of functionally tolerant dimensions at the plurality of locations, and rejects the component if either of the testing branch or the machine learning branch determines the component fails to be functionally tolerant dimensions, respectively, at the plurality of sections.

[0059] In another embodiment according to the previous embodiment, the component includes an airfoil.

[0060] In another embodiment according to any of the previous embodiments, the generated data includes curvature and dimensional measurements.

[0061] In another embodiment according to any of the previous embodiments, the locations are cross-sections.

[0062] In another embodiment according to any of the previous embodiments, the component is an integrally bladed rotor.

[0063] In another embodiment according to any of the previous embodiments, functionally tolerant components are identified which have dimensions outside of a nominal tolerance range.

[0064] In another embodiment according to any of the previous embodiments, the machine learning branch utilizes K-fold validation with plural folds at each of the plural locations.

[0065] In another embodiment according to any of the previous embodiments, the plural folds are provided with training data from prior assessments.

[0066] In another embodiment according to any of the previous embodiments, each of the plural folds receive training data from a common part, and the training data across the plural folds is all distinct.

[0067] In another embodiment according to any of the previous embodiments, an evaluation is reached as to a percentage chance that the component is acceptable and a percentage chance that the component is rejectable at each of the location.

[0068] In another featured embodiment, a system for component assessment includes processing circuitry operable to assess the quality of a manufactured component by receiving generated data from a component at each of a plurality of locations through the component and also operable to provide the generated data to a testing branch which performs tests on the generated data at each of the plurality of locations, and reaches a conclusion as to whether the component is functionally tolerant at each of the plurality of locations. The system is also operable to provide the generated data to a machine learning branch. The generated data is compared to training data at each of the plurality of locations to determine whether the component is a functionally tolerant dimension at each of the plurality of locations. The system is operable to make a decision to accept the

component should both the testing branch and the machine learning branch determine the component is within functionally tolerant dimensions at the plurality of locations and rejecting the component if either the testing branch or the machine learning branch determines the component is not within functionally tolerant dimensions at the plurality of locations.

[0069] In another embodiment according to any of the previous embodiments, the component includes an airfoil.

[0070] In another embodiment according to any of the previous embodiments, the generated data includes curvature and dimensional measurement.

[0071] In another embodiment according to any of the previous embodiments, the locations are cross-sections.

[0072] In another embodiment according to any of the previous embodiments, the component is an integrally bladed rotor.

[0073] In another embodiment according to any of the previous embodiments, functionally tolerant components are identified which have dimensions outside of a nominal tolerance range.

[0074] In another embodiment according to any of the previous embodiments, the machine learning branch utilizes a K-fold validation with plural folds at each of the plurality of sections.

[0075] In another embodiment according to any of the previous embodiments, the plural folds are provided with training data from prior assessments, and test data for at least one of the plural folds.

[0076] In another embodiment according to any of the previous embodiments, each of the plural folds receive training data from a common part, and the training data across the plural folds is distinct.

[0077] In another embodiment according to any of the previous embodiments, an evaluation is reached as to a percentage chance that the component is acceptable and a percentage chance that the component is rejectable at each of the location.

[0078] Although embodiments have been disclosed, a worker of skill in this art would recognize that modifications would come within the scope of this disclosure. For that reason, the following claims should be studied to determine the true scope and content.

Claims

1. A method of assessing the quality of a manufactured component comprising the steps of: manufacturing a component and generating data at each of a plurality of locations on the component; passing the generated data to a testing branch which performs tests on the generated data at each of the plurality of locations, and reaches a conclusion as to whether the component is functionally tolerant at each of the plurality of locations; also passing the generated data to a machine learning branch wherein the generated data is compared to training data at each of the plurality of locations to determine whether the component is of a functionally tolerant dimension at each of the plurality of locations; and accepting the manufactured component should both the testing branch and the machine learning branch determine the component is of functionally tolerant dimensions at the plurality of locations, and rejecting the component if either of the testing branch or the machine learning branch determines the component fails to be functionally tolerant dimensions, respectively, at the plurality of sections.
2. The method as set forth in claim 1, wherein the component includes an airfoil.
3. The method as set forth in claim 2, wherein the generated data includes curvature and dimensional measurements.
4. The method as set forth in claim 3, wherein the locations are cross-sections.
5. The method as set forth in claim 2, wherein the component is an integrally bladed rotor.
6. The method as set forth in claim 1, wherein functionally tolerant components are identified which have dimensions outside of a nominal tolerance range.
7. The method as set forth in claim 1, wherein the machine learning branch utilizes K-fold

validation with plural folds at each of the plural locations.

8. The method as set forth in claim 7, wherein the plural folds are provided with training data from prior assessments.

9. The method as set forth in claim 8, wherein each of the plural folds receive training data from a common part, and the training data across the plural folds is all distinct.

10. The method as set forth in claim 1, wherein an evaluation is reached as to a percentage chance that the component is acceptable and a percentage chance that the component is rejectable at each of the location.

11. A system for component assessment comprising: processing circuitry operable to assess the quality of a manufactured component by receiving generated data from a component at each of a plurality of locations through the component; also operable to provide the generated data to a testing branch which performs tests on the generated data at each of the plurality of locations, and reaches a conclusion as to whether the component is functionally tolerant at each of the plurality of locations; also operable to provide the generated data to a machine learning branch wherein the generated data is compared to training data at each of the plurality of locations to determine whether the component is a functionally tolerant dimension at each of the plurality of locations; and operable to make a decision to accept the component should both the testing branch and the machine learning branch determine the component is within functionally tolerant dimensions at the plurality of locations and rejecting the component if either the testing branch or the machine learning branch determines the component is not within functionally tolerant dimensions at the plurality of locations.

12. The system as set forth in claim 11, wherein the component includes an airfoil.

13. The system as set forth in claim 12, wherein the generated data includes curvature and dimensional measurement.

14. The system as set forth in claim 13, wherein the locations are cross-sections.

15. The system as set forth in claim 12, wherein the component is an integrally bladed rotor.

16. The system as set forth in claim 1, wherein functionally tolerant components are identified which have dimensions outside of a nominal tolerance range.

17. The system as set forth in claim 11, wherein the machine learning branch utilizes a K-fold validation with plural folds at each of the plurality of sections.

18. The system as set forth in claim 17, wherein the plural folds are provided with training data from prior assessments, and test data for at least one of the plural folds.

19. The system as set forth in claim 18, wherein each of the plural folds receive training data from a common part, and the training data across the plural folds is distinct.

20. The system as set forth in claim 11, wherein an evaluation is reached as to a percentage chance that the component is acceptable and a percentage chance that the component is rejectable at each of the location.
