

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276881

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

MATHÉ; Ewald

CRANE COLUMN ASSEMBLY, A CRANE, AND A VEHICLE

Abstract

It is provided a crane column assembly for a crane to be mounted on a mobile platform. The crane column assembly comprises a support arrangement arranged to support a crane boom, wherein the support arrangement is connected to a base structure. The crane column assembly further comprises a cover arrangement arranged between the support arrangement, wherein the cover arrangement covers a region of the crane column assembly which comprises a region between the support arrangement.

Inventors: MATHÉ; Ewald (Elixhausen, AT)

Applicant: Palfinger AG (Bergheim bei Salzburg, AT)

Family ID: 94869810

Appl. No.: 18/592915

Filed: March 01, 2024

Publication Classification

Int. Cl.: B66C23/42 (20060101); B66C23/62 (20060101)

U.S. Cl.:

CPC B66C23/42 (20130101); B66C23/62 (20130101); B66C2700/0371 (20130101)

Background/Summary

FIELD

[0001] Examples relate to a crane column assembly, a crane, and a vehicle cranes as set out in the appended set of claims.

BACKGROUND

[0002] In the field of crane operations, the equipment is routinely exposed to a variety of environmental elements, including dirt, dust, and water, which can significantly impact performance, necessitate frequent maintenance, and reduce overall lifespan. These considerations are widespread across the spectrum of crane operations, from stationary to mobile cranes, including those mounted on trucks, facing particularly acute conditions due to their operation across diverse and often demanding environments. Among the specific aspects encountered, water ingress in the area of the crane column represents an important subject. This phenomenon may jeopardize the structural integrity and functional reliability of the crane. Addressing these specific matters may be important to ensure resilience of cranes, their operational efficacy, and extending their service life in the face of environmental impacts.

SUMMARY

[0003] An example relates to a crane column assembly for a crane to be mounted on a mobile platform. The crane column assembly comprises a support arrangement, which is arranged to support a crane boom, wherein the support arrangement is connected to a base structure. Further, the crane column assembly comprises a cover arrangement arranged between the support arrangement, wherein the cover arrangement covers a region of the crane column assembly comprising a region between the support arrangement.

Description

BRIEF DESCRIPTION OF THE FIGURES

[0004] Some examples of apparatuses and/or methods will be described in the following by way of example only, and with reference to the accompanying figures, in which

[0005] FIG. 1 illustrates an example of a crane assembly;

[0006] FIG. 2A illustrates an example of a crane column assembly;

[0007] FIG. 2B illustrates an example of a crane column assembly;

[0008] FIG. 3 illustrates an example of a crane column assembly in an exploded view diagram;

[0009] FIG. 4 illustrates an example of the crane column assembly of FIG. 3 in an assembled state;

[0010] FIG. 5 illustrates a section of the crane column assembly of FIG. 4 taken along the line V-V;

[0011] FIG. 6 illustrates a section of the crane column assembly of FIG. 4 taken along the line VI-VI;

[0012] FIG. 7 illustrates a section of the crane column assembly of FIG. 4 taken along the line VII-VII;

[0013] FIG. 8 illustrates a section of the crane column assembly of FIG. 4 taken along the line VIII-VIII;

[0014] FIG. 9 illustrates a section of the crane column assembly of FIG. 4 taken along the line IX-IX;

[0015] FIG. 10 illustrates a section of the crane column assembly of FIG. 4 taken along the line X-X; and

[0016] FIG. 11 illustrates an example of a vehicle on which the crane column assembly is mounted.

DETAILED DESCRIPTION

[0017] Some examples are now described in more detail with reference to the enclosed figures.

However, other possible examples are not limited to the features of these embodiments described in detail. Other examples may include modifications of the features as well as equivalents and alternatives to the features. Furthermore, the terminology used herein to describe certain examples should not be restrictive of further possible examples.

[0018] Throughout the description of the figures same or similar reference numerals refer to same or similar elements and/or features, which may be identical or implemented in a modified form

while providing the same or a similar function. The thickness of lines, layers and/or areas in the figures may also be exaggerated for clarification.

[0019] When two elements A and B are combined using an “or”, this is to be understood as disclosing all possible combinations, i.e. only A, only B as well as A and B, unless expressly defined otherwise in the individual case. As an alternative wording for the same combinations, “at least one of A and B” or “A and/or B” may be used. This applies equivalently to combinations of more than two elements.

[0020] If a singular form, such as “a”, “an” and “the” is used and the use of only a single element is not defined as mandatory either explicitly or implicitly, further examples may also use several elements to implement the same function. If a function is described below as implemented using multiple elements, further examples may implement the same function using a single element or a single processing entity. It is further understood that the terms “include”, “including”, “comprise” and/or “comprising”, when used, describe the presence of the specified features, integers, steps, operations, processes, elements, components and/or a group thereof, but do not exclude the presence or addition of one or more other features, integers, steps, operations, processes, elements, components and/or a group thereof.

[0021] FIG. 1 illustrates an example of a crane assembly **100**. FIG. 1 is an overview figure illustrating an example of how a crane column assembly **120** as described in this disclosure may be employed.

[0022] The crane assembly **100** comprises a crane **110**. The crane **110** may comprise the crane column assembly **120** as described in this disclosure (see FIGS. 2 to 10). Further, the crane **110** may comprise a crane boom **130** that is supported by the crane column assembly **120**. For instance, the crane column assembly **120** and the boom **130** form a hinge. Further, the crane assembly **100** may comprise a crane compartment box **140**. For instance, the crane column assembly **120** is mounted onto the compartment box **140**. The compartment box **140** may comprise a controller configured to control the crane. Further, in some embodiments the compartment box **140** may comprise a winch controlling a crane hook. Further, the crane assembly **100** may comprise a body **150**. The compartment box may be part of the body **150**. The body **150** may be configured to mount the crane assembly onto a platform (see FIG. 11). In another embodiment the compartment box **140** or the crane column assembly **120** may be mounted onto a platform directly (without a body and/or compartment box).

[0023] The proposed technology of a crane column assembly **120** will be explained in the following. FIGS. 2a to 10 illustrate different views and parts of the crane column assembly **120**. Those figures are subsequently used to discuss several aspects of the examples described in this document. However, as will become evident from the following description, the various embodiments are not limited to the illustrations described herein. The proposed technology of a crane column assembly may, in general, be used for any type of crane and any structure of the crane.

[0024] FIG. 2a illustrates an example of a crane column assembly **120**. FIG. 2b illustrates the example of the crane column assembly **120** of FIG. 2a from a different angle, i.e. rotated by 90° about a vertical axis. The crane column assembly **120** for the crane **110** may be mounted on a mobile platform. The crane column assembly **120** comprises a support arrangement **210**. The support arrangement **210** is arranged to support a crane boom, for instance the crane boom **130**. The support arrangement **210** is connected to a base structure **220**.

[0025] The support arrangement **210** may have a height dimension, a width dimension, and a length dimension. The plane spanned by the length-width dimension may be referred to as a horizontal plane and the height dimension may be referred to as a vertical direction. For instance, a horizontal plane surface of the support arrangement **210** may be mounted on the base structure **220**, i.e., that the support arrangement **210** extends vertically. In some examples the support arrangement **210** may have the shape of a cylinder or cube or the like.

[0026] The support arrangement **210** may be an object with an empty space or cavity inside, at least partly surrounded by material that forms or outlines outer limits support arrangement **210**. For example, the support arrangement **210** may form a frame, i.e., it outlines space which may not be fully enclosed by the outer frame limits. For instance, the support arrangement **210** may comprise a plurality of portions. The one or more portions of the support arrangement **210** may form the outer limits of the support arrangement **210**. In some examples, the support arrangement may comprise a first portion **212** and a second portion **214**. For instance, the first **212** and the second portion **214** are plates extending in the vertical direction and that are mounted in the horizontal plane on the base structure **220**.

[0027] In some examples, the crane arm **130** may be movably connected to support arrangement **210**, for example by a ball bearing or a bolt **216a/216b**. For instance, the first portion **212** and the second portion **214** of the support arrangement **210** form a hinge with the crane boom **130**. For example, an attachment of the hinge (for example the bolt **216a/216b**) may extend between the first portion **212** and the second portion **214** of the support arrangement **210**. For instance, an attachment of the hinge (for example the bolt **216a/216b**), may extend in the horizontal plane between the vertically extending first portion **212** and second portion **214** of the support arrangement **210**. In some examples, the support arrangement **210** may be rigidly connected to the crane arm **130**, for example by bolting or welding. The crane boom may be part of a crane boom system, wherein the crane boom system may comprise a stiff boom system or a bendable boom system (e.g. a knuckle-boom system, which comprising at least one further hinge joint between the hinge at the support arrangement **210** and the crane tip).

[0028] In some examples the support structure may support one or more crane arms and/or one or more hydraulic cylinders for moving the one or more crane arms or a segment thereof. For instance, the crane arm **130** and/or the one or more hydraulic cylinders may be movably connected to support arrangement **210**, for example by respective a ball bearing or bolt **216a/216b**.

[0029] In some examples, a length and width dimension (which may be equal or different) of the base structure **220** may be significantly larger than a height dimension of the base structure **220** (e.g. 2, 5, 10 or 20 times as large). The base structure **220** may have a round or square or a polygonal or irregular cross-section. In some examples, the base structure has a shape of a plate or a disc. The base structure **220** may have one or more recesses or holes along the height dimension. For example, the base structure **220** may have a concentric, hollow cylindrical recess along the height dimension. The support arrangement **210** may be mounted perpendicular to a length-width dimension of the base structure **220** on a length-width surface. The support arrangement **210** may be centered or non-centered on the length-width surface of the base structure **220**.

[0030] Further, the crane column assembly **120** comprises a cover arrangement **230**. The cover arrangement **230** is arranged between the support arrangement **210**. In other words, the cover arrangement **230** is at least partly positioned within the empty space outlined by the support arrangement **210**. That is the cover arrangement **230** is at least partly positioned between the outer frame limits of the support arrangement **210**. For instance, the cover arrangement **230** may be at least partly formed between the plurality of portions forming the outer limits of the support arrangement **210**. In some examples, where the support structure **210** may be formed by a first vertically extending plate **212** and parallel second vertically extending plate **214**, the cover arrangement **230** may be arranged at least partly between these two parallel plates.

[0031] Further, the cover arrangement **230** covers a region **240** of the crane column assembly comprising a region between the support arrangement **210**. In some examples, the crane column assembly may be a cylindrical, concentric, and/or ring-formed assembly. The region **240** of the crane column assembly **120** may be a region of the empty space that is formed inside crane column assembly **120** or outlined by the crane column assembly **120**. That is the region **240** of the crane column assembly **120** may comprise an inner region of the crane column assembly **120**. The region between the support arrangement **210** is a part of the empty space, which is formed inside the

support arrangement **230** or outlined by the support arrangement **230**. The region **240** of the crane column assembly as well as the region between the support arrangement **210** may be at least partly formed and bounded by the outer limits of the support arrangement **210** and the cover arrangement **230**. The cover arrangement **230** may span over and provide coverage for the inner region of the crane column assembly.

[0032] That is the cover arrangement **230** may be arranged to seal the region **240** of the crane column assembly and/or the region between the support arrangement **210**. Therefore, no, or less fluid or other substances may enter or region the region **240** of the crane column assembly and/or the region between the support arrangement **210**. For example, rainwater that could damage the components inside the crane column assembly **120** is kept out by the cover arrangement **230** (which is also referred to as housing). Therefore, rust, or other wear caused by the ingress of fluid inside the crane column assembly **120** is minimized or prevented. Furthermore, components that may be mounted inside the region **240** (e.g. the rotary transfer system, see below) may be protected from rust or other wear caused by the ingress of fluid. Furthermore, components (e.g., for improved operation of the crane such as an endless slewing drive, see below) which are very sensitive to fluid or the like may be accommodated in a now sealed region **240**, which otherwise could not have been accommodated in a non-sealed region due to rapid wear or damage by fluid.

[0033] Furthermore, the cover arrangement **230** may ensure that a body **150** and/or a platform on which the crane column assembly **120** is mounted is not damaged by moisture seeping from the region **240** of the crane column assembly **120** to the body **150**. That is due to the sealing of the region **240** by the cover arrangement **230** no, or at least less, fluid will be in the region **240** and therefore no or less moisture may seep from the region **240** to the body **150** and/or a platform. In some examples, the crane column assembly **120** may be mounted onto the crane compartment box **140** (e.g., in a turn-key-solution of a stiff-boom-crane this may be a toolbox under the crane compartment where the tools and/or control electronic is integrated). The compartment box **140** that may contain, among other things, control units and/or other electronics for operating and controlling the crane (see FIGS. **1** and **11**). Due the cover arrangement **230** as described above there is less moisture in the compartment box **140** and therefore no or less rust or other wear and tear caused by the ingress of fluid. Furthermore, damage to the electronics or other sensitive components in the compartment box **230** may be prevented or minimized, thereby extending the lift time of the corresponding components.

[0034] For instance, the cover arrangement **230** may be screwed, riveted, glued, welded, or connected with another type of fastening to the support arrangement **210**. In another example, the cover arrangement **230** may be connected to the support arrangement **210** in such a way that they can be easily removed and reconnected, for example with a re-closable fastener. In any case the cover arrangement is sealingly connected to the support arrangement **210**. Thus, the cover arrangement **230** may be arranged to seal the region **240** of the crane column assembly and/or the region between the support arrangement **210**. Therefore, no fluid or other substances may enter or region the region **240** of the crane column assembly and/or the region between the support arrangement **210**.

[0035] For instance, the region **240** of the crane column assembly **120** may further comprise (beside the region between the support arrangement **230**) a region formed by one or more recesses or holes (along the vertical dimension) of the base structure **220** or a region below (in the vertical dimension) the base structure **220**. For example, the inner region of the column assembly **120** may comprise 50%, 60%, 70% or 80% or more or less of the empty space that is formed inside or outlined by the column assembly **120**.

[0036] In some examples, the region **240** of the crane column assembly **120** and/or the region between the support arrangement **210** comprises space for receiving one or more components arranged to control or operate the crane (for example rotary transfer system, see below). The cover arrangement **230** may cover at least a part of the one or more components.

[0037] In some examples, the cover arrangement **230** comprises a canopy portion **232** arranged over the region **240** of the crane column assembly and between the support arrangement **210**. The canopy portion **232** of the cover arrangement **230** may be at least partly arranged in the horizontal plane between the support arrangement **230**. For example, the canopy section **232** may be mounted horizontally at 50%, 60%, 70% or 80% or the like of the height of the support arrangement **210**. In some examples, the cover arrangement **230** is sealed to the support structure to form a sealed canopy covering at least part of the base structure **220**.

[0038] In yet another example, the cover arrangement **230** comprises at least one of a first lateral portion **234**, a canopy portion **232** and a second lateral portion **236**. The first lateral portion **234** and the second lateral portion **236** are arranged at least partially between the support arrangement **230**. For instance, the cover arrangement **230** may have a cross-section of an upside-down U-shape or V-shape or a polygon, which is for instance approximating a semicircle or a semi-ellipse or the like.

[0039] FIG. **3** illustrates an example of the crane column assembly **120** in an exploded view diagram. FIG. **4** illustrates an example of the crane column assembly **120** of FIG. **3** in an assembled state. FIGS. **5** to **10** show different sections of the crane column assembly **120** illustrated in FIG. **4**. The following descriptions apply to all these figures.

[0040] The crane column assembly **120** further comprises a base plate **310** mounted below the base structure **220**. For instance, the base structure **220** may be mounted directly onto an upper surface of the base plate **310** or some other components may be mounted between the base structure **220** and the base plate **310** (see below).

[0041] Base plate **310** (see also FIG. **6**) may have a round or square or a butterfly-shaped or polygonal or irregular cross-section. The base plate **310** may comprise one or more through holes **314** with which the base plate **310** may be mounted on a body **150** or a platform. These through holes **314** may be symmetrically distributed, for example at the four corners of the base plate **310**. Furthermore, the base plate **310** may comprise one or more holes or bores with which other components of the crane column assembly **120** may be connected to the base plate **310**. In one example, the base plate **310** comprises holes **316** with which a rotary transfer system (see below) can be mounted to it. These holes **316** may be arranged symmetrically, for example along a circle. Furthermore, the base plate **310** may comprise one or more through holes through which a connection between a component of the crane column assembly **120** or the crane and underlying components is made. For example, signal lines, power lines, oil lines, a cable for the crane hook or the like may run through the one or more connecting holes. For example, a connecting hole **318** may be located in the center of the base plate **310**.

[0042] Further, the base plate **310** comprises at least one drainage channel **312** arranged to drain fluid from the region **240** covered by the cover arrangement **230**. That is the drainage channel **312** is arranged to drain fluid from the inner region of the crane column assembly **120** (which is a part of the empty space that is formed inside or outlined by the column assembly **120**). The drainage channel is arranged to drain fluid outwardly from the inner region of the crane column assembly **120**. The drainage channel **312** may comprise a starting point inside the (inner) region **240** of the crane column assembly, an outflow point outside the region **240** of the crane column assembly **120** and a connecting piece between the starting point and the outflow point. The drainage channel **312** may drain the fluid radially or laterally away from the starting point to the outflow point on the outside, outside of the region **240** of the crane column assembly **120**. Further, the starting point of the drainage channel **312** may be a point where the fluid of the (inner) region **240** of the crane column assembly **120** assembly collects or is collected, for example a low point or a lowest point of the (inner) region **240** of the crane column assembly **120** to which the fluid naturally flows. The fluid may be water, for instance rainwater, lubricating fluid, such as oil, or the like. The drainage channel **312** is described in more detail with regards to sections illustrated in FIGS. **5** and **6** below.

[0043] The drainage channel **312** may ensure that fluid that has penetrated the region **240** of the crane column assembly **120** and/or the region between the support arrangement **210** may be drained

away quickly and to a great extent. For example, rainwater that has penetrated the crane column assembly **120** during when driving with airstream is drained off. This may reduce rust, or other wear caused by the ingress of fluid inside the crane column assembly **120**. Furthermore, components that may be mounted inside the region **240** (e.g. the rotary transfer system, see below) may be less attacked by rust or other wear caused by the ingress of fluid. Furthermore, components (e.g., for improved operation of the crane such as an endless slewing drive, see below) which are very sensitive to fluid, or the like may be accommodated in the region **240** where penetrated liquids get drained away quickly.

[0044] Furthermore, the drainage channel **312** may ensure that a body **150** and/or a platform on which the crane column assembly **120** is mounted is not or less damaged by moisture seeping from the region **240** of the crane column assembly **120** to the body **150**. That is due to the drainage of fluids from the region **240** by the drainage channel **312** less fluid will be in the region **240** and therefore no or less moisture may seep from the region **240** to the body **150** and/or a platform. In the case of the crane column assembly **120** being mounted on the compartment box **140**, less or no moisture may be seeping into the compartment box **140** and therefore no or less rust or other wear and tear may be caused by the ingress of fluid. Furthermore, damage to the electronics or other sensitive components in the compartment box **230** may be prevented or minimized, thereby extending the life time of the corresponding components. All of this applies regardless of the cover arrangement **230**, but in particular these aspects also work synergistically together with the cover arrangement **230**, which ensures that less water penetrates into the region **240**.

[0045] In some examples, the crane column assembly **120** comprises a slewing drive **320**. The slewing drive **320** may be arranged below the base structure. The slewing drive **320** may be configured for slewing at least part of the crane column assembly **120**. In some examples, the slewing drive **320** may be mounted between the support arrangement **210** and the base plate **310**. The slewing drive **320** may enable precise rotational movement of the support arrangement **210** and the crane boom **130** supported by support arrangement **210** around the vertical axis of the support arrangement **210**. The slewing drive **320** may comprise a slewing bearing, which is capable of handling axial, radial, and moment loads, ensuring smooth rotation of the support arrangement **210** and the crane boom **130**. Further, the slewing drive **320** may comprise a drive mechanism, for instance a worm gear driven by electric, hydraulic, or pneumatic motors, to provide the necessary rotational force with high precision and control. For instance, the slewing drive **320** may be mounted to the base plate **310** using screws **322**, or rivets or welding or another type of fastening.

[0046] In some examples, the crane column assembly **120** may further comprise a rotary transfer system **330** which may be mounted onto a surface of the base plate **310**. That is the region **240** of the crane column assembly **120** and/or the region between the support arrangement **210** comprises space for receiving the rotary transfer system **330**. The rotary transfer system is arranged to facilitate the transfer of electricity, power, signals, and/or fluids/gases between stationary parts (e.g., the base plate **310**) and the rotating parts (e.g., the support structure **210** and the supported crane boom **130**) of the crane column assembly **120**. This enables a continuous rotation (also referred to as 360°endless rotation) without tangling or disconnecting and connection. In some examples the rotary transfer system **330** comprises a rotary distributor (for example an oil distributor) and/or a slip ring.

[0047] For instance, the slewing drive **320** may be mounted to the base plate **310** using screws **322**, or rivets or welding or another type of fastening. Similarly, the base structure **220** of the support arrangement **210** may be mounted to the slewing drive **320** using, for example, screws **222**, rivets, welding, or another type of fastening, or may likewise be mounted directly to the base plate **310**.

[0048] The usage of the rotary transfer system **330** may be specifically suited for the above-described design of the crane column assembly **120** because the crane column assembly **120** may only provide a confined space. For instance, the support arrangement **210** may comprise at least one of the following dimensions: Width at least 15 cm and/or maximum 35 cm, length at least 20

cm and/or maximum 45 cm and/or height at least 30 cm and/or maximum 60 cm.

[0049] Further, the support arrangement **210** may comprise one or more lateral through-holes (e.g., a hole in the horizontal plane along the vertical dimension of the support structure **210**). For instance, one or more portions of the support arrangement **210** may comprise one or more lateral through-holes. In some examples, if the support arrangement **210** comprises two portions, the first portion **212** and the second portion **214**, the first portion may comprise a first lateral through-hole **252** and the second portion may comprise a second lateral through-hole (not shown in the figures).

[0050] In some examples, the crane column assembly **120** may comprise one or more cover portions mounted adjacent to the one or more portions of the support arrangement **210** arranged to cover the one or more lateral through-holes. For instance, the crane column assembly **120** comprises a first cover portion **342** arranged adjacent to a first portion **212** of the support arrangement **210**. This first cover portion **342** may cover a first through-hole **252** which is located in the first support portion **212**. In some examples, the first cover portion **342** may be arranged at a side of the first portion **212** of the support arrangement **210** opposite to the cover structure **230**. Accordingly, the crane column assembly **120** may comprise a second cover portion **344** arranged adjacent to the second portion **214** of the support arrangement **210**. This second cover portion **344** may cover a second through-hole (now shown in the figures) which may be located in the second portion **214** of the support arrangement **210**. The second cover portion **344** may be arranged at a side of the second portion **214** of the support arrangement **210** which is opposite to the cover structure **210**. For example, the first cover portion **342** and the second cover portion **344** may be mounted at an outer surface of the support arrangement **210** and the cover arrangement **230** may be mounted at an inner side of the support arrangement **230**.

[0051] For instance, the one or more cover portions may be screwed, riveted, glued, welded, or connected with another type of fastening to the support arrangement **210**. In another example, the one or more cover portions may be connected to the support arrangement **210** in such a way that they can be easily removed and reconnected, for example with a re-closable fastener. In any case, however, the cover portions are sealingly connected to the support arrangement **210**. Thus, the one or more cover portions may be arranged to seal the region **240** of the crane column assembly and/or the region between the support arrangement **210**. Therefore, no or less fluid or other substances may enter or region the region **240** of the crane column assembly **120** and/or the region between the support arrangement **210** from the side on which the one or more cover portions are attached to the support arrangement **210**. Therefore, the one or more cover portions may prevent or minimize rust, or other wear caused by the ingress of fluid to the inside the crane column assembly **120** or any component mounted inside the region **240** or below the crane column assembly **120**.

[0052] In one embodiment, the one or more cover portions may have one or more slits or recesses. The recesses can be arranged in such a way that very little water can penetrate. The recesses can be used for ventilation.

[0053] Coming to the sections of the crane column assembly of FIG. 4 illustrated in FIGS. 5 and 6 which illustrate the drainage channel **312** in more detail. FIG. 5 illustrates a section taken along the line V-V of FIG. 4. FIG. 6 illustrates a section taken along the line VI-VI of FIG. 4.

[0054] In some examples, the at least one drainage channel **312** may extend away from an upper side of the base plate **310**. The upper side of the base plate **310** may be a surface facing the support arrangement **210**, that is the upper side extends in a horizontal plane of the base plate **310**. That is the drainage channel **312**, or a portion of the drainage channel **312**, may start at the side facing the support arrangement **210** and is extending vertically into the base plate **310**.

[0055] In some examples the at least one drainage channel **312** may extend laterally outwards at an upper surface (e.g., a side facing the support arrangement **210**) of the base plate **310** and/or inside the base plate **310**. The starting point of the drainage channel **312** may for example be at the upper surface of the base plate **310**. The lateral extension (also referred to as radial extension) of the drainage channel **312** may comprise the drainage channel **312** extending from its starting point

outwards to a side surface of the base plate **310**. A side surface may be a surface of the base plate **310** that is orthogonal to the upper surface of the base plate **310**. In some examples, the drainage channel **312** may comprise a component which extends within the horizontal plane of the base plate. The drainage channel may extend partially or completely within the horizontal plane. In some examples, the drainage channel **312** may however comprise a component extending in the vertical direction. For example, an angle formed between the drainage channel **312** and the vertical dimension may be 0°, 5°, 10°, 15°, 20° or more. This may make it easier for water to drain outwards, for example. For instance, the drainage channel **312** may extend outwards at a surface of the base plate **310**, for example as a semi-open channel. In another example, the drainage channel **312** may extend partially or fully inside base plate **310**.

[0056] In some examples, the draining channel **312** may comprise one or more portions that may be directed in different directions. For instance, the draining channel **312** may change its direction one or more times. For example, the drainage channel **312** may have a cross-section of an “L” or of a cascade, i.e., comprising one or more portions running in a vertical direction and comprising one or more portions running in the horizontal plane.

[0057] For example, the starting point of the drainage channel **312** may be located along a lateral/radial line (between the center of the base plate **310** and a side surface of the base plate **310**) beyond (in direction of the side surface of the base plate) a fastening element **510**. The fastening element **510** may be connecting the rotary transfer system **330** and the base plate **310**.

[0058] In some examples, the base plate **310** comprises a plurality of drainage channels arranged to drain fluid from the region **240** covered by the cover arrangement **230**. The one or more drainage channels may start at the same starting point and extending outwards in different directions, or they may be fully distinct with different starting points. They may be arranged symmetrically or asymmetrically on the surface and/or inside the base plate **230**.

[0059] Further, the crane column assembly **120** may comprise a sealing **512** between the rotary transfer system **330** and the base plate **310**. For instance, the sealing **512** may be positioned between the fastening element **510**, which is connecting the rotary transfer system **330** and the base plate **310**, and the base plate **310**. For instance, the sealing **512** may comprise a sealing material such as rubber, Polytetrafluorethylene (PTFE), silicone, anaerobic adhesives, metallic components (such as copper, aluminum or lead) or the like which is inserted between the fastening element **512**/the rotary transfer system **330** and the base plate **310**. Further, the sealing **512** may comprise a (flat) gasket selected according to the required size and thickness may to optimally cover the sealing surfaces. Further, the sealing **512** may comprise an O-ring for instance made from elastomeric materials or the like.

[0060] FIGS. 7 to 10 illustrate further sections of the crane column assembly **120** illustrated in FIG. 4, that is: FIG. 7 illustrates a section taken along the line VII-VII of FIG. 4. FIG. 8 illustrates a section taken along the line VIII-VIII of FIG. 4. FIG. 9 illustrates a section taken along the line IX-IX of FIG. 4. FIG. 10 illustrates a section taken along the line X-X of FIG. 4.

[0061] As described with regards to FIG. 1 the crane column assembly **120** as described in this disclosure may be used together with a crane boom in a crane. For instance, the column assembly **120** as described in this disclosure may be used in a transportable crane (such as mobile crane, a service crane, a loader crane, a lorry or truck-mounted crane, a stiff boom crane and a knuckle boom crane the like), tower crane, telescopic crane, jib crane, gantry crane, marine crane, deck crane or the like.

[0062] In some examples crane **110** (e.g., the crane column assembly **120**) may be mounted onto the body **150** and/or a compartment box **140**. The crane **110** together with the compartment box **140** and/or the body **150** may form a crane assembly **100** which may be mounted on a platform. A platform may be a vehicle, like a car or a truck or a train or the like. Further, the platform may be ship or the like.

[0063] The crane column assembly **120** as described with this disclosure may be used in a turnkey

solution crane. That is the crane column assembly **120** may be integrated in a crane, for example together with a compartment box **140** and/or the body **150** which may be assembled and provided as a ready-to-operate crane assembly (crane system). Such a crane assembly may be a fully functional crane setup which may be mounted on a plurality of different platform as described above.

[0064] FIG. **11** illustrates an example of a vehicle on which the crane column assembly **120** is mounted. The vehicle **1100** comprise a crane assembly **100**. The crane assembly **100** may comprise a body **150**. The body **150** may be configured to mount the crane assembly onto the vehicle. The crane assembly **100** comprises a compartment box **140**. The compartment box **140** may comprise a controller configured to control the crane and/or a winch controlling a crane hook. The compartment box **140** may be part of the body **150**. In another embodiment the compartment box **140** or the crane column assembly **120** may be mounted onto a platform directly (without a body and/or compartment box, see FIG. **11**). Further, the crane assembly **100** comprises the crane column assembly **120** as described in this disclosure. The crane column assembly **120** is mounted onto the compartment box **140** and/or the body. The crane column assembly **120** supports a crane boom **130**.

[0065] In the following, some examples of the proposed concept are presented:

[0066] An example (e.g., example 1) relates to a crane column assembly for a crane to be mounted on a mobile platform, the crane column assembly comprising a support arrangement arranged to support a crane boom, wherein the support arrangement is connected to a base structure, and a cover arrangement arranged between the support arrangement, wherein the cover arrangement covers a region of the crane column assembly comprising a region between the support arrangement.

[0067] Another example (e.g., example 2) relates to a previous example (e.g., example 1) or to any other example, further comprising a base plate mounted below the base structure, wherein the base plate comprises at least one drainage channel arranged to drain fluid from the region covered by the cover arrangement.

[0068] Another example (e.g., example 3) relates to a previous example (e.g., example 2) or to any other example, further comprising a slewing drive, mounted between the support arrangement and the base plate.

[0069] Another example (e.g., example 4) relates to a previous example (e.g., one of the examples 1 to 3) or to any other example, further comprising that the cover arrangement comprises a canopy portion arranged over the region of the crane column assembly and between the support arrangement, the region of the crane column assembly comprising an inner region of the crane column assembly.

[0070] Another example (e.g., example 5) relates to a previous example (e.g., one of the examples 1 to 4) or to any other example, further comprising that the cover arrangement comprises at least one of a first lateral portion, a canopy portion and a second lateral portion, wherein the first lateral portion and the second lateral portion are arranged at least partially between the support arrangement.

[0071] Another example (e.g., example 6) relates to a previous example (e.g., one of the examples 1 to 5) or to any other example, further comprising that the region between the support arrangement comprises space for receiving a rotary transfer system, wherein the cover arrangement covers at least part of the rotary transfer system.

[0072] Another example (e.g., example 7) relates to a previous example (e.g., one of the examples 2 to 6) or to any other example, further comprising that a rotary transfer system of the crane column assembly is mounted onto a surface of the base plate.

[0073] Another example (e.g., example 8) relates to a previous example (e.g., one of the examples 1 to 6) or to any other example, further comprising a sealing mounted between the rotary transfer system and the base plate.

[0074] Another example (e.g., example 9) relates to a previous example (e.g., one of the examples 6 to 8) or to any other example, further comprising that the rotary transfer system comprises a rotary distributor and/or a slip ring.

[0075] Another example (e.g., example 10) relates to a previous example (e.g., one of the examples 2 to 9) or to any other example, further comprising that the at least one drainage channel extends away from an upper side of the base plate, the upper side of the base plate facing the support arrangement.

[0076] Another example (e.g., example 11) relates to a previous example (e.g., one of the examples 2 to 10) or to any other example, further comprising that the at least one drainage channel extends laterally outwards at an upper side of the base plate and/or inside the base plate.

[0077] Another example (e.g., example 12) relates to a previous example (e.g., one of the examples 2 to 11) or to any other example, further comprising that the base plate comprises a plurality of drainage channels arranged to drain fluid from the region covered by the cover arrangement.

[0078] Another example (e.g., example 13) relates to a previous example (e.g., one of the examples 1 to 12) or to any other example, further comprising that the support arrangement comprises a first portion and a second portion.

[0079] Another example (e.g., example 14) relates to a previous example (e.g., example 13) or to any other example, further comprising that the first portion and the second portion of the support arrangement form a hinge with the crane boom.

[0080] Another example (e.g., example 15) relates to a previous example (e.g., example 14) or to any other example, further comprising that an attachment of the hinge extends between the first portion and the second portion support arrangement.

[0081] Another example (e.g., example 16) relates to a previous example (e.g., one of the examples 1 to 15) or to any other example, further comprising that a first portion and/or a second portion of the support arrangement comprises a lateral through-hole.

[0082] Another example (e.g., example 17) relates to a previous example (e.g., one of the examples 1 to 16) or to any other example, further comprising a first cover portion arranged adjacent to a first portion of the support arrangement, wherein the first cover portion covers a through-hole located in the first support portion.

[0083] Another example (e.g., example 18) relates to a previous example (e.g., example 17) or to any other example, further comprising that the first cover portion is arranged at a side of the first portion of the support arrangement opposite to the cover structure.

[0084] Another example (e.g., example 19) relates to a previous example (e.g., one of the examples 17 or 18) or to any other example, further comprising a second cover portion arranged adjacent to a second portion of the support arrangement, wherein the second cover portion covers a through-hole located in the second portion of the support arrangement.

[0085] Another example (e.g., example 20) relates to a previous example (e.g., example 19) or to any other example, further comprising that the second cover portion is arranged at a side of the second portion of the support arrangement opposite to the cover structure.

[0086] Another example (e.g., example 21) relates to a previous example (e.g., one of the examples 19 or 20) or to any other example, further comprising that the first cover portion and the second cover portion are arranged to seal the region between the support arrangement.

[0087] Another example (e.g., example 22) relates to a previous example (e.g., one of the examples 1 to 21) or to any other example, further comprising that the cover arrangement is welded to the support arrangement.

[0088] Another example (e.g., example 23) relates to a previous example (e.g., one of the examples 1 to 22) or to any other example, further comprising that the crane column assembly is mountable onto a compartment box, wherein the compartment box is arranged to be mounted on the mobile platform.

[0089] An example (e.g., example 24) relates to a crane, comprising the crane column assembly

according to any one of examples 1 to 23, the crane boom supported by the crane column assembly. [0090] An example (e.g., example 25) relates to a crane assembly, comprising the crane according to example 24, a compartment box comprising circuitry configured to control the crane, wherein the crane is mounted onto the compartment box and wherein compartment box is mounted onto the vehicle.

[0091] An example (e.g., example 26) relates to a vehicle, comprising the crane assembly according to example 25, wherein compartment box is mounted onto the vehicle.

[0092] The aspects and features described in relation to a particular one of the previous examples may also be combined with one or more of the further examples to replace an identical or similar feature of that further example or to additionally introduce the features into the further example.

[0093] The following claims are hereby incorporated in the detailed description, wherein each claim may stand on its own as a separate example. It should also be noted that although in the claims a dependent claim refers to a particular combination with one or more other claims, other examples may also include a combination of the dependent claim with the subject matter of any other dependent or independent claim. Such combinations are hereby explicitly proposed, unless it is stated in the individual case that a particular combination is not intended. Furthermore, features of a claim should also be included for any other independent claim, even if that claim is not directly defined as dependent on that other independent claim.

Claims

1. A crane column assembly for a crane to be mounted on a mobile platform, the crane column assembly comprising: a support arrangement arranged to support a crane boom, wherein the support arrangement is connected to a base structure; and a cover arrangement arranged between the support arrangement, wherein the cover arrangement covers a region of the crane column assembly comprising a region between the support arrangement.
2. The crane column assembly according to claim 1, further comprising a base plate mounted below the base structure, wherein the base plate comprises at least one drainage channel arranged to drain fluid from the region covered by the cover arrangement.
3. The crane column assembly according to claim 2, further comprising a slewing drive, arranged below the base structure, wherein the slewing drive is configured for slewing at least part of the crane column assembly.
4. The crane column assembly according to claim 1, wherein the cover arrangement comprises a canopy portion arranged over the region of the crane column assembly and between the support arrangement, the region of the crane column assembly comprising an inner region of the crane column assembly.
5. The crane column assembly according to claim 1, wherein the cover arrangement comprises at least one of a first lateral portion, a canopy portion and a second lateral portion, wherein the first lateral portion and the second lateral portion are arranged at least partially between the support arrangement.
6. The crane column assembly according to claim 1, wherein the region between the support arrangement comprises space for receiving a rotary transfer system, wherein the cover arrangement covers at least part of the rotary transfer system.
7. The crane column assembly according to claim 2, wherein a rotary transfer system of the crane column assembly is mounted onto a surface of the base plate.
8. The crane column assembly according to claim 1, further comprising a sealing mounted between the rotary transfer system and the base plate.
9. The crane column assembly according to claim 2, wherein the at least one drainage channel extends away from an upper side of the base plate, the upper side of the base plate facing the support arrangement.

- 10.** The crane column assembly according to claim 2, wherein the at least one drainage channel extends laterally outwards at an upper side of the base plate and/or inside the base plate.
- 11.** The crane column assembly according to claim 1, wherein the support arrangement comprises a first portion and a second portion.
- 12.** The crane column assembly according to claim 11, wherein the first portion and the second portion of the support arrangement form a hinge with the crane boom.
- 13.** The crane column assembly according to claim 12, wherein an attachment of the hinge extends between the first portion and the second portion support arrangement.
- 14.** The crane column assembly according to claim 1, wherein a first portion and/or a second portion of the support arrangement comprises a lateral through-hole.
- 15.** The crane column assembly according to claim 1, further comprising a first cover portion arranged adjacent to a first portion of the support arrangement, wherein the first cover portion covers a through-hole located in the first support portion.
- 16.** The crane column assembly according to claim 15, further comprising a second cover portion arranged adjacent to a second portion of the support arrangement, wherein the second cover portion covers a through-hole located in the second portion of the support arrangement.
- 17.** The crane column assembly according to claim 1, wherein the crane column assembly is mountable onto a compartment box, wherein the compartment box is arranged to be mounted on the mobile platform.
- 18.** A crane, comprising: the crane column assembly according to claim 1; the crane boom supported by the crane column assembly.
- 19.** A crane assembly, comprising: the crane according to claim **18**; a compartment box comprising circuitry configured to control the crane, wherein the crane is mounted onto the compartment box and wherein compartment box is mounted onto the vehicle.
- 20.** A vehicle, comprising: **10** the crane assembly according to claim **19**, wherein compartment box is mounted onto the vehicle.
-