

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278053

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

KOSEKI; HIROMICHI

IMAGE FORMING APPARATUS

Abstract

An image forming apparatus configured to form an image on a recording medium includes a first block including a first frame, a transfer member for transferring the image onto the recording medium, and a first conveyance path in which the recording medium is conveyed, a second block including a second frame separably stacked on the first frame, a second conveyance path in which the recording medium is conveyed from the first conveyance path, and a discharging unit configured to discharge the recording medium conveyed through the second conveyance path to an outside, three supporting portions for supporting the first block, and three supporting portions for supporting the second block. The first block is supported via the three supporting portions for supporting the first block. The second block is supported via the three supporting portions for supporting the second block with respect to the first block.

Inventors: KOSEKI; HIROMICHI (Saitama, JP)
Applicant: CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID: 94868755
Appl. No.: 19/062668
Filed: February 25, 2025

Foreign Application Priority Data

JP 2024-030718 Feb. 29, 2024

Publication Classification

Int. Cl.: G03G21/16 (20060101)

U.S. Cl.:

CPC G03G21/1619 (20130101); G03G2221/1684 (20130101)

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] This disclosure relates to an image forming apparatus such as a printer, a copier, a facsimile, or a multifunction machine.

Description of the Related Art

[0002] Hitherto, in image forming apparatuses, a single main frame is constructed by integrating a plurality of sheet metals using screw fastening or welding (see Japanese Patent Laid-Open No. 2021-39153). Then, various units are supported by the single main frame.

SUMMARY OF THE INVENTION

[0003] This disclosure provides an image forming apparatus including a plurality of separable frames.

[0004] According to one aspect of the present invention, an image forming apparatus configured to form an image on a recording medium includes a first block including a first frame, a transfer member for transferring the image onto the recording medium, and a first conveyance path in which the recording medium is conveyed, a second block including a second frame separably stacked on the first frame, a second conveyance path in which the recording medium is conveyed from the first conveyance path, and a discharging unit configured to discharge the recording medium conveyed through the second conveyance path to an outside, three supporting portions for supporting the first block, and three supporting portions for supporting the second block. The first block is supported via the three supporting portions for supporting the first block. The second block is supported via the three supporting portions for supporting the second block with respect to the first block.

[0005] Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 is a schematic diagram illustrating a configuration of an image forming apparatus.

[0007] FIG. 2A is a schematic diagram illustrating a discharging frame.

[0008] FIG. 2B is a schematic diagram illustrating an imaging frame.

[0009] FIG. 2C is a schematic diagram illustrating a supply frame.

[0010] FIG. 3 is a schematic diagram illustrating supporting portions of each block.

[0011] FIG. 4 is a schematic diagram illustrating positions of a third supporting portion of the imaging frame, and a connecting strut.

[0012] FIG. 5A is a schematic diagram illustrating positional relationships among the supporting portions in a discharging block.

[0013] FIG. 5B is a schematic diagram illustrating positional relationships among the supporting portions in an imaging block.

[0014] FIG. 5C is a schematic diagram illustrating positional relationships among the supporting portions in a supply block.

DESCRIPTION OF THE EMBODIMENTS

[0015] The present inventors have identified that conventional techniques, involving the assembly of various units and the like into the single main frame, have issues. For example, it is difficult to expand functions of the image forming apparatuses. Sometimes, it is necessary to replace some units of the image forming apparatuses with units that have different functions. However, the

conventional single main frames are designed with the premise of supporting specific units. Therefore, in most cases, it is not possible to replace the units with alternative units. In addition, as another example, sometimes, according to diverse requirements from users, it is necessary to provide a plurality of image forming apparatuses with specifications that differ from each other. In cases of the image forming apparatuses that possess the single main frame, the main frame is designed on a zero base for each specification. This is a bottleneck in development, design, and manufacturing.

First Embodiment

Image Forming Apparatus

[0016] Hereinafter, this embodiment will be described. First, using FIG. **1**, a schematic configuration of an image forming apparatus of this embodiment will be described. To be noted, “front” and “rear” used in the following description refer to a front side of the image forming apparatus as the front, and a rear side as the rear. “Right” and “left” correspond to the sides in a case where the apparatus is viewed from the front. The front side is a side on which a user operates the apparatus, and, for example, is a side on which an operation panel is arranged or from which a cassette that stores a recording material is drawn out. “Vertical direction” refers to an upper/lower direction in a state in which the image forming apparatus is installed on an installation surface such as a floor. FIG. **1** illustrates the image forming apparatus **1** as viewed from the front side.

[0017] The image forming apparatus **1** illustrated in FIG. **1** is a full color printer of an intermediate transfer system. Image forming units PY, PM, PC, and PK of four colors, which form toner images of yellow (Y), magenta (M), cyan (C), and black (K), are arranged to face an intermediate transfer belt **21**. The image forming apparatus **1** includes an image formation unit **500**. The image formation unit **500** forms the toner image on a recording material S based on an image signal received from a document reading unit **30**, an external device such as a personal computer, not shown, or the like. The image formation unit **500** includes the image forming units PY, PM, PC, and PK and an intermediate transfer unit **600**.

[0018] While not illustrated, the document reading unit **30** disposed on top of an apparatus body **1A** includes an image conveying unit and a document reading unit. The document conveying unit is disposed such that the front side (front face side) can be opened and closed with respect to the image reading unit. The user can stack a document, whose image requires reading, on the document conveying unit. In a closed state, the document conveying unit can automatically convey the document to the image reading unit one sheet of the document at a time. The image reading unit includes a document table and a reading sensor, and reads the image of the document placed on the document table one sheet of the document at a time. To be noted, the user can place the document on the document table with the document conveying unit opened, and can also capture the image of the document with the reading sensor by closing the document conveying unit with the document remaining on the document table.

[0019] A conveyance process of the recording material S in the image forming apparatus **1** will be described. The recording material S is stored in a cassette **31**, serving as a container, in a stacked manner. The conveyance of the recording material S is started by a supply unit **300**, serving as a supply unit. The supply unit **300** includes a supply roller **31a**. The recording material S is supplied from the cassette **31** to a conveyance path **60** by the supply roller **31a** one sheet at a time in synchronization with the timing for image formation. In the image forming apparatus **1** of this embodiment, the conveyance path **60** can convey the recording material S from below to above (so-called vertical conveyance method). To be noted, the recording material S includes various type of sheet materials, including a paper sheet such as standard paper, thick paper, rough paper, embossed paper, and coated paper, a plastic film, cloth, and the like.

[0020] The recording material S supplied from the cassette **31** to the conveyance path **60** is conveyed to a pre-registration roller pair **41** arranged in the middle of the conveyance path **60**. The pre-registration roller pair **41** and a registration roller pair **42** correct the skew of the recording

material S. In particular, a leading edge of the recording material S conveyed by the pre-registration roller pair **41** abuts against a nip portion of the registration roller pair **42**, which is stopping. With the leading edge of the recording material S aligned at a position of the nip portion of the registration roller pair **42**, the skew correction is performed by looping or bending the recording material S. Subsequent to performing the skew correction, the registration roller pair **42** starts rotation in synchronization with the timing of secondary transfer, and conveys the recording material S. The intermediate transfer belt **21** and a secondary transfer portion are arranged above the registration roller pair **42**, serving as a conveyance rotary member. The registration roller pair **42** conveys the recording material S to the secondary transfer portion from below to above in synchronization with the timing at which the toner image on the intermediate transfer belt **21** is transferred onto the recording material S (timing of secondary transfer). The registration roller pair **42** is arranged at the closest position to the secondary transfer portion on an upstream side of the secondary transfer portion with respect to the conveyance direction (vertical direction) of the recording material S conveyed through the conveyance path **60**. The secondary transfer portion is formed by a secondary transfer inner roller **22** and a secondary transfer outer roller **44** with the intermediate transfer belt **21**. The secondary transfer inner roller **22** and the secondary transfer outer roller **44** (second transfer member, secondary transfer member) face each other across the intermediate transfer belt **21**, serving as a transfer member (first transfer member, intermediate transfer member). The secondary transfer portion (secondary transfer inner and outer rollers **22** and **44**) forms a nip portion, and transfers the toner image onto the recording material S by applying a predetermined pressure force and secondary transfer voltage.

[0021] With respect to the conveyance process of the recording material S up to the secondary transfer portion described above, an image forming process of the image that is sent to the secondary transfer portion at a similar timing will be described. First, the image forming units PY to PK will be described. However, since the image forming units PY to PK are essentially the same except for the color of the toner, in the following description, the image forming unit PY for yellow will be described as a representative example.

[0022] The image forming unit PY includes a photosensitive drum **11Y**, serving as a photosensitive member, a charging apparatus **12Y**, serving as a charge unit, an exposing apparatus **13Y**, serving as an exposing unit, and a developing apparatus **14Y**, serving as a developing unit. A surface of the photosensitive drum **11Y** that is rotatably driven has been uniformly charged by the charging apparatus **12Y** beforehand, and, thereafter, an electrostatic latent image is formed with a laser beam emitted from the exposing apparatus **13Y** that is driven based on the image signal. Then, the electrostatic latent image formed on the photosensitive drum **11Y** is developed into the toner image by the developing apparatus **14Y**. The developing apparatus **14Y** develops the electrostatic latent image into the toner image using developer containing the toner and a carrier. To be noted, since the toner is consumed along with the development, at a suitable timing, the toner is replenished from a toner bottle, not shown, which stores the toner for replenishment, to the developing apparatus **14Y**.

[0023] A primary transfer voltage is applied to the toner image formed on the photosensitive drum **11Y** (on the photosensitive member) by a primary transfer roller **25Y**, which is arranged to face the photosensitive drum **11Y** across the intermediate transfer belt **21**, and the toner image is primarily transferred from the photosensitive drum **11Y** onto the intermediate transfer belt **21**. Primary transfer residual toner that remains on the photosensitive drum **11Y** after the primary transfer is collected by a photosensitive drum cleaner.

[0024] The intermediate transfer belt **21** is an endless belt that is stretched by the secondary transfer inner roller **22**, a drive roller **23**, a tension roller **24**, and the like, and is moved in an arrow A direction in FIG. **1**. That is, the intermediate transfer belt is configured in an annular shape. The tension roller **24** is a driven rotary member, and, while applying tension to the intermediate transfer belt **21**, rotates in conjunction with a movement of the intermediate transfer belt **21** that is driven by

the drive roller **23**. The image forming processes for each color, which are processed in parallel by the image forming units PY to PK described above, are performed at the timing of sequentially superimposing on the toner image of each color primarily transferred upstream in the moving direction on the intermediate transfer belt. As a result, eventually, the toner image of the full color is formed on the intermediate transfer belt **21**, and, by the movement of the intermediate transfer belt **21**, the toner image is conveyed to the secondary transfer portion. To be noted, in this embodiment, the primary transfer rollers **25Y** to **25K**, the intermediate transfer belt **21**, the secondary transfer inner roller **22**, the drive roller **23**, and the tension roller **24** are configured integrally as the intermediate transfer unit **600**. However, the technology of this disclosure is not limited to such a configuration.

[0025] As described above, through the conveyance process and the image forming process each described above, at the secondary transfer portion, the timing of the recording material S and the full color toner image aligns, and the secondary transfer of the toner image from the intermediate transfer belt **21** onto the recording material S is performed. Secondary transfer residual toner that remains on the intermediate transfer belt **21** after passing through the secondary transfer portion is collected from the intermediate transfer belt **21** by a belt cleaner. The recording material S onto which the toner image has been transferred is conveyed to a fixing apparatus **50** through the conveyance path **60**, and, by applying heat and pressure in the fixing apparatus **50**, the toner image is fixed on the recording material S. The fixing apparatus **50** includes a fixing roller, which is heated by a heater, not shown, and a pressing roller, which forms a fixing nip portion by coming into contact with the fixing roller, and fixes the toner image on the recording material S by applying the heat and pressure to the recording material S that passes through the fixing nip portion. The recording material S on which the toner image has been fixed by the fixing apparatus **50** is conveyed further upward through the conveyance path **60**, and is discharged outside by a sheet discharge unit **700**, serving as a sheet discharge unit. The sheet discharge unit **700** includes a sheet discharge roller **61**, and the recording material S is supported on a sheet discharge tray **81** by being discharged by the sheet discharge roller **61**.

[0026] In the apparatus body **1A** of the image forming apparatus **1**, the operation panel **40**, which includes a display for displaying various information, keys capable of inputting various information according to user operations, and the like, is arranged to face the front (front face side). The user can adjust various settings at the time of operating the image forming apparatus **1** using the operation panel **40**. For example, in a case where the user performs a copy operation, the user can set parameters such as the number of sheets of the recording material S to be printed out, the size of the recording material S to be printed out, the cassette storing the recording material S to be printed out, scaling and density adjustments of a copy image, single-sided/double-sided copying, color/monochrome copying, etc., using the operation panel **40**.

Apparatus Body

[0027] Next, the apparatus body **1A** of this embodiment will be described. In a case of this embodiment, the apparatus body **1A** (structure) is divided into three separable structures: a supply block **110**, an imaging block **120**, and a discharging block **130**. To be noted, in this specification, the term “structure” refers to a state in which various units or components are mounted to a frame formed by members such as a strut and a stay (beam). In other words, the state in which the various units or the components are mounted to the frame is a state in which the various units or the components are supported by the frame. The supply, imaging and discharging blocks **110**, **120**, and **130** respectively include a supply frame **100e**, an imaging frame **100f**, and a discharging frame **100g**, as described below. For the purpose of making the three structures separable, the supply, imaging, and discharging frames **100e**, **100f**, and **100g** are configured to be separable from each other.

[0028] In this embodiment, the apparatus body **1A**, which achieves a series of functions for forming the image on the recording material S, is configured such that the imaging block **120** is

stacked on top of the supply block **110** and the discharging block **130** is stacked on top of the imaging block **120**. While not illustrated, the stacked imaging and discharging blocks **120** and **130** are interconnected by fastening a metallic plate-shaped member (coupling member), which bridges between the struts positioned vertically, using screws. The supply and imaging blocks **110** and **120** are also similarly interconnected with the coupling member.

Supply, Imaging, and Discharging Blocks

[0029] The supply block **110**, serving as a third block, is a structure in which the supply unit **300** and a supply conveyance path **610** are assembled into the supply frame **100e**, described below. In addition, a rail member, not shown, which slidably supports the cassette **31** in a front-to-rear direction, and the like are assembled into the support block **110**. The imaging block **120**, serving as a first block, is a structure in which the image formation unit **500** including the intermediate transfer unit **600** and an imaging conveyance path **620** are assembled into the imaging frame **100f**, described below. The image formation unit **500** may be detachably disposed in the imaging frame **100f**. The discharging block **130**, serving as a second block, is a structure in which the sheet discharge unit **700**, a discharging conveyance path **630**, and the fixing apparatus **50** are assembled into the discharging frame **100g**, described below.

[0030] In this embodiment, the conveyance path **60** that conveys the recording material **S** from below to above is divided and formed into each of the supply, imaging, and discharging blocks **110**, **120**, and **130**. That is, the supply conveyance path **610**, serving as a third conveyance path, forms part of the conveyance path **60** in the supply block **110**, the imaging conveyance path **620**, serving as a first conveyance path, forms part of the conveyance path **60** in the imaging block **120**, and the discharging conveyance path **630**, serving as a second conveyance path, forms part of the conveyance path **60** in the discharging block **130**. In the supply conveyance path **610**, the recording material **S** is conveyed from the cassette **31** toward the imaging conveyance path **620**, and, in the discharging conveyance path **630**, the recording material **S** is conveyed from the imaging conveyance path **620**.

Discharging, Imaging, and Supply Frames

[0031] Here, using FIGS. 2A to 2C, the discharging, imaging, and supply frames **100g**, **100f**, and **100e** described above will be described. As illustrated in FIG. 2A, the discharging frame **100g**, serving as a second frame, includes a right front strut **114ga**, a rear-side plate **115g**, a right upper stay **113ga**, a right lower stay **113gb**, a left stay **113gc**, and a front stay **113gd**. The right front strut **114ga** is extended in the vertical direction. The right upper and lower stays **113ga** and **113gb** are arranged in the vertical direction with respect to the right front strut **114ga**, are arranged substantially parallel to each other, and each connect the right front strut **114ga** with the rear-side plate **115g**. On the right lower stay **113gb**, the left stay **113gc** is arranged in a direction substantially perpendicular to the rear-side plate **115g** such that the left stay **113gc** is arranged substantially parallel and opposite to the right lower stay **113gb**. The front stay **113gd** is arranged in a direction (lateral direction) parallel to the rear-side plate **115g** such that the front stay **113gd** connects the left stay **113gc** and the right front strut **114ga**.

[0032] In addition, the discharging frame **100g** includes a front strut **114gb**, an upper stay **113ge**, and a right upper stay **113gf**. The right strut **114gb** is arranged further to the right than the center of the front stay **113gd** is between the left stay **113gc** and the right lower stay **113gb** in the lateral direction, and is arranged substantially parallel to the right front strut **114ga**. The front strut **114gb** is connected to the front stay **113gd**. The upper stay **113ge** is arranged substantially parallel to the right upper stay **113ga** such that the upper stay **113ge** connects the front strut **114gb** and the rear-side plate **115g**. The right upper stay **113gf** is arranged substantially parallel to the front stay **113gd** such that the right upper stay **113gf** connects the right front strut **114ga** and the front strut **114gb**. The discharging unit **700** described above is assembled into a space secured by these struts **114ga** and **114gb** and stays **113ga**, **113gb**, **113ge**, and **113gf**, and the rear-side plate **115g**.

[0033] As illustrated in FIG. 2B, the imaging frame **100f**, serving as a first frame, includes a right

front strut **114fa**, a left front strut **114fb**, a rear-side plate **115f**, a right upper stay **113fa**, a right lower stay **113fb**, a left upper stay **113ff**, a left lower stay **113fc**, a front upper stay **113fe**, and a front lower stay **113fd**. The right front strut **114fa** is extended in the vertical direction. The right upper and lower stays **113fa** and **113fb** are arranged in the vertical direction with respect to the right front strut **114fa**, are arranged substantially parallel to each other, and each connect the right front strut **114fa** and the rear-side plate **115f**. The left front strut **114fb** is extended in the vertical direction such that the left front strut **114fb** is arranged substantially parallel and opposite to the right front strut **114fa**. The left upper and lower stays **113ff** and **113fc** are arranged in the vertical direction with respect to the left front strut **114fb**, are arranged substantially parallel to each other, and each connect the left front strut **114fb** and the rear-side plate **115f**. The front upper stay **113fe** is arranged in a direction (lateral direction) parallel to the rear side plate **115f** such that the front upper stay **113fe** connects the right and left front struts **114fa** and **114fb** at their upper end portions. The front lower stay **113fd** is arranged in the direction (lateral direction) parallel to the rear-side plate **115f**, to connect the right and left front struts **114fa** and **114fb** at their lower end portions. In the imaging frame **100f**, to ensure strength as the frame, the right front strut **114fa**, the left front strut **114fb**, and reinforcement members **1151**, which correspond to struts disposed in the rear-side plate **115f**, are arranged at four corners of the frame. In the rear-side plate **115f**, the reinforcement members **1151** are disposed at both end portions in the lateral direction.

[0034] As illustrated in FIG. 2C, the supply frame **100e**, serving as a third frame, includes a right front strut **114ea**, a left front strut **114eb**, a rear-side plate **115e**, a right upper stay **113ea**, a right lower stay **113eb**, a left upper stay **113ef**, a left lower stay **113ec**, a front upper stay **113ee**, and a front lower stay **113ed**. The right front strut **114ea** is extended in the vertical direction. The right upper and lower stays **113ea** and **113eb** are arranged in the vertical direction with respect to the right front support column **114ea**, are arranged substantially parallel to each other, and each connect the right front strut **114ea** and the rear-side plate **115e**. The left front strut **114eb** is extended in the vertical direction such that the left front strut **114eb** is arranged substantially parallel and oppose to the right front strut **114ea**. The left upper and lower stays **113ef** and **113ec** are arranged in the vertical direction with respect to the left front strut **114eb**, are arranged substantially parallel to each other, and each connect the left front strut **114eb** and the rear-side plate **115e**. The front upper stay **113ee** is arranged in a direction (lateral direction) parallel to the rear-side plate **115e** such that the front upper stay **113ee** connects the right and left front struts **114ea** and **114eb** at their upper end portions. The front lower stay **113ed** is arranged in the direction (lateral direction) parallel to the rear-side plate **115e** such that the front lower stay **113ed** connects the right and left front struts **114ea** and **114eb** at their lower end portions. To be noted, in the vertical direction, a connecting position of the right upper stay **113ea** with respect to the right front strut **114ea** and a connecting position of the left upper stay **113ef** with respect to the left front strut **114eb** are below connecting positions of the front upper stay **113ee** with respect to the right and left front struts **114ea** and **114eb**. In the supply frame **100e**, to ensure strength as the frame, the right front strut **114ea**, the left front strut **114eb**, and reinforcement members **1152**, which correspond to struts disposed in the rear-side plate **115e**, are arranged at four corners of the frame. In the rear-side plate **115e**, the reinforcement members **1152** are disposed at both end portions in the lateral direction.

[0035] As described above, the apparatus body **1A** can be assembled by dividing it into the supply, imaging, and discharging blocks **110**, **120**, and **130**. The supply frame **100e** of the supply block **110** is mounted beneath the imaging frame **100f** of the imaging block **120**, and can be divided from the imaging frame **100f**. The discharging frame **100g** of the discharging block **130** is mounted on top of the imaging frame **100f** of the imaging block **120**, and can be divided from the imaging frame **100f**. Thereby, since units and components can be assembled into each of the supply, imaging, and discharging blocks **110**, **120**, and **130**, it is possible to significantly reduce assembly man-hours for the apparatus body **1A**, and it is possible to improve the product quality of the apparatus body **1A**.

Further, since it is straightforward to add and assemble units that achieve new functions (such as, a second fixing apparatus) into the supply, imaging, and discharging frames **100e**, **100f**, and **100g** by dividing the apparatus body **1A** into the supply, imaging, and discharging blocks **110**, **120**, and **130**, it is easy to expand the functions of the image forming apparatus **1**.

Supporting Configuration of Block

[0036] Next, with reference to FIGS. **1** and **2A** to **2C**, supporting configurations of the supply, imaging, and discharging blocks **110**, **120**, and **130** will be described using FIGS. **3** to **5C**. In this embodiment, as illustrated in FIG. **3**, the imaging block **120** is supported at three portions (**101f**, **102f**, **103f**) with respect to the supply frame **100e** through the imaging frame **100f**. The discharging block **130** is supported at three portions (**101g**, **102g**, **103g**) with respect to the imaging frame **100f** through the discharging frame **100g**. In addition, the supply block **110** is supported at three portions (**101e**, **102e**, **103e**) with respect to the installation surface such as the floor or desk through the supply frame **100e**. To be noted, while not illustrated, three supporting portions that protrude downward are formed in each of the discharging, imaging, and supply frames **100g**, **100f**, and **100e**, and these supporting portions provide support at three portions (**101**, **102**, **103**).

[0037] Incidentally, in a case where the apparatus body **1A** can be divided into the supply, imaging, and discharging blocks **110**, **120**, and **130**, if these supply, imaging, and discharging blocks **110**, **120**, and **130** are not supported via three portions, issues concerning the positional accuracy of the units and components mounted on the apparatus body **1A** may emerge. Hereinafter, two issues will be specifically illustrated with examples.

[0038] A first issue is to ensure the flatness of the intermediate transfer belt **21**. Since the intermediate transfer belt **21** is moved in a state of being stretched over the plurality of rollers (**22**, **23**, **24**), if the flatness of the intermediate transfer belt **21** fails to be maintained at equal to or more than a certain level, due to a difference in frictional resistance among the intermediate transfer belt **21** and the rollers (**22**, **23**, **24**), distortion will occur in the intermediate transfer belt **21**, and transfer defects may be caused. In addition, since, due to the difference in the frictional resistance, a movement force in a rotational axis direction is generated in the intermediate transfer belt **21** at the drive roller **23**, a regulation member to regulate so called “belt drift” where the intermediate transfer belt **21** shifts toward one end of the drive roller **23** or an alignment mechanism (also called as a steering mechanism) to correct the “belt drift” is disposed. However, if the movement force of the intermediate transfer belt **21** is too large, it is difficult to return the intermediate transfer belt **21** to its predetermined position in the rotational axis direction, and there is a risk that failures such as tearing of the intermediate transfer belt **21** could occur.

[0039] One of the factors contributing to inability to maintain the flatness of the intermediate transfer belt **21** is the distortion of the apparatus body **1A** caused by the unevenness of the installation surface on which the image forming apparatus **1** is installed. In a case of supporting via four portions, there is a possibility that one portion of the four portions may not make contact with the installation surface due to an effect of the unevenness of the installation surface. At this time, there is a possibility that a load applied to the one portion without contact may cause the deformation of the frame. The deformation of the frame consequently results in a reduction in the positional accuracy of the units and components mounted on the frame.

[0040] Therefore, in the image forming apparatus of this embodiment, the apparatus body **1A** is supported via the three portions, and, thereby the effect of the unevenness of the installation surface is suppressed, and, above the supporting portions, a relative position of each unit assembled into the apparatus body frame is ensured through the rigidity of the apparatus body frame. In more particular, by supporting the supply frame body **100e** on the installation surface via the three portions (**101e**, **102e**, **103e**), the effect of the unevenness of the installation surface on the supply frame **100e** is suppressed.

[0041] In addition, in this embodiment, a configuration in which the imaging frame **100f** (and the discharging frame **100g**) can be divided with respect to the supply frame **100e** is adopted.

Therefore, additionally, it is necessary to consider the distortion of the imaging frame **100f**. As a solution with respect to the distortion of the imaging frame **100f**, for example, a four-portion supporting configuration in which the supply and imaging frames **100e** and **100f** are secured near their four corners can be considered. By securing the frames near the four corners, through the rigidity of the supply and imaging frames **100e** and **100f**, the relative position of each unit assembled into the frames can be ensured.

[0042] However, in a case where the four-portion supporting configuration is adopted to the supply and imaging frames **100e** and **100f**, the supply and imaging frames **100e** and **100f** are susceptible to the effects of the installation surface of the supply frame **100e** and component tolerances of the supporting portions of the imaging frame **100f**. The required precision for the flatness of the intermediate transfer belt **21** is high, and the effects of such component tolerances cannot be ignored. Therefore, there is a room for further improvement in the four-portion supporting configuration described above.

[0043] Therefore, in this embodiment, as illustrated in FIG. 3, a three-portion supporting configuration in which the imaging frame **100f** is supported with respect to the supply frame **100e** via the three portions (**101f**, **102f**, **103f**) is adopted. The imaging frame **100f** is supported with respect to the supply frame **100e** via the first supporting portions **101f**, the second supporting portions **102f**, and the third supporting portion **103f**. By supporting the imaging frame **100f** via the three portions ((**101f**, **102f**, **103f**), it is possible to suppress the effect of the unevenness of the installation surface, the effect of the distortion of imaging frame **100f**, and the effects of the component tolerances. To be noted, the supply frame **100e** is supported with respect to the installation surface via the three supporting portions: a fourth supporting portion **101e**, a fifth supporting portion **102e**, and a sixth supporting portion **103e**. In addition, the discharging frame **100g** is supported with respect to the imaging frame **100f** via the three supporting portions: a seventh supporting portion **101g**, an eighth supporting portion **102g**, and a ninth supporting portion **103g**.

[0044] A second issue is an alignment assurance of roller pairs, which nip and convey the recording material S in the supply, imaging, and discharging conveyance paths **610**, **620**, and **630** (refer to FIG. 1), which are divided. Here, the alignment assurance refers to ensuring a state in which rotational axes are not misaligned among the roller pairs. When the rotational axes are misaligned among the roller pairs, a conveyance distance and the sliding resistance of the recording material S may vary, and there is a risk that the recording material S may be skewed. This can result in factors that degrade image position quality with respect to deliverables, referred to as geometric characteristics such as a left-edge margin. The misalignment among the roller pairs in the rotational axis direction may occur due to positional deviations in the lateral and vertical directions among the frames.

[0045] In this embodiment, as the solution to the first issue, the three-portion supporting configuration is adopted. While, at the supporting portions, it is possible to regulate positions in the vertical, front-to-rear, and lateral directions, at non-supporting portions, it is necessary to maintain degrees of freedom in the vertical and lateral positions to ensure the target flatness of the intermediate transfer belt **21**. Therefore, as illustrated in FIG. 3, in each block, two portions (**101**, **102**) among the three portions are arranged along the front-to-rear direction on a side of the conveyance path **60** (conveyance path side). In particular, when the imaging block **120** is viewed from above, the first and second supporting portions **101f** and **102f** of the imaging frame **100f** are positioned further to a side of the imaging conveyance path **620** (refer to FIG. 1) than the center of the imaging block **120** is. When the supply block **110** is viewed from above, the fourth and fifth supporting portions **101e** and **102e** of the supply frame **100e** are positioned further to a side of the supply conveyance path **610** (refer to FIG. 1) than the center of the supply block **110** is. In addition, when the discharging block **130** is viewed from above, the seventh and eighth supporting portions **101g** and **102g** of the discharging frame **100g** are positioned further to a side of the discharging

conveyance path **630** (refer to FIG. **1**) than the center of the discharging block **130** is.

[0046] As described above, by arranging two (**101**, **102**) of the three supporting portions on the side of the conveyance path **60** of each block in the front-to-rear direction, the positional relationship in the vertical direction can be ensured. Thereby, in the vertical conveyance method by which the recording material **S** is conveyed from below to above, even when the apparatus body **1A** is configured to be divided into the plurality of blocks (**110**, **120**, **130**), it is possible to suppress the distortion in a series of the conveyance path **60** (vertical conveyance path) in the apparatus body **1A**. Therefore, it is possible to suppress the occurrence of the deviations (alignment errors) in the rotational axis direction among the roller pairs that convey the recording material **S**.

[0047] The supply, imaging, and discharging frames **100e**, **100f**, and **100g** include high strength struts (**114ea**, **114eb**, **114fa**, **114fb**, **114ga**) and the reinforcement members (**1152**, **1151**, **1150**) (refer to FIGS. **2A** to **2C**). Therefore, the first supporting portion **101f** of the imaging frame **100f** is arranged on the right front strut **114fa**, and the second supporting portion **102f** of the imaging frame **100f** is arranged on the reinforcement member **1151** on the right side of the rear-side plate **115f**. The fourth supporting portion **101e** of the supply frame **100e** is arranged on the right front strut **114ea**, and the fifth supporting portion **102e** of the supply frame body **100e** is arranged on the reinforcement member **1152** on the right side of the rear-side plate **115e**. In addition, the seventh supporting portion **101g** of the discharging frame **100g** is arranged on the right front strut **114ga**, and the eighth supporting portion **102g** of the discharging frame **100g** is arranged on the reinforcement member **1150** on the right side of the rear-side plate **115g**. When the image forming apparatus **1** is viewed from above, it is preferred that the two supporting portions (**101**, **102**) are respectively arranged to overlap the seventh, first, and fourth supporting portions **101g**, **101f**, and **101e** and overlap the eighth, second, and fifth supporting portions **102g**, **102f**, and **102e**. As described above, since the two supporting portions (**101**, **102**) on the side of the conveyance path **60** of each block are arranged on the high strength struts and reinforcement members, the strength of supporting surfaces (seating surfaces) that support the two supporting portions (**101**, **102**) is ensured by these struts and reinforcement members.

[0048] On the other hand, as illustrated in FIG. **3**, remaining one supporting portion (**103**) of the three supporting portions is arranged on the opposite side across the conveyance path **60** in the lateral direction. In particular, when the imaging block **120** is viewed from above, the third supporting portion **103f** of the imaging frame **100f** is arranged on the left lower stay **113fc** (refer to FIG. **2B**) that is on a side further opposite to the imaging conveyance path **620** (refer to FIG. **1**) than the center of the imaging block **120** is. When the supply block **110** is viewed from above, the sixth supporting portion **103e** of the supply frame **100e** is arranged on the left lower stay **113ec** (refer to FIG. **2C**) that is on a side further opposite to the supply conveyance path **610** (refer to FIG. **1**) than the center of the supply block **110** is. In addition, the ninth supporting portion **103g** of the discharging frame **100g** is arranged on the left stay **113gc** (refer to FIG. **2A**) that is on a side further opposite to the discharging conveyance path **630** than the center of the discharging block **130** is.

[0049] As described above, the third supporting portion **103f** of the imaging frame **100f** and the ninth supporting portion **103g** of the discharging frame **100g** are respectively supported by the left upper stays **113ef** and **113ff**. Therefore, in comparison with the two supporting portions (**101**, **102**) arranged on the strut or the reinforcement member, the supporting surface (seating surface) is susceptible to deflection. In particular, since both the imaging and discharging blocks **120** and **130** exert loads on the lowermost supply frame **100e**, there is a high probability that the left upper stay **113ef** may bend. When the left upper stay **113ef** bends, it becomes difficult to resolve the issue described above.

[0050] Therefore, in this embodiment, as illustrated in FIG. **4**, in the supply frame **100e**, a connecting strut **104** is disposed to connect the left upper stay **113ef**, serving as a second stay, and the left lower stay **113ec**, serving as a first stay. The left upper stay **113ef** and the left lower stay **113ec** extend from the rear-side plate **115e** and extends in a direction perpendicularly to the vertical

direction. When viewed from above, the third supporting portion **103f** of the imaging frame **100f** is arranged in a position overlapping the connecting strut **104**. In addition, when viewed from above, the supporting portion **103e** of the supply frame **100e** is also arranged in a position overlapping the connecting strut **104**. As described above, the connecting strut **104** is arranged in the position overlapping the supporting portion **103e** of the supply frame **100e** and the supporting portion **103f** of the imaging frame **100f**. In this way, after ensuring the strength and rigidity by the connecting strut **104**, by arranging the supporting portion **103f** of the imaging frame **100f** on the connecting strut **104**, even when the loads from both the imaging and discharge blocks **120** and **130** are applied, the left upper stay **113ef** is prevented from bending.

[0051] To be noted, as illustrated in FIG. 4, for the third supporting portion **103f** of the imaging frame **100f** and the sixth supporting portion **103e** of the supply frame **100e**, in addition to cases where one contact portion, such as a projection, which comes into contact with the supporting surface, is provided at a single location, there are also cases where equal to or more than two contact portions (**1031f** and **1032f**, **1031e** and **1032e**) are provided at a single location. For example, by reducing a distance between the two contact portions, a single supporting portion can be configured. However, in the configuration having the three supporting portions, if any one of the supporting portions has two contact portions and the distance between the contact portions is substantial, it eventually results in a configuration that is not different from the four-portion supporting configuration. Therefore, in such a case, the distance between the two contact portions is set to be “equal to or less than 20%” of the length of the left lower stays (**113fc**, **113ec**) on which the supporting portions are arranged. For example, in a case where the length of one side of the left lower stay (**113fc**, **113ec**) is 600 millimeters (mm), the distance between the two contact portions is equal to or less than 120 mm. In this case, the two contact portions (**1031f** and **1032f**, **1031e** and **1032e**) are each arranged in the position overlapping the connecting strut **104**. To be noted, it is preferable that the two contact portions described above are arranged to align along the front-to-rear direction. In addition, while a lower limit distance between the two contact portions is not specifically restricted, “equal to or more than 5%” of the length of the left lower stay (**113fc**, **113ec**) on which the contact portions are disposed is preferable.

[0052] Further, positional relationships among the three supporting portions (**101**, **102**, **103**) described above will be described using FIGS. 5A to 5C. FIG. 5A is a schematic diagram illustrating the positional relationships among the three supporting portions (**101g**, **102g**, **103g**) in the discharging block **130** when viewed from above. FIG. 5B is a schematic diagram illustrating the positional relationships among the three supporting portions (**101f**, **102f**, **103f**) in the imaging block **120** when viewed from above. FIG. 5C is a schematic diagram illustrating the positional relationships among the three supporting portions (**101e**, **102e**, **103e**) in the supply block **130** when viewed from above.

[0053] In the image forming apparatus **1**, to improve usability during maintenance or replacement, a configuration that allows the user to insert and remove components such as the photosensitive drums **11Y** to **11K** and the developing apparatuses **14Y** to **14K** from the front side with respect to the apparatus body **1A** is adopted. Then, on the rear side (back side) of the apparatus body **1A**, a power unit for electricity supply and drive units such as a motor are arranged. In addition, the document reading unit **30** (refer to FIG. 1) is arranged on top of the apparatus body **1A**, and, as described above, the document conveyance unit of the document reading unit **30** can be opened and closed to the front side (front face side). In such an image forming apparatus **1** of the vertical conveyance method, when the apparatus body **1A** is configured to be divided into the aforementioned blocks (**110**, **120**, **130**), the center of gravity of the discharging and imaging blocks **130** and **120** shifts toward the rear.

[0054] In a case of adopting the three supporting portions described above, when each center of gravity (**110g**, **110f**, **110e**, refer to FIGS. 5A, 5B, and 5C) of each individual block (**110**, **120**, **130**) falls outside of a triangular area formed by the three supporting portions (**101**, **102**, **103**), the three-

portion supporting by the three supporting portions (**101**, **102**, **103**) cannot be preserved with respect to a block whose center of gravity is outside of the triangular area. As a result, since the apparatus body **1A**, which stacks the blocks, is installed in a deformed state, it becomes difficult to ensure the flatness of the intermediate transfer belt **21** described above and to realize the alignment assurance of the roller pairs. Therefore, in each block (**110**, **120**, **130**), using the two supporting portions (**101**, **102**) arranged on the side of the conveyance path **60** as a reference, it is necessary to determine the position of the remaining portion (**103**) such that the center of gravity (**110g**, **110f**, **110e**) does not fall outside of the triangular area.

[0055] In this embodiment, as illustrated in FIG. 5A, in the discharging block **130**, the supporting portion **103g** is arranged on the left stay **113gc** such that the center of gravity **110g**, including the document reading unit **30**, is positioned on a center line, indicated by a dotted line, of the triangular area. To be noted, as described above, the seventh supporting portion **101g** of the discharging frame **100g** is arranged on the right front strut **114ga**, and the eighth supporting portion **102g** of the discharging frame **100g** is arranged on the reinforcement member **1150** on the right side of the rear-side plate **115g**.

[0056] As illustrated in FIG. 5B, in the imaging block **120**, the supporting portion **103f** is arranged on the left lower stay **113fc** such that the center of gravity **110g** of the discharging block **130**, the center of gravity **110f** of the imaging block **120** alone, and the first composite center of gravity **111**, which is formed by combining these center of gravity **110g** and center of gravity **110f**, are positioned inside of the triangular area. The first composite center of gravity **111** is positioned on a linear line connecting the center of gravity **110g** of the discharging block **130** and the center of gravity of the imaging block **120** alone. To be noted, as described above, the first supporting portion **101f** of the imaging frame **100f** is arranged on the right front strut **114fa**, and the second supporting portion **102f** of the imaging frame **100f** is arranged on the reinforcement member **1151** on the right side of the rear-side plate **115f**.

[0057] As illustrated in FIG. 5C, in the support frame **100e**, the supporting portion **103e** is arranged on the left lower stay **113ec** such that the center of gravity **110e** of the support block **110** alone, the first composite center of gravity **111** described above, and a second composite center of gravity **112**, which is formed by combining these center of gravity **110e** and composite center of gravity **111**, are positioned inside of the triangular area. The second composite center of gravity **112** is positioned on a linear line connecting the center of gravity **110g** of the supply block **110** and the first composite center of gravity **111**, and serves as the center of gravity of the entire apparatus body **1A**. To be noted, as described above, the fourth supporting portion **101e** of the supply frame **100e** is arranged on the right front strut **114ea**, and the fifth supporting portion **102e** of the supply frame **100e** is arranged on the reinforcement member **1152** on the right side of the rear-side plate **115e**.

[0058] In this embodiment, the document reading unit **30** that shifts the center of gravity toward the rear, is disposed on top of the discharging block **130**. Therefore, in the discharging frame **100g**, on which the document reading unit **30** exerts a load, the supporting portion **103g** is arranged further rearward than the supporting portion **103f** of the imaging frame **100f** and the supporting portion **103e** of the supply frame **100e** is. On the other hand, the supporting portion **103f** of the imaging frame **100f** is arranged further forward than the supporting portion **103g** of the discharging frame **100g** in the front-to-rear direction is. Further, the supporting portion **103e** of the supply frame **100e** is arranged further forward than the supporting portion **103f** of the imaging frame **100f** in the front-to-rear direction is. This is because, by shifting the center of gravity of the discharging block **130**, on which the document reading unit is disposed, toward the rear and by placing the center of gravity of the supply frame **100e** toward the front, the apparatus body **1A** constituted by the discharging, imaging, and supply blocks **130**, **120**, and **110** achieves stability.

[0059] As described above, the image forming apparatus **1** of this embodiment includes the three structures: the supply, imaging, and discharging blocks **110**, **120**, and **130** which are separable.

These supply, imaging, and discharging blocks **110**, **120**, and **130** respectively include the supply, imaging, and discharging frames **100e**, **100f**, and **100g**, and various units and components are mounted within each frame. While the apparatus body **1A** of the image forming apparatus **1** is assembled by stacking these supply, imaging, and discharging blocks **110**, **120**, and **130**, the imaging block **120** is supported via the three supporting portions with respect to the supply block **110**. In addition, the discharging block **130** is supported via the three supporting portions with respect to the imaging block **120**. By supporting each block via the three supporting portions as described above, the apparatus body **1A** becomes more resistant to being affected by the unevenness of the installation surface. Therefore, the flatness of the intermediate transfer belt **21** within the apparatus body **1A** is ensured, and it is possible to suppress the occurrence of alignment errors among the roller pairs that convey the recording material **S**.

[0060] To be noted, to expand the functions of the image forming apparatus **1**, sometimes, units that implement new functions (such as a second fixing unit) are added and mounted to the supply, imaging, and discharging frames **100e**, **100f**, and **100g**. In such a case, the arrangement of the three supporting portions (**101**, **102**, **103**) described above is adjusted according to the centers of gravity of the supply, imaging, and discharging blocks **110**, **120**, and **130**. For example, it is acceptable to configure such that, by detachably disposing the three supporting portions each forming the supporting portion at a plurality of positions on struts and stays, the positions of the supporting portions in each block are adjusted according to the center of gravity of a block to which units have been newly added.

OTHER EMBODIMENT

[0061] To be noted, while, in this embodiment, the image forming apparatus **1** utilizes the intermediate transfer system in which the toner images of each color are secondarily transferred onto the recording material **S** after having been primarily transferred from the photosensitive drums **11Y** to **11K** onto the intermediate transfer belt **21**, it is not limited to this. For example, the image forming apparatus may utilize a direct transfer system in which the recording material **S** is conveyed by a conveyance belt that forms a nip portion with photosensitive drums, the toner images on the photosensitive drums are directly transferred onto a sheet by applying voltage to a transfer roller arranged to face the photosensitive drums across the conveyance belt.

[0062] While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

[0063] This application claims the benefit of Japanese Patent Application No. 2024-030718, filed Feb. 29, 2024, which is hereby incorporated by reference herein in its entirety.

Claims

1. An image forming apparatus configured to form an image on a recording medium, the image forming apparatus comprising: a first block including: a first frame, a transfer member configured to transfer the image onto the recording medium, and a first conveyance path in which the recording medium is conveyed; a second block including: a second frame separably stacked on the first frame, a second conveyance path in which the recording medium is conveyed from the first conveyance path, and a discharging unit configured to discharge the recording medium conveyed through the second conveyance path to an outside; three supporting portions for supporting the first block; and three supporting portions for supporting the second block, wherein the first block is supported via the three supporting portions for supporting the first block, and wherein the second block is supported via the three supporting portions for supporting the second block with respect to the first block.

2. The image forming apparatus according to claim 1, further comprising: a third block including: a

third frame separably arranged beneath the first frame, a container configured to store the recording medium, a supply unit configured to supply the recording medium from the container toward an inside of the first frame, and a third conveyance path in which the recording medium is conveyed from the container toward the first conveyance path, wherein the first block is supported via the three supporting portions for supporting the first block with respect to the third block.

3. The image forming apparatus according to claim 1, wherein the three supporting portions for supporting the first block are a first supporting portion, a second supporting portion, and a third supporting portion, and wherein, when the first block is viewed from above, among the first supporting portion, the second supporting portion, and the third supporting portion, the first supporting portion and the second supporting portion are positioned further to a side of the first conveyance path than a center of the first block is.

4. The image forming apparatus according to claim 3, wherein, when the first block is viewed from above, the third supporting portion is positioned further to a side opposite to the first conveyance path than the center of the first block is.

5. The image forming apparatus according to claim 4, wherein each of the first supporting portion, the second supporting portion, and the third supporting portion is composed of one contacting portion contacting with a supporting surface supporting the first block.

6. The image forming apparatus according to claim 4, wherein each of the first supporting portion and the second supporting portion is composed of one contacting portion contacting with a supporting surface supporting the first block, wherein the third supporting portion is composed of two contacting portions contacting with the supporting surface, and wherein a distance between the two contacting portions of the third supporting portion is equal to or less than 20% of a length of a stay with the third supporting portion provided.

7. The image forming apparatus according to claim 2, further comprising three supporting portions for supporting the third block, wherein the three supporting portions for supporting the third block are a fourth supporting portion, a fifth supporting portion, and a sixth supporting portion for supporting the third block with respect to an installation surface, and wherein, when the third block is viewed from above, among the fourth supporting portion, the fifth supporting portion, and the sixth supporting portion, the fourth supporting portion and the fifth supporting portion are positioned further to a side of the third conveyance path than a center of the third block is.

8. The image forming apparatus according to claim 7, wherein, when the third block is viewed from above, the sixth supporting portion is positioned further to a side opposite to the third conveyance path than the center of the third block is.

9. The image forming apparatus according to claim 7, wherein each of the fourth supporting portion, the fifth supporting portion, and the sixth supporting portion is composed of one contacting portion contacting with a supporting surface supporting the third block.

10. The image forming apparatus according to claim 7, wherein each of the fourth supporting portion and the fifth supporting portion is composed of one contacting portion contacting with a supporting surface supporting the third block, wherein the sixth supporting portion is composed of two contacting portions contacting with the supporting surface, and wherein a distance between the two contacting portions of the sixth supporting portion is equal to or less than 20% of a length of a stay with the sixth supporting portion provided.

11. The image forming apparatus according to claim 2, further comprising three supporting portions for supporting the third block, wherein the three supporting portions of the first block are a first supporting portion, a second supporting portion, and a third supporting portion, wherein, when the first block is viewed from above, among the first supporting portion, the second supporting portion, and the third supporting portion, the first supporting portion and the second supporting portion are positioned further to a side of the first conveyance path than a center of the first block is, wherein the three supporting portions for supporting the third block are a fourth supporting portion, a fifth supporting portion, and a sixth supporting portion for supporting the third block

with respect to an installation surface, and wherein, when the third block is viewed from above, among the fourth supporting portion, the fifth supporting portion, and the sixth supporting portion, the fourth supporting portion and the fifth supporting portion are positioned further to a side of the third conveyance path than a center of the third block is, wherein the third frame includes a side plate, a strut extending in a vertical direction, a first stay extending in a direction intersecting the vertical direction to connect the side plate and the strut, a second stay arranged above the first stay to connect the side plate and the strut, and a connecting strut extending from the first stay toward the second stay to connect the first stay and the second stay, and wherein, when the image forming apparatus is viewed from above, the third supporting portion and the sixth supporting portion overlap the connecting strut.

12. The image forming apparatus according to claim 3, wherein the three supporting portions for supporting the second block are a seventh supporting portion, an eighth supporting portion, and a ninth supporting portion, and wherein, when the second block is viewed from above, among the seventh supporting portion, the eighth supporting portion, and the ninth supporting portion, the seventh supporting portion and the eighth supporting portion are positioned further to a side of the second conveyance path than a center of the second block is.

13. The image forming apparatus according to claim 12, wherein, when the second block is viewed from above, the ninth supporting portion is positioned further to a side opposite to the second conveyance path than the center of the second block is.

14. The image forming apparatus according to claim 12, wherein, when the image forming apparatus is viewed from above, the first supporting portion and the seventh supporting portion overlap each other, and wherein, when the image forming apparatus is viewed from above, the second supporting portion and the eighth supporting portion overlap each other.

15. The image forming apparatus according to claim 12, wherein, when the image forming apparatus is viewed from above, the first supporting portion, the second supporting portion, and the third supporting portion are arranged in the first block such that a center of gravity of the first block, a center of gravity of the second block, and a first composite center of gravity, that is formed by combining the center of gravity of the first block and the center of gravity of the second block, are positioned inside of an area formed by connecting the first supporting portion, the second supporting portion, and the third supporting portion.

16. The image forming apparatus according to claim 11, wherein, when the image forming apparatus is viewed from above, the fourth supporting portion, the fifth supporting portion, and the sixth supporting portion are arranged in the third block such that a center of gravity of the third block, a first composite center of gravity that is formed by combining a center of gravity of the first block and a center of gravity of the second block, and a second composite center of gravity that is formed by combining the center of gravity of the third block and the first composite center of gravity are positioned inside of an area formed by connecting the fourth supporting portion, the fifth supporting portion, and the sixth supporting portion.

17. The image forming apparatus according to claim 1, further comprising: a photosensitive member; a charge unit configured to charge the photosensitive member; an exposing unit configured to form an electrostatic latent image by exposing the photosensitive member that has been charged; a developing unit configured to develop the electrostatic latent image on the photosensitive member into a toner image; and a second transfer member configured to form a transfer portion with the transfer member to transfer the toner image from the transfer member onto the recording medium, wherein the transfer member includes an intermediate transfer member onto which the toner image formed on the photosensitive member is primarily transferred, and wherein the second transfer member is configured to secondarily transfer the toner image from the intermediate transfer member onto the recording medium.
