

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278512

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Koo; Peter et al.

ELECTRONIC DEVICE WITH IMPROVED PRIVACY

Abstract

An electronic device can comprise physiological sensors that can generate sensor data, a device processor, an actuator, and a controller electrically connected with the device processor and the actuator. The controller can monitor the state of the actuator; communicate a notification signal to the device processor to cause the device processor to prepare for a privacy mode responsive to determining that the actuator is in a privacy state, delay implementing the privacy mode until one or more conditions have been satisfied to allow the device processor to prepare for the privacy mode pursuant to communicating the notification signal to the device processor; and implement the privacy mode to inhibit access to the sensor data responsive to satisfaction of the one or more conditions.

Inventors: Koo; Peter (Irvine, CA), Kiani; Massi Joe E. (Laguna Niguel, CA), Muhsin; Bilal (Irvine, CA), Priddell; Richard (Irvine, CA), Ahmed; Omar (Lake Forest, CA)

Applicant: Masimo Corporation (Irvine, CA)

Family ID: 94869587

Appl. No.: 19/064496

Filed: February 26, 2025

Related U.S. Application Data

us-provisional-application US 63650339 20240521

us-provisional-application US 63571844 20240329

us-provisional-application US 63560547 20240301

us-provisional-application US 63638799 20240425

Publication Classification

Int. Cl.: G06F21/62 (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57 for all purposes and for all that they contain.

TECHNICAL FIELD

[0002] The present disclosure relates to electronic devices including wearable devices. Specifically, the present disclosure relates to user input on electronic devices, including a privacy switch for protecting data.

BACKGROUND

[0003] Electronic devices can collect and maintain data which can include private or personal data. Data on an electronic device can be accessible by third-party applications executing on the electronic device or may be accessible to remote computing devices such as if the data is communicated from the electronic device to a remote computing device. Access to data can pose risks to privacy.

SUMMARY

[0004] Disclosed herein is a wearable electronic device for protecting private data, comprising: one or more physiological sensors configured to generate sensor data indicating a physiological status of a user of the wearable electronic device; a device processor electrically connected with the one or more physiological sensors and configured to access the sensor data; an actuator disposed on the wearable electronic device configured to change states responsive to user input; and a controller electrically connected with the device processor and the actuator. The controller can be configured to: monitor the state of the actuator; responsive to determining that the actuator is in a privacy state, communicate a notification signal to the device processor to cause the device processor to prepare for a privacy mode, wherein the device processor is configured to terminate one or more processes responsive to the notification signal from the controller to prepare for the privacy mode; delay implementing the privacy mode until one or more conditions have been satisfied to allow the device processor to prepare for the privacy mode pursuant to communicating the notification signal to the device processor; and implement the privacy mode to inhibit access to the sensor data responsive to satisfaction of the one or more conditions.

[0005] In some implementations, the device processor is configured to provide confirmation to the controller when the one or more processes have been terminated, wherein the one or more conditions comprise receiving the confirmation at the controller from the device processor that the one or more processes have been terminated.

[0006] In some implementations, the controller is configured to initiate a timer pursuant to determining that the actuator is in the privacy state, wherein the one or more conditions include the timer exceeding a threshold.

[0007] In some implementations, the controller is configured to initiate the timer in response to communicating the notification signal to the device processor.

[0008] In some implementations, the controller is configured to implement the privacy mode responsive to the timer exceeding the threshold regardless of whether the one or more processes have been terminated.

[0009] In some implementations, the controller is configured to implement the privacy mode based

on disconnecting a privacy component of the wearable electronic device from a power source, the privacy component comprising one or more of a communication component, a GNSS component, a microphone, a camera, or an altimeter.

[0010] In some implementations, the controller is configured to implement the privacy mode based on holding a privacy component of the wearable electronic device in a reset mode, the privacy component comprising one or more of a communication component, a GNSS component, a microphone, a camera, or an altimeter.

[0011] In some implementations, the controller is non-programmable.

[0012] In some implementations, the device processor is electrically isolated from the actuator and does not read the state of the actuator.

[0013] In some implementations, the wearable electronic device comprises a display screen configured to display indicia responsive to implementing the privacy mode, wherein the display screen is configured to display the indicia throughout the privacy mode.

[0014] In some implementations, the controller is configured to cause the indicia to be displayed on the display screen.

[0015] Disclosed herein is a method of implementing privacy on an electronic device, comprising: generating sensor data with one or more physiological sensors, the sensor data indicating a physiological status of a user of the electronic device; causing an actuator of the electronic device to change states responsive to user input; monitoring the state of the actuator with a controller electrically connected with the actuator; responsive to determining that the actuator is in a privacy state, communicating a notification signal from the controller to a device processor to cause the device processor to prepare for a privacy mode; terminating one or more processes with the device processor responsive to the notification signal from the controller to prepare for the privacy mode; delaying implementing the privacy mode until one or more conditions have been satisfied to allow the device processor to prepare for the privacy mode; and implementing the privacy mode to inhibit access to the sensor data responsive to satisfaction of the one or more conditions.

[0016] In some implementations, the one or more conditions comprise receiving confirmation at the controller from the device processor that the one or more processes have been terminated.

[0017] In some implementations, the method further comprises initiating a timer pursuant to determining that the actuator is in the privacy state, wherein the one or more conditions include the timer exceeding a threshold.

[0018] In some implementations, the method further comprises implementing the privacy mode based on disconnecting a privacy component of the electronic device from a power source, the privacy component comprising one or more of a communication component, a GNSS component, a microphone, a camera, or an altimeter.

[0019] In some implementations, the method further comprises implementing the privacy mode based on holding a privacy component of the electronic device in a reset mode, the privacy component comprising one or more of a communication component, a GNSS component, a microphone, a camera, or an altimeter.

[0020] Disclosed herein is non-transitory computer-readable media including computer-executable instructions that, when executed by a computing system, cause the computing system to perform operations comprising: monitoring a state of an actuator configured to change states responsive to user input; responsive to determining that the actuator is in a privacy state, causing a device processor to prepare for a privacy mode by terminating one or more processes; delaying implementing the privacy mode until one or more conditions have been satisfied to allow the device processor to terminate the one or more processes; and implementing the privacy mode to inhibit access to sensor data responsive to satisfaction of the one or more conditions.

[0021] In some implementations, the computer-executable instructions, when executed by the computing system, cause the computing system to perform operations comprising: implementing the privacy mode when the one or more processes have been terminated, wherein the one or more

conditions include termination of the one or more processes.

[0022] In some implementations, the computer-executable instructions, when executed by the computing system, cause the computing system to perform operations comprising: initiating a timer pursuant to determining that the actuator is in the privacy state; implementing the privacy mode when the timer exceeds a threshold, wherein the one or more conditions include the timer exceeding the threshold.

[0023] In some implementations, the computer-executable instructions, when executed by the computing system, cause the computing system to perform operations comprising implementing the privacy mode based on disconnecting a privacy component from a power source and/or holding the privacy component in a reset mode, the privacy component comprising one or more of a communication component, a GNSS component, a microphone, a camera, or an altimeter.

[0024] Disclosed herein is an electronic device comprising: one or more physiological sensors configured to generate sensor data indicating a physiological status of a user of the electronic device; and one or more hardware processors that can be configured to: determine whether a privacy mode is executing on the electronic device based on monitoring a state of an actuator, wherein one or more communication components are disabled during the privacy mode to inhibit communication of the electronic device; responsive to determining that the privacy mode is executing, cause the one or more physiological sensors to generate the sensor data during the privacy mode to measure a physiological status of the user during the privacy mode; obfuscate the sensor data with one or more encryption protocols and an encryption key to inhibit program applications without access to the encryption key from decrypting the sensor data; and modify metadata of the sensor data to indicate a privacy status of the sensor data, the privacy status corresponding to whether the sensor data was generated during the privacy mode.

[0025] In some implementations, the one or more hardware processors are configured to cause the one or more communication components to communicate the sensor data from the electronic device to a receiving electronic device during a non-privacy mode.

[0026] In some implementations, the one or more hardware processors are configured to cause the one or more communication components to communicate the sensor data over a secure channel.

[0027] In some implementations, the one or more hardware processors are configured to cause the one or more communication components to communicate the sensor data with the metadata.

[0028] In some implementations, the one or more hardware processors are configured to cause the one or more physiological sensors to generate the sensor data during the privacy mode responsive to determining that the user has selected to generate the sensor data during the privacy mode.

[0029] In some implementations, the one or more hardware processors are configured to allow the sensor data to be erased from short-term storage without storing the sensor data as persistent data responsive to determining that the user has not selected to store the sensor data.

[0030] In some implementations, the one or more hardware processors are configured to store the sensor data responsive to determining that the user has selected to store the sensor data.

[0031] In some implementations, the one or more hardware processors are configured to store the sensor data as persistent data in long-term storage.

[0032] In some implementations, the one or more hardware processors are configured to store the sensor data in a first location in storage and store non-private sensor data generated during a non-privacy mode in a second location in storage.

[0033] In some implementations, the one or more hardware processors are configured to store the sensor data in a same partition of storage as non-private sensor data generated during a non-privacy mode.

[0034] In some implementations, the one or more hardware processors are configured to store the sensor data in a structured data format based on the privacy status of the sensor data.

[0035] In some implementations, the one or more hardware processors are configured to: store the sensor data as historical sensor data; access the historical sensor data from storage; determine a

privacy status of the historical sensor data from the metadata; and generate user interface data for rendering a display comprising indicia of the historical sensor data and an indication of the privacy status of the historical sensor data.

[0036] In some implementations, the one or more hardware processors are configured to obfuscate non-private sensor data generated during a non-privacy mode with another encryption key different than the encryption key.

[0037] In some implementations, the one or more hardware processors are configured to obfuscate non-private sensor data generated during a non-privacy mode with another encryption protocol different than the one or more encryption protocols.

[0038] Disclosed herein is an electronic device that can comprise: one or more physiological sensors configured to generate sensor data indicating a physiological status of a user of the electronic device; and one or more hardware processors that can be configured to: access the sensor data; determine whether the sensor data was generated during a privacy mode based on metadata of the sensor data, the metadata indicating the sensor data is private if the sensor data was generated during the privacy mode; determine whether the user has selected to enable private data to be communicated from the electronic device; and communicate the sensor data from the electronic device to a receiving computing device over a secure channel responsive to determining that the sensor data is private and that the user has selected to enable private data to be communicated.

[0039] In some implementations, the one or more hardware processors are configured to inhibit the sensor data from being communicated from the electronic device to the receiving computing device responsive to determining that the sensor data is private and that the user has not selected to enable private data to be communicated.

[0040] In some implementations, the one or more hardware processors are configured to encrypt the sensor data.

[0041] In some implementations, the one or more hardware processors are configured to: implement a key exchange protocol to generate a key; and communicate the sensor data over the secure channel with the key.

[0042] In some implementations, the one or more hardware processors are configured to communicate the sensor data over the secure channel by communicating the sensor data to a trusted third-party device.

[0043] In some implementations, the one or more hardware processors are configured to inhibit program applications executing on the electronic device from accessing the sensor data responsive to determining that the sensor data is private.

[0044] Disclosed herein is an electronic device configured to monitor physiological parameters of a user. The electronic device can comprise: a sensor assembly integrated with the electronic device, the sensor assembly comprising one or more physiological sensors configured to generate physiological data of the user; a user input unit protruding from a housing of the electronic device, wherein the user input unit is contiguously integrated with an exterior surface of the housing and forms a portion of the exterior surface of the housing, wherein the user input unit is responsive to touch from the user; a display screen connected to the housing, wherein the user input unit is positioned on the housing out of a plane on which the display screen lies; and a processor in electrical communication with the display screen, the one or more physiological sensors, and the user input unit. The processor can be configured to cause the display screen to: display a plurality of display layout previews, wherein the display screen is configured to display less than all of the display layout previews at a time, wherein the display layout previews provide visualizations of display layouts on a reduced scale of size; move the display layout previews along a path within the display screen responsive to user input via the user input unit, wherein the path comprises an arc of a circle with a center that is offset from a center of the display screen, the center of the display screen being positioned between the center of the circle and the user input unit; and responsive to user selection of a display layout preview via the electronic device, render a display layout

corresponding to the selected display layout preview, wherein the display layout is larger than the selected display layout preview, the display layout comprising indicia of the physiological data originating from the one or more physiological sensors arranged within the display layout according to the selected display layout preview.

[0045] In some implementations, the user input unit does not move relative to the housing.

[0046] In some implementations, the display screen is configured to display no more than two of the display layout previews at a time.

[0047] In some implementations, the user input unit is positioned on the housing to the right of the display screen.

[0048] In some implementations, the processor is configured to receive the user selection of the display layout preview via the user input unit.

[0049] In some implementations, the processor is configured to receive the user selection of the display layout preview via the display screen.

[0050] In some implementations, the user input via the user input unit comprises user contact sliding across the user input unit.

[0051] In some implementations, the user input unit comprises a plurality of zones independently responsive to touch from the user, wherein the processor is configured to cause the display screen to move the display layout previews along the path based on user interaction with the plurality of zones.

[0052] In some implementations, the processor is configured to cause the display screen to move the display layout previews along the path with a speed that depends on time between user interactions with the plurality of zones.

[0053] In some implementations, the processor is configured to cause the display screen to move the display layout previews along the path in a direction that depends on an order in which the user interacts with the plurality of zones.

[0054] In some implementations, the user input unit has a length between about 25% and about 75% a diameter of the display screen.

[0055] In some implementations, the user input unit has a height between about 0.4 cm and 0.6 cm.

[0056] In some implementations, the user input unit is one of a capacitive, resistive, infrared, surface capacitive, or projected capacitive touch (PCAP) user input unit.

[0057] Various combinations of the above and below recited features, embodiments, implementations, and aspects are also disclosed and contemplated by the present disclosure.

[0058] Additional implementations of the disclosure are described below in reference to the appended claims, which may serve as an additional summary of the disclosure.

[0059] In various implementations, systems and/or computer systems are disclosed that comprise a computer-readable storage medium having program instructions embodied therewith, and one or more processors configured to execute the program instructions to cause the systems and/or computer systems to perform operations comprising one or more aspects of the above- and/or below-described implementations (including one or more aspects of the appended claims).

[0060] In various implementations, computer-implemented methods are disclosed in which, by one or more processors executing program instructions, one or more aspects of the above- and/or below-described implementations (including one or more aspects of the appended claims) are implemented and/or performed.

[0061] In various implementations, computer program products comprising a computer-readable storage medium are disclosed, wherein the computer-readable storage medium has program instructions embodied therewith, the program instructions executable by one or more processors to cause the one or more processors to perform operations comprising one or more aspects of the above- and/or below-described implementations (including one or more aspects of the appended claims).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0062] Various implementations will be described hereinafter with reference to the accompanying drawings. These implementations are illustrated and described by example only, and are not intended to limit the scope of the disclosure. In the drawings, similar elements may have similar reference numerals.

[0063] FIGS. **1A-1F** illustrate an example electronic device with user input including a privacy switch.

[0064] FIG. **2** is a schematic block diagram illustrating an example implementation of an electronic device in communication with one or more remote devices.

[0065] FIG. **3** illustrates a schematic system diagram of an electronic device including a sensor assembly and user input unit.

[0066] FIGS. **4A-4D** illustrate example user interfaces of an electronic device.

[0067] FIG. **5** is a front view of the example electronic device according to aspects of the disclosure.

[0068] FIG. **6A-6B** are perspective views of example implementations of electronic devices.

[0069] FIG. **7** is a block diagram of an example electronic device.

[0070] FIGS. **8A-8C** are block diagrams illustrating example implementations of an electronic device.

[0071] FIG. **9A** is a flowchart illustrating an example process of implementing a privacy mode on an electronic device.

[0072] FIG. **9B** is a flowchart illustrating an example process of managing device data generating during privacy modes and non-privacy modes.

[0073] FIG. **9C** is a flowchart illustrating an example process of managing access to and communication of device data.

[0074] FIG. **10** is a perspective view illustrating an example implementation of an actuator of an electronic device.

[0075] FIGS. **11A-11D** illustrate example displays of an electronic device which may display user interfaces.

[0076] FIG. **12** illustrates an example electronic device with a privacy switch implemented as a sound bar.

[0077] FIG. **13** illustrates an example electronic device with a privacy switch implemented as a phone.

[0078] FIG. **14** illustrates an example electronic device with a privacy switch implemented as a monitoring hub.

DETAILED DESCRIPTION

[0079] The present disclosure will now be described with reference to the accompanying figures, wherein like numerals may refer to like elements throughout. The following description is merely illustrative in nature and is in no way intended to limit the disclosure, its application, or uses.

Furthermore, the devices, systems, and/or methods disclosed herein can include several novel features, no single one of which is solely responsible for its desirable attributes or which is essential to practicing the devices, systems, and/or methods disclosed herein. Additionally, the structures, systems, and/or devices described herein may be embodied as integrated components or as separate components.

[0080] Some aspects and/or implementations have been described in connection with the accompanying drawings. The figures may be drawn to scale, but such scale is not limiting, since dimensions and proportions other than what are shown are contemplated and are within the scope of the disclosed invention. Distances, angles, etc. are merely illustrative and do not necessarily bear

an exact relationship to actual dimensions and layout of the devices illustrated. Components can be added, removed, and/or rearranged. Further, the disclosure herein of any particular feature, aspect, method, property, characteristic, quality, attribute, element, or the like in connection with various embodiments can be used in all other embodiments set forth herein. Additionally, any methods described herein may be practiced using any device suitable for performing the recited steps. Various steps within a method may be executed in different order without altering the principles of the present disclosure.

[0081] A dedicated privacy button for electronic device or wireless communications device (for example, cell phone, smart watch, etc.) can permit a user to control if and/or when third party apps, such as apps downloaded from an app store) are allowed to access private or sensitive data, such as health data. Some legitimate third party apps are given permission (for example, by the user) to access a user's health data via an API. However, the permission is typically "all or nothing."

Disclosed herein is a dedicated privacy button (for example, a hardware switch, a software switch, etc.) that allows a user to activate a privacy window (for example, a particular duration of time) over which little or no health data is shared (for example, with any apps, or with a particular app). Disclosed herein is an electronic device that includes software, firmware, hardware, or any combination thereof to provide or facilitate healthcare related services or applications. The electronic device may include hardware or software configurations that allows a user to adjust privacy-related settings, for example restricting private and personal data.

[0082] An electronic device can include any of the example electronic devices shown and/or described herein or can include one or more features or components thereof. For example, the electronic device can be implemented as a wearable device, smart watch, cell phone, smart phone, tablet computer, desktop computer, laptop, mobile computing device, mobile phone, personal digital assistant (PDA), hybrid PDA/mobile phone, any electronic device configured to communicate over a network, or any device configured for the internet of things.

[0083] The health care module can be configured to obtain or generate health data from a user of the wireless communications device. For example, the health care module can include one or more sensors configured to obtain physiological data. In some cases, the electronic device **10** includes an emitter and a detector for obtaining one or more physiological measurements. In some cases, the health data is private, sensitive, confidential and/or HIPPA protected.

[0084] The electronic device can include one or more processors. The one or more processors can be configured to implement a third party application, such as a mobile app. In some cases, the user can adjust privacy-related settings (for example, permissions) for third party applications. For example, in some cases, the user can choose to prevent the third party application from obtaining, or having access to, private or sensitive data, such as health data. Alternatively, in some cases, the user can choose to allow the third party application to obtain, or have access to, private or sensitive data. In some cases, the electronic device includes a dedicated privacy switch that is implemented in hardware and/or software. In some cases, activation of the dedicated privacy switch can cause the electronic device to prevent the third party application from obtaining the private or sensitive data. For example, for data that is generated while the privacy switch is activated, the third party application may not have access to such data while the privacy switch is activated and/or after the privacy switch is deactivated. In some implementations, deactivation of the dedicated privacy switch can cause the electronic device to allow the third party application to obtain or access the private or sensitive data. In some cases, activation of the dedicated privacy switch can cause the electronic device to temporarily prevent the third party application from obtaining the private or sensitive data for a first period of time (for example, 30 minutes, 1 hour, 8 hours, 24 hours, 1 week, etc.). In some cases, the third party application is automatically allowed to resume obtaining the private or sensitive data after the expiration of the first period of time. Furthermore, in some cases, deactivation of the dedicated privacy switch can cause the electronic device to temporarily allow the third party application to obtain the private or sensitive data for a second period of time. In

some cases, the third party application is automatically prevented from obtaining the private or sensitive data after the expiration of the second period of time.

[0085] The electronic device can identify some or all of the private or sensitive data, including data obtained or generated by the health care module. For example, the electronic device can associate an attribute (for example, use metadata to tag) with all of the private or sensitive data obtained or generated by the health module. In some such cases, in response to the activation of the dedicated privacy switch and for the duration of the first period of time, the electronic device can prevent transmission of or access to any data associated with the attribute. In some cases, the private or sensitive data is restricted by default. A user can give permission sell the private or sensitive data to the third party application. In some cases, the user shares in income from the sale of the private or sensitive data.

[0086] FIGS. 1A-1F illustrate perspective views of an example electronic device 10. The electronic device 10 may be a wearable device such as a smartwatch. FIGS. 1A-1F are not intended to be limiting of the present disclosure. One or more of any of the structural and/or operational features shown and/or discussed with respect to electronic device 10, or any of the other electronic devices herein, can be implemented in any of the example electronic and/or computing devices shown and/or discussed herein such as a phone, a laptop, a computer, a tablet, or any other computing device.

[0087] The electronic device 10 can include a display screen 12, housing 105, and one or more straps 30. The straps 30 can be adjustable. The straps 30 can be configured to secure the electronic device 10 to a body part of a user of the electronic device 10, such as a wrist. The display screen 12 can be an LED display. The display screen 12 can be configured to display day, month, date, year, and/or time. The display screen 12 can display time as analog or digital. The display screen 12 can display physiological related data such as physiological parameters, physiological trends, physiological graphs, or the like. For example, the display screen 12 can display heart rate, respiration rate, ECG data, SpO2, a step count of the number of steps taken by a user of the electronic device 10, or the like. The housing 105 can be circular and can surround the display screen 12. The housing 105 can be formed of an electrically conductive material, such as metal. The housing 105 can include one or more electrodes for monitoring cardiac electrical activity.

[0088] The electronic device 10 can include a user input unit 18 which may be positioned on, or coupled to, the housing 105 of the electronic device 10. In some examples, the user input unit 18 may be in the shape of a square, rectangular, circle, and/or any other geometric and/or irregular shape. The user input unit 18 may be generally curved and follow a circular curvature of the housing 105 as depicted in FIGS. 1A-1F. In some examples, a user input unit 18 may be fixed to the housing 105 such that user input unit 18 does not rotate, slide, or otherwise move relative to the housing 105. The user input unit 18 protrudes from an exterior surface of the housing, protruding from a cavity along an exterior surface of the housing, and/or the like. The user input unit 18 is contiguously integrated with the housing 105, or exterior surface thereof such that the outer surfaces of the user input unit 18 and housing 105 form a single unitary surface. The user input unit 18 can comprise an electrically conductive material such as metal. The user input unit 18 can comprise a non-conductive material such as glass or plastic and which may be responsive to changes in capacitance. In some implementations, the user input unit 18 can comprise a physical vapor deposition (PVD) coating layer. In some implementations, electronic device 10 can include a plurality of user input units 18 (e.g., two, three, four, five, and/or more).

[0089] In some examples, the user input unit 18 may be located on a right side of the housing 105 between straps 30. Typically, a user input unit 18 may be placed on the right side of a housing 105 as viewed from the display screen 12, as users may generally wear a watch on their left wrist. In this configuration, a user may use a finger on their right hand to operate the user input unit 18. Additionally and/or alternatively, the user input unit 18 may be positioned at another location on the housing 105 and/or the electronic device 10. In some examples, one user input unit 18 may be

located on the left side of the housing, between straps **30**, while one or more user input units **18** are positioned at other locations (e.g., the face, the bottom, a second user input unit **18** on a same side, a second user input unit **18** on an opposite side, and/or the like). Optionally and/or alternatively, the user input unit **18** may include one or more of an actuator, a button, a switch and/or the like, in combination and/or in addition to a user input unit **18**.

[0090] As depicted in FIG. **1B**, electronic device **10** can include an actuator **101**. The actuator **101** can include one or more physical components. For example, the actuator **101** can be a switch, a lever, a button, a dial, a knob, a rocker, a toggle, or the like. The actuator **101** can be a slideable switch. The actuator **101** can include one or more electrical components. For example, the actuator **101** can be a capacitive touch screen. In some implementations, the actuator **101** can be a button displayed on a touch screen, a slider displayed on a touch screen, or the like.

[0091] In some implementations, the actuator **101** can include a camera configured to capture images and a hardware processor configured to perform one or more image processing techniques such as facial recognition. In some implementations, the actuator **101** can include a microphone configured to capture audio input and a hardware processor configured to perform one or more audio processing techniques such as voice recognition.

[0092] The actuator **101** can transition between states such as a first state and second state. In some implementations, the states represent a physical state (for example, switch is in one position or another position). In some implementations, the states represent an electrical state (for example, change in electrical capacitance, resistance, or the like). The actuator **101** can be configured to actuate (for example, transition between states) in response to a physical input, such as a motion to slide a switch, depress a button, or the like. The actuator **101** can be configured to actuate (for example, transition between states) in response to an electrical input, such as a change in capacitance, voice recognition, facial recognition, or the like.

[0093] The actuator **101** can be located on a housing **105** of the electronic device **10**. The actuator **101** can be adjacent to the display screen **12**. In some implementations, the actuator **101** can be included on the display screen **12**, such as a portion of the display screen **12**, for example, in implementations where the actuator **101** is a capacitive touchscreen or portion thereof.

[0094] A user can actuate the actuator **101** to cause the electronic device **10** to transition between a privacy mode and non-privacy mode. For example, the actuator **101**, when in a first state, can cause the electronic device **10** to enter a privacy mode, and the actuator **101**, when in a second state, can cause the electronic device **10** to enter a non-privacy mode. The electronic device **10**, or components thereof, can operate differently when in the privacy mode than when in the non-privacy mode. For example, one or more components of the electronic device **10**, such as a communication component, may not operate during a privacy mode. As another example, a hardware processor of the electronic device **10** can handle data, such as sensor data, differently during a privacy mode than during a non-privacy mode. The electronic device **10** can operate normally during a non-privacy mode.

[0095] In some implementations, the actuator **101** can cause the electronic device **10** to only transition between the privacy mode and non-privacy mode. For example, the actuator **101** can be dedicated to transitioning the electronic device **10** between privacy and non-privacy modes and may not serve any other purpose. Advantageously, an actuator **101** dedicated to only causing the electronic device **10** to transition between privacy and non-privacy states can provide an improved user experience for transitioning the electronic device between privacy and non-privacy modes by providing a simple and easy-to-understand process that does not involve determining which operations actuating the actuator **101** will affect, such as in implementations where the actuator **101** can affect other operations of the electronic device in addition to transitioning between privacy and non-privacy modes. In some implementations, the actuator **101** can cause to electronic device **10** perform other operations in addition to transitioning between privacy and non-privacy modes. For example, in some implementations, actuating the actuator **101** can also cause the electronic device

to power on/off, can turn the display screen **12** on/off, or the like.

[0096] In some implementations, the actuator **101** can be a single component. In some implementations, the actuator **101** can be the only component necessary to transition the electronic device **10** between privacy and non-privacy modes. For example, a user may not need to perform any other operation, other than actuating the actuator **101**, to transition the electronic device **10** between privacy and non-privacy modes. Advantageously, the ability to transition the electronic device **10** between privacy and non-privacy states by only actuating the actuator **101** can provide an improved user experience for transitioning the electronic device between privacy and non-privacy modes by providing a simple and easy-to-understand process that does not involve multiple operations. For example, the privacy switch does not require actuating multiple actuators simultaneously or sequentially. In some implementations, more than one operation may be required to transition the electronic device **10** between privacy and non-privacy modes. This can include actuating more than one actuator.

[0097] Advantageously, a user may be able to easily toggle the electronic device **10** between privacy modes and non-privacy modes by actuating the actuator **101**.

[0098] As depicted in FIG. 1C, a bottom side of a wearable electronic device **10** can include a sensor assembly **107** which can include emitters **104**, detectors **106**, and/or electrodes **123**. The electrode(s) **123** can be configured to contact the skin of a user of the electronic device **10**. The electrodes **123** can be configured to measure electrical activity. The electrode(s) **123** can obtain data related to the cardiac activity of a user of the electronic device **10**, such as ECG data. The emitter(s) **104** can include one or more light emitting diodes (LEDs). The emitter(s) **104** can emit light of various wavelengths which can penetrate into a tissue of the user of the electronic device **10**. The detector(s) **106** can detect light emitted by the emitter(s) **104** and attenuated by the tissue of a wearer. The attenuation of light can be via transreflectance by the user's body tissue, for example, by the pulsatile arterial blood flowing through the capillaries (and optionally also the arteries) within a tissue site where the electronic device **10** is worn (for example, the wrist). The detector(s) **106** can generate one or more signals based at least in part on the light detected that was emitted by the emitter(s) **104**. The detector(s) **106** can generate data relating to blood oxygen saturation of a user of the electronic device **10**. The detector(s) **106** can generate data relating to spectroscopy.

[0099] The wearable electronic device **10** can measure an indication of the wearer's physiological parameters, which can include, for example, pulse rate, respiration rate, oxygen saturation (SpO₂), Pleth Variability Index (PVI), Perfusion Index (PI), Respiration from the pleth (RRp), hydration, glucose, blood pressure, and/or other parameters. The wearable electronic device **10** can calculate a wellness index based on more than one individual physiological parameter measured by the wearable electronic device **10** and/or received by the wearable electronic device **10**. The wearable electronic device **10** can perform intermittent and/or continuous monitoring of measured parameters. The sensors can additionally and/or alternatively perform a spot check of the measured parameters, for example, upon request by the wearer.

[0100] A strap **30** can be stretchable and evenly distribute the pressure of the electronic device **10** around the wrist so as to provide better contact between sensor assembly **107** and the wrist while not compromising the comfort of the wearer and/or reducing the blood flow across the wrist in a way that reduces the accuracy of the measurement by sensor assembly **107**. In some examples, the strap **30** can include a rubber base. The rubber base can be molded through a plurality of metal loops arranged along a length of strap **30** to form the strap **30**.

[0101] As depicted in FIG. 1D, the actuator **101** can be located on a housing **105** of the electronic device **10**. The sensor(s) of the electronic device **10**, such as the electrode(s) **123**, the emitter(s) **104**, and/or the detector(s) **106**, can be located on a housing **105** of the electronic device **10**. The actuator **101** can be located on a different portion of the electronic device **10** housing **105** than one or more of the sensors. The actuator **101** may not be in physical contact with one or more of the sensors of the electronic device **10**. In some implementations, the actuator **101** can be located on a

portion of the electronic device **10** housing **105** that is accessible to a user to actuate the actuator **101**. In some implementations, one or more of the sensors of the electronic device **10** can be located on a portion of the electronic device **10** housing **105** that is not readily accessible to user. For example, a user may not be able to access the one or more sensors with their fingers. For example, the sensors can be located on an underside portion of the electronic device **10** such that when the electronic device **10** is worn by a user, the electronic device **10** covers the sensors against the user, such as against a wrist area of the user such that the user may not be able to readily access the sensors with their fingers. Advantageously, a user can be able to easily actuate the actuator **101** without interfering with or disrupting the sensors, such as data collection of the sensors, because the actuator **101** and sensors are located on different portions of the electronic device **10** housing, for example. For example, the sensors can continue to operate when a user actuates the actuator **101** between states. In some implementations, the actuator **101** may not cover or block one or more of the sensors when the actuator is in any of the actuator states.

[0102] In some implementations, the actuator **101** can be located on a same portion of electronic device **10** housing **105** as some sensors and a different portion of the electronic device **10** housing **105** than other sensors. In some implementations, some sensors can be located on a different portion of the electronic device **10** housing **105** than other sensors

[0103] As shown in FIG. **1F**, for example, the user input unit **18** can have a length **L1** extending along the housing **105** (e.g., between the straps **30**). The length **L1** of the user input unit **18** can be between 1.5 cm and 3.0 cm, between 1.75 cm and 2.75 cm, between 2.0 cm and 2.5 cm, or about 2.25 cm. The length **L1** of the user input unit **18** can be between 25% and 100% the diameter **D1** of the display screen **12**, between 25% and 75% of **D1**, between 25% and 50% of **D1**, between 50% and 100% of **D1**, between 50% and 75% of **D1**, or any other ratio therebetween. In some implementations, the length **L1** of the user input unit **18** can be greater than of **D1** such as if the user input unit **18** wraps around the circumference of the display screen **12**. The user input unit **18** can have a height **H1** extending from the top from the top of the housing **105** to the bottom of the housing, with respect to the page of FIG. **1F**. The height **H1** of the user input unit **18** can be between 0.25 cm and 1.0 cm, between 0.25 cm and 0.75 cm, between 0.35 cm and 0.65 cm, between 0.4 cm and 0.6 cm, or about 0.5 cm. The height **H1** and/or length **L1** of the housing can be uniform such that a profile of the user input unit is rectangular from the view shown in FIG. **1F**. FIG. **1F** may be drawn to scale.

[0104] Distance **S1** represents a distance between user input unit **18** and a plane in which display screen **12** lies. In this case, the display screen **12** is represented as being below the top part of housing **105**. In some cases, display screen **12** may be flush with the top part of housing **105**. Thus, the distance **S1** may vary depending on the implementation. As represented by distance **S1**, user input unit **18** is out of the plane in which the display screen **12** lies such that the plane in which display screen **12** lies does not intersect user input unit **18**. User input unit **18** is beneath the display screen **12** such that user input unit **18** is between the plane of the display screen **12** and the user's wrist when the electronic device **10** is worn by the user.

[0105] FIG. **2** is a schematic block diagram illustrating an example implementation of an electronic device **200** in communication with one or more devices remote to the electronic device **200** via a network **204**. Electronic device **200** can be implemented as any of the other example electronic devices shown and/or described herein. Electronic device **200** can communicate with one or more servers **203** via network **204**. The network **204** can include one or more communications networks. The network **204** can include a plurality of computing devices configured to communicate with one another. The network **204** can include the Internet. The network **204** can include any combination of a body area network (e.g., implementing human body communication with capacitive coupling via the tissue of a user's body), a local area network ("LAN") and/or a wide area network ("WAN"), or the like. Accordingly, various computing devices can communicate with one another directly or indirectly via any appropriate communications links and/or networks, such as network

204 (e.g., one or more communications links, one or more computer networks, one or more wired or wireless connections, the Internet, any combination of the foregoing, and/or the like). The electronic device **200** can, via the network **204**, communicate data to the server **203** and/or receive data from the server **203**, such as sensor data which can include physiological data.

[0106] In some implementations, one or more aspects of electronic device **200** can be open (e.g., open source and/or including open architecture) to allow third party access to aspects of the electronic device **200** such as physiological data or other sensor data. Third party applications can be installed on the electronic device **200** such as from the server **203**. In some cases, third party applications can access data on the electronic device **200** such as physiological data from sensors on the electronic device **200**.

[0107] The server **203** can comprise one or more computing devices including one or more hardware processors. The server **203** can comprise program instructions configured to cause the server **203** to perform one or more operations when executed by the hardware processors. The server **203** can include, and/or have access to (e.g., be in communication with and/or host) a storage device, database, or system which can include any computer readable storage medium and/or device (or collection of data storage mediums and/or devices), including, but not limited to, one or more memory devices that store data, including without limitation, dynamic and/or static random-access memory (RAM), programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), optical disks (e.g., CD-ROM, DVD-ROM, etc.), magnetic disks (e.g., hard disks, floppy disks, etc.), memory circuits (e.g., solid state drives, random-access memory (RAM), etc.), and/or the like. In some implementations, the server **203** can include and/or be in communication with a hosted storage environment that includes a collection of physical data storage devices that may be remotely accessible and may be rapidly provisioned as needed (commonly referred to as “cloud” storage). Data stored in and/or accessible by the server **203** can include sensor data, such as physiological data, including historical physiological data previously obtained by one or more sensors of the electronic device **200**. In some implementations, the server **203** can comprise and/or be in communication with an electronic medical records (EMR). An EMR can comprise a propriety EMR. An EMR can comprise an EMR associated with a hospital. An EMR can store data including medical records.

[0108] Electronic device **200** can communicate with one or more computing devices **201** via the network **204**. Computing devices **201** can include one or more of a patient monitor (for example, a bedside monitor), a patient monitoring and connectivity hub, a handheld patient monitoring device, a wearable patient monitoring device, a mobile communication device (for example, a smartphone), a smart watch, a wearable device, an earbud, a computer (which can be a laptop or a desktop), a tablet, a nurses' station system, physiological sensors, glucose monitors, a home monitoring system, or the like. In some implementations, the computing device(s) **201** can include a same or similar device as the electronic device **200**. The electronic device **200** can, via the network **204**, communicate data to the computing device(s) **201** and/or receive data from the computing device(s) **201**, such as sensor data which can include physiological data. In some implementations, the electronic device **200** can communicate with the computing device(s) **201** directly such as via a wireless and/or wired communication protocol.

[0109] The electronic device **200** can communicate directly with the computing device(s) **201** and/or server(s) **203** via a wireless communication protocol including one or more of WiFi, Bluetooth, near field communication (NFC), radio frequency identification (RFID), cellular telephony, Zigbee, Z-wave, and/or the like.

[0110] In some implementations, the electronic device **200** can communicate with the server(s) and/or computing devices **201** during a non-privacy mode. In some implementations, the electronic device **200** may not communicate with the server(s) and/or computing devices **201** during a privacy mode. For example, the electronic device **200** may not be capable of communicating with the

server(s) and/or computing devices **201** during a privacy mode because a communication component of the electronic device **200** may be powered off.

[0111] As illustrated in FIG. 3, the electronic device **10** can include a housing **105** coupled to a strap connection **22** and a strap **30**. The housing **105** may include a sensor assembly **107** having a printed circuit board **116** (referred to herein as “PCB **116**”), a connector **118** to a computing device (referred to herein as “connector **118**”), and/or ECG electrodes **124**, **125**. The PCB **116** may include emitters **104**, detectors **106**, a sensor processor **108**, thermistor(s) **110**, a gyroscope **112**, and/or an accelerometer **114**. The housing **105** may further include a display screen **12**, a device processor **14**, a power source **16**, a user input unit **18**, and a strain gauge **20**. The electronic device **10** can further include strap **30** and strap connection **22**.

[0112] The one or more components of the sensor assembly **107**, the PCB **116** and/or the wearable electronic device **10** can be in electrical communication with one or more components. As an example and not meant to be limiting, the power source **16** may provide power for components of the PCB **116**, the device processor **14**, and the display screen **12**. The PCB **116** may be in electrical communication with the display screen **12**, the user input unit **18**, the device processor **14** and/or the like.

[0113] A display screen **12** can be positioned at a top side of the device housing **105**. The display screen **12** can provide, among other indications, an indication of time and date. The display screen **12** can further include a display layout (for example, the default display layout) indicating the wearer's SpO2 measurement, pulse rate (PR) measurement, respiration rate (RR) measurement, hydration status (H2O), and/or the like. The format of the display layout is not limiting. For example, some measurements, such as the SpO2 measurement and/or PR measurements, can be displayed as numerical values. As another example, some measurements, such as the RR measurements and hydration status, can be displayed as a sliding scale. As an illustrative example, the display screen **12** can indicate a hydration status having three levels from low (L) to high (H). A respiration rate can be displayed as ranging from 5 bpm to 25 bpm. The display screen **12** may allow the wearer to transition between user interfaces similar to and/or the same as described with reference to the user input unit **18**. For example, the display screen **12** may be a touch screen allowing a user to view individual display layouts for each measurement or a group of measurements, transition and/or display additional measurements within a user interface, and/or the like, by one or more of and/or a combination of a tap, a press, a slide, a touch, a pinch, a swipe, and/or the like on the display screen **12**. The display screen **12** may provide one or more measurements as described herein. Each of the measurements can be displayed constantly, at certain intervals, and/or upon receiving instructions for display (for example, by the wearer tapping on the display screen **12**, sliding the user input unit **18**, and/or pressing a button on the electronic device **10**).

[0114] The display screen **12** can display measurements with different or the same frequencies. Time and certain physiological parameters (for example, SpO2 and pulse rate) can be immediately and/or intermittently available, and/or continuously measured (for example, at least every 5 to 10 measurements per minute or more) and the displayed values constantly updated. Optionally, the display screen **12** can further show a trend line for some parameters, such as SpO2 and pulse rate. In one example, the display of the wearable electronic device **10** can be configured to display only time, SpO2, and pulse rate.

[0115] In some examples, the display screen **12** can use e-ink or ULP (ultra-low power screen) technology, which draws little amount of current for displaying information. The display screen **12** may automatically adjust the brightness, being brighter when outdoors and dimmer when indoors to further prolong battery life.

[0116] A device processor **14** can be a digital/analog chip or other processor(s), such as a digital watch processor or a smartwatch processor. The electronic device **10** may include nonvolatile memory to store the critical patient information and/or computer-executable instructions that may

be executed by the device processor **14**. The device processor **14** can execute one or more functions of the electronic device **10** as described herein. For example, the device processor **14** can generate an instruction of the display to continue displaying critical patient information (for example, the patient's name, date of admission, etc.) after the power source **16** has been depleted. In other examples, the device processor **14** can process a reading from a strain gauge **20** and transmit an instruction to display the processed reading of the pressure asserted by the electronic device **10** on the wearer to the display screen **12**. Further, the device processor **14** may, in response to determining a change in state of the user input unit **18** (e.g., via a single tap, a double tap, a short tap, a long tap, a slide, a press, and/or the like), may generate user interface data and display user interface data via display screen **12**. In some examples, the processor **14** may, in response to a change in state of the user input unit **18**, scroll through one or more user interfaces which can include various indicia of measurements and/or display layouts of the display screen **12**.

[0117] Power source **16** can include a battery for powering one or more components of the electronic device **10** such as the device processor **14**, the display screen **12**, and/or the sensor assembly **107**. The battery **16** can last at least 10 hours, or at least 12 hours, or at least 14 hours, or at least about 16 hours after each charge, with continuous measurements and/or displaying of certain physiological parameters, such as SpO2 and pulse rate. In some examples, the power source **16** can send an indication to the display screen **12**, after the power source **16** has been depleted, even if other features (for example, measuring physiological parameters using the sensor assembly **107**) may not be available when the power source **16** has been depleted. Additionally, when the electronic device **10** is used clinically, the display screen **12** can also continue displaying critical patient information (for example, the patient's name, date of admission, etc.) after the battery **16** has been depleted.

[0118] As described above, the electronic device **10** can include a user input unit **18**. The user input unit **18** may sense an input by a user, such as one or more of and/or a combination of: a tap, a press, a slide, a touch, a pinch, a swipe, and/or the like. The user input unit **18** may include one or more and/or a combination of different types of user input unit **18** such as, but not limited to capacitive, resistive, infrared, surface capacitive, and/or projected capacitive touch (PCAP) devices.

[0119] A capacitive user input unit **18** may detect a user's capacitance by registering changes in capacitance when, for example, a finger of a user and/or a stylus interacts with the user input unit **18**. A resistive user input unit **18** may include multiple layers (e.g., two flexible layer sheets coated with a resistive material and/or the like) where pressing the screen causes the layers to touch, generating a signal. An infrared user input unit **18** may include an array of infrared LEDs and photodetectors around the perimeter of a user input unit **18**, to detect an interruption in infrared light beams when touched. A surface capacitive user input unit **18** may function similarly to a capacitive user input unit **18**, however the surface capacitive user input unit **18** may operate with a single of electrodes placed on a glass surface of the user input unit **18**, enabling better durability and/or quality. Additionally, a user input unit **18** may be a PCAP device, where a grid of electrodes detect touch, allowing for multi-touch functionality (e.g., a pinch, two simultaneous presses, and/or the like) and higher sensitivity than one or more other types of user input units **18**.

[0120] User input unit **18** may be electrically coupled to the device processor **14**, sensor processor **108**, display screen **12**, and/or the like. The user input unit **18** may receive an input by a user in the form of, but not limited to, a tap, a press, a slide, a touch, a pinch, a swipe, and/or the like, on the user input unit **18**. For example, and as further discussed with reference to FIGS. 4A-4C, a user input unit **18** may cause a display screen **12** to scroll through one or more display layout previews, transition display layouts, manipulate one or more characteristics and/or parameters associated with a display layout, and/or the like. In some examples, device processor **14** may monitor a state of the user input unit **18** and, in response to a determined state of the user input unit **18**, generate signals to cause a display unit **12** to update its user interfaces as described herein. Additionally and/or alternatively, the user input unit **18** may be used by the device processor **14** to change and/or

control another feature other than a display. For example, the user input unit **18** may receive an input by a user resulting in an adjustment of a volume output level from the electronic device **10**, a brightness level of the display unit **12**, a zoom level of user interfaces displayed within display unit **12**, an adjustment to a tactile feedback setting (e.g., a vibration and/or the like), or another non-display function as described herein. In some implementations, the user input unit **18** may receive a fingerprint of a user to identify the user (and to authorize the user to use the electronic device **10** and/or perform operations with the electronic device **10**).

[0121] The electronic device **10** can include an optional strain gauge **20**. The strain gauge **20** can measure a pressure of the electronic device **10** on the wearer. Readings from the strain gauge **20** can be communicated to the device processor **14**, which can process the readings and output an indication of the pressure asserted by the electronic device **10** on the wearer to be displayed on the display screen **12**. In one example, the display screen **12** can display a green light when the pressure on the wearer is suitable for using the sensor assembly **107** and display a red or other colored light for a pressure that is too high or too low than the desired pressure or pressure range. In some examples, once the strain gauge **20** indicates that the desired pressure or pressure range has been achieved, the sensor processor **108** may activate one or more measurements as described herein (e.g., PR, SpO₂, and/or the like). Optionally, the device processor **14** can also deactivate the sensor assembly **107**, and/or any other sensors on or attached to the electronic device **10**, in response to not detecting any readings from the strain gauge **20**, indicating that the electronic device **10** is not worn on the wearer.

[0122] The strap(s) **30** can be connected to the electronic device **10** using any suitable strap connections **22**. For example, the strap connections **22** can be compatible with third party watch bands, wearable blood pressure monitors, and/or the like.

[0123] The sensor assembly **107** of the wearable electronic device **10** can include a sensor or sensor processor **108** (which can include a memory, other electronics, and/or the like). The sensor processor **108** can process signals from one or more of the sensors in sensor assembly **107** (or optionally other sensors in communication with the electronic device **10**) to determine a plurality of physiological parameters. Processing of raw sensor data of the sensors in communication (via a wired and/or wireless connection) with the sensor or sensor processor **108** may be performed by the sensor or sensor processor **108**. For example, the sensor processor **108** can be configured to drive the emitters **104** to emit light of different wavelengths and/or to process signals of attenuated light after absorption by the body tissue of the wearer from the detectors **106**.

[0124] The sensor processor **108** can determine and output for display on the display screen **12**, one or more physiological parameters based on the detected signals. Optionally, the device processor **14** can receive signals from detectors **106** (for example, preprocessed signals) and determine and output physiological parameters for display.

[0125] The sensor assembly **107** can include more than one group or cluster of optical emitters **104** (such as LEDs) and more than one group of photodetectors **106** (also referred to as “detectors **106**”). Each group of emitters **104** can be configured to emit four (or three) different wavelengths based on. Emitters **104** can be driven by the processor **108**, to emit light of four (and/or three) different wavelengths. Detectors **106** may transmit a received reflection of one or more light signals to the processor **108**, to determine physiological parameters.

[0126] The emitters **341** of the sensor assembly **340** can be configured to emit a plurality of (for example, three, four, five, or more) wavelengths. The emitters **341** can be configured to emit light of a first wavelength providing an intensity signal that can act as a reference signal. The first wavelength can be more absorbent by the human body than light of other wavelengths emitted by the emitters **341**. The reference signal can be used by the sensor assembly processor **348** to extract information from the other signals, for example, information relevant to and/or indicative of the pulsing rate, harmonics, or otherwise. The sensor assembly processor **348** can focus the analysis on the extracted information for calculating the physiological parameters of the wearer. The first

wavelength can be between about 500 nm and about 540 nm, between about 505 nm and about 535 nm, between about 510 nm and about 530 nm, between about 515 nm and about 525 nm, or about 520 nm, or any value or range between any of these values or ranges or any value or range bounded by any combination of these values, although values or ranges outside these values or ranges can be used in some cases. The light providing the reference signal can have a green color or alternatively an orange color or yellow color.

[0127] The emitters **341** can be configured to emit light of a second wavelength having a red or orange color. The second wavelength can be between about 600 nm and about 640 nm, between about 605 nm and about 635 nm, between about 610 nm and about 630 nm, between about 615 nm and about 625 nm, or about 620 nm, or any value or range between any of these values or ranges or any value or range bounded by any combination of these values, although values or ranges outside these values or ranges can be used in some cases. Light of the second wavelength can be more sensitive to changes in SpO₂. The second wavelength can be closer to 620 nm (for example, about 625 nm or 620 nm), which results in greater absorption by the body tissue of the wearer, and therefore a stronger signal and/or a steeper curve in the signal, than a wavelength that is closer to 660 nm. The sensor assembly processor **348** can extract information such as the pleth waveform from signals of the second wavelength.

[0128] The emitters **341** can be configured to emit light of a third wavelength between about 640 nm and about 680 nm, between about 645 nm and about 675 nm, between about 650 nm and about 670 nm, between about 655 nm and about 665 nm, or about 660 nm, or any value or range between any of these values or ranges or any value or range bounded by any combination of these values, although values or ranges outside these values or ranges can be used in some cases.

[0129] The emitters **341** can be configured to emit light of a fourth wavelength between about 900 nm and about 910 nm, between about 900 nm and about 905 nm, between about 905 nm and about 910 nm, or about 905 nm, or about 907 nm, or any value or range between any of these values or ranges or any value or range bounded by any combination of these values, although values or ranges outside these values or ranges can be used in some cases. The fourth wavelength can be in the infrared range. The pulse oximeter processor can use the fourth wavelength as a normalizing wavelength when calculating ratios of the intensity signals of the other wavelengths, for example, a ratio of the intensity signals of the second wavelength (red) to the third wavelength (infrared).

[0130] Additionally or optionally, the emitters **341** can be configured to emit light having a fifth wavelength that is more sensitive to changes in water than the other emitted wavelengths. The fifth wavelength can be in the infrared range or between about 950 nm and about 990 nm, between about 955 nm and about 985 nm, between about 960 nm and about 980 nm, between about 965 nm and about 975 nm, or about 970 nm, or any value or range between any of these values or ranges or any value or range bounded by any combination of these values, although values or ranges outside these values or ranges can be used in some cases. The sensor assembly processor **348** can determine physiological parameters such as a hydration status of the wearer based at least in part on a comparison of the intensity signals of the fifth wavelength and a different wavelength detected by certain detectors **345**.

[0131] The sensor assembly **107** can include one or more thermistors **110** and/or other types of temperature sensors (e.g., RTD, thermocouple, and/or the like). The thermistor(s) **110** can be placed near one or more groups of emitters **104**. There can be at least one thermistor **110** near each group of emitters **104**. The thermistor(s) **110** can provide for wavelength correction of the light emitted by the emitters **104**. Optionally, the thermistor(s) **110** can additionally measure a temperature of the wearer of the electronic device **10**. Optionally there can be one or more thermistors **110** located at other places of sensor assembly **107**. In some examples, the emitters **104**, the thermistor(s) **110**, and/or the detectors **106** can be positioned on the PCB **116**.

[0132] The electronic device **10** can include a gyroscope **112**, an accelerometer **114**, and/or other inertial sensor. The gyroscope **112** and/or the accelerometer **114** can be in electrical communication

with the sensor processor **108**. The sensor processor **108** can determine motion information from signals from the gyroscope **112** and/or the accelerometer **114**. The motion information can provide a noise reference for analysis of the plethysmograph information and/or other signal processing (for example, processing of ECG signals) performed by the sensor processor **108**.

[0133] The sensor assembly **107** can include a connector **118** for connecting to a computing device such as a sensor, which can be a plethysmograph sensor or other suitable sensors. The connector **118** can be oriented such that the second sensor can extend from a housing of the electronic device **10** with reduced and/or no impingement of the tissue at the device/tissue interface, resulting in less or no effect of the connector **118** on the blood flow through the device measurement site.

[0134] Optionally, the electronic device **10** can include ECG electrodes **124**, **125** configured to make contact with the wearer's skin. One or more ECG electrodes **124** may be located on sensor assembly **107**. One or more ECG electrodes **125** may be located elsewhere on the electronic device **10** (for example, an ECG electrode **125** can form a part of the housing **105** of the wearable electronic device **10**). The ECG electrodes **124**, **125** can be in electrical communication with the sensor processor **108** via an ECG connector. The sensor assembly **107** can optionally include a plurality of ECG electrodes **124**, **125**. Some of the ECG electrodes **125** can be located away from the sensor assembly **107** and some of the ECG electrodes **124** can be located on the sensor assembly **107**.

[0135] The ECG electrodes **124**, **125** can include a negative electrode, a positive electrode, and a reference electrode. Electrodes **124** located on sensor assembly **107** can act as a reference electrode and a negative (or positive) electrode respectively. In some examples, a portion of the housing **105** that surrounds the display screen **12** can function as another ECG electrode **125**. In some examples, an electrically insulating material can separate the ECG electrode **125** from the remainder of the housing **105** so that an electrical current between the ECG electrode **125** and the ECG electrodes **124** would travel through the wearer's body. When the wearer wants to make a measurement using the ECG sensor that includes the ECG electrodes **124**, **125**, the wearer can press on or touch the electrode **125** using the wearer's finger or another part of the wearer's body such that the wearer's skin makes contact with the electrode **125**.

[0136] FIGS. **4A-4C** depict example user interfaces **400A-400C** respectively, from a display screen **12** of electronic device **10**. User interfaces **400A-400C** can occupy an entirety of display screen **12** in some cases or can occupy less than an entirety of display screen **12** in some cases. In other words, the area of the user interfaces **400A-400C** can be less than or equal to the area of the display screen **12**, depending on the implementation. The example user interfaces **400A-400C** illustrate various example functionality of the electronic device **10** as described, for example, in reference to an input from a user on a user input unit **18**. Advantageously, the electronic device **10** can enable a user to quickly scroll and/or manipulate user interfaces displayed via a display screen **12** in accordance with one or more inputs by the user on the user input unit **18**. FIGS. **4A-4C** illustrate an example of using the user input unit **18** to transition between user interfaces **400A-400C** to change display layout previews (e.g., **406a-406b**) displayed via display screen **12**. In some implementations, the user input unit **18** can cause the display screen **12** to transition between other user interfaces such as user interfaces comprising various formats of indicia of physiological parameters, various watch face layouts, various physiological parameter layouts, etc. Accordingly, a user may scroll through and/or select various user interfaces with user input unit **18**. In some implementations, the user input unit **18** can cause the display screen **12** to transition between various color schemes associated with user interfaces. For example, a user may be able to transition through various color scheme options with user input unit **18** and select a color scheme with user input unit **18**. In some implementations, the user input unit **18** can cause the display screen **12** to change brightness level.

[0137] FIG. **4A** shows the length **L1** and width **W1** of the user input unit **18** and the diameter **D1** of the display screen **12** (which in some cases may also be equal to the diameter of the user interface

400A). User input unit **18** may have a width **W1** such that user input unit **18** protrudes out from the housing **105**. As shown here, width **W1** varies along the length **L1** such that width **W1** is thickest at the center of the user input unit **18**. In some implementations, width **W1** is uniform along the length **L1**. The width **W1**, such as at the maximum, can be between 0.05 cm and 1.0 cm, between 0.10 cm and 0.75 cm, between 0.10 cm and 0.5 cm, between 0.10 cm and 0.25 cm, between 0.10 cm and 0.20 cm, or between 0.15 cm and 0.25 cm. The width **W1** can be less than the height **H1**, such as between about 20% and 50% of **H1**, or any value therebetween. The width **W1** of user input unit **18** can provide structural variation from housing **105** to help a user tactilely distinguish between the user input unit **18** and the housing **105**.

[0138] In this example, **D1** represents a diameter because the display is circular **12**. In some implementations, **D1** may represent a distance between the top of the display screen **12** to the bottom of the display screen **12** such as if the display were rectangular. As discussed in FIG. **1F**, **L1** can be between about 25% and about 100% of **D1**, between about 25% and 75% of **D1**, between about 50% and about 100% of **D1**, between about 30% and about 70% of **D1**, between about 40% and about 60% of **D1**, or any value therebetween. In some implementations, **L1** may be between about 10% and about 50% the circumference of the display screen **12**, between about 10% and about 25% the circumference of the display screen **12**, between about 5% and about 15% the circumference of the display screen **12**, between about 25% and about 50% the circumference of the display screen **12**, etc. Advantageously, because the size and/or shape of the user input unit **18** may generally correspond with the size and/or shape of the display screen **12**, user interaction with the user input unit **12** may more closely correspond with resulting actions on the display screen **12**. FIG. **4A** may be drawn to scale.

[0139] FIG. **4A** depicts an example user interface **400A** showing display layout preview **406a** for user selection. A user can transition through various display layout previews (e.g., **406a**, **406b**) to select which display layout they would like. The various display layout previews **406a**, **406b** each correspond with, and are smaller versions of, respect display layouts that govern how elements of a user interface, such as indicia of physiological data, are arranged within the user interface. Path **420** is shown as superimposed on the electronic device **10** and may not be displayed within user interface **400A** and/or a physical component of electronic device **10**. Path **420** governs how the display layout preview **406a** moves within user interface **400A**. In this example, path **420** is an arc of a circle with center **421**. In this example, center **421** is positioned on electronic device **10**, within display screen **12**, and on the edge of user interface **400A**. In some implementations, center **421** can be positioned entirely outside of user interface **400A**, display screen **12**, and/or electronic device **10**. In some implementations, center **421** can be positioned entirely within user interface **400A**. In this example, the diameter of path **420** is equal, or substantially equal to, the diameter of the user interface **400A**. In some implementations, the diameter of path **420** can be the same size as diameter **D1** of the display screen **12** (which in some cases may be the same size as the diameter of user interface **400A**). In some implementations, the diameter of path **420** may be less than the diameter of user interface **400A**.

[0140] Path **420** can pass through the center of display screen **12**. Thus, path center **421** is offset from the center of the display screen **12**. In this example, path center **421** is positioned to the left of the center of the display screen **12** such that the center of the display screen **12** is positioned between path center **421** and user input unit **18**. Path center **421** can be positioned at any angular position within the 360 degrees surrounding the center of the display screen **12**. For example, path **420** can at least partially surround user input unit **18** and path center **421** can be positioned between the center of the display screen **12** and the user input unit **18**.

[0141] Display layout preview **406a** has point **422** which may be located at the center of display layout preview **406a** and/or the center of display screen **12**. Point **422** lies on path **420** and may be constrained to reside on path **420** as display layout preview **406a** moves within user interface **400A**. Accordingly, display layout preview **406a** (or center thereof) may travel along a path **420**

within user interface **400A**.

[0142] User interface **400A** includes indicator **413**. As illustrated, the indicator **413** may provide a user with a reference and/or location of a display layout preview **406a** on the display screen **12**. Indicator **413** comprises a plurality of circles including a larger circle in between smaller circles above and below the larger circle. Indicator **413** is positioned within the display screen **12** on a side proximate the user input unit **18**. In some implementations, indicator **413** can be positioned within the display screen **12** across from the user input unit **18**. Indicator **413** has the same general shape as the user input unit **18** (e.g., a curve). As depicted in the example user interface **400A**, the user is currently viewing the second of seven display layout previews (e.g., display layout preview **406a**), however, this is not meant to be limiting as there can be less and/or more display layout previews.

[0143] Display layout preview **406a** (and/or another display layout preview of the electronic device **10**) may include characteristics and/or parameters associated with one or more inputs and/or sensors of the electronic device **10**, such as oxygen saturation (SpO₂), pulse rate, a plethysmograph waveform, perfusion index (PI), pleth variability index (PVI), methemoglobin (MetHb), carboxyhemoglobin (CoHb), total hemoglobin (tHb), respiration rate, glucose, date and time, a step counter, and/or the like. A display layout preview **406a** (and/or any other display layout preview) may be configured by a device processor **14** and/or sensor processor **108**.

[0144] As depicted in example user interface **400B** of FIG. **4B**, display screen **12** may transition between user interfaces as indicated by arrow **410**, from display layout preview **406a** to display layout preview **406b**. The display screen **12** may transition in response to actuation of user input unit **18**. For example, sensor processor **108** can generate a signal (responsive to actuation of user input unit **18**) to update display screen **12** with various user interfaces. Actuation of user input unit **18** can include a tap, a press, a touch, (e.g., a single tap, a double tap, a short tap, a long tap, and/or the like) which may be used in some implementations to make selections. Actuation of user input unit **18** can include a slide, a pinch, a swipe, along arrows **402**, **404** which may be used in some implementations to transition through various options (e.g., various UI options).

[0145] In the example of FIG. **4B**, the user has swiped along user input unit **18** in the direction of arrow **402**. Based on the user input (e.g., a swipe across the user input unit **18**), the device processor **14** and/or sensor processor **108** may determine a change in state of the user input unit **18**. Based on the change in state of the user input unit **18**, the processor **14** and/or **108** may cause display screen **12** to update user interfaces displayed thereon such as by generating user interface data for rendering and/or updated user interfaces. For example, the processor **14** and/or processor **108** may transmit a signal to the display screen **12**, to scroll from display layout preview **406a** to display layout preview **406b** as indicated by arrow **410**. (Note that arrow **410** is superimposed on the example user interfaces **400A-400C** and is shown for illustrative purposes only. Arrow **410** does not form part of the example user interface **400A-400C**). Additionally and/or optionally, indicator **413** may transition a portion of the user interface **400B** by enlarging a next circle in a sequence of circles and reducing the size of a current circle.

[0146] The direction in which display layout previews **406** move through display screen **12** may correspond to the direction in which a user slides along user input unit **18**. For example, in this case, a user sliding upward along user input unit **18** as shown by arrow **402** can cause display layout previews **406** to also move upward. Likewise, sliding downward along user input unit **18** as shown by arrow **402** can cause display layout previews **406** to move downward. In some cases the display layout previews **406** may move opposite the direction of user input on the user input unit **18**. For example, swiping downward on user input unit **18** can cause display layout previews **406** to move upward, and swiping upward can cause display layout previews **406** to move downward. In such an implementation, the path center **421** may be positioned between the center of the display screen **12** and the user input unit **18** such that the path **420** surrounds the user input unit **18**.

[0147] Movement along the user input unit **18** can result in movement of indicia on the display screen **12** as shown and/or described in FIG. **4B** where a user moves their finger along user input

unit **18** causing display layout previews **406a** and **406b** to move along display screen **12**. The ratio of user movement on user input unit **18** to movement of indicia on the display screen **12** can be 1:2, where if the user moves their finger certain distance along user input unit **18**, indicia on the display screen **12** moves twice as far as that distance. In some implementations, the ratio can be 1:4, 1:3, 1:2.5, 1:1.5, 1:1, 4:1, 3:1, 2.5:1, 2:1, 1.5:1, etc. The ratio can change based on the speed at which the user moves their finger along user input unit **18** with faster movement resulting in a higher output ratio, and vice versa. In some cases, the ratio can also be set by a user. If the ratio were 1:1 and the length **L1** of the user input unit **18** were about 50% the diameter **D1** of the display screen **12**, the user would advantageously only need to move their finger twice along the length **L1** of the user input unit **18** to move indicia the entire distance of the diameter **D1** of the display screen **12**. [0148] Electronic device **10** may be capable of displaying a plurality of unique display layout previews, including display layout previews **406a**, **406b**. In the examples shown in FIGS. **4A-4C**, there may be seven different display layout previews as indicated by indicator **413** showing that display layout preview **406a** is the 2nd of 7 options and that display layout preview **406b** is the 3rd of 7 options. Electronic device **10** may display less than all of the possible display layout previews simultaneously. For example, in FIG. **4B**, display screen **12** shows only two of the seven display layout previews simultaneously. In some implementations, electronic device **10** may display no more than two of the display layout previews simultaneously.

[0149] As depicted in example user interface **400C** of FIG. **4C**, display screen **12** indicates display layout preview **406b** in response to an input by a user via user input unit **18**. Indicator **413** transitions to indicate that the third of seven layouts is displayed. To show display layout preview **406a** (e.g., a previously displayed layout option), a user may swipe in an opposite direction along user input unit **18** and/or may a tap, a press, a slide, a touch, a pinch, a swipe, and/or the like, along the user input unit **18**. Additionally and/or alternatively, user input unit **18** may transmit a signal to a device processor **14**, sensor processor **108**, display screen **12**, and/or the like, based on an input from a stylus and/or another component.

[0150] A user can select display layout preview **406b** (or any of the others) as the option they would like to select for the corresponding display layout to govern the arrangement of elements, such as indicia of physiological data, within the display screen **12**. The user can make the selection via the user input unit **18** and/or the display screen **12**. For example, a user can touch on the display screen **12** and/or the user input unit **18** to select display layout preview **406b**. Processor **14** can determine a change in state on the display screen **12** and/or user input unit **18** responsive to the user's touch and can generate instructions in response to cause the display screen **12** to update based on the selection.

[0151] FIG. **4D** illustrates electronic device **10** with display screen **12** showing user interface **400D** with display layout **416**. Display layout **416** corresponds to display layout preview **406b** and is displayed within display screen **12** responsive to user selection of display layout preview **406b**. Display layout preview **406b** may be a smaller rendition of display layout **416**. Display layout preview **406b** provides a visualization of display layout **416** on a smaller scale of size. The display layout preview **406b** can be between 20% and 90% the size of display layout **416**, or between 50% and 90%, between 50% and 80%, between 50% and 70%, between 30% and 50%, between 40% and 50%, between 40% and 60%, or any value therebetween. Display layout **416** governs how user interface elements, such as indicia of physiological data, are arranged within user interface **400D**. Display layout **416** can occupy an entirety of user interface **400D** and/or display screen **12**. In some cases, display layout **416** may be used interchangeably with user interface **400D**.

[0152] FIG. **5** illustrates a front view of the wearable electronic device **10** with housing **105**, display screen **12**, and user input unit **18**. The user input unit **18** can comprise a plurality of zones, such as first zone **501**, second zone **502**, third zone **503**, and fourth zone **504**. Each of the zones **501-504** can be independently responsive to user input (e.g., touch) and can independently communicate with an internal processor. For example, a processor of the electronic device **10** can

register user input from zone **501** independently of registering user input from the other zones **502-504**. The user input unit **18** can have less than four zones, such as three zones, two zones, or one zone. The user input unit **18** can have more than four zones, such as five zones, six zones, seven zones, or more than seven zones.

[0153] A hardware processor of the electronic device **10** can monitor the states of the zones **501-504** to determine one or more characteristics of a user input, such as direction of a user input motion, speed of a user input motion, location along the user input unit **18** where a user touches, time that a user touches the user input unit **18** or its various zones, etc.

[0154] For example, if a user swipes their finger along the user input unit from bottom to top, starting at zone **504** and ending at zone **501**, the processor can determine that the user has swiped their finger in an upward direction and can control one or more operations accordingly, such as to transition user interfaces in an upward direction (illustrated in FIGS. **4A-4C**), or to increase a volume of a speaker output, or to increase a brightness of display screen **12**, etc. Thus, the processor can determine a direction in which the user has swiped based on determining an order in which the user interacts with the various zones **501-504**.

[0155] As another example, if a user sequentially touches more than one of the zones **501-504** (e.g., while swiping along user input unit **18** with their finger), the processor can determine a speed with which the user transitions between contacting the various zones to determine how fast the user is swiping along the user input unit **18** and can control one or more operations accordingly, such as to transition between user interfaces more rapidly or slowly for a faster or slower swipe, respectively or to transition through a greater or smaller number of user interfaces for a faster or slower swipe, respectively. The processor can also vary the speed at which it changes volume output or display screen **12** brightness based on swipe speed. Thus, the processor can determine the speed that a user swipes along user input unit **18** based on determining the amount of time between user interactions with the various zones **501-504**.

[0156] As another example, if a user touches a single zone, the processor can determine where on the user input unit **18** the user has touched and can control one or more operations based on the location of the touch, such as to increase volume output to a set amount based on the zone (e.g., 100% output volume if zone **501** is touched by itself or 0% output volume if zone **504** is touched by itself). Corresponding controls could also be implemented for selecting user interfaces to display via the display screen **12**, for selecting selectable components within user interfaces, or for controlling brightness of the display screen **12**.

[0157] The zone **501-504** may not be marked on the user input unit **18**. For example, a user may not be able to distinguish the various zones **501-504** based on touch or sight, etc. The user may be unaware of the existence of the zones **501-504**. In some implementations, the zones **501-504** may be demarcated on the user input unit **18** for a user to distinguish such as visually and/or tactilely. Zones that are adjacent may contact each other. A user can contact more than one zone at a time.

[0158] One or more of the zones **501-504** can be a same size as each other or may be a different size from each other. Implementing one more of the zones **501-504** with a different size can allow for varying degrees of control along the user input unit **18**. For example, a user may wish to implement control with a high degree of precision via a top portion of the user input unit **18** such that zones **501-502** can be smaller than zones **503-504** thus allowing for finer granularity of touch via zones **501-502**. Correspondingly, a user may wish to implement control with a lower degree of precision via a bottom portion of the user input unit **18** such that zones **503-504** can be larger than zones **501-502** thus allowing for larger ranges of motion to via zones **503-504** to implement certain operations.

[0159] FIG. **6A** is a perspective view of an example implementation of an electronic device **600A**. The electronic device **600A** can include an actuator **601A** and a display **612A**. The display **612A** can be configured to display data, including sensor data obtained by one or more sensors of the electronic device **600A**.

[0160] The actuator **601A** can be a slideable switch. The actuator **601A** can be configured to transition between states. For example, the actuator **601A** can slide between a first state and a second state. The actuator **601A** can cause the electronic device **600A** to transition between privacy and non-privacy modes of operation. For example, a user can actuate the actuator **601A** from one state to another to cause the electronic device to enter a privacy mode or a non-privacy mode.

[0161] The actuator **601A**, or portion thereof, can include shading or coloring. For example, a portion of the actuator **601A** can be colored red, green, black, or any other color, and can be viewable when the actuator **601A** is in a certain state. In the example implementation shown in FIG. **6A**, the actuator **601A** is in a certain state which can cause the electronic device **600A** to enter a privacy mode. A portion of the actuator **601A** can be visible and can be colored a certain color, such as green, black, red, etc., to indicate the electronic device **600A** is in the privacy mode.

[0162] In some implementations, the actuator **601A** can be configured to transition between two states which can correspond to a privacy mode and a non-privacy mode. In some implementations, the actuator **601A** can be configured to transition between more than two states. For example, **601A** can be configured to transition between three states which can correspond to a privacy mode, a first privacy mode wherein the sensors are powered on and continue to operate and one or more privacy components, such as a communication component, is powered off and does not operate, and a second privacy mode wherein one or more sensors and one or more privacy components are powered off and do not operate.

[0163] During a privacy mode, the display **612A** can be configured to display data such as physiological data obtained from one or more sensors. The display **612A** can be configured to display data that was generated and/or obtained during a privacy mode. Advantageously, a user of the electronic device **600A** can be able to continue to view data via the display **612A** during a privacy mode, while the data is still protected by the electronic device **600A**. In some implementations, the display **612A** may not display data during a privacy mode, for example, because the display **612A** can be powered off during the privacy mode.

[0164] FIG. **6B** is a perspective view of an example implementation of an electronic device **600B**. The electronic device **600B** can include an actuator **601B** and a display **612B**. The electronic device **600A**, or its components, such as the actuator **601B** and/or display **612B** can include similar structural and/or operational features as electronic device **600A** shown and/or discussed with respect to FIG. **6A**.

[0165] The actuator **601B**, or portion thereof, can include shading or coloring. For example, a portion of the actuator **601B** can be colored red, green, black, or any other color, and can be viewable when the actuator **601B** is in a certain state. In the example implementation shown in FIG. **6B**, the actuator **601B** is in a certain state which can cause the electronic device **600B** to enter a non-privacy mode. A portion of the actuator **601B** can be visible and can be colored a certain color, such as green, black, red, etc., to indicate the electronic device **600B** is in the non-privacy mode. In some implementations, the portion of the actuator **601B** that is visible in FIG. **6B** when the actuator **601B** is in one state can be different than the portion of the actuator **601A** that is visible in FIG. **6A** when the actuator **601A** is in another state.

[0166] FIG. **7** is a block diagram of an example electronic device **750**. Electronic device **750** can include similar structural and/or operational features as any of the other example electronic devices shown and/or described herein. Electronic device **750** can be a wearable device such as a watch, a soundbar, a phone such as a mobile phone, a monitoring hub, a physiological sensor, a tablet computer, desktop computer, laptop, mobile computing device, mobile phone, personal digital assistant (PDA), hybrid PDA/mobile phone, or the like. Electronic device **750** can include a hardware processor **751**, a storage component **753**, one or more communication components **755**, a power source **757**, one or more sensors **759**, and a display **761**.

[0167] The hardware processor **751** can comprise one or more integrated circuits. The hardware processor **751** can comprise and/or have access to memory. The hardware processor **751** can

comprise and/or be embodied as one or more chips, controllers such as microcontrollers (MCUs), and/or microprocessors (MPUs). The hardware processor **751** can comprise a central processing unit (CPU). In some implementations, the hardware processor **751** can be embodied as a system-on-a-chip (SoC). The hardware processor **751** can be configured to implement an operating system which can allow multiple processes to execute simultaneously. The hardware processor **751** can be configured to execute program instructions to cause the electronic device **750**, or components thereof, to perform one or more operations. The hardware processor **751** can be configured, among other things, to process data, execute instructions to perform one or more functions, and/or control the operation of the electronic device **750** or components thereof. For example, the hardware processor **751** can process physiological data obtained from physiological sensors and can execute instructions to perform functions related to storing and/or transmitting such physiological data. In some implementations, the hardware processor **751** may be remote to the electronic device **750**.

[0168] The storage component **753** can include any computer readable storage medium and/or device (or collection of data storage mediums and/or devices), including, but not limited to, one or more memory devices that store data, including without limitation, dynamic and/or static random-access memory (RAM), programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), optical disks (e.g., CD-ROM, DVD-ROM, etc.), magnetic disks (e.g., hard disks, floppy disks, etc.), memory circuits (e.g., solid state drives, random-access memory (RAM), etc.), and/or the like. Such stored data can be processed and/or unprocessed physiological data originating from physiological sensors, for example. The storage component **753** can store program instructions that when executed by the hardware processor **751** cause the electronic device **750** to perform one or more operations.

[0169] The communication components **755** can facilitate communication (via wireless, wired, and/or wire-like connection) between the electronic device **750** (and/or components thereof) and separate devices, such as separate electronic devices, monitoring devices, computing devices, mobile devices, sensors, systems, servers, or the like. For example, the communication components **755** can be configured to allow the electronic device **750** to wirelessly communicate with other devices, systems, and/or networks over any of a variety of communication protocols, including near-field communication protocols and far-field communication protocols. Near-field communication protocols, which may also be referred to as non-radiative communication, can implement inductive coupling between coils of wire to transfer energy via magnetic fields (e.g., NFMI). Near-field communication protocols can implement capacitive coupling between conductive electrodes to transfer energy via electric fields. Far-field communication protocols, which may also be referred to as radiative communication, can transfer energy via electromagnetic radiation (e.g., radio waves). The communication components **755** can communicate via any variety of communication protocols such as Wi-Fi, Bluetooth®, ZigBee®, Z-wave®, cellular telephony, such as long-term evolution (LTE) and/or 1G, 2G, 3G, 4G, 5G, etc., infrared, radio frequency identification (RFID), satellite transmission, inductive coupling, capacitive coupling, proprietary protocols, combinations of the same, and the like. In some implementations, communication components **755** can implement human body communication (HBC) which may include capacitively coupling a transmitter and receiver via an electric field propagating through the human body. The communication components **755** can allow data and/or instructions to be transmitted and/or received to and/or from the electronic device **750** and separate computing devices. The communication components **755** can be configured to transmit and/or receive (for example, wirelessly) processed and/or unprocessed physiological data with separate computing devices including physiological sensors, other monitoring hubs, remote servers, or the like. In some implementations, communication components **755** can transfer power required for operation of a computing device. The communication components **755** can be embodied in one or more components that are in communication with each other. The communication components **755** can

include one or more of: transceivers, antennas, transponders, radios, emitters, detectors, coils of wire (e.g., for inductive coupling), and/or electrodes (e.g., for capacitive coupling). The communication components **755** can include one or more integrated circuits, chips, controllers, processors, or the like, such as a Wi-Fi chip, a Bluetooth chip, and/or a cellular telephony chip and/or modem.

[0170] The power source **757** can provide power for components of the electronic device **750**. The power source **757** can include a battery. In some implementations, the power source **757** can be external to the electronic device **750**. For example, the auricular device **200** can include or can be configured to connect to a cable which can itself connect to an external power source to provide power to the electronic device **750**. The power source **757** can include a dual-battery configuration with a main battery and a backup battery. The electronic device **750** can additionally or alternatively be configured to be solar-powered, for example, by including a solar panel on the dial or elsewhere of the electronic device **750**.

[0171] The sensors **759** can include one or more physiological sensors configured to generate physiological data of physiological parameters. The sensors **759** can include acoustic sensors, optical sensors, inertial sensors, temperatures sensors, electrical sensors, voltage sensors, impedance sensors, etc. The sensors **759** can include an oximeter. The sensors **309** can include a photoplethysmography (PPG) sensor configured to measure volumetric variation in blood circulation and derive one or more parameters therefrom, such as pulse rate, blood pressure, respiration rate, cardiac output, perfusion index, pleth variability index, PPG waveform data, blood oxygen saturation, etc. The sensors **309** can include one or more optical emitters configured to emit optical radiation of a plurality of wavelengths, which can include visible light. The sensors **309** can include one or more optical detectors configured to detect optical radiation attenuated by the tissue of subject (which may have been emitted by optical emitters) and generate data relating to the pulsatile characteristics of the subject, including blood oxygen saturation, hydration, hemoglobin content, etc. The sensors **759** can include electrocardiogram (ECG) sensors, including one or more electrodes, configured to measure electrical activity of the subject, such as cardiac signals. The sensors **759** can measure and/or generate data relating to respiration rate, blood oxygen saturation (e.g., SpO2), heart rate, pulse rate, skin temperature, core body temperature, spatial orientation, or the like.

[0172] The sensors **759** can include a microphone configured to generate audio data responsive to detecting audio. The sensors **759** can include a camera configured to generate image data responsive to capturing light. Image data generated by the camera can be processed to render images and/or video.

[0173] The display **761** can display user interfaces, such as any of the example user interfaces, or aspects thereof, that are shown and/or described herein. The display **761** can include an LED screen, an LCD screen, an OLED screen (such as an AMOLED screen), a QLED screen, a plasma display screen, a quantum dot display screen, or the like. The display **761** may be responsive to touch. For example, the display screen can comprise a touchscreen such as a resistive touchscreen, a capacitive touchscreen, an infrared touchscreen, a surface acoustic wave touchscreen, or the like.

[0174] FIG. **8A** is a schematic block diagram illustrating an example implementation of an electronic device **800**. Electronic device **800** can be implemented as any of the other example electronic devices shown and/or described herein. The electronic device **800** can include an actuator **801**, one or more sensors **809**, one or more privacy components **811**, a power source **803**, one or more hardware processors **805**, one or more storage devices **807**, and one or more switches such as switch **804A** and/or switch **804B**. In some implementations, the electronic device **800** may not include switch **804A**.

[0175] The power source **803** can provide power to hardware components of the electronic device **800** described herein. The power source **803** can include a battery. The power source **803** can be, for example, a lithium battery. Additionally or alternatively, the electronic device **800** can be

configured to obtain power from a power source that is external to the electronic device **800**. For example, the electronic device **800** can include or can be configured to connect to a cable which can itself connect to an external power source to provide power to the electronic device **800**.

[0176] The switch(es) **804** (such as switch **804B** and/or switch **804A**) can include an electrical switch, relay, conductor, circuit breaker, or the like. The switch(es) **804** can include a two-way, three-way, four-way switch, or the like. The switch(es) **804** can include a single pole, single throw (SPST) switch, a single pole, double throw (SPDT) switch, a double pole, single throw (DPST) switch, a double pole, double throw (DPDT) switch, or the like. The switch(es) **804** can be configured to transition between one or more states, such as in response to input from the actuator **801**. In some implementations, the switch(es) **804** can transition between one or more states in response to a signal from the processor(s) **805**. In some implementations, the switch(es) **804** can transition between states automatically based, at least in part, on one or more conditions such as time, location of the electronic device **800**, or the like. The switch(es) **804** can be configured to conduct energy in a first state and not conduct energy in a second state. The switch **804B** can be configured to electrically disconnect the privacy component(s) **811** from the power source **803**. The switch **804A** can be configured to electrically disconnect the sensor(s) **809** from the power source **803**. In some implementations, the switch **804A** may be different than switch **804B**. In some implementations, switch **804A** may be the same as switch **804B**.

[0177] The processor(s) **805** can be configured, among other things, to process data, execute instructions to perform one or more functions, and/or control the operation of the electronic device **800**, or components thereof. For example, the processor(s) **805** can process data obtained from the sensor(s) **809** and can execute instructions to perform functions related to processing, storing, displaying, and/or transmitting such data.

[0178] The storage device(s) **807** can include one or more memory devices that store data, including without limitation, dynamic and/or static random-access memory (RAM), programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), and the like. Such stored data can be data obtained from the sensor(s) **809** which can include processed and/or unprocessed physiological data, for example.

[0179] The sensor(s) **809** can include an altimeter **809A**, a microphone **809B**, a camera **809C**, and/or one or more physiological sensors **809D**. FIG. **8A** is not intended to be limiting of the present disclosure. In some implementations, the sensor(s) **809** can include additional sensors not shown. In some implementations, the sensor(s) **809** can include fewer sensors than what are shown.

[0180] The sensor(s) **809** can generate sensor data, for example in response to obtaining, measuring, and/or collecting input data. The altimeter **809A** can generate altitude data in response to obtaining barometric pressure data. The microphone **809B** can generate audio data in response to receiving audio input. The camera **809C** can generate image and/or video data in response to capturing image input. The physiological sensor(s) can generate physiological data in response to obtaining physiological measurements of user of the electronic device **800**. The physiological sensor(s) **809D** can include one or more of electrodes, emitters, detectors, thermistor, gyroscope, accelerometer, or the like.

[0181] The privacy component(s) **811** can include a display **811A**, a speaker **811B**, one or more communication components **811C**, and/or a GNSS **811D**. FIG. **8A** is not intended to be limiting of the present disclosure. In some implementations, the privacy component(s) **811** can include additional devices not shown. In some implementations, the privacy component(s) **811** can include fewer devices than what are shown. In some implementations, the privacy component(s) **811** may not include a display **811A** and/or a speaker **811B**.

[0182] The display **811A** can display one or more images relating to sensor data. For example, the display **811A** can display physiological parameters or data obtained from one or more physiological sensors **809D**. The display **811A** can include an LED display.

[0183] The speaker **811B** can output auditory signals. The auditory signals can include an alarm. The auditory signals can relate to sensor data such as data from physiological sensors **809D**. The auditory signals can include sounds and/or verbal words.

[0184] The GNSS **811D** can facilitate communication between the electronic device **800** (and/or components thereof) and separate devices such as one or more satellites. The GNSS can transmit and/or receive data relating to a geographic location of the GNSS **811D** and electronic device **800**. The GNSS **811D** can include a transceiver, an antenna, or the like. In some implementations, the GNSS **811D** can be embodied in the communication component **811C**.

[0185] The communication component(s) **811C** can facilitate communication (via wired and/or wireless connection) between the electronic device **800** (and/or components thereof) and separate devices, such as separate computing devices, sensors, systems, servers, or the like. For example, the communication component(s) **811C** can be configured to allow the electronic device **800** to wirelessly communicate with other devices, systems, and/or networks over any of a variety of communication protocols. The communication component(s) **811C** can be configured to use any of a variety of wireless communication protocols, such as Wi-Fi, Bluetooth®, ZigBee®, Z-wave®, cellular telephony, infrared, near-field communications (NFC), radio frequency identification (RFID), satellite transmission, proprietary protocols, combinations of the same, and/or the like. The communication component(s) **811C** can allow data and/or instructions to be transmitted and/or received to and/or from the electronic device **800** and separate computing devices. The communication component(s) **811C** can be configured to transmit and/or receive (for example, wirelessly) sensor data such as processed and/or unprocessed physiological data with separate computing devices remote to the electronic device **800**, remote servers, or the like. The communication component(s) **11C** can be embodied in one or more components that are in communication with each other. The communication component(s) **811C** can include a wireless transceiver, an antenna, and/or a near field communication (NFC) component such as a transponder.

[0186] The power source **803** can be in electrical communication with the privacy component(s) **811** via switch **804B**. The power source **803** can be removably electrically coupled with the privacy component(s) **811** via the switch **804B**. For example, the switch **804B** can electrically connect the power source **803** with the privacy component(s) **811** in a first state and can electrically disconnect the power source **803** from the privacy component(s) **811** in a second state. The switch **804B** can transition between states in response to actuation of the actuator **801**.

[0187] Transitioning of the switch **804B** between states can correspond to various modes of operation of the electronic device **800**. For example, the switch **804B** can electrically disconnect the power source **803** from the privacy component(s) **811** during a privacy mode operation and can electrically connect the power source **803** to the privacy component(s) **811** during a non-privacy mode operation. One or more of the privacy component(s) **811** may not operate when disconnected from the power source **803** by the switch **804B**, such as during a privacy mode. Advantageously, when the privacy component(s) **811** are electrically disconnected from the power source **803** by the switch **804B**, such as during a privacy mode, the electronic device can protect private data, such as sensitive sensor data, by preventing the data from being transmitted, obtained, received, viewed, heard, or the like, by other computing devices, people, etc., for example. For example, during a privacy mode, when the privacy component(s) **811** may be electrically disconnected from the power source **803**, the communication component(s) **811C** may not be capable of communicating data to one or more remote devices at least because the communication component(s) **811C** are powered off. As another example, during a privacy mode, the communication component(s) **811C** may not be capable of receiving data, such as phone calls, text messages, email messages, software updates, notifications, or the like, from one or more remote devices at least because the communication component(s) **811C** are powered off. As another example, during a privacy mode, display **811A** may be disabled. For example, the display **811A** may not display data, such as

physiological data, at least because the display **811A** is powered off, which can prevent certain people from viewing the data on the display **811A** such as when a user of the electronic device **800A** is in a public area and does not desire other people to view data displayed via the display **811A**. As another example, during a privacy mode, the speaker **811B** may not be capable of outputting an audio signal, at least because the speaker **811B** is powered off, which can prevent certain people from hearing audio signals relating to private data such as when a user of the electronic device **800** is in a public area and does not desire other people to hear audio sounds relating to certain data, such as voice audio reciting physiological parameters of the user. As another example, during a privacy mode, the GNSS **811D** may not be capable of determining a location of the GNSS **811D** and/or the electronic device **800**, at least because the GNSS **811D** is powered off, which can prevent other computing devices and/or people from receiving, obtaining data relating to the location of the GNSS **811D** and/or the electronic device **800**.

[0188] In some implementations, the switch **804B** can transition between states to electrically connect/disconnect each of the privacy component(s) **811** collectively from the power source **803**. For example, the switch **804B** can electrically connect/disconnect the power source **803** with each of the privacy component(s) **811** via a single pole. In some implementations, the switch **804B** can transition between states to electrically connect/disconnect the privacy component(s) **811** from the power source **803** independently of one another. For example, the switch **804B** can electrically connect/disconnect some or all of the privacy component(s) **811** with the power source **803** individually such as via multiple switches or multiples poles. For example, each pole can correspond to a unique device of the privacy component(s) **811**.

[0189] As an example, the switch **804B** can electrically connect each of the privacy component(s) **811** with the power source **803** in a first state and can electrically disconnect each of the privacy component(s) **811** from the power source **803** in a second state. As another example, the switch **804B** can electrically connect a first group of privacy component(s) **811** with the power source **803** in a first state and can electrically connect a second group of privacy component(s) **811** with the power source **803** in a second state and can electrically connect each of the privacy component(s) **811** with the power source **803** in a third state and can electrically disconnect each of the privacy component(s) **811** from the power source **803** in a fourth state.

[0190] In some implementations, the power source **803** can be in electrical communication with the privacy component(s) **811** optionally via switch **804B**. The power source **803** can be removably electrically coupled with the privacy component(s) **811** via the switch **804B**. For example, the switch **804B** can electrically connect the power source **803** with the privacy component(s) **811** in a first state and can electrically disconnect the power source **803** from the privacy component(s) **811** in a second state. The switch **804B** can transition between states in response to actuation of the actuator **801**. The switch **804A** can include similar and/or the same structural and/or operational features discussed with respect to switch **804B**.

[0191] In some implementations, the power source **803** can be in direct electrical communication with the privacy component(s) **811**. For example, the power source **803** may not be electrically coupled with the privacy component(s) **811** via the switch **804A**. For example, the sensor(s) **809** can be in electrical communication with the power source **803** and can receive power therefrom whether during a privacy mode or non-privacy mode. Advantageously, the sensor(s) **809** can continue to operate during a privacy mode of the electronic device **800**. In some implementations, the sensor(s) **809** can continue to operate regardless of actuation of the actuator **801**.

Advantageously, the sensor can continue to generate sensor data whether during a privacy mode or non-privacy mode such that the sensor data may be continuous over a length and/or may not include any gaps due to changes in modes of operation. Advantageously, a continuous set of data may be important and can improve data monitoring and/or analysis, such as when analyzing trends in data, as is often the case with physiological data, for example, for which a user may desire to have access to an uninterrupted series of data. Advantageously, the electronic device **800** may still

protect private sensor data that is generated during a privacy mode such as by preventing the sensor data from being communicated to any external devices, for example, at least because the communication component **811C** is powered off during a privacy mode. Advantageously, a user of the electronic device **800** may still have access to all sensor data, including private sensor data, generated during a privacy mode. For example, the sensor(s) **809** can generate sensor data during a privacy mode and the display **811A** can display that sensor data during and/or after the privacy mode such that a user of the electronic device **800** can view the private sensor data. However, the electronic device **800** may still protect such private sensor data by preventing the communication component **811C** from communicating the sensor data to remote devices during and/or after the privacy mode, for example. Accordingly, the electronic device **800** can continue to generate sensor data during a privacy mode while still protecting that sensor data.

[0192] The electronic device **800** can receive a user input **812**, such as via the actuator **801**. The user input **812** can include a physical motion or movement such as a mechanical force to push, slide, switch, toggle, move, etc. the actuator **801**. The user input **812** can include an electrical force or signal, such as a change in capacitance on a capacitive touchscreen, a change in voltage, a change in current, or the like. The user input **812** can include one or more auditory signals, such as a voice command detected by a microphone and processed by a processor (for example, using voice recognition), to actuate the actuator **801**. The user input **812** can include one or more visual signals, such as an image of a face captured by a camera and processed by a processor (for example, using face recognition), to actuate the actuator **801**.

[0193] The actuator **801** can change states based on the user input **812**. Actuation of the actuator **801** can cause the switch **804A** and/or the switch **804B** to change states, which can cause the electronic device **800** to transition between one or more operating modes, such as privacy and non-privacy modes. The actuator **801** may be directly physically and/or electrically connected with the switch **804A** and/or the switch **804B**. For example, the actuator **801** may be hardwired with the switch **804A** and/or the switch **804B**. Advantageously, a direct connection between the actuator **801** and the switch(es) **804** may ensure that actuation of the actuator **801** causes the switch(es) **804** to change state. Advantageously, transitioning the switch(es) **804** between states may depend only on actuating the actuator **801** (which may be a physical action), and may not depend on program instructions, such as instructions generated by a hardware processor, which may reduce the risk of erroneous operation caused by software bugs, software hacking, software incompatibilities, or the like.

[0194] The actuator **801** is in communication with the processor(s) **805**. The actuator **801**, or actuation thereof, can cause the processor(s) **805** to perform one or more operations and/or change mode of operation. For example, the processor(s) **805** can process data differently based on actuation of the actuator **801**.

[0195] The processor(s) **805** can receive sensor data from the sensor(s) **809**. The processor(s) **805** can tag sensor data with metadata. The metadata can include identifiers to specify one or more attributes of the sensor data, such as a time the sensor data was generated, a mode of operation (for example, privacy, non-privacy) during which the sensor data was generated, a location the sensor data was generated, a privacy status level of the sensor data, or the like. The **805** can assign and/or update the metadata of the sensor data based at least on actuation of the actuator **801**.

Advantageously, metadata of the sensor data can improve efficiency with which the data is handled and improve protection of private data. For example, the processor(s) **805** can perform one or more operations relating to the sensor data according to metadata of the sensor data. The processor(s) **805** can handle certain sensor data, such as private data, differently based on its metadata. The processor(s) **805** may be able to quickly and efficiently identify data that should be handled differently based on the metadata, which may lead to faster search times when accessing and/or retrieving data such as from storage.

[0196] The processor(s) **805** can store sensor data in the storage device(s) **807**. In some

implementations, the processor(s) **805** can store all sensor data received from the sensor(s) **809**. For example, the processor(s) **805** may store sensor data regardless of whether the sensor data was received from and/or generated by the sensor(s) **809** during a privacy mode. In some implementations, the processor(s) **805** may not delete sensor data received from and/or generated by the sensor(s) **809** during a privacy mode. Advantageously, sensor data, whether received and/or generated during a privacy mode, may be stored in the storage device(s) **807** and thus the electronic device **800** may have access to all of the sensor data, while still protecting private data as described herein. This may reduce the amount data that is lost and/or deleted for being private but which may still be valuable and desirable to be kept, although being private and requiring protection. In some implementations, the processor(s) **805** may delete and/or may not save to storage sensor data received from and/or generated by the sensor(s) **809** during a privacy mode.

[0197] The processor(s) **805** can store all of the sensor data in a same storage device and/or similar location in storage. For example, the storage device(s) **807** can include a single storage device configured to store all of the sensor data. In some implementations, the processor(s) **805** can store all of the sensor data in a similar manner and/or location, such as regardless of whether the sensor data was received and/or generated during a privacy mode, for example. Advantageously, the processor(s) **805** can identify, retrieve, and/or access sensor data from storage based on metadata of the sensor data, and not based on sensor data location in storage. Advantageously, by identifying its metadata, the processor(s) **805** may be able to more quickly access the sensor data, at least because the processor(s) **805** will not have to search across multiple storage locations and/or devices. Advantageously, the processor(s) **805** may not be required to expend time and processing power to allocate storage, partition storage, segregate storage, etc. to store private data differently than other data. Advantageously, the entire storage device(s) **807** may be available to store any data (for example, private or non-private) which may improve memory requirements, such as by reducing the need to allocate a relatively large amount of storage space for a relatively small amount of data such as private data. Advantageously, eliminating the need to allocate particular storage for certain data, such as private data, may reduce the amount of storage space required by the electronic device **800**.

[0198] Advantageously, the processor(s) **805** and/or storage device(s) **807** may be in direct communication with the sensor(s) **809**. For example, the storage device(s) **807** and/or storage device(s) **807** may be in communication with the sensor(s) **809** regardless of whether the electronic device **800** is in a privacy mode or non-privacy mode and/or whether the actuator **801** is actuated.

[0199] FIG. **8B** is a block diagram of an example electronic device **820**. The electronic device **820** can include similar structural and/or operational features as any of the other example electronic devices shown and/or described herein. The electronic device **820** may be a phone, a watch, a computer, a soundbar, or the like. Electronic device **820** can include an actuator **821**, a controller **822**, power source **823**, a device processor **825**, storage **827**, one or more switches (e.g., switch **824A** and/or switch **824B**), device components **830**, and privacy components **840**.

[0200] The privacy components **840** can include WiFi component **841**, a Bluetooth component **842**, a cellular telephony component **848**, a Global Navigation Satellite System (GNSS) component **843**, NFC component **844**, microphone **845**, altimeter **846**, and camera **847**. The privacy components **840** may be the components that are eligible to be disabled during a privacy mode. The privacy components **840** can include one or more communication components, such as WiFi component **841**, a Bluetooth component **842**, a GNSS component **843**, and NFC component **844**, which can include similar structural and/or operation features as any of the example communication components shown and/or described herein.

[0201] The WiFi component **841** can facilitate wireless communication between the electronic device **820** and separate devices, such as separate electronic devices. The WiFi component **841** can implement a WiFi communication protocol to communicate with remote electronic devices (e.g., over a network, which may include the Internet). The WiFi component **841** can allow data and/or

instructions to be transmitted from the electronic device **820** (e.g., data from the device processor **825** and/or the storage **827**) to separate computing devices. The WiFi component **841** can allow data and/or instructions to be received at the electronic device **820** from separate computing devices, which the WiFi component **841** can communicate to the device processor **825**, such as for processing and/or storage. The WiFi component **841** can be embodied in one or more components that are in communication with each other. The WiFi component **841** can include one or more transceivers, antennas, transponders, and/or radios. The WiFi component **841** can include one or more integrated circuits, chips, controllers, processors, or the like, such as a WiFi chip, which may be configured to execute instructions to perform operations and which may be in communication with the controller **822** and/or the device processor **825**.

[0202] The Bluetooth component **842** can facilitate wireless communication between the electronic device **820** and separate devices, such as separate electronic devices. The Bluetooth component **842** can implement a Bluetooth communication protocol to communicate with remote electronic devices. The Bluetooth component **842** can allow data and/or instructions to be transmitted from the electronic device **820** (e.g., data from the device processor **825** and/or the storage **827**) to separate computing devices. The Bluetooth component **842** can allow data and/or instructions to be received at the electronic device **820** from separate computing devices, which the Bluetooth component **842** can communicate to the device processor **825**, such as for processing and/or storage. The Bluetooth component **842** can be embodied in one or more components that are in communication with each other. The Bluetooth component **842** can include one or more transceivers, antennas, transponders, and/or radios. The Bluetooth component **842** can include one or more integrated circuits, chips, controllers, processors, or the like, such as a Bluetooth chip, which may be configured to execute instructions to perform operations and which may be in communication with the controller **822** and/or the device processor **825**.

[0203] The cellular telephony component **848** can facilitate wireless communication between the electronic device **820** and separate electronic devices, such as base transceiver stations and/or mobile devices. The cellular telephony component **848** can implement a cellular communication protocol, such as 1G, 2G, 3G, 4G, 5G, and/or LTE, to communicate with remote electronic devices (e.g., over a network, which can include a cellular network). The cellular telephony component **848** can allow data and/or instructions to be transmitted from the electronic device **820** (e.g., data from the device processor **825** and/or the storage **827**) to separate computing devices. The cellular telephony component **848** can allow data and/or instructions to be received at the electronic device **820** from separate computing devices, which the cellular telephony component **848** can communicate to the device processor **825**, such as for processing and/or storage. The cellular telephony component **848** can implement voice calls over a cellular network. The cellular telephony component **848** can be embodied in one or more components that are in communication with each other. The cellular telephony component **848** can include one or more transceivers, antennas, transponders, and/or radios. The cellular telephony component **848** can include one or more integrated circuits, chips, modems, controllers, processors, or the like, which may be configured to execute instructions to perform operations and which may be in communication with the controller **822** and/or the device processor **825**.

[0204] The GNSS component **843** can facilitate wireless communication between the electronic device **820** and remote satellites in orbit around the Earth. The GNSS component **843** can allow data and/or instructions to be transmitted and/or received to and/or from the electronic device **820** and satellites. For example, the GNSS component **843** can receive data from one or more satellites and can determine a location of the GNSS component **843** (and the electronic device **820**) from the data received from the satellites. The GNSS component **843** can communicate data received from satellites and/or location data generated by the GNSS component **843** to the device processor **825** which can process said data and/or store said data in storage **827**. The GNSS component **843** can be embodied in one or more components that are in communication with each other. The GNSS

component **843** can include one or more transceivers, antennas, transponders, and/or radios. The GNSS component **843** can include one or more integrated circuits, chips, controllers, processors, or the like, which may be configured to execute instructions to perform operations and which may be in communication with the controller **822** and/or the device processor **825**. The GNSS component **843** can implement one or more of GPS, GLONASS, Galileo, BDS, IRNSS, NavIC, and/or QZSS. [0205] The NFC component **844** can facilitate communication between the electronic device **820** and separate devices. The NFC component **844** can allow the electronic device **820** to communicate with other devices, systems, and/or networks via near-field communication protocols. Near-field communication protocols, which may also be referred to as non-radiative communication, can implement inductive coupling between coils of wire to transfer energy via magnetic fields (e.g., NFMI). Near-field communication protocols can implement capacitive coupling between conductive electrodes to transfer energy via electric fields. In some implementations, NFC component **844** can implement human body communication (HBC) which may include capacitively coupling a transmitter and receiver via an electric field propagating through the human body. The NFC component **844** can allow data and/or instructions to be transmitted from the electronic device **820** (e.g., data from the device processor **825** and/or the storage **827**) to separate computing devices. The NFC component **844** can allow data and/or instructions to be received at the electronic device **820** from separate computing devices, which the NFC component **844** may communicate to the device processor **825**, such as for processing and/or storage. The NFC component **844** can be embodied in one or more components that are in communication with each other. The NFC component **844** can include one or more of: emitters, detectors, coils of wire (e.g., for inductive coupling), and/or electrodes (e.g., for capacitive coupling). The NFC component **844** can include one or more integrated circuits, chips, controllers, processors, or the like, which may be configured to execute instructions to perform operations and which may be in communication with the controller **822** and/or the device processor **825**.

[0206] The microphone **845** can detect audio (e.g., sound). The microphone **845** can generate an electrical signal (e.g., audio data) responsive to detecting audio. The microphone **845** can include a transducer configured to convert sound pressure waves into an electrical signal. The microphone **845** may be in communication with the controller **822** and/or the device processor **825**. The microphone **845** can generate and communicate audio data to the device processor **825** which can process said data and/or store said data in storage **827**.

[0207] The altimeter **846** can measure pressure, such as the pressure of the atmosphere surrounding the electronic device **820**. The altimeter **846** can generate pressure data based on pressure measurements. The altimeter **846** can determine altitude of the altimeter **846** (and electronic device **820**) from pressure data. The altimeter **846** can communicate pressure data and/or altitude data to the device processor **825** which can process said data and/or store said data in storage **827**.

[0208] The camera **847** can capture light. The camera **847** can generate image data from captured light. The camera **847** can communicate image data to the device processor **825** which can process said data and/or store said data in storage **827**.

[0209] The device components **830** can include one or more sensors. The device components **830** can include optical emitters **831**, optical detectors **832**, a gyroscope **833**, an accelerometer **834**, a temperature sensor **835**, a sensor processor **836**, a display **837**, and a speaker **838**. The device components **830** may be the components that are not eligible to be disabled during a privacy mode. The device components **830**, including sensors, can continue to operate regardless of the state of the actuator **821** and/or a privacy mode state.

[0210] The optical emitters **831** can include can emit optical radiation having one or more wavelengths, such as three, four, five, or six wavelengths. Optical radiation can include infrared radiation and/or visible light. The optical emitters **831** can include one or more light emitting diodes (LEDs).

[0211] The optical detectors **832** can include one or more photodetectors, such as photodiodes. The

optical detectors **832** may generate data responsive to detecting optical radiation emitted from the optical emitters **831** (e.g., after attenuation by the tissue of a subject).

[0212] The gyroscope **833** can generate motion information, such as rotation data including angular velocity and/or acceleration. The accelerometer **834** can generate motion information, including acceleration data with respect three orthogonal directions.

[0213] The temperature sensor **835** can generate temperature data indicating a temperature of a subject. The temperature sensor **835** can include a thermistor.

[0214] The sensor processor **836** can control operations of the device components **830**. For example, the sensor processor **836** can drive the optical emitters **831** to emit light of different wavelengths. The sensor processor **836** can process signals from one or more of the device components **830**. For example, the sensor processor **836** can process signals generated by the detectors **852** responsive to detecting attenuated light after absorption by the body tissue of the user. The sensor processor **836** can generate processed physiological data, including physiological parameters, from sensor data. Physiological parameters can include pulse rate, heart rate, respiration rate, SpO₂, Pleth Variability Index (PVI), Perfusion Index (PI), respiration from the pleth (RRp), total hemoglobin (SpHb), hydration, glucose, blood pressure, hydration index, and/or other parameters. In some implementations, the sensor processor **836** can perform some or all of the processing of the raw sensor data of the sensors. The sensor processor **836** can cause sensors to perform intermittent and/or continuous data generation, or can perform a spot check, for example, upon request by the user.

[0215] The sensor processor **836** can implement electrocardiogram with sensor data (e.g., electrical data originating from an electrode) to generate processed physiological data. For example, the sensor processor **836** can implement ECG techniques to determine heart rate, can generate ECG waveform data, and/or can determine cardiac arrhythmias from sensor data. The sensor processor **836** can implement photoplethysmography (PPG) to determine volumetric changes in the tissue of a user, such as volumetric changes in arterial blood flow. For example, the sensor processor **836** can implement PPG techniques to determine one or more of pulse rate, blood pressure, respiration rate, cardiac output, perfusion index, pleth variability index, and/or PPG waveform data. The sensor processor **836** determine pulsatile characteristics of the subject from optical detector data such as blood oxygen saturation, hydration, hemoglobin content, etc.

[0216] In some implementations, the device processor **825** can perform one or more of the operations described with respect to sensor processor **836**. In some implementations, the electronic device **820** may not include a sensor processor **836** and the device processor **825** can perform the operations described for sensor processor **836**.

[0217] The display **837** can display indicia of physiological data, such as physiological parameters. The display **837** can render user interfaces including physiological data.

[0218] The speaker **838** can emit audio such as alerts, notifications, alarms, voice call audio, or the like.

[0219] The device processor **825** can comprise one or more integrated circuits. The device processor **825** can comprise and/or have access to memory. The device processor **825** can comprise and/or be embodied as one or more chips, controllers such as microcontrollers (MCUs), and/or microprocessors (MPUs). The device processor **825** can comprise a central processing unit (CPU). In some implementations, the device processor **825** can be embodied as a system-on-a-chip (SoC). The device processor **825** can be configured to implement an operating system which may allow multiple processes to execute simultaneously. The device processor **825** can be configured to execute program instructions to cause the electronic device **820**, or components thereof, to perform one or more operations. The device processor **825** can be configured, among other things, to process data, execute instructions to perform one or more functions, and/or control the operation of the electronic device **820** or components thereof. For example, the device processor **825** can process data obtained from the device components **830** and/or the privacy components **840** and can

execute instructions to perform functions related to storing and/or transmitting such data. The device processor **825** may be in communication with the device components **830**, the privacy components **840**, the storage **827**, or other components of the electronic device **820**. The device processor **825** can comprise program instructions that are programmable (e.g., can be updated, modified, provisioned, etc.). For example, the device processor **825** can receive firmware updates on a periodic basis.

[0220] The storage **827** can include any computer readable storage medium and/or device (or collection of data storage mediums and/or devices), including, but not limited to, one or more memory devices that store data, including without limitation, dynamic and/or static random-access memory (RAM), programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), optical disks (e.g., CD-ROM, DVD-ROM, etc.), magnetic disks (e.g., hard disks, floppy disks, etc.), memory circuits (e.g., solid state drives, random-access memory (RAM), etc.), and/or the like. Data stored at the storage **827** can include processed and/or unprocessed physiological data, sensor data, data originating from device components **830**, and/or data originating from privacy components **840**. The storage **827** can store program instructions that when executed by the device processor **825** cause the electronic device **820** to perform one or more operations.

[0221] The actuator **821** can be positioned on a frame or housing of the electronic device **820**. The actuator **821** can be accessible and/or operable by a user. The actuator **821** can comprise one or more physical components such as switch, button, lever, slider, pin, knob, dial, or the like. The actuator **821** can exist in one of a plurality of states which can include physical states or electrical states. The electrical states can correspond with, and depend on, the physical states such that causing the actuator **821** to change physical states also cause the actuator **821** to change electrical states. Actuator **821** can include and/or be electrically connected with an electrical output pin which can generate different output (e.g., voltages) based on the state of the actuator **821**. The actuator **821** output may be binary (e.g., high or low) or tertiary. Thus, electrical output at an actuator **821** output pin can depend on the state of the actuator **821** and can change whenever the actuator **821** changes states. Thus, the state of the actuator **821** can be monitored by monitoring the electrical output from the actuator **821**. In some implementations, actuator **821** can be implemented in software, such as program instructions configured to perform operations responsive to user input via a touchscreen.

[0222] The actuator **821** may be pressed, slid, rotated, turned, pulled, switched, etc. The actuator **821** may change states based on user input **829**. User input **829** may be a physical input such as a force to physically move the actuator **821**. For example, a user may physically move the actuator **821** to cause the actuator **821** to change states. User input **829** can include a voice command detected by the actuator **821** which may include a microphone and which may be configured to implement voice recognition. User input **829** can include a gesture detected by the actuator **821** which may include a camera. The actuator **821** may comprise a component in an interactive graphical user interface (GUI). For example, the actuator **821** can be displayed as a selectable GUI component, such as a slidable or pressable GUI component, within a display screen that is responsive to touch (e.g., a resistive touchscreen, a capacitive touchscreen, an infrared touchscreen, a surface acoustic wave touchscreen) and the user input **829** can include a user interaction with the selectable GUI component via the touch responsive display screen.

[0223] The actuator **821** may exist in a state that corresponds to a privacy mode and a state that corresponds to a non-privacy mode. The actuator **821** may exist in one of a plurality of states corresponding to a plurality of respective different types of privacy modes. Types of privacy modes can correspond to the components they disable and/or how they disable components (e.g., by cutting power and/or resetting the components). As an example, the actuator **821** may be a slidable switch and may exist in a left position corresponding to a non-privacy mode, a middle position corresponding to a privacy mode wherein certain components are operational and other

components are disabled, and a right position corresponding to a privacy mode wherein all eligible components are disabled. In some implementations, the actuator **821** may exist in only one state at a time.

[0224] The controller **822** may comprise a microcontroller unit (MCU). The controller **822** may comprise one or more independent and/or dedicated processors configured to execute program instructions. The controller **822** may comprise one or more integrated circuits. The controller **822** may comprise and/or have access to memory. The controller **822** may also be referred to as a dedicated controller or a privacy controller. The controller **822** may be non-programmable. For example, program instructions stored on, accessible by, and/or executable by the controller **822** may not be programmable, such as by utilizing a ROM memory. The controller **822** may comprise program instructions, which after initial configuration (e.g., during manufacturing) can not be updated, modified, provisioned, etc. The controller **822** may not receive, and/or may not be capable of receiving, firmware updates, such as may be provisioned over-the-air or via a physical connection. Advantageously, because the program instructions of the controller **822** may not change, the operation of the controller **822** may not be susceptible to malware.

[0225] The controller **822** may be electrically connected with the actuator **821**. The controller **822** can monitor the state of the actuator **821** such as by monitoring an electrical output from the actuator **821** which in some cases can correspond with, and depend on, the physical position of the actuator **821**. For example, the controller **822** can determine whether the actuator **821** is in a privacy state or a non-privacy state based on an electrical output from the actuator **821** which can depend on the physical position of the actuator **821**. The controller **822** may continuously monitor the state of the actuator **821**. In some implementations, the controller **822** may be the only component in communication with, and/or electrically connected to, the actuator **821**. For example, the controller **822** may be the only device to read the electrical output from the actuator **821** indicative of the state of the actuator **821**. For example, the device processor **825** may not read the state of the actuator **821**, in some cases.

[0226] The controller **822** may be electrically connected with and/or in communication with the device processor **825**. For example, the controller **822** can communicate signals to the device processor **825** and/or can receive signals from the device processor **825**. The controller **822** may be a non-isolated controller in that the controller can communicate with the device processor **825** and/or that the operation of the controller **822** may be affected by the device processor **825** or signals communicated therefrom. The controller **822** may be accessible by the device processor **825** and vice, versa. In some implementations, the controller **822** may be in one-way communication with the device processor **825**. For example, the controller **822** can communicate data to the device processor **825** but may not receive data from the device processor **825**. Accordingly, the controller **822** may be able to control an operation of the device processor **825** but may not be controllable by the device processor **825** in some cases. In such implementations, the controller **822** can implement a privacy mode upon expiration of a time threshold after actuation of actuator **821** without considering whether the device processor **825** has confirmed that the electronic device **820** is prepared for the privacy mode (or without even sending a notification signal to the device processor **825** to prepare for privacy mode).

[0227] The controller **822** can communicate a signal (e.g., a notification signal) to the device processor **825** in response to determining that the actuator **821** is in a privacy state. The notification signal can cause the device processor **825** to prepare the electronic device **820** to enter a privacy mode. Implementing a privacy mode on the electronic device **820** can include disabling components, severing power to components, resetting components, etc. which may cause processes that are executing on the electronic device to **820** to terminate. Terminating a process suddenly or without adequate preparation may cause loss of data, such as if the process is terminated asynchronously. The device processor **825** can prepare the electronic device **820** to enter a privacy mode such as by terminating processes executing on the electronic device **820**, which can include

synchronously terminating the processes, storing data in storage, or the like. The device processor **825** can terminate processes that are executing on the device processor **825**, on the sensor processor **836**, or on other processors or circuits of the electronic device **820**. The device processor **825** can communicate a signal (e.g., a confirmation signal) to the controller **822**. The confirmation signal can indicate that the electronic device **820** is ready to safely enter a privacy mode (e.g., that processes executing on the electronic device **820** have been properly terminated). The device processor **825** can communicate the confirmation signal to the controller **822** in response to successfully terminating one or more processes.

[0228] The controller **822** can implement a privacy mode on the electronic device **820** in response to one or more conditions. The conditions can include receiving the confirmation signal at the controller **822** from the device processor **825** and/or expiration of a time period. For example, the controller **822** can implement a privacy mode in response to receiving a signal from the device processor **825** indicating that the electronic device **820** is ready to enter a privacy mode. In some implementations, the controller **822** may wait to initiate the privacy mode until receiving confirmation from the device processor **825** that the electronic device **820** is ready to enter the privacy mode. As another example, the controller **822** can initiate a timer in response to determining that the actuator **821** is in a privacy state and/or in response to communicating a notification signal to the device processor **825**. The controller **822** can initiate the privacy mode in response to the timer exceeding a threshold. The timer (or threshold associated with the timer) can be between 1 second and 60 seconds, between 1 second and 30 seconds, between 1 second and 10 seconds, between 1 second and 5 seconds, between 1 second and 3 seconds, or between 1 second and 2 seconds. The timer (or threshold associated with the timer) can be between 0.1 seconds and 1 second or between 0.1 seconds and 0.5 seconds. The timer (or threshold associated with the timer) can be about 1 second, about 2 seconds, about 3 seconds, about 4 seconds, or about 5 seconds. As an example, the controller **822** can initiate a privacy mode 5 seconds after determining that the actuator **821** is in a privacy state and/or after communicating the notification signal to the device processor **825**. In some implementations, a time between determining that the actuator **821** is in a privacy state and communicating the notification signal may be negligible. The controller **822** can initiate a privacy mode after a time period has elapsed regardless of whether the controller **822** has received a signal from the device processor **825** confirming that the electronic device **820** is ready to safely enter a privacy mode. For example, the controller **822** can initiate a privacy mode after expiration of a time period even if one or more processes are still executing on the electronic device **820**. The device processor **825** may fail to prepare the electronic device **820** to enter a privacy mode (e.g., within a certain time frame), in some examples, if malicious software is executing on the device processor **825** and preventing the device processor **825** from operating properly. Advantageously, the controller **822** may bias the decision to initiate privacy mode on the side of privacy such as by prioritizing privacy over safely executing and terminating processes. For example, the controller **822** may initiate a privacy mode to ensure privacy even if doing so may result in data loss or crashing a process that is currently executing.

[0229] Other conditions that may cause the controller **822** to implement a privacy mode can include location data or time data. For example, the controller **822** can implement a privacy mode in response to determining that the electronic device **820** is in a certain location or in response to determining that a current date, time, day, etc, match a criteria. For example, the controller **822** can implement a privacy mode at a particular time of day, or certain days of the week. The controller **822** may receive location data or time data from the device processor **825**, from another device on the electronic device **820**, or from a remote device or server.

[0230] The power source **823** can include a battery and/or capacitor, such as lithium-based battery such as a lithium-ion battery. The power source **823** can include an energy generation system, such as a system configured to generate electrical energy from solar energy. The power source **823** can be removably integrated with the electronic device **820**. The power source **823** can be rechargeable

such as with inductive charging and/or direct electrical contact. The power source **823** may provide power to the electronic device **820** for the electronic device **820** to operate. The power source **823** may provide power to at least the device components **830**, the controller **822**, the device processor **825**, the storage **827**, the privacy components **840**, among others. The power source **823** may be fixedly coupled to the device components **830** without a switch therebetween such that the device components **830** can be continuously connected to the power source **823** regardless of a privacy mode state. The power source **823** may be selectively coupled to the privacy components **840**. For example, the power source **823** may be removably coupled to the privacy components **840** via switch **824A**. The power source **823** may selectively provide power to the privacy components **840** based on an operation of the switch **824A**. In some implementations, the power source **823** may be coupled to the privacy components **840** via a plurality of switches, such as one switch per privacy component **840**.

[0231] The switch **824A** may comprise one or more switches. The switch **824A** may comprise an analog switch. The switch **824A** may be embodied in circuitry. The switch **824A** may comprise one or more MOSFETs. The switch **824A** can transition between a plurality of states, such as an open state and a closed state. The switch **824A** may be a single pole, double throw (SPDT) switch. In some implementations, the switch **824A** can transition between two or more states which may correspond to a non-privacy mode and one or more different types of privacy modes (for example, two types of privacy can be implement, a first privacy mode disabling all communication components, camera and audio device and a second mode where only the camera and audio devices are disabled, but communication components are not disabled). The switch **824A** can be a single pole, triple throw (SPTT) switch, or may include more than three throws. The switch **824A** can conduct an electrical signal (comprising data and/or energy) in a closed state. The switch **824A** may inhibit the conduction of electrical signals in an open state. The switch **824A** may allow the power source **823** to provide power to one or more of the privacy components **840** when the switch **824A** is in the closed state. The switch **824A** may inhibit the power source **823** from providing power to one or more of the privacy components **840** when the switch **824A** is in an open state. The switch **824A** can control whether the power source **823** is electrically coupled with one or more privacy components **840**. The switch **824A** can sever an electrical connection between the power source **823** and one or more privacy components **840**.

[0232] The controller **822** can implement a privacy mode on the electronic device **820**.

Implementing a privacy mode can include disabling one or more privacy components **840** such as by severing the power source **823** from one or more privacy components **840**. Severing the privacy components **840** from the power source **823** may prevent the privacy components **840** from receiving power which may cause the privacy components **840** to shut down. Advantageously, severing power to privacy components **840** may ensure that the privacy components **840** do not operate during a privacy mode. Advantageously, severing power to privacy components **840** may inhibit malicious software from operating the privacy components **840** during a privacy mode, for example, if malicious software were to attempt to override a privacy mode. Advantageously, severing power to privacy components **840** may inhibit access to data stored on the electronic device **820**, such as from software applications executing on the electronic device **820** and/or from computing devices that are remote to the electronic device **820**. For example, severing power to privacy components **840** may prevent data that originates and/or is stored on electronic device **820** from being communicated to remote devices. The controller **822** may be in communication with the switch **824A**. The controller **822** can control an operation of the switch **824A**. The controller **822** can cause the switch **824A** to change states (e.g., transition between an open state and a closed state). The controller **822** can implement a privacy mode by causing the switch **824A** to transition to an open state. The controller **822** can cause the switch **824A** to transition to an open state in response to any of the conditions discussed herein prerequisite to implementing a privacy mode. The controller **822** can implement a privacy mode on the electronic device **820** by severing all of

the privacy components **840** from the power source **823** (e.g., via switch **824A**). In some implementations, the controller **822** can implement a privacy mode on the electronic device **820** by severing less than all of the privacy components **840** from the power source **823** (e.g., via switch **824A**). For example, in some cases, the controller **822** may implement a privacy mode by severing power to only a few of the privacy components **840** such as to the WiFi component **841**, the Bluetooth component **842**, the cellular telephony component **848**, the GNSS component **843**, and/or the NFC component **844**. Thus, the state of the actuator **821** and/or privacy mode state of the electronic device **820** can affect the GNSS component **843** and/or other privacy components **840**.

[0233] Implementing a privacy mode can include disabling one or more privacy components **840** such as by holding one or more privacy components **840** in a reset mode. A privacy component **840** that is in a reset mode may fail to execute program instructions to perform operations. A privacy component **840** that is in a reset mode may ignore input data (e.g., electronic commands to perform operations). One or more of the privacy components **840** may comprise and/or be embodied as a chip configured to execute computer-executable instructions to perform operations. The chips of the privacy components **840** may be programmable. The chips may comprise an input pin corresponding to a reset mode. The chips may cause respective privacy components **840** to enter a reset mode based on input to their respective reset mode input pins. The controller **822** may be in communication with one or more privacy components **840**, collectively or individually. For example, the controller **822** can communicate data to one or more of the privacy components **840**. The controller **822** may be in communication with reset mode input pins on chips of respective privacy components **840**. The controller **822** can communicate data to the privacy components **840** to drive reset mode input pins of respective chips to cause the privacy components **840** to enter a reset mode. For example, the controller **822** can drive the reset mode input pins high (or low depending on the implementation) to cause the privacy components **840** to enter a reset mode. The controller **822** can continuously drive the reset mode input pins during a privacy mode.

[0234] The controller **822** can implement a privacy mode on the electronic device **820** by causing all of the privacy components **840** to enter a reset mode. In some implementations, the controller **822** can implement a privacy mode on the electronic device **820** by causing less than all of the privacy components **840** to enter a privacy mode. For example, in some cases, the controller **822** may implement a privacy mode by causing only a few of the privacy components **840** such as the microphone **845**, the altimeter **846**, and/or the camera **847** to enter a reset mode. In some implementations, one or more of the privacy components **840** may be in communication with the power source **823** and may receive power from the power source **823** (via switch **824A**) during a privacy mode, but may fail to execute program instructions to perform operations due to being in a reset mode.

[0235] The electronic device **820** can optionally include switch **824B**. The switch **824B** may include similar structural and/or operational features as switch **824A**. The switch **824B** may comprise one or more switches. The switch **824B** may comprise an analog switch. The switch **824B** may be embodied in circuitry. The switch **824B** may comprise one or more MOSFETs. The switch **824B** can transition between a plurality of states, such as an open state and a closed state. The switch **824A** may be a single pole, double throw (SPDT) switch. The switch **824B** can conduct an electrical signal (comprising data and/or energy) in a closed state. The switch **824A** may inhibit the conduction of electrical signals in an open state. The switch **824B** may be in communication with the device processor **825** and the privacy components **840**, and may allow communication of data between the device processor **825** and the privacy components **840** when in a close state and may inhibit the communication of data in an open state.

[0236] Implementing a privacy mode can include disabling one or more privacy components **840** such as by severing the device processor **825** from one or more privacy components privacy components **840** (e.g., via switch **824B**). Severing the privacy components **840** from the device processor **825** may prevent the privacy components **840** from sending to and/or receiving data from

the device processor **825**. For example, the device processor **825** may not be able to send commands to the privacy components **840** to control an operation of the privacy components **840** during a privacy mode and/or the privacy components **840** may not be able to send data (e.g., location data, data received from remote devices, etc.) during a privacy mode which can prevent data originating from the privacy components **840** from being stored in storage **827** and/or from being processed by the device processor **825**. In some implementations, one or more of the privacy components **840** may be in communication with the power source **823** and may receive power from the power source **823** (via switch **824A**) during a privacy mode, but may fail to communicate with the device processor **825**. The controller **822** may be in communication with the switch **824B**. The controller **822** can control an operation of the switch **824B**. The controller **822** can cause the switch **824B** to change states (e.g., transition between an open state and a closed state). The controller **822** can implement a privacy mode by causing the switch **824B** to transition to an open state. The controller **822** can cause the switch **824B** to transition to an open state in response to any of the conditions discussed herein prerequisite to initiating privacy mode. The controller **822** can implement a privacy mode on the electronic device **820** by severing all of the privacy components **840** from the device processor **825** (e.g., via switch **824B**). In some implementations, the controller **822** can implement a privacy mode on the electronic device **820** by severing less than all of the privacy components **840** from the device processor **825** (e.g., via switch **824B**).

[0237] Implementing a privacy mode can include disabling one or more privacy components **840** such as by interfering with a wireless communication signal or a wireless communication component, such as WiFi component **841**, Bluetooth component **842**, cellular telephony component **848**, GNSS component **843**, or NFC component **844**. For example, the controller **822** (or the device processor **825**) can interfere with a wireless communication antenna to decrease the antenna efficiency which can decrease the quality of a signal communicated from a wireless communication component or received at the wireless communication component.

[0238] FIG. **8C** is a block diagram illustrating an example implementation of an electronic device **820** which may include similar structural and/or operational features as shown and/or described with reference to FIG. **8B**. In this example implementation, the switch **824A** is in communication with the power source **823** as well as the WiFi component **841**, the Bluetooth component **842**, the cellular telephony component **848**, the GNSS component **843**, and the NFC component **844** (which may collectively be referred to as communication components). The controller **822** can cause the switch **824A** to transition between states to disconnect the communication components from the power source **823** or to establish connection between the communication components and the power source **823**. The controller **822** can implement a privacy mode (or a type of privacy mode) by causing the switch **824A** to transition states to sever an electrical connection between the power source **823** and the communication components.

[0239] As shown in this example, the controller **822** is in communication with the microphone **845**, the altimeter **846**, and the camera **847**. The controller **822** can communicate data to the microphone **845**, the altimeter **846**, and the camera **847**, such as to cause the microphone **845**, the altimeter **846**, and the camera **847** to implement a reset mode. For example, the controller **822** can continuously drive an input pin (high or low depending on the implementation) on each of the microphone **845**, the altimeter **846**, and the camera **847** to cause the microphone **845**, the altimeter **846**, and the camera **847** to enter (and stay) in a reset mode. The controller **822** can implement a privacy mode (or a type of privacy mode) by causing the microphone **845**, the altimeter **846**, and/or the camera **847** to enter (and stay) in a reset mode.

[0240] As shown in this example implementation, the electronic device **820** can implement more than one type of privacy mode, and may implement a plurality of types of privacy mode simultaneously or independently. Examples are provided as follows. The electronic device **820** can implement a first type of privacy mode by disabling each of the privacy components **840**. The electronic device **820** can implement a second type of privacy mode by disabling one or more of

the WiFi component **841**, the Bluetooth component **842**, the cellular telephony component **848**, the GNSS component **843**, and the NFC component **844** (e.g., by severing their connection to power source **823**) while not disabling one or more of the microphone **845**, the altimeter **846**, and the camera **847**. The electronic device **820** can implement a third type of privacy mode by disabling one or more of the microphone **845**, the altimeter **846**, and the camera **847** (e.g., by holding them in reset mode) while not disabling one or more of the WiFi component **841**, the Bluetooth component **842**, the cellular telephony component **848**, the GNSS component **843**, and the NFC component **844**.

[0241] The example implementation shown and/or discussed with reference to FIG. **8C** is not intended to be limiting of the present disclosure. Any combination of the privacy components **840** may be selectively coupled to the power source **823** via the switch **824A** and any combination of the privacy components **840** may be in communication with the controller **822** to receive data to force a reset mode. In some implementations, at least some of the privacy components **840** may be either coupled to the switch **824A** or in communication with the controller **822**, but not both. In some implementations, at least some of the privacy components **840** can be coupled to the switch **824A** and can be in communication with the controller **822**.

[0242] FIG. **9A** is a flowchart illustrating an example process **900** of implementing a privacy mode on an electronic device. This process, in full or parts, can be executed by one or more hardware processors and/or controllers, whether they're associated with a singular or multiple computing devices, and even devices in remote or wireless communication. By way of example, the one or more hardware processors and/or controllers executing process **900** can be associated with any of the example electronic devices shown and/or described herein. For example, controller **822** shown and/or described herein can implement process **900** in full or in parts. The implementations of this process may vary and can involve modifications like omitting blocks, adding blocks, and/or rearranging the order of execution of the blocks. Process **900** serves as an example and isn't intended to restrict the present disclosure.

[0243] At block **901**, an electronic device (e.g., one or more hardware processors and/or controllers of a computing device executing program instructions) can read an electronic state of an actuator which can correspond to a physical position of the actuator. The actuator can comprise any of the example actuators shown and/or described herein. The state of the actuator can change responsive to actuation of the actuator by a user.

[0244] At decision block **903** the electronic device can determine whether the actuator is in a privacy mode state. The actuator can exist in one or more states such as a privacy mode state and a non-privacy mode state. The electronic device can determine the state of the actuator from the actuator signal originating from and/or induced by the actuator at block **901**. The electronic device can return to block **901** in response to determining that the actuator is not in a privacy mode state (which can coincide with a non-privacy mode state). The electronic device can proceed to block **905** in response to determining that the actuator is in a privacy mode state.

[0245] At block **905** the electronic device can cause a device processor to prepare for a privacy mode. For example, the controller can communicate a signal to the device processor to cause the device processor to prepare. The signal can be referred to as a notification signal. The device processor can be any of the example device processors shown and/or described herein.

Implementing a privacy mode can include disabling components, severing power to components, resetting components, etc. which can cause processes that are executing to terminate. Terminating a process suddenly or without adequate preparation can cause loss of data, such as if the process is terminated asynchronously. The device processor can prepare the electronic device for privacy mode such as by terminating processes executing on the electronic device, which can include synchronously terminating the processes, storing data in storage, or the like. The device processor can terminate processes that are executing on the device processor or on other processors or circuits of the electronic device.

[0246] At decision block **907** the electronic device can optionally determine whether preparation for privacy mode has been confirmed as completed from the device processor. For example, upon completing preparation for privacy mode, the device processor can generate a signal (e.g., a confirmation signal) which can indicate that the electronic device is ready to safely enter privacy mode. Confirming that preparation for privacy mode is complete can include confirming that processes have been successfully terminated, that data has been properly stored, and/or that one or more components can be disabled (e.g., cut off from power or reset). If the electronic device determines at block **907**, that the electronic device is prepared for a privacy mode (e.g., based on confirmation signal from the device processor), the electronic device can proceed to block **911**. Block **907** can be optional at least because a controller of the electronic device that is executing block **907** may not be configured to receive communication from the device processor such as if the controller is isolated from the device processor or if the controller is in one-way communication with the device processor to send data to, but not receive data from, the device processor. If the electronic device does not determine at block **907**, that the electronic device is prepared for a privacy mode (because a controller has not yet received a confirmation signal from a device processor and/or because the controller is not configured to receive data from the device processor), the electronic device can proceed to block **909**.

[0247] At block **909** the electronic device can determine whether a wait time has exceeded a threshold. The electronic device can track a wait time (e.g., by setting a timer), to monitor a length of time spent preparing for privacy mode. For example, the electronic device can start a timer upon communicating a signal to the device processor to prepare for privacy mode at block **905**. In some implementations, the electronic device can start a timer in response to determining that the actuator is in a privacy mode state at block **901**. The threshold time can be between 1 second and 60 seconds, between 1 second and 30 seconds, between 1 second and 10 seconds, between 1 second and 5 seconds, between 1 second and 3 seconds, or between 1 second and 2 seconds. The threshold time can be between 0.1 seconds and 1 second or between 0.1 seconds and 0.5 seconds. The threshold time can be about 1 second, about 2 seconds, about 3 seconds, about 4 seconds, or about 5 seconds.

[0248] In response to determining that the wait time has not exceeded the threshold at block **909**, the electronic device can return to block **907**. Advantageously, allowing the electronic device a period of time to prepare to enter privacy mode reduce the likelihood of adverse effects, such as data loss, asynchronous process termination, applications crashing, etc.

[0249] In response to determining that the wait time has exceeded the threshold at block **909**, the electronic device can proceed to block **911** to implement the privacy mode. Advantageously, implementing a privacy mode even if the electronic device is not prepared to safely enter the privacy mode can ensure privacy when desired. The electronic device can thus prioritize privacy over other concerns such as data loss, etc.

[0250] At block **911** the electronic device can implement a privacy mode. Implementing a privacy mode can include disabling one or more components of the electronic device, such as communication components (e.g., for near-field or far-field communication), location tracking components such as GNSS, microphones, altimeters, cameras, or the like. Disabling components during a privacy mode can include severing the components from a power source, holding the components in a reset mode, and/or severing the components from the device processor. In some implementations, certain components and/or processes of the electronic device can continue to operate. For example, physiological sensors can continue to generate sensor data during a privacy mode. As another example, the device processor of the electronic device can continue to operate during a privacy mode.

[0251] FIG. **9B** is a flowchart illustrating an example process **920** of managing device data generated during privacy or non-privacy modes. This process, in full or parts, can be executed by one or more hardware processors, whether they're associated with a singular or multiple computing

devices, and even devices in remote or wireless communication. By way of example, the one or more hardware processors executing process **920** can be associated with any of the example electronic devices shown and/or described herein. The implementations of this process can vary and can involve modifications like omitting blocks, adding blocks, and/or rearranging the order of execution of the blocks. Process **920** serves as an example and isn't intended to restrict the present disclosure. Process **920**, or portions thereof, can be implemented during a privacy mode and/or during a non-privacy mode.

[0252] Process **920** can commence at block **921**. At block **923**, an electronic device (e.g., one or more hardware processors of a computing device executing program instructions) can determine whether the electronic device is in a privacy mode, such as any of the example privacy modes described herein. The electronic device can determine the occurrence of a privacy mode based on at least the state of an actuator, such as a mechanically actuated actuator such as a switch that can generate signals (e.g., change voltage) responsive to actuation and indicative of the actuator state. For example, the electronic device can read the state of the actuator to determine whether the actuator is actuated. The process **920** can proceed to block **925** responsive to determining the electronic device is in a privacy mode. The process **920** can proceed to block **941** responsive to determining the electronic device is in a non-privacy mode.

[0253] At decision block **925** the electronic device can determine whether a user has selected to enable generating select device data (e.g., during the privacy mode). For example, a user can select for the electronic device to continue generating certain data during a privacy mode while not generating other data during the privacy mode. Select device data can include sensor data originating from one or more sensors such as any of the example sensors shown and/or described herein such as physiological data originating from physiological sensors. Select device data can include processed and/or unprocessed sensor data. Select device data can include physiological parameters derived from physiological data. Select device data can include audio data originating from microphones, image data originating from cameras, altitude data originating from altimeters, location data originating from a GNSS component, etc.

[0254] In some implementations, a user can select to enable or disable generating select device data with a hardware actuator disposed on the electronic device, such as a button or switch. In some implementations, a user can select to enable or disable generating select device data via a graphical user interface such as can be displayed on a screen of the electronic device. In some implementations, a user can toggle between enabling and disabling generating select device data as desired. If the electronic device determines at decision block **925** that the user has not selected to enable generating select device data or has selected to disable generating select device data, the process can proceed to block **927**. If the electronic device determines at decision block **925** that the user has selected to enable generating select device data, the process can proceed to block **931**.

[0255] At block **927** the electronic device can disable generation of select device data. For example, the electronic device can disable one or more sensors from generating select device data. The electronic device can disable the sensors from generating data according to any of the example implementations described herein, such as severing power to the sensors or holding the sensors in a reset mode. In some implementations, the electronic device can disable select data generation by not providing instructions to the sensors to generate the data (while allowing the sensors to receive power and remain operational). In some implementations, the electronic device can disable select data generation by severing electrical communication between the sensors and a processor (while allowing the sensors to continue to operate).

[0256] At block **931** the electronic device can generate select device data during the privacy mode. For example, one or more sensors can continue to generate (or not generate) data according to normal operational functionality, such as generating data intermittently at a certain frequency, generating data based on time conditions, generating data based on location conditions, generating data in response to user requests (e.g., spot checks), generating data automatically, generating data

based on health conditions (e.g., determined from real-time physiological sensor data), and the like. Advantageously, the electronic device can continue to generate select device data, such as physiological data, during a privacy mode to preserve data continuity. Such select data that is generated during a privacy mode can still remain secure during the privacy mode at least because other operations, such as communication from the electronic device are disabled during the privacy mode, and can also remain secure after the privacy mode as will be described in greater detail throughout process **920** and process **950**.

[0257] From block **931**, the process **920** can proceed to block **933** and other blocks. In some implementations, certain aspects of process **920**, including block **933** or other operations appearing in FIG. **9B** after block **933**, such as blocks **935**, **936**, **937**, or **938**, can occur during the privacy mode discuss at block **923** or after the privacy mode has terminated, such as during a non-privacy mode. Moreover, the order of blocks **933** and **935** can be reversed from what is shown in FIG. **9B** and/or one or more of blocks **933** and **935** can occur after decision block **936** and/or after block **937**.

[0258] At block **933**, the electronic device can obfuscate the select device data generated during the privacy mode. For example, the electronic device can encrypt the device data according to one or more encryption protocols with one or more encryption algorithms. The electronic device can encrypt the device data with an encryption key which can be stored locally on the electronic device. Advantageously, encrypting the device data can prevent the device data from being decrypted, deciphered, or useable by another computing device, for example, if the device data were communicated to another computing device. Advantageously, encrypting the device data can prevent unauthorized program applications executing on the electronic device (e.g., malware) from decrypting or using the device data.

[0259] At block **935**, the electronic device can indicate a privacy status of the select device data with metadata. For example, the electronic device can create a tag, marker, or identifier to assign to the device data to indicate that the device data is private. Data can be private if it was generated during a privacy mode. Data can be non-private if it was generated during a non-privacy mode. In some implementations, metadata can indicate various levels of privacy status (e.g., not private, private level 1, private level 2), such as may be based on a type of privacy mode during which the data was generated. In some implementations, the electronic device can update existing metadata or delete existing metadata at block **935** to accurately reflect the privacy status of the data. Advantageously, the electronic device may be able to quickly identify whether device data is private, based on its metadata, and can manage the device data accordingly.

[0260] At decision block **936** the electronic device can determine whether a user has selected to store the select device data generated during the privacy. The user selection to store the device data can include storing the device data in long-term storage. In some implementations, a user can select to store the select device data with a hardware actuator disposed on the electronic device, such as a button or switch. In some implementations, a user can select to store the select device data via a graphical user interface such as can be displayed on a screen of the electronic device. In some implementations, a user can toggle between storing and not storing the select device data as desired. If the electronic device determines at decision block **925** that the user has selected to store the select device data, the process **920** can proceed to block **937**. If the electronic device determines at decision block **926** that the user has not selected to store the select device data, the process **920** can proceed to block **938**.

[0261] At block **938** the electronic device can allow select device data to be erased and/or may not store the select device data. For example, the electronic device can store the device data as non-persistent data in short term storage and can allow the device data to be erased from short-term storage without storing the data as persistent data in long-term storage. Short-term storage can include volatile memory such as registers, caches, buffers, and/or RAM. The electronic device can periodically erase data from short-term storage, such as based on clock timing.

[0262] At block **937** the electronic device can store the select device data, for example, as persistent data in long-term storage. Long-term storage can include non-volatile storage such as hard drives. Persistent data (e.g., stored in long-term storage) can persist after powering off the electronic device and/or terminating a process or application having the data executing on the electronic device. The long-term storage can be local to the electronic device. In some implementations, the electronic device can store the device data as organized data structures based on metadata. Data structures can include tables, rows, and columns. For example, the electronic device can sort the device data within a table based on metadata and/or can separate the device data into various tables or columns based on metadata. Advantageously, storing the device data within formatted data structures based on its metadata can increase electronic processing efficiencies such as faster data queries, data retrieval, and/or data analysis. In some implementations, the electronic device can store the device data in various locations in storage based on whether it is private or non-private according to its metadata such that the private data may be separate from non-private data. Storing data at various locations can include storing data at different addresses in memory, which may or may not be within a same partition. For example, private data can be stored at location in storage corresponding to a first memory address and the non-private data can be stored at another location in storage corresponding to another memory address. In some implementations, the electronic device can store private data and non-private data (e.g., depending on its metadata) within a same partition in storage. Advantageously, the electronic device may not need to divide the storage into separate partitions to store the device data based on whether it is private at least because the electronic device may be able to track private data and non-private data by its metadata rather than having to track based on a partition in which it is stored. In some implementations, the electronic device can store the device data at various locations within separate partitions based on whether the data is private or non-private. In some implementations, the electronic device can store the device data within separate storage devices based on whether the data is private or non-private.

[0263] From block **923**, the process **920** can proceed to block **941** responsive to determining the electronic device is in a non-privacy mode. Thus, blocks **941**, **943**, **945**, and **947** can execute during a non-privacy mode.

[0264] At block **941** the electronic device can generate device data. For example, one or more physiological sensors, cameras, microphones, altimeters, and/or location devices can continue to generate (or not generate) data according to normal operational functionality, such as generating data intermittently at a certain frequency, generating data based on time conditions, generating data based on location conditions, generating data in response to user requests (e.g., spot checks), generating data automatically, generating data based on health conditions (e.g., determined from real-time physiological sensor data), and the like. Device data generated at block **941** can include physiological data originating from physiological sensors, audio data originating from microphones, image data originating from cameras, altitude data originating from altimeters, location data originating from a GNSS component, etc

[0265] At block **943**, the electronic device can obfuscate the device data generated during the non-privacy mode. For example, the electronic device can encrypt the device data according to one or more encryption protocols with one or more encryption algorithms. The electronic device can encrypt the device data with an encryption key which can be stored locally on the electronic device. Advantageously, encrypting the device data can prevent the device data from being decrypted, deciphered, or usable by another computing device, for example, if the device data were communicated to another computing device. Advantageously, encrypting the device data can prevent unauthorized program applications executing on the electronic device (e.g., malware) from decrypting or using the device data.

[0266] At block **945**, the electronic device can optionally indicate a privacy status of the device data with metadata. For example, the electronic device can create a tag, marker, or identifier to assign to the device data to indicate that the device data is private. Data may be private if it was

generated during a privacy mode. Data may be non-private if it was generated during a non-privacy mode. In some implementations, all health-related data can be treated as confidential according to government health data restrictions, however such confidential health-related data generated during a privacy mode can be further indicated as being private to distinguish other confidential health-related data generated during a non-privacy mode. In some implementations, the electronic device can update existing metadata or delete existing metadata at block **945** to accurately reflect the privacy status of the data. Advantageously, the electronic device may be able to quickly identify whether device data is private or non-private, based on its metadata, and can manage the device data accordingly. In addition or alternatively to using metadata, data indicated as private can be encrypted using a different encryption key than data not indicated as private.

[0267] At block **947** the electronic device can store the select device data, for example, as persistent data in long-term storage as discussed in greater detail at block **937**.

[0268] FIG. **9C** is a flowchart illustrating an example process **950** of managing access to and communication of device data. This process, in full or parts, can be executed by one or more hardware processors, whether they're associated with a singular or multiple computing devices, and even devices in remote or wireless communication. By way of example, the one or more hardware processors executing process **950** can be associated with any of the example electronic devices shown and/or described herein. The implementations of this process can vary and can involve modifications like omitting blocks, adding blocks, and/or rearranging the order of execution of the blocks. Process **950** serves as an example and isn't intended to restrict the present disclosure.

[0269] Process **950**, or portions thereof, can be implemented during a privacy mode and/or during a non-privacy mode. In some implementations, process **950**, or portions thereof, can be implemented during a non-privacy mode such as when a communication component of an electronic device is powered on and/or operating.

[0270] At block **951**, an electronic device (e.g., one or more hardware processors of a computing device executing program instructions) can access device data. Accessing device data can include retrieving the device data from storage (e.g., local storage on the electronic device). Accessing device data can include receiving the device data (e.g., at a processor) from one or more sensors such as in real-time as the device data is generated at the sensors. Device data can include sensor data originating from one or more sensors such as any of the example sensors shown and/or described herein such as physiological sensors, microphones, altimeters, cameras, etc. Device data can include data originating from devices or components of the electronic device, such as location data originating from a GNSS component. Device data can include physiological data, audio data, and/or image data. Device data can include processed or unprocessed data. For example, device data can include raw and/or unprocessed sensor data and could also include processed sensor data such as physiological parameters derived from physiological data. Device data can originate from sensors local to the electronic device. Device data can originate from computing devices remote to the electronic device. Device data can include historical data previously generated and/or real-time data generated at substantially the same time as execution of process **950** or portions thereof.

[0271] At decision block **953**, the electronic device can determine whether the device data is private. The electronic device can determine whether the device data is private, based on at least, metadata of the device data. For example, metadata of the device data can include an identifier that indicates whether the device data is private. Device data can be private if it was generated, processed, stored, and/or received during a privacy mode. For example, private device data can include sensor data that was generated by sensors on the electronic device while the electronic device was in a privacy mode. Advantageously, the electronic device can be able to quickly determine whether the device data is private based on the metadata which can result in faster processing and/or improved processing efficiency. In some implementations, the electronic device can additionally or alternatively, at block **953**, determine whether the device data is not private. In some implementations, device data is either private or not private. In some implementations, device

data cannot be both private and not private. If the electronic device determines that the device data is private, the electronic device can proceed to block **955**. If the electronic device determines that the device data is not private, the electronic device can proceed to block **956**.

[0272] At block **955**, the electronic device can inhibit access to the private device data. Inhibiting access to the device data can include preventing remote computing devices from accessing the device data. Inhibiting access to the device data can include preventing program applications executing on the electronic device from accessing the device data. Program applications can include software and/or firmware applications executing program instructions on the electronic device to cause the electronic device to perform various operations. Program applications can be installed on the electronic device such as downloaded from a remote server. Program applications can include third-party applications executing on the electronic device. Program applications can include mobile apps. In some implementations, the electronic device can prevent program applications from accessing the device data regardless of any permission granted to the program applications by the user to access data, such as user authorizations during initial installation of the software app on the electronic device. In some implementations, the electronic device can prevent access to the device data to all program applications currently on the electronic device and/or to all program applications that can be installed on the electronic device in the future. In some implementations, the electronic device can inhibit access to the device data to less than all program applications on the electronic device. The electronic device can inhibit access to the device data based on the metadata of the device data or separate encryption key. The electronic device can determine which program application can access which device data based on the metadata or level/type of encryption. For example, device data metadata or level/type of encryption can indicate which program applications can access the device data and which program applications cannot access the device data.

[0273] At block **956**, the electronic device can allow access to non-private device data. Allowing access to the device data can include allowing remote computing devices to access the device data. Allowing access to the device data can include allowing software applications, such as third-party applications, executing on the electronic device to access the device data. In some implementations, the electronic device can allow access to the device data to all software applications currently on the electronic device and/or to all software applications that can be installed on the electronic device in the future. In some implementations, the electronic device can allow access to the device data to less than all software applications currently on the electronic device, such as determined by the device data metadata.

[0274] At decision block **957**, the electronic device can determine whether a user has selected to enable private data to be communicated from the electronic device. In some implementations, a user can select to enable or disable private data transmission with a hardware actuator disposed on the electronic device, such as a button or switch. In some implementations, a user can select to enable or disable private data transmission via a graphical user interface such as can be displayed on a screen of the electronic device. In some implementations, a user can toggle between enabling and disabling private data transmission as desired. If the electronic device determines at decision block **957** that the user has not selected to enable private data transmission or has selected to disable private data transmission, the process can proceed to block **958**. If the electronic device determines at decision block **957** that the user has selected to enable private data transmission, the process can proceed to block **959**.

[0275] At block **958**, the electronic device can inhibit the private device data from being communicated to remote computing devices. For example, the electronic device can cause a communication component of the electronic device to not communicate the device data.

[0276] At block **959**, the electronic device can allow or cause the private device data to be communicated to remote computing devices. For example, the electronic device can cause a communication component of the electronic device to communicate the device data.

Communicating the device data can include transmitting the device data (for example, wirelessly) to one or more remote computing devices or servers. The electronic device can communicate the private device data over a secure channel. Communicating data over a secure channel can inhibit eavesdropping (e.g., to preserve confidentiality) and/or can inhibit data tampering (e.g., to preserve authenticity). Communicating data over a secure channel can include relying on a trusted third party. For example, the electronic device can communicate data to a trusted third party device which can in turn communicate the data to a destination computing device. A trusted third party can be a certificate authority (CA) that issues certificates indicating its security. The electronic device can communicate private data to a trusted third party responsive to receiving a security certificate from the trusted third party indicating the third party can be trusted to manage data communication securely. Communicating data over a secure channel can include the communicating parties relying on trust between them. For example, the electronic device can communicate data to a receiving computing device with a key exchange protocol, such as a D-H key exchange protocol. For example, the electronic device and the receiving computing device can exchange information between them that is useable and/or combinable to generate a key that is only known to them that can be used to communicate data between them. The electronic device can encrypt the private device data prior to communicating the device data, even when communicating the data over a secure channel. Thus, the electronic device can communicate encrypted data over a secure channel.

[0277] Device metadata can persist across devices. For example, device data metadata can continue to exist on a receiving computing device after the device data is communicated from the electronic device to the receiving computing device. A receiving computing device can determine the privacy status of device data based on its metadata and can manage the data appropriately, including storing the data in a certain location based on its privacy status, displaying the data with an indication to indicate it is private, etc.

[0278] At block **960**, the electronic device can allow or cause the non-private device data to be communicated to remote computing devices. For example, the electronic device can cause a communication component of the electronic device to communicate the device data.

Communicating the device data can include transmitting the device data (for example, wirelessly) to one or more remote computing devices or servers. The electronic device can communicate non-private device data over a secure channel or in some implementations can communicate non-private device data over an insecure channel which can be subject to eavesdropping and/or tampering. Communicating data over an insecure channel can improve communication speed, reduce processing requirements, and/or improve computational efficiency. In some implementations, the electronic device can communicate non-private device data over an authentic channel (which can be resistant to tampering but which can be subject to eavesdropping). In some implementations, the electronic device can communicate non-private device data over a confidential channel (which can be resistant to eavesdropping but which can be subject to tampering). The electronic device can encrypt non-private device data prior to communicating said data. Thus, the electronic device can securely communicate the encrypted non-private device data over an insecure channel.

[0279] Process **950** is provided as an example and is not intended to be limiting of the present disclosure. In some implementations, the processor can communicate and/or not communicate device data regardless of whether the device data is private.

[0280] FIG. **10** is a perspective view illustrating an example implementation of an actuator **1001**. The actuator **1001** can include similar structural and/or operational features as any of the other example actuators shown and/or discussed herein. The actuator **1001** can be implemented in an electronic device such as any of the example electronic devices shown and/or discussed herein. The actuator **1001** can include a first portion **1003** and a second portion **1005**. The first portion **1003** can include a first coloring or shading such as red, orange, yellow, green, blue, purple, black, gray, white, brown, or any other color or shade. The second portion can include a second coloring or

shading such as red, orange, yellow, green, blue, purple, black, gray, white, brown, or any other color or shade. In some implementations, the first portion **1003** can include a same coloring or shading as the second portion. In some implementations, the first portion **1003** can include a different coloring or shading than the second portion.

[0281] The first portion **1003** can be visible when the actuator **1001** is in a certain state and may not be visible when the actuator **1001** is in another state. For example, the first portion **1003** can be exposed to an exterior surface when in one state and not exposed to an exterior surface when in another state. The second portion **1005** can be visible when the actuator **1001** is in a certain state and may not be visible when the actuator **1001** is in another state. The first portion **1003** may not be visible when the second portion **1005** is visible and vice versa.

[0282] FIGS. **11A-11D** illustrate an electronic device **1100** with display screen **1112** showing example user interfaces **1113A-1113D**. The display screen **1112** can be a digital displays such as LED and/or LCD displays. A hardware processor, such as any of the example hardware processors shown and/or described herein, can generate user interface data for rendering the user interfaces **1113A-1113D** shown and/or described in FIGS. **11A-11D**. In some implementations, a dedicated controller (e.g., controller **822** shown and/or described herein) can cause a hardware processor to generate user interface data for rendering any portions of user interfaces **1113A-1113D**.

[0283] As shown in FIG. **11A**, the user interface **1113A** can display time, such as an analog watch face, date, and indicia of physiological data such as icons and physiological parameters such as heart rate, step counter, pulse rate, respiration rate, SpO2, etc. The user interface **1113A** can be displayed during a non-privacy mode.

[0284] As shown in FIG. **11B**, the user interface **1113B** can include a first indication **1101** that the electronic device has entered a privacy mode. The first indication **1101** can indicate to a user what will happen to certain data during the privacy mode. The user interface **1113B** can include a second indication **1103** to indicate that the electronic device is in a privacy mode. The second indication **1103** can be a symbol. The first indication **1101** and/or second indication **1103** can be displayed responsive to first entering a privacy mode, such as for the first 10 seconds of privacy mode, for the first minute of privacy mode, etc. In some implementations, a dedicated controller (e.g., controller **822** shown and/or described herein) can cause electronic device **1100** to display first indication **1101** and/or second indication **1103** such as by instructing a hardware processor to generate user interface data for rendering first indication **1101** and/or second indication **1103**. Controlling the display of first indication **1101** and/or second indication **1103** with a dedicated controller can advantageously prevent electronic device **1100** from erroneously displaying first indication **1101** and/or second indication **1103** (e.g., when not in a privacy mode) such as if the electronic device **1100** is hacked. As discussed, a dedicated controller can be impervious to hacking at least because a dedicated controller may be non-programmable. A hardware processor, such as device processor **825** shown and/or described herein, may not control whether certain portions of user interfaces are displayed (and a dedicated controller may have sole control over displaying those portions) although, in some cases, the device processor may be involved in generating user interface data for rendering those portions responsive to instructions to do so. In some implementations, the dedicated controller can generate user interface data for rendering portions of user interfaces.

[0285] As shown in FIG. **11C**, the user interface **1112C** can include time, date, and indicia of physiological data such as icons and/or physiological parameters such as heart rate and step counter. The user interface **1112C** can be displayed during a privacy mode. The indicia of physiological data can correspond to real-time data originating from physiological sensors on the electronic device **1100** during the privacy mode. Advantageously, a user can continue to view and monitor their physiological status during a privacy mode. The user interface **1112C** can include a first indication **1105** that the electronic device is in a privacy mode. The first indication **1105** can be annular or semi-annular. In some implementations, the first indication **1105** can be rectangular. The first indication **1105** can surround user interface **1112C** around a perimeter of user interface **1112C**.

The first indication **1105** can circumscribe display and/or watch face. In some implementations, the display screen **1112** can display the first indication **1105** for an entire duration of a privacy mode. In some implementations, the display screen **1112** can display the first indication **1105** only upon activation of the privacy mode. For example, the display screen **1112** can display the first indication **1105**, for a length of time after entering privacy mode and may not display the first indication **1105** for an entire duration of the privacy mode. The user interface **1112C** can include a second indication **1107** that the electronic device is in a privacy mode. The display screen **1112** can display the second indication **1107** for an entire duration of the privacy mode. In some implementations, a dedicated controller (e.g., controller **822** shown and/or described herein) can cause electronic device **1100** to display indications **1105** and/or **1107** such as by instructing a hardware processor to generate user interface data for rendering indications **1105** and/or **1107**. Controlling the display of indications **1105** and/or **1107** with a dedicated controller can advantageously prevent electronic device **1100** from erroneously displaying indications **1105** and/or **1107** (e.g., when not in a privacy mode) such as if the electronic device **1100** is hacked.

[0286] As shown in FIG. **11D**, the display screen **1112** can display time, date, and indicia of physiological data such as icons and/or physiological parameters such as heart rate and step counter which can correspond to real-time physiological data and/or historical physiological data. The user interface **1113D** can include an indication **1109**. In some implementations, the indication **1109** can indicate that the electronic device is currently in a privacy mode. The display screen **1112** can display the indication **1109** for an entire duration of the privacy mode. In some implementations, the indication **1109** can indicate that indicia of physiological data displayed on the display screen **1112** (e.g., heart rate, step counter) corresponds to physiological data that was generated during a privacy mode (e.g., is private data). Electronic device **1100** can cause display screen **1112** to display indication **1109** only when private data is displayed. In some implementations, the indicia of physiological data displayed on the display screen **1112D** (e.g., heart rate, step counter) corresponds to physiological data originating from another electronic device and received at the electronic device **1100** (e.g., via wireless communication). The electronic device **1100** can determine that physiological data originating from another electronic device is private (and can thus display the indication **1109**) based on metadata of the physiological data, as discussed herein. In some implementations, a dedicated controller (e.g., controller **822** shown and/or described herein) can cause electronic device **1100** to display indication **1109** such as by instructing a hardware processor to generate user interface data for rendering indication **1109**. Controlling the display of indication **1109** with a dedicated controller can advantageously prevent electronic device **1100** from erroneously displaying indication **1109** (e.g., when displayed data is not private data) such as if the electronic device **1100** is hacked.

[0287] FIG. **12** illustrates an example electronic device **1200** implemented as a soundbar. The electronic device **1200** can include one or more speakers **1213** (e.g., speaker **1213A**, speaker **1213B**), a camera **1203**, and an actuator **1201** (which may also be referred to as a privacy switch). The speakers **1213** can emit audio. The camera **1203** can collect images. The electronic device **1200** can communicate with separate devices via a wireless communication protocol. For example, the electronic device **1200** can communicate images captured by the camera **1203** to separate computing devices. As another example, the electronic device **1200** can cause the speakers **1213** to emit audio that is received from separate computing devices. The actuator **1201** can control one or more operations of the electronic device **1200** to secure a user's data. For example, actuation of the actuator **1201** can enable/disable the camera **1203** to inhibit the camera **1203** from capturing images. As another example, the actuation of the actuator **1201** can allow/inhibit the electronic device **1200** from communicating with separate devices to send and/or receive data from separate devices. In some aspects, actuation of the actuator **1201** may not affect operation of some components of the electronic device **1200** such as the speakers **1213**.

[0288] FIG. **13** illustrates a perspective view of an example electronic device **1300** implemented as

a mobile phone. In this example, the electronic device **1300** includes a display **1312** which can be a touch screen, an audio control **1354**, a control button **1356**, a microphone **1366**, a camera **1360**, a pairing button **1364** for establishing wireless connectivity with separate devices, and a speaker **1362**. The electronic device **1300** can also include an actuator **1301** that can facilitate the protection of a user's data. The actuator **1301** can be a slideable switch or a button. The electronic device **1300** can include fewer, additional, or different components. The electronic device **1300** can communicate with other separate devices via a wireless communication protocol. Actuation of the actuator **1301** can enable/inhibit the electronic device **1300** from communicating with separate computing devices. In some implementations, actuation of the actuator **1301** can disable one or more components of the electronic device such as the camera **1360** and/or the microphone **1366**. In some cases, actuation of the actuator **1301** may not affect operation of some components of the electronic device **1300** such as the display **1312** and/or the speaker **1362**. In some implementations, actuation of the actuator **1301** can disable the electronic device **1300** from communicating with separate devices.

[0289] FIG. **14** illustrates an example electronic device **1400** implemented as a monitoring hub (which may also be referred to as a tablet, a health monitoring device, a display device, etc.). Electronic device **1400** can include a display **1412**, a status indicator **1403**, a microphone **1413**, a camera **1415**, and an actuator **1401**. Display **1412** can display indicia of physiological data such as charts, trend lines, graphs, physiological parameters, gauges, dials, alerts, notifications, medication protocol, or other health related information. Microphone **1413** can detect audio. Camera **1415** can collect images. Status indicator **1403** can indicate a status of the electronic device **1400** including whether the electronic device **1400** is in a privacy mode or a non-privacy and/or what type of privacy mode the electronic device **1400** is in. Actuator **1401** can enable/disable a privacy mode of the electronic device **1400**. For example, actuation of the actuator **1401** can disable one or more components of the electronic device **1400** such as the microphone **1413** and/or the camera **1415**. As another example, actuation of the actuator **1401** can disable communication of the electronic device **1400** with separate computing devices. In some implementations, actuation of the actuator **1401** may not affect operation of at least some of the components of the electronic device such as the display **1412** and/or the status indicator **1403**.

Additional Considerations

[0290] Certain categories of persons, such as caregivers, clinicians, doctors, nurses, and friends and family of a user, may be used interchangeably to describe a person providing care to the user. Furthermore, patients or users used herein interchangeably refer to a person who is wearing a sensor or is connected to a sensor or whose measurements are used to determine a physiological parameter or a condition. Parameters may be, be associated with, and/or be represented by, measured values, display icons, alphanumeric characters, graphs, gages, power bars, trends, or combinations. Real time data may correspond to active monitoring of a user, however, such real time data may not be synchronous to an actual physiological state at a particular moment. Measurement value(s) of a parameter and the parameter used herein such as, SpO₂, RR, PaO₂ and the like, unless specifically stated otherwise, or otherwise understood with the context as used is generally intended to convey a measurement or determination that is responsive to the physiological parameter.

[0291] Although certain implementations and examples have been described herein, it will be understood by those skilled in the art that many aspects of the systems and devices shown and described in the present disclosure may be differently combined and/or modified to form still further implementations or acceptable examples. All such modifications and variations are intended to be included herein within the scope of this disclosure. A wide variety of designs and approaches are possible. No feature, structure, or step disclosed herein is essential or indispensable. The various features and processes described herein may be used independently of one another, or may be combined in various ways. For example, elements may be added to, removed from, or

rearranged compared to the disclosed example implementations. All possible combinations and sub-combinations are intended to fall within the scope of this disclosure.

[0292] Any methods and processes described herein are not limited to any particular sequence, and the blocks or states relating thereto can be performed in other sequences that are appropriate. For example, described blocks or states may be performed in an order other than that specifically disclosed, or multiple blocks or states may be combined in a single block or state, or certain method or process blocks may be omitted, or certain blocks or states may be performed in a reverse order from what is shown and/or described. The example blocks or states may be performed in serial, in parallel, or in some other manner. Blocks or states may be added to or removed from the disclosed example implementations.

[0293] The methods disclosed herein may include certain actions taken by a practitioner; however, they can also include any third-party instruction of those actions, either expressly or by implication.

[0294] The methods and tasks described herein may be performed and fully automated by a computer system. The computer system may, in some cases, include multiple distinct computers or computing devices (e.g., physical servers, workstations, storage arrays, cloud computing resources, etc.) that communicate and interoperate over a network to perform the described functions. The computer system may, in some cases, include a single computing device, processor, controller, or the like. Each such computing device typically includes a processor (or multiple processors) that executes program instructions or modules stored in a memory or other non-transitory computer-readable storage medium or device (e.g., solid state storage devices, disk drives, etc.). The various functions disclosed herein may be embodied in such program instructions, and/or may be implemented in application-specific circuitry (e.g., ASICs or FPGAs) of the computer system. Where the computer system includes multiple computing devices, these devices may, but need not, be co-located. The results of the disclosed methods and tasks may be persistently stored by transforming physical storage devices, such as solid state memory chips and/or magnetic disks, into a different state. The computer system may be a cloud-based computing system whose processing resources are shared by multiple distinct entities or other users. The systems and modules may also be transmitted as generated data signals (for example, as part of a carrier wave or other analog or digital propagated signal) on a variety of computer-readable transmission mediums, including wireless-based and wired/cable-based mediums, and may take a variety of forms (for example, as part of a single or multiplexed analog signal, or as multiple discrete digital packets or frames).

[0295] Many other variations than those described herein will be apparent from this disclosure. For example, depending on the implementation, certain acts, events, or functions of any of the algorithms described herein can be performed in a different sequence, can be added, merged, or left out altogether (for example, not all described acts or events are necessary for the practice of the algorithms). Moreover, in certain implementations, acts or events can be performed concurrently, for example, through multi-threaded processing, interrupt processing, or multiple processors or processor cores or on other parallel architectures, rather than sequentially. In addition, different tasks or processes can be performed by different machines and/or computing systems that can function together.

[0296] Various illustrative logical blocks, modules, routines, and algorithm steps that may be described in connection with the disclosure herein can be implemented as electronic hardware (e.g., ASICs or FPGA devices), computer software that runs on computer hardware, or combinations of both. Various illustrative components, blocks, and steps may be described herein generally in terms of their functionality. Whether such functionality is implemented as specialized hardware versus software running on general-purpose hardware depends upon the particular application and design constraints imposed on the overall system. The described functionality can be implemented in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the disclosure.

[0297] Moreover, various illustrative logical blocks and modules that may be described in

connection with the implementations disclosed herein can be implemented or performed by a machine, such as a general purpose processor, a digital signal processor (“DSP”), an application specific integrated circuit (“ASIC”), a field programmable gate array (“FPGA”) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor can be a microprocessor, controller, microcontroller, or state machine, combinations of the same, or the like. A processor can include electrical circuitry configured to process computer-executable instructions. A processor can include an FPGA or other programmable devices that performs logic operations without processing computer-executable instructions. A processor can also be implemented as a combination of computing devices, for example, a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. Although described herein primarily with respect to digital technology, a processor may also include primarily analog components. For example, some, or all, of the signal processing algorithms described herein may be implemented in analog circuitry or mixed analog and digital circuitry. A computing environment can include any type of computer system, including, but not limited to, a computer system based on a microprocessor, a mainframe computer, a digital signal processor, a portable computing device, a device controller, or a computational engine within an appliance, to name a few.

[0298] The elements of any method, process, routine, or algorithm described in connection with the disclosure herein can be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. A software module can reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of non-transitory computer-readable storage media. An exemplary storage medium can be coupled to the processor such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium can be integral to the processor. The storage medium can be volatile or nonvolatile. The processor and the storage medium can reside in an ASIC. The ASIC can reside in a user terminal. In the alternative, the processor and the storage medium can reside as discrete components in a user terminal.

[0299] Conditional language used herein, such as, among others, “can,” “could,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain features, elements, and/or steps are optional. Thus, such conditional language is not generally intended to imply that features, elements, and/or steps are in any way required or that one or more embodiments necessarily include logic for deciding, with or without other input or prompting, whether these features, elements, and/or steps are included or are to be always performed. The terms “comprising,” “including,” “having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list. Further, the term “each,” as used herein, in addition to having its ordinary meaning, can mean any subset of a set of elements to which the term “each” is applied.

[0300] Conjunctive language such as the phrase “at least one of X, Y, and Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to convey that an item, term, etc. may be either X, Y, or Z. Thus, such conjunctive language is not generally intended to imply that certain embodiments require the presence of at least one of X, at least one of Y, and at least one of Z.

[0301] Language of degree used herein, such as the terms “approximately,” “about,” “generally,” and “substantially” as used herein represent a value, amount, or characteristic close to the stated value, amount, or characteristic that still performs a desired function or achieves a desired result.

For example, the terms “approximately”, “about”, “generally,” and “substantially” may refer to an amount that is within less than 10% of, within less than 5% of, within less than 1% of, within less than 0.1% of, and within less than 0.01% of the stated amount. As another example, in certain embodiments, the terms “generally parallel” and “substantially parallel” refer to a value, amount, or characteristic that departs from exactly parallel by less than or equal to 10 degrees, 5 degrees, 3 degrees, or 1 degree. As another example, in certain embodiments, the terms “generally perpendicular” and “substantially perpendicular” refer to a value, amount, or characteristic that departs from exactly perpendicular by less than or equal to 10 degrees, 5 degrees, 3 degrees, or 1 degree.

[0302] As used herein, “real-time” or “substantial real-time” may refer to events (e.g., receiving, processing, transmitting, displaying etc.) that occur at a same time as each other, during a same time as each other, or overlap in time with each other. “Real-time” may refer to events that occur at distinct or non-overlapping times the difference between which is imperceptible and/or inconsequential to humans such as delays arising from electrical conduction or transmission. A human may perceive real-time events as occurring simultaneously, regardless of whether the real-time events occur at an exact same time. As a non-limiting example, “real-time” may refer to events that occur within a time frame of each other that is on the order of milliseconds, seconds, tens of seconds, or minutes. For example, “real-time” may refer to events that occur within a time frame of less than 1 minute, less than 30 seconds, less than 10 seconds, less than 1 second, less than 0.05 seconds, less than 0.01 seconds, less than 0.005 seconds, less than 0.001 seconds, etc.

[0303] Unless otherwise explicitly stated, articles such as “a” or “an” should generally be interpreted to include one or more described items. Accordingly, phrases such as “a device configured to” are intended to include one or more recited devices. Such one or more recited devices can also be collectively configured to carry out the stated recitations. For example, “a processor configured to carry out recitations A, B and C” can include a first processor configured to carry out recitation A working in conjunction with a second processor configured to carry out recitations B and C.

[0304] As used herein, “system,” “instrument,” “apparatus,” and “device” generally encompass both the hardware (for example, mechanical and electronic) and, in some implementations, associated software (for example, specialized computer programs for operational control) components.

[0305] It should be emphasized that many variations and modifications may be made to the herein-described implementations, the elements of which are to be understood as being among other acceptable examples. All such modifications and variations are intended to be included herein within the scope of this disclosure. Any section headings used herein are merely provided to enhance readability and are not intended to limit the scope of the implementations disclosed in a particular section to the features or elements disclosed in that section. The foregoing description details certain implementations. It will be appreciated, however, that no matter how detailed the foregoing appears in text, the systems and methods can be practiced in many ways. As is also stated herein, it should be noted that the use of particular terminology when describing certain features or aspects of the systems and methods should not be taken to imply that the terminology is being re-defined herein to be restricted to including any specific characteristics of the features or aspects of the systems and methods with which that terminology is associated.

[0306] Those of skill in the art would understand that information, messages, and signals may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

[0307] While the above detailed description has shown, described, and pointed out novel features, it can be understood that various omissions, substitutions, and changes in the form and details of

the devices or algorithms illustrated can be made without departing from the spirit of the disclosure. As can be recognized, certain portions of the description herein can be embodied within a form that does not provide all of the features and benefits set forth herein, as some features can be used or practiced separately from others. The scope of certain embodiments disclosed herein is indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

Claims

1. A wearable electronic device for protecting private data, comprising: one or more physiological sensors configured to generate sensor data indicating a physiological status of a user of the wearable electronic device; a device processor electrically connected with the one or more physiological sensors and configured to access the sensor data; an actuator disposed on the wearable electronic device configured to change states responsive to user input; and a controller electrically connected with the device processor and the actuator, the controller configured to: monitor the state of the actuator; responsive to determining that the actuator is in a privacy state, communicate a notification signal to the device processor to cause the device processor to prepare for a privacy mode, wherein the device processor is configured to terminate one or more processes responsive to the notification signal from the controller to prepare for the privacy mode; delay implementing the privacy mode until one or more conditions have been satisfied to allow the device processor to prepare for the privacy mode pursuant to communicating the notification signal to the device processor; and implement the privacy mode to inhibit access to the sensor data responsive to satisfaction of the one or more conditions.
2. The wearable electronic device of claim 1, wherein the device processor is configured to provide confirmation to the controller when the one or more processes have been terminated, wherein the one or more conditions comprise receiving the confirmation at the controller from the device processor that the one or more processes have been terminated.
3. The wearable electronic device of claim 1, wherein the controller is configured to initiate a timer pursuant to determining that the actuator is in the privacy state, wherein the one or more conditions include the timer exceeding a threshold.
4. The electronic device of claim 3, wherein the controller is configured to initiate the timer in response to communicating the notification signal to the device processor.
5. The wearable electronic device of claim 3, wherein the controller is configured to implement the privacy mode responsive to the timer exceeding the threshold regardless of whether the one or more processes have been terminated.
6. The wearable electronic device of claim 1, wherein the controller is configured to implement the privacy mode based on disconnecting a privacy component of the wearable electronic device from a power source, the privacy component comprising one or more of a communication component, a GNSS component, a microphone, a camera, or an altimeter.
7. The wearable electronic device of claim 1, wherein the controller is configured to implement the privacy mode based on holding a privacy component of the wearable electronic device in a reset mode, the privacy component comprising one or more of a communication component, a GNSS component, a microphone, a camera, or an altimeter.
8. The wearable electronic device of claim 1, wherein the controller is non-programmable.
9. The wearable electronic device of claim 1, wherein the device processor is electrically isolated from the actuator and does not read the state of the actuator.
10. The wearable electronic device of claim 1, further comprising a display screen configured to display indicia responsive to implementing the privacy mode, wherein the display screen is configured to display the indicia throughout the privacy mode.
11. The wearable electronic device of claim 10, wherein the controller is configured to cause the

indicia to be displayed on the display screen.

12. A method of implementing privacy on an electronic device, comprising: generating sensor data with one or more physiological sensors, the sensor data indicating a physiological status of a user of the electronic device; causing an actuator of the electronic device to change states responsive to user input; monitoring the state of the actuator with a controller electrically connected with the actuator; responsive to determining that the actuator is in a privacy state, communicating a notification signal from the controller to a device processor to cause the device processor to prepare for a privacy mode; terminating one or more processes with the device processor responsive to the notification signal from the controller to prepare for the privacy mode; delaying implementing the privacy mode until one or more conditions have been satisfied to allow the device processor to prepare for the privacy mode; and implementing the privacy mode to inhibit access to the sensor data responsive to satisfaction of the one or more conditions.

13. The method of claim 12, wherein the one or more conditions comprise receiving confirmation at the controller from the device processor that the one or more processes have been terminated.

14. The method of claim 12, further comprising initiating a timer pursuant to determining that the actuator is in the privacy state, wherein the one or more conditions include the timer exceeding a threshold.

15. The method of claim 12, further comprising implementing the privacy mode based on disconnecting a privacy component of the electronic device from a power source, the privacy component comprising one or more of a communication component, a GNSS component, a microphone, a camera, or an altimeter.

16. The method of claim 12, further comprising implementing the privacy mode based on holding a privacy component of the electronic device in a reset mode, the privacy component comprising one or more of a communication component, a GNSS component, a microphone, a camera, or an altimeter.

17. Non-transitory computer-readable media including computer-executable instructions that, when executed by a computing system, cause the computing system to perform operations comprising: monitoring a state of an actuator configured to change states responsive to user input; responsive to determining that the actuator is in a privacy state, causing a device processor to prepare for a privacy mode by terminating one or more processes; delaying implementing the privacy mode until one or more conditions have been satisfied to allow the device processor to terminate the one or more processes; and implementing the privacy mode to inhibit access to sensor data responsive to satisfaction of the one or more conditions.

18. The non-transitory computer-readable media of claim 17, wherein the computer-executable instructions, when executed by the computing system, cause the computing system to perform operations comprising: implementing the privacy mode when the one or more processes have been terminated, wherein the one or more conditions include termination of the one or more processes.

19. The non-transitory computer-readable media of claim 17, wherein the computer-executable instructions, when executed by the computing system, cause the computing system to perform operations comprising: initiating a timer pursuant to determining that the actuator is in the privacy state; and implementing the privacy mode when the timer exceeds a threshold, wherein the one or more conditions include the timer exceeding the threshold.

20. The non-transitory computer-readable media of claim 17, wherein the computer-executable instructions, when executed by the computing system, cause the computing system to perform operations comprising: implementing the privacy mode based on disconnecting a privacy component from a power source and/or holding the privacy component in a reset mode, the privacy component comprising one or more of a communication component, a GNSS component, a microphone, a camera, or an altimeter.
