

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279606

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

IVANOV; Ivan et al.

Contacting Assembly

Abstract

Contacting assembly for arrangement between two electrical components. The contacting assembly that is easy to manufacture and to install. The contacting assembly is configured for arrangement between two electrical components, which comprises a carrier and at least one contact spring unit, wherein the at least one contact spring unit comprises a holding section and contact spring tongues, wherein the contact spring tongues extend from opposite sides of the carrier and are connected with each other via the holding section and wherein the holding section clasps the carrier in sections and is frictionally held on the carrier.

Inventors: IVANOV; Ivan (Schaffhausen, CH), FERTIG; Jochen (Schaffhausen, CH), BUCHHOLZ; Ron (Schaffhausen, CH), SCHWINDT; Jens (Schaffhausen, CH), BURGHARD; Michael (Schaffhausen, CH)

Applicant: TE Connectivity Solutions GmbH (Schaffhausen, CH)

Family ID: 94826178

Assignee: TE Connectivity Solutions GmbH (Schaffhausen, CH)

Appl. No.: 19/064776

Filed: February 27, 2025

Foreign Application Priority Data

DE 102024106044.1

Mar. 01, 2024

Publication Classification

Int. Cl.: H01R13/24 (20060101)

U.S. Cl.:

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to and the benefit of German Patent Application No. 102024106044.1 filed Mar. 1, 2024, which is hereby incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

[0002] Contacting assembly for arrangement between two electrical components, wherein the contacting assembly comprises a carrier and at least one contact spring unit, wherein the at least one contact spring unit comprises a holding section and contact spring tongues and is frictionally held on the carrier.

[0003] Contacting assemblies with contact spring units are used, for example, to establish an electrical contact and to shield electrical components against electromagnetic interferences.

[0004] Such contacting assemblies can, for example, be constructed monolithically. However, a monolithic design usually lacks the flexibility to adapt to a mounting surface. Therefore, in addition to the monolithically constructed component, other components such as spacer sleeves are often required, which eliminates the one-piece structure and the associated advantages and increases costs again. The selection of materials is limited due to the manufacturing method.

[0005] In another typical manufacturing method for a contacting assembly, individual contact springs are inserted into a carrier using stitching. Although the carrier may be made of a different material than the contact springs, the insertion of individual contact springs is, however, complex and highly dependent on the—usually delicate—geometries of the mating pair when using a stitching machine. Furthermore, additional design elements are required for stitching, which further increases the complexity of the design, in particular the contact spring design. Another disadvantage of a stitching design is the often inadequate electromagnetic compatibility.

SUMMARY OF THE INVENTION

[0006] The problem underlying the invention is to provide a contacting assembly that is easy to manufacture and assemble.

[0007] The present invention solves this problem by manufacturing a contacting assembly for arrangement between two electrical components, comprising a carrier and at least one contact spring unit, wherein the at least one contact spring unit comprises a holding section and contact spring tongues, and wherein the contact spring tongues extend from opposite sides of the carrier and are connected with each other via the holding section, and wherein the holding section clasps the carrier in sections and is frictionally held on the carrier.

[0008] Furthermore, the problem is solved by an arrangement with such a contacting assembly and two electrical components, wherein the contacting assembly is located between the two electrical components in the operating state, wherein the contact spring tongues of the two electrical components are elastically, in particular predominantly elastically, deformed towards the carrier and press the holding section against the carrier and the clamping force applied by the holding section to the carrier is thus increased.

[0009] These solutions allow an easy assembly and manufacturing of the contacting assembly, which, compared to stitching, requires no additional tools and no tight tolerances, which increases efficiency and reduces costs. The solutions mentioned are suitable for use in both manual and automated processes and allow more flexibility in the selection of materials for the carrier and contact spring unit, as well as for mounting the contacting assembly on any mounting surface as a monolithic design.

[0010] The invention can be further improved by the following configurations, each of which is

preferred on its own and can be arbitrarily combined with each other.

[0011] In a preferred embodiment, the carrier can be plate-shaped. In this case, the carrier can be configured in particular as a plate or a disc. The carrier can be arbitrarily adapted in its form to a predetermined mounting surface and provided with recesses and mounting holes, such as holes that accept screw, pin and/or rivet connections or serve to save material, which allows a high degree of flexibility in the design and adaptation of the carrier to different applications. Likewise, the carrier can be preferably designed as a frame to save material and weight and, for example, have at least one large through-opening in the center. In particular, this allows further configurations and constellations of the contacting assembly with other assemblies, for example, an assembly can be provided within the frame.

[0012] The carrier can be made of one material or a combination of different materials and, in particular, can have a different material from the contact spring unit. For example, the carrier can be made of an electrically non-conductive plastic.

[0013] An injection molding process can be used to manufacture the carrier, which reduces production costs.

[0014] The section of the carrier that is clasped by the holding section can be a flange section that is formed by an edge of the carrier and extends away from a center section of the carrier. In this case, the flange section can have a smaller material thickness than the area of the carrier adjacent to the center of the carrier, in order to be mounted more easily and to reduce the space required.

[0015] To enable a high degree of flexibility and adaptability to a wide range of applications, the carrier sides, in particular all four narrow sides of the carrier, can be used for attaching contact spring units. Likewise, the flat sides of the carrier can be used for attaching contact spring units.

[0016] The contact spring unit can be pushed onto the flange section. Likewise, the contact spring unit can be pressed onto the flange section to establish a secure and backlash-free connection.

[0017] Alternatively, the contact spring unit can have a clamp connection with the flange section and be clamped with clamping elements such as screws or wedges, which offers the advantage of easy adjustability. A clamp connection with clamping lugs is also possible.

[0018] The contact spring unit can be configured as a contact spring strip and can have a plurality of contact spring tongues or, equivalently, contact spring lamellae, in particular in a monolithic design. In one configuration, the contact spring tongues are arranged next to one another. The contact spring strip can be a stamped and bent part. The plurality of contact spring tongues can be in pairs opposite one another.

[0019] The contact spring unit can have a band-shaped or, equivalently, strip-shaped material connection that connects the contact spring tongues to one another. The material connection can extend in particular along the carrier, in particular along the edge or the flange section. The material connection can particularly extend along the edge or the flange section that is clasped by the holding section. The material connection prevents interruptions between the individual contact spring tongues, which increases the electromagnetic compatibility of such an assembly when installed compared to stitching. The material connection ensures the structural integrity of the contact spring unit.

[0020] The contact spring strip can have any number of contact spring tongues. The number of contact spring tongues depends in particular on the respective application.

[0021] For easy manufacturing of the contact spring unit, the holding section can be configured to be continuous, i.e. uninterrupted. The holding section can also be provided with material interruptions between two contact spring tongues arranged next to each other in order to reduce the force required for pressing on.

[0022] The holding section of the contact spring unit can have two opposing legs in cross-section. At their ends located towards the center section of the carrier, the legs of the holding section can each merge into a contact spring tongue. This transition of the legs of the holding section to one contact spring tongue each can be made in a radius. Alternatively, the transition can be bent or

kinked. This monolithic design is stable under mechanical loads or vibrations.

[0023] The legs of the holding section can be formed by the material connection. Alternatively, the holding section can also be constructed from individual clamping sections that extend away from the material connection and are each spaced apart from one another in the direction along the material connection. Each of these clamping sections can continue into a contact spring tongue. In this case, the clamping sections can run parallel to one another.

[0024] The holding section can have a U-, V-, C- or at least an approximately omega-shaped cross-section. For example, the material connection can be bent into a U-, V-, C- or at least an approximately omega-shape.

[0025] To ensure sufficient pressing on the flange section, the holding section can have a clear width that is smaller in the force-free state than a material thickness of the carrier in the area clamped by the holding section. It is preferred if the holding section is bent beforehand, creating a preload that allows a lower contact pressure.

[0026] The at least two contact spring tongues of the contact spring unit can be elastically deflected and can be located opposite each other with respect to the flange section. The free ends of the contact spring tongues can, in this case, point away from the center section of the carrier and be spaced apart from the holding section. The directed force presses the contact spring tongues and the holding section connected to them against the carrier.

[0027] The contact spring tongues can be arranged alternately above and below the carrier or in pairs opposite each other along the edge of the carrier.

[0028] Above and below the carrier or on both sides of the material connection, the contact spring tongues can have the same length. Alternatively, the contact spring tongues that extend on one side of the carrier or material connection can have a different length than the contact spring tongues that extend on the other side of the carrier, which is preferred for meeting predetermined space requirements and for compensating manufacturing and/or assembly tolerances.

[0029] In addition to the frictional connection, the carrier can be connected to the contact spring unit via a form-fit connection. For this purpose, the contact spring unit can be provided with at least one form-fit element. At least one form-fit element of the form-fit connection can, for example, be formed by the carrier edge and be in engagement or be brought into engagement with the at least one form-fit element of the at least one contact spring unit.

[0030] In one configuration, the form-fit element of the carrier can be located on the flange section. The at least one form-fit element of the contact spring unit can be part of the contact spring strip. This form-fit connection can be completely decoupled from the functional connection between the contact spring unit and the carrier and can be used, for example, as assembly protection for transporting the contacting assembly. In particular, the form-fit element of the contact spring unit can be formed by the material connection.

[0031] In a further configuration, the carrier can have spacers that extend away from at least one of the two flat sides of the carrier. In one configuration, the spacers cannot protrude beyond the contact spring tongues in the direction pointing away from the respective flat side in the force-free state. The spacers can minimize overloading of the contact spring tongues and prevent the contact spring tongues from being compressed too far. The spacers can thus act as an overstretch protection for the contact spring tongues.

[0032] Furthermore, the at least one spacer can be configured as contact force limitation, which limits the contact force of a contact spring tongue to a certain amount or range, which is reached at the level of the spacer.

[0033] In a preferred embodiment, the contacting assembly can comprise a plurality of contact spring strips that are arranged next to one another and/or on two opposite narrow sides of the carrier, spaced apart from one another. It is also conceivable that the contact spring strips are arranged in multiple rows on the carrier and that the contact spring strips are arranged on at least one or on two or more sides of the carrier that are not opposite one another.

[0034] Another configuration provides for the arrangement of the contacting assembly and two electrical components. In the assembled state, the contacting assembly can be located between the two electrical components. The contact spring tongues can be elastically, in particular predominantly elastically, deformed from the two electrical components towards the carrier. The holding section of the contact spring units is pressed against the carrier. This increases the clamping force applied by the holding section to the carrier. As a result, the frictional engagement is increased in a preferred manner.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0035] In the following, the invention is described by way of example with reference to the drawings based on several embodiments. In doing so, the same reference signs are always used in the drawings for elements that correspond to one another in terms of function and/or structure.

[0036] In accordance with the description above, a feature of the embodiment can be omitted if the technical effect associated with that feature is not important for a particular application. Conversely, a feature not yet present can also be added to the embodiment in accordance with the description above if the technical effect of the feature to be added is important for a particular application.

[0037] It is shown by:

[0038] FIG. 1 an illustration of the contacting assembly;

[0039] FIG. 2 a side view of a contact spring unit with the holding section between the two contact spring tongues;

[0040] FIG. 3 an illustration of the contacting assembly with the configuration of the spacer;

[0041] FIG. 4 an illustration of the contacting group with a frame as carrier;

[0042] FIG. 5 an illustration of the arrangement of the contacting assembly between two electrical components; and

[0043] FIG. 6 an illustration of the contacting assembly with contact spring units on all narrow sides.

DETAILED DESCRIPTION

[0044] The description of illustrative embodiments according to principles of the present invention is intended to be read in connection with the accompanying drawings, which are to be considered part of the entire written description. In the description of embodiments of the invention disclosed herein, any reference to direction or orientation is merely intended for convenience of description and is not intended in any way to limit the scope of the present invention. In various applications, relative terms such as “lower,” “upper,” “horizontal,” “vertical,” “above,” “below,” “up,” “down,” “top” and “bottom” as well as derivative thereof (e.g., “horizontally,” “downwardly,” “upwardly,” etc.) should be construed to refer to the orientation as then described or as shown in the drawing under discussion. These relative terms are for convenience of description only and do not require that the apparatus be constructed or operated in a particular orientation unless explicitly indicated as such. Terms such as “attached,” “affixed,” “connected,” “coupled,” “interconnected,” and similar refer to a relationship wherein structures are secured or attached to one another either directly or indirectly through intervening structures, as well as both movable or rigid attachments or relationships, unless expressly described otherwise. Moreover, the features and benefits of the invention are illustrated by reference to the preferred embodiments. Accordingly, the invention expressly should not be limited to such preferred embodiments illustrating some possible non-limiting combination of features that may exist alone or in other combinations of features, the scope of the invention being defined by the claims appended hereto.

[0045] Exemplary embodiments of the present invention are now described with reference to the

Figures. Reference numerals are used throughout the detailed description to refer to the various elements and structures. Although the following detailed description contains many specifics for the purposes of illustration, a person of ordinary skill in the art will appreciate that many variations and alterations to the following details are within the scope of the invention. Accordingly, the following embodiments of the invention are set forth without any loss of generality to, and without imposing limitations upon, the claimed invention.

[0046] FIG. 1 shows the contacting assembly 1 with contact spring units 2 mounted on a carrier 4.

[0047] In this preferred embodiment, the carrier 4 is configured merely exemplarily as a plate. In one direction 6, the carrier 4 is extended longer than in the other directions and has a material thick-ness 8, which forms the narrow sides 10 of the carrier 4. In this illustration, the material thickness 8 in the center of the carrier or the center section 14 of the carrier 4 is exemplarily characterized. The material thickness 8 of the carrier 4 can be different over the entire carrier 4. In the direction of one or the longitudinal extension 6 of the carrier 4, the carrier 4 can have several flanks or, equivalently, flange sections 12 along the narrow sides 10, which extend away from the center section 14 of the carrier 4. A further configuration can provide a continuous flange section 12 over the entire narrow side 10 of the carrier 4 for each narrow side. The at least one flange section 12 can thereby have a smaller thickness or material thickness 18 than the center section 14 of the carrier 4.

[0048] Manufacturing of the contact spring unit 2 and carrier 4 can be done separately and thus both units can be made of different materials. In one embodiment, the carrier 4 can be configured as a cast part. It is also conceivable to use an electrically non-conductive plastic as a material for the carrier 4, since the carrier 4 does not necessarily have to be conductive—this increases flexibility during manufacturing and reduces costs.

[0049] The at least one contact spring unit 2 is pressed onto the flange section 12 of the carrier 4. The flange sections 12 may be chamfered and/or rounded to simplify assembly. Another preferred configuration could provide for the attachment of contact spring units 2 over the flat sides 20 of the carrier 4. Of course, the at least one contact spring unit 2 can also be pressed directly onto the carrier 4 if there is no flange section 12.

[0050] Instead of being pressed on, the at least one contact spring unit 2 can also be connected to the flange section 12 of the carrier 4 by means of a clamp connection and clamped with clamping elements such as screws or wedges.

[0051] Furthermore, the flange sections 12 can be interrupted by form-fit elements 22. The form-fit elements 22 can be configured such that they protrude away from the narrow side 10 of the carrier 4, perpendicular to the direction of the longitudinal extension 6, and each have two elastically deflectable arms 24, each with a latching protrusion 26. Other embodiments of the form-fit elements 22 can have, for example, clamping lugs or latching hooks.

[0052] The form-fit elements 22 of the carrier 4 can be attached in pairs to the carrier edge 28 and form the form-fit counterpart for a contact spring unit 2. In this case, the form-fit elements 22 can be configured such that they are each engaged with a complementary form-fit element 30 of the con-tact spring unit 2 and are spaced apart from one another. In one configuration, the form-fit element 22 can also be positioned on the shorter narrow side 10 of the carrier 4. The complementary form-fit element 30 of the contact spring unit 2 can accordingly be engaged with at least one form-fit element 22 on the shorter narrow side 10 of the carrier 4.

[0053] The carrier 4 can have an arbitrary number and size of recesses 32 for, for example, plug or screw connections and/or to save material. The shape of the carrier 4 can be arbitrarily adapted to the respective mounting surface. One possible configuration provides at least one recess 32 for at least one mounting bush 34 that can be used for screw connections. For example, the carrier 4 can be configured as a frame surrounding a central opening (FIG. 4).

[0054] Several contact spring units 2 can be clipped onto the carrier 4 along at least one narrow side 10 running in the direction of the longitudinal extension 6. Of course, the carrier 4 can also be

con-figured to be square and have one or more contact spring units **2** along each of the four sides, in particular the four narrow sides **10**. In FIG. **1**, several contact spring units **2** are arranged next to each other on the two opposite longer narrow sides **10**, with each contact spring unit **2** being located opposite a contact spring unit **2** on the other narrow side **10**. It is also possible that on all four narrow sides **10** of the carrier **4** contact spring units **2** are attached (FIG. **6**), which can be arranged next to each other, but also on top of each other.

[0055] The contact spring unit **2** can be configured as an elongated contact spring strip **36**, as shown in FIG. **1**, the longitudinal direction of which runs parallel here to the direction of the longitudinal ex-tension **6**. The contact spring unit **2** can be configured monolithically. The contact spring strip **36** can, for example, be configured as a stamped and bent part.

[0056] The contact spring strip **36** has several contact spring tongues—or, equivalently, contact spring lamellae—**38** arranged next to each other along its longitudinal direction. The number of contact spring tongues **38** can be arbitrarily adapted to the respective needs and requirements. The con-tact spring tongues **38** can be connected by means of a material connection **39** that extends along the longitudinal direction of the contact spring strip **36**. In a preferred configuration, the material connection **39** can extend along the flange section **12** of the carrier **4**. In this case, the material connection **39** can be configured in the form of a band or a strip. At their one end, the contact spring tongues **38** are connected to the material connection **39**; the other end of the contact spring tongues **38** is configured as a free, resilient end.

[0057] The at least one form-fit element **30** of such a contact spring strip **36** can have an opening **40**. The opening **40** can, for example, be surrounded by a rectangular frame **41** at the end **42** of the contact spring strip **36**. The frame **41** can, in particular, be located at one end of the material connection **39**.

[0058] In this context, the opening **40** points away from the carrier narrow side **10**. The opening should be large enough to receive the form-fit element **22** of the carrier **4** and to latch it in the frame **41**, as shown in this embodiment in FIG. **1**. Another preferred configuration provides for a further opening **40** at the other end **42** of the contact spring strip **36** along the narrow side **10** in the direction of the longitudinal extension **6** of the carrier **4**, which may be configured symmetrically to the other opening **40**. Of course, other configurations of complementary form-fit elements on carrier **4** and contact spring strip **36** are also possible. For example, the edges of the material connection **39** can be clipped into the latching tongues of the carrier **4**.

[0059] One possible embodiment of the contact spring strip **36** provides two opposing contact spring lamellae or tongues **38** pointing in opposite directions, which point away from the respective flat sides **20** of the carrier **4** and can be elastically deflected. Here, as in the rest of the text, an “elastic” deflection describes any deflection with elastic components. The respective contact spring tongues **38** can be configured symmetrically with respect to the direction of the longitudinal extension **6** or, however, can be asymmetrical, for example, having a longer contact spring tongue **38** on the carrier upper side **44** than on the carrier lower side **46**.

[0060] In a further preferred configuration, for example, one row **48** (FIG. **5**) of the contact spring tongues **38** pointing in the same direction on the carrier upper side **44** can be offset with respect to the other row **48** of contact spring tongues **38** on the carrier lower side **46**, so that between two contact spring tongues **38** pointing in the same direction on the carrier upper side **44**, on the opposite carrier side **46**, one contact spring tongue **38** points in the opposite direction. The contact spring tongues **38** above **44** and below **46** of the carrier **4** are therefore arranged alternately. The row **48** can be a contact spring package or a contact spring magazine.

[0061] The contact spring tongues **38** above **44** and below **46** of the carrier **4** are connected to one another by means of a holding section **50** (FIG. **2**), which is located between the two opposing con-tact spring tongues **38**. The material connection **39** can be part of the holding section **50**.

[0062] FIG. **2** shows a contact spring unit **2** and illustrates the configuration of the contact spring tongues **38** with the holding section **50**.

[0063] The holding section **50** has a U-shaped cross-section **52**, the open side of which points to the flange section **12** of the carrier **4** or the carrier center section **14** (FIG. **1**). The two legs **54** of the U-shaped cross-section **52** lie opposite each other. In this case, the holding section **50** can have a clear width **56** that is less than the material thickness **18** of the carrier **4** in the area that is clasped by the holding section **50**.

[0064] At either end **58** of the U-shaped cross-section **52**, the holding section **50** can have a bend **60** that merges smoothly into one contact spring tongue **38** each. The bend, or equivalently, the arcuate deflection **60** positions the respective contact spring tongue **38** at an acute angle **62** to the connected leg **54** of the U-shaped cross-section **52** and thus to the flat side **20** or flange section **12** of the carrier **4**, which later rests against the leg **54**. The free end **64** of the respective contact spring tongue **38** can point away from the carrier center section **14** and be spaced apart from the holding section **50**.

[0065] The contact spring tongues **38** located opposite one another with respect to the holding section **50** are preferably configured symmetrically and extend at the same angle **62** from the respective carrier flat side **20** or the holding section **50**. An asymmetrical configuration is also possible. In this way, the contact spring tongues **38** can be shorter on one side of the holding section **50** than on the opposite side of the holding section **50**, as shown in FIG. **4**. The longer contact spring tongues **38** and their greater free spring travel can be used to compensate for coarser manufacturing and/or assembly tolerances when assembling with other electrical components **82**. In this case, the shorter contact spring tongue **38** can extend at a smaller angle **62** from the holding section **50** than the longer contact spring tongue **38** on the opposite side.

[0066] The holding section **50** encompasses the flange section **12** of the carrier **4** and is frictionally connected to the flange section **12** of the carrier **4**, as shown in FIG. **3**. If the contact spring unit **2** is configured as a contact spring strip **36** as described above, the contact spring tongues **38** arranged next to one another form a holding section **50** which extends in the longitudinal direction of the contact spring strip **36** and into which the flange section **12** can be inserted.

[0067] FIG. **3** shows the contacting assembly **1** with contact spring tongues **38** and, in the embodiment with spacers **70** at each shorter end **72** of the carrier **4**.

[0068] Another configuration provides for an interruption of the holding section **50** on the flat sides **20** or on the flange section **12** of the carrier **4** between contact spring tongues **38** arranged next to each other. In this way, the width of the bending edge of the contact spring unit **2** is preferably reduced. The holding section **50** can already be bent before assembly and thus have a pretension, as a result of which no large press-on force is necessary during assembly. The clamping force **68** (FIG. **5**) generated after assembly presses the contact spring unit **2** onto the carrier **4**.

[0069] Furthermore, the carrier **4** can comprise spacers **70** that point away from the flat sides **20** of the carrier **4**. The spacers **70** can be part of a monolithic configuration of the carrier **4**.

[0070] The spacers **70** can protrude perpendicularly to the respective flat side **20**. The height **76** of the spacers **70** thereby does not exceed the height **78** of the protruding contact spring tongues **38** in the force-free state. Preferably, the height **76** is smaller than the height **78**. The spacers **70** prevent the contact spring tongues **38** from being compressed too far. This prevents the contact spring tongues **38** from being overloaded. The spacers **70** can thus be an overstretch protection for the contact spring tongues **38**.

[0071] Another configuration provides that the height **76** of the spacer **70** corresponds to the height **78** of the compressed contact spring tongues **38**, in which a predetermined contact force **80** is generated (FIGS. **2** and **5**). The spacer **70** can thus be used as a contact force limitation.

[0072] FIG. **4** shows a configuration of the contacting assembly **1** with a frame-shaped carrier **4**.

[0073] The carrier **4** can have an essentially oval base area with a recess **32** that can completely penetrate the carrier **4**. Other embodiments can provide an angular, for example rectangular or square, or a circular frame as a carrier **4**. The material thickness or material strength **8** can be the same over the entire carrier **4**.

[0074] In the embodiment shown, the carrier **4** has a flange section **12** with form-fit elements **22** that are in engagement with the complementary form-fit elements **30** of the contact spring units **2**. Analogous to the other embodiments, the respective flange section **12** of the carrier **4** can have a lower thickness or material strength **18**.

[0075] The contact spring units **2** are arranged along the two opposite longer narrow sides **10** of the carrier **4**. The flange section **12** can have ribs **81**, which each protrude between the individual contact spring tongues **38** of a contact spring unit **2** on the carrier upper side **44** of the flange section **12** perpendicularly to the carrier upper side **44** upwards and become steeper towards the carrier center **14**. In an alternative embodiment, the ribs **81** can also protrude downwards from the carrier lower side **46**, in particular from the flange section **12**, perpendicularly to the carrier lower side **46**.

[0076] The spacers **70** can be formed on only one side of the carrier **4**, for example on the carrier lower side **46**. The spacers **70** can also each have a latching hook **71**, with which the carrier **4** can be attached to a mounting surface (not shown). In one configuration, there should be at least two latching hooks **71** to secure the entire assembly during storage and transportation.

[0077] FIG. **5** shows the arrangement of the contacting assembly **1** with two interfaces, such as two electrical components **82**.

[0078] In the operating state, the contacting assembly **1** can be mounted between two further electrical components **82**, as shown in FIG. **5**, wherein the contact spring tongues **38**, which protrude away from the carrier upper side **44** and carrier lower side **46**, press with a contact force **80** (see also FIG. **2**) against the respective complementary contacts **84** of the two electrical components **82**. As soon as the complementary contacts **84** press on the contact spring tongues **38**, the holding section **50** of the contact spring units **2** is pressed against the carrier **4** and the clamping force **68** (FIG. **2**) is thus increased once again. The portion of the clamping force **68** that is exerted by the contact force **80** generated by the contact spring tongues **38** may be greater or smaller than the portion of the clamping force **68** that is exerted by the holding section **50** prior to assembly.

[0079] FIG. **6** shows an alternative embodiment with a carrier **4** and contact spring units **2** on all four narrow sides **10** of the carrier **4**.

[0080] In this configuration, the carrier **4** is an elongated plate with flange sections **12** on each of the four narrow sides **10**. The flat sides **20** of the carrier **4** are perforated by recesses **32**.

[0081] Along the longer narrow sides **10**, a plurality of contact spring units **2** are attached in a row in the direction of the longitudinal extension **6**, spaced apart from one another, wherein the at least one holding section **50** of the respective contact spring unit **2** holds the contact spring unit **2** on the flange section **12** of the carrier **4**. In addition, the contact spring units **2** are secured to the carrier **4** by form-fit elements **22** of the carrier **4**, which protrude away from the flange section **12** perpendicular to the narrow side **10** and engage with complementary form-fit elements **30** of the contact spring units **2**, on the carrier **4**.

[0082] Along the shorter narrow sides **10**, one contact spring unit **2** is held on the carrier **4** in each case. Here, too, form-fit elements **22** protrude away from the carrier **4** perpendicular to the corresponding narrow side **10**. A configuration with several contact spring units **2** on the shorter narrow side **10** is also possible.

[0083] While the invention has been described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the spirit and scope of the invention as defined in the accompanying claims. One skilled in the art will appreciate that the invention may be used with many modifications of structure, arrangement, proportions, sizes, materials and components and otherwise used in the practice of the invention, which are particularly adapted to specific environments and operative requirements without departing from the principles of the present invention. The presently disclosed embodiments are therefore to be considered in all

respects as illustrative and not restrictive, the scope of the invention being defined by the appended claims, and not limited to the foregoing description or embodiments.

Claims

1. A contacting assembly for arrangement between two electrical components, wherein the contacting assembly comprises a carrier and at least one contact spring unit, wherein the at least one contact spring unit comprises a holding section and contact spring tongues, wherein the contact spring tongues extend from opposite sides of the carrier and are connected to each other via the holding section, and wherein the holding section clasps the carrier in sections and is frictionally held on the carrier.
2. The contacting assembly according to claim 1, wherein the carrier is made of a different material from that of the contact spring unit.
3. The contacting assembly according to claim 1, wherein the clasped section of the carrier is a flange section that is formed by an edge of the carrier and extends from a center section of the carrier.
4. The contacting assembly according to claim 3, wherein the contact spring unit is pressed onto the flange section.
5. The contacting assembly according to claim 1, wherein the holding section has two opposing legs which merge at their ends, located towards the carrier center section, into a respective contact spring tongue.
6. The contacting assembly according to claim 1, wherein the holding section has a clear width which in the force-free state is smaller than a material thickness of the carrier in the area clasped by the holding section.
7. The contacting assembly according to claim 1, wherein the contact spring unit has a band-shaped material connection which extends along the carrier and by which the contact spring tongues are connected to one another.
8. The contacting assembly according to claim 1, wherein the free ends of the contact spring tongues point away from the carrier center section and are spaced apart from the holding section.
9. The contacting assembly according to claim 1, wherein the contact spring unit is configured as a contact spring strip and has a plurality of contact spring tongues that are arranged next to one another.
10. The contacting assembly according to claim 1, wherein the contact spring tongues are arranged above and below the carrier alternately or in pairs opposite one another along the carrier edge.
11. The contacting assembly according to claim 1, wherein the carrier has a form-fit connection to the contact spring unit in addition to the frictional connection.
12. The contacting assembly according to claim 11, wherein at least one form-fit element of the carrier is formed by the carrier edge and is in engagement with a complementary form-fit element of the at least one contact spring unit.
13. The contacting assembly according to claim 1, wherein the carrier has at least one spacer on at least one of its two flat sides, extending away from the respective flat side of the carrier, and the at least one spacer does not protrude beyond the contact spring tongues in the direction pointing away from the respective flat side in the force-free state.
14. The contacting assembly according to claim 9, wherein the contact spring strips are arranged next to one another and on two opposite narrow sides of the carrier, spaced apart from one another.
15. An arrangement comprising a contacting assembly according to claim 1 and two electrical components, wherein the contacting assembly is located between the two electrical components in the operating state, wherein the contact spring tongues of the two electrical components are elastically deformed towards the carrier and press the holding section of the contact spring units

against the carrier and the clamping force applied by the holding section to the carrier is thus increased.
