



US 20250280365A1

(19) **United States**

(12) **Patent Application Publication**
ABOTABL et al.

(10) **Pub. No.: US 2025/0280365 A1**

(43) **Pub. Date: Sep. 4, 2025**

(54) **PHYSICAL UPLINK SHARED CHANNEL
POWER CONTROL**

H04W 52/24 (2009.01)

H04W 52/32 (2009.01)

(71) Applicant: **QUALCOMM Incorporated**, San
Diego, CA (US)

(52) **U.S. Cl.**

CPC *H04W 52/10* (2013.01); *H04W 52/146*
(2013.01); *H04W 52/242* (2013.01); *H04W*
52/325 (2013.01)

(72) Inventors: **Ahmed Attia ABOTABL**, San Diego,
CA (US); **Abdelrahman Mohamed**
Ahmed Mohamed IBRAHIM, San
Diego, CA (US); **Muhammad Sayed**
Khairy ABDELGHAFAR, San Jose,
CA (US)

(57)

ABSTRACT

Various aspects of the present disclosure generally relate to wireless communication. In some aspects, a user equipment (UE) may receive an open loop power control configuration for a physical uplink shared channel (PUSCH) communication, wherein the open loop power control configuration includes rules for one or more sounding reference signal (SRS) resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode. The UE may transmit the PUSCH communication in accordance with the open loop power control configuration. Numerous other aspects are described.

(21) Appl. No.: **18/593,699**

(22) Filed: **Mar. 1, 2024**


Publication Classification

(51) **Int. Cl.**

H04W 52/10 (2009.01)

H04W 52/14 (2009.01)

600 →






FIG. 1




FIG. 2

300 →





FIG. 3






FIG. 5




FIG. 6

700 →




FIG. 7

800 →




FIG. 8




FIG. 9




FIG. 10

PHYSICAL UPLINK SHARED CHANNEL POWER CONTROL

FIELD OF THE DISCLOSURE

[0001] Aspects of the present disclosure generally relate to wireless communication and specifically relate to techniques, apparatuses, and methods for power control for a physical uplink shared channel.

BACKGROUND

[0002] Wireless communication systems are widely deployed to provide various services that may include carrying voice, text, messaging, video, data, and/or other traffic. The services may include unicast, multicast, and/or broadcast services, among other examples. Typical wireless communication systems may employ multiple-access radio access technologies (RATs) capable of supporting communication with multiple users by sharing available system resources (for example, time domain resources, frequency domain resources, spatial domain resources, and/or device transmit power, among other examples). Examples of such multiple-access RATs include code division multiple access (CDMA) systems, time division multiple access (TDMA) systems, frequency division multiple access (FDMA) systems, orthogonal frequency division multiple access (OFDMA) systems, single-carrier frequency division multiple access (SC-FDMA) systems, and time division synchronous code division multiple access (TD-SCDMA) systems.

[0003] The above multiple-access RATs have been adopted in various telecommunication standards to provide common protocols that enable different wireless communication devices to communicate on a municipal, national, regional, or global level. An example telecommunication standard is New Radio (NR). NR, which may also be referred to as 5G, is part of a continuous mobile broadband evolution promulgated by the Third Generation Partnership Project (3GPP). NR (and other mobile broadband evolutions beyond NR) may be designed to better support Internet of things (IoT) and reduced capability device deployments, industrial connectivity, millimeter wave (mmWave) expansion, licensed and unlicensed spectrum access, non-terrestrial network (NTN) deployment, sidelink and other device-to-device direct communication technologies (for example, cellular vehicle-to-everything (CV2X) communication), massive multiple-input multiple-output (MIMO), disaggregated network architectures and network topology expansions, multiple-subscriber implementations, high-precision positioning, and/or radio frequency (RF) sensing, among other examples. As the demand for mobile broadband access continues to increase, further improvements in NR may be implemented, and other radio access technologies such as 6G may be introduced, to further advance mobile broadband evolution.

SUMMARY

[0004] In some aspects, a user equipment (UE) for wireless communication includes one or more memories; and one or more processors, coupled to the one or more memories, configured to cause the UE to: receive an open loop power control configuration for a physical uplink shared channel (PUSCH) communication, wherein the open loop power control configuration includes rules for one or more

sounding reference signal (SRS) resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and transmit the PUSCH communication in accordance with the open loop power control configuration.

[0005] In some aspects, a network node for wireless communication includes one or more memories; and one or more processors, coupled to the one or more memories, configured to cause the network node to: output, to a UE, an open loop power control configuration for a PUSCH communication, wherein the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and receive the PUSCH communication in accordance with the open loop power control configuration.

[0006] In some aspects, a method of wireless communication performed by a UE includes receiving an open loop power control configuration for a PUSCH communication, wherein the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and transmitting the PUSCH communication in accordance with the open loop power control configuration.

[0007] In some aspects, a method of wireless communication performed by a network node includes outputting, to a UE, an open loop power control configuration for a PUSCH communication, wherein the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and receiving the PUSCH communication in accordance with the open loop power control configuration.

[0008] In some aspects, a non-transitory computer-readable medium storing a set of instructions for wireless communication includes one or more instructions that, when executed by one or more processors of a UE, cause the UE to: receive an open loop power control configuration for a PUSCH communication, wherein the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and transmit the PUSCH communication in accordance with the open loop power control configuration.

[0009] In some aspects, a non-transitory computer-readable medium storing a set of instructions for wireless communication includes one or more instructions that, when executed by one or more processors of a network node, cause the network node to: output, to a UE, an open loop power control configuration for a PUSCH communication, wherein the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and receive the PUSCH communication in accordance with the open loop power control configuration.

[0010] In some aspects, an apparatus for wireless communication includes means for receiving an open loop power control configuration for a PUSCH communication, wherein the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a

full-duplex mode; and means for transmitting the PUSCH communication in accordance with the open loop power control configuration.

[0011] In some aspects, an apparatus for wireless communication includes means for outputting, to a UE, an open loop power control configuration for a PUSCH communication, wherein the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and means for receiving the PUSCH communication in accordance with the open loop power control configuration.

[0012] Aspects of the present disclosure may generally be implemented by or as a method, apparatus, system, computer program product, non-transitory computer-readable medium, user equipment, base station, network node, network entity, wireless communication device, and/or processing system as substantially described with reference to, and as illustrated by, the specification and accompanying drawings.

[0013] The foregoing paragraphs of this section have broadly summarized some aspects of the present disclosure. These and additional aspects and associated advantages will be described hereinafter. The disclosed aspects may be used as a basis for modifying or designing other aspects for carrying out the same or similar purposes of the present disclosure. Such equivalent aspects do not depart from the scope of the appended claims. Characteristics of the aspects disclosed herein, both their organization and method of operation, together with associated advantages, will be better understood from the following description when considered in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The appended drawings illustrate some aspects of the present disclosure, but are not limiting of the scope of the present disclosure because the description may enable other aspects. Each of the drawings is provided for purposes of illustration and description, and not as a definition of the limits of the claims. The same or similar reference numbers in different drawings may identify the same or similar elements.

[0015] FIG. 1 is a diagram illustrating an example of a wireless communication network in accordance with the present disclosure.

[0016] FIG. 2 is a diagram illustrating an example network node in communication with an example user equipment (UE) in a wireless network in accordance with the present disclosure.

[0017] FIG. 3 is a diagram illustrating an example disaggregated base station architecture in accordance with the present disclosure.

[0018] FIG. 4 is a diagram illustrating examples of full-duplex communication in a wireless network, in accordance with the present disclosure.

[0019] FIG. 5 is a diagram illustrating an example of sounding reference signal resource sets, in accordance with the present disclosure.

[0020] FIG. 6 is a diagram of an example associated with physical uplink shared channel power control, in accordance with the present disclosure.

[0021] FIG. 7 is a diagram illustrating an example process performed, for example, at a UE or an apparatus of a UE, in accordance with the present disclosure.

[0022] FIG. 8 is a diagram illustrating an example process performed, for example, at a network node or an apparatus of a network node, in accordance with the present disclosure.

[0023] FIG. 9 is a diagram of an example apparatus for wireless communication, in accordance with the present disclosure.

[0024] FIG. 10 is a diagram of an example apparatus for wireless communication, in accordance with the present disclosure.

DETAILED DESCRIPTION

[0025] Various aspects of the present disclosure are described hereinafter with reference to the accompanying drawings. However, aspects of the present disclosure may be embodied in many different forms and is not to be construed as limited to any specific aspect illustrated by or described with reference to an accompanying drawing or otherwise presented in this disclosure. Rather, these aspects are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the disclosure to those skilled in the art. One skilled in the art may appreciate that the scope of the disclosure is intended to cover any aspect of the disclosure disclosed herein, whether implemented independently of or in combination with any other aspect of the disclosure. For example, an apparatus may be implemented or a method may be practiced using various combinations or quantities of the aspects set forth herein. In addition, the scope of the disclosure is intended to cover an apparatus having, or a method that is practiced using, other structures and/or functionalities in addition to or other than the structures and/or functionalities with which various aspects of the disclosure set forth herein may be practiced. Any aspect of the disclosure disclosed herein may be embodied by one or more elements of a claim.

[0026] Several aspects of telecommunication systems will now be presented with reference to various methods, operations, apparatuses, and techniques. These methods, operations, apparatuses, and techniques will be described in the following detailed description and illustrated in the accompanying drawings by various blocks, modules, components, circuits, steps, processes, or algorithms (collectively referred to as “elements”). These elements may be implemented using hardware, software, or a combination of hardware and software. Whether such elements are implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system.

[0027] Some wireless networks use physical uplink shared channel (PUSCH) power control to provide efficient use of radio resources while maintaining quality of service (QoS). PUSCH power control may involve adjusting a transmit power of a user equipment (UE) for uplink data transmission on a PUSCH. In doing so, the UE may mitigate inter-cell interference, optimize battery usage, and improve channel conditions.

[0028] Various aspects relate generally to PUSCH power control. Some aspects more specifically relate to PUSCH power control with one or more sounding reference signal (SRS) resource sets. Some aspects more specifically relate to PUSCH power control with one or more SRS resource sets when the UE is operating in a full-duplex mode. In some aspects, the UE transmits the PUSCH communication in accordance with an open loop power control configuration. The open loop power control configuration may include

rules for one or more SRS resource sets, and each SRS resource set may be associated with one or more of a half-duplex mode or a full-duplex mode. In some aspects, the network node outputs the open loop power control configuration to the UE and receives PUSCH communications in accordance with the open loop power control configuration.

[0029] Particular aspects of the subject matter described in this disclosure can be implemented to realize one or more of the following potential advantages. In some examples, with PUSCH communications transmitted in accordance with the open loop power control configuration, the described techniques can be used to mitigate inter-cell interference, optimize battery usage, and improve channel conditions.

[0030] Multiple-access radio access technologies (RATs) have been adopted in various telecommunication standards to provide common protocols that enable wireless communication devices to communicate on a municipal, enterprise, national, regional, or global level. For example, 5G New Radio (NR) is part of a continuous mobile broadband evolution promulgated by the Third Generation Partnership Project (3GPP). 5G NR supports various technologies and use cases including enhanced mobile broadband (eMBB), ultra-reliable low-latency communication (URLLC), massive machine-type communication (mMTC), millimeter wave (mmWave) technology, beamforming, network slicing, edge computing, Internet of Things (IoT) connectivity and management, and network function virtualization (NFV).

[0031] As the demand for broadband access increases and as technologies supported by wireless communication networks evolve, further technological improvements may be adopted in or implemented for 5G NR or future RATs, such as 6G, to further advance the evolution of wireless communication for a wide variety of existing and new use cases and applications. Such technological improvements may be associated with new frequency band expansion, licensed and unlicensed spectrum access, overlapping spectrum use, small cell deployments, non-terrestrial network (NTN) deployments, disaggregated network architectures and network topology expansion, device aggregation, advanced duplex communication, sidelink and other device-to-device direct communication, IoT (including passive or ambient IoT) networks, reduced capability (RedCap) UE functionality, industrial connectivity, multiple-subscriber implementations, high-precision positioning, radio frequency (RF) sensing, and/or artificial intelligence or machine learning (AI/ML), among other examples. These technological improvements may support use cases such as wireless backhauls, wireless data centers, extended reality (XR) and metaverse applications, meta services for supporting vehicle connectivity, holographic and mixed reality communication, autonomous and collaborative robots, vehicle platooning and cooperative maneuvering, sensing networks, gesture monitoring, human-brain interfacing, digital twin applications, asset management, and universal coverage applications using non-terrestrial and/or aerial platforms, among other examples. The methods, operations, apparatuses, and techniques described herein may enable one or more of the foregoing technologies and/or support one or more of the foregoing use cases.

[0032] FIG. 1 is a diagram illustrating an example of a wireless communication network 100 in accordance with the present disclosure. The wireless communication network

100 may be or may include elements of a 5G (or NR) network or a 6G network, among other examples. The wireless communication network 100 may include multiple network nodes 110, shown as a network node (NN) 110a, a network node 110b, a network node 110c, and a network node 110d. The network nodes 110 may support communications with multiple UEs 120, shown as a UE 120a, a UE 120b, a UE 120c, a UE 120d, and a UE 120e.

[0033] The network nodes 110 and the UEs 120 of the wireless communication network 100 may communicate using the electromagnetic spectrum, which may be subdivided by frequency or wavelength into various classes, bands, carriers, and/or channels. For example, devices of the wireless communication network 100 may communicate using one or more operating bands. In some aspects, multiple wireless networks 100 may be deployed in a given geographic area. Each wireless communication network 100 may support a particular radio access technology (RAT) (which may also be referred to as an air interface) and may operate on one or more carrier frequencies in one or more frequency ranges. Examples of RATs include a 4G RAT, a 5G/NR RAT, and/or a 6G RAT, among other examples. In some examples, when multiple RATs are deployed in a given geographic area, each RAT in the geographic area may operate on different frequencies to avoid interference with one another.

[0034] Various operating bands have been defined as frequency range designations FR1 (410 MHz through 7.125 GHz), FR2 (24.25 GHz through 52.6 GHz), FR3 (7.125 GHz through 24.25 GHz), FR4a or FR4-1 (52.6 GHz through 71 GHz), FR4 (52.6 GHz through 114.25 GHz), and FR5 (114.25 GHz through 300 GHz). Although a portion of FR1 is greater than 6 GHz, FR1 is often referred to (interchangeably) as a “Sub-6 GHz” band in some documents and articles. Similarly, FR2 is often referred to (interchangeably) as a “millimeter wave” band in some documents and articles, despite being different than the extremely high frequency (EHF) band (30 GHz through 300 GHz), which is identified by the International Telecommunications Union (ITU) as a “millimeter wave” band. The frequencies between FR1 and FR2 are often referred to as mid-band frequencies, which include FR3. Frequency bands falling within FR3 may inherit FR1 characteristics or FR2 characteristics, and thus may effectively extend features of FR1 or FR2 into mid-band frequencies. Thus, “sub-6 GHz,” if used herein, may broadly refer to frequencies that are less than 6 GHz, that are within FR1, and/or that are included in mid-band frequencies. Similarly, the term “millimeter wave,” if used herein, may broadly refer to frequencies that are included in mid-band frequencies, that are within FR2, FR4, FR4-a or FR4-1, or FR5, and/or that are within the EHF band. Higher frequency bands may extend 5G NR operation, 6G operation, and/or other RATs beyond 52.6 GHz. For example, each of FR4a, FR4-1, FR4, and FR5 falls within the EHF band. In some examples, the wireless communication network 100 may implement dynamic spectrum sharing (DSS), in which multiple RATs (for example, 4G/LTE and 5G/NR) are implemented with dynamic bandwidth allocation (for example, based on user demand) in a single frequency band. It is contemplated that the frequencies included in these operating bands (for example, FR1, FR2, FR3, FR4, FR4-a, FR4-1, and/or FR5) may be modified, and techniques described herein may be applicable to those modified frequency ranges.

[0035] A network node **110** may include one or more devices, components, or systems that enable communication between a UE **120** and one or more devices, components, or systems of the wireless communication network **100**. A network node **110** may be, may include, or may also be referred to as an NR network node, a 5G network node, a 6G network node, a Node B, an eNB, a gNB, an access point (AP), a transmission reception point (TRP), a mobility element, a core, a network entity, a network element, a network equipment, and/or another type of device, component, or system included in a radio access network (RAN).

[0036] A network node **110** may be implemented as a single physical node (for example, a single physical structure) or may be implemented as two or more physical nodes (for example, two or more distinct physical structures). For example, a network node **110** may be a device or system that implements part of a radio protocol stack, a device or system that implements a full radio protocol stack (such as a full gNB protocol stack), or a collection of devices or systems that collectively implement the full radio protocol stack. For example, and as shown, a network node **110** may be an aggregated network node (having an aggregated architecture), meaning that the network node **110** may implement a full radio protocol stack that is physically and logically integrated within a single node (for example, a single physical structure) in the wireless communication network **100**. For example, an aggregated network node **110** may consist of a single standalone base station or a single TRP that uses a full radio protocol stack to enable or facilitate communication between a UE **120** and a core network of the wireless communication network **100**.

[0037] Alternatively, and as also shown, a network node **110** may be a disaggregated network node (sometimes referred to as a disaggregated base station), meaning that the network node **110** may implement a radio protocol stack that is physically distributed and/or logically distributed among two or more nodes in the same geographic location or in different geographic locations. For example, a disaggregated network node may have a disaggregated architecture. In some deployments, disaggregated network nodes **110** may be used in an integrated access and backhaul (IAB) network, in an open radio access network (O-RAN) (such as a network configuration in compliance with the O-RAN Alliance), or in a virtualized radio access network (vRAN), also known as a cloud radio access network (C-RAN), to facilitate scaling by separating base station functionality into multiple units that can be individually deployed.

[0038] The network nodes **110** of the wireless communication network **100** may include one or more central units (CUs), one or more distributed units (DUs), and/or one or more radio units (RUs). A CU may host one or more higher layer control functions, such as radio resource control (RRC) functions, packet data convergence protocol (PDCP) functions, and/or service data adaptation protocol (SDAP) functions, among other examples. A DU may host one or more of a radio link control (RLC) layer, a medium access control (MAC) layer, and/or one or more higher physical (PHY) layers depending, at least in part, on a functional split, such as a functional split defined by the 3GPP. In some examples, a DU also may host one or more lower PHY layer functions, such as a fast Fourier transform (FFT), an inverse FFT (IFFT), beamforming, physical random access channel (PRACH) extraction and filtering, and/or scheduling of resources for one or more UEs **120**, among other examples.

An RU may host RF processing functions or lower PHY layer functions, such as an FFT, an IFFT, beamforming, or PRACH extraction and filtering, among other examples, according to a functional split, such as a lower layer functional split. In such an architecture, each RU can be operated to handle over the air (OTA) communication with one or more UEs **120**.

[0039] In some aspects, a single network node **110** may include a combination of one or more CUs, one or more DUs, and/or one or more RUs. Additionally or alternatively, a network node **110** may include one or more Near-Real Time (Near-RT) RAN Intelligent Controllers (RICs) and/or one or more Non-Real Time (Non-RT) RICs. In some examples, a CU, a DU, and/or an RU may be implemented as a virtual unit, such as a virtual central unit (VCU), a virtual distributed unit (VDU), or a virtual radio unit (VRU), among other examples. A virtual unit may be implemented as a virtual network function, such as associated with a cloud deployment.

[0040] Some network nodes **110** (for example, a base station, an RU, or a TRP) may provide communication coverage for a particular geographic area. In the 3GPP, the term “cell” can refer to a coverage area of a network node **110** or to a network node **110** itself, depending on the context in which the term is used. A network node **110** may support one or multiple (for example, three) cells. In some examples, a network node **110** may provide communication coverage for a macro cell, a pico cell, a femto cell, or another type of cell. A macro cell may cover a relatively large geographic area (for example, several kilometers in radius) and may allow unrestricted access by UEs **120** with service subscriptions. A pico cell may cover a relatively small geographic area and may allow unrestricted access by UEs **120** with service subscriptions. A femto cell may cover a relatively small geographic area (for example, a home) and may allow restricted access by UEs **120** having association with the femto cell (for example, UEs **120** in a closed subscriber group (CSG)). A network node **110** for a macro cell may be referred to as a macro network node. A network node **110** for a pico cell may be referred to as a pico network node. A network node **110** for a femto cell may be referred to as a femto network node or an in-home network node. In some examples, a cell may not necessarily be stationary. For example, the geographic area of the cell may move according to the location of an associated mobile network node **110** (for example, a train, a satellite base station, an unmanned aerial vehicle, or a non-terrestrial network (NTN) network node).

[0041] The wireless communication network **100** may be a heterogeneous network that includes network nodes **110** of different types, such as macro network nodes, pico network nodes, femto network nodes, relay network nodes, aggregated network nodes, and/or disaggregated network nodes, among other examples. In the example shown in FIG. 1, the network node **110a** may be a macro network node for a macro cell **130a**, the network node **110b** may be a pico network node for a pico cell **130b**, and the network node **110c** may be a femto network node for a femto cell **130c**. Various different types of network nodes **110** may generally transmit at different power levels, serve different coverage areas, and/or have different impacts on interference in the wireless communication network **100** than other types of network nodes **110**. For example, macro network nodes may have a high transmit power level (for example, 5 to 40

watts), whereas pico network nodes, femto network nodes, and relay network nodes may have lower transmit power levels (for example, 0.1 to 2 watts).

[0042] In some examples, a network node **110** may be, may include, or may operate as an RU, a TRP, or a base station that communicates with one or more UEs **120** via a radio access link (which may be referred to as a “Uu” link). The radio access link may include a downlink and an uplink. “Downlink” (or “DL”) refers to a communication direction from a network node **110** to a UE **120**, and “uplink” (or “UL”) refers to a communication direction from a UE **120** to a network node **110**. Downlink channels may include one or more control channels and one or more data channels. A downlink control channel may be used to transmit downlink control information (DCI) (for example, scheduling information, reference signals, and/or configuration information) from a network node **110** to a UE **120**. A downlink data channel may be used to transmit downlink data (for example, user data associated with a UE **120**) from a network node **110** to a UE **120**. Downlink control channels may include one or more physical downlink control channels (PDCCHs), and downlink data channels may include one or more physical downlink shared channels (PDSCHs). Uplink channels may similarly include one or more control channels and one or more data channels. An uplink control channel may be used to transmit uplink control information (UCI) (for example, reference signals and/or feedback corresponding to one or more downlink transmissions) from a UE **120** to a network node **110**. An uplink data channel may be used to transmit uplink data (for example, user data associated with a UE **120**) from a UE **120** to a network node **110**. Uplink control channels may include one or more physical uplink control channels (PUCCHs), and uplink data channels may include one or more physical uplink shared channels (PUSCHs). The downlink and the uplink may each include a set of resources on which the network node **110** and the UE **120** may communicate.

[0043] Downlink and uplink resources may include time domain resources (frames, subframes, slots, and/or symbols), frequency domain resources (frequency bands, component carriers, subcarriers, resource blocks, and/or resource elements), and/or spatial domain resources (particular transmit directions and/or beam parameters). Frequency domain resources of some bands may be subdivided into bandwidth parts (BWPs). A BWP may be a continuous block of frequency domain resources (for example, a continuous block of resource blocks) that are allocated for one or more UEs **120**. A UE **120** may be configured with both an uplink BWP and a downlink BWP (where the uplink BWP and the downlink BWP may be the same BWP or different BWPs). A BWP may be dynamically configured (for example, by a network node **110** transmitting a DCI configuration to the one or more UEs **120**) and/or reconfigured, which means that a BWP can be adjusted in real-time (or near-real-time) based on changing network conditions in the wireless communication network **100** and/or based on the specific requirements of the one or more UEs **120**. This enables more efficient use of the available frequency domain resources in the wireless communication network **100** because fewer frequency domain resources may be allocated to a BWP for a UE **120** (which may reduce the quantity of frequency domain resources that a UE **120** is required to monitor), leaving more frequency domain resources to be spread across multiple UEs **120**. Thus, BWPs may also assist in the

implementation of lower-capability UEs **120** by facilitating the configuration of smaller bandwidths for communication by such UEs **120**.

[0044] As described above, in some aspects, the wireless communication network **100** may be, may include, or may be included in, an IAB network. In an IAB network, at least one network node **110** is an anchor network node that communicates with a core network. An anchor network node **110** may also be referred to as an IAB donor (or “IAB-donor”). The anchor network node **110** may connect to the core network via a wired backhaul link. For example, an Ng interface of the anchor network node **110** may terminate at the core network. Additionally or alternatively, an anchor network node **110** may connect to one or more devices of the core network that provide a core access and mobility management function (AMF). An IAB network also generally includes multiple non-anchor network nodes **110**, which may also be referred to as relay network nodes or simply as IAB nodes (or “IAB-nodes”). Each non-anchor network node **110** may communicate directly with the anchor network node **110** via a wireless backhaul link to access the core network, or may communicate indirectly with the anchor network node **110** via one or more other non-anchor network nodes **110** and associated wireless backhaul links that form a backhaul path to the core network. Some anchor network node **110** or other non-anchor network node **110** may also communicate directly with one or more UEs **120** via wireless access links that carry access traffic. In some examples, network resources for wireless communication (such as time resources, frequency resources, and/or spatial resources) may be shared between access links and backhaul links.

[0045] In some examples, any network node **110** that relays communications may be referred to as a relay network node, a relay station, or simply as a relay. A relay may receive a transmission of a communication from an upstream station (for example, another network node **110** or a UE **120**) and transmit the communication to a downstream station (for example, a UE **120** or another network node **110**). In this case, the wireless communication network **100** may include or be referred to as a “multi-hop network.” In the example shown in FIG. 1, the network node **110d** (for example, a relay network node) may communicate with the network node **110a** (for example, a macro network node) and the UE **120d** in order to facilitate communication between the network node **110a** and the UE **120d**. Additionally or alternatively, a UE **120** may be or may operate as a relay station that can relay transmissions to or from other UEs **120**. A UE **120** that relays communications may be referred to as a UE relay or a relay UE, among other examples.

[0046] The UEs **120** may be physically dispersed throughout the wireless communication network **100**, and each UE **120** may be stationary or mobile. A UE **120** may be, may include, or may be included in an access terminal, another terminal, a mobile station, or a subscriber unit. A UE **120** may be, include, or be coupled with a cellular phone (for example, a smart phone), a personal digital assistant (PDA), a wireless modem, a wireless communication device, a handheld device, a laptop computer, a cordless phone, a wireless local loop (WLL) station, a tablet, a camera, a gaming device, a netbook, a smartbook, an ultrabook, a medical device, a biometric device, a wearable device (for example, a smart watch, smart clothing, smart glasses, a

smart wristband, and/or smart jewelry, such as a smart ring or a smart bracelet), an entertainment device (for example, a music device, a video device, and/or a satellite radio), an extended reality (XR) device, a vehicular component or sensor, a smart meter or sensor, industrial manufacturing equipment, a Global Navigation Satellite System (GNSS) device (such as a Global Positioning System device or another type of positioning device), a UE function of a network node, and/or any other suitable device or function that may communicate via a wireless medium.

[0047] A UE **120** and/or a network node **110** may include one or more chips, system-on-chips (SoCs), chipsets, packages, or devices that individually or collectively constitute or comprise a processing system. The processing system includes processor (or “processing”) circuitry in the form of one or multiple processors, microprocessors, processing units (such as central processing units (CPUs), graphics processing units (GPUs), neural processing units (NPUs) and/or digital signal processors (DSPs)), processing blocks, application-specific integrated circuits (ASIC), programmable logic devices (PLDs) (such as field programmable gate arrays (FPGAs)), or other discrete gate or transistor logic or circuitry (all of which may be generally referred to herein individually as “processors” or collectively as “the processor” or “the processor circuitry”). One or more of the processors may be individually or collectively configurable or configured to perform various functions or operations described herein. A group of processors collectively configurable or configured to perform a set of functions may include a first processor configurable or configured to perform a first function of the set and a second processor configurable or configured to perform a second function of the set, or may include the group of processors all being configured or configurable to perform the set of functions.

[0048] The processing system may further include memory circuitry in the form of one or more memory devices, memory blocks, memory elements or other discrete gate or transistor logic or circuitry, each of which may include tangible storage media such as random-access memory (RAM) or read-only memory (ROM), or combinations thereof (all of which may be generally referred to herein individually as “memories” or collectively as “the memory” or “the memory circuitry”). One or more of the memories may be coupled (for example, operatively coupled, communicatively coupled, electronically coupled, or electrically coupled) with one or more of the processors and may individually or collectively store processor-executable code (such as software) that, when executed by one or more of the processors, may configure one or more of the processors to perform various functions or operations described herein. Additionally or alternatively, in some examples, one or more of the processors may be preconfigured to perform various functions or operations described herein without requiring configuration by software. The processing system may further include or be coupled with one or more modems (such as a Wi-Fi (for example, IEEE compliant) modem or a cellular (for example, 3GPP 4G LTE, 5G, or 6G compliant) modem). In some implementations, one or more processors of the processing system include or implement one or more of the modems. The processing system may further include or be coupled with multiple radios (collectively “the radio”), multiple RF chains, or multiple transceivers, each of which may in turn be coupled with one or more of multiple antennas. In some

implementations, one or more processors of the processing system include or implement one or more of the radios, RF chains or transceivers. The UE **120** may include or may be included in a housing that houses components associated with the UE **120** including the processing system.

[0049] Some UEs **120** may be considered machine-type communication (MTC) UEs, evolved or enhanced machine-type communication (eMTC), UEs, further enhanced eMTC (feMTC) UEs, or enhanced feMTC (efeMTC) UEs, or further evolutions thereof, all of which may be simply referred to as “MTC UEs”). An MTC UE may be, may include, or may be included in or coupled with a robot, an uncrewed aerial vehicle, a remote device, a sensor, a meter, a monitor, and/or a location tag. Some UEs **120** may be considered IoT devices and/or may be implemented as NB-IoT (narrowband IoT) devices. An IoT UE or NB-IoT device may be, may include, or may be included in or coupled with an industrial machine, an appliance, a refrigerator, a doorbell camera device, a home automation device, and/or a light fixture, among other examples. Some UEs **120** may be considered Customer Premises Equipment, which may include telecommunications devices that are installed at a customer location (such as a home or office) to enable access to a service provider’s network (such as included in or in communication with the wireless communication network **100**).

[0050] Some UEs **120** may be classified according to different categories in association with different complexities and/or different capabilities. UEs **120** in a first category may facilitate massive IoT in the wireless communication network **100**, and may offer low complexity and/or cost relative to UEs **120** in a second category. UEs **120** in a second category may include mission-critical IoT devices, legacy UEs, baseline UEs, high-tier UEs, advanced UEs, full-capability UEs, and/or premium UEs that are capable of ultra-reliable low-latency communication (URLLC), enhanced mobile broadband (eMBB), and/or precise positioning in the wireless communication network **100**, among other examples. A third category of UEs **120** may have mid-tier complexity and/or capability (for example, a capability between UEs **120** of the first category and UEs **120** of the second category). A UE **120** of the third category may be referred to as a reduced capacity UE (“RedCap UE”), a mid-tier UE, an NR-Light UE, and/or an NR-Lite UE, among other examples. RedCap UEs may bridge a gap between the capability and complexity of NB-IoT devices and/or eMTC UEs, and mission-critical IoT devices and/or premium UEs. RedCap UEs may include, for example, wearable devices, IoT devices, industrial sensors, and/or cameras that are associated with a limited bandwidth, power capacity, and/or transmission range, among other examples. RedCap UEs may support healthcare environments, building automation, electrical distribution, process automation, transport and logistics, and/or smart city deployments, among other examples.

[0051] In some examples, two or more UEs **120** (for example, shown as UE **120a** and UE **120e**) may communicate directly with one another using sidelink communications (for example, without communicating by way of a network node **110** as an intermediary). As an example, the UE **120a** may directly transmit data, control information, or other signaling as a sidelink communication to the UE **120e**. This is in contrast to, for example, the UE **120a** first transmitting data in an UL communication to a network node

110, which then transmits the data to the UE **120e** in a DL communication. In various examples, the UEs **120** may transmit and receive sidelink communications using peer-to-peer (P2P) communication protocols, device-to-device (D2D) communication protocols, vehicle-to-everything (V2X) communication protocols (which may include vehicle-to-vehicle (V2V) protocols, vehicle-to-infrastructure (V2I) protocols, and/or vehicle-to-pedestrian (V2P) protocols), and/or mesh network communication protocols. In some deployments and configurations, a network node **110** may schedule and/or allocate resources for sidelink communications between UEs **120** in the wireless communication network **100**. In some other deployments and configurations, a UE **120** (instead of a network node **110**) may perform, or collaborate or negotiate with one or more other UEs to perform, scheduling operations, resource selection operations, and/or other operations for sidelink communications.

[0052] In various examples, some of the network nodes **110** and the UEs **120** of the wireless communication network **100** may be configured for full-duplex operation in addition to half-duplex operation. A network node **110** or a UE **120** operating in a half-duplex mode may perform only one of transmission or reception during particular time resources, such as during particular slots, symbols, or other time periods. Half-duplex operation may involve time-division duplexing (TDD), in which DL transmissions of the network node **110** and UL transmissions of the UE **120** do not occur in the same time resources (that is, the transmissions do not overlap in time). In contrast, a network node **110** or a UE **120** operating in a full-duplex mode can transmit and receive communications concurrently (for example, in the same time resources). By operating in a full-duplex mode, network nodes **110** and/or UEs **120** may generally increase the capacity of the network and the radio access link. In some examples, full-duplex operation may involve frequency-division duplexing (FDD), in which DL transmissions of the network node **110** are performed in a first frequency band or on a first component carrier and transmissions of the UE **120** are performed in a second frequency band or on a second component carrier different than the first frequency band or the first component carrier, respectively. In some examples, full-duplex operation may be enabled for a UE **120** but not for a network node **110**. For example, a UE **120** may simultaneously transmit an UL transmission to a first network node **110** and receive a DL transmission from a second network node **110** in the same time resources. In some other examples, full-duplex operation may be enabled for a network node **110** but not for a UE **120**. For example, a network node **110** may simultaneously transmit a DL transmission to a first UE **120** and receive an UL transmission from a second UE **120** in the same time resources. In some other examples, full-duplex operation may be enabled for both a network node **110** and a UE **120**.

[0053] In some examples, the UEs **120** and the network nodes **110** may perform MIMO communication. “MIMO” generally refers to transmitting or receiving multiple signals (such as multiple layers or multiple data streams) simultaneously over the same time and frequency resources. MIMO techniques generally exploit multipath propagation. MIMO may be implemented using various spatial processing or spatial multiplexing operations. In some examples, MIMO may support simultaneous transmission to multiple receivers, referred to as multi-user MIMO (MU-MIMO). Some

radio access technologies (RATs) may employ advanced MIMO techniques, such as mTRP operation (including redundant transmission or reception on multiple TRPs), reciprocity in the time domain or the frequency domain, single-frequency-network (SFN) transmission, or non-coherent joint transmission (NC-JT).

[0054] In some aspects, the UE **120** may include a communication manager **140**. As described in more detail elsewhere herein, the communication manager **140** may receive an open loop power control configuration for a PUSCH communication. The open loop power control configuration may include rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode. The communication manager **140** may transmit the PUSCH communication in accordance with the open loop power control configuration. Additionally, or alternatively, the communication manager **140** may perform one or more other operations described herein.

[0055] In some aspects, the network node **110** may include a communication manager **150**. As described in more detail elsewhere herein, the communication manager **150** may output, to a UE (such as UE **120**), an open loop power control configuration for a PUSCH communication. As discussed above, the open loop power control configuration may include rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode. The communication manager **150** may receive the PUSCH communication in accordance with the open loop power control configuration. Additionally, or alternatively, the communication manager **150** may perform one or more other operations described herein.

[0056] As indicated above, FIG. 1 is provided as an example. Other examples may differ from what is described with regard to FIG. 1.

[0057] FIG. 2 is a diagram illustrating an example network node **110** in communication with an example UE **120** in a wireless network in accordance with the present disclosure.

[0058] As shown in FIG. 2, the network node **110** may include a data source **212**, a transmit processor **214**, a transmit (TX) MIMO processor **216**, a set of modems **232** (shown as **232a** through **232t**, where $t \geq 1$), a set of antennas **234** (shown as **234a** through **234v**, where $v \geq 1$), a MIMO detector **236**, a receive processor **238**, a data sink **239**, a controller/processor **240**, a memory **242**, a communication unit **244**, a scheduler **246**, and/or a communication manager **150**, among other examples. In some configurations, one or a combination of the antenna(s) **234**, the modem(s) **232**, the MIMO detector **236**, the receive processor **238**, the transmit processor **214**, and/or the TX MIMO processor **216** may be included in a transceiver of the network node **110**. The transceiver may be under control of and used by one or more processors, such as the controller/processor **240**, and in some aspects in conjunction with processor-readable code stored in the memory **242**, to perform aspects of the methods, processes, and/or operations described herein. In some aspects, the network node **110** may include one or more interfaces, communication components, and/or other components that facilitate communication with the UE **120** or another network node.

[0059] The terms “processor,” “controller,” or “controller/processor” may refer to one or more controllers and/or one or more processors. For example, reference to “a/the pro-

cessor,” “a/the controller/processor,” or the like (in the singular) should be understood to refer to any one or more of the processors described in connection with FIG. 2, such as a single processor or a combination of multiple different processors. Reference to “one or more processors” should be understood to refer to any one or more of the processors described in connection with FIG. 2. For example, one or more processors of the network node 110 may include transmit processor 214, TX MIMO processor 216, MIMO detector 236, receive processor 238, and/or controller/processor 240. Similarly, one or more processors of the UE 120 may include MIMO detector 256, receive processor 258, transmit processor 264, TX MIMO processor 266, and/or controller/processor 280.

[0060] In some aspects, a single processor may perform all of the operations described as being performed by the one or more processors. In some aspects, a first set of (one or more) processors of the one or more processors may perform a first operation described as being performed by the one or more processors, and a second set of (one or more) processors of the one or more processors may perform a second operation described as being performed by the one or more processors. The first set of processors and the second set of processors may be the same set of processors or may be different sets of processors. Reference to “one or more memories” should be understood to refer to any one or more memories of a corresponding device, such as the memory described in connection with FIG. 2. For example, operation described as being performed by one or more memories can be performed by the same subset of the one or more memories or different subsets of the one or more memories.

[0061] For downlink communication from the network node 110 to the UE 120, the transmit processor 214 may receive data (“downlink data”) intended for the UE 120 (or a set of UEs that includes the UE 120) from the data source 212 (such as a data pipeline or a data queue). In some examples, the transmit processor 214 may select one or more MCSs for the UE 120 in accordance with one or more channel quality indicators (CQIs) received from the UE 120. The network node 110 may process the data (for example, including encoding the data) for transmission to the UE 120 on a downlink in accordance with the MCS(s) selected for the UE 120 to generate data symbols. The transmit processor 214 may process system information (for example, semi-static resource partitioning information (SRPI)) and/or control information (for example, CQI requests, grants, and/or upper layer signaling) and provide overhead symbols and/or control symbols. The transmit processor 214 may generate reference symbols for reference signals (for example, a cell-specific reference signal (CRS), a demodulation reference signal (DMRS), or a channel state information (CSI) reference signal (CSI-RS)) and/or synchronization signals (for example, a primary synchronization signal (PSS) or a secondary synchronization signals (SSS)).

[0062] The TX MIMO processor 216 may perform spatial processing (for example, precoding) on the data symbols, the control symbols, the overhead symbols, and/or the reference symbols, if applicable, and may provide a set of output symbol streams (for example, T output symbol streams) to the set of modems 232. For example, each output symbol stream may be provided to a respective modulator component (shown as MOD) of a modem 232. Each modem 232 may use the respective modulator component to process (for example, to modulate) a respective output symbol

stream (for example, for orthogonal frequency division multiplexing ((OFDM)) to obtain an output sample stream. Each modem 232 may further use the respective modulator component to process (for example, convert to analog, amplify, filter, and/or upconvert) the output sample stream to obtain a time domain downlink signal. The modems 232a through 232t may together transmit a set of downlink signals (for example, T downlink signals) via the corresponding set of antennas 234.

[0063] A downlink signal may include a DCI communication, a MAC control element (MAC-CE) communication, an RRC communication, a downlink reference signal, or another type of downlink communication. Downlink signals may be transmitted on a PDCCCH, a PDSCH, and/or on another downlink channel. A downlink signal may carry one or more transport blocks (TBs) of data. A TB may be a unit of data that is transmitted over an air interface in the wireless communication network 100. A data stream (for example, from the data source 212) may be encoded into multiple TBs for transmission over the air interface. The quantity of TBs used to carry the data associated with a particular data stream may be associated with a TB size common to the multiple TBs. The TB size may be based on or otherwise associated with radio channel conditions of the air interface, the MCS used for encoding the data, the downlink resources allocated for transmitting the data, and/or another parameter. In general, the larger the TB size, the greater the amount of data that can be transmitted in a single transmission, which reduces signaling overhead. However, larger TB sizes may be more prone to transmission and/or reception errors than smaller TB sizes, but such errors may be mitigated by more robust error correction techniques.

[0064] For uplink communication from the UE 120 to the network node 110, uplink signals from the UE 120 may be received by an antenna 234, may be processed by a modem 232 (for example, a demodulator component, shown as DEMOD, of a modem 232), may be detected by the MIMO detector 236 (for example, a receive (Rx) MIMO processor) if applicable, and/or may be further processed by the receive processor 238 to obtain decoded data and/or control information. The receive processor 238 may provide the decoded data to a data sink 239 (which may be a data pipeline, a data queue, and/or another type of data sink) and provide the decoded control information to a processor, such as the controller/processor 240.

[0065] The network node 110 may use the scheduler 246 to schedule one or more UEs 120 for downlink or uplink communications. In some aspects, the scheduler 246 may use DCI to dynamically schedule DL transmissions to the UE 120 and/or UL transmissions from the UE 120. In some examples, the scheduler 246 may allocate recurring time domain resources and/or frequency domain resources that the UE 120 may use to transmit and/or receive communications using an RRC configuration (for example, a semi-static configuration), for example, to perform semi-persistent scheduling (SPS) or to configure a configured grant (CG) for the UE 120.

[0066] One or more of the transmit processor 214, the TX MIMO processor 216, the modem 232, the antenna 234, the MIMO detector 236, the receive processor 238, and/or the controller/processor 240 may be included in an RF chain of the network node 110. An RF chain may include one or more filters, mixers, oscillators, amplifiers, analog-to-digital converters (ADCs), and/or other devices that convert between

an analog signal (such as for transmission or reception via an air interface) and a digital signal (such as for processing by one or more processors of the network node 110). In some aspects, the RF chain may be or may be included in a transceiver of the network node 110.

[0067] In some examples, the network node 110 may use the communication unit 244 to communicate with a core network and/or with other network nodes. The communication unit 244 may support wired and/or wireless communication protocols and/or connections, such as Ethernet, optical fiber, common public radio interface (CPRI), and/or a wired or wireless backhaul, among other examples. The network node 110 may use the communication unit 244 to transmit and/or receive data associated with the UE 120 or to perform network control signaling, among other examples. The communication unit 244 may include a transceiver and/or an interface, such as a network interface.

[0068] The UE 120 may include a set of antennas 252 (shown as antennas 252a through 252r, where $r \geq 1$), a set of modems 254 (shown as modems 254a through 254u, where $u \geq 1$), a MIMO detector 256, a receive processor 258, a data sink 260, a data source 262, a transmit processor 264, a TX MIMO processor 266, a controller/processor 280, a memory 282, and/or a communication manager 140, among other examples. One or more of the components of the UE 120 may be included in a housing 284. In some aspects, one or a combination of the antenna(s) 252, the modem(s) 254, the MIMO detector 256, the receive processor 258, the transmit processor 264, or the TX MIMO processor 266 may be included in a transceiver that is included in the UE 120. The transceiver may be under control of and used by one or more processors, such as the controller/processor 280, and in some aspects in conjunction with processor-readable code stored in the memory 282, to perform aspects of the methods, processes, or operations described herein. In some aspects, the UE 120 may include another interface, another communication component, and/or another component that facilitates communication with the network node 110 and/or another UE 120.

[0069] For downlink communication from the network node 110 to the UE 120, the set of antennas 252 may receive the downlink communications or signals from the network node 110 and may provide a set of received downlink signals (for example, R received signals) to the set of modems 254. For example, each received signal may be provided to a respective demodulator component (shown as DEMOD) of a modem 254. Each modem 254 may use the respective demodulator component to condition (for example, filter, amplify, downconvert, and/or digitize) a received signal to obtain input samples. Each modem 254 may use the respective demodulator component to further demodulate or process the input samples (for example, for OFDM) to obtain received symbols. The MIMO detector 256 may obtain received symbols from the set of modems 254, may perform MIMO detection on the received symbols if applicable, and may provide detected symbols. The receive processor 258 may process (for example, decode) the detected symbols, may provide decoded data for the UE 120 to the data sink 260 (which may include a data pipeline, a data queue, and/or an application executed on the UE 120), and may provide decoded control information and system information to the controller/processor 280.

[0070] For uplink communication from the UE 120 to the network node 110, the transmit processor 264 may receive

and process data (“uplink data”) from a data source 262 (such as a data pipeline, a data queue, and/or an application executed on the UE 120) and control information from the controller/processor 280. The control information may include one or more parameters, feedback, one or more signal measurements, and/or other types of control information. In some aspects, the receive processor 258 and/or the controller/processor 280 may determine, for a received signal (such as received from the network node 110 or another UE), one or more parameters relating to transmission of the uplink communication. The one or more parameters may include a reference signal received power (RSRP) parameter, a received signal strength indicator (RSSI) parameter, a reference signal received quality (RSRQ) parameter, a channel quality indicator (CQI) parameter, or a transmit power control (TPC) parameter, among other examples. The control information may include an indication of the RSRP parameter, the RSSI parameter, the RSRQ parameter, the CQI parameter, the TPC parameter, and/or another parameter. The control information may facilitate parameter selection and/or scheduling for the UE 120 by the network node 110.

[0071] The transmit processor 264 may generate reference symbols for one or more reference signals, such as an uplink DMRS, an uplink SRS, and/or another type of reference signal. The symbols from the transmit processor 264 may be precoded by the TX MIMO processor 266, if applicable, and further processed by the set of modems 254 (for example, for DFT-s-OFDM or CP-OFDM). The TX MIMO processor 266 may perform spatial processing (for example, precoding) on the data symbols, the control symbols, the overhead symbols, and/or the reference symbols, if applicable, and may provide a set of output symbol streams (for example, U output symbol streams) to the set of modems 254. For example, each output symbol stream may be provided to a respective modulator component (shown as MOD) of a modem 254. Each modem 254 may use the respective modulator component to process (for example, to modulate) a respective output symbol stream (for example, for OFDM) to obtain an output sample stream. Each modem 254 may further use the respective modulator component to process (for example, convert to analog, amplify, filter, and/or upconvert) the output sample stream to obtain an uplink signal.

[0072] The modems 254a through 254u may transmit a set of uplink signals (for example, R uplink signals or U uplink symbols) via the corresponding set of antennas 252. An uplink signal may include a UCI communication, a MAC-CE communication, an RRC communication, or another type of uplink communication. Uplink signals may be transmitted on a PUSCH, a PUCCH, and/or another type of uplink channel. An uplink signal may carry one or more TBs of data. Sidelink data and control transmissions (that is, transmissions directly between two or more UEs 120) may generally use similar techniques as were described for uplink data and control transmission, and may use sidelink-specific channels such as a physical sidelink shared channel (PSSCH), a physical sidelink control channel (PSCCH), and/or a physical sidelink feedback channel (PSFCH).

[0073] One or more antennas of the set of antennas 252 or the set of antennas 234 may include, or may be included within, one or more antenna panels, one or more antenna groups, one or more sets of antenna elements, or one or more antenna arrays, among other examples. An antenna panel, an

antenna group, a set of antenna elements, or an antenna array may include one or more antenna elements (within a single housing or multiple housings), a set of coplanar antenna elements, a set of non-coplanar antenna elements, or one or more antenna elements coupled with one or more transmission or reception components, such as one or more components of FIG. 2. As used herein, “antenna” can refer to one or more antennas, one or more antenna panels, one or more antenna groups, one or more sets of antenna elements, or one or more antenna arrays. “Antenna panel” can refer to a group of antennas (such as antenna elements) arranged in an array or panel, which may facilitate beamforming by manipulating parameters of the group of antennas. “Antenna module” may refer to circuitry including one or more antennas, which may also include one or more other components (such as filters, amplifiers, or processors) associated with integrating the antenna module into a wireless communication device.

[0074] In some examples, each of the antenna elements of an antenna 234 or an antenna 252 may include one or more sub-elements for radiating or receiving radio frequency signals. For example, a single antenna element may include a first sub-element cross-polarized with a second sub-element that can be used to independently transmit cross-polarized signals. The antenna elements may include patch antennas, dipole antennas, and/or other types of antennas arranged in a linear pattern, a two-dimensional pattern, or another pattern. A spacing between antenna elements may be such that signals with a desired wavelength transmitted separately by the antenna elements may interact or interfere constructively and destructively along various directions (such as to form a desired beam). For example, given an expected range of wavelengths or frequencies, the spacing may provide a quarter wavelength, a half wavelength, or another fraction of a wavelength of spacing between neighboring antenna elements to allow for the desired constructive and destructive interference patterns of signals transmitted by the separate antenna elements within that expected range.

[0075] The amplitudes and/or phases of signals transmitted via antenna elements and/or sub-elements may be modulated and shifted relative to each other (such as by manipulating phase shift, phase offset, and/or amplitude) to generate one or more beams, which is referred to as beamforming. The term “beam” may refer to a directional transmission of a wireless signal toward a receiving device or otherwise in a desired direction. “Beam” may also generally refer to a direction associated with such a directional signal transmission, a set of directional resources associated with the signal transmission (for example, an angle of arrival, a horizontal direction, and/or a vertical direction), and/or a set of parameters that indicate one or more aspects of a directional signal, a direction associated with the signal, and/or a set of directional resources associated with the signal. In some implementations, antenna elements may be individually selected or deselected for directional transmission of a signal (or signals) by controlling amplitudes of one or more corresponding amplifiers and/or phases of the signal(s) to form one or more beams. The shape of a beam (such as the amplitude, width, and/or presence of side lobes) and/or the direction of a beam (such as an angle of the beam relative to a surface of an antenna array) can be dynamically controlled by modifying the phase shifts, phase offsets, and/or amplitudes of the multiple signals relative to each other.

[0076] Different UEs 120 or network nodes 110 may include different numbers of antenna elements. For example, a UE 120 may include a single antenna element, two antenna elements, four antenna elements, eight antenna elements, or a different number of antenna elements. As another example, a network node 110 may include eight antenna elements, 24 antenna elements, 64 antenna elements, 128 antenna elements, or a different number of antenna elements. Generally, a larger number of antenna elements may provide increased control over parameters for beam generation relative to a smaller number of antenna elements, whereas a smaller number of antenna elements may be less complex to implement and may use less power than a larger number of antenna elements. Multiple antenna elements may support multiple-layer transmission, in which a first layer of a communication (which may include a first data stream) and a second layer of a communication (which may include a second data stream) are transmitted using the same time and frequency resources with spatial multiplexing.

[0077] While blocks in FIG. 2 are illustrated as distinct components, the functions described above with respect to the blocks may be implemented in a single hardware, software, or combination component or in various combinations of components. For example, the functions described with respect to the transmit processor 264, the receive processor 258, and/or the TX MIMO processor 266 may be performed by or under the control of the controller/processor 280.

[0078] As indicated above, FIG. 2 is provided as an example. Other examples may differ from what is described with regard to FIG. 2.

[0079] FIG. 3 is a diagram illustrating an example disaggregated base station architecture 300 in accordance with the present disclosure. One or more components of the example disaggregated base station architecture 300 may be, may include, or may be included in one or more network nodes (such one or more network nodes 110). The disaggregated base station architecture 300 may include a CU 310 that can communicate directly with a core network 320 via a backhaul link, or that can communicate indirectly with the core network 320 via one or more disaggregated control units, such as a Non-RT RIC 350 associated with a Service Management and Orchestration (SMO) Framework 360 and/or a Near-RT RIC 370 (for example, via an E2 link). The CU 310 may communicate with one or more DUs 330 via respective midhaul links, such as via F1 interfaces. Each of the DUs 330 may communicate with one or more RUs 340 via respective fronthaul links. Each of the RUs 340 may communicate with one or more UEs 120 via respective RF access links. In some deployments, a UE 120 may be simultaneously served by multiple RUs 340.

[0080] Each of the components of the disaggregated base station architecture 300, including the CUs 310, the DUs 330, the RUs 340, the Near-RT RICs 370, the Non-RT RICs 350, and the SMO Framework 360, may include one or more interfaces or may be coupled with one or more interfaces for receiving or transmitting signals, such as data or information, via a wired or wireless transmission medium.

[0081] In some aspects, the CU 310 may be logically split into one or more CU-UP units and one or more CU-CP units. A CU-UP unit may communicate bidirectionally with a CU-CP unit via an interface, such as the E1 interface when implemented in an O-RAN configuration. The CU 310 may be deployed to communicate with one or more DUs 330, as

necessary, for network control and signaling. Each DU 330 may correspond to a logical unit that includes one or more base station functions to control the operation of one or more RUs 340. For example, a DU 330 may host various layers, such as an RLC layer, a MAC layer, or one or more PHY layers, such as one or more high PHY layers or one or more low PHY layers. Each layer (which also may be referred to as a module) may be implemented with an interface for communicating signals with other layers (and modules) hosted by the DU 330, or for communicating signals with the control functions hosted by the CU 310. Each RU 340 may implement lower layer functionality. In some aspects, real-time and non-real-time aspects of control and user plane communication with the RU(s) 340 may be controlled by the corresponding DU 330.

[0082] The SMO Framework 360 may support RAN deployment and provisioning of non-virtualized and virtualized network elements. For non-virtualized network elements, the SMO Framework 360 may support the deployment of dedicated physical resources for RAN coverage requirements, which may be managed via an operations and maintenance interface, such as an O1 interface. For virtualized network elements, the SMO Framework 360 may interact with a cloud computing platform (such as an open cloud (O-Cloud) platform 390) to perform network element life cycle management (such as to instantiate virtualized network elements) via a cloud computing platform interface, such as an O2 interface. A virtualized network element may include, but is not limited to, a CU 310, a DU 330, an RU 340, a non-RT RIC 350, and/or a Near-RT RIC 370. In some aspects, the SMO Framework 360 may communicate with a hardware aspect of a 4G RAN, a 5G NR RAN, and/or a 6G RAN, such as an open eNB (O-eNB) 380, via an O1 interface. Additionally or alternatively, the SMO Framework 360 may communicate directly with each of one or more RUs 340 via a respective O1 interface. In some deployments, this configuration can enable each DU 330 and the CU 310 to be implemented in a cloud-based RAN architecture, such as a vRAN architecture.

[0083] The Non-RT RIC 350 may include or may implement a logical function that enables non-real-time control and optimization of RAN elements and resources, artificial intelligence and/or machine learning (AI/ML) workflows including model training and updates, and/or policy-based guidance of applications and/or features in the Near-RT RIC 370. The Non-RT RIC 350 may be coupled to or may communicate with (such as via an A1 interface) the Near-RT RIC 370. The Near-RT RIC 370 may include or may implement a logical function that enables near-real-time control and optimization of RAN elements and resources via data collection and actions via an interface (such as via an E2 interface) connecting one or more CUs 310, one or more DUs 330, and/or an O-eNB with the Near-RT RIC 370.

[0084] In some aspects, to generate AI/ML models to be deployed in the Near-RT RIC 370, the Non-RT RIC 350 may receive parameters or external enrichment information from external servers. Such information may be utilized by the Near-RT RIC 370 and may be received at the SMO Framework 360 or the Non-RT RIC 350 from non-network data sources or from network functions. In some examples, the Non-RT RIC 350 or the Near-RT RIC 370 may tune RAN behavior or performance. For example, the Non-RT RIC 350 may monitor long-term trends and patterns for performance and may employ AI/ML models to perform corrective

actions via the SMO Framework 360 (such as reconfiguration via an O1 interface) or via creation of RAN management policies (such as A1 interface policies).

[0085] As indicated above, FIG. 3 is provided as an example. Other examples may differ from what is described with regard to FIG. 3.

[0086] The network node 110, the controller/processor 240 of the network node 110, the UE 120, the controller/processor 280 of the UE 120, the CU 310, the DU 330, the RU 340, or any other component(s) of FIG. 1, 2, or 3 may implement one or more techniques or perform one or more operations associated with PUSCH power control, as described in more detail elsewhere herein. For example, the controller/processor 240 of the network node 110, the controller/processor 280 of the UE 120, any other component(s) of FIG. 2, the CU 310, the DU 330, or the RU 340 may perform or direct operations of, for example, process 700 of FIG. 7, process 800 of FIG. 8, or other processes as described herein (alone or in conjunction with one or more other processors). The memory 242 may store data and program codes for the network node 110, the network node 110, the CU 310, the DU 330, or the RU 340. The memory 282 may store data and program codes for the UE 120. In some examples, the memory 242 or the memory 282 may include a non-transitory computer-readable medium storing a set of instructions (for example, code or program code) for wireless communication. The memory 242 may include one or more memories, such as a single memory or multiple different memories (of the same type or of different types). The memory 282 may include one or more memories, such as a single memory or multiple different memories (of the same type or of different types). For example, the set of instructions, when executed (for example, directly, or after compiling, converting, or interpreting) by one or more processors of the network node 110, the UE 120, the CU 310, the DU 330, or the RU 340, may cause the one or more processors to perform process 700 of FIG. 7, process 800 of FIG. 8, or other processes as described herein. In some examples, executing instructions may include running the instructions, converting the instructions, compiling the instructions, and/or interpreting the instructions, among other examples.

[0087] In some aspects, the UE 120 includes means for receiving an open loop power control configuration for a PUSCH communication. The open loop power control configuration may include rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode. The UE 120 may additionally or alternatively include means for transmitting the PUSCH communication in accordance with the open loop power control configuration. The means for the UE 120 to perform operations described herein may include, for example, one or more of communication manager 140, antenna 252, modem 254, MIMO detector 256, receive processor 258, transmit processor 264, TX MIMO processor 266, controller/processor 280, or memory 282.

[0088] In some aspects, the network node 110 includes means for outputting, to a UE (such as UE 120), an open loop power control configuration for a PUSCH communication. As discussed above, the open loop power control configuration may include rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode. The network node 110 may additionally or alternatively

include means for receiving the PUSCH communication in accordance with the open loop power control configuration. The means for the network node to perform operations described herein may include, for example, one or more of communication manager 150, transmit processor 220, TX MIMO processor 230, modem 232, antenna 234, MIMO detector 236, receive processor 238, controller/processor 240, memory 242, or scheduler 246.

[0089] FIG. 4 is a diagram illustrating examples 400, 405, and 410 of full-duplex communication in a wireless network, in accordance with the present disclosure. “Full-duplex communication” in a wireless network refers to simultaneous bi-directional communication between devices in the wireless network. For example, a UE (e.g., UE 120) operating in a full-duplex mode may transmit an uplink communication and receive a downlink communication at the same time (e.g., in the same slot or the same symbol). “Half-duplex communication” in a wireless network refers to unidirectional communications (e.g., only downlink communication or only uplink communication) between devices at a given time (e.g., in a given slot or a given symbol).

[0090] As shown in FIG. 4, examples 400 and 405 show examples of in-band full-duplex (IBFD) communication. In IBFD, a UE may transmit an uplink communication to a network node (e.g., network node 110) and receive a downlink communication from the network node on the same time and frequency resources. As shown in example 400, in a first example of IBFD, the time and frequency resources for uplink communication may fully overlap with the time and frequency resources for downlink communication. As shown in example 405, in a second example of IBFD, the time and frequency resources for uplink communication may partially overlap with the time and frequency resources for downlink communication.

[0091] As further shown in FIG. 4, example 410 shows an example of sub-band full-duplex (SBFD) communication, which may also be referred to as “sub-band frequency division duplex (SBFDD)” or “flexible duplex.” In SBFD, a UE may transmit an uplink communication to a network node and receive a downlink communication from the network node at the same time, but on different frequency resources. For example, the different frequency resources may be sub-bands of a frequency band, such as a time division duplexing band. In this case, the frequency resources used for downlink communication may be separated from the frequency resources used for uplink communication, in the frequency domain, by a guard band.

[0092] As indicated above, FIG. 4 is provided as an example. Other examples may differ from what is described with respect to FIG. 4.

[0093] FIG. 5 is a diagram illustrating an example 500 of SRS resource sets, in accordance with the present disclosure.

[0094] A UE 120 may be configured with one or more SRS resource sets to allocate resources for SRS transmissions by the UE 120. For example, a configuration for SRS resource sets may be indicated in an RRC message (e.g., an RRC configuration message or an RRC reconfiguration message). As shown by reference number 505, an SRS resource set may include one or more resources (e.g., shown as SRS resources), which may include time resources and/or frequency resources (e.g., a slot, a symbol, a resource block, and/or a periodicity for the time resources).

[0095] As shown by reference number 510, an SRS resource may include one or more antenna ports on which an

SRS is to be transmitted (e.g., in a time-frequency resource). Thus, a configuration for an SRS resource set may indicate one or more time-frequency resources in which an SRS is to be transmitted and may indicate one or more antenna ports on which the SRS is to be transmitted in those time-frequency resources. In some aspects, the configuration for an SRS resource set may indicate a use case (e.g., in an SRS-SetUse information element) for the SRS resource set. For example, an SRS resource set may have a use case of antenna switching, codebook, non-codebook, or beam management.

[0096] An antenna switching SRS resource set may be used to indicate downlink CSI with reciprocity between an uplink and downlink channel. For example, when there is reciprocity between an uplink channel and a downlink channel, a network node 110 may use an antenna switching SRS (e.g., an SRS transmitted using a resource of an antenna switching SRS resource set) to acquire downlink CSI (e.g., to determine a downlink precoder to be used to communicate with the UE 120).

[0097] A codebook SRS resource set may be used to indicate uplink CSI when a network node 110 indicates an uplink precoder to the UE 120. For example, when the network node 110 is configured to indicate an uplink precoder to the UE 120 (e.g., using a precoder codebook), the network node 110 may use a codebook SRS (e.g., an SRS transmitted using a resource of a codebook SRS resource set) to acquire uplink CSI (e.g., to determine an uplink precoder to be indicated to the UE 120 and used by the UE 120 to communicate with the network node 110). In some aspects, virtual ports (e.g., a combination of two or more antenna ports) with a maximum transmit power may be supported at least for a codebook SRS.

[0098] A non-codebook SRS resource set may be used to indicate uplink CSI when the UE 120 selects an uplink precoder (e.g., instead of the network node 110 indicated an uplink precoder to be used by the UE 120. For example, when the UE 120 is configured to select an uplink precoder, the network node 110 may use a non-codebook SRS (e.g., an SRS transmitted using a resource of a non-codebook SRS resource set) to acquire uplink CSI. In this case, the non-codebook SRS may be precoded using a precoder selected by the UE 120 (e.g., which may be indicated to the network node 110).

[0099] A beam management SRS resource set may be used for indicating CSI for millimeter wave communications.

[0100] An SRS resource can be configured as periodic, semi-persistent (sometimes referred to as semi-persistent scheduling (SPS)), or aperiodic. A periodic SRS resource may be configured via a configuration message that indicates a periodicity of the SRS resource (e.g., a slot-level periodicity, where the SRS resources occurs every Y slots) and a slot offset. In some cases, a periodic SRS resource may always be activated, and may not be dynamically activated or deactivated. A semi-persistent SRS resource may also be configured via a configuration message that indicates a periodicity and a slot offset for the semi-persistent SRS resource, and may be dynamically activated and deactivated (e.g., using DCI or a MAC-CE). An aperiodic SRS resource may be triggered dynamically, such as via DCI (e.g., UE-specific DCI or group common DCI) or a MAC-CE.

[0101] In some aspects, the UE 120 may be configured with a mapping between SRS ports (e.g., antenna ports) and corresponding SRS resources. The UE 120 may transmit an

SRS on a particular SRS resource using an SRS port indicated in the configuration. In some aspects, an SRS resource may span N adjacent symbols within a slot (e.g., where N equals 1, 2, or 4). The UE 120 may be configured with X SRS ports (e.g., where $X \leq 4$). In some aspects, each of the X SRS ports may be mapped to a corresponding symbol of the SRS resource and used for transmission of an SRS in that symbol.

[0102] As shown in FIG. 5, in some aspects, different SRS resource sets indicated to the UE 120 (e.g., having different use cases) may overlap (e.g., in time and/or in frequency, such as in the same slot). For example, as shown by reference number 515, a first SRS resource set (e.g., shown as SRS Resource Set 1) is shown as having an antenna switching use case. As shown, this example antenna switching SRS resource set includes a first SRS resource (shown as SRS Resource A) and a second SRS resource (shown as SRS Resource B). Thus, antenna switching SRS may be transmitted in SRS Resource A (e.g., a first time-frequency resource) using antenna port 0 and antenna port 1 and may be transmitted in SRS Resource B (e.g., a second time-frequency resource) using antenna port 2 and antenna port 3.

[0103] As shown by reference number 520, a second SRS resource set (e.g., shown as SRS Resource Set 2) may be a codebook use case. As shown, this example codebook SRS resource set includes only the first SRS resource (shown as SRS Resource A). Thus, codebook SRSs may be transmitted in SRS Resource A (e.g., the first time-frequency resource) using antenna port 0 and antenna port 1. In this case, the UE 120 may not transmit codebook SRSs in SRS Resource B (e.g., the second time-frequency resource) using antenna port 2 and antenna port 3.

[0104] In some aspects, the SRS may be transmitted according to a power control configuration, such as an open loop power control configuration, discussed in greater detail below. With the open loop power control configuration, the UE may be configured to transmit the SRS on one or more SRS resource sets in accordance with a transmission power that minimizes self-interference for half-duplex and full-duplex communications.

[0105] As indicated above, FIG. 5 is provided as an example. Other examples may differ from what is described with regard to FIG. 5.

[0106] FIG. 6 is a diagram of an example 600 associated with PUSCH power control, in accordance with the present disclosure. As shown in FIG. 6, a network node (e.g., network node 110, a CU, a DU, and/or an RU) may communicate with a UE (e.g., UE 120). In some aspects, the network node and the UE may be part of a wireless network (e.g., wireless network 100). The UE and the network node may have established a wireless connection prior to operations shown in FIG. 6.

[0107] As shown by reference number 605, the network node may transmit, and the UE may receive, configuration information. In some aspects, the UE may receive the configuration information via one or more of system information (e.g., a master information block (MIB) and/or a system information block (SIB), among other examples), RRC signaling, one or more MAC-CEs, and/or downlink control information (DCI), among other examples.

[0108] In some aspects, the configuration information may indicate one or more candidate configurations and/or communication parameters. In some aspects, the one or more candidate configurations and/or communication parameters

may be selected, activated, and/or deactivated by a subsequent indication. For example, the subsequent indication may indicate a candidate configuration and/or communication parameter from the one or more candidate configurations and/or communication parameters. In some aspects, the subsequent indication (e.g., an indication described herein) may include a dynamic indication, such as one or more MAC CEs and/or one or more DCI messages, among other examples.

[0109] In some aspects, the configuration information may indicate that the UE is to apply rules in accordance with an open loop power control configuration for PUSCH communications. For example, the configuration information may indicate that the UE is to apply rules for one or more SRS resource sets, each of the SRS resource sets being associated with one or more of a half-duplex mode or a full-duplex mode. The UE may configure itself based at least in part on the configuration information. In some aspects, the UE may be configured to perform one or more operations described herein based at least in part on the configuration information.

[0110] As shown by reference number 610, the UE may transmit, and the network node may receive, a capabilities report. The capabilities report may indicate whether the UE supports a feature and/or one or more parameters related to the feature. For example, the capability information may indicate a capability and/or parameter for open loop power control for PUSCH communications. As another example, the capabilities report may indicate a capability and/or parameter for SRS resource sets for operating in a half-duplex mode, a full-duplex mode, and/or a combination thereof, among other examples. One or more operations described herein may be based on capability information of the capabilities report. For example, the UE may perform a communication in accordance with the capability information, or may receive configuration information that is in accordance with the capability information. In some aspects, the capabilities report may indicate UE support for PUSCH communications in accordance with the open loop power control configuration.

[0111] In some aspects, the configuration information described in connection with reference number 605 and/or the capabilities report may include information transmitted via multiple communications. Additionally, or alternatively, the network node may transmit the configuration information, or a communication including at least a portion of the configuration information, before and/or after the UE transmits the capabilities report. For example, the network node may transmit a first portion of the configuration information before the capabilities report, the UE may transmit at least a portion of the capabilities report, and the network node may transmit a second portion of the configuration information after receiving the capabilities report.

[0112] As shown by reference number 615, the UE may receive, and the network node may transmit, an activation signal. The activation signal may indicate, to the UE, to transmit a PUSCH communication in accordance with the open loop power control configuration. In some aspects, the activation signal may include a dynamic grant for the PUSCH communication.

[0113] As shown by reference number 620, the UE may configure itself, based at least in part on receiving the indication described in connection with reference number 615 to transmit PUSCH communications in accordance with the open loop power control configuration. For example, the

UE may configure itself to apply a first nominal transmit power parameter ($P_{0,1}$) for transmitting the PUSCH communication at a nominal transmit power while the UE operates in the full-duplex mode. In some aspects, the first nominal transmit power parameter may include (e.g., be defined in accordance with) an offset relative to a second nominal transmit power parameter ($P_{0,2}$).

[0114] In some aspects, the open loop power control configuration may configure the UE to apply a first path loss parameter associated with transmitting the PUSCH communication in the full-duplex mode. In some aspects, the open loop power control configuration may configure the UE to apply a second path loss parameter associated with transmitting the PUSCH communication in the half-duplex mode. In some aspects, the open loop power control configuration may configure the UE to calculate a path loss using the first path loss parameter, the second path loss parameter, and/or a combination thereof, among other examples. In some aspects, the first path loss parameter and/or the second path loss parameter may include an alpha set identifier. The alpha set identifier may be associated with a path loss compensation factor (alpha). In some aspects, the open loop power control configuration may configure the UE to calculate an initial transmit power and path loss using an alpha set identifier indicated by an SRS resource indicator (SRI).

[0115] In some aspects, the open loop power control configuration may include different pairs of parameters. As discussed above, each parameter may include a value for a nominal PUSCH power (P_0) and a path loss compensation factor (alpha). In some aspects, the open loop power control configuration may include a first pair of parameters for the full-duplex mode and a second pair of parameters, different from the first pair of parameters, for the half-duplex mode. In some aspects, the second pair of parameters may be associated with the SRI.

[0116] As shown by reference number 625, the UE may transmit PUSCH communications to the network node based at least in part on the open loop power control configuration. For example, the UE may transmit the PUSCH communication to the network node over multiple layers via a dynamic grant ($j > 1$, where j represents the number of layers).

[0117] By applying the open loop power control configuration as described herein (e.g., determining the transmit power parameter P_0 and path loss compensation factor (alpha) based on whether the UE is operating in a full-duplex mode or a half-duplex mode, the UE may mitigate inter-cell interference, optimize battery usage, and improve channel conditions.

[0118] As indicated above, FIG. 6 is provided as an example. Other examples may differ from what is described with respect to FIG. 6.

[0119] FIG. 7 is a diagram illustrating an example process 700 performed, for example, at a UE or an apparatus of a UE, in accordance with the present disclosure. Example process 700 is an example where the apparatus or the UE (e.g., UE 120) performs operations associated with PUSCH power control.

[0120] As shown in FIG. 7, in some aspects, process 700 may include receiving an open loop power control configuration for a PUSCH communication. The open loop power control configuration may include rules for one or more SRS resource sets, each SRS resource set being associated with

one or more of a half-duplex mode or a full-duplex mode (block 710). For example, the UE (e.g., using reception component 902 and/or communication manager 906, depicted in FIG. 9) may receive an open loop power control configuration for a PUSCH communication as described above. In some aspects, as discussed above, the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode.

[0121] As further shown in FIG. 7, in some aspects, process 700 may include transmitting the PUSCH communication in accordance with the open loop power control configuration (block 720). For example, the UE (e.g., using transmission component 904 and/or communication manager 906, depicted in FIG. 9) may transmit the PUSCH communication in accordance with the open loop power control configuration, as described above.

[0122] Process 700 may include additional aspects, such as any single aspect or any combination of aspects described below and/or in connection with one or more other processes described elsewhere herein.

[0123] In a first aspect, process 700 includes receiving a dynamic grant for the PUSCH communication.

[0124] In a second aspect, alone or in combination with the first aspect, the open loop power control configuration includes a first nominal transmit power parameter for transmitting the PUSCH communication at a nominal transmit power in the full-duplex mode.

[0125] In a third aspect, alone or in combination with one or more of the first and second aspects, the first nominal transmit power parameter includes an offset relative to a second nominal transmit power parameter.

[0126] In a fourth aspect, alone or in combination with one or more of the first through third aspects, the open loop power control configuration includes a first pair of parameters for full-duplex mode and a second pair of parameters for half-duplex mode.

[0127] In a fifth aspect, alone or in combination with one or more of the first through fourth aspects, the second pair of parameters is associated with an SRI.

[0128] In a sixth aspect, alone or in combination with one or more of the first through fifth aspects, the open loop power control configuration includes a first path loss parameter for transmitting the PUSCH communication in the full-duplex mode and a second path loss parameter for transmitting the PUSCH communication in the half-duplex mode.

[0129] In a seventh aspect, alone or in combination with one or more of the first through sixth aspects, process 700 includes calculating a path loss using one of the first path loss parameter or the second path loss parameter.

[0130] In an eighth aspect, alone or in combination with one or more of the first through seventh aspects, one or more of the first path loss parameter or the second path loss parameter includes an alpha set identifier.

[0131] In a ninth aspect, alone or in combination with one or more of the first through eighth aspects, process 700 includes calculating an initial transmit power and path loss using an alpha set identifier indicated by an SRI.

[0132] Although FIG. 7 shows example blocks of process 700, in some aspects, process 700 may include additional blocks, fewer blocks, different blocks, or differently arranged blocks than those depicted in FIG. 7. Additionally,

or alternatively, two or more of the blocks of process 700 may be performed in parallel.

[0133] FIG. 8 is a diagram illustrating an example process 800 performed, for example, at a network node or an apparatus of a network node, in accordance with the present disclosure. Example process 800 is an example where the apparatus or the network node (e.g., network node 110) performs operations associated with PUSCH power control.

[0134] As shown in FIG. 8, in some aspects, process 800 may include outputting, to a UE, an open loop power control configuration for a PUSCH communication, wherein the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode (block 810). For example, the network node (e.g., using transmission component 1004 and/or communication manager 1006, depicted in FIG. 10) may output, to a UE, an open loop power control configuration for a PUSCH communication, as described above. In some aspects, the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode.

[0135] As further shown in FIG. 8, in some aspects, process 800 may include receiving the PUSCH communication in accordance with the open loop power control configuration (block 820). For example, the network node (e.g., using reception component 1002 and/or communication manager 1006, depicted in FIG. 10) may receive the PUSCH communication in accordance with the open loop power control configuration, as described above.

[0136] Process 800 may include additional aspects, such as any single aspect or any combination of aspects described below and/or in connection with one or more other processes described elsewhere herein.

[0137] In a first aspect, process 800 includes outputting, to the UE, a dynamic grant for the PUSCH communication.

[0138] In a second aspect, alone or in combination with the first aspect, the open loop power control configuration includes a first nominal transmit power parameter for transmitting the PUSCH communication at a nominal transmit power in the full-duplex mode.

[0139] In a third aspect, alone or in combination with one or more of the first and second aspects, the first nominal transmit power parameter includes an offset relative to a second nominal transmit power parameter.

[0140] In a fourth aspect, alone or in combination with one or more of the first through third aspects, the open loop power control configuration includes a first pair of parameters for full-duplex mode and a second pair of parameters for half-duplex mode.

[0141] In a fifth aspect, alone or in combination with one or more of the first through fourth aspects, the second pair of parameters is associated with an SRI.

[0142] In a sixth aspect, alone or in combination with one or more of the first through fifth aspects, the open loop power control configuration includes a first path loss parameter for transmitting the PUSCH communication in the full-duplex mode and a second path loss parameter for transmitting the PUSCH communication in the half-duplex mode.

[0143] In a seventh aspect, alone or in combination with one or more of the first through sixth aspects, process 800

includes configuring the UE to calculate a path loss using one of the first path loss parameter or the second path loss parameter.

[0144] In an eighth aspect, alone or in combination with one or more of the first through seventh aspects, one or more of the first path loss parameter or the second path loss parameter includes an alpha set identifier.

[0145] In a ninth aspect, alone or in combination with one or more of the first through eighth aspects, process 800 includes configuring the UE to calculate an initial transmit power and path loss using an alpha set identifier indicated by an SRI.

[0146] Although FIG. 8 shows example blocks of process 800, in some aspects, process 800 may include additional blocks, fewer blocks, different blocks, or differently arranged blocks than those depicted in FIG. 8. Additionally, or alternatively, two or more of the blocks of process 800 may be performed in parallel.

[0147] FIG. 9 is a diagram of an example apparatus 900 for wireless communication, in accordance with the present disclosure. The apparatus 900 may be a UE, or a UE may include the apparatus 900. In some aspects, the apparatus 900 includes a reception component 902, a transmission component 904, and/or a communication manager 906, which may be in communication with one another (for example, via one or more buses and/or one or more other components). In some aspects, the communication manager 906 is the communication manager 140 described in connection with FIG. 1. As shown, the apparatus 900 may communicate with another apparatus 908, such as a UE or a network node (such as a CU, a DU, an RU, or a base station), using the reception component 902 and the transmission component 904.

[0148] In some aspects, the apparatus 900 may be configured to perform one or more operations described herein in connection with FIGS. 4-6. Additionally, or alternatively, the apparatus 900 may be configured to perform one or more processes described herein, such as process 700 of FIG. 7. In some aspects, the apparatus 900 and/or one or more components shown in FIG. 9 may include one or more components of the UE described in connection with FIG. 2. Additionally, or alternatively, one or more components shown in FIG. 9 may be implemented within one or more components described in connection with FIG. 2. Additionally, or alternatively, one or more components of the set of components may be implemented at least in part as software stored in one or more memories. For example, a component (or a portion of a component) may be implemented as instructions or code stored in a non-transitory computer-readable medium and executable by one or more controllers or one or more processors to perform the functions or operations of the component.

[0149] The reception component 902 may receive communications, such as reference signals, control information, data communications, or a combination thereof, from the apparatus 908. The reception component 902 may provide received communications to one or more other components of the apparatus 900. In some aspects, the reception component 902 may perform signal processing on the received communications (such as filtering, amplification, demodulation, analog-to-digital conversion, demultiplexing, deinterleaving, de-mapping, equalization, interference cancellation, or decoding, among other examples), and may provide the processed signals to the one or more other

components of the apparatus **900**. In some aspects, the reception component **902** may include one or more antennas, one or more modems, one or more demodulators, one or more MIMO detectors, one or more receive processors, one or more controllers/processors, one or more memories, or a combination thereof, of the UE described in connection with FIG. 2.

[0150] The transmission component **904** may transmit communications, such as reference signals, control information, data communications, or a combination thereof, to the apparatus **908**. In some aspects, one or more other components of the apparatus **900** may generate communications and may provide the generated communications to the transmission component **904** for transmission to the apparatus **908**. In some aspects, the transmission component **904** may perform signal processing on the generated communications (such as filtering, amplification, modulation, digital-to-analog conversion, multiplexing, interleaving, mapping, or encoding, among other examples), and may transmit the processed signals to the apparatus **908**. In some aspects, the transmission component **904** may include one or more antennas, one or more modems, one or more modulators, one or more transmit MIMO processors, one or more transmit processors, one or more controllers/processors, one or more memories, or a combination thereof, of the UE described in connection with FIG. 2. In some aspects, the transmission component **904** may be co-located with the reception component **902** in one or more transceivers.

[0151] The communication manager **906** may support operations of the reception component **902** and/or the transmission component **904**. For example, the communication manager **906** may receive information associated with configuring reception of communications by the reception component **902** and/or transmission of communications by the transmission component **904**. Additionally, or alternatively, the communication manager **906** may generate and/or provide control information to the reception component **902** and/or the transmission component **904** to control reception and/or transmission of communications.

[0152] The reception component **902** may receive an open loop power control configuration for a PUSCH communication. The open loop power control configuration may include rules for one or more SRS resource sets, with each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode. The transmission component **904** may transmit the PUSCH communication in accordance with the open loop power control configuration. The reception component **902** may receive a dynamic grant for the PUSCH communication.

[0153] The communication manager **906** may calculate a path loss using one of the first path loss parameter or the second path loss parameter. The communication manager **906** may calculate an initial transmit power and path loss using an alpha set identifier indicated by an SRI.

[0154] The number and arrangement of components shown in FIG. 9 are provided as an example. In practice, there may be additional components, fewer components, different components, or differently arranged components than those shown in FIG. 9. Furthermore, two or more components shown in FIG. 9 may be implemented within a single component, or a single component shown in FIG. 9 may be implemented as multiple, distributed components. Additionally, or alternatively, a set of (one or more) com-

ponents shown in FIG. 9 may perform one or more functions described as being performed by another set of components shown in FIG. 9.

[0155] FIG. 10 is a diagram of an example apparatus **1000** for wireless communication, in accordance with the present disclosure. The apparatus **1000** may be a network node, or a network node may include the apparatus **1000**. In some aspects, the apparatus **1000** includes a reception component **1002**, a transmission component **1004**, and/or a communication manager **1006**, which may be in communication with one another (for example, via one or more buses and/or one or more other components). In some aspects, the communication manager **1006** is the communication manager **150** described in connection with FIG. 1. As shown, the apparatus **1000** may communicate with another apparatus **1008**, such as a UE or a network node (such as a CU, a DU, an RU, or a base station), using the reception component **1002** and the transmission component **1004**.

[0156] In some aspects, the apparatus **1000** may be configured to perform one or more operations described herein in connection with FIGS. 4-6. Additionally, or alternatively, the apparatus **1000** may be configured to perform one or more processes described herein, such as process **800** of FIG. 8. In some aspects, the apparatus **1000** and/or one or more components shown in FIG. 10 may include one or more components of the network node described in connection with FIG. 2. Additionally, or alternatively, one or more components shown in FIG. 10 may be implemented within one or more components described in connection with FIG. 2. Additionally, or alternatively, one or more components of the set of components may be implemented at least in part as software stored in one or more memories. For example, a component (or a portion of a component) may be implemented as instructions or code stored in a non-transitory computer-readable medium and executable by one or more controllers or one or more processors to perform the functions or operations of the component.

[0157] The reception component **1002** may receive communications, such as reference signals, control information, data communications, or a combination thereof, from the apparatus **1008**. The reception component **1002** may provide received communications to one or more other components of the apparatus **1000**. In some aspects, the reception component **1002** may perform signal processing on the received communications (such as filtering, amplification, demodulation, analog-to-digital conversion, demultiplexing, deinterleaving, de-mapping, equalization, interference cancellation, or decoding, among other examples), and may provide the processed signals to the one or more other components of the apparatus **1000**. In some aspects, the reception component **1002** may include one or more antennas, one or more modems, one or more demodulators, one or more MIMO detectors, one or more receive processors, one or more controllers/processors, one or more memories, or a combination thereof, of the network node described in connection with FIG. 2. In some aspects, the reception component **1002** and/or the transmission component **1004** may include or may be included in a network interface. The network interface may be configured to obtain and/or output signals for the apparatus **1000** via one or more communications links, such as a backhaul link, a midhaul link, and/or a fronthaul link.

[0158] The transmission component **1004** may transmit communications, such as reference signals, control informa-

tion, data communications, or a combination thereof, to the apparatus **1008**. In some aspects, one or more other components of the apparatus **1000** may generate communications and may provide the generated communications to the transmission component **1004** for transmission to the apparatus **1008**. In some aspects, the transmission component **1004** may perform signal processing on the generated communications (such as filtering, amplification, modulation, digital-to-analog conversion, multiplexing, interleaving, mapping, or encoding, among other examples), and may transmit the processed signals to the apparatus **1008**. In some aspects, the transmission component **1004** may include one or more antennas, one or more modems, one or more modulators, one or more transmit MIMO processors, one or more transmit processors, one or more controllers/processors, one or more memories, or a combination thereof, of the network node described in connection with FIG. 2. In some aspects, the transmission component **1004** may be co-located with the reception component **1002** in one or more transceivers.

[0159] The communication manager **1006** may support operations of the reception component **1002** and/or the transmission component **1004**. For example, the communication manager **1006** may receive information associated with configuring reception of communications by the reception component **1002** and/or transmission of communications by the transmission component **1004**. Additionally, or alternatively, the communication manager **1006** may generate and/or provide control information to the reception component **1002** and/or the transmission component **1004** to control reception and/or transmission of communications.

[0160] The transmission component **1004** may output, to a UE, an open loop power control configuration for a PUSCH communication. The open loop power control configuration may include rules for one or more SRS resource sets, with each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode. The reception component **1002** may receive the PUSCH communication in accordance with the open loop power control configuration.

[0161] The transmission component **1004** may output, to the UE, a dynamic grant for the PUSCH communication.

[0162] The communication manager **1006** may configure the UE to calculate a path loss using one of the first path loss parameter or the second path loss parameter. The communication manager **1006** may configure the UE to calculate an initial transmit power and path loss using an alpha set identifier indicated by an SRI.

[0163] The number and arrangement of components shown in FIG. 10 are provided as an example. In practice, there may be additional components, fewer components, different components, or differently arranged components than those shown in FIG. 10. Furthermore, two or more components shown in FIG. 10 may be implemented within a single component, or a single component shown in FIG. 10 may be implemented as multiple, distributed components. Additionally, or alternatively, a set of (one or more) components shown in FIG. 10 may perform one or more functions described as being performed by another set of components shown in FIG. 10.

[0164] The following provides an overview of some Aspects of the present disclosure:

[0165] Aspect 1: A method of wireless communication performed by a UE, comprising: receiving an open loop

power control configuration for a PUSCH communication, wherein the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and transmitting the PUSCH communication in accordance with the open loop power control configuration.

[0166] Aspect 2: The method of Aspect 1, further comprising receiving a dynamic grant for the PUSCH communication.

[0167] Aspect 3: The method of Aspect 2, wherein the open loop power control configuration includes a first nominal transmit power parameter for transmitting the PUSCH communication at a nominal transmit power in the full-duplex mode.

[0168] Aspect 4: The method of Aspect 3, wherein the first nominal transmit power parameter includes an offset relative to a second nominal transmit power parameter.

[0169] Aspect 5: The method of any of Aspects 1-4, wherein the open loop power control configuration includes a first pair of parameters for full-duplex mode and a second pair of parameters for half-duplex mode.

[0170] Aspect 6: The method of Aspect 5, wherein the second pair of parameters is associated with an SRI.

[0171] Aspect 7: The method of Aspect 2, wherein the open loop power control configuration includes a first path loss parameter for transmitting the PUSCH communication in the full-duplex mode and a second path loss parameter for transmitting the PUSCH communication in the half-duplex mode.

[0172] Aspect 8: The method of Aspect 7, further comprising calculating a path loss using one of the first path loss parameter or the second path loss parameter.

[0173] Aspect 9: The method of Aspect 7, wherein one or more of the first path loss parameter or the second path loss parameter includes an alpha set identifier.

[0174] Aspect 10: The method of Aspect 2, further comprising calculating an initial transmit power and path loss using an alpha set identifier indicated by an SRI.

[0175] Aspect 11: A method of wireless communication performed by a network node, comprising: outputting, to a UE, an open loop power control configuration for a PUSCH communication, wherein the open loop power control configuration includes rules for one or more SRS resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and receiving the PUSCH communication in accordance with the open loop power control configuration.

[0176] Aspect 12: The method of Aspect 11, further comprising outputting, to the UE, a dynamic grant for the PUSCH communication.

[0177] Aspect 13: The method of Aspect 12, wherein the open loop power control configuration includes a first nominal transmit power parameter for transmitting the PUSCH communication at a nominal transmit power in the full-duplex mode.

[0178] Aspect 14: The method of Aspect 13, wherein the first nominal transmit power parameter includes an offset relative to a second nominal transmit power parameter.

[0179] Aspect 15: The method of any of Aspects 11-14, wherein the open loop power control configuration includes a first pair of parameters for full-duplex mode and a second pair of parameters for half-duplex mode.

[0180] Aspect 16: The method of Aspect 15, wherein the second pair of parameters is associated with an SRI.

[0181] Aspect 17: The method of Aspect 12, wherein the open loop power control configuration includes a first path loss parameter for transmitting the PUSCH communication in the full-duplex mode and a second path loss parameter for transmitting the PUSCH communication in the half-duplex mode.

[0182] Aspect 18: The method of Aspect 17, further comprising configuring the UE to calculate a path loss using one of the first path loss parameter or the second path loss parameter.

[0183] Aspect 19: The method of Aspect 17, wherein one or more of the first path loss parameter or the second path loss parameter includes an alpha set identifier.

[0184] Aspect 20: The method of Aspect 12, further comprising configuring the UE to calculate an initial transmit power and path loss using an alpha set identifier indicated by an SRI.

[0185] Aspect 21: An apparatus for wireless communication at a device, the apparatus comprising one or more processors; one or more memories coupled with the one or more processors; and instructions stored in the one or more memories and executable by the one or more processors to cause the apparatus to perform the method of one or more of Aspects 1-20.

[0186] Aspect 22: An apparatus for wireless communication at a device, the apparatus comprising one or more memories and one or more processors coupled to the one or more memories, the one or more processors configured to cause the device to perform the method of one or more of Aspects 1-20.

[0187] Aspect 23: An apparatus for wireless communication, the apparatus comprising at least one means for performing the method of one or more of Aspects 1-20.

[0188] Aspect 24: A non-transitory computer-readable medium storing code for wireless communication, the code comprising instructions executable by one or more processors to perform the method of one or more of Aspects 1-20.

[0189] Aspect 25: A non-transitory computer-readable medium storing a set of instructions for wireless communication, the set of instructions comprising one or more instructions that, when executed by one or more processors of a device, cause the device to perform the method of one or more of Aspects 1-20.

[0190] Aspect 26: A device for wireless communication, the device comprising a processing system that includes one or more processors and one or more memories coupled with the one or more processors, the processing system configured to cause the device to perform the method of one or more of Aspects 1-20.

[0191] Aspect 27: An apparatus for wireless communication at a device, the apparatus comprising one or more memories and one or more processors coupled to the one or more memories, the one or more processors individually or collectively configured to cause the device to perform the method of one or more of Aspects 1-20.

[0192] The foregoing disclosure provides illustration and description but is not intended to be exhaustive or to limit the aspects to the precise forms disclosed. Modifications and variations may be made in light of the above disclosure or may be acquired from practice of the aspects.

[0193] As used herein, the term “component” is intended to be broadly construed as hardware or a combination of

hardware and at least one of software or firmware. “Software” shall be construed broadly to mean instructions, instruction sets, code, code segments, program code, programs, subprograms, software modules, applications, software applications, software packages, routines, subroutines, objects, executables, threads of execution, procedures, or functions, among other examples, whether referred to as software, firmware, middleware, microcode, hardware description language, or otherwise. As used herein, a “processor” is implemented in hardware or a combination of hardware and software. It will be apparent that systems or methods described herein may be implemented in different forms of hardware or a combination of hardware and software. The actual specialized control hardware or software code used to implement these systems or methods is not limiting of the aspects. Thus, the operation and behavior of the systems or methods are described herein without reference to specific software code, because those skilled in the art will understand that software and hardware can be designed to implement the systems or methods based, at least in part, on the description herein. A component being configured to perform a function means that the component has a capability to perform the function, and does not require the function to be actually performed by the component, unless noted otherwise.

[0194] As used herein, “satisfying a threshold” may, depending on the context, refer to a value being greater than the threshold, greater than or equal to the threshold, less than the threshold, less than or equal to the threshold, equal to the threshold, or not equal to the threshold, among other examples.

[0195] As used herein, a phrase referring to “at least one of” a list of items refers to any combination of those items, including single members. As an example, “at least one of: a, b, or c” is intended to cover a, b, c, a+b, a+c, b+c, and a+b+c, as well as any combination with multiples of the same element (for example, a+a, a+a+a, a+a+b, a+a+c, a+b+b, a+c+c, b+b, b+b+b, b+b+c, c+c, and c+c+c, or any other ordering of a, b, and c).

[0196] No element, act, or instruction used herein should be construed as critical or essential unless explicitly described as such. Also, as used herein, the articles “a” and “an” are intended to include one or more items and may be used interchangeably with “one or more.” Further, as used herein, the article “the” is intended to include one or more items referenced in connection with the article “the” and may be used interchangeably with “the one or more.” Furthermore, as used herein, the terms “set” and “group” are intended to include one or more items and may be used interchangeably with “one or more.” Where only one item is intended, the phrase “only one” or similar language is used. Also, as used herein, the terms “has,” “have,” “having,” and similar terms are intended to be open-ended terms that do not limit an element that they modify (for example, an element “having” A may also have B). Further, the phrase “based on” is intended to mean “based on or otherwise in association with” unless explicitly stated otherwise. Also, as used herein, the term “or” is intended to be inclusive when used in a series and may be used interchangeably with “and/or,” unless explicitly stated otherwise (for example, if used in combination with “either” or “only one of”). It should be understood that “one or more” is equivalent to “at least one.”

[0197] Even though particular combinations of features are recited in the claims or disclosed in the specification, these combinations are not intended to limit the disclosure of various aspects. Many of these features may be combined in ways not specifically recited in the claims or disclosed in the specification. The disclosure of various aspects includes each dependent claim in combination with every other claim in the claim set.

What is claimed is:

1. A user equipment (UE) for wireless communication, comprising:

one or more memories; and

one or more processors, coupled to the one or more memories, configured to cause the UE to:

receive an open loop power control configuration for a physical uplink shared channel (PUSCH) communication,

wherein the open loop power control configuration includes rules for one or more sounding reference signal (SRS) resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and

transmit the PUSCH communication in accordance with the open loop power control configuration.

2. The UE of claim 1, wherein the one or more processors are further configured to cause the UE to receive a dynamic grant for the PUSCH communication.

3. The UE of claim 2, wherein the open loop power control configuration includes a first nominal transmit power parameter for transmitting the PUSCH communication at a nominal transmit power in the full-duplex mode.

4. The UE of claim 3, wherein the first nominal transmit power parameter includes an offset relative to a second nominal transmit power parameter.

5. The UE of claim 1, wherein the open loop power control configuration includes a first pair of parameters for full-duplex mode and a second pair of parameters for half-duplex mode.

6. The UE of claim 5, wherein the second pair of parameters is associated with an SRS resource indicator (SRI).

7. The UE of claim 2, wherein the open loop power control configuration includes a first path loss parameter for transmitting the PUSCH communication in the full-duplex mode and a second path loss parameter for transmitting the PUSCH communication in the half-duplex mode.

8. The UE of claim 7, wherein the one or more processors are further configured to cause the UE to calculate a path loss using one of the first path loss parameter or the second path loss parameter.

9. The UE of claim 7, wherein one or more of the first path loss parameter or the second path loss parameter includes an alpha set identifier.

10. The UE of claim 2, wherein the one or more processors are further configured to cause the UE to calculate an initial transmit power and path loss using an alpha set identifier indicated by an SRS resource indicator (SRI).

11. A network node for wireless communication, comprising:

one or more memories; and

one or more processors, coupled to the one or more memories, configured to cause the network node to:

output, to a user equipment (UE), an open loop power control configuration for a physical uplink shared channel (PUSCH) communication,

wherein the open loop power control configuration includes rules for one or more sounding reference signal (SRS) resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and

receive the PUSCH communication in accordance with the open loop power control configuration.

12. The network node of claim 11, wherein the one or more processors are further configured to cause the network node to output, to the UE, a dynamic grant for the PUSCH communication.

13. The network node of claim 12, wherein the open loop power control configuration includes a first nominal transmit power parameter for transmitting the PUSCH communication at a nominal transmit power in the full-duplex mode.

14. The network node of claim 13, wherein the first nominal transmit power parameter includes an offset relative to a second nominal transmit power parameter.

15. The network node of claim 11, wherein the open loop power control configuration includes a first pair of parameters for full-duplex mode and a second pair of parameters for half-duplex mode.

16. The network node of claim 15, wherein the second pair of parameters is associated with an SRS resource indicator (SRI).

17. The network node of claim 12, wherein the open loop power control configuration includes a first path loss parameter for transmitting the PUSCH communication in the full-duplex mode and a second path loss parameter for transmitting the PUSCH communication in the half-duplex mode.

18. The network node of claim 17, wherein the one or more processors are further configured to cause the network node to configure the UE to calculate a path loss using one of the first path loss parameter or the second path loss parameter.

19. The network node of claim 17, wherein one or more of the first path loss parameter or the second path loss parameter includes an alpha set identifier.

20. The network node of claim 12, wherein the one or more processors are further configured to cause the network node to configure the UE to calculate an initial transmit power and path loss using an alpha set identifier indicated by an SRS resource indicator (SRI).

21. A method of wireless communication performed by a user equipment (UE), comprising:

receiving an open loop power control configuration for a physical uplink shared channel (PUSCH) communication,

wherein the open loop power control configuration includes rules for one or more sounding reference signal (SRS) resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and

transmitting the PUSCH communication in accordance with the open loop power control configuration.

22. The method of claim 21, further comprising receiving a dynamic grant for the PUSCH communication.

23. The method of claim 22, wherein the open loop power control configuration includes a first nominal transmit power

parameter for transmitting the PUSCH communication at a nominal transmit power in the full-duplex mode.

24. The method of claim **21**, wherein the open loop power control configuration includes a first pair of parameters for full-duplex mode and a second pair of parameters for half-duplex mode.

25. The method of claim **22**, wherein the open loop power control configuration includes a first path loss parameter for transmitting the PUSCH communication in the full-duplex mode and a second path loss parameter for transmitting the PUSCH communication in the half-duplex mode.

26. The method of claim **25**, further comprising calculating a path loss using one of the first path loss parameter or the second path loss parameter.

27. The method of claim **22**, further comprising calculating an initial transmit power and path loss using an alpha set identifier indicated by an SRS resource indicator (SRI).

28. A method of wireless communication performed by a network node, comprising:

outputting, to a user equipment (UE), an open loop power control configuration for a physical uplink shared channel (PUSCH) communication,

wherein the open loop power control configuration includes rules for one or more sounding reference signal (SRS) resource sets, each SRS resource set being associated with one or more of a half-duplex mode or a full-duplex mode; and

receiving the PUSCH communication in accordance with the open loop power control configuration.

29. The method of claim **28**, further comprising outputting, to the UE, a dynamic grant for the PUSCH communication.

30. The method of claim **29**, further comprising configuring the UE to calculate an initial transmit power and path loss using an alpha set identifier indicated by an SRS resource indicator (SRI).

* * * * *