

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396548
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Wang; Siwen

Brush head mounting structure of liquid spraying brush

Abstract

A brush head mounting structure of a liquid spraying brush, includes a connecting base provided at the end of a handle and a mounting base provided on a brush head; the other side of the connecting base with respect to the handle is provided with a slider, one side of the mounting base adjacent to the connecting base is provided with a sliding groove in sliding fit with the slider, a limiting structure is provided between the connecting base and the mounting base, the limiting structure is capable of limiting the connecting base and the mounting base along the sliding direction perpendicular to the slider, both sides of the mounting base corresponding to the sliding groove are provided with elastic arms, the position of the mounting base corresponding to the elastic arm is provided with an avoidance space for the elastic arm to expand outwards.

Inventors:	Wang; Siwen (Zhejiang, CN)
Applicant:	Ningbo Shijia Cleaning Tools Co., Ltd. (Zhejiang, CN)
Family ID:	1000008779220
Assignee:	Ningbo Shijia Cleaning Tools Co., Ltd. (Ningbo, CN)
Appl. No.:	17/831614
Filed:	June 03, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230232972 A1	Jul. 27, 2023

Foreign Application Priority Data

CN	202220185136.4	Jan. 24, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: A46B7/04 (20060101); A46B7/02 (20060101); A46B11/00 (20060101); A46B5/00 (20060101)

U.S. Cl.:

CPC A46B11/002 (20130101); A46B7/02 (20130101); A46B7/04 (20130101); A46B5/0095 (20130101)

Field of Classification Search

CPC: A46B (7/04); A46B (7/042); A46B (7/044); A46B (7/02)

USPC: 15/176.1; 15/176.6; 401/270; 401/290

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
730040	12/1902	McKinley	401/268	A46B 11/0041
6250833	12/2000	Perry	401/206	A46B 11/0013
6425701	12/2001	Jacobs	401/206	A46B 11/0013
7040830	12/2005	Kliegman	401/187	A47L 17/04
2004/0265042	12/2003	Chan	401/270	A47L 1/08
2005/0069375	12/2004	Kliegman	401/185	A47L 17/04
2014/0311524	12/2013	Call	15/104.94	B08B 1/14
2016/0113384	12/2015	Olson	15/104.94	A46B 11/0058
2022/0232960	12/2021	Brown	N/A	B25G 3/12

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
209610267	12/2018	CN	N/A

Primary Examiner: Jennings; Michael D

Background/Summary

TECHNICAL FIELD

(1) The present utility model relates to the technical field of cleaning products, in particular to a brush head mounting structure of a liquid spraying brush.

BACKGROUND

(2) When people are cleaning, they usually use a cleaning brush to brush the objects to be cleaned. In the cleaning process, a cleaning brush and cleaning liquid are usually used together. A user holds the cleaning brush in one hand and the cleaning liquid in the other, squeezes some cleaning liquid before or during cleaning, and then brushes with the cleaning brush.

(3) As the cleaning brush and the cleaning liquid are provided separately, it is necessary not only to hold the cleaning brush by hand, but also to pour the cleaning liquid with the other hand during the cleaning process, which makes the cleaning process more troublesome. Aiming at this technical problem, Chinese patent (authorized announcement number CN209610267U) discloses a liquid

spraying brush, which comprises a shell with an opening. A soft rubber part located at the opening is provided on the shell. The soft rubber part forms a liquid storage cavity with the inner wall of the shell. The shell is provided with an ejection opening communicated with the liquid storage cavity. A nozzle valve is provided in the ejection opening. The nozzle valve comprises a soft film with openable holes. The ejection opening of the shell is provided with a brush head. In order to facilitate the disassembly of the brush head from the shell, the liquid spraying brush is provided with a plug-in block at the bottom of the shell. A bump is provided on the plug-in block. A plug-in slot into which the plug-in block is plugged is provided on the brush head. An elastic block corresponding to the bump is provided in the plug-in slot. The elastic block can drive the plug-in block to move away from the plug-in slot, and the brush head is provided with a positioning fixture block for fixing the plug-in block, so that the brush head can be detachably connected to the shell. When the brush head needs to be disassembled and replaced, the positioning fixture block is pressed downwards, so that the plug-in block loses the blocking effect of the positioning fixture block, and the plug-in block can be separated from the plug-in slot under the elastic force of the elastic block. In this way, the brush head can be disassembled from the shell quickly and conveniently.

(4) However, the above structure has the following disadvantages. 1. When disassembling the brush head, it is necessary to press the positioning fixture block first and then push the brush head out of the shell, which is inconvenient to operate. 2. Because the positioning fixture block is provided outside the plug-in slot corresponding to the brush head, when the liquid spraying brush is used, the positioning fixture block is pressed by mistake, so that the brush head is unlocked from the shell, and then the brush head falls off from the shell.

SUMMARY

(5) The purpose of the present utility model is to provide a brush head mounting structure of a liquid spraying brush with a simple structure and convenient brush head disassembly. The elastic arm is provided in the sliding groove of the mounting base, which can prevent the positioning protrusion on the elastic arm and the groove on the slider from being unlocked due to being triggered by mistake.

(6) The above technical purpose of the present utility model is realized by the following technical scheme: a brush head mounting structure of a liquid spraying brush, comprising a connecting base provided at the end of a handle and a mounting base provided on a brush head, wherein the other side of the connecting base with respect to the handle is provided with a slider, one side of the mounting base adjacent to the connecting base is provided with a sliding groove in sliding fit with the slider, a limiting structure is provided between the connecting base and the mounting base, the limiting structure is capable of limiting the connecting base and the mounting base along the sliding direction perpendicular to the slider, both sides of the mounting base corresponding to the sliding groove are provided with elastic arms, the position of the mounting base corresponding to the elastic arm is provided with an avoidance space for the elastic arm to expand outwards, the other side of the elastic arm with respect to the avoidance space is provided with a positioning protrusion, the slider is provided with a groove in positioning fit with the positioning protrusion, and the connecting base and the mounting base are capable of being limited along the sliding direction of the slider in such a manner that the positioning protrusion is fit with the groove.

(7) Further, one end of the sliding groove is a closed end and the other end thereof is an open end, and a pressing part is provided on one side of the mounting base corresponding to the open end.

(8) Further, the pressing part protrudes from the mounting base toward the side away from the closed end.

(9) Further, after the mounting base is assembled on the connecting base, a distance L1 between an end face of the pressing part and the connecting base is greater than or equal to a distance L2 by which the positioning protrusion slides out of the groove.

(10) Further, an interval between a limiting grooves gradually increases from the closed end to the

open end, and the slider is matched with the structure of the sliding groove.

(11) Further, the limiting structure comprises limiting blocks provided on both sides of the slider, both sides of the mounting base corresponding to the sliding groove are provided with limiting grooves in limiting fit with the limiting blocks, or both sides of the mounting base corresponding to the sliding groove are provided with limiting blocks, and both sides of the connecting base corresponding to the sliding groove are provided with limiting grooves in limiting fit with the limiting blocks.

(12) Further, the connecting base is detachably connected to the handle.

(13) Further, the pressing part is provided with a smooth curved surface which is convenient for fingers to push.

(14) Further, the other side of the slider corresponding to the handle is provided with a weight-reducing groove.

(15) To sum up, the present utility model has the following beneficial effects. 1. The mounting structure of the brush head is simple, and it is convenient to disassemble the brush head. The brush head can slide out of the connecting base only by pushing the pressing part, so that the brush head can be disassembled from the connecting base for replacement. When the brush head needs to be assembled on the connecting base, it is only necessary to insert the brush head into the connecting base along the sliding direction of the slider. The positioning protrusion on the elastic arm is matched with the groove on the slider, and the brush head is firmly assembled on the connecting base through the limiting structure. 2. By designing the pressing part, the distance L1 between the end face of the pressing part far away from the open end and the connecting base is greater than or equal to the distance L2 by which the positioning protrusion slides out of the groove, so that the end face of the pressing part is just flush with the end face of the connecting base or is still outside the connecting base when the positioning protrusion is separated from the groove. In this way, fingers will not be in contact with the sharp surface of the connecting base in the process of pushing the pressing part. 3. The elastic arm is provided in the sliding groove of the mounting base, which can prevent the positioning protrusion on the elastic arm and the groove on the slider from being unlocked due to being triggered by mistake.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic diagram of the overall structure of the present utility model.

(2) FIG. 2 is an explosion diagram of the present utility model.

(3) FIG. 3 is a cross-sectional diagram of the present utility model.

(4) FIG. 4 is a schematic diagram of a mounting base according to the present utility model.

(5) In the figures: **1**. Handle; **11**. Liquid storage cavity; **2**. Brush head; **21**. Mounting base; **211**.

Through holes; **212**. Sliding groove; **2121**. Closed end; **2122**. Open end; **213**. Elastic arm; **2131**.

Positioning protrusion; **214**. Avoid space; **215**. Pressing part; **2151**. Smooth curved surface; **216**.

Limiting groove; **22**. Washing part; **3**. Connecting base; **31**. Liquid outlet; **32**. Slider; **321**. Groove;

322. Limiting block; **323**. Weight-reducing groove.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(6) The present utility model will be further explained with reference to the attached drawings hereinafter.

(7) As shown in FIGS. 1-4, a brush head mounting structure of a liquid spraying brush comprises a connecting base **3** provided at the end of a handle **1** and a mounting base **21** provided on a brush head **2**. A liquid storage cavity **11** is provided in the handle **1**. A connecting base **3** for sealing the liquid storage cavity **11** is provided at one end of the handle **1** adjacent to the brush head **2**. In the present utility model, the connecting base **3** is detachably connected to the handle **1**, and the

connecting base **3** is provided with a liquid outlet **31** communicated with the liquid storage cavity **11**. The structure of the handle **1** is the prior art. For details, refer to Chinese patent (authorized announcement number CN209610267U) which discloses a liquid spraying brush. The brush head **2** comprises a mounting base **21** and a washing part **22** fixedly provided on the mounting base **21**. In the present utility model, the washing part **22** is a hairbrush or a sponge scouring pad, etc. Through holes **211** communicated with the liquid outlet **31** penetrate through the mounting base **21** in the direction of the washing part **22**, which constitutes the basic structure of the liquid spraying brush.

(8) The other side of the connecting base **3** with respect to the handle **1** is provided with a slider **32**. In the present utility model, the liquid outlet **31** is located in the area where the slider **32** is located, and the liquid outlet **31** penetrates through the slider **32**. One side of the mounting base **21** adjacent to the connecting base **3** is provided with a sliding groove **212** in sliding fit with the slider **32**, that is, the other side of the mounting base **21** with respect to the washing part **22** is provided with a sliding groove **212** in sliding fit with the slider **32**. The slider **32** is matched with the sliding groove **212** for guiding, so that the mounting base **21** is conveniently inserted to the connecting base **3**. Specifically, one end of the sliding groove **212** is a closed end **2121** and the other end thereof is an open end **2122**. A pressing part **215** is provided on one side of the mounting base **21** corresponding to the open end **2122**, and the pressing part **215** is provided with a smooth curved surface **2151** which is convenient for fingers to push.

(9) A limiting structure is provided between the connecting base **3** and the mounting base **21**. The limiting structure is capable of limiting the connecting base **3** and the mounting base **21** along the sliding direction perpendicular to the slider **32**. Specifically, the limiting structure comprises limiting blocks **322** provided on both sides of the slider **32**. Both sides of the mounting base **21** corresponding to the sliding groove **212** are provided with limiting grooves **216** in limiting fit the limiting blocks **322**, or both sides of the mounting base **21** corresponding to the sliding groove **212** are provided with limiting blocks, and both sides of the connecting base **3** corresponding to the sliding groove **212** are provided with limiting grooves **216** in limiting fit with the limiting blocks **322**, which are not shown in the structure diagram.

(10) Both sides of the mounting base **21** corresponding to the sliding groove **212** are provided with elastic arms **213**. The position of the mounting base **21** corresponding to the elastic arm **213** is provided with an avoidance space **214** for the elastic arm **213** to expand outwards. The other side of the elastic arm **213** with respect to the avoidance space **214** is provided with a positioning protrusion **2131**. The slider **32** is provided with a groove **321** in positioning fit with the positioning protrusion **2131**. The connecting base **3** and the mounting base **21** are capable of being limited along the sliding direction of the slider **32** in such a manner that the positioning protrusion **2131** is fit with the groove **321**. The elastic arm **213** is provided in the sliding groove **212** of the mounting base **21**, which can prevent the positioning protrusion **2131** on the elastic arm **213** and the groove **321** on the slider **32** from being unlocked due to being triggered by mistake.

(11) An interval between the limiting grooves (**216**) gradually increases from the closed end (**2121**) to the open end **2122**. The slider **32** is matched with the structure of the sliding groove (**212**), so that when the slider **32** passes through the elastic arm **213**, the elastic arm **213** can be pushed to the side of the avoidance space **214**. The slider **32** can smoothly enter the sliding slot **212** and abut against the closed end **2121** of the sliding slot **212**. At this time, the positioning protrusion **2131** on the elastic arm **213** is clamped into the groove **321** of the slider **32** under the action of elastic force, thus playing a positioning role. The structural design of the sliding groove **212** can effectively prevent the slider **32** from being inserted into the sliding groove **212** due to the influence of the elastic arm **213**.

(12) The pressing part **215** protrudes from the mounting base **21** toward the side away from the closed end **2121**. After the mounting base **21** is assembled on the connecting base **3**, a distance **L1** between an end face of the pressing part **215** and the connecting base **3** is greater than or equal to a distance **L2** by which the positioning protrusion **2131** slides out of the groove **321**. In the present

utility model, the distance L1 is 2 mm-5 mm. By designing the pressing part 215, the end face of the pressing part 215 is just flush with the end face of the connecting base 3 or is still outside the connecting base 3 when the positioning protrusion 2131 is separated from the groove 321. In this way, fingers will not be in contact with the sharp surface of the connecting base 3 in the process of pushing the pressing part 215.

(13) The other side of the slider 32 corresponding to the handle 1 is provided with a weight-reducing groove 323. The design of the weight-reducing groove 323 can reduce the material of the connecting base 3 to reduce the manufacturing cost of the connecting base 3, and at the same time, reduce the overall quality of the liquid spraying brush.

(14) The mounting structure of the brush head is simple, and it is convenient to disassemble the brush head 2. The brush head 2 can slide out of the connecting base 3 only by pushing the pressing part 215, so that the brush head 2 can be disassembled from the connecting base 3 for replacement. When the brush head 2 needs to be assembled on the connecting base 3, it is only necessary to insert the brush head 2 into the connecting base 3 along the sliding direction of the slider 32. The positioning protrusion 2131 on the elastic arm 213 is matched with the groove 321 on the slider 32, and the brush head 2 is firmly assembled on the connecting base 3 through the limiting structure.

(15) The above is only the preferred embodiment of the present utility model. Therefore, any equivalent changes or modifications made according to the structure, characteristics and principles described in the patent application scope of the present utility model are included in the patent application scope of the present utility model.

Claims

1. A brush head mounting structure of a liquid spraying brush, comprising: a connecting base (3) provided at the end of a handle (1) and a mounting base (21) provided on a brush head (2), wherein the other side of the connecting base (3) with respect to the handle (1) is provided with a slider (32) having two sides, wherein one side of the two sides of the slider (32) corresponding to the handle (1) is provided with a weight-reducing groove (323), one side of the mounting base (21) adjacent to the connecting base (3) is provided with a sliding groove (212) in sliding fit with the slider (32), wherein one end of the sliding groove (212) is a closed end (2121) and the other end thereof is an open end (2122), a pressing part (215) is provided on one side of the mounting base (21) corresponding to the open end (2122), the pressing part (215) protrudes from the mounting base (21) toward the side away from the closed end (2121), wherein the disengagement of the brush head from the connecting base is based on pushing the pressing part (215) so that the brush head (2) can slide out of the connecting base (3) and thus the brush head (2) can be disassembled from the connecting base (3) for replacement, wherein the pressing part has a smooth curved surface, and the smooth curved surface is along circumferential direction of the mounting base (21), a limiting structure is provided between the connecting base (3) and the mounting base (21), the limiting structure is capable of limiting the connecting base (3) and the mounting base (21) along the sliding direction perpendicular to the slider (32), both sides of the mounting base (21) corresponding to the sliding groove (212) are provided with elastic arms (213), the position of the mounting base (21) corresponding to the elastic arm (213) is provided with an avoidance space (214) for the elastic arm (213) to expand outwards, the other side of the elastic arm (213) with respect to the avoidance space (214) is provided with a positioning protrusion (2131), the slider (32) is provided with a groove (321) in positioning fit with the positioning protrusion (2131), and the connecting base (3) and the mounting base (21) are capable of being limited along the sliding direction of the slider (32) in such a manner that the positioning protrusion (2131) is fit with the groove (321).

2. The brush head mounting structure of the liquid spraying brush according to claim 1, wherein after the mounting base (21) is assembled on the connecting base (3), the distance L1 between the

end face of the pressing part (215) and the connecting base (3) is greater than or equal to the distance L2 by which the positioning protrusion (2131) slides out of the groove (321).

3. The brush head mounting structure of the liquid spraying brush according to claim 1, wherein the interval between the sliding grooves (212) gradually increases from the closed end to the open end (2122), and the slider (32) is matched with the structure of the sliding grooves (212).

4. The brush head mounting structure of the liquid spraying brush according to claim 1, wherein the limiting structure comprises limiting blocks (322) provided on each of the two sides of the slider (32), both sides of the mounting base (21) corresponding to the sliding groove (212) are provided with limiting grooves (216) in limiting fit the limiting blocks (322), or both sides of the mounting base (21) corresponding to the sliding groove (212) are provided with limiting blocks, and both sides of the connecting base (3) corresponding to the sliding groove (212) are provided with limiting grooves (216) in limiting fit with the limiting blocks (322).

5. The brush head mounting structure of the liquid spraying brush according to claim 1, wherein the connecting base (3) is detachably connected to the handle (1).
