

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397393
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Bando; Kazuaki

Processing apparatus for brittle plate and processing method for brittle plate

Abstract

A processing apparatus for brittle plate includes a table which holds a brittle plate, a processing head having a processing wheel for processing an outer peripheral edge of the brittle plate held by the table, a measuring portion which measures a positional shift amount Δ in an axis direction of the processing wheel with respect to the brittle plate, and a control portion which corrects a positional shift in a Z-axis direction of the processing wheel on the basis of a positional shift amount Δ in the axis direction of the processing wheel measured by the measuring portion and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate. The processing apparatus and its method can reduce time and labor of manually positioning of a processing wheel to the brittle plate after processing wheel replacement.

Inventors:	Bando; Kazuaki (Tokushima, JP)
Applicant:	BANDO KIKO Co., Ltd. (Tokushima, JP)
Family ID:	1000008778651
Assignee:	Bando Kiko Co., LTD (Tokushima, JP)
Appl. No.:	17/619287
Filed (or PCT Filed):	July 15, 2021
PCT No.:	PCT/JP2021/026550
PCT Pub. No.:	WO2022/195907
PCT Pub. Date:	September 22, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230146769 A1	May. 11, 2023

Foreign Application Priority Data

JP 2021-045291 Mar. 18, 2021

Publication Classification

Int. Cl.: B24B9/10 (20060101); B24B49/00 (20120101); B24B49/12 (20060101)

U.S. Cl.:

CPC B24B49/12 (20130101); B24B9/10 (20130101); B24B49/00 (20130101);

Field of Classification Search

CPC: B24B (49/12); B24B (49/10); B24B (49/00); B24B (49/02); B24B (49/04); B24B (49/08); B24B (49/16); B24B (49/105); B24B (9/10); B24B (9/00); B24B (9/065); B24B (9/08); B24B (9/002); B24B (9/005); B24B (9/06); B24B (9/102); B24B (9/107); B24B (41/02); B24B (47/22); H01L (21/68); H01L (2223/54426); B23Q (3/18); B23Q (3/186); B23Q (17/2233); B23Q (15/22); B25J (9/1692)

USPC: 451/5

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1723529	12/1928	Schwieterman	33/642	B23Q 15/22

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
11-300612	12/1998	JP	N/A
H11300612	12/1998	JP	N/A
2010-058265	12/2009	JP	N/A
20120013929	12/2011	KR	N/A
2018/132661	12/2017	WO	N/A

Primary Examiner: Posigian; David S

Assistant Examiner: Gump; Michael A

Attorney, Agent or Firm: Millen, White, Zelano & Branigan, P.C.

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a processing apparatus for brittle plate, which grinds or polishes or grinds and polishes (hereinafter, referred to as processing) an outer peripheral edge of a rectangular brittle plate, for example, in the brittle plate for automobiles, for liquid crystal panels

such as liquid crystal TV sets, for solar batteries, for furniture, for construction and the like and a processing method for brittle plate.

BACKGROUND ART

(2) Conventionally, in a grinding device for a glass plate, for example, a grinding wheel is rotated by an operation of an electric motor and is brought into contact with a peripheral edge of the glass plate so as to grind the glass plate, for example.

CITATION LIST

Patent Literature

(3) [Patent Literature 1] Japanese Patent Application Publication No. 2010-58265

SUMMARY OF INVENTION

Technical Problem

(4) With the grinding device for a glass plate disclosed in the aforementioned Patent Literature 1, as a method for aligning a glass grinding position with a grinding wheel position at replacement of the grinding wheel or the like, a dimension from a grinding-wheel mounting surface to a reference position of grinding wheel groove is manually aligned in the grind wheel production, but with this method, a processed shape can be slightly shifted when the glass plate is processed. Thus, such a method is employed that the grinding wheel position is re-adjusted by checking the processed shape of the glass plate at first processing, which takes time to position the grinding wheel to the glass plate and lowers efficiency of the processing of the glass plate as a whole.

(5) The present invention was made in view of the aforementioned problems and has an object to provide a processing apparatus for brittle plate and a processing method for brittle plate, which can reduce time and labor of manual positioning of a processing wheel with respect to the brittle plate after the replacement of the processing wheel and has high efficiency in processing of the brittle plate as a whole by automatically measuring a positional shift amount of the processing wheel before processing of the brittle plate without testing the positioning between the brittle plate and the processing wheel groove by a manual work several times, and by automatically correcting the positional shift of the processing wheel on the basis of the positional shift amount so as to cause the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate.

(6) Another object of the present invention is to provide a processing apparatus for brittle plate and a processing method for brittle plate, which can reduce time and labor of manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel and has high efficiency in processing of the brittle plate as a whole by automatically measuring the positional shift amount of the processing wheel before the processing of the brittle plate, by automatically correcting the positional shift of the processing wheel on the basis of the positional shift amount, by alternately repeating the measurement and correction, and by automatically correcting the positional shift of the processing wheel with more accuracy so as to cause the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate.

Solution to Problem

(7) A first feature of the present invention in order to solve the aforementioned problem is characterized by that a processing apparatus for brittle plate includes a table which holds the brittle plate, a processing head having a processing wheel for processing an outer peripheral edge of the brittle plate held by the table, a measuring portion which measures a positional shift amount in an axis direction of the processing wheel with respect to the brittle plate, and a control portion which corrects a positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel measured by the measuring portion and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate.

(8) As an example of the processing apparatus for brittle plate of the present invention having the

first feature, the measuring portion includes a mounting plate, a moving base provided capable of relative movement with respect to the mounting plate in a first direction orthogonal to an axis of the processing wheel, moving means for moving the moving base in the first direction, and rotating means provided on the moving base and having a shaft member including a distal end portion, in which

(9) the measuring portion causes the shaft member to be rotated in a first rotating direction around a shaft thereof and causes the distal end portion to be brought into contact with the processing surface of the processing wheel, measures a first position where the distal end portion is rotated in the first rotating direction and is brought into contact with the processing surface of the processing wheel, causes the shaft member to be rotated in a second rotating direction which is a direction opposite to the first rotating direction and causes the distal end portion to be brought into contact with the processing surface of the processing wheel, and measures a second position where the distal end portion is rotated in the second rotating direction and is brought into contact with the processing surface of the processing wheel, and

(10) the control portion calculates a first distance from a predetermined processing reference position to the first position in the axis direction of the processing wheel, calculates a second distance from the predetermined processing reference position to the second position in the axis direction of the processing wheel, calculates a positional shift amount in the axis direction of the processing wheel on the basis of the first distance and the second distance, corrects the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and causes the processing wheel whose positional shift was corrected to process an outer peripheral edge of the brittle plate.

(11) As another example of the processing apparatus for brittle plate of the present invention having the first feature, the processing apparatus for brittle plate alternately repeats measurement of a first position and a second position by the measuring portion and correction of a positional shift in the axis direction of the processing wheel by the control portion several times and causes the processing wheel whose positional shift was corrected several times to process the outer peripheral edge of the brittle plate.

(12) Another example of the processing apparatus for brittle plate of the present invention having the first feature is that the rotating means is a servomotor which controls a torque.

(13) As another example of the processing apparatus for brittle plate of the present invention having the first feature, the measuring portion includes a mounting plate, a moving base provided capable of relative movement with respect to the mounting plate in a first direction orthogonal to the axis of the processing wheel, moving means for moving the moving base in the first direction, and laser measuring means provided on the moving base and measuring a processing surface by emitting a laser to the processing surface of the processing wheel, in which the control portion calculates a positional shift amount in the axis direction of the processing wheel from a predetermined processing reference position on the basis of a measured value measured by the laser measuring means, corrects the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount from the predetermined processing reference position in the axis direction of the processing wheel, and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate.

(14) As another example of the processing apparatus for brittle plate of the present invention having the first feature, in a state where a laser is emitted to the processing surface of the processing wheel, the laser measuring means measures the processing surface of the processing wheel by movement of at least either one of the processing wheel and the laser measuring means from one to the other in the axis direction of the processing wheel, and

(15) the control portion calculates a positional shift amount in the axis direction of the processing wheel on the basis of a position where a distance from the laser measuring means to the processing surface of the processing wheel in the first direction measured by the laser measuring means

becomes the maximum and the predetermined processing reference position, corrects the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate.

(16) As another example of the processing apparatus for brittle plate of the present invention having the first feature, the laser measuring means measures the processing surface of the processing wheel by emitting a laser to a predetermined region or the entire region on the processing surface in the axis direction of the processing wheel and,

(17) the control portion calculates a positional shift amount in the axis direction of the processing wheel on the basis of a position where a distance from the laser measuring means to the processing surface of the processing wheel in the first direction measured by the laser measuring means becomes the maximum and the predetermined processing reference position, corrects the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate.

(18) A second feature of the present invention for solving the aforementioned problem is a processing method for brittle plate using a processing apparatus for brittle plate, including a table which holds the brittle plate, a processing head having a processing wheel for processing an outer peripheral edge of the brittle plate held by the table, a measuring portion which measures a positional shift amount in an axis direction of the processing wheel with respect to the brittle plate, and a control portion which corrects a positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel measured by the measuring portion and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate,

(19) the processing method for brittle plate, including

(20) a measuring process of measuring a positional shift amount in an axis direction of the processing wheel with respect to the brittle plate,

(21) a correcting process of correcting a positional shift in the axis direction of the processing wheel on the basis of the positional shift amount measured in the measuring process, and

(22) a processing process of causing the processing wheel whose positional shift was corrected after the correcting process to process an outer peripheral edge of the brittle plate.

(23) A third feature of the present invention for solving the aforementioned problem is a processing method for brittle plate using a processing apparatus for brittle plate, including a table which holds the brittle plate, a processing head having a processing wheel for processing an outer peripheral edge of the brittle plate held by the table, a measuring portion which measures a positional shift amount in an axis direction of the processing wheel with respect to the brittle plate, and a control portion which corrects a positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel measured by the measuring portion and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate, the measuring portion including a mounting plate, a moving base provided capable of relative movement with respect to the mounting plate in a first direction orthogonal to the axis of the processing wheel, moving means for moving the moving base in the first direction, and rotating means provided on the moving base and having a shaft member including a distal end portion,

(24) the processing method for brittle plate, including a positioning process of positioning the shaft member to a predetermined position, a first measuring process of bringing the distal end portion into contact with the processing surface of the processing wheel by rotating the shaft member in a first rotating direction around a shaft thereof and of measuring a first position on the processing surface of the processing wheel with which the distal end portion is brought into contact, a second measuring process of bringing the distal end portion into contact with the processing surface of the

processing wheel by rotating the shaft member in a second rotating direction which is a direction opposite to the first rotating direction and of measuring a second position on the processing surface of the processing wheel with which the distal end portion is brought into contact, a calculating process of calculating a first distance in the axis direction of the processing wheel from a predetermined processing reference position to the first position, of calculating a second distance in the axis direction of the processing wheel from the predetermined processing reference position to the second position and of calculating a positional shift amount in the axis direction of the processing wheel on the basis of the first distance and the second distance, a correcting process of correcting the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and a processing process of causing the processing wheel whose positional shift was corrected after the correcting process to process an outer peripheral edge of the brittle plate.

(25) As an example of the processing apparatus for brittle plate of the present invention having the third feature, the processing method for brittle plate repeats the first measuring process, the second measuring process, the calculating process, and the correcting process several times, and the processing wheel whose positional shift was corrected several times is caused to process the outer peripheral edge of the brittle plate.

(26) A fourth feature of the present invention for solving the aforementioned problem is a processing method for brittle plate using a processing apparatus for brittle plate, including a table which holds the brittle plate, a processing head having a processing wheel for processing an outer peripheral edge of the brittle plate held by the table, a measuring portion which measures a positional shift amount in an axis direction of the processing wheel with respect to the brittle plate, and a control portion which corrects a positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel measured by the measuring portion and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate, the measuring portion including a mounting plate, a moving base provided capable of relative movement with respect to the mounting plate in a first direction orthogonal to the axis of the processing wheel, moving means for moving the moving base in the first direction, and laser measuring means provided on the moving base and measuring a processing surface by emitting a laser to the processing surface of the processing wheel,

(27) the processing method for brittle plate, including a positioning process of positioning the laser measuring means to a predetermined position, a measuring process of measuring the processing surface of the processing wheel by emitting the laser beam of the laser measuring means to the processing surface of the processing wheel, a calculating process of calculating a positional shift amount in the axis direction of the processing wheel on the basis of a measured value measured by the laser measuring means, a correcting process of correcting the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and a processing process of causing the processing wheel whose positional shift was corrected after the correcting process to process an outer peripheral edge of the brittle plate.

(28) As an example of the processing apparatus for brittle plate of the present invention having the fourth feature,

(29) in the measuring process, in a state where the laser measuring means emits a laser to the processing surface of the processing wheel, the processing surface of the processing wheel is measured by movement of at least either one of the processing wheel and the laser measuring means from one to the other in the axis direction of the processing wheel, and

(30) in the calculating process, a positional shift amount in the axis direction of the processing wheel is calculated on the basis of a position where a distance from the laser measuring means to the processing surface of the processing wheel in the first direction measured by the laser

measuring means becomes the maximum and a predetermined processing reference position.

(31) As another example of the processing apparatus for brittle plate of the present invention having the fourth feature, in the measuring process, the processing surface of the processing wheel is measured by the laser measuring means by emitting a laser to a predetermined region or the entire region on the processing surface in the axis direction of the processing wheel, and

(32) in the calculating process, on the basis of the position where the distance from the laser measuring means to the processing surface of the processing wheel in the first direction measured by the laser measuring means becomes the maximum and the predetermined processing reference position, the positional shift amount in the axis direction of the processing wheel is calculated.

Advantageous Effect of Invention

(33) According to the processing apparatus for brittle plate having the first feature, since the measuring portion measures the positional shift amount in the axis direction of the processing wheel with respect to the brittle plate, and the control portion corrects the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel measured by the measuring portion and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate, such a processing apparatus for brittle plate can be provided that, without a need to test the positioning by a manual work between the brittle plate and the processing wheel groove several times, the labor and time for the manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

(34) According to the one processing apparatus for brittle plate having the first feature, since the control portion calculates the first distance from the predetermined processing reference position to the first position in the axis direction of the processing wheel, calculates the second distance from the predetermined processing reference position to the second position in the axis direction of the processing wheel, calculates the positional shift amount in the axis direction of the processing wheel on the basis of the first distance and the second distance, corrects the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate, such a processing apparatus for brittle plate can be provided that, without a need to test the positioning by a manual work between the brittle plate and the processing wheel groove several times, the labor and time for the manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

(35) According to another processing apparatus for brittle plate having the first feature, by alternately repeating the measurement of the first position and the second position by the measuring portion and the correction of the positional shift in the axis direction of the processing wheel by the control portion several times, since the positional shift of the processing wheel is automatically corrected with more accuracy, and the processing wheel whose positional shift was corrected is caused to process the outer peripheral edge of the brittle plate, such a processing apparatus for brittle plate can be provided that, the labor and time for the manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

(36) According to another processing apparatus for brittle plate having the first feature, since the rotating means is a servomotor which controls a torque, at a position where the distal end portion of the shaft member is in contact with the processing surface, a rotation (angle) of the rotating means can be controlled and reliably stopped and thus, the positional shift amount of the processing wheel can be measured with more accuracy, and the positional shift of the processing wheel can be corrected with accuracy.

(37) According to another processing apparatus for brittle plate having the first feature, since the control portion calculates the positional shift amount from the predetermined processing reference position in the axis direction of the processing wheel on the basis of the measured value measured by the laser measuring means, corrects the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount from the predetermined processing reference position in the axis direction of the processing wheel, and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate, such a processing apparatus for brittle plate can be provided that, without a need to test the positioning by a manual work between the brittle plate and the processing wheel groove several times, the labor and time for the manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

(38) According to another processing apparatus for brittle plate having the first feature, in the state where the laser measuring means emits a laser to the processing surface of the processing wheel, the laser measuring means measures the processing surface of the processing wheel by movement of at least either one of the processing wheel and the laser measuring means from one to the other in the axis direction of the processing wheel, and the control portion calculates the positional shift amount in the axis direction of the processing wheel on the basis of the position where the distance from the laser measuring means to the processing surface of the processing wheel in the first direction measured by the laser measuring means becomes the maximum and the predetermined processing reference position, corrects the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate and thus, such a processing apparatus for brittle plate can be provided that, without a need to test the positioning by a manual work between the brittle plate and the processing wheel groove several times, the labor and time for the manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

(39) According to another processing apparatus for brittle plate having the first feature, since the laser measuring means measures the processing surface of the processing wheel by emitting a laser to the predetermined region or the entire region on the processing surface in the axis direction of the processing wheel, and the control portion calculates the positional shift amount in the axis direction of the processing wheel on the basis of the position where the distance from the laser measuring means to the processing surface of the processing wheel in the first direction measured by the laser measuring means becomes the maximum and the predetermined processing reference position, corrects the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate, such a processing apparatus for brittle plate can be provided that, without a need to test the positioning by a manual work between the brittle plate and the processing wheel groove several times, the labor and time for the manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

(40) According to the processing method for brittle plate having the second feature, since the processing method for brittle plate includes the measuring process of measuring the positional shift amount in the axis direction of the processing wheel with respect to the brittle plate, the correcting process of correcting the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount measured in the measuring process, and the processing process of causing the processing wheel whose positional shift was corrected after the correcting process to process the outer peripheral edge of the brittle plate, such a processing method for brittle plate can

be provided that, without a need to test the positioning by a manual work between the brittle plate and the processing wheel groove several times, the labor and time for the manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

(41) According to the processing method for brittle plate having the third feature, since the processing method for brittle plate includes the positioning process of positioning the shaft member to the predetermined position, the first measuring process of bringing the distal end portion into contact with the processing surface of the processing wheel by rotating the shaft member in the first rotating direction around the shaft thereof and of measuring the first position on the processing surface of the processing wheel with which the distal end portion is brought into contact, the second measuring process of bringing the distal end portion into contact with the processing surface of the processing wheel by rotating the shaft member in the second rotating direction which is the direction opposite to the first rotating direction and of measuring the second position on the processing surface of the processing wheel with which the distal end portion is brought into contact, the calculating process of calculating the first distance in the axis direction of the processing wheel from the predetermined processing reference position to the first position, of calculating the second distance in the axis direction of the processing wheel from the predetermined processing reference position to the second position, and of calculating the positional shift amount in the axis direction of the processing wheel on the basis of the first distance and the second distance, the correcting process of correcting the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and the processing process of causing the processing wheel whose positional shift was corrected after the correcting process to process the outer peripheral edge of the brittle plate, such a processing method for brittle plate can be provided that, without a need to test the positioning by a manual work between the brittle plate and the processing wheel groove several times, the labor and time for the manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

(42) According to the one processing method for brittle plate having the third feature, since the processing method for brittle plate repeats the first measuring process, the second measuring process, the calculating process, and the correcting process several times so that the positional shift of the processing wheel can be automatically corrected with more accuracy, and the processing wheel whose positional shift was corrected several times is caused to process the outer peripheral edge of the brittle plate, such a processing method for brittle plate can be provided that the labor and time for the manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

(43) According to the processing method for brittle plate having the fourth feature, since the processing method for brittle plate includes the positioning process of positioning the laser measuring means to the predetermined position, the measuring process of measuring the processing surface of the processing wheel by emitting the laser beam of the laser measuring means to the processing surface of the processing wheel, the calculating process of calculating the positional shift amount in the axis direction of the processing wheel on the basis of the measured value measured by the laser measuring means, the correcting process of correcting the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and the processing process of causing the processing wheel whose positional shift was corrected after the correcting process to process the outer peripheral edge of the brittle plate, such a processing method for brittle plate can be provided that, without a need to test the positioning by a manual work between the brittle plate and the processing wheel groove several times, the labor and time for the manual positioning of the processing wheel with

respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

(44) According to the one processing method for brittle plate having the fourth feature, since in the measuring process, in the state where the laser measuring means emits a laser to the processing surface of the processing wheel, the processing surface of the processing wheel is measured by movement of at least either one of the processing wheel and the laser measuring means from one to the other in the axis direction of the processing wheel, and in the calculating process, the positional shift amount in the axis direction of the processing wheel is calculated on the basis of the position where the distance from the laser measuring means to the processing surface of the processing wheel in the first direction measured by the laser measuring means becomes the maximum and the predetermined processing reference position, such a processing method for brittle plate can be provided that, without a need to test the positioning by a manual work between the brittle plate and the processing wheel groove several times, the labor and time for the manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

(45) According to another processing method for brittle plate having the fourth feature, in the measuring process, the processing surface of the processing wheel is measured by the laser measuring means by emitting a laser to the predetermined region or the entire region on the processing surface in the axis direction of the processing wheel, and in the calculating process, on the basis of the position where the distance from the laser measuring means to the processing surface of the processing wheel in the first direction measured by the laser measuring means becomes the maximum and the predetermined processing reference position, the positional shift amount in the axis direction of the processing wheel is calculated, such a processing method for brittle plate can be provided that, without a need to test the positioning by a manual work between the brittle plate and the processing wheel groove several times, the labor and time for the manual positioning of the processing wheel with respect to the brittle plate after the replacement of the processing wheel can be reduced, and efficiency of the processing of the brittle plate is high as a whole.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a front view of a processing apparatus for brittle plate illustrated as an example.
- (2) FIG. 2 is a partially-omitted planar explanatory view of the processing apparatus for brittle plate shown in FIG. 1.
- (3) FIG. 3 is a partially-omitted left-side explanatory view of the processing apparatus for brittle plate shown in FIG. 1.
- (4) FIG. 4 are explanatory views of a processing head of the processing apparatus for brittle plate shown in FIG. 1.
- (5) FIG. 5 is a flowchart illustrating a processing method for brittle plate using the processing apparatus for brittle plate shown in FIG. 1.
- (6) FIG. 6 are explanatory views of an operation of a measuring portion of the processing apparatus for brittle plate shown in FIG. 1.
- (7) FIG. 7 are explanatory views of an operation of a shaft member of the processing apparatus for brittle plate shown in FIG. 1.
- (8) FIG. 8 are explanatory view of a measuring operation of the shaft member of the processing apparatus for brittle plate shown in FIG. 1.
- (9) FIG. 9 is a front view of a processing apparatus for brittle plate shown as another example.
- (10) FIG. 10 is a flowchart illustrating a processing method for brittle plate using the processing

apparatus for brittle plate shown in FIG. 9.

DESCRIPTION OF EMBODIMENTS

(11) Hereinafter, embodiments for working the present invention will be described by referring to the drawings. In each figure, the same or corresponding signs are given to the same or corresponding constitutions, and explanation will be omitted. The present invention is not limited to these embodiments at all.

(12) By referring to the drawings attached to FIG. 1, which is a front view of a processing apparatus 1 for brittle plate shown as an example and the like, details of the processing apparatus for brittle plate according to the present invention will be described as follows. FIG. 2 is a partially-omitted planar explanatory view of the processing apparatus 1 for brittle plate, FIG. 3 is a partially-omitted left-side explanatory view of the processing apparatus 1 for brittle plate, FIG. 4 are explanatory views of a processing head 7 of the processing apparatus 1 for brittle plate, and FIG. 5 is a flowchart illustrating a processing method for brittle plate using the processing apparatus 1 for brittle plate. FIG. 6 are explanatory views of an operation of a measuring portion 8 of the processing apparatus 1 for brittle plate, FIG. 7 are explanatory views of an operation of a shaft member 97 of the processing apparatus 1 for brittle plate, FIG. 8 are explanatory views of a measuring operation of the shaft member 97 of the processing apparatus 1 for brittle plate, and in FIG. 1, illustration of an upstream side of the processing apparatus 1 for brittle plate or a carrying-in portion for brittle plate, a scribe, a folding/breaking portion and the like is omitted, for example, in FIG. 2, illustration of a lateral support frame 13 for a base 3, the processing head 7 and the like is omitted, and in FIG. 3, illustration of a table 4, the processing head 7 and the like is omitted. In FIG. 1, a conveying direction of the brittle plate 2 is shown as an X-axis direction, an up-and-down direction as a Z-axis direction, and a direction orthogonal to the X-axis direction and the Z-axis direction as a Y-axis direction.

(13) In FIGS. 1 to 3, the processing apparatus 1 for brittle plate shown as an example includes a base 3,

(14) a table 4 provided on the base 3 and holding the rectangular flat-plate shaped brittle plate 2 having a predetermined area defined by an XY plane from a lower surface, the processing head 7 having a processing wheel 6 for processing an outer peripheral edge 5 of the brittle plate 2 held by the table 4, the measuring portion 8 for measuring a positional shift amount Δ in an axis direction of the processing wheel 6 with respect to the brittle plate 2 and in the Z-axis direction orthogonal to the XY plane, and a control portion 9 which corrects a positional shift in the Z-axis direction of the processing wheel 6 on the basis of the positional shift amount Δ in the Z-axis direction of the processing wheel 6 measured by the measuring portion 8 and causes the processing wheel 6 whose positional shift was corrected to process the outer peripheral edge 5 of the brittle plate 2.

(15) In this embodiment, the brittle plate 2 only needs to be a plate having brittleness for an automobile, a liquid crystal panel of a liquid crystal TV and the like, a solar battery, furniture, and construction, for example, types of the brittle plate 2 are wide and diverse, and the brittle plate 2 may be a glass plate, a silicon-carbide plate, a silicone substrate and the like.

(16) In this embodiment, the brittle plate 2 has a rectangular flat-plate shape, but instead of this, the brittle plate 2 may have any shape such as oval, circular, polygonal, square, rectangular and the like, and the brittle plate 2 only needs to have a predetermined area and a predetermined thickness.

(17) The base 3 includes a main body 11 placed on a ground 10, a pair of gate-shaped frames 12 stood on an upper surface of the main body 11 and on both end portions in the X-axis direction, which is a conveying direction of the brittle plate 2, and a lateral support frame 13 extended between the pair of gate-shaped frames 12 and extending in the X-axis direction.

(18) The table 4 is provided on the upper surface of the main body 11, the measuring portion 8 is provided on a gate-shaped frame 12A which is one of the pair of gate-shaped frames 12, and the processing head 7 is provided on the lateral support frame 13.

(19) The table 4 includes a plurality of sucking discs 21 for adsorbing/holding from a lower surface

of the brittle plate **2**, a sucking-disc base **22** on which the plurality of sucking discs **21** are placed, Y-axis moving means **23** for guiding/moving the sucking-disc base **22** in the Y-axis direction orthogonal to the X-axis direction, and a Cable Bear (Registered Trademark) **24** electrically connected to the Y-axis moving means **23**.

(20) In this embodiment, the brittle plate **2** is supported by the plurality of sucking discs **21**, but instead of them, the brittle plate **2** may be supported by one sucking disc **21**.

(21) The Y-axis moving means **23** includes two guide rails **25** extending in the Y-axis direction and laid in parallel with each other in the Y-axis direction, a slide block **26** attached to each of the guide rails **25** movably in the Y-axis direction and mounted on the lower surface of the sucking-disc base **22**, a feed screw **27** screwed with a nut (not shown) fixed to the lower surface of the sucking-disc base **22** and provided between the pair of guide rails **25**, and a Y-axis control motor (not shown) for rotating the feed screw **27**.

(22) The sucking-disc base **22** moves in the Y-axis direction by rotation of the feed screw **27** by an operation of the Y-axis control motor.

(23) The processing head **7** will be described in detail by referring to FIGS. **4(a)** to **4(c)**, Note that FIG. **4(a)** is a partially-omitted front view of the processing head **7**, FIG. **4(b)** is a partially-omitted side view of the processing head **7**, and FIG. **4(c)** is a partially-omitted plan view of the processing head **7**.

(24) The processing head **7** includes the pencil-edge type processing wheel **6** for processing the outer peripheral edge **5** of the brittle plate **2**, rotating means **31** in which the processing wheel **6** is attached to a lower end in the Z-axis direction and having an output rotating shaft for rotating the processing wheel **6** around an axis C1, a cut-in amount adjusting means **32** for adjusting a cut-in amount of the processing wheel **6** to the brittle plate **2**, X-axis moving means **33** for moving the processing wheel **6** in the X-axis direction, Z-axis moving means **34** for moving the processing wheel **6** in the Z-axis direction, turning means **36** having a turning shaft **35** for turning the processing wheel **6** around an axis C2, and a base **39** mounted on a turning shaft holder **38** on a lower end portion **37** of the turning shaft **35** in the turning means **36**.

(25) The processing wheel **6** includes a disc-shaped main body **41** and a processing surface **42** containing diamond abrasive grains and the like. Moreover, the processing wheel **6** grinds, polishes or grinds and polishes (hereinafter, referred to as processing) the brittle plate **2** with the processing surface **42**.

(26) The processing head **7** and the brittle plate **2** are numerically controlled by the control portion **9** and move on an XY-plane coordinate system, and the processing wheel **6** rotates around the outer periphery of the brittle plate **2** with an angle controlled so as to be directed to a normal direction all the time with respect to the outer peripheral edge **5** of the brittle plate **2**, and processes the outer peripheral edge **5** of the brittle plate **2**.

(27) The rotating means **31** is a spindle motor having an output rotating shaft **46** in which the processing wheel **6** is mounted on a lower end **45** in the Z-axis direction and rotates the processing wheel **6** in an R1 direction around the rotation axis C1 with the rotation axis C1 of the output rotating shaft **46** as a center by driving of the spindle motor.

(28) The cut-in amount adjusting means **32** includes two cut-in slides **51** mounted on the base **39**, extending in the X-axis direction, and laid in parallel with each other, an X-axis direction slide base **52** attached to each of the cut-in slides **51** and capable of relative movement in the X-axis direction, a feed screw **54** screwed with a nut **53** fixed to the X-axis direction slide base **52**, a cut-in gear **55** mounted on the feed screw **54**, and a cut-in servomotor **58** for adjusting the cut-in amount, having a cut-in gear **56** meshed with the cut-in gear **55** and mounted on the base **39** through a bracket **57**.

(29) The control portion **9** operates the cut-in servomotor **58**, rotates the feed screw **54** through the cut-in gear **55** and the cut-in gear **56**, moves the X-axis direction slide base **52** in the X-axis direction, and adjusts the cut-in amount of the processing wheel **6** with respect to the brittle plate **2**.

(30) The processing wheel **6** is constituted such that a peripheral end surface (processing surface

42) thereof matches the rotation axis C2 of the turning shaft **35** by adjustment by the cut-in amount adjusting means **32**.

(31) The X-axis moving means **33** includes an X-axis moving base **61** on which the processing head **7** is mounted, a pair of guide rails **63** mounted on a side surface **62** of the lateral support frame **13** and extending in parallel in the X-axis direction, a slider (not shown) slidably fitted with the pair of guide rails **63** and fixed to a rear surface of the x-axis moving base **61**, a nut (not shown) mounted on the X-axis moving base **61**, a feed screw **64** provided between the pair of guide rails **63** and with which the nut is screwed, and an X-axis servomotor **67** having an output rotating shaft **66** with which the feed screw **64** is linked through a bearing **65**.

(32) The processing head **7** is constituted so as to linearly move integrally with the X-axis moving base **61** in the X-axis direction by the X-axis moving means **33**, and the linear motion of the X-axis moving base **61** in the X-axis direction rotates the feed screw **64** through the bearing **65** by driving of the X-axis servomotor **67**, and the X-axis moving base **61** is moved in the X-axis direction.

(33) The Z-axis moving means **34** includes two guide rails **71** mounted on the X-axis direction slide base **52**, extending in the Z-axis direction, and laid in parallel with each other, a Z-axis direction slide base **72** movably attached to each of the guide rails **71** and mounted capable of relative movement in the Z-axis direction with respect to the X-axis direction slide base **52**, a feed screw **74** screwed with a nut **73** fixed to the X-axis direction slide base **52**, a gear box **75** linked with the feed screw **74**, and a Z-axis servomotor **77** having an output rotating shaft **76** linked with the gear box **75** and adjusting a position in the Z-axis direction of the processing wheel **6**.

(34) The control portion **9** operates the Z-axis servomotor **77**, rotates the feed screw **74**, moves the Z-axis direction slide base **72** in the Z-axis direction, and moves the processing wheel **6** in the Z-axis direction.

(35) The processing wheel **6** has a positional shift in the axis direction corrected by adjustment of the Z-axis moving means **34**.

(36) The turning means **36** includes a turning servomotor **81** for rotating the processing head **7** around the axis C2, a gear box **82** linked with an output rotating shaft of the turning servomotor **81**, the turning shaft **35** having a rotating gear **84** meshed with a rotating gear **83** of the gear box **82**, and a bearing case **85** rotatably holding the turning shaft **35**.

(37) The turning means **36** is mounted on the X-axis moving base **61** moving in the X-axis, and the turning shaft **35** has the axis C2 thereof incorporated orthogonally to the XY-plane coordinate system, that is, an upper surface of the brittle plate **2**.

(38) The processing head **7** is mounted on the turning shaft **35** of the turning means **36** through the base **39** and horizontally and rotationally moved with the axis C2 of the turning shaft **35** as the center, integrally with the turning shaft **35**, while an angle is controlled in an R2 direction around the axis C2.

(39) The measuring portion **8** includes a mounting plate **91** mounted on a side surface of one frame **12A** in the pair of frames **12**, a Z-axis moving base **92** mounted movably in the Z-axis direction on the mounting plate **91**, Z-axis moving means **93** for moving the Z-axis moving base **92** in the Z-direction, an X-axis moving base **94** mounted movably in the X-axis direction with respect to the mounting plate **91**, X-axis moving means **95** for moving the X-axis moving base **94** in the X-axis direction as a first direction orthogonal to the axis C1 of the processing wheel **6**, rotating means **98** provided on the X-axis moving base **94** and having a shaft member **97** having a distal end portion **96**, and a position measurement sensor **99** for measuring a position of the processing surface **44** of the processing wheel **6**.

(40) The Z-axis moving base **92** includes a base **101**, a plate **104** mounted on the base **101** and having a flange portion **103** extending in the Y-axis direction from one end **102** in the Z-axis direction, and a plate portion **107** having a groove **106** with which a distal end portion **105** in the Y-axis direction of the flange portion **103** is fitted.

(41) In the plate **104** in this embodiment, the flange portion **103** is formed integrally on the one end

102 in the Z-axis direction.

(42) The Z-axis moving means **93** includes one guide rail (not shown) extending in the Z-axis direction and laid in parallel with each other, a slide block (not shown) attached to each of the guide rail (not shown) movably in the Z-axis direction and mounted on the Z-axis moving base **92**, a feed screw (not shown) screwed with a nut (not shown) fixed to the lower surface of the Z-axis moving base **92**, and a Z-axis control motor **108** for rotating the feed screw.

(43) The X-axis moving base **94** is formed of a plate portion **111** having a predetermined area extending in the X-axis direction, and a Cable-Bear mounting plate **113** for mounting a Cable Bear **112** is mounted on the plate portion **111**.

(44) The X-axis moving means **95** includes a rodless air cylinder **123** mounted on one surface **109** in the Y-axis direction of the plate portion **107** and having a slider **121** movable in the X-axis direction, a rodless air-cylinder connecting plate **124** connected to the slider **121** and also connected to the plate portion **111**, a guide rail **125** laid on the other surface **110** in the Y-axis direction of the plate portion **107** and extending in the X-axis direction, and a guide block **126** attached movably in the X-axis direction to the guide rail **125** and mounted on the one surface **115** in the Y-axis direction of the plate portion **111**.

(45) The X-axis moving means **95** moves the plate portion **111** in the X-axis direction through the rodless air-cylinder connecting plate **124** connected to the slider **121** by driving of the rodless air cylinder **123**.

(46) The rotating means **98** includes a servomotor **133** for controlling a torque, mounted on the other surface **116** in the Y-axis direction of the plate portion **111** through a bracket **131** and having an output rotating shaft **132**, a shaft member **97** having a distal end portion **96**, a coupling **134** for connecting the output rotating shaft **132** and the shaft member **97** to each other, and a bearing case **135** mounted on the other surface **116** in the Y-axis direction of the plate portion **111** and rotatably supporting the shaft member **97**.

(47) In this embodiment, the axis of the shaft member **97** and the axis of the output rotating shaft **132** of the servomotor **133** are disposed on an axis C3 (coaxially).

(48) The rotating means **98** rotates the shaft member **97** through the coupling **134** in an R3 direction around the axis C3 by driving of the servomotor **133**.

(49) The shaft member **97** includes a shaft body **141** extending in the X-axis direction, a notched portion **143** provided on one end portion **142** of the shaft body **141** in the X-axis direction, the distal end portion **96** inserted and held by the notched portion **143**, and fixing means **144** for fixing the distal end portion **96** to the shaft body **141**.

(50) The distal end portion **96** is formed of a hard material and includes a rectangular distal-end portion body **152** having a through hole **151** and a distal-end portion notched part **154** formed in an end portion **153** of the distal-end portion body **152** in the axis C3 direction.

(51) The distal end portion **96** only needs to be formed of a hard material, and the distal end portion **96** is formed of a stainless hard material in this embodiment.

(52) The fixing means **144** is formed of a screw body **161** in which a male thread part (not shown) is formed on an outer peripheral surface and a head portion **162** provided on one end of the screw body **161**, and in the through hole **151** of the shaft member **97**, a female thread part (not shown) formed on an inner peripheral surface defining the through hole **151** is formed, and the fixing means **144** fixes the distal end portion **96** to the shaft member **97** by penetrating the screw body **161** through the through hole **151** and by screwing the male thread part with the female thread part of the through hole.

(53) The position measurement sensor **99** includes a contact sensor **172** mounted on the other surface **116** in the Y-axis direction of the plate portion **111** through a bracket **171** and a stopper **174** mounted on the other surface **116** in the Y-axis direction of the plate portion **111** through the bracket **171** and brought into contact with one side surface **173** in the Y-axis direction of the flange portion **103**.

(54) Regarding the x-axis moving base **94**, in the X1 direction which is one direction in the X-axis direction by the rodless air cylinder **123**, first, the contact sensor **172** is brought into contact with the side surface **173** of the flange portion **103**, and then, the X-axis moving base **94** further moves in the X1 direction, whereby the stopper **174** is brought into contact with the side surface **173** of the flange portion **103**, and the movement in the X1 direction is stopped.

(55) The X-axis moving base **94** is biased in the X1 direction by an elastic force by an air pressure by the rodless air cylinder **123** in a state where the contact sensor **172** and the stopper **174** are in contact with the side surface **173** of the flange portion **103**.

(56) The contact sensor **172** is connected to the control portion **9**, and the control portion **9** moves the X-axis moving base **94** in an X2 direction by movement of the processing head **7** in the X2 direction. The control portion **9** stops the movement of the processing head **7** in the X1 direction when a movement amount set in advance in the contact sensor **172** is reached in the movement of this X-axis moving base **94** in the X2 direction.

(57) The contact sensor **172** is a contact-type sensor in this embodiment, but in place of this, a digital dial gauge, a laser displacement sensor, a non-contact sensor or the like which detects displacement electrically or optically may be used, for example.

(58) The stopper **174** can adjust a distance until the stopper **174** is brought into contact with the side surface **173** of the flange portion **103** by adjusting a protruding amount in the X1 direction from the bracket **171**.

(59) The control portion **9** includes arithmetic processing (processing) means **181** such as a CPU (Central Processing Unit) or the like and a memory (memory) means **182** such as a flash memory or the like. For example, the control portion **9** may be a computer (computer) such as a microprocessor, or the control portion **9** may be a virtual server constructed in a cloud or a physical computer installed in a machine room or the like. Moreover, the control portion **9** may be configured by a single computer, may be configured by a plurality of computers linked with each other, or may be configured by a cloud which is a collection of computer resources.

(60) The control portion **9** is connected to the table **4**, the processing head **7**, motors required for driving the measuring portion **8** and the processing apparatus **1** for brittle plate, the rodless air cylinder, the Cable Bear and the like and controls them through numerical control instructions programmed in advance. Since the control portion **9** as above is well-known, detailed description thereof is omitted.

(61) The memory means **182** is a recording medium including a ROM (Read Only Memory), a RAM (Random Access Memory), a hard disk drive and the like. The memory means **182** stores a program executed by the control portion **9** in advance. The memory means **182** may be provided outside the processing apparatus **1** for brittle plate and in that case, transmission/reception of data with the control portion **9** may be performed via a network.

(62) In this embodiment, each of the table **4**, the processing head **7**, and the measuring portion **8** is numerically controlled individually or each of the table **4**, the processing head **7**, and the measuring portion **8** may be numerically controlled in synchronization.

(63) Subsequently, by referring to FIGS. **5** to **8**, a processing method for brittle plate for processing the brittle plate **2** by using the processing apparatus **1** for brittle plate will be described. The following operation of the processing apparatus **1** for brittle plate is controlled by the control portion **9**. Moreover, FIG. **5** is a flowchart illustrating the processing method for brittle plate for processing the brittle plate **2** by using the processing apparatus **1** for brittle plate in this embodiment.

(64) As shown in FIG. **5**, the processing method for brittle plate includes a positioning process **S101** of positioning the shaft member **97** to a predetermined position, a first measuring process **S102** of rotating the shaft member **97** in an R4 direction which is a first rotating direction in the R3 direction around the axis C3 so as to bring the distal end portion **96** into contact with the processing surface **42** of the processing wheel **6** and of measuring a first position A on the processing surface

42 of the processing wheel **6** with which the distal end portion **96** is in contact, a second measuring process **S103** of rotating the shaft member **97** in an R5 direction which is a second rotating direction opposite to the R4 direction which is the first rotating direction in the R3 direction around the axis C3 so as to bring the distal end portion **96** into contact with the processing surface **42** of the processing wheel **6** and of measuring a second position B on the processing surface **42** of the processing wheel **6** with which the distal end portion **96** is in contact, a calculating process **S104** of calculating a first distance D3 from a predetermined processing reference position B1 to the first position A in the Z-axis direction of the processing wheel **6**, of calculating a second distance D4 from the predetermined processing reference position B1 to the second position B in the Z-axis direction of the processing wheel **6**, and of calculating a positional shift amount Δ in the Z-axis direction of the processing wheel **6** with respect to the brittle plate **2** on the basis of the first distance D3 and the second distance D4, a correcting process **S105** of correcting a positional shift in the Z-axis direction of the processing wheel **6** on the basis of the positional shift amount Δ in the Z-axis direction of the processing wheel **6**, and a processing process **S106** of causing the processing wheel **6** after the correcting process to process the outer peripheral edge **5** of the brittle plate **2**.

(65) First, as the positioning process **S101**, the brittle plate **2** to be processed is placed above the table **4** and positioned by vacuum sucking/supporting the brittle plate **2** by the sucking discs **21** of the table **4**.

(66) The Z-axis moving table **92** is moved in the Z-axis direction by the Z-axis moving means **93** so that the axis C3 of the shaft member **97** is positioned to the predetermined processing reference position B1. In this embodiment, the predetermined processing reference position B1 is a position where the brittle plate **2** is divided into halves in the Z-axis direction (thickness direction of the brittle plate **2**).

(67) As shown in FIGS. **6(a)** and **6(b)**, the X-axis moving means **95** is driven, whereby the X-axis moving base **94** is moved in the X1 direction, the shaft member **97** after the positioning to the processing reference position B1 is moved in the X1 direction, the contact sensor **172** is brought into contact with the side surface **173** of the flange portion **103**, the x-axis moving base **94** is further moved in the X1 direction, the stopper **174** is brought into contact with the side surface **173** of the flange portion **103**, and the movement of the x-axis moving base **94** in the X1 direction is stopped (limited).

(68) As shown in FIGS. **6(b)** and **6(c)**, in a state where the contact sensor **172** is in contact with the side surface **173** of the flange portion **103**, the stopper **174** is in contact with the side surface **173** of the flange portion **103**, and the movement of the X-axis moving base **94** in the X1 direction is stopped (limited), the processing wheel **6** is moved in the X2 direction by the X-axis moving means **33**, and the processing surface **42** of the processing wheel **6** is gradually brought closer to the shaft member **97**.

(69) The control portion **9** gradually moves the processing wheel **6** in the X2 direction, brings the processing surface **42** of the processing wheel **6** closer to the end portion **153** of the distal-end portion body **152**, and the processing wheel **6** is further moved in the X2 direction by a countervailing force in the X2 direction opposite to a direction of the air pressure in the X1 direction of the rodless air cylinder **123**.

(70) The processing wheel **6** is moved in the X2 direction in a state where the end portion **153** of the distal-end portion body **152** is in contact with the processing surface **42**.

(71) The control portion **9** stops the movement of the processing wheel **6** in the X2 direction when the horizontal distance D1 by which the contact sensor **172** is moved by the processing wheel **6** from the side surface **173** of the flange portion **103** in the X2 direction reaches the movement amount set in advance in the contact sensor **172**.

(72) At this time, the processing surface **42** of the processing wheel **6** and the end portion **153** of the distal-end portion body **152** maintain a contact state. The horizontal distance D1 by which the

contact sensor **172** is moved in the X2 direction is equal to the horizontal distance D2 by which the processing wheel **6** is moved in the X2 direction.

(73) After the movement of the processing wheel **6** in the X2 direction is stopped, the state where the processing surface **42** of the processing wheel **6** and the end portion **153** of the distal-end portion body **152** are in contact is maintained, the processing wheel **6** is moved in the X1 direction on the basis of the movement amount set in advance in the contact sensor **172**.

(74) As described above, the control portion **9** measures the position where the processing surface **42** is in contact with the end portion **153** of the distal-end portion body **152** and acquires position information.

(75) In order to cause the processing surface **42** of the processing wheel **6** faced to the end portion **153** of the distal-end portion body **152** with a predetermined clearance S1, the processing wheel **6** is further moved in the x1 direction.

(76) As shown in FIGS. 7, the predetermined clearance **51** may be such a degree that the end portion **153** of the distal-end portion body **152** is not in contact with the processing surface **42** of the processing wheel **6**, or the clearance S1 is preferably approximately 0.1 to 0.5 mm or more preferably it is 0.3 mm. The clearance S1 can be changed depending on a shape of the processing surface **42**.

(77) The end portion **153** of the distal-end portion body **152** is located in an annular space **52** defined by an outer profile and the processing surface **42** of the processing wheel **6** in a radial direction.

(78) Subsequently, a measuring operation of the shaft member **97** will be described in detail by referring to FIG. 8(a1) to 8(a3) and FIGS. 8(b1) to 8(b3). Note that FIGS. 8(a1) to 8(a3) are partially-omitted sectional views of the shaft member **97**, and FIGS. 8(b1) to 8(b3) are partially-omitted side views of the distal end portion **96**.

(79) As the first measuring process S102, as shown in FIGS. 8(a1) to 8(a2) and FIGS. 8(b1) to 8(b2), the measuring portion **8** causes the shaft member **97** to be rotated in the R4 direction so that the end portion **153** of the distal-end portion body **152** is brought into contact with the processing surface **42** of the processing wheel **6** and measures a positional coordinate of the first position A where the end portion **153** of the distal-end portion body **152** is rotated in the R4 direction and is brought into contact with the processing surface **42** of the processing wheel **6**.

(80) Subsequently, as shown in FIG. 8(a3) and FIG. 8(b3), as the second measuring process **103**, the measuring portion **8** causes the shaft member **97** to be rotated in the R5 direction so that the end portion **153** of the distal-end portion body **152** is brought into contact with the processing surface **42** of the processing wheel **6** and measures a positional coordinate of the second position B where the end portion **153** of the distal-end portion body **152** is rotated in the R5 direction and is brought into contact with the processing surface **42** of the processing wheel **6**.

(81) Subsequently, as the calculating process S104, the control portion **9** calculates the first distance D3 in the Z-axis direction of the processing wheel **6** from the predetermined processing reference position B1 to the first position A, and calculates the second distance D4 in the Z-axis direction of the processing wheel **6** from the predetermined processing reference position B1 to the second position B. For example, the first distance D3 is calculated from an angle $\theta 1$ formed by the distal-end portion body **152** and the processing reference position B1 and a length hl in the Y-axis direction of the distal-end portion body **152**, and the second distance D4 is calculated from an angle $\theta 2$ formed by the distal-end portion body **152** and the processing reference position B1 and the length hl in the Y-axis direction of the distal-end portion body **152**. Moreover, the angle $\theta 1$ and the angle $\theta 2$ may be calculated from the servomotor **133**.

(82) On the basis of the first distance D3 and the second distance D4, the positional shift amount Δ in the Z-axis direction of the processing wheel **6** with respect to the brittle plate **2** is calculated.

(83) The calculation of the positional shift amount Δ is executed by the arithmetic processing means **181**. In the calculation by the arithmetic processing means **181**, the positional shift amount Δ

is acquired by the positional shift amount Δ (correction amount) $= ((D3+D4)/2-D3)$, in the case of $D3 < D4$, for example.

(84) Subsequently, as the correcting process **S105**, the control portion **9** causes the Z-axis moving means **34** to be driven on the basis of the positional shift amount Δ by the arithmetic processing means **181**, moves the processing wheel **6** in a Z2 direction (upward) which is the other in the Z-axis direction, and corrects the positional shift (positional shift from the predetermined processing reference position B1 of the brittle plate **2** to the position B2 dividing the processing surface **42** of the processing wheel **6** into halves in the Z-axis direction) in the Z-axis direction of the processing wheel **6**.

(85) Subsequently, as the processing process **S106**, the processing wheel **6** whose positional shift was corrected is caused to process the outer peripheral edge **5** of the brittle plate **2**.

(86) According to the processing method for brittle plate in this embodiment, since the shaft member **97** having the distal end portion **96** of the rotating means **31** is inserted into the annular space S2 of the processing surface **42** of the processing wheel **6**, the shaft member **97** is rotated in the R4 direction and in the R5 direction, and the positional coordinates (the first position A and the second position B) where the distal end portion **96** is in contact with the processing surface **42** of the processing wheel **6** are measured, respectively, the positional shift amount Δ in the Z-axis direction of the processing wheel **6** is automatically calculated by the control portion **9** by the positional coordinates from the processing reference position B1, and the positional shift in the Z-axis direction of the processing wheel **6** can be automatically corrected, the manual positioning of the processing wheel **6** performed at each replacement of the processing wheel **6**, for example, can be automated, labor and time for the manual positioning of the processing wheel **6** with respect to the brittle plate **2** after the replacement of the processing wheel **6** can be reduced, and efficiency of the processing of the brittle plate as a whole can be made high.

(87) According to another example of this embodiment, in the processing method for brittle plate, by repeating the first measuring process **S102**, the second measuring process **S103**, the calculating process **S104**, and the correcting process **S105** in order several times, the positional shift amount Δ in the Z-axis direction of the processing wheel **6** with respect to the brittle plate **2** can be brought closer to 0 as much as possible, the positional shift in the Z-axis direction of the processing wheel **6** is eliminated, the processing surface **42** of the processing wheel **6** corrected several times is brought into contact with the brittle plate **2** with accuracy, and the brittle plate **2** can be processed with high accuracy. In another example of this embodiment, in the processing method for brittle plate, each process from the first measuring process **S102** to the correcting process **S105** may be preferably repeated in order from twice to five times, or more preferably, the processes from the first measuring process **S102** to the correcting process **S105** may be repeated in order three times so that the positional shift amount Δ in the Z-axis direction of the processing wheel **6** with respect to the brittle plate **2** can be brought closer to 0 as much as possible. Moreover, in order to reduce the positional shift in the Z-axis direction of the processing wheel **6** with respect to the brittle plate **2**, the first measuring process **S102**, the second measuring process **S103**, the calculating process **S104**, and the correcting process **S105** may be further repeated in order.

(88) According to another example of this embodiment, in the processing method for brittle plate, in the processing wheel **6** whose positional shift in the Z-axis direction was corrected after the correcting process **S105** or in the processing wheel **6** whose positional shift was corrected several times by repeating each process from the first measuring process **S102** to the correcting process **S105** in order several times, in a state where the control portion **9** causes the X-axis moving means **95** to be driven, causes the X-axis moving base **94** to move in the X1 direction, causes the shaft member **97** after the positioning to the processing reference position B1 to move in the X1 direction, causes the contact sensor **172** and the stopper **174** to be brought into contact with the side surface **173** of the flange portion **103**, stops (limits) the movement of the X-axis moving table **94** in the X1 direction so that the movement of the X-axis moving base **94** in the X1 direction is stopped

(limited), the processing wheel **6** is moved by the X-axis moving means **33** in the X2 direction, the processing surface **42** of the processing wheel **6** is gradually brought closer (moved) to the shaft member **97**, the processing surface **42** of the processing wheel **6** is brought into contact with the end portion **153** of the distal-end portion body **152**, the processing wheel **6** is further moved in the X2 direction by the countervailing force in the X2 direction which is the direction opposite to the air pressure of the rodless air cylinder **123** in the X1 direction, and when the horizontal distance D1 by which the sensor **172** is moved in the X2 direction from the side surface **175** of the flange portion **103** of the sensor **172** reaches the movement amount set in advance in the contact sensor **172**, the movement of the processing wheel **6** in the X2 direction is stopped, and after the movement of the processing wheel **6** in the X2 direction is stopped, while the state where the processing surface **42** of the processing wheel **6** and the end portion **153** of the distal-end portion body **152** are in contact is maintained, on the basis of the movement amount set in advance in the contact sensor **172**, by moving the processing wheel **6** in the X1 direction, the control portion **9** can measure the position where the processing surface **42** of the processing wheel **6** whose positional shift in the Z-axis direction was corrected is brought into contact with the end portion **153** of the distal-end portion body **152**, acquire the position information, and cause the processing surface **42** of the processing wheel **6** to be brought into contact with the outer peripheral edge **5** of the brittle plate **2** with accuracy on the basis of this position information and valued set in the control portion **9** in advance, that is, information set in advance such as dimensions of the processing wheel **6**, the shaft member **97**, the distal end portion **96** and the like, for example, and thus, accurate cut-in can be performed in the brittle plate **2** by the processing wheel **6** whose positional shift in the Z-axis direction was corrected after the correcting process S105 or the processing wheel **6** whose positional shift was corrected several times by repeating each process from the first measuring process S102 to the correcting process S105 in order several times.

(89) By referring to the drawings attached to FIG. **9** which is a front view of a processing apparatus **200** for brittle plate and the like illustrated as another example, details of the processing apparatus **200** for brittle plate according to the present invention will be described as follows. FIG. **10** is a flowchart illustrating a processing method for brittle plate of the processing apparatus **200** for brittle plate. Moreover, the processing apparatus **200** for brittle plate shown in FIG. **9** is different from that in FIG. **1** in a point that, instead of the rotating means **98** and the position measurement sensor **99**, laser measuring means **201** is used. The other constitutions of this processing apparatus **200** for brittle plate are the same as those of the processing apparatus **1** for brittle plate in FIG. **1** and thus, by giving the same signs as those in FIG. **1** and by incorporating the explanation in FIG. **1**, the detailed description of the other constitutions of this processing apparatus **1** for brittle plate will be omitted.

(90) The laser measuring means **201** is provided on the X-axis moving base **94** and measures the processing surface **42** by emitting a laser to the processing surface **42** of the processing wheel **6**.

(91) A measurement range of the laser measuring means **201** is different depending on a type of the laser measuring means **201**, but in the case of a middle-range type of CL-3000 series by KEYENCE (CL-L070/CL-P070), its measurement range is $70\text{ mm}\pm 10\text{ mm}$, in the case of the middle-range type of the LJ-G5000 series (LJ-G080), its measurement range is $80\text{ mm}\pm 23\text{ mm}$, and in the case of the highly accurate one (LJ-G030) of the LJ-G5000 series, its measurement range is $80\text{ mm}\pm 23\text{ mm}$. Moreover, the types of the laser measuring means **201** are not particularly limited to them, but they can be selected and used as appropriate in accordance with the applications.

(92) Moreover, the laser measuring means **201** can conduct various measurements such as a height (peak height, bottom height, average height), a width, a position, a step, an angle, an intersection, a shape, a sectional area, shape comparison and the like, for example, can conduct momentary measurement of a predetermined region or an entire region and can measure a position where a distance in the X-axis direction from the laser measuring means **201** to the processing surface **42** of the processing wheel **6** becomes the maximum in this embodiment.

(93) The control portion **9** calculates a position where the distance in the X-axis direction from the laser measuring means **201** to the processing surface **42** of the processing wheel **6** becomes the maximum by a measured value measured by the laser measuring means **201**, calculates the positional shift amount Δ in the Z-axis direction of the processing wheel **6** on the basis of the position (center B2 in the Z-axis direction of the processing wheel **6**) where the distance from the laser measuring means **201** to the processing surface **42** of the processing wheel **6** becomes the maximum, and the processing reference position B1, corrects the positional shift in the Z-axis direction of the processing wheel **6** on the basis of the positional shift amount Δ in the Z-axis direction of the processing wheel **6**, and causes the processing wheel **6** whose positional shift was corrected to process the outer peripheral edge **5** of the brittle plate **2**.

(94) Subsequently, by referring to FIG. **10**, a processing method for brittle plate for processing the brittle plate **2** by the processing apparatus **200** for brittle plate in this embodiment will be described. The following operations of the processing apparatus **200** for brittle plate are controlled by the control portion **9**. Moreover, FIG. **10** is a flowchart illustrating the processing method for brittle plate for processing the brittle plate **2** by using the processing apparatus **200** for brittle plate in this embodiment.

(95) As shown in FIG. **10**, the processing method for brittle plate includes a positioning process **8201** of positioning the laser measuring means **201** to a predetermined position, a measuring process **8202** of measuring the processing surface **42** of the processing wheel **6** by emitting a laser beam of the laser measuring means **201** to the processing surface **42** of the processing wheel **6**, a calculating process **s203** of calculating the positional shift amount Δ in the Z-axis direction of the processing wheel **6** on the basis of a measured value measured by the laser measuring means **201**, a correcting process **S204** of correcting the positional shift in the Z-axis direction of the processing wheel **6** on the basis of the positional shift amount Δ in the Z-axis direction of the processing wheel **6**, and a processing process **s205** of causing the processing wheel **6** after the correcting process to process the outer peripheral edge **5** of the brittle plate **2**.

(96) First, as the positioning process **S201**, the brittle plate **2** to be processed is placed above the table **4** and positioned by vacuum sucking/supporting the brittle plate **2** by the sucking discs **21** of the table **4**.

(97) In order to dispose the processing surface **42** of the processing wheel **6** in a range where measurement can be made by the laser measuring means **201**, the Z-axis moving means **93** is driven, the position in the Z-axis direction of the Z-axis moving base **92** is adjusted, the X-axis moving means **95** is driven, the X-axis moving base **94** is moved in the X1 direction, and the laser measuring means **201** is brought closer to the processing wheel **6** in the measurement range of the laser measuring means **201**.

(98) Subsequently, as the measuring process **S202**, the laser measuring means **201** measures the processing surface **42** of the processing wheel **6** by emitting a laser beam to the processing surface **42** of the processing wheel **6**.

(99) Subsequently, as the calculating process **s203**, the control portion **9** calculates the positional shift amount Δ in the Z-axis direction of the processing wheel **6** on the basis of the measured value measured by the laser measuring means **201**.

(100) The calculation of the positional shift amount Δ is performed by the arithmetic processing means **181**.

(101) Subsequently, as the correcting process **s204**, the control portion **9** causes the Z-axis moving means **34** to be driven on the basis of the positional shift amount Δ by the arithmetic processing means **181** so as to correct the positional shift in the Z-axis direction of the processing wheel **6**.

(102) Subsequently, as the processing process **s205**, the processing wheel **6** whose Z-positional shift was corrected is caused to process the outer peripheral edge **5** of the brittle plate **2**.

(103) According to the processing method for brittle plate of an example of this another embodiment, since the positional shift in the Z-axis direction of the processing wheel **6** can be

automatically corrected by automatically calculating the positional shift amount Δ in the Z-axis direction of the processing wheel **6** by the laser measuring means **201** easily, for example, the manual positioning of the processing wheel **6** performed at each replacement of the processing wheel **6** can be automated, labor and time for the manual positioning of the processing wheel **6** with respect to the brittle plate **2** after the replacement of the processing wheel **6** can be reduced, and efficiency of the processing of the brittle plate as a whole can be made high.

(104) According to an example of this another embodiment, in the measuring process **s202**, in the state where the laser measuring means **201** emits the laser to the processing surface **42** of the processing wheel **6**, time for measurement of the processing surface **42** of the processing wheel **6** can be reduced by relative movement of at least either one of the processing wheel **6** and the laser measuring means **201** from one to the other in the Z-axis direction and thus, for example, the manual positioning of the processing wheel **6** with respect to the brittle plate **2** performed at each replacement of the processing wheel **6** can be automated, and time for the positioning of the processing wheel **6** with respect to the brittle plate **2** can be drastically reduced.

(105) According to another example of this another embodiment, in the measuring process **s202**, since the laser measuring means **201** can measure the processing surface **42** of the processing wheel **6** by emitting the laser to at least one predetermined region, a plurality of predetermined regions or the entire region on the processing surface **42** of the processing wheel **6** in the Z-axis direction, time for measurement of the processing surface **42** of the processing wheel **6** can be reduced, for example, the manual positioning of the processing wheel **6** performed at each replacement of the processing wheel **6** can be automated, and time for the positioning of the processing wheel **6** can be drastically reduced. The predetermined region only needs to have an irradiation width of the laser to the processing surface **42** of the processing wheel **6** in the Z-axis direction, and it may be a region having one width or a region having a plurality of widths.

(106) According to another example of this another embodiment, in the measuring process **s202**, the processing surface **42** of the processing wheel **6** can be measured at the same time by emitting the laser at the same time to a predetermined region on the processing surface **42** of the processing wheel **6** in the Z-axis direction or arbitrary **8** spots on the processing surface **42** of the processing wheel **6** in the Z-axis direction, for example, and moreover, in the measuring process **s202**, the processing surface **42** of the processing wheel **6** can be measured at the same time by emitting the laser at the same time to the entire region on the processing surface **42** of the processing wheel **6** in the Z-axis direction.

(107) In the examples of the processing apparatus **1** for brittle plate and the processing apparatus **200** for brittle plate, the measuring portion **8** is constituted to include the Z-axis moving base **92** mounted movably in the Z-axis direction on the mounting plate **91** and the Z-axis moving means **93** for moving the Z-axis moving base **92** in the Z-direction, but instead of this, the measuring portion **8** may be mounted immovably in the Z-axis direction in a state positioned to the frame **12A** in the Z-axis direction without including the Z-axis moving base **92** and the Z-axis moving means **93**.

REFERENCE SIGNS LIST

(108) **1** Processing apparatus for brittle plate **2** Brittle plate **3** Base **4** Table **5** Outer peripheral edge **6** Processing wheel **7** Processing head **8** Measuring portion **9** Control portion **10** Ground **11** Main body **12** Frame **12A** Frame **13** Lateral support frame **21** Sucking disc **22** Sucking-disc base **23** Y-axis moving means **24** Cable **25** Guide rail **26** Slide block **27** Feed screw **31** Rotating means **32** Cut-in amount adjusting means **33** X-axis moving means **34** Z-axis moving means **35** Turning shaft **36** Turning means **37** Lower end portion **38** Turning holder **39** Base **41** Main body **42** Processing surface **45** lower end **46** Output rotating shaft **51** Cut-in slide **52** X-axis direction slide base **53** Nut **54** Feed screw **55** Cut-in gear **56** Cut-in gear **57** Bracket **58** Cut-in servomotor **61** X-axis moving base **62** Side surface **63** Guide rail **64** Feed screw **65** Bearing **66** Output rotating shaft **67** X-axis servomotor **71** Guide rail **72** Z-axis direction slide base **73** Nut **74** Feed screw **75** Gear

box 76 Output rotating shaft 77 Z-axis servomotor 81 Turning servomotor 82 Gear box 83 Rotating gear 84 Rotating gear 85 Bearing case 91 Mounting base 92 Z-axis moving base 93 Z-axis moving means 94 X-axis moving base 95 X-axis moving means 96 Distal end portion 97 Shaft member 98 Rotating means 99 Position measurement sensor 101 Base 102 One end 103 Flange portion 104 Plate 105 Distal end portion 106 Groove 107 Plate portion 108 Z-axis control motor 109 Surface 110 Surface 111 Plate portion 112 Cable Bear 113 Cable-Bear mounting plate 115 Surface 116 Surface 121 Slider 123 Rodless air cylinder 124 Rodless air-cylinder connecting plate 125 Guide rail 126 Guide block 131 Bracket 132 output rotating shaft 133 Servomotor 134 Coupling 135 Bearing case 141 Shaft body 142 End portion 143 notched portion 144 Fixing means 151 Through hole 152 Distal-end portion body 153 End portion 154 Distal-end portion notched part 161 Screw body 162 Head portion 171 Bracket 172 Contact sensor 173 Side surface 174 Stopper 181 Arithmetic processing means 182 Memory means 200 Processing apparatus for brittle plate 201 Laser measuring means

Claims

1. A processing apparatus for brittle plate, comprising: a table which holds the brittle plate, a processing head having a processing wheel for processing an outer peripheral edge of the brittle plate held by the table, a measuring portion which measures a positional shift amount in an axis direction of the processing wheel with respect to the brittle plate, and a control portion which corrects a positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel measured by the measuring portion and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate, and wherein said measuring portion includes: a mounting plate, a moving base provided capable of relative movement with respect to the mounting plate in a first direction orthogonal to an axis of the processing wheel, a moving portion for moving the moving base in the first direction, and a rotating portion provided on the moving base and having a shaft member including a distal end portion; the measuring portion causes the shaft member to be rotated in a first rotating direction and causes the distal end portion to be brought into contact with a processing surface of the processing wheel, measures a first position where the distal end portion is rotated in the first rotating direction and is brought into contact with the processing surface of the processing wheel, causes the shaft member to be rotated in a second rotating direction which is a direction opposite to the first rotating direction and causes the distal end portion to be brought into contact with the processing surface of the processing wheel, and measures a second position where the distal end portion is rotated in the second rotating direction and is brought into contact with the processing surface of the processing wheel; and the control portion calculates a first distance from a predetermined processing reference position to the first position in the axis direction of the processing wheel, calculates a second distance from the predetermined processing reference position to the second position in the axis direction of the processing wheel, calculates the positional shift amount in the axis direction of the processing wheel on the basis of the first distance and the second distance, corrects the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate.
2. The processing apparatus for brittle plate according to claim 1, wherein the processing apparatus for brittle plate alternately repeats measurement of the first position and the second position by the measuring portion and correction of the positional shift in the axis direction of the processing wheel by the control portion several times and causes the processing wheel whose positional shift was corrected several times to process the outer peripheral edge of the brittle plate.
3. The processing apparatus for brittle plate according to claim 1, wherein the rotating portion is a

servomotor which controls a torque.

4. A processing method for brittle plate using a processing apparatus for brittle plate, including: a table which holds the brittle plate, a processing head having a processing wheel for processing an outer peripheral edge of the brittle plate held by the table, a measuring portion which measures a positional shift amount in an axis direction of the processing wheel with respect to the brittle plate, and a control portion which corrects a positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel measured by the measuring portion and causes the processing wheel whose positional shift was corrected to process the outer peripheral edge of the brittle plate, the measuring portion including: a mounting plate, a moving base provided capable of relative movement with respect to the mounting plate in a first direction orthogonal to the axis of the processing wheel, a moving portion for moving the moving base in the first direction, and a rotating portion provided on the moving base and having a shaft member including a distal end portion, and the processing method for brittle plate, comprising: a positioning process of positioning the shaft member to a predetermined position, a first measuring process of bringing the distal end portion into contact with the processing surface of the processing wheel by rotating the shaft member in a first rotating direction around a shaft thereof and of measuring a first position on the processing surface of the processing wheel with which the distal end portion is brought into contact, a second measuring process of bringing the distal end portion into contact with the processing surface of the processing wheel by rotating the shaft member in a second rotating direction which is a direction opposite to the first rotating direction and of measuring a second position on the processing surface of the processing wheel with which the distal end portion is brought into contact, a calculating process of calculating a first distance in the axis direction of the processing wheel from a predetermined processing reference position to the first position, of calculating a second distance in the axis direction of the processing wheel from the predetermined processing reference position to the second position, and of calculating the positional shift amount in the axis direction of the processing wheel on the basis of the first distance and the second distance, a correcting process of correcting the positional shift in the axis direction of the processing wheel on the basis of the positional shift amount in the axis direction of the processing wheel, and a processing process of causing the processing wheel whose positional shift was corrected after the correcting process to process the outer peripheral edge of the brittle plate.

5. The processing method for brittle plate according to claim 4, wherein the first measuring process, the second measuring process, the calculating process, and the correcting process are repeated several times, and the processing wheel whose positional shift was corrected several times is caused to process the outer peripheral edge of the brittle plate.
