

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398607
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Strohla; Nick

Swivel sub with intermediate lug for extended rotation

Abstract

An apparatus may include a connector sub rigidly securable to a conveyance for running the connector sub along a wellbore. The connector sub has a connector lug. Further, the apparatus may include a spool mandrel having a mandrel lug that is rotatable with respect to the connector sub. Additionally, the apparatus may include an intermediate sub disposed between the connector sub and the spool mandrel. The intermediate sub includes an intermediate lug extending outward from an outer surface of the intermediate sub and contact between the intermediate lug, the connector lug, and the mandrel lug bounds rotational movement of the spool mandrel with respect to the connector sub between a first angular position and a second angular position.

Inventors:	Strohla; Nick (Carrollton, TX)
Applicant:	Halliburton Energy Services, Inc. (Houston, TX)
Family ID:	1000008778814
Assignee:	Halliburton Energy Services, Inc. (Houston, TX)
Appl. No.:	18/204312
Filed:	May 31, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240401425 A1	Dec. 05, 2024

Publication Classification

Int. Cl.: E21B23/02 (20060101)

U.S. Cl.:

Field of Classification SearchCPC: E21B (23/02); E21B (17/05); E21B (17/023)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4688649	12/1986	Buck	N/A	N/A
8061430	12/2010	Du et al.	N/A	N/A
8511392	12/2012	Howlett et al.	N/A	N/A
9683412	12/2016	Richards	N/A	N/A
9784073	12/2016	Bailey et al.	N/A	N/A
2005/0045339	12/2004	Hall	166/380	E21B 17/003
2006/0213670	12/2005	Bishop et al.	N/A	N/A
2016/0168923	12/2015	Richards	166/227	E21B 43/04
2019/0169941	12/2018	Bauer	N/A	E21B 17/07
2021/0254432	12/2020	Honeker et al.	N/A	N/A
2022/0090879	12/2021	Walker et al.	N/A	N/A
2023/0167712	12/2022	Pearce	166/381	H02K 5/132

OTHER PUBLICATIONS

International Search Report and Written Opinion for International Patent Application No. PCT/US2023/025769 dated Feb. 20, 2024. PDF file. 9 pages. cited by applicant

Primary Examiner: Yao; Theodore N

Attorney, Agent or Firm: C. Tumey Law Group PLLC

Background/Summary**BACKGROUND**

(1) In the process of completing an oil or gas well, various downhole tools (e.g., flow regulating systems, production packers, etc.) may be run-in-hole to assist in production operations. For example, a flow regulating system may be disposed proximate a producing formation. The flow regulating system may have a screen assembly that controls and limits debris, such as gravel, sand, and other particulate matter, from entering the tubular as the fluid passes through the screen assembly from the producing formation. The flow regulating system or other downhole tools may include completion devices (e.g., valves, sensors, actuators, etc.) that require electricity and/or control signals (e.g., electrical, light, or hydraulic) from the surface to operate.

(2) However, these downhole tools may not extend to the surface as they may be disposed deep in the wellbore proximate the producing formation. As such, running a control line from the surface to the downhole tools may be required to operate these downhole tools. Unfortunately, the tubular running the control line and/or the downhole tool may rotate or twist from their respective surface orientations while being run-in-hole, and failing to achieve a particular angular orientation between

the control line and the downhole tool requires adjustments, which may be time consuming and costly. Further, over rotation of the tubular may strain and damage the control line, which may interrupt production operations.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) These drawings illustrate certain aspects of some of the embodiments of the present disclosure and should not be used to limit or define the method.
- (2) FIG. 1 illustrates an elevation view of a well system, in accordance with some embodiments of the present disclosure.
- (3) FIGS. 2A-B illustrate respective side views of a swivel sub apparatus, in accordance with some embodiments of the present disclosure.
- (4) FIG. 3 illustrates a cross-sectional view of a swivel sub apparatus, in accordance with some embodiments of the present disclosure.
- (5) FIG. 4 illustrates a side view of a connector sub, an intermediate sub, and a spool mandrel of a swivel sub apparatus, in accordance with some embodiments of the present disclosure.
- (6) FIGS. 5A-E illustrate respective cross-sectional views of a connector lug of a connector sub, an intermediate lug of an intermediate sub, and a mandrel lug of a spool mandrel, in accordance with some embodiments of the present disclosure.
- (7) FIG. 6 illustrates a side view of a swivel sub apparatus having a return spring, in accordance with some embodiments of the present disclosure.
- (8) FIG. 7 illustrates a cross-sectional view of a radially extending connector lug, a radially extending mandrel lug, and an intermediate lug, in accordance with some embodiments of the present disclosure.
- (9) FIGS. 8A-B illustrate respective cross-sectional views of a shear mechanism, in accordance with some embodiments of the present disclosure.

DETAILED DESCRIPTION

(10) Disclosed herein are systems and methods for connecting a downhole tool with the surface via a control line. Example embodiments may include an apparatus (e.g., a swivel sub) for running the control line to the downhole tool. The apparatus includes a connector sub rigidly secured to a conveyance (e.g., tubular), a spool mandrel that is rotatably coupled to the connector sub, and an intermediate sub disposed between the connector sub and the spool mandrel. The control line extends from the surface along the conveyance and across the swivel sub. The control line is displaceable to permit at least some rotation of the spool mandrel with respect to the connector sub without straining and damaging the control line. To reduce strain to the control line, rotation of the spool mandrel with respect to the connector sub is limited between a first angular position and a second angular position by contact between a connector lug of the connector sub, an intermediate lug of the intermediate sub, and a mandrel lug of the spool mandrel to prevent over rotation of the spool mandrel, which may strain and damage the control line. However, rotation of the swivel sub between the first angular position and the second angular position may be sufficient rotation to allow the control line to be moved into the correct angular orientation to couple with the downhole tool such that electricity and/or control signals (e.g., electrical, light, and/or hydraulic) may be transmitted between the surface to the downhole tool.

(11) FIG. 1 illustrates an elevation view of a well system **100**, in accordance with some embodiments of the present disclosure. As illustrated, casing **102** may be run into a wellbore **104** to protect the wellbore **104** from failure (e.g., collapse, erosion) and provide a fluid path for hydrocarbons during production. To access the hydrocarbons for production, a perforating gun system may be deployed into the casing **102** to form perforations in the casing **102** and wellbore

wall **106** such that hydrocarbons may flow into the casing **102** via the perforation. Various downhole tools **108** may be run-in-hole once the perforations are formed. For example, a flow regulating system **110** may be disposed proximate the perforations. The flow regulating system **110** may control and limits debris, such as gravel, sand, and other particulate matter, from entering the casing **102** as the fluid passes through the flow regulating system **110** from the perforations. Further, the flow regulating system **110** or downhole tools **108** may include completion devices **112** (e.g., valves, sensors, actuators, etc.) that require electricity and/or control signals (e.g., electrical, light, hydraulic) from the surface to operate. Accordingly, as set forth above, a swivel sub apparatus **114** may be run-in-hole with a control line **116** to couple the control line **116** to the respective downhole tool **108** such that electricity and/or control signals may be transmitted between the surface to the downhole tool **108**.

(12) In particular, the swivel sub **114** may be run-in-hole, via a conveyance **118** (e.g., a tubular). The swivel sub **114** includes a connector sub **120** rigidly secured to the conveyance **118** such that rotational, axial, and radial movement between the connector sub **120** and the conveyance **118** are restrained. For example, the connector sub **120** may be threaded onto the conveyance **118**. The swivel sub **114** further includes a spool mandrel **122** that is rotatably coupled to the connector sub **120** and an intermediate sub (shown in FIG. 3) disposed between the connector sub **120** and the spool mandrel **122**. The connector sub **120**, spool mandrel **122**, and intermediate sub may each comprise a short section of piping/tubular material (e.g., a short drill collar, thread crossover, etc.) Moreover, the control line **116** extends from the surface along the conveyance **118** and across the swivel sub **114** such that a mating end **124** of the control line **116** is disposed at a downhole end **126** of the swivel sub **114**. The control line **116** may be displaceable to prevent strain on the control line **116** from rotation or twisting of the conveyance **118** as the swivel sub **114** is run-in-hole. Further, as set forth above, the control line **116** is also displaceable to permit rotation of the spool mandrel **122** with respect to the connector sub **120** between a first angular position and a second angular position (shown in FIGS. 5A-E).

(13) The swivel sub **114** may be configured to only couple to the downhole tool **108** in a particular angular orientation. As such, the spool mandrel **122** may rotate between the first angular position and the second angular position to align the mating end **124** of the control line **116** with a corresponding connector **128** of the downhole tool **108** as the conveyance **118** drives the swivel sub **114** toward and/or into the downhole tool **108**. Contact between the swivel sub **114** and the downhole tool **108** may drive rotation of the swivel sub **114** to the particular angular orientation with respect to the downhole tool **108**. The swivel sub **114** and/or the downhole tool **108** may comprise at least one guide feature configured to drive rotation of the spool mandrel **122** of the swivel sub **114** in response to contact between the swivel sub **114** and the downhole tool **108**. Alternatively, the swivel sub **114** may be configured to self-rotate to the particular angular orientation via any suitable mechanical, electrical, hydraulic, pneumatic, and/or magnetic driving mechanism. Driving the swivel sub **114** into the downhole tool **108** in the particular angular orientation (e.g., with the mating end **124** of the control line **116** aligned with the corresponding connector **128**) may couple the control line **116** with the downhole tool **108** to put the downhole tool **108** in electrical communication with the surface such that electricity and/or control signals may be transmitted between the surface and the downhole tool **108**.

(14) Moreover, the conveyance **118** may pull the swivel sub **114** in the uphole direction to disengage the swivel sub **114** from the downhole tool **108** in response to an unsuccessful coupling of the control line **116** with the downhole tool **108**. As set forth in greater detail below, the swivel sub **114** may include a return spring (shown in FIG. 6) to drive the spool mandrel **122** to rotate toward a neutral angular position of the spool mandrel **122** with respect to the connector sub **120** in response to disengaging the swivel sub **114** from the downhole tool **108**. Having the swivel sub **114** in the neutral position may be ideal for coupling with the downhole tool **108** as the spool mandrel **122** may be configured to rotate freely from the neutral position to align the control line **116** with

the corresponding connector **128** of the downhole tool **108**. Accordingly, with the swivel sub **114** in the neutral position, the conveyance **118** may drive the swivel sub **114** into the downhole tool **108** to re-attempt to couple the control line **116** with the downhole tool **108**. Having the return spring bias the swivel sub **114** to the neutral position, in response to disengaging the swivel sub **114** from the downhole tool **108**, may permit the swivel sub **114** to re-attempt to couple with the downhole tool **108** from an ideal angular position after each disengagement from the downhole tool **108**.

(15) FIGS. 2A-B illustrate respective side views of the swivel sub apparatus **114**, in accordance with some embodiments of the present disclosure. Specifically, FIGS. 2A-B illustrate the displaceability of the control line **116** in response to rotation of the spool mandrel **122** with respect to the connector sub **120**. FIG. 2A discloses the swivel sub **114** with the spool mandrel **122** in a neutral position with respect to the connector sub **120**. As illustrated, the control line **116** may be secured to the connector sub **120** via a first control line housing **200**. The first control line housing **200** may be secured to a radially outer connector surface **202** of the connector sub **120**. Further, the first control line housing **200** may include a bore configured to receive the control line **116**. That is, the control line **116** may extend through the bore. As the first control line housing **200** is secured to the connector sub **120**, an inner surface of the bore may restrain radial and circumferential movement of the control line **116** with respect to the connector sub **120**. The first control line housing **200** may also be configured to clamp onto the control line **116** to further restrain axial movement of the control line **116** with respect to the first control line housing **200**.

(16) Moreover, the control line **116** may be secured to a retainer sub **204** via a second control line housing **206** secured to a radially outer retainer surface **208** of the retainer sub **204**. As illustrated, the control line **116** extends from the first control line housing **200** on the connector sub **120** across to the second control line housing **206** on the retainer sub **204**. The second control line housing **206** may include a second bore configured to receive the control line **116** such that the control line may extend through the second bore. The inner surface of the second bore may restrain radial and circumferential movement of the control line **116** with respect to the connector sub **120**. The second control line housing **206** may also be configured to clamp onto the control line **116** to restrain axial movement of the control line **116** with respect to the second control line housing **206**. As the retainer sub **204** is rotationally fixed with respect to the connector sub **120**, the first control line housing **200** and the second control line housing **206** may maintain a fixed distance during rotation of the spool mandrel **122**, such that restraining axial movement of the control line **116** at the first control line housing **200** and the second control line housing **206** may not strain the control line **116** as the spool mandrel **122** rotates.

(17) Further, the control line **116** may be secured to a clamped mandrel **210** via a third control line housing **212** secured to a radially outer clamped surface **214** of the clamped mandrel **210**. Alternatively, the control line housing **212** may be secured to another portion of the swivel sub (e.g., a lower connector mandrel **218**) to secure the control line **116** proximate a downhole end **126** of the swivel sub **114**. As illustrated, the clamped mandrel **210** may be disposed about a portion of the lower connector mandrel **218**. Moreover, the third control line housing **212** may include a third bore configured to receive the control line **116** such that the control line **116** may extend through the third bore. The inner surface of the third bore may restrain radial and circumferential movement of the control line **116** with respect to the clamped mandrel **210** and/or the lower connector mandrel **218**. Further, the third control line housing **212** may be configured to clamp onto the control line **116** to restrain axial movement of the control line **116** with respect to the clamped mandrel **210** and/or the lower connector mandrel **218**.

(18) As illustrated, the control line **116** extends from the second control line housing **206** on the retainer sub **204** across to the third control line housing **212** on the clamped mandrel **210** and/or the lower connector mandrel **218**, which are disposed proximate a downhole end **126** of the swivel sub **114**. The clamped mandrel **210** and/or the lower connector mandrel **218** may be rotationally fixed with respect to the spool mandrel **122**. As such, rotation of the spool mandrel **122** may drive

rotation of the clamped mandrel **210** and/or the lower connector mandrel **218** with respect to the connector sub **120** and the retainer sub **204**, which may also rotate the angular position of the control line **116** with respect to the downhole tool **108** (shown in FIG. **1**). That is, rotating the spool mandrel **122** may drive rotation of the clamped mandrel **210** and/or the lower connector mandrel **218** to rotate the mating end **124** of the control line **116** for aligning and mating with the corresponding connector **128** (shown in FIG. **1**) of the downhole tool **108**. Indeed, restraining axial movement of the control line **116** at the clamped mandrel **210** and/or the lower connector mandrel **218** may hold the mating end **124** of the control line **116** in a fixed angular position on the clamped mandrel **210** and/or the lower connector mandrel **218** at the downhole end **126** of the swivel sub **114** such that rotation of the spool mandrel **122** also rotates the angular position of the control line **116** with respect to the downhole tool **108**.

(19) Moreover, the distance between the second control line housing **206** and the third control line housing **212** may increase as the clamped mandrel **210** and/or the lower connector mandrel **218** rotates with respect to the connector sub **120** and the retainer sub **204** in response to rotation of the spool mandrel **122**. As set forth above, the control line **116** extends from the second control line housing **206** on the connector sub **120** to the third control line housing **212** on the clamped mandrel **210** and/or the lower connector mandrel **218**. However, the control line **116** may comprise a coiled portion **216** between the second control line housing **206** and the third control line housing **212** to accommodate the variable distance between the second control line housing **206** and the third control line housing **212**. That is, the control line **116** may be coiled about the spool mandrel **122** (e.g., forming the coiled portion) between the second control line housing **206** and the third control line housing **212**. The control line **116** may comprise a material that may be displaced (e.g., elastic deformation) without permanently straining (e.g., plastic deformation). As such, the coiled portion **216** of the control line **116** may be displaced (e.g., stretch, uncoil, recoil, etc.) in response to rotation of the spool mandrel **122** without permanently straining and damaging the control line **116**. Further, increasing a number of coils or wraps of the coiled portion **216** about the spool mandrel **122** may increase a length of the control line **116** between the second control line housing **206** and the third control line housing **212**. Increasing the length of the control line **116** may reduce strain on the control line **116** by spreading the deformation or displacement across a greater length. As such, the coiled portion **216** of the control line **116** may be advantageous for reducing strain on the control line **116** as the spool mandrel **122** rotates to vary the distance between the second control line housing **206** and the third control line housing **212**.

(20) FIG. **2B** discloses the swivel sub apparatus **114** with the spool mandrel **122** in a rotated position with respect to the connector sub **120**. In particular, the spool mandrel **122** is rotated counterclockwise with respect to the connector sub **120**. Such rotation increases the distance between the second control line housing **206** and the third control line housing **212**. As set forth above, the control line **116** is axially fixed at the second control line housing **206** and the third control line housing **212**. As such, the coiled portion **216** of the control line **116** may be displaced (e.g., stretch, uncoil, etc.) to accommodate the increased distance between the second control line housing **206** and the third control line housing **212**.

(21) Moreover, rotating the spool mandrel **122** back to the neutral position may reduce the distance between the second control line housing **206** and the third control line housing **212**. As such, the coiled portion **216** of the control line **116** may recoil and/or compress back to a neutral state to reduce slack in the control line **116** between the second control line housing **206** and the third control line housing **212**. Such displacement of the coiled portion **216** may permit rotation of the spool mandrel **122** between the first angular position and the second angular position without permanently straining and damaging the control line **116**.

(22) FIG. **3** illustrates a cross-sectional view of the swivel sub apparatus **114**, in accordance with some embodiments of the present disclosure. The swivel sub **114** includes the connector sub **120** and the spool mandrel **122**, which is rotatable with respect to the connector sub **120**. The swivel

sub further includes the intermediate sub **338** disposed between the connector sub **120** and the spool mandrel **122**. The intermediate sub **338** may rotate independent of both the connector sub **120** and the spool mandrel **122**. The spool mandrel **122** may rotate with respect to the connector sub **120** between the first angular position and the second angular position. The first angular position and the second angular position may be between six hundred and thirty to seven hundred and twenty degrees apart. However, the first angular position and the second angular position may be offset by any amount between zero to seven hundred and twenty degrees. As set forth in greater detail below, rotation of the intermediate sub **338** may permit the spool mandrel **122** to rotate more than one revolution, which may help facilitate reliable mating between the swivel sub **114** and the downhole tool **108** (shown in FIG. 1).

(23) As illustrated, an uphole end **340** of the intermediate sub **338** may be at least partially disposed within the connector sub **120**, and a downhole end **342** of the intermediate sub **338** may be at least partially disposed within the spool mandrel **122**. Alternatively, the uphole end **340** of the intermediate sub **338** may be axially offset from the connector sub **120**, and the downhole end **342** of the intermediate sub **338** may be axially offset from the spool mandrel **122**. Further, in another alternative, the uphole end **340** of the intermediate sub **338** may be disposed about the connector sub **120** such that the connector sub **120** is disposed at least partially within the intermediate sub **338**, and the downhole end **342** of the intermediate sub **338** may be disposed about the spool mandrel **122** such that the spool mandrel **122** is disposed at least partially within the intermediate sub **338**. Moreover, the connector sub **120**, the intermediate sub **338**, and the spool mandrel **122** each comprise a substantially tubular shape (e.g., a substantially hollow cylindrical shape). As illustrated, a radially inner connector surface **300** of a downhole end **302** of the connector sub **120** may have a greater diameter than a radially outer intermediate surface **344** of the uphole end **340** of the intermediate sub **338**, such that the uphole end **340** of the intermediate sub **338** may be disposed in the downhole end **302** of the connector sub **120**. Having the uphole end **340** of the intermediate sub **338** disposed in the downhole end **302** of the connector sub **120** may restrain radial movement of the intermediate sub **338** with respect to the connector sub **120**. Further, a radially inner mandrel surface **346** of an uphole end **306** of the spool mandrel **122** may have a greater diameter than the radially outer intermediate surface **344** of the downhole end **342** of the intermediate sub **338**, such that the downhole end **342** of the intermediate sub **338** may be disposed in the uphole end **306** of the spool mandrel **122**. Having the downhole end **342** of the intermediate sub **338** disposed in the uphole end **306** of the spool mandrel **122** may restrain radial movement of the intermediate sub **338** with respect to the spool mandrel **122**. Alternatively, or additionally, the swivel sub **114** may include the retainer sub **204** for restraining radial movement of the connector sub **120**, the intermediate sub **338**, and/or the spool mandrel **122**.

(24) Moreover, the swivel sub **114** may include the retainer sub **204** for restraining axial movement between the spool mandrel **122**, the intermediate sub **338**, and the connector sub **120**. As illustrated, the retainer sub **204** may be disposed radially exterior to the connector sub **120**, the intermediate sub **338**, and the spool mandrel **122**. The connector sub **120** and the spool mandrel **122** may each include slots and or shoulders formed in their respective radially outer surfaces (e.g., the radially outer connector surface **202** and a radially outer spool surface **308**). The retainer sub **204** may include corresponding features formed in a radially inner retainer surface **310** of the retainer sub **204** for interfacing with the slots and/or shoulders formed in connector sub **120** and spool mandrel **122**. Such interfaces may restrain axial movement of the spool mandrel **122** with respect to the connector sub **120**. Further, as the intermediate sub **338** is disposed between the connector sub **120** and the spool mandrel **122**, restraining axial movement of the connector sub **120** and the spool mandrel **122** may restrain axial movement of the intermediate sub **338**.

(25) For example, as illustrated, the connector sub **120** may include an outer connector slot **312** formed in the radially outer connector surface **202** of the connector sub **120**. The outer connector slot **312** may at least partially extend about the circumference of the connector sub **120**. The

retainer sub **204** may include a corresponding retainer protrusion **314** extending radially inward from the radially inner retainer surface **310** of the retainer sub **204**. The retainer protrusion **314** may at least partially extend about the circumference of the radially inner retainer surface **310**. The retainer protrusion **314** may be disposed within the outer connector slot **312** and contact between the retainer protrusion **314** and the outer connector slot **312** may restrain axial movement of the connector sub **120** with respect to the retainer sub **204**. Further, the swivel sub **114** may include additional fasteners and/or interfaces between the connector sub **120** and the retainer sub **204** to rigidly secure the connector sub **120** to the retainer sub **204** (i.e., to restrain axial, radial, and rotational movement between the connector sub **120** and the retainer sub **204**).

(26) Moreover, the spool mandrel **122** may include a spool shoulder **316** formed at a transition between a protruding portion **318** of the spool mandrel **122** and a base portion **320** of the spool mandrel **122**. The protruding portion **318** may have a larger diameter than the base portion **320** such that the spool shoulder **316** is formed at the transition. As illustrated, the retainer sub **204** may include a radially inner lip **322** formed in the radially inner retainer surface **310** of the retainer sub **204**. An uphole end **324** of the radially inner lip **322** may interface with the spool shoulder **316** to restrain downhole movement of the spool mandrel **122** with respect to the retainer sub **204** and the connector sub **120**. Additionally, uphole movement of the spool mandrel **122** with respect to the retainer sub **204** and the connector sub **120** may be restrained by an interface between the uphole end **306** of the spool mandrel **122** and the downhole end **342** of the intermediate sub **338**, which is restrained by contact between the uphole end **340** of the intermediate sub **338** and the downhole end **302** of the connector sub **120**. As such, axial movement between the spool mandrel **122**, the intermediate sub **338**, and the connector sub **120** may be restrained.

(27) Additionally, a shroud **326** may be disposed about the coiled portion **216** of the control line **116**. An uphole end **328** of the shroud **326** may be secured to the retainer sub **204**, and a downhole end **330** of the shroud **326** may be secured to the clamped mandrel **210**. Further, the shroud **326** may be radially offset from the spool mandrel **122** such that a control line cavity **332** is formed between the spool mandrel **122** and the shroud **326** for housing the coiled portion **216** of the control line **116**. The shroud **326** may shield the coiled portion **216** of the control line **116** from the downhole environment.

(28) Moreover, as set forth above, the spool mandrel **122** may freely rotate with respect to the connector sub **120** between the first angular position and the second angular position. However, as the swivel sub **114** is run-in-hole, rotation of the spool mandrel **122** with respect to the connector sub **120** may be undesirable. As such, the swivel sub **114** may include a shear member **334** (e.g., shear pin or other suitable fastener) configured to restrain rotation of the spool mandrel **122** with respect to the connector sub **120**. The shear member **334** may initially hold the spool mandrel **122** in a neutral position between the first and second angular position. However, once the swivel sub **114** is positioned proximate the downhole tool **108**, rotation of the spool mandrel **122** may be needed to re-orient the control line **116** with respect to the corresponding connector **128** of the downhole tool **108**. As such, the swivel sub **114** may include a shear mechanism **336** to shear the shear member **334**, which releases the spool mandrel **122** to rotate with respect to the connector sub **120**. As set forth in greater detail below, the shear mechanism **336** may be configured to actuate in response to the shear mechanism **336** contacting the downhole tool **108** (shown in FIG. 1). Such contact may apply a threshold force needed for shearing the shear member **334**.

(29) FIG. 4 illustrates a side view of the connector sub **120**, the intermediate sub **338**, and the spool mandrel **122** of the swivel sub apparatus **114**, in accordance with some embodiments of the present disclosure. The connector sub **120** may include a connector lug **400**. As illustrated, the connector lug **400** may comprise an axially extending connector lug **400** that may extend axially outward from the downhole end **302** of the connector sub **120**. However, the connector lug **400** may comprise any suitable shape and/or orientation. Moreover, the spool mandrel **122** may include a mandrel lug **402**. The mandrel lug **402** may comprise an axially extending mandrel lug **402** that

may extend axially outward from the uphole end **306** of the spool mandrel **122**. However, the mandrel lug **402** may also comprise any suitable shape and/or orientation. As set forth above, the downhole end **302** of the connector sub **120** may be spaced apart axially from the uphole end **306** of the spool mandrel **122** to form a gap between the connector sub **120** and the spool mandrel **122** for the intermediate sub **338**.

(30) Further, the connector lug **400** and the mandrel lug **402** may also be spaced apart axially to form a gap between the connector lug **400** and the mandrel lug **402** such that the mandrel lug **402** may not contact the connector lug **400** during rotation of the spool mandrel **122**. Instead, the connector lug **400** interfaces with an uphole end **416** of an intermediate lug **418** of the intermediate sub **338**, and the mandrel lug **402** interfaces with a downhole end **420** of the intermediate lug **418**. As illustrated, the intermediate sub **338** is disposed between the connector sub **120** and the spool mandrel **122**, and the intermediate sub **338** includes the intermediate lug **418** extending radially outward from the radially outer intermediate surface **344** of the intermediate sub **338**.

(31) Additionally, the intermediate lug may extend axially between the downhole end **302** of the connector sub **120** and the uphole end **306** of the spool mandrel **122**. In particular, as illustrated, the uphole end **416** of the intermediate lug **418** may extend to the downhole end **302** of the connector sub **120**. Alternatively, the intermediate lug **418** may be offset from the downhole end **302** of the connector sub **120**, but may extend toward the downhole end **302** such that the intermediate lug **418** is axially aligned with at least a portion of the connector lug **400**. Further, as illustrated, the downhole end **420** of the intermediate lug **418** may extend to the uphole end **306** of the spool mandrel **122**. Alternatively, the intermediate lug **418** may be offset from the uphole end **306** of the spool mandrel **122**, but may extend toward the uphole end **306** such that the intermediate lug **418** is axially aligned with at least a portion of the mandrel lug **402**.

(32) Having the intermediate lug **418** axially aligned with at least a portion of the connector lug **400** may cause the intermediate lug **418** to contact the connector lug **400** at a particular angular orientation during rotation of the spool mandrel **122**, which may restrain rotation of the intermediate sub **338** with respect to the connector sub **120**. Additionally, having the intermediate lug **418** axially aligned with at least a portion of the mandrel lug **402** may cause the intermediate lug **418** to contact the mandrel lug **402** at a particular angular orientation during rotation of the spool mandrel **122**, which may restrain rotation of the intermediate sub **338** with respect to the spool mandrel **122**. Indeed, contact between the intermediate lug **418**, the connector lug **400**, and the mandrel lug **402** bounds rotational movement of the spool mandrel **122** with respect to the connector sub **120** between a first angular position and a second angular position.

(33) In the first angular position of the spool mandrel **122**, a first side **404** of the connector lug **400** is disposed proximate a first side **422** of the intermediate lug **418** and a first side **406** of the mandrel lug **402** is disposed proximate a second side **424** of the intermediate lug **418**. The swivel sub **114** may be run-in-hole with the spool mandrel **122** in the first angular position. However, in response to contact with the downhole tool **108** (shown in FIG. 1), the spool mandrel **122** may rotate from the first angular position toward the second angular position in a first direction **414** (e.g., a clockwise direction). In particular, as the spool mandrel **122** rotates in the first direction **414**, the mandrel lug **402** rotates away from the second side **424** of the intermediate lug **418** toward the first side **422** of the intermediate lug **418**. Further, continued rotation of the spool mandrel **122** may drive a second side **410** of the mandrel lug **402** into the first side **422** of the intermediate lug **418**, which may drive the intermediate lug **418** away from the first side **404** of the connector lug **400** toward the second side **408** of the connector lug **400**. Moreover, contact between the second side **410** of the mandrel lug **402** with the first side **422** of the intermediate lug **418** and contact between the second side **424** of the intermediate lug **418** and the second side **408** of the connector lug **400** may restrain rotational movement of the spool mandrel **122** with respect to the connector sub **120** at the second angular position. In the illustrated embodiment, the spool mandrel **122** is disposed in the second angular position.

(34) FIGS. 5A-E illustrate respective cross-sectional views of the connector lug **400** of the connector sub **120**, the intermediate lug **418** of the intermediate sub **338**, and the mandrel lug **402** of the spool mandrel **122**, in accordance with some embodiments of the present disclosure. In particular, FIG. 5A discloses the mandrel lug **402** disposed in the first angular position **500** with respect to the connector lug **400** of the connector sub **120**. In the first angular position **500**, the first side **404** of the connector lug **400** is disposed proximate the first side **422** of the intermediate lug **418** and the first side **406** of the mandrel lug **402** is disposed proximate the second side **424** of the intermediate lug **418**. The spool mandrel **122** may be bounded in the second direction **502** (e.g., the counterclockwise direction) at the first angular position **500** by contact between the first side **404** of the connector lug **400** and the first side **422** of the intermediate lug **418**, as well as the contact between the first side **406** of the mandrel lug **402** and the second side **424** of the intermediate lug **418**. As set forth above, restraining angular movement of the spool mandrel **122** with respect to the connector sub **120** may prevent over-rotation of the spool mandrel **122** and avoid strain and damage to the control line **116** (shown in FIGS. 2A-B).

(35) FIG. 5B discloses the mandrel lug **402** having moved in the first direction **414** (e.g., the clockwise direction) away from the intermediate lug **418**. As the spool mandrel **122** rotates in the first direction **414**, the mandrel lug **402** rotates away from the second side **424** of the intermediate lug **418** toward the first side **422** of the intermediate lug **418**. Additionally, the mandrel lug **402** rotates independent of the intermediate lug **418** and the connector lug **400**. As such, the intermediate lug **418** may remain positioned proximate the connector lug **400** as the mandrel lug **402** moves in the first direction **414** from the first angular position **500** (shown in FIG. 5A).

(36) FIG. 5C discloses the mandrel lug **402** positioned proximate the first side **422** of the intermediate lug **418**. As illustrated, continued rotation of the spool mandrel **122** in the first direction **414** drives the second side **410** of the mandrel lug **402** into the first side **422** of the intermediate lug **418**, which may drive the intermediate lug **418** in the first direction **414** away from the first side of the connector lug **400** toward the second side **408** of the connector lug **400**. Moreover, as the mandrel lug **402** is axially offset or spaced apart from the connector lug **400**, the mandrel lug **402** may continue to rotate past the connector lug **400** as the spool mandrel **122** rotates in the first direction **414**.

(37) FIG. 5D discloses the mandrel lug **402** driving the intermediate lug **418** in the first direction **414** away from the connector lug **400**. Indeed, contact between the second side **410** of the mandrel lug **402** into the first side **422** of the intermediate lug **418** may allow rotation of the spool mandrel **122** to drive both the mandrel lug **402** and the intermediate lug **418** in the first direction **414** towards the second side **408** of the connector lug **400**.

(38) FIG. 5E discloses the mandrel lug **402** disposed in the second angular position **506**. Moreover, in the second angular position **506**, the second side **424** of the intermediate lug **418** is in contact with the second side **408** of the connector lug **400** and the second side **410** of the mandrel lug **402** is in contact with the first side **422** of the intermediate lug **418**. Contact between the second side **410** of the mandrel lug **402** and the first side **422** of the intermediate lug **418**, as well as contact between the second side **424** of the intermediate lug **418** and the second side **408** of the connector lug **400** may restrain rotational movement of the spool mandrel **122** in the first direction **414** (e.g., the clockwise direction) with respect to the connector sub **120** at the second angular position **506**.

(39) Moreover, the first angular position **500** (shown in FIG. 5A) and the second angular position **506** may be between six hundred and thirty degrees to seven hundred and twenty degrees apart. As such, the spool mandrel **122** may freely rotate six hundred and thirty degrees to seven hundred and twenty degrees between the first angular position **500** and the second angular position **506** in response to contact of the swivel sub **114** with the downhole tool **108** to align the mating end **124** of the control line **116** with the corresponding connector **128** of the downhole tool **108** (shown in FIG. 1).

(40) FIG. 6 illustrates a side view of a swivel sub **114** having at least one return spring **412**, in

accordance with some embodiments of the present disclosure. As set forth above, the at least one return spring **412** may be configured to bias the spool mandrel **122** toward an initial angular position and/or neutral position of the spool mandrel **122** with respect to the connector sub **120**. For example, the initial angular position of the spool mandrel **122** may be the first angular position **500** (e.g., shown in FIG. 5A). As such, the at least one return spring **412** may bias the spool mandrel **122** toward the first angular position **500** of the spool mandrel **122** in response to the spool mandrel **122** rotating toward the second angular position **506** (e.g., in the clockwise direction or the counterclockwise direction). Further, the at least one return spring **412** may comprise a compression spring, a tension spring, a torsion spring, or some combination thereof.

(41) Moreover, as illustrated, the at least one return spring **412** may comprise a first return spring **600** and a second return spring **602**. A first end **604** of the first return spring **600** may be attached to the connector sub **120** and a second end **606** of the first return spring **600** may be attached to the intermediate sub **338**. In particular, the second end **606** of the first return spring **600** may be attached to the intermediate lug **418** of the intermediate sub **338**. Further, a first end **608** of the second return spring **602** may be attached to the intermediate sub **338** and a second end **610** of the second return spring **602** may be attached to the spool mandrel **122**. In particular, the first end **608** of the second return spring **602** may be attached to the intermediate lug **418** of the intermediate sub **338**. As illustrated, the first return spring **600** and the second return spring **602** may comprise torsion springs configured to bias the spool mandrel **122** toward the initial angular position and/or neutral position of the spool mandrel **122**.

(42) As set forth above, in the neutral position, the first side **404** of the connector lug **400** is disposed proximate the first side **422** of the intermediate lug **418** and the first side **406** of the mandrel lug **402** is disposed proximate the second side **424** of the intermediate lug **418**. Rotation of the mandrel lug **402** of the spool mandrel **122** away from the neutral position (e.g., in the clockwise direction) may strain the second return spring **602**, such that the second return spring **602** may bias the mandrel lug **402** back toward the intermediate lug **418**. Further, as set forth above, continued rotation of the spool mandrel **122** in the clockwise direction may drive the second side **410** of the mandrel lug **402** into the first side **422** of the intermediate lug **418**, which may drive the intermediate lug **418** in the clockwise direction away from the first side **404** of the connector lug **400** and toward the second side **408** of the connector lug **400**. Rotation of the intermediate lug **418** away from the connector lug **400** may strain the first return spring **600**, such that the first return spring **600** may bias the intermediate lug **418** back toward connector lug **400**. Accordingly, the first return spring **600** biasing the intermediate lug **418** toward the connector lug **400** and the second return spring **602** biasing the mandrel lug **402** toward the intermediate lug **418** may, in combination, bias the spool mandrel **122** toward the initial angular position and/or neutral position of the spool mandrel **122**.

(43) FIG. 7 illustrates a cross-sectional view of a radially extending connector lug **400**, a radially extending mandrel lug **402**, and the intermediate lug **418**, in accordance with some embodiments of the present disclosure. As illustrated, the swivel sub **114** has the mandrel lug **402** disposed in the first angular position **500**. Further, the connector lug **400** may extend radially inward from the radially inner connector surface **300** of the connector sub **120**. Further, the mandrel lug **402** may extend radially outward from the radially outer spool surface **308** of the spool mandrel **122**. Alternatively, the mandrel lug **402** may extend radially inward from the radially inner mandrel surface **346** of the spool mandrel **122**. Additionally, the intermediate lug **418** may extend radially outward from the radially outer intermediate surface **344** (not shown) of the intermediate sub **338**. Having radially extending lugs (e.g., the connector lug **400** and the mandrel lug **402**) may be advantageous for reducing a length of the swivel sub **114** as having lugs extend axially outward from respective ends of the connector sub **120** and the spool mandrel **122** may not be needed.

(44) FIGS. 8A-B illustrate respective cross-sectional views of a shear mechanism, in accordance with some embodiments of the present disclosure. In particular, FIG. 8A discloses the shear

mechanism **336** and the shear member **334** (e.g., shear pin) holding the spool mandrel **122** in a run-in position (e.g., a position of the spool mandrel **122** while being run-in-hole). As set forth above, the retainer sub **204** may be rigidly secured to the connector sub **120** such that the retainer sub **204** is axially and rotationally fixed with respect to the connector sub **120**. Further, the shear mechanism **336** may be secured to the retainer sub **204** in a first axial position **800**. The shear mechanism **336** may comprise a sleeve **802** having a shear member slot **804**. As illustrated, the shear member **334** may be disposed in the shear member slot **804** to hold the spool mandrel **122** in the run-in position as the swivel sub **114** is run-in-hole. That is, the shear member **334** may extend through the shear member slot **804** and into a spool slot **806** formed in the spool mandrel **122**. As such, the shear member **334** may restrain rotational movement, as well as axial movement, between the shear mechanism **336** and the spool mandrel **122**, which may restrain rotational movement between the spool mandrel **122** and the connector sub **120**.

(45) The shear mechanism **336** may further comprise an interface feature **808** configured to engage (e.g., contact) the downhole tool **108** as the conveyance **118** drives the swivel sub **114** into the downhole tool **108** (shown in FIG. 1). As set forth above, the shear member **334** may restrain axial movement of the sleeve **802** of the shear mechanism **336** with respect to the spool mandrel **122**. The interface feature **808** may include a protrusion (e.g., retractable interface pin **810**) extending radially outward from the sleeve **802**. Indeed, the retractable interface pin **810** may be disposed in a radially extended position as the swivel sub **114** is run-in-hole. As the retractable interface pin **810** engages the downhole tool **108**, a force on retractable interface pin **810** may drive the sleeve **802** in the axially uphole direction **812** with respect to the spool mandrel **122**. The shear member **334** may restrain axial movement of the sleeve **802** with respect to the spool mandrel **122**. However, in response to at least a threshold force being applied to the retractable interface pin **810** from the engagement of the retractable interface pin **810** with the downhole tool **108**, the sleeve **802** may shear the shear member **334** and slide in the axially uphole direction **812**. As such, the shear mechanism **336** may be configured to shear the shear member **334** in response to the swivel sub apparatus **114** engaging a downhole tool **108** disposed in the wellbore **104** (shown in FIG. 1).

(46) FIG. 8B discloses the shear mechanism **336** disposed in a locked position **814** (e.g., a second axial position) after sliding in the axially uphole direction **812** in response to the shear member **334** being sheared. As set forth above, the interface feature (e.g., retractable interface pin **810**) is disposed in the radially extended position as the swivel sub **114** is run-in-hole. Specifically, the radially outer retainer surface **208** of the retainer sub **204** may bias the retractable interface pin **810** toward the radially extended position in the run-in position. However, in the locked position **814**, the retractable interface pin **810** may be axially aligned with a corresponding interface feature slot **816** formed in the retainer sub **204**. The retractable interface pin **810** is configured to retract into the interface feature slot **816** as the shear mechanism **336** slides to the locked position **814**. The retractable interface pin **810** may cease to engage the downhole tool **108** once retracted such that the shear mechanism **336** avoids interfering with rotation of the spool mandrel **122** with respect to the downhole tool **108** as the mating end **124** of the control line **116** is re-oriented to mate with the corresponding connector **128** of the downhole tool **108** (shown in FIG. 1).

(47) Moreover, the shear mechanism **336** may further include a locking mechanism **818** configured to secure the shear mechanism **336** in the locked position **814**. As illustrated, the locking mechanism **818** may include a biasing arm **820** connected to the retractable interface pin **810**. The biasing arm **820** may be configured to bias the retractable interface pin **810** radially inward to hold the retractable interface pin **810** in the interface feature slot **816** in the locked position **814**. Further, contact between axial surfaces of the retractable interface pin **810** and the interface feature slot **816** may restrain axial movement of the retractable interface pin **810**, which also restrains axial movement of the sleeve **802** to hold the shear mechanism **336** in the locked position **814**. Although, a particular shear mechanism **336** is shown in the illustrated embodiment, the swivel sub **114** may include any suitable shear mechanism to shear the shear member **334** and release to spool mandrel

122 to rotate with respect to the connector sub **120** in response to engagement of the swivel sub **114** with the downhole tool **108**.

(48) Accordingly, the present disclosure may provide a swivel sub having a spool mandrel configured to rotate with respect to a connector sub, between a first angular position and a second angular position bounded by a connector lug, a mandrel lug, and an intermediate lug, to align a mating end of a control line with a corresponding connector of a downhole tool while avoiding straining and damaging the control line. The methods and systems may include any of the various features disclosed herein, including one or more of the following statements.

(49) Statement 1. An apparatus, comprising: a connector sub rigidly securable to a conveyance for running the connector sub along a wellbore, the connector sub having a connector lug; a spool mandrel having a mandrel lug, wherein the spool mandrel is rotatable with respect to the connector sub; and an intermediate sub disposed between the connector sub and the spool mandrel, wherein the intermediate sub includes an intermediate lug extending outward from an outer surface of the intermediate sub, and wherein contact between the intermediate lug, the connector lug, and the mandrel lug bounds rotational movement of the spool mandrel with respect to the connector sub between a first angular position and a second angular position.

(50) Statement 2. The apparatus of statement 1, wherein a first side of the connector lug is disposed proximate a first side of the intermediate lug and a first side of the mandrel lug is disposed proximate a second side of the intermediate lug in the first angular position of the spool mandrel.

(51) Statement 3. The apparatus of statement 1 or statement 2, wherein the mandrel lug is configured to rotate away from the second side of the intermediate lug toward the first side of the intermediate lug in response to rotation of the spool mandrel in a first rotational direction, and wherein a second side of the mandrel lug contacts the first side of the intermediate lug to drive the intermediate lug away from the first side of the connector lug toward the second side of the connector lug in response to further rotation of the spool mandrel in the first rotational direction.

(52) Statement 4. The apparatus of any preceding statement, wherein contact between the second side of the mandrel lug with the first side of the intermediate lug and contact between the second side of the intermediate lug and the second side of the connector lug bounds rotational movement of the spool mandrel with respect to the connector sub at the second angular position.

(53) Statement 5. The apparatus of any preceding statement, wherein the connector lug and the mandrel lug are spaced apart axially to form a gap between the connector lug and the mandrel lug.

(54) Statement 6. The apparatus of any preceding statement, wherein the connector lug interfaces with an uphole axial end of the intermediate lug, and wherein the mandrel lug interfaces with a downhole axial end of the intermediate lug.

(55) Statement 7. The apparatus of any preceding statement, wherein the first angular position and the second angular position are between 630 to 720 degrees apart.

(56) Statement 8. The apparatus of any preceding statement, further comprising a retainer sub disposed radially exterior to the connector sub and the spool mandrel, wherein the retainer sub restrains axial movement of the spool mandrel with respect to the connector sub to couple the spool mandrel to the connector sub.

(57) Statement 9. The apparatus of any preceding statement, further comprising a shear pin and a shear mechanism, wherein the shear pin restrains rotational movement of the spool mandrel with respect to the connector sub as the apparatus is run-in-hole, and wherein the shear mechanism is configured to shear the shear pin in response to the apparatus engaging a downhole tool disposed in the wellbore.

(58) Statement 10. The apparatus of any preceding statement, wherein the shear mechanism comprises a sleeve having a shear pin slot and an interface feature configured to engage the downhole tool, wherein the shear pin is disposed in the shear pin slot as the apparatus is run-in-hole, and wherein the sleeve is configured to slide axially to shear the shear pin in response to the interface feature engaging the downhole tool.

(59) Statement 11. The apparatus of any preceding statement, wherein the interface feature comprises a protrusion extending radially outward from the sleeve, wherein the sleeve is configured to slide axially to shear the shear pin in response to the protrusion engaging the downhole tool.

(60) Statement 12. The apparatus of any preceding statement, wherein the interface feature comprises a retractable interface pin, wherein the retractable interface pin is in a radially extended position as the apparatus is run-in-hole, and wherein the sleeve is configured to slide axially to shear the shear pin in response to the retractable interface pin engaging the downhole tool.

(61) Statement 13. The apparatus of any preceding statement, wherein the sleeve of the shear mechanism is slidable from a first axial position to a second axial position in response to the shear pin shearing, wherein the retractable interface pin is configured to retract into a corresponding slot formed in a retainer sub in the second axial position.

(62) Statement 14. The apparatus of any preceding statement, wherein the shear mechanism further comprises a locking mechanism configured to secure the sleeve in a locked position that is axially offset from the first position with the shear pin.

(63) Statement 15. An apparatus, comprising: a connector sub rigidly securable to a conveyance for running the connector sub along a wellbore, the connector sub having an axially extending connector lug; a spool mandrel having an axially extending mandrel lug, wherein the spool mandrel is rotatable with respect to the connector sub; an intermediate sub disposed between the connector sub and the spool mandrel, wherein the intermediate sub includes an intermediate lug extending radially outward from an outer surface of the intermediate sub, and wherein contact between the intermediate lug, the connector lug, and the mandrel lug bounds rotational movement of the spool mandrel with respect to the connector sub between a first angular position and a second angular position; at least one return spring configured to bias the spool mandrel to rotate toward an initial angular position of the spool mandrel with respect to the connector sub; and a control line extending between the connector sub and the spool mandrel, wherein the control line is displaceable to permit rotation of the spool mandrel with respect to the connector sub.

(64) Statement 16. The apparatus of statement 15, wherein the at least one return spring is configured to bias the spool mandrel to rotate toward the first angular position of the spool mandrel with respect to the connector sub.

(65) Statement 17. The apparatus of statement 15 or statement 16, wherein the at least one return spring comprises a first return spring and a second return spring, wherein a first end of the first return spring is attached to the spool mandrel and a second end of the first return spring is attached to the intermediate sub, and wherein a first end of the second return spring is attached to the intermediate sub and a second end of the second return spring is attached to the connector sub.

(66) Statement 18. The apparatus of any of statements 15-17, wherein the at least one return spring comprises a compression spring, a tension spring, a torsion spring, or some combination thereof.

(67) Statement 19. An apparatus, comprising: a connector sub rigidly securable to a conveyance for running the connector sub along a wellbore, the connector sub having an axially extending connector lug; a spool mandrel having an axially extending mandrel lug, wherein the spool mandrel is rotatable with respect to the connector sub; an intermediate sub disposed between the connector sub and the spool mandrel, wherein the intermediate sub includes an intermediate lug extending radially outward from an outer surface of the intermediate sub, and wherein contact between the intermediate lug, the connector lug, and the mandrel lug bounds rotational movement of the spool mandrel with respect to the connector sub between a first angular position and a second angular position; a return spring configured to bias the spool mandrel to rotate toward an initial angular position of the spool mandrel with respect to the connector sub; and a control line extending between the connector sub and the spool mandrel, wherein the control line is displaceable to permit rotation of the spool mandrel with respect to the connector sub; a retainer sub disposed radially exterior to the connector sub and the spool mandrel, wherein the retainer sub restrains axial

movement of the spool mandrel with respect to the connector sub; a shear pin for restraining rotational movement of the spool mandrel with respect to the connector sub as the apparatus is run-in-hole; and a shear mechanism for shearing the shear pin in response to the apparatus engaging a downhole tool.

(68) Statement 20. The apparatus of statement 19, wherein the shear mechanism comprises an interface surface, wherein the shear mechanism is actuatable in response to the interface surface contacting a corresponding surface of the downhole tool.

(69) For the sake of brevity, only certain ranges are explicitly disclosed herein. However, ranges from any lower limit may be combined with any upper limit to recite a range not explicitly recited, as well as, ranges from any lower limit may be combined with any other lower limit to recite a range not explicitly recited, in the same way, ranges from any upper limit may be combined with any other upper limit to recite a range not explicitly recited. Additionally, whenever a numerical range with a lower limit and an upper limit is disclosed, any number and any included range falling within the range are specifically disclosed. In particular, every range of values (of the form, “from about a to about b,” or, equivalently, “from approximately a to b,” or, equivalently, “from approximately a-b”) disclosed herein is to be understood to set forth every number and range encompassed within the broader range of values even if not explicitly recited. Thus, every point or individual value may serve as its own lower or upper limit combined with any other point or individual value or any other lower or upper limit, to recite a range not explicitly recited.

(70) Therefore, the present embodiments are well adapted to attain the ends and advantages mentioned as well as those that are inherent therein. The particular embodiments disclosed above are illustrative only, as the present embodiments may be modified and practiced in different but equivalent manners apparent to those skilled in the art having the benefit of the teachings herein. Although individual embodiments are discussed, all combinations of each embodiment are contemplated and covered by the disclosure. Furthermore, no limitations are intended to the details of construction or design herein shown, other than as described in the claims below. Also, the terms in the claims have their plain, ordinary meaning unless otherwise explicitly and clearly defined by the patentee. It is therefore evident that the particular illustrative embodiments disclosed above may be altered or modified and all such variations are considered within the scope and spirit of the present disclosure.

Claims

1. An apparatus, comprising: a connector sub rigidly securable to a conveyance for running the connector sub along a wellbore, the connector sub having a connector lug; a spool mandrel having a mandrel lug, wherein the spool mandrel is rotatable with respect to the connector sub; and an intermediate sub disposed between the connector sub and the spool mandrel, wherein the intermediate sub includes an intermediate lug extending outward from an outer surface of the intermediate sub, and wherein contact between the intermediate lug, the connector lug, and the mandrel lug bounds rotational movement of the spool mandrel with respect to the connector sub between a first angular position and a second angular position.
2. The apparatus of claim 1, wherein a first side of the connector lug is disposed proximate a first side of the intermediate lug and a first side of the mandrel lug is disposed proximate a second side of the intermediate lug in the first angular position of the spool mandrel.
3. The apparatus of claim 2, wherein the mandrel lug is configured to rotate away from the second side of the intermediate lug toward the first side of the intermediate lug in response to rotation of the spool mandrel in a first rotational direction, and wherein a second side of the mandrel lug contacts the first side of the intermediate lug to drive the intermediate lug away from the first side of the connector lug toward the second side of the connector lug in response to further rotation of the spool mandrel in the first rotational direction.

4. The apparatus of claim 3, wherein contact between the second side of the mandrel lug with the first side of the intermediate lug and contact between the second side of the intermediate lug and the second side of the connector lug bounds rotational movement of the spool mandrel with respect to the connector sub at the second angular position.
5. The apparatus of claim 1, wherein the connector lug and the mandrel lug are spaced apart axially to form a gap between the connector lug and the mandrel lug.
6. The apparatus of claim 1, wherein the connector lug interfaces with an uphole axial end of the intermediate lug, and wherein the mandrel lug interfaces with a downhole axial end of the intermediate lug.
7. The apparatus of claim 1, wherein the first angular position and the second angular position are between 630 to 720 degrees apart.
8. The apparatus of claim 1, further comprising a retainer sub disposed radially exterior to the connector sub and the spool mandrel, wherein the retainer sub restrains axial movement of the spool mandrel with respect to the connector sub to couple the spool mandrel to the connector sub.
9. The apparatus of claim 1, further comprising a shear pin and a shear mechanism, wherein the shear pin restrains rotational movement of the spool mandrel with respect to the connector sub as the apparatus is run-in-hole, and wherein the shear mechanism is configured to shear the shear pin in response to the apparatus engaging a downhole tool disposed in the wellbore.
10. The apparatus of claim 9, wherein the shear mechanism comprises a sleeve having a shear pin slot and an interface feature configured to engage the downhole tool, wherein the shear pin is disposed in the shear pin slot as the apparatus is run-in-hole, and wherein the sleeve is configured to slide axially to shear the shear pin in response to the interface feature engaging the downhole tool.
11. The apparatus of claim 10, wherein the interface feature comprises a protrusion extending radially outward from the sleeve, wherein the sleeve is configured to slide axially to shear the shear pin in response to the protrusion engaging the downhole tool.
12. The apparatus of claim 10, wherein the interface feature comprises a retractable interface pin, wherein the retractable interface pin is in a radially extended position as the apparatus is run-in-hole, and wherein the sleeve is configured to slide axially to shear the shear pin in response to the retractable interface pin engaging the downhole tool.
13. The apparatus of claim 12, wherein the sleeve of the shear mechanism is slidable from a first axial position to a second axial position in response to the shear pin shearing, wherein the retractable interface pin is configured to retract into a corresponding slot formed in a retainer sub in the second axial position.
14. The apparatus of claim 10, wherein the shear mechanism further comprises a locking mechanism configured to secure the sleeve in a locked position that is axially offset from the first position with the shear pin.
15. An apparatus, comprising: a connector sub rigidly securable to a conveyance for running the connector sub along a wellbore, the connector sub having an axially extending connector lug; a spool mandrel having an axially extending mandrel lug, wherein the spool mandrel is rotatable with respect to the connector sub; an intermediate sub disposed between the connector sub and the spool mandrel, wherein the intermediate sub includes an intermediate lug extending radially outward from an outer surface of the intermediate sub, and wherein contact between the intermediate lug, the connector lug, and the mandrel lug bounds rotational movement of the spool mandrel with respect to the connector sub between a first angular position and a second angular position; at least one return spring configured to bias the spool mandrel to rotate toward an initial angular position of the spool mandrel with respect to the connector sub; and a control line extending between the connector sub and the spool mandrel, wherein the control line is displaceable to permit rotation of the spool mandrel with respect to the connector sub.
16. The apparatus of claim 15, wherein the at least one return spring is configured to bias the spool

mandrel to rotate toward the first angular position of the spool mandrel with respect to the connector sub.

17. The apparatus of claim 15, wherein the at least one return spring comprises a first return spring and a second return spring, wherein a first end of the first return spring is attached to the spool mandrel and a second end of the first return spring is attached to the intermediate sub, and wherein and a first end of the second return spring is attached to the intermediate sub and a second end of the second return spring is attached to the connector sub.

18. The apparatus of claim 15, wherein the at least one return spring comprises a compression spring, a tension spring, a torsion spring, or some combination thereof.

19. An apparatus, comprising: a connector sub rigidly securable to a conveyance for running the connector sub along a wellbore, the connector sub having an axially extending connector lug; a spool mandrel having an axially extending mandrel lug, wherein the spool mandrel is rotatable with respect to the connector sub; an intermediate sub disposed between the connector sub and the spool mandrel, wherein the intermediate sub includes an intermediate lug extending radially outward from an outer surface of the intermediate sub, and wherein contact between the intermediate lug, the connector lug, and the mandrel lug bounds rotational movement of the spool mandrel with respect to the connector sub between a first angular position and a second angular position; a return spring configured to bias the spool mandrel to rotate toward an initial angular position of the spool mandrel with respect to the connector sub; and a control line extending between the connector sub and the spool mandrel, wherein the control line is displaceable to permit rotation of the spool mandrel with respect to the connector sub; a retainer sub disposed radially exterior to the connector sub and the spool mandrel, wherein the retainer sub restrains axial movement of the spool mandrel with respect to the connector sub; a shear pin for restraining rotational movement of the spool mandrel with respect to the connector sub as the apparatus is run-in-hole; and a shear mechanism for shearing the shear pin in response to the apparatus engaging a downhole tool.

20. The apparatus of claim 19, wherein the shear mechanism comprises an interface surface, wherein the shear mechanism is actuatable in response to the interface surface contacting a corresponding surface of the downhole tool.
