

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399726
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Wayne; Ashley Michelle et al.

Interface to configure media content

Abstract

Embodiments of the present disclosure relate to systems for performing operations that include: receiving a first media object, such as a digital representation of a logo (e.g., JPEG, TIFF, PNG, BMP, etc.), wherein the first media object comprises at least color data that defines a set of colors of the media object; detecting the set of colors of the first media object responsive to receiving the first media object; selecting a portion of the set of colors of the first media object; and generating an interface to configure a second media object, the interface comprising a display of one or more configuration options that include a color selection, the color selection comprising a presentation of the portion of the set of colors.

Inventors: Wayne; Ashley Michelle (Los Angeles, CA), Gardelli; Giovanni (Los Angeles, CA)

Applicant: Snap Inc. (Santa Monica, CA)

Family ID: 1000008778454

Assignee: Snap Inc. (Santa Monica, CA)

Appl. No.: 18/361764

Filed: July 28, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230376324 A1	Nov. 23, 2023

Related U.S. Application Data

continuation parent-doc US 17948972 20220920 US 11782740 child-doc US 18361764
continuation parent-doc US 17329469 20210525 US 11520607 20221206 child-doc US 17948972
continuation parent-doc US 16206742 20181130 US 11099862 20210824 child-doc US 17329469

Publication Classification

Int. Cl.: **G06F3/0482** (20130101); **G06F3/04817** (20220101); **G06F3/04842** (20220101); **G06F3/04845** (20220101); **G06F9/451** (20180101); **G06F40/109** (20200101); **G06T7/90** (20170101); **H04W4/021** (20180101)

U.S. Cl.:

CPC **G06F9/451** (20180201); **G06F3/04817** (20130101); **G06F3/0482** (20130101); **G06F3/04842** (20130101); **G06F3/04845** (20130101); **G06F40/109** (20200101); **G06T7/90** (20170101); **H04W4/021** (20130101);

Field of Classification Search

CPC: G06F (3/048-05)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7146179	12/2005	Parulski	455/566	H04N 1/00151
7675647	12/2009	Tsue	358/1.9	H04N 1/00196
8866841	12/2013	Distler	345/619	G06T 11/60
8990288	12/2014	Hendrey	709/203	G06F 16/29
9501724	12/2015	Yang	N/A	G06T 3/40
10163173	12/2017	McKinley	N/A	G06F 3/0484
10217488	12/2018	Huang	N/A	H04N 9/8205
10382373	12/2018	Yang	N/A	G06F 16/5854
11099862	12/2020	Wayne et al.	N/A	N/A
11520607	12/2021	Wayne et al.	N/A	N/A
11782740	12/2022	Wayne et al.	N/A	N/A
2002/0080153	12/2001	Zhao	715/700	H04N 1/644
2003/0174174	12/2002	Fitzpatrick	715/809	G06F 3/0482
2004/0117358	12/2003	von Kaenel	N/A	G06Q 40/08
2005/0268227	12/2004	Carlson	715/223	G06F 40/186
2007/0036371	12/2006	Buil	381/312	G06F 16/5838
2007/0061714	12/2006	Stuple	715/248	G06F 40/166
2007/0242284	12/2006	Schalkwijk	358/1.6	H04N 1/00145
2008/0138030	12/2007	Bryan	348/E5.103	H04N 21/4221
2008/0256136	12/2007	Holland	715/764	G11B 27/034
2009/0022424	12/2008	Chen	358/1.18	H04N 1/0045
2009/0106680	12/2008	Brownholtz	715/769	G06F 3/0486
2009/0309894	12/2008	Lam	358/1.18	G06F 40/103
2010/0077327	12/2009	Pulsipher	715/764	G06Q 10/10
2010/0107062	12/2009	Bacus	715/781	G06F 40/109
2010/0182618	12/2009	Akiyama	358/1.9	H04N 1/40
2010/0246950	12/2009	De Kruif	382/167	H04N 1/6005
2010/0275161	12/2009	DiCamillo	715/810	G06F 40/103
2011/0055765	12/2010	Neubrand	713/400	H04N 1/32122

2011/0306304	12/2010	Forutanpour	455/67.11	H04M 1/72457
2012/0206655	12/2011	Pettigrew	348/E9.037	G09G 5/02
2012/0225672	12/2011	Tholkes	455/456.3	H04W 4/02
2012/0299942	12/2011	Braun	345/589	G06T 11/001
2013/0019204	12/2012	Kotler	715/833	G06F 3/0481
2013/0091026	12/2012	Deng	705/26.5	G06Q 30/06
2013/0305130	12/2012	Slatter	715/202	G06F 40/106
2013/0335335	12/2012	Neelakant	345/173	G06F 3/0486
2013/0339868	12/2012	Sharpe	715/739	G06F 3/0484
2014/0013212	12/2013	Von Haden	715/243	G06F 40/186
2014/0096041	12/2013	Gowen	715/753	G06Q 30/0621
2014/0162243	12/2013	Lamkin	434/365	G09B 5/08
2014/0215362	12/2013	Barros	715/763	G06F 16/245
2014/0236468	12/2013	Dave	701/300	H04W 4/029
2014/0280258	12/2013	Nicholas	707/756	G06F 16/258
2014/0304582	12/2013	Bills	715/224	H04W 4/029
2014/0379317	12/2013	Sanden	703/10	G06T 3/40
2014/0380229	12/2013	Volodin	715/780	G06F 3/04842
2015/0019595	12/2014	Kritt	707/809	G06F 16/258
2015/0149317	12/2014	Marschke	705/26.7	G06Q 30/0621
2015/0149895	12/2014	Furman	715/269	G06F 40/109
2015/0153927	12/2014	Kashibuchi	345/173	G06F 3/0488
2015/0301989	12/2014	Xin	715/256	G06F 16/9577
2015/0363380	12/2014	McNaught	715/235	G06F 16/986
2016/0026612	12/2015	Zhang	715/234	G06T 7/90
2016/0133030	12/2015	Manuja	345/594	G06F 3/04847
2016/0246491	12/2015	Wu	N/A	G06F 3/04847
2016/0364633	12/2015	Yang	N/A	G06V 30/245
2017/0004113	12/2016	Gore	N/A	G06F 40/109
2017/0039353	12/2016	James	N/A	G06F 21/10
2017/0132822	12/2016	Marschke	N/A	G06Q 30/0631
2017/0192651	12/2016	Yang	N/A	G06F 3/04845
2017/0206003	12/2016	Paek	N/A	G06F 3/0485
2017/0255597	12/2016	Sinn	N/A	G06F 3/04842
2017/0358274	12/2016	Garcia	N/A	G09G 5/14
2017/0364481	12/2016	Scapa	N/A	H04L 51/48
2018/0136827	12/2017	Bae	N/A	G06F 3/04817
2018/0176730	12/2017	Szymczyk	N/A	H04W 4/022
2018/0246983	12/2017	Rathod	N/A	G06F 16/972
2018/0350144	12/2017	Rathod	N/A	G06Q 20/3224
2019/0020983	12/2018	Thompson	N/A	H04W 4/021
2019/0090085	12/2018	Masterson	N/A	H04M 1/72457
2019/0102060	12/2018	Ishida	N/A	G06F 3/0483
2019/0143213	12/2018	Pastorino	463/31	A63F 13/46
2019/0243531	12/2018	Chou	N/A	G06F 3/0482
2019/0281410	12/2018	Ahmed	N/A	H04L 67/52
2020/0151442	12/2019	Singh	N/A	G06V 10/82
2021/0279082	12/2020	Wayne et al.	N/A	N/A
2023/0018594	12/2022	Wayne et al.	N/A	N/A

OTHER PUBLICATIONS

“U.S. Appl. No. 16/206,742, Final Office Action mailed Mar. 5, 2020”, 17 pgs. cited by applicant
“U.S. Appl. No. 16/206,742, Final Office Action mailed Oct. 19, 2020”, 19 pgs. cited by applicant
“U.S. Appl. No. 16/206,742, Non Final Office Action mailed Jan. 1, 2021”, 20 pgs. cited by applicant
“U.S. Appl. No. 16/206,742, Non Final Office Action mailed May 22, 2020”, 18 pgs. cited by applicant
“U.S. Appl. No. 16/206,742, Non Final Office Action mailed Nov. 15, 2019”, 16 pgs. cited by applicant
“U.S. Appl. No. 16/206,742, Notice of Allowance mailed Apr. 21, 2021”, 13 pgs. cited by applicant
“U.S. Appl. No. 16/206,742, Response filed Feb. 18, 2020 to Non Final Office Action mailed Nov. 15, 2019”, 10 pgs. cited by applicant
“U.S. Appl. No. 16/206,742, Response filed Mar. 25, 2021 to Non Final Office Action mailed Jan. 1, 2021”, 10 pgs. cited by applicant
“U.S. Appl. No. 16/206,742, Response filed May 5, 2020 to Final Office Action mailed Mar. 5, 2020”, 11 pgs. cited by applicant
“U.S. Appl. No. 16/206,742, Response filed Aug. 24, 2020 to Non Final Office Action mailed May 22, 2020”, 10 pgs. cited by applicant
“U.S. Appl. No. 16/206,742, Response filed Dec. 18, 2020 to Final Office Action mailed Oct. 19, 2020”, 11 pgs. cited by applicant
“U.S. Appl. No. 17/329,469, Final Office Action mailed Apr. 8, 2022”, 13 pgs. cited by applicant
“U.S. Appl. No. 17/329,469, Non Final Office Action mailed May 17, 2022”, 16 pgs. cited by applicant
“U.S. Appl. No. 17/329,469, Non Final Office Action mailed Sep. 22, 2021”, 14 pgs. cited by applicant
“U.S. Appl. No. 17/329,469, Notice of Allowance mailed Jul. 21, 2022”, 9 pgs. cited by applicant
“U.S. Appl. No. 17/329,469, Response filed May 6, 2022 to Final Office Action mailed Apr. 8, 2022”, 9 pgs. cited by applicant
“U.S. Appl. No. 17/329,469, Response filed Jun. 9, 2022 to Non Final Office Action mailed May 17, 2022”, 9 pgs. cited by applicant
“U.S. Appl. No. 17/329,469, Response filed Nov. 18, 2021 to Non Final Office Action mailed Sep. 22, 2021”, 9 pgs. cited by applicant
“U.S. Appl. No. 17/948,972, Final Office Action mailed Apr. 4, 2023”, 12 pgs. cited by applicant
“U.S. Appl. No. 17/948,972, Non Final Office Action mailed Jan. 17, 2023”, 14 pgs. cited by applicant
“U.S. Appl. No. 17/948,972, Notice of Allowance mailed Jun. 2, 2023”, 17 pgs. cited by applicant
“U.S. Appl. No. 17/948,972, Response filed Jan. 19, 2023 to Non Final Office Action mailed Jan. 17, 2023”, 9 pgs. cited by applicant
“U.S. Appl. No. 17/948,972, Response filed May 4, 2023 to Final Office Action mailed Apr. 4, 2023”, 9 pgs. cited by applicant
Biersdorfer, J D, “Locating a Lost Windows Device”, [Online] Retrieved from the internet: <<https://www.nytimes.com/2016/05/25/technology/personaltech/locating-a-lost-windows-device.html>>, (2016). cited by applicant

Primary Examiner: Rodriguez; Daniel

Attorney, Agent or Firm: Schwegman Lundberg & Woessner, P.A.

Background/Summary

PRIORITY CLAIM (1) This application is a continuation of and claims the benefit of priority of U.S. patent application Ser. No. 17/948,972, filed Sep. 20, 2022, which application is a continuation of and claims the benefit of priority of U.S. patent application Ser. No. 17/329,469, filed May 25, 2021, now issued as U.S. Pat. No. 11,520,607, which is a continuation of and claims the benefit of priority of U.S. patent application Ser. No. 16/206,742, filed Nov. 30, 2018, now issued as U.S. Pat. No. 11,099,862, which are hereby incorporated by reference herein in their entireties.

TECHNICAL FIELD

(1) Embodiments of the present disclosure relate generally to graphical user interfaces (GUI), and more particularly, to systems for generating and causing display of GUIs.

BACKGROUND

(2) Media content is typically created with the goal of having the content viewed or otherwise received by a target audience. The target audience could for example be a specific subset of people, defined by a particular attribute, or could include be all people at a specific location. Various systems currently exist to enable advertisers to create and distribute such content. While these systems do provide the functionality necessary to create such media content, the amount of user interaction required varies greatly. For example, some systems may provide advanced graphic design interfaces that require a significant amount of user skill and training, while others are simplified for ease of use at the compromise of functionality.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

(1) To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced.

(2) FIG. 1 is a block diagram showing an example messaging system for exchanging data (e.g., messages and associated content) over a network in accordance with some embodiments, wherein the messaging system includes a media configuration system.

(3) FIG. 2 is block diagram illustrating further details regarding a messaging system, according to example embodiments.

(4) FIG. 3 is a block diagram illustrating various modules of a media configuration system, according to certain example embodiments.

(5) FIG. 4 is a flowchart illustrating a method for generating a graphical user interface to configure media content, according to certain example embodiments.

(6) FIG. 5 is a flowchart illustrating a method for generating a graphical user interface to configure media content, according to certain example embodiments.

(7) FIG. 6 is a flowchart illustrating a method for generating a graphical user interface to configure media content, according to certain example embodiments.

(8) FIG. 7 is a flowchart illustrating a method for generating a graphical user interface to configure media content, according to certain example embodiments.

(9) FIG. 8 is a flowchart illustrating a method for generating a graphical user interface to configure media content, according to certain example embodiments.

(10) FIG. 9 is an interface diagram depicting a graphical user interface to configure media content, according to certain example embodiments.

(11) FIG. 10 is an interface diagram depicting a graphical user interface to configure media content, according to certain example embodiments.

(12) FIG. 11 is a block diagram illustrating a representative software architecture, which may be used in conjunction with various hardware architectures herein described and used to implement various embodiments.

(13) FIG. 12 is a block diagram illustrating components of a machine, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein.

DETAILED DESCRIPTION

(14) Advertisers often need to create brand-specific media content to distribute to a population of users. Existing systems in place for creating such content requires significant user involvement. For example, a graphic designer may need to create a customized logo based on colors identified by an advertiser, and then prepare drafts to be reviewed and selected by the advertiser. As a result of custom nature of the media content, the process of creating the media content is both time consuming, and expensive. For example, current systems for creating such content (e.g., Adobe Illustrator), require a high level of user skill and advertiser involvement to provide inputs identifying colors, patterns, fonts, as well as overall design themes. A simplified system to enable an advertiser to quickly prepare and review media content for immediate distribution would therefore be beneficial.

(15) The system disclosed below provides a method to generate and review media content by performing operations for receiving a first media object, wherein the first media object may for example include a logo or design uploaded by an advertiser, identify one or more colors that are included in the logo, select a portion of the one or more colors, and generate and cause display of a media content configuration interface to configure second media object, wherein the media content configuration interface comprises a display of one or more configuration options, wherein the configuration options are based on (among other things) the portion of the one or more colors detected in the first media object.

(16) For example, a user (e.g., an advertiser) may upload a digital logo. In response to receiving the digital logo, a media configuration system detects colors in the logo, and ranks the colors of the logo based on their corresponding prominence in the logo. In some embodiments, to rank the colors of the logo the media configuration system determines pixel counts of each color, and then ranks each color based on their corresponding pixel counts. The media configuration system determines the top colors based on the ranking (e.g., top 3, top 10%), and presents the top colors as selectable options in the interface.

(17) In some embodiments, the first media object uploaded to the media configuration system includes text data that identifies a font associated with the first media object. Responsive to receiving the first media object, the media configuration system identifies the font of the first media object, and causes display of a set of font options in the interface, wherein the font options are presented as a list that includes the font of the first media object.

(18) In some embodiments, the media configuration system may cause display of a set of content templates, wherein each content template comprises a set of user interface elements that may be customized and displayed on the fly based on selections of the user. For example, responsive to receive a selection of a color or font, the media configuration system may update the display of the set of content templates in real-time. The user may review the templates before making a selection of a template for use in creating media content.

(19) Therefore, a system to generate and cause display of an interface to configure media content is described. Embodiments of the present disclosure relate to systems for performing operations that include: receiving a first media object, such as a digital representation of a logo (e.g., JPEG, TIFF, PNG, BMP, etc.), wherein the first media object comprises at least color data that defines a set of colors of the media object; detecting the set of colors of the first media object responsive to receiving the first media object; selecting a portion of the set of colors of the first media object; and generating an interface to configure a second media object, the interface comprising a display of

one or more configuration options that include a color selection, the color selection comprising a presentation of the portion of the set of colors.

(20) FIG. 1 is a block diagram showing an example messaging system **100** for exchanging data (e.g., messages and associated content) over a network. The messaging system **100** includes multiple client devices **102**, each of which hosts a number of applications including a messaging client application **104**. Each messaging client application **104** is communicatively coupled to other instances of the messaging client application **104** and a messaging server system **108** via a network **106** (e.g., the Internet).

(21) Accordingly, each messaging client application **104** is able to communicate and exchange data with another messaging client application **104** and with the messaging server system **108** via the network **106**. The data exchanged between messaging client applications **104**, and between a messaging client application **104** and the messaging server system **108**, includes functions (e.g., commands to invoke functions) as well as payload data (e.g., text, audio, video or other multimedia data).

(22) The messaging server system **108** provides server-side functionality via the network **106** to a particular messaging client application **104**. While certain functions of the messaging system **100** are described herein as being performed by either a messaging client application **104** or by the messaging server system **108**, it will be appreciated that the location of certain functionality either within the messaging client application **104** or the messaging server system **108** is a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the messaging server system **108**, but to later migrate this technology and functionality to the messaging client application **104** where a client device **102** has a sufficient processing capacity.

(23) The messaging server system **108** supports various services and operations that are provided to the messaging client application **104**. Such operations include transmitting data to, receiving data from, and processing data generated by the messaging client application **104**. In some embodiments, this data includes, message content, client device information, geolocation information, media annotation and overlays, message content persistence conditions, social network information, and live event information, as examples. In other embodiments, other data is used. Data exchanges within the messaging system **100** are invoked and controlled through functions available via GUIs of the messaging client application **104**.

(24) Turning now specifically to the messaging server system **108**, an Application Program Interface (API) server **110** is coupled to, and provides a programmatic interface to, an application server **112**. The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data associated with messages processed by the application server **112**.

(25) Dealing specifically with the Application Program Interface (API) server **110**, this server receives and transmits message data (e.g., commands and message payloads) between the client device **102** and the application server **112**. Specifically, the Application Program Interface (API) server **110** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the messaging client application **104** in order to invoke functionality of the application server **112**. The Application Program Interface (API) server **110** exposes various functions supported by the application server **112**, including account registration, login functionality, the sending of messages, via the application server **112**, from a particular messaging client application **104** to another messaging client application **104**, the sending of media files (e.g., images or video) from a messaging client application **104** to the messaging server application **114**, and for possible access by another messaging client application **104**, the setting of a collection of media data (e.g., story), the retrieval of a list of friends of a user of a client device **102**, the retrieval of such collections, the retrieval of messages and content, the adding and deletion of friends to a social graph, the location of friends within a social graph, opening and application event (e.g., relating to the messaging

client application **104**).

(26) The application server **112** hosts a number of applications and subsystems, including a messaging server application **114**, an image processing system **116**, a social network system **122**, and a media configuration system **124**. The messaging server application **114** implements a number of message processing technologies and functions, particularly related to the aggregation and other processing of content (e.g., textual and multimedia content) included in messages received from multiple instances of the messaging client application **104**. As will be described in further detail, the text and media content from multiple sources may be aggregated into collections of content (e.g., called stories, galleries, or collections). These collections are then made available, by the messaging server application **114**, to the messaging client application **104**. Other processor and memory intensive processing of data may also be performed server-side by the messaging server application **114**, in view of the hardware requirements for such processing.

(27) The application server **112** also includes an image processing system **116** that is dedicated to performing various image processing operations, typically with respect to images or video received within the payload of a message at the messaging server application **114**.

(28) The social network system **122** supports various social networking functions services, and makes these functions and services available to the messaging server application **114**. To this end, the social network system **122** maintains and accesses an entity graph **304** within the database **120**. Examples of functions and services supported by the social network system **122** include the identification of other users of the messaging system **100** with which a particular user has relationships or is “following,” and also the identification of other entities and interests of a particular user.

(29) The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data associated with messages processed by the messaging server application **114**.

(30) FIG. 2 is block diagram illustrating further details regarding the messaging system **100**, according to example embodiments. Specifically, the messaging system **100** is shown to comprise the messaging client application **104** and the application server **112**, which in turn embody a number of some subsystems, namely an ephemeral timer system **202**, a collection management system **204** and an annotation system **206**.

(31) The ephemeral timer system **202** is responsible for enforcing the temporary access to content permitted by the messaging client application **104** and the messaging server application **114**. To this end, the ephemeral timer system **202** incorporates a number of timers that, based on duration and display parameters associated with a message, collection of messages, or graphical element, selectively display and enable access to messages and associated content via the messaging client application **104**. Further details regarding the operation of the ephemeral timer system **202** are provided below.

(32) The collection management system **204** is responsible for managing collections of media (e.g., a media collection that includes collections of text, image video and audio data). In some examples, a collection of content (e.g., messages, including images, video, text and audio) may be organized into an “event gallery” or an “event story.” Such a collection may be made available for a specified time period, such as the duration of an event to which the content relates. For example, content relating to a music concert may be made available as a “story” for the duration of that music concert. The collection management system **204** may also be responsible for publishing an icon that provides notification of the existence of a particular collection to the user interface of the messaging client application **104**.

(33) The collection management system **204** furthermore includes a curation interface **208** that allows a collection manager to manage and curate a particular collection of content. For example, the curation interface **208** enables an event organizer to curate a collection of content relating to a specific event (e.g., delete inappropriate content or redundant messages). Additionally, the

collection management system **204** employs machine vision (or image recognition technology) and content rules to automatically curate a content collection. In certain embodiments, compensation may be paid to a user for inclusion of user generated content into a collection. In such cases, the curation interface **208** operates to automatically make payments to such users for the use of their content.

(34) The annotation system **206** provides various functions that enable a user to annotate or otherwise modify or edit media content associated with a message. For example, the annotation system **206** provides functions related to the generation and publishing of media overlays for messages processed by the messaging system **100**. The annotation system **206** operatively supplies a media overlay to the messaging client application **104** based on a geolocation of the client device **102**. In another example, the annotation system **206** operatively supplies a media overlay to the messaging client application **104** based on other information, such as, social network information of the user of the client device **102**. A media overlay may include audio and visual content and visual effects, as well as augmented reality overlays. Examples of audio and visual content include pictures, texts, logos, animations, and sound effects, as well as animated facial models, image filters, and augmented reality media content. An example of a visual effect includes color overlaying. The audio and visual content or the visual effects can be applied to a media content item (e.g., a photo or video or live stream) at the client device **102**. For example, the media overlay including text that can be overlaid on top of a photograph generated taken by the client device **102**. In another example, the media overlay includes an identification of a location overlay (e.g., Venice beach), a name of a live event, or a name of a merchant overlay (e.g., Beach Coffee House). In another example, the annotation system **206** uses the geolocation of the client device **102** to identify a media overlay that includes the name of a merchant at the geolocation of the client device **102**. The media overlay may include other indicia associated with the merchant. The media overlays may be stored in the database **120** and accessed through the database server **118**.

(35) In one example embodiment, the annotation system **206** provides a user-based publication platform that enables users to select a geolocation on a map, and upload content associated with the selected geolocation. The user may also specify circumstances under which a particular media overlay should be offered to other users. The annotation system **206** generates a media overlay that includes the uploaded content and associates the uploaded content with the selected geolocation.

(36) In another example embodiment, the annotation system **206** provides a merchant-based publication platform that enables merchants to select a particular media overlay associated with a geolocation. For example, the annotation system **206** associates the media overlay of a highest bidding merchant with a corresponding geolocation for a predefined amount of time.

(37) FIG. 3 is a block diagram illustrating components of the media configuration system **124** that configure the media configuration system **124** to generate and cause display of an interface to configure media content, according to some example embodiments. The media configuration system **124** is shown as including a presentation module **302**, a media module **304**, an interface module **306**, and a geo-fence module **308**, all configured to communicate with each other (e.g., via a bus, shared memory, or a switch). Any one or more of these modules may be implemented using one or more processors **310** (e.g., by configuring such one or more processors to perform functions described for that module) and hence may include one or more of the processors **310**.

(38) Any one or more of the modules described may be implemented using hardware alone (e.g., one or more of the processors **310** of a machine) or a combination of hardware and software. For example, any module described of the media configuration system **124** may physically include an arrangement of one or more of the processors **310** (e.g., a subset of or among the one or more processors of the machine) configured to perform the operations described herein for that module. As another example, any module of the media configuration system **124** may include software, hardware, or both, that configure an arrangement of one or more processors **310** (e.g., among the one or more processors of the machine) to perform the operations described herein for that module.

Accordingly, different modules of the media configuration system **124** may include and configure different arrangements of such processors **310** or a single arrangement of such processors **310** at different points in time. Moreover, any two or more modules of the media configuration system **124** may be combined into a single module, and the functions described herein for a single module may be subdivided among multiple modules. Furthermore, according to various example embodiments, modules described herein as being implemented within a single machine, database, or device may be distributed across multiple machines, databases, or devices.

(39) FIG. **4** is a flowchart illustrating a method **400** for generating a graphical user interface to configure media content, according to certain example embodiments. Operations of the method **400** may be performed by the modules described above with respect to FIG. **3**. As shown in FIG. **4**, the method **400** includes one or more operations **402**, **404**, **406**, and **408**.

(40) At operation **402**, the media module **304** receives a first media object that comprises at least color data that defines a set of colors of the media object. The media object may comprise one or more digital media objects that include various image file formats, including but not limited to: JPEG, TIFF, PNG, BPG, BMP, GIF, or Exif. In some embodiments, the first media object includes a logo.

(41) Responsive to receiving the first media object, at operation **404** the media module **304** detects and identifies the set of colors of the first media object. For example, the media module **304** may apply one or more color detection algorithms which identifies pixels in an image that match a specified color or color range.

(42) At operation **406**, the media module **304** selects a portion of the set of colors detected in the first media object. For example, the media module **304** may select the most prominent (based on number of pixels) or top 3 most prominent colors in the first media object.

(43) Responsive to the media module **304** selecting the portion of the set of colors, the interface module **306** generates a graphical user interface (GUI) to configure a second media object, wherein the GUI comprises a display of one or more configuration options that include a color selection, and wherein the color selection comprises a presentation of the portion of the set of colors selected by the media module **304**. GUI **905** of FIG. **9** depicts such an interface.

(44) FIG. **5** is a flowchart illustrating a method **500** for generating a graphical user interface to configure media content, according to certain example embodiments. Operations of the method **500** may be performed by the modules described above with respect to FIG. **3**. As shown in FIG. **5**, the method **500** includes one or more operations **502**, **504**, and **506** that may be performed as a part of (e.g., a subroutine) operation **406** of the method **400**, as depicted in FIG. **4**.

(45) At operation **502**, responsive to the media module **304** detecting the set of colors of the first media object, as in operation **404** of the method **400**, the media module **304** determines pixel counts of each color from among the set of colors that make up the first media object.

(46) At operation **504**, the media module **304** ranks each color among the set of colors based on their corresponding pixel counts, and at operation **506**, selects a portion of the set of colors based on the ranking. For example, the media module **304** may select the top 10% of colors based on pixel count, or the top 3 colors of the first media object based on their corresponding pixel counts.

(47) FIG. **6** is a flowchart illustrating a method **600** for generating a graphical user interface to configure media content, according to certain example embodiments. Operations of the method **600** may be performed by the modules described above with respect to FIG. **3**. As shown in FIG. **6**, the method **600** includes one or more operations **602**, and **604** that may be performed as a part of (e.g., a subroutine) the method **400**, as depicted in FIG. **4**.

(48) Responsive to receiving the first media object, at operation **602** the media module **304** identifies one or more fonts depicted in the first media object. For example, the first media object may include a logo that comprises a display of text in one or more fonts. Responsive to receiving the first media object, the media module **304** applies one or more image recognition techniques. For example, in some embodiments, the media module **304** may apply optical character recognition

techniques, that utilize optical properties of text characters to identify the one or more fonts of the first media object.

(49) At operation **604**, responsive to the media module **304** identifying the one or more fonts of the first media object, the interface module **304** causes display of a text selection menu within the GUI, wherein the text selection menu comprises a list of selectable fonts that include the one or more fonts depicted in the first media object. In some embodiments, the one or more fonts of the first media object may be displayed at a more prominent position in the list of fonts (e.g., the top of the list), or may otherwise be visually distinguished from the other fonts in the list by highlighting, italicizing, bolding, or displaying in a different color.

(50) FIG. 7 is a flowchart illustrating a method **700** for generating a graphical user interface to configure media content, according to certain example embodiments. Operations of the method **700** may be performed by the modules described above with respect to FIG. 3. As shown in FIG. 7, the method **700** includes one or more operations **702**, and **704** that may be performed as a part of the method **400**, as depicted in FIG. 4.

(51) At operation **702**, the interface module **306** receives a selection of a color from among the presentation of the portion of the set of colors. For example, the presentation module **302** may cause display of the interface generated by the interface module **306** at a client device **102**. A user operating the client device **102** may provide one or more inputs selecting a color from among the portion of the set of colors.

(52) At operation **704**, responsive to the interface module **306** receiving the selection of the color from among the portion of the set of colors depicted in the color selection presented in the GUI, the media module **304** configures one or more media objects, including a second media object, based on the selection. For example, the second media object may include a templated media object that comprises a set of graphical elements. Responsive to receiving the selection of the color, the media module **304** configures the one or more media objects including the second media object based on the selection.

(53) FIG. 8 is a flowchart illustrating a method **800** for generating a graphical user interface to configure media content, according to certain example embodiments. Operations of the method **800** may be performed by the modules described above with respect to FIG. 3. As shown in FIG. 8, the method **800** includes one or more operations **802**, **804**, **806**, and **808** that may be performed as a part of the method **400**, as depicted in FIG. 4.

(54) At operation **802**, the media module **304** determines a location associated with the first media object. For example, responsive to receiving the first media object, the media module **304** may determine the location associated with the first media object based on a user account of a user that uploaded the first media object to the media configuration system **124**, or may prompt the user by causing the presentation module **302** to cause display of a request to identify a location.

(55) At operation **804**, responsive to the media module **304** determining the location associated with the first media object, the interface module **306** cause display of a map image that includes a depiction of the location associated with the first media object. For example, the map image may depict a region that includes the location.

(56) At operation **806**, the interface module **306** receives a user input selecting an area within the region depicted in the map image. For example, a user may draw a closed shape on the map image that defines an area within the map image, or in further embodiments may provide an input that defines a radius of a circle with the location associated with the first media item as the center of the circle. At operation **808**, the geo-fence module **308** assigns the second media object to a geo-fence that encompasses the area defined by the input.

(57) FIG. 9 is a diagram **900** illustrating an interface **920** to configure media content, according to certain example embodiments. As seen in the diagram **900**, a user may provide an input via a cursor **915** to upload a logo **905** (e.g., a first media object) into the interface **920**, wherein the logo **905** comprises a set of colors and text data that define a font of the logo **905**.

(58) In some embodiments, and as discussed in the method **800** of FIG. **8**, a user may associate a location with media content. In response to determining a location of the media content, the media configuration system **124** may cause display of a map image **910** that depicts a region that includes the location associated with the media content. A user may provide one or more inputs into the map image **910** that identify an area within the region in order to assign media content to one or more geo-fences. For example, the user may draw a closed shape within the map image **910**, or may provide an input selecting a point and defining a radius.

(59) In some embodiments, responsive to receiving the logo **905** through the interface **920**, the media configuration system generates and causes display of the interface **1035**, as depicted in FIG. **10**.

(60) FIG. **9** is a diagram **1000** illustrating an interface **1035** to configure media content, according to certain example embodiments. As seen in the diagram **1000**, the media configuration system **124** may receive a logo **905** via a user input, and in response perform the various operations of the methods **400**, **500**, and **600**, as depicted in FIGS. **4**, **5**, and **6**, in order to configure the interface **1035**.

(61) Responsive to receiving the logo **905**, the media configuration system **124** detects one or more colors and fonts depicted in the logo **905**, and causes display of interface elements to configure a second media object, based on the one or more colors and fonts. For example, the media configuration system may cause display of the color selection **1005**, wherein the color selection **1005** comprises a display of the one or more colors depicted in the logo **905**, and the font selection **1025**, wherein the font selection **1025** comprises a display of the fonts detected in the logo **905**.

(62) For example, as discussed in the method **400** of FIG. **4**, and the method **600** of FIG. **6**, responsive to detecting the set of colors and fonts depicted in the logo (e.g., the logo **905**), the media configuration system **124** causes display of the color selection **1005**, and font selection **1025**, wherein the color selection **1005** comprises the portion of the set of colors depicted in the logo **905**, and the font selection **1025** comprises a list of the fonts detected in the logo **905**. While the color selection **1005** is depicted as being two colors in FIG. **10**, and similarly the font selection **1025** depicts one font, the media configuration system **124** is not limited to such embodiments. The number of colors and fonts displayed within the interface **1035** may vary based on attributes of the logo **905** itself, such as number of colors and fonts present in the logo **905**. For example, upon detecting **10** color in the logo **905**, the media configuration system **124** may rank the **10** colors, and display all **10** in a sort order based on the ranking, or may display a portion of the **10** colors based on the ranking.

(63) In some embodiments, the media configuration system **124** causes display of a presentation of a set of media templates **1020**, wherein each media template within the presentation of the set of templates **1020** is configured based on the one or more colors and fonts detected in the logo **905**. For example, media template **1030** comprises a display of the logo **905**, and graphical and text elements at positions within the media template **1030**, wherein the positions are based on an associated media layout of the media template **1030**.

(64) In response to receiving a selection of a media template (e.g., media template **1030**) from among the set of media templates **1020**, the media configuration system **124** causes display of the media presentation **1015**, wherein the media presentation **1015** comprises a display of the media template **1030**, overlaid upon an image or other media item selected by the user (e.g., a picture, video, gif).

(65) Software Architecture

(66) FIG. **11** is a block diagram illustrating an example software architecture **1106**, which may be used in conjunction with various hardware architectures herein described. FIG. **11** is a non-limiting example of a software architecture and it will be appreciated that many other architectures may be implemented to facilitate the functionality described herein. The software architecture **1106** may execute on hardware such as the machine **1200** of FIG. **12** that includes, among other things,

processors **1204**, memory **1214**, and I/O components **1218**. A representative hardware layer **1152** is illustrated and can represent, for example, the machine **1100** of FIG. **11**. The representative hardware layer **1152** includes a processing unit **1154** having associated executable instructions **1104**. Executable instructions **1104** represent the executable instructions of the software architecture **1106**, including implementation of the methods, components and so forth described herein. The hardware layer **1152** also includes memory and/or storage modules memory/storage **1156**, which also have executable instructions **1104**. The hardware layer **1152** may also comprise other hardware **1158**.

(67) In the example architecture of FIG. **11**, the software architecture **1106** may be conceptualized as a stack of layers where each layer provides particular functionality. For example, the software architecture **1106** may include layers such as an operating system **1102**, libraries **1120**, applications **1116** and a presentation layer **1114**. Operationally, the applications **1116** and/or other components within the layers may invoke application programming interface (API) API calls **1108** through the software stack and receive a response as in response to the API calls **1108**. The layers illustrated are representative in nature and not all software architectures have all layers. For example, some mobile or special purpose operating systems may not provide a frameworks/middleware **1118**, while others may provide such a layer. Other software architectures may include additional or different layers.

(68) The operating system **1102** may manage hardware resources and provide common services. The operating system **1102** may include, for example, a kernel **1122**, services **1124** and drivers **1126**. The kernel **1122** may act as an abstraction layer between the hardware and the other software layers. For example, the kernel **1122** may be responsible for memory management, processor management (e.g., scheduling), component management, networking, security settings, and so on. The services **1124** may provide other common services for the other software layers. The drivers **1126** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **1126** include display drivers, camera drivers, Bluetooth® drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), Wi-Fi® drivers, audio drivers, power management drivers, and so forth depending on the hardware configuration.

(69) The libraries **1120** provide a common infrastructure that is used by the applications **1116** and/or other components and/or layers. The libraries **1120** provide functionality that allows other software components to perform tasks in an easier fashion than to interface directly with the underlying operating system **1102** functionality (e.g., kernel **1122**, services **1124** and/or drivers **1126**). The libraries **1120** may include system libraries **1144** (e.g., C standard library) that may provide functions such as memory allocation functions, string manipulation functions, mathematical functions, and the like. In addition, the libraries **1120** may include API libraries **1146** such as media libraries (e.g., libraries to support presentation and manipulation of various media format such as MPREG4, H.264, MP3, AAC, AMR, JPG, PNG), graphics libraries (e.g., an OpenGL framework that may be used to render 2D and 3D in a graphic content on a display), database libraries (e.g., SQLite that may provide various relational database functions), web libraries (e.g., WebKit that may provide web browsing functionality), and the like. The libraries **1120** may also include a wide variety of other libraries **1148** to provide many other APIs to the applications **1116** and other software components/modules.

(70) The frameworks/middleware **1118** (also sometimes referred to as middleware) provide a higher-level common infrastructure that may be used by the applications **1116** and/or other software components/modules. For example, the frameworks/middleware **1118** may provide various graphic user interface (GUI) functions, high-level resource management, high-level location services, and so forth. The frameworks/middleware **1118** may provide a broad spectrum of other APIs that may be utilized by the applications **1116** and/or other software components/modules, some of which may be specific to a particular operating system **1102** or platform.

(71) The applications **1116** include built-in applications **1138** and/or third-party applications **1140**. Examples of representative built-in applications **1138** may include, but are not limited to, a contacts application, a browser application, a book reader application, a location application, a media application, a messaging application, and/or a game application. Third-party applications **1140** may include an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform, and may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or other mobile operating systems. The third-party applications **1140** may invoke the API calls **1108** provided by the mobile operating system (such as operating system **1102**) to facilitate functionality described herein.

(72) The applications **1116** may use built in operating system functions (e.g., kernel **1122**, services **1124** and/or drivers **1126**), libraries **1120**, and frameworks/middleware **1118** to create user interfaces to interact with users of the system. Alternatively, or additionally, in some systems interactions with a user may occur through a presentation layer, such as presentation layer **1114**. In these systems, the application/component “logic” can be separated from the aspects of the application/component that interact with a user.

(73) FIG. **12** is a block diagram illustrating components of a machine **1200**, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein. Specifically, FIG. **12** shows a diagrammatic representation of the machine **1200** in the example form of a computer system, within which instructions **1210** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1200** to perform any one or more of the methodologies discussed herein may be executed. As such, the instructions **1210** may be used to implement modules or components described herein. The instructions **1210** transform the general, non-programmed machine **1200** into a particular machine **1200** programmed to carry out the described and illustrated functions in the manner described. In alternative embodiments, the machine **1200** operates as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **1200** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1200** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1210**, sequentially or otherwise, that specify actions to be taken by machine **1200**. Further, while only a single machine **1200** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the instructions **1210** to perform any one or more of the methodologies discussed herein.

(74) The machine **1200** may include processors **1204**, memory memory/storage **1206**, and I/O components **1218**, which may be configured to communicate with each other such as via a bus **1202**. The memory/storage **1206** may include a memory **1214**, such as a main memory, or other memory storage, and a storage unit **1216**, both accessible to the processors **1204** such as via the bus **1202**. The storage unit **1216** and memory **1214** store the instructions **1210** embodying any one or more of the methodologies or functions described herein. The instructions **1210** may also reside, completely or partially, within the memory **1214**, within the storage unit **1216**, within at least one of the processors **1204** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1200**. Accordingly, the memory **1214**, the storage unit **1216**, and the memory of processors **1204** are examples of machine-readable media.

(75) The I/O components **1218** may include a wide variety of components to receive input, provide

output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **1218** that are included in a particular machine **1200** will depend on the type of machine. For example, portable machines such as mobile phones will likely include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **1218** may include many other components that are not shown in FIG. **12**. The I/O components **1218** are grouped according to functionality merely for simplifying the following discussion and the grouping is in no way limiting. In various example embodiments, the I/O components **1218** may include output components **1226** and input components **1228**. The output components **1226** may include visual components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input components **1228** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or other pointing instrument), tactile input components (e.g., a physical button, a touch screen that provides location and/or force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

(76) In further example embodiments, the I/O components **1218** may include biometric components **1230**, motion components **1234**, environmental environment components **1236**, or position components **1238** among a wide array of other components. For example, the biometric components **1230** may include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram based identification), and the like. The motion components **1234** may include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope), and so forth. The environment components **1236** may include, for example, illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometer that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position components **1238** may include location sensor components (e.g., a Global Position system (GPS) receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

(77) Communication may be implemented using a wide variety of technologies. The I/O components **1218** may include communication components **1240** operable to couple the machine **1200** to a network **1232** or devices **1220** via coupling **1222** and coupling **1224** respectively. For example, the communication components **1240** may include a network interface component or other suitable device to interface with the network **1232**. In further examples, communication components **1240** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices **1220** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled

via a Universal Serial Bus (USB)).

(78) Moreover, the communication components **1240** may detect identifiers or include components operable to detect identifiers. For example, the communication components **1240** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **1240**, such as, location via Internet Protocol (IP) geo-location, location via Wi-Fi® signal triangulation, location via detecting a NFC beacon signal that may indicate a particular location, and so forth.

GLOSSARY

(79) “CARRIER SIGNAL” in this context refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible medium to facilitate communication of such instructions. Instructions may be transmitted or received over the network using a transmission medium via a network interface device and using any one of a number of well-known transfer protocols.

(80) “CLIENT DEVICE” in this context refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, portable digital assistants (PDAs), smart phones, tablets, ultra books, netbooks, laptops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, or any other communication device that a user may use to access a network.

(81) “COMMUNICATIONS NETWORK” in this context refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other type of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard setting organizations, other long range protocols, or other data transfer technology.

(82) “EPHEMERAL MESSAGE” in this context refers to a message that is accessible for a time-limited duration. An ephemeral message may be a text, an image, a video and the like. The access time for the ephemeral message may be set by the message sender. Alternatively, the access time may be a default setting or a setting specified by the recipient. Regardless of the setting technique, the message is transitory.

(83) “MACHINE-READABLE MEDIUM” in this context refers to a component, device or other tangible media able to store instructions and data temporarily or permanently and may include, but

is not be limited to, random-access memory (RAM), read-only memory (ROM), buffer memory, flash memory, optical media, magnetic media, cache memory, other types of storage (e.g., Erasable Programmable Read-Only Memory (EEPROM)) and/or any suitable combination thereof. The term “machine-readable medium” should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, or associated caches and servers) able to store instructions. The term “machine-readable medium” shall also be taken to include any medium, or combination of multiple media, that is capable of storing instructions (e.g., code) for execution by a machine, such that the instructions, when executed by one or more processors of the machine, cause the machine to perform any one or more of the methodologies described herein. Accordingly, a “machine-readable medium” refers to a single storage apparatus or device, as well as “cloud-based” storage systems or storage networks that include multiple storage apparatus or devices. The term “machine-readable medium” excludes signals per se.

(84) “COMPONENT” in this context refers to a device, physical entity or logic having boundaries defined by function or subroutine calls, branch points, application program interfaces (APIs), or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. A “hardware component” is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a Field-Programmable Gate Array (FPGA) or an Application Specific Integrated Circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) may be driven by cost and time considerations. Accordingly, the phrase “hardware component” (or “hardware-implemented component”) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. Considering embodiments in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time. Hardware components can provide information

to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In embodiments in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information). The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented component” refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an Application Program Interface (API)). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented components may be distributed across a number of geographic locations.

(85) “PROCESSOR” in this context refers to any circuit or virtual circuit (a physical circuit emulated by logic executing on an actual processor) that manipulates data values according to control signals (e.g., “commands”, “op codes”, “machine code”, etc.) and which produces corresponding output signals that are applied to operate a machine. A processor may, for example, be a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC) or any combination thereof. A processor may further be a multi-core processor having two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously.

(86) “TIMESTAMP” in this context refers to a sequence of characters or encoded information identifying when a certain event occurred, for example giving date and time of day, sometimes accurate to a small fraction of a second.

Claims

1. A method comprising: accessing a media object from a user account that comprises a set of attributes; determining a ranking of the set of attributes; identifying a portion of the set of attributes

of the media object based on the ranking; causing display of a graphical user interface that includes a plurality of media templates, a map image that displays a location of interest, and a presentation of a menu element that includes a set of configuration options based on the portion of the set of attributes in a sort order based on the ranking; receiving a selection of a configuration option from among the set of configuration options; receiving an input that identifies the location of interest within the map image; updating, in real-time, a customization of the plurality of media templates responsive to the selection of the configuration option, each media template among the plurality of media templates including a display of the media object, and assigning the media object that includes the customization to a geo-fence that encompasses the location of interest identified by the input.

2. The method of claim 1, wherein the set of attributes include a set of colors.

3. The method of claim 2, wherein the selecting the portion of the set of attributes includes: determining a pixel count of each color among the set of colors; and selecting the portion of the set of colors based on the pixel count.

4. The method of claim 2, wherein the colors with a larger pixel count are ranked higher than those with a smaller pixel count.

5. A system comprising: a memory; and at least one hardware processor coupled to the memory and comprising instructions that causes the system to perform operations comprising: accessing a media object from a user account that comprises a set of attributes; determining a ranking of the set of attributes; identifying a portion of the set of attributes of the media object based on the ranking; causing display of a graphical user interface that includes a plurality of media templates, a map image that displays a location of interest, and a presentation of a menu element that includes a set of configuration options based on the portion of the set of attributes in a sort order based on the ranking; receiving a selection of a configuration option from among the set of configuration options; receiving an input that identifies the location of interest within the map image; updating, in real-time, a customization of the plurality of media templates responsive to the selection of the configuration option, each media template among the plurality of media templates including a display of the media object; and assigning the media object that includes the customization to a geo-fence that encompasses the location of interest identified by the input.

6. The system of claim 5, wherein the set of attributes include a set of colors.

7. The system of claim 6, wherein the selecting the portion of the set of attributes includes: determining a pixel count of each color among the set of colors; and selecting the portion of the set of colors based on the pixel count.

8. The system of claim 7, wherein the colors with a larger pixel count are ranked higher than those with a smaller pixel count.

9. A non-transitory machine-readable storage medium comprising instructions that, when executed by one or more processors of a machine, cause the machine to perform operations comprising: accessing a media object from a user account that comprises a set of attributes; determining a ranking of the set of attributes; identifying a portion of the set of attributes of the media object based on the ranking; causing display of a graphical user interface that includes a plurality of media templates, a map image that displays a location of interest, and a presentation of a menu element that includes a set of configuration options based on the portion of the set of attributes in a sort order based on the ranking; receiving a selection of a configuration option from among the set of configuration options; receiving an input that identifies the location of interest within the map image; updating, in real-time, a customization of the plurality of media templates responsive to the selection of the configuration option, each media template among the plurality of media templates including a display of the media object, and assigning the media object that includes the customization to a geo-fence that encompasses the location of interest identified by the input.

10. The non-transitory machine-readable storage medium of claim 9, wherein the set of attributes include a set of colors.

11. The non-transitory machine-readable storage medium of claim 10, wherein the selecting the portion of the set of attributes includes: determining a pixel count of each color among the set of colors; and selecting the portion of the set of colors based on the pixel count.
