

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400456
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Takagi; Toshihiro et al.

Peripheral monitoring device

Abstract

A peripheral monitoring device includes: a photographing device that is configured to photograph a peripheral area of a vehicle; and a control unit that is configured to display a peripheral screen including a predetermined peripheral image generated based on an image photographed by the photographing device, when a predetermined display condition is established.

Inventors:	Takagi; Toshihiro (Nisshin, JP), Tanaka; Hiroshi (Toyota, JP)
Applicant:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Family ID:	1000008778439
Assignee:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Appl. No.:	18/082015
Filed:	December 15, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230252792 A1	Aug. 10, 2023

Foreign Application Priority Data

JP	2022-018172	Feb. 08, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: G06V20/56 (20220101); G06F3/04883 (20220101); G06F3/14 (20060101); G09G5/36 (20060101)

U.S. Cl.:

CPC **G06V20/56** (20220101); **G06F3/04883** (20130101); **G06F3/14** (20130101); **G09G5/36** (20130101); G09G2380/10 (20130101)

Field of Classification Search

CPC: G06V (20/56); G06F (3/04883); G06F (3/14); G06F (3/04847); G09G (5/36); G09G (2380/10); B60R (1/22); B60R (16/023); B60R (2300/105); H04N (7/181)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2008/0071475	12/2007	Takaoka	701/469	G01C 21/20
2021/0076009	12/2020	Choi	N/A	G08B 13/19632
2021/0279959	12/2020	Watanabe	N/A	H04N 7/18
2023/0095245	12/2022	Peters	701/1	B60W 40/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2005-291785	12/2004	JP	N/A
2006-237974	12/2005	JP	N/A
2008-26007	12/2007	JP	N/A
2012-071833	12/2011	JP	N/A
2014/020889	12/2013	WO	N/A
2021/180433	12/2020	WO	N/A

OTHER PUBLICATIONS

Honda Navigation VXU-227VFNi Feb. 2022 Model. cited by applicant

Primary Examiner: Chio; Tat C

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to Japanese Patent Application No. 2022-018172 filed on Feb. 8, 2022, incorporated herein by reference in its entirety.

BACKGROUND

1. Technical Field

(2) The present disclosure relates to a peripheral monitoring device in which a peripheral screen including a predetermined peripheral image is displayed on a display device mounted on a vehicle, when a predetermined display condition is established.

2. Description of Related Art

(3) Conventionally, a peripheral monitoring device that displays a peripheral screen including a peripheral image on a display device is known. For example, a peripheral monitoring device (hereinafter referred to as a “conventional device”) described in Japanese Unexamined Patent

Application Publication No. 2012-71833 (JP 2012-71833 A) automatically displays a peripheral screen including an image of a range including a car body part that is most likely to be contacted when a vehicle is traveling on a narrow road or a narrow bend road.

SUMMARY

(4) The present inventors, and the like are considering a peripheral monitoring device that automatically displays a peripheral screen when a vehicle is positioned near a “registration position stored in advance by a driver”. Such a peripheral monitoring device needs to delete the registration position in accordance with an upper limit of a storage capacity of a storage device that stores the registration position or a request of the driver.

(5) When the peripheral monitoring device deletes the registration position, the peripheral monitoring device causes the driver to select the registration position to be deleted. In this case, the peripheral monitoring device needs to display a screen in which the driver can identify which position is the registration position.

(6) A peripheral monitoring device that displays a registration position on a map of map data using the map data stored by a navigation device mounted on a vehicle can be considered. However, there are the following problems. It is not able to be applied to a vehicle that does not have map data. When multiple registration positions exist at a relatively short distance, the driver must perform an enlargement operation to enlarge the map.

(7) The present disclosure has been made to address the above-mentioned issues. That is, one of the objects of the present disclosure to provide a peripheral monitoring device that is applicable to a vehicle that does not have map data, and that can cause the driver to identify which position a registration position is without requiring an enlargement operation of the map.

(8) The peripheral monitoring device of the present disclosure (hereinafter also referred to as “the device of the present disclosure”) includes: a photographing device (**22FR**, **22RR**, **22L**, **22R**) that is configured to photograph a peripheral area of a vehicle; a control unit (**20**) that is configured to display on a display device (**30**) mounted on the vehicle, a peripheral screen including a predetermined peripheral image generated based on an image photographed by the photographing device, when a predetermined display condition is established, in which the control unit is configured to acquire the peripheral image generated based on the image photographed by the photographing device at a current position of the vehicle as a registration time image (step **715**), when a driver of the vehicle performs a registration operation for registering the current position as a registration position (step **705** “Yes”), and store registration position information in which the registration time image and the current position are associated (step **725**), display the peripheral screen on the display device (step **605** “Yes”, step **630**, step **640**) by establishing the display condition (step **540**) when a position condition that the vehicle is positioned within a predetermined first range (**AR1**) centered on the registration position is established (step **525** “Yes”), display on the display device, a selection screen (**320**) including a stored registration time image of the registration position information (step **730**) when a predetermined delete condition is established (step **720** “No”), and delete registration position information of a registration time image selected by the driver on the selection screen (step **740**).

(9) The device of the present disclosure displays the selection screen including a registration time image, and deletes the registration position information of the registration time image selected by the driver on the selection screen. Thereby, the driver can identify which position the registration position of the registration position information is at by viewing the registration time image included in the selection screen. Accordingly, the device of the present disclosure can also be applied to a vehicle that does not have map data, and the device of the present disclosure can allow the driver to specify which position the registration position is at without the need for an enlargement operation of the map.

(10) In one aspect of the device of the device of the present disclosure, the control unit is configured to end display of the peripheral screen (step **840**) when the vehicle is positioned outside

a second range set to a range wider than the first range centered on the registration position (step **835** “Yes”), in a case in which the peripheral screen is displayed on the display device due to the position condition being established (step **820** “Yes”).

(11) In the present aspect, display of the peripheral screen display is ended when the vehicle is positioned outside the “second range set to a range wider than the first range centered on the registration position”, and not when the vehicle is positioned outside the first range. Thus, even when the identifying accuracy of the current position of the vehicle VA is poor, by having the current position of the vehicle being determined to be within the first range or being determined to be outside the first range, the possibility that display of the peripheral screen is repeatedly started and ended can be reduced. Therefore, it is possible to reduce the possibility that the driver feels that the repetition of the start and end of display of the peripheral screen is troublesome.

(12) In one aspect of the device of the present disclosure, the control unit is configured to identify the current position of the vehicle based on a positioning signal received from a plurality of artificial positioning satellites (**25**), and end display of the peripheral screen (step **840**) when a traveling distance in which the vehicle has traveled from a time point at which the current position of the vehicle is not able to be identified is equal to or more than a predetermined threshold value distance (step **850** “Yes”), in a case in which the current position of the vehicle is not able to be identified while the peripheral screen is displayed on the display device due to the position condition being established (step **825** “No”).

(13) In this embodiment, in a case in which the current position of the vehicle becomes un-identifiable, display of the peripheral screen ends when the traveling distance from the time point at which the current position of the vehicle can no longer be identified becomes equal to or more than the threshold value distance. Thereby, even when the current position of the vehicle is not able to be identified due to the inability to receive the positioning signal as a result of the vehicle being positioned in an underground parking lot or the like, display of the peripheral screen can be appropriately ended.

(14) In one aspect of the device of the present disclosure, the control unit is configured to acquire as the peripheral image, at least one of an image (**302**) of a traveling direction of the vehicle and an overhead view image (**304**) of a peripheral area of the vehicle (step **615**, step **715**), and display on the display device, the peripheral screen that includes the peripheral image and display the selection screen (step **630**, step **640**, step **730**).

(15) Thereby, the driver can grasp the situation of at least one of the area of the traveling direction of the vehicle and the peripheral area of the vehicle by visually viewing the peripheral screen.

(16) In one aspect of the device of the present disclosure, the control unit is configured to display the selection screen on the display device by establishing the delete condition (step **730**), when the number of pieces of the stored registration position information is equal to or more than a predetermined threshold value (step **720** “No”), in a case in which the driver performs the registration operation (step **705**, “Yes”).

(17) In this embodiment, when the number of stored (number of registrations of) registration position information is equal to or greater than the threshold value, the selection screen is displayed, and the driver is made to select the registration position information to be deleted. Thereby, it is possible to suppress the storage capacity of the registration position information from becoming too large.

(18) In one aspect of the device of the present disclosure, the control unit is configured to display the peripheral screen on the display device by establishing the display condition, even when either an operation condition that the driver performs a request operation requesting display of the peripheral screen (step **520** “Yes”) or an obstacle condition that an obstacle is detected in a vicinity of the vehicle is established (step **530** “Yes”), in addition to a case in which the position condition is established.

(19) In this embodiment, since the peripheral screen is displayed when the operation condition is

established, the peripheral screen can be displayed by performing the request operation when the driver wants the peripheral screen to be displayed. Furthermore, in this embodiment, since the peripheral screen is displayed when the obstacle condition is established, the peripheral screen can be displayed when there is an obstacle in the vicinity of the vehicle, and the possibility that the driver can recognize the obstacle can be increased.

(20) In the above aspect, the display device is a touch screen style display device, and the control unit is configured to display a registration switch image (306) on the display device together with the peripheral image when the peripheral screen is displayed on the display device, and assume that the driver has performed the registration operation when the driver touches the registration switch image (step 705 “Yes”), acquire the registration time image, and store the registration position information (step 725).

(21) In this embodiment, since the registration switch image is displayed together with the peripheral screen, it is possible to improve operability when the driver performs the registration operation.

(22) In the above aspect, the control unit is configured to assume that the driver has performed the registration operation when the driver touches the registration switch image in a case in which a vehicle speed that is a speed of the vehicle is equal to or less than a predetermined threshold value vehicle speed (step 620 “Yes), and not assume that the driver has performed the registration operation even when the driver touches the registration switch image in a case in which the vehicle speed is greater than the threshold value vehicle speed (step 620 “No”).

(23) Since it is assumed that the driver has performed the registration operation only when the driver touches the registration switch image in a case in which the vehicle speed is below the threshold value vehicle speed, the possibility that the driver tries to touch the registration switch image when the vehicle speed is greater than the threshold value vehicle speed can be reduced.

(24) In the above description, in order to help understanding of the disclosure, the names and/or the reference symbols used in the embodiment are added in parentheses to the configurations of the disclosure corresponding to the embodiment to be described later. However, respective components of the disclosure are not limited to the embodiment defined by the above names and/or reference symbols. Other objects, other features and accompanying advantages of the present disclosure will be readily understood from the description of embodiments of the present disclosure described with reference to the following drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Features, advantages, and technical and industrial significance of exemplary embodiments of the disclosure will be described below with reference to the accompanying drawings, in which like signs denote like elements, and wherein:

(2) FIG. 1 is a schematic system configuration diagram of a peripheral monitoring device according to an embodiment of the present disclosure;

(3) FIG. 2A is an explanatory diagram of an outline of an operation of the peripheral monitoring device according to the embodiment of the present disclosure;

(4) FIG. 2B is an explanatory diagram of an outline of an operation of the peripheral monitoring device according to the embodiment of the present disclosure;

(5) FIG. 2C is an explanatory diagram of an outline of an operation of the peripheral monitoring device according to the embodiment of the present disclosure;

(6) FIG. 2D is an explanatory diagram of an outline of an operation of the peripheral monitoring device according to the embodiment of the present disclosure;

(7) FIG. 3 is an explanatory diagram of a selection screen displayed in a display device shown in

FIG. 1;

(8) FIG. 4 is an explanatory diagram of a first range and a second range;

(9) FIG. 5 is a flowchart showing a display condition determination routine executed by a PVMECU CPU shown in FIG. 1;

(10) FIG. 6 shows a flowchart of a display control routine executed by the PVMECU CPU shown in FIG. 1;

(11) FIG. 7 shows a flowchart of a registration position information registration routine executed by the PVMECU CPU shown in FIG. 1;

(12) FIG. 8 shows a flowchart of an end condition determination routine executed by the PVMECU CPU shown in FIG. 1; and

(13) FIG. 9 is a flowchart of a distance-while-lost acquisition subroutine executed by the PVMECU CPU shown in FIG. 1.

DETAILED DESCRIPTION OF EMBODIMENTS

(14) Configuration

(15) As shown in FIG. 1, a peripheral monitoring device **10** according to an embodiment of the present disclosure is mounted on a vehicle VA.

(16) The peripheral monitoring device **10** includes a panoramic view monitor ECU **20** (hereinafter referred to as a “PVMECU **20**”).

(17) The ECU is an abbreviation for an electronic control unit, and is an electronic control circuit having a microcomputer including a central processing unit (CPU), a read-only memory (ROM), a random access memory (RAM), an interface, and the like as a main component. The ECU may be referred to as a “control unit”, a “controller” or a “computer”. The CPU realizes various functions by executing instructions (routines, programs) stored in the memory (ROM). The functions of the ECU may be distributed across a plurality of ECUs.

(18) The peripheral monitoring device **10** includes a wheel speed sensor **21**, a front camera **22FR**, a rear camera **22RR**, a left camera **22L**, a right camera **22R**, four front sonars **23FR**, four rear sonars **23RR**, a camera switch (SW) **24**, and a global navigation satellite system (GNSS) receiver **25**. These are connected to the PVMECU **20** so as to be able to exchange data.

(19) The wheel speed sensor **21** is provided for each wheel of the vehicle VA. Each wheel speed sensor **21** generates one wheel pulse signal each time the corresponding wheel rotates at a predetermined angle. The PVMECU **20** counts the number of pulses in the unit time of the wheel pulse signal generated by each wheel speed sensor **21**, and acquires the rotational speed of each wheel based on the number of pulses. Then, the PVMECU **20** acquires a vehicle speed Vs that indicates the speed of the vehicle VA based on the rotational speed of each wheel. As an example, the PVMECU **20** acquires the average value of the wheel speed of the four wheels as the vehicle speed Vs.

(20) The front camera **22FR** is disposed near the center of a vehicle width direction of a front grille FG of the vehicle VA, for example. The front camera **22FR** acquires a front image that is an image of the front area of the vehicle VA and transmits the front image to the PVMECU **20**.

(21) The rear camera **22RR** is disposed, for example, near the center of the vehicle width direction of a back door (not shown) of the vehicle VA. The rear camera **22RR** acquires a rear image that is an image of an area behind the vehicle VA and transmits the rear image to the PVMECU **20**.

(22) The left camera **22L** is disposed in, for example, in a left side mirror LSM. The left camera **22L** acquires a left side image that is an image of the area by photographing a left side area of the vehicle VA, and transmits the left side image to the PVMECU **20**.

(23) The right camera **22R** is disposed in, for example, in a right side mirror RSM. The right camera **22R** acquires a right side image that is an image of a right side area of the vehicle VA and transmits the right side image to the PVMECU **20**.

(24) When the images taken by the cameras **22FR** to **22R** are combined, it becomes an image of the area around the vehicle VA (360 degrees).

- (25) The four front sonars **23FR** are located at the left end, left center, right center, and right end of the front bumper FB of the vehicle VA, respectively.
- (26) The front sonar **23FR** emits sound waves and receives sound waves reflected by a three-dimensional object (hereinafter sometimes referred to as an “obstacle”). Based on the received sound wave, the front sonar **23FR** acquires a distance from the vehicle VA to the three-dimensional object and a horizontal position of the three-dimensional object with respect to the vehicle VA as forward three-dimensional object information, and transmits the forward three-dimensional object information to the PVMECU **20**.
- (27) The PVMECU **20** can detect a three-dimensional object present in the area from the left front side to the right front side of the vehicle VA based on the front three-dimensional information received from each front sonar FR **23**.
- (28) The four rear sonars **23RR** are disposed at the left end, left center, right center, and right end of the rear bumper (not shown) of the vehicle VA, respectively.
- (29) The rear sonar **23RR** emits a sound wave, receives the sound wave reflected by the three-dimensional object, acquires the distance to the three-dimensional object and the horizontal position of the three-dimensional object based on the received sound wave as back-solid-object information, and transmits the rear three-dimensional object information to the PVMECU **20**.
- (30) The PVMECU **20** can detect a three-dimensional object present in the area from the left rear side to the right rear side of the vehicle VA based on the rear three-dimensional information received from each rear sonar **23RR**.
- (31) A camera SW **24** is disposed at a position near a steering wheel (not shown) of the vehicle VA and where the driver of the vehicle VA can operate the camera **24**. When the driver operates the camera SW **24**, the PVMECU **20** displays a front mode screen **300** shown in FIGS. 2A to 2D on a display device **30**. The front mode screen **300** may be referred to as a “peripheral screen”.
- (32) The GNSS receiver **25** is a device for receiving positioning signals transmitted from a plurality of artificial positioning satellites. The PVMECU **20** identifies the current position (latitude and longitude) of the vehicle VA based on the positioning signals received by the GNSS receiver **25**.
- (33) Further, the peripheral monitoring device **10** includes the display device **30** and a storage device **31**. These are connected to the PVMECU **20** so as to be able to exchange data.
- (34) The display device **30** is disposed in a position where the driver can see in the vehicle cabin of the vehicle VA, and is a touch screen style display in which the driver can perform input by touching the screen displayed on the display device **30**. For example, the display device **30** is a multimedia display provided near the center of an instrument panel of the vehicle VA.
- (35) A storage device **26** is a non-volatile storage device in which the PVMECU **20** can read and write data. For example, the storage device **26** is a hard disk drive, but is not limited to a hard disk drive, and may be a well-known storage device or storage medium in which the PVMECU **20** can read and write data.
- (36) The storage device **26** includes an image storage unit **310** and a registration position information storage unit **312**. The image storage unit **310** stores a registration time image described later. The registration position information storage unit **312** stores the registration position information in which the registration position and the registration time image, which will be described later, are associated.
- (37) Outline of Operation
- (38) With reference to FIGS. 2 and 3, an outline of the operation of the peripheral monitoring device **10** will be described.
- (39) As shown in FIG. 2A, when the vehicle VA enters a T-shaped road, the driver operates the camera SW **24** because the visibility is poor on this T-shaped road, and wants to check the situation on the left and right sides of the T-shaped road. When the camera SW **24** is operated and the vehicle speed Vs is equal to or less than a first threshold value vehicle speed Vsth1, the peripheral monitoring device **10** displays the front mode screen **300** on the display device **30**.

(40) The front mode screen **300** includes a traveling direction image area **302**, a panoramic view (PV) image area **304**, and a registration switch (SW) image **306**. The traveling direction image area **302** displays a traveling direction image generated based on the front image acquired by the front camera **22FR**.

(41) The PV image area **304** displays a PV image generated based on a front image, a rear image, a left side image, and a right side image. The PV image is a bird's-eye view when the peripheral area of the vehicle VA is viewed from a vertical upward viewpoint of the vehicle VA.

(42) The registration SW image **306** is an image to be touched when the driver registers the current position as a registration position. When the vehicle speed V_s is less than or equal to “a second threshold value vehicle speed v_{sth} that is smaller than the first threshold value vehicle speed V_{sth1} ” and the driver touches the registration SW image **306**, the peripheral monitoring device **10** regards this touch operation as a registration operation and registers the current position of the vehicle VA as the registration position.

(43) Thereafter, as shown in FIG. 2B, the vehicle VA stops before the stop line (that is, the vehicle speed V_s is the second threshold value vehicle speed V_{sth2} or less). The driver desires that the front mode screen **300** be displayed when the vehicle VA passes through this T-shaped road in the future, and touches the registration SW image **306**.

(44) When the vehicle speed V_s is less than or equal to the second threshold value vehicle speed V_{sth2} and the driver touches the registration SW image **306**, the peripheral monitoring device **10** determines whether the number N of registration position information stored in the registration position information storage unit **312** (hereinafter referred to as the “number of registrations”) is less than a threshold N_{th} .

(45) When the number of registrations N is less than the threshold value N_{th} , as shown in FIG. 2C, the peripheral monitoring device **10** acquires a front image, a rear image, a left side image, and a right side image, generates a PV image based on these images and generates a traveling direction image based on the front image, and stores the traveling direction image and the PV image in the image storage unit **310** as the registration time image. Furthermore, in this case, the peripheral monitoring device **10** stores in the registration position information storage unit **312**, the registration position information in which the current position of the vehicle VA and the registration time image are associated. Specifically, the peripheral monitoring device **10** stores in the registration position information storage unit **312**, the registration position information in which the current position of the vehicle VA and a “storage path representing a place where the registration time image is stored” are associated.

(46) On the other hand, when the number of registrations N is the threshold value N_{th} or more, as shown in FIG. 2D, the peripheral monitoring device **10** displays a selection screen **320** shown in FIG. 3. The selection screen **320** is a screen for allowing the driver to select the registration position information to be deleted.

(47) The selection screen **320** will be described with reference to FIG. 3.

(48) On the selection screen **320**, the registration time image of the registration position information stored in the registration position information storage unit **312** is displayed. The selection screen **320** includes a checkbox area **322**, a registration time image area **324**, an OK image **326**, and a cancellation image **328**.

In the checkbox area **322**, a checkbox image corresponding to each registration time image is displayed. When a registration time image is not selected, the checkbox image corresponding to the registration time image is white, and when the registration time image is selected, the checkbox image corresponding to the registration time image changes to black. In the registration time image area **324**, the registration time images (traveling direction image and PV image) are displayed.

(49) When the OK image **326** is touched in a state in which at least one registration time image selected, the peripheral monitoring device **10** deletes the registration position information of the selected registration time image from the registration position information storage unit **312** and

deletes the registration position information of the registration time image that is selected from the image storage unit **310**. Then, the peripheral monitoring device **10** stores in the registration position information storage unit **312**, the registration position information in which the current position of the vehicle VA and the newly acquired registration time image are associated, and stores the registration time image in the image storage unit **310**.

(50) When the cancellation image **328** is touched in a state in which at least one registration time image is selected, the peripheral monitoring device **10** cancels the selection. Furthermore, when the cancellation image **328** is touched in a state in which none of the registration time images are selected, the peripheral monitoring device **10** cancels storing the new registration position information.

(51) The peripheral monitoring device **10** according to the present embodiment displays the selection screen **320** including the registration time image of the registration position information stored in the registration position information storage unit **312**. Thereby, since the driver can easily identify which position the registration position information is, unnecessary registration position information can be deleted.

(52) The peripheral monitoring device that displays the registration position information of the registration position information on the map in order to allow the driver to select the registration position information to be deleted cannot be applied to the vehicle VA that does not have the map data. On the other hand, since the peripheral monitoring device **10** according to the present embodiment should store the registration time image when storing (registering) the registration position information, it can be applied to the vehicle VA that does not have the map data. Furthermore, according to the peripheral monitoring device **10** according to the present embodiment, even when a plurality of registration positions exist at a relatively short distance, the driver can identify the position at which the registration position is by viewing the registration time image and thus, an enlargement operation of the map is unnecessary.

(53) Display Condition

(54) When the display condition is established, the peripheral monitoring device **10** starts display on the display device **30** of the front mode screen **300**.

(55) The display condition is established when any of the following operation condition, obstacle condition, and position condition are established, in a case in which the vehicle speed V_s is equal to or less than the first threshold value vehicle speed V_{sth1} and a shift position SP is a position other than a parking (P) position and a reverse (R) position.

(56) Operation condition: The camera SW **24** is operated.

(57) Obstacle condition: At least one of the front sonar **23FR** and the rear sonar **23RR** has detected a three-dimensional object (obstacle).

(58) Position condition: The vehicle VA is positioned in a predetermined first range AR1 from the registration position of the registration position information (see FIG. 4).

(59) As shown in FIG. 4, for example, the first range AR1 is a circular shape having a predetermined radius $r1$ centered on the registration position.

End Conditions

(60) When the end conditions are established, the peripheral monitoring device **10** ends the display on the display device **30** of the front mode screen **300**, and displays on the display device **30**, the screen that was displayed on the display device **30** before the front mode screen **300** was displayed.

(61) The end condition is established when the following condition 1 is established.

(62) Condition 1: The vehicle speed V_s is greater than the first threshold value vehicle speed V_{sth1} .

(63) Furthermore, when the display condition is established because the obstacle condition is established, the end condition is established when the following condition 2 is established even if condition 1 is not established.

(64) Condition 2: Neither the front sonar **23FR** nor the rear sonar **23RR** detects a three-dimensional object.

(65) Furthermore, when the display condition is established because the position condition is established, the end condition is established when any of the following conditions 3 and 4 are established even if condition 1 is not established.

(66) Condition 3: The vehicle VA is positioned outside a second range AR2 shown in FIG. 4.

(67) As shown in FIG. 4, for example, the second range AR2 is a circular shape having a predetermined radius $r2$ centered on the registration position. The radius $r2$ is longer than the radius $r1$. For this reason, the second range AR2 has a wider range than the first range AR1.

(68) If the display of the front mode screen 300 ends when the condition that the vehicle VA is positioned outside the first range AR1 is established, even when the specific accuracy of the current position of the vehicle VA is poor, the current position of the vehicle is determined to be within the first range or is determined to be outside the first range. Due to this, the start and end of the display of the front mode screen 300 are repeated, and the driver may feel that it is troublesome. In the present embodiment, since the second range AR2 is set to be wider than the first range AR1, the possibility that the start and end of the display of the front mode screen 300 is repeated is reduced, and the possibility that the driver feels troublesome can be reduced.

(69) Condition 4: When the GNSS receiver 25 can no longer receive the positioning signals (that is, when the current position of the vehicle VA can no longer be identified), a distance D traveled by the vehicle VA from the time when the positioning signals could not be received (traveling-distance-while-lost) is equal to or greater than a threshold value distance Dth.

(70) If the display of the front mode screen 300 ends when the condition that the GNSS receiver 25 can no longer receive the positioning signal is established, the display of the front mode screen 300 ends even though the driver wants to see the front mode screen 300, and there is a possibility that the driver feels troublesome. According to the present embodiment, even when the GNSS receiver 25 can no longer receive the positioning signal, if the vehicle VA does not travel for the threshold value distance Dth or more, the display of the front mode screen 300 does not end. If the vehicle VA is traveling for the threshold value distance Dth or more, it is likely that the need for the driver to see the front mode screen 300 has already been lost. For this reason, the possibility that the driver feels troublesome as described above can be reduced.

(71) Specific Operation

(72) Display Condition Determination Routine

(73) The CPU of the PVMECU 20 (hereinafter, "CPU" in the description refers to the CPU of the PVMECU 20 unless otherwise specified) executes a display condition determination routine shown by the flowchart in FIG. 5 every time a predetermined time elapses.

(74) Therefore, at a predetermined timing, the CPU starts the process from step 500 shown in FIG. 5 and proceeds to step 505. In step 505, the CPU determines whether values of a first display flag Xdp1, a second display flag Xdp2, and a third display flag Xdp3 are

(75) The value of the first display flag Xdp1 is set to "1" when the display condition is established due to the establishment of the above operation condition, and is set to "0" when the above end condition is established. The CPU sets the value of the first display flag Xdp1 to "0" in an initial routine executed when an ignition key switch (not shown) of the vehicle VA is changed from an off position to an on position.

(76) The value of the second display flag Xdp2 is set to "1" when the display condition is established due to the establishment of the above position condition, and is set to "0" when the above end condition is established. The CPU sets the value of the second display flag Xdp2 to "0" in the initial routine.

(77) The value of the third display flag Xdp3 is set to "1" when the display condition is established due to the establishment of the above obstacle condition, and is set to "0" when the above end condition is established. The CPU sets the value of the third display flag Xdp3 to "0" in the initial routine.

(78) When the values of the first display flag Xdp1, the second display flag Xdp2, and the third

display flag Xdp3 are “0”, the CPU determines “Yes” in step 505 and proceeds to step 510.

(79) In step 510, the CPU determines whether the vehicle speed Vs is equal to or less than the first threshold value vehicle speed Vsth1. When the vehicle speed Vs is greater than the first threshold value vehicle speed Vsth1, the CPU determines “No” in step 510 and proceeds to step 595 to temporarily end this routine.

(80) When the vehicle speed Vs is equal to or less than the first threshold value vehicle speed Vsth1, the CPU determines “Yes” in step 510 and proceeds to step 515. In step 515, the CPU determines whether the shift position SP is either the P position or the R position.

(81) When the shift position SP is either the P position or the R position, the CPU determines “Yes” in step 515 and proceeds to step 595 to temporarily end this routine.

(82) When the shift position SP is neither the P position nor the R position, the CPU determines “No” in step 515 and proceeds to step 520. In step 520, the CPU determines whether the camera SW 24 has been operated.

(83) When the camera SW 24 has not been operated, the CPU determines “No” in step 520 and proceeds to step 525. In step 525, the CPU determines whether the vehicle VA is positioned in the first range AR1.

(84) When the vehicle VA is not located in the first range AR1, the CPU determines “No” in step 525 and proceeds to step 530. In step 530, the CPU determines whether at least one of the front sonar 23FR and the rear sonar 23RR detects an obstacle based on the front three-dimensional object information and the rear three-dimensional object information.

(85) When neither the front sonar 23FR nor the rear sonar 23RR detect an obstacle, the CPU determines “No” in step 530 and proceeds to step 595 to temporarily end this routine.

(86) On the other hand, when the camera SW 24 is operated when the CPU proceeds to step 520, the CPU determines “Yes” in step 520 and proceeds to step 535. In this case, since the display condition is established because the operation condition is established, in step 535, the CPU sets the value of the first display flag Xdp1 to “1”, and proceeds to step 595 to temporarily end this routine.

(87) On the other hand, when the vehicle VA is positioned in the first range AR1 when the CPU proceeds to step 525, the CPU determines “Yes” in step 525 and proceeds to step 540. In this case, since the display condition is established because the position condition is established, in step 540, the CPU sets the value of the second display flag Xdp2 to “1”, proceeds to step 595 and temporarily ends this routine.

(88) On the other hand, when at least one of the front sonar 23FR and the rear sonar 23RR detects an obstacle when the CPU proceeds to step 530, the CPU determines “Yes” in step 530 and proceeds to step 545. In this case, since the display condition is established because the obstacle condition is established, in step 545, the CPU sets the value of the third display flag Xdp3 to “1”, and proceeds to step 595 to temporarily end this routine.

(89) On the other hand, when the CPU proceeds to step 505, when the value of any of the first display flag Xdp1, the second display flag Xdp2, and the third display flag Xdp3 is “1”, the CPU determines “No” in step 505 and proceeds to step 595 to temporarily end this routine.

(90) Display Control Routine

(91) The CPU executes a display control routine shown by the flowchart in FIG. 6 every time a predetermined time elapses.

(92) Therefore, at a predetermined timing, the CPU starts the process from step 600 shown in FIG. 6 and proceeds to step 605. In step 605, the CPU determines whether values of a first display flag Xdp1, a second display flag Xdp2, and a third display flag Xdp3 are

(93) When the values of the first display flag Xdp1, the second display flag Xdp2, and the third display flag Xdp3 are all “0”, the CPU determines “No” in step 605, and the procedure proceeds to step 695 and temporarily ends this routine.

(94) When the value of any of the first display flag Xdp1, the second display flag Xdp2, and the

third display flag Xdp3 is “1”, the CPU determines “Yes” in step **605**, and steps **610** to **620** are executed in order.

(95) Step **610**: The CPU acquires a front image, a rear image, a left side image, and a right side image from each of the cameras **22FR** to **22R**.

(96) Step **615**: The CPU generates the PV image based on the front image, the rear image, the left side image and the right side image, and generates the traveling direction image based on the front image.

(97) Step **620**: The CPU determines whether the vehicle speed V_s is equal to or less than the second threshold value vehicle speed V_{sth2} .

(98) When the vehicle speed V_s is the second threshold value vehicle speed V_{sth2} or less, the CPU determines “Yes” in step **620** and executes step **625** and step **630** in order.

(99) Step **625**: The CPU sets the first registration SW image as the registration SW image **306**.

(100) Step **630**: The CPU transmits a first display command including the traveling direction image, the PV image, and the first registration SW image to the display device **30**.

(101) After that, the CPU proceeds to step **695** and temporarily ends this routine.

(102) When the display device **30** receives the first display command, it displays the front mode screen **300** including the traveling direction image, the PV image, and the first registration SW image included in the first display command. When the first registration SW image is touched, the display device **30** transmits touch information indicating that the registration SW image **306** has been touched to the PVMECU **20**.

(103) On the other hand, when the vehicle speed V_s is larger than the second threshold value vehicle speed V_{sth2} , the CPU determines “No” in step **620** and executes step **635** and step **640** in order.

(104) Step **635**: The CPU sets the second registration SW image as the registration SW image **306**. It is desirable that the second registration SW image is an image of the registered SW in such a manner that it is less conspicuous than the first registration SW image. For example, the first registration SW image is a solid line, while the second registration SW image is a dotted line. The color of the second registration SW image may be a color closer to the background color of the front mode screen **300** than the color of the first registration SW image.

(105) Step **640**: The CPU transmits a second display command including the traveling direction image, the PV image, and the second registration SW image.

(106) After that, the CPU proceeds to step **695** and temporarily ends this routine.

(107) When the display device **30** receives the second display command, it displays the front mode screen **300** including the traveling direction image, the PV image, and the second registration SW image included in the second display command. Even when the second registration SW image is touched, the display device **30** does not transmit the touch information to the PVMECU **20**.

(108) Since the registration SW image **306** is also displayed on the front mode screen **300** along with the traveling direction image and the PV image, it becomes easy for the driver to register the current position of the vehicle VA as the registration position.

(109) Furthermore, when the vehicle speed V_s is larger than the second threshold value vehicle speed V_{sth2} , even if the registration SW image **306** is touched, the CPU does not deem that the registration operation of the registration position has been performed. On the other hand, when the vehicle speed V_s is less than or equal to the second threshold value vehicle speed V_{sth2} , when the registration SW image **306** is touched, the CPU deems that a registration operation has been performed. Thereby, when the vehicle VA is traveling at the vehicle speed V_s larger than the second threshold value vehicle speed V_{sth2} , the possibility that the driver tries to touch operate the registration SW image and performs sideways driving can be reduced.

Registration Position Information Registration Routine

(110) The CPU executes the registration position information registration routine shown by flowchart in FIG. **7** every time a predetermined time elapses.

(111) Therefore, at a predetermined timing, the CPU starts the process from step **700** shown in FIG. 7 and proceeds to step **705**. In step **705**, the CPU determines whether the touch information has been received (that is, whether the registration SW image **306** has been touched).

(112) When the registration SW image **306** is not touched, the CPU determines “No” in step **705**, and proceeds to step **795** to temporarily end this routine.

(113) When the registration SW image **306** is touched, the CPU determines “Yes” in step **705** and executes steps **710** to **720** in order.

(114) Step **710**: The CPU acquires the current position of the vehicle VA based on the positioning signals received by the GNSS receiver **25**.

(115) Step **715**: The CPU generates the PV image based on the front image, the rear image, the left side image and the right side image, that are acquired from each of the cameras **22FR** to **22R** and generates the traveling direction image based on the front image, and acquires the traveling direction image and the PV image as the registration time image.

Step **720**: The CPU determines whether the number of registration position information (number of registrations) N stored in the position information at the time of registration is less than the threshold value Nth.

(116) Step **725**: The CPU stores in the registration position information storage unit **312**, the registration position information in which the current position of the vehicle VA and the registration time image are associated, and stores the registration time image in the image storage unit **310**.

(117) After that, the CPU proceeds to step **795** and temporarily ends this routine.

(118) On the other hand, when the number of registrations N is the threshold value Nth or more when the CPU advances to step **720**, the CPU determines “No” in step **720** and executes step **730** and step **735** in order.

(119) Step **730**: The CPU displays the selection screen **320** on the display device **30**.

(120) Step **735**: The CPU determines whether the OK image **326** is touched with at least one registration time image selected on the selection screen **320**.

(121) When the OK image **326** is touched with at least one registration time image selected, the CPU determines “Yes” in step **735** and proceeds to step **740**. In step **740**, the CPU deletes the registration position information of the selected registration time image from the registration position information storage unit **312** and deletes the registration time image from the image storage unit **310**. Thereafter, the CPU proceeds to step **725** to newly store the registration position information, and proceeds to step **795** to temporarily end this routine.

(122) When the OK image **326** is not touched when the CPU proceeds to step **735**, the CPU determines “No” in step **735** and proceeds to step **745**. In step **745**, the CPU determines whether the cancellation image **328** is touched while the registration time image is not selected on the selection screen **320**.

(123) When the cancellation image **328** is not touched, the CPU determines “No” in step **745** and returns to step **735**.

(124) When the cancellation image **328** is touched with at least one registration time image selected, the CPU determines “Yes” in step **745** and proceeds to step **750**. In step **750**, the CPU ends the display of the selection screen **320** and displays the front mode screen **300**. After that, the CPU proceeds to step **795** and temporarily ends this routine.

(125) Display End Condition Determination Routine

(126) The CPU executes an end condition determination routine shown by the flowchart in FIG. 8 every time a predetermined time elapses.

(127) Therefore, at a predetermined timing, the CPU starts the process from step **800** shown in FIG. 8 and proceeds to step **805**. In step **805**, the CPU determines whether values of a first display flag Xdp1, a second display flag Xdp2, and a third display flag Xdp3 are “1”.

(128) When the values of the first display flag Xdp1, the second display flag Xdp2, and the third display flag Xdp3 are all “0”, the CPU determines “No” in step **805**, and the procedure proceeds to

step **895** and temporarily ends this routine.

(129) When the values of the first display flag Xdp1, the second display flag Xdp2, and the third display flag Xdp3 are “1”, the CPU determines “Yes” in step **805** and proceeds to step **810**. In step **810**, the CPU determines whether the vehicle speed Vs is greater than the first threshold value vehicle speed Vsth1.

(130) When the vehicle speed Vs is greater than the first threshold value vehicle speed Vsth1, the CPU determines “Yes” in step **810** and proceeds to step **815**. In step **815**, the CPU sets the values of the first display flag Xdp1, the second display flag Xdp2, and the third display flag Xdp3 to “0”. After that, the CPU proceeds to step **895** and temporarily ends this routine.

(131) When the vehicle speed Vs is equal to or less than the first threshold value vehicle speed Vsth1, the CPU determines “No” in step **810** and proceeds to step **820**. In step **820**, the CPU determines whether the value of the second display flag Xdp2 is “1”.

(132) When the value of the second display flag Xdp2 is “1”, the CPU determines “Yes” in step **820** and proceeds to step **825**. In step **825**, the CPU determines whether the current position of the vehicle VA can be specified (that is, whether the GNSS receiver 25 is receiving positioning signals).

(133) When the current position of the vehicle VA can be specified (that is, when the GNSS receiver 25 is receiving the positioning signals), the CPU determines “Yes” in step **825**, and step **830** and step **835** are executed in order.

(134) Step **830**: The CPU sets the value of a lost flag Xlost to “0” and sets a traveling-distance-while-lost D to “0” during the loss.

(135) The value of the lost flag Xlost is set to “1” when the current position of the vehicle VA cannot be determined, and is set to “0” when the current position of the vehicle VA can be determined. The CPU sets the value of the lost flag Xlost to “0” in the initial routine.

(136) The traveling-distance-while-lost D is the distance traveled by vehicle VA while the current position of vehicle VA cannot be identified.

(137) Step **835**: The CPU determines whether the vehicle VA is positioned outside the second range AR2. The second range AR2 is a range centered on the registration position used for establishing the position condition when the value of the second display flag Xdp2 is set to “1”.

(138) When the vehicle VA is positioned outside the second range AR2, the CPU determines “Yes” in step **835** and proceeds to step **840**. In step **840**, the CPU sets the values of the second display flag Xdp2 and the lost flag Xlost to “0” and sets the traveling-distance-while-lost D to “0”. After that, the CPU proceeds to step **895** and temporarily ends this routine.

(139) When the vehicle VA is not located outside the second range AR2 (that is, when the vehicle VA is positioned in the second range AR2), the CPU determines “No” in step **835** and proceeds to step **895** to temporarily end this routine.

(140) On the other hand, when the current position of the vehicle VA cannot be specified when the CPU proceeds to step **825** (that is, when the GNSS receiver 25 is not receiving the positioning signals), the CPU determines “No” in step **825** and executes step **845** and step **850** in order.

(141) Step **845**: The CPU executes a traveling-distance-while-lost acquisition subroutine.

(142) Actually, when the CPU proceeds to step **845**, the CPU executes the subroutine shown by the flowchart in FIG. 9. In this subroutine, the CPU acquires the traveling-distance-while-lost D.

(143) Step **850**: The CPU determines whether the traveling-distance-while-lost D is the threshold value distance Dth or more.

(144) When the traveling-distance-while-lost D is the threshold value distance Dth or more, the CPU determines “Yes” in step **850**, proceeds to step **840**, and sets the value of the second display flag Xdp2 to “0”. After that, the CPU proceeds to step **895** and temporarily ends this routine.

(145) When the traveling-distance-while-lost D is less than the threshold value distance Dth, the CPU determines “No” in step **850** and proceeds to step **895** to end this routine once.

(146) On the other hand, when the value of the second display flag Xdp2 is “0” when the CPU

proceeds to step **820**, the CPU determines “No” in step **820** and proceeds to step **855**.

(147) In step **855**, the CPU determines whether the value of the third display flag Xdp3 is “1”.

(148) When the value of the third display flag Xdp3 is “1”, the CPU determines “Yes” in step **855** and proceeds to step **860**. At step **860**, the CPU determines whether at least one of the front sonar **23FR** and the rear sonar **23RR** detects an obstacle.

(149) When at least one of the front sonar **23FR** and the rear sonar **23RR** detects an obstacle, the CPU determines “Yes” in step **860** and proceeds to step **895** to temporarily ends this routine.

(150) When neither the front sonar **23FR** nor the rear sonar **23RR** detects an obstacle, the CPU determines “No” in step **860** and proceeds to step **865**. In step **865**, the CPU sets the value of the third display flag Xdp3 to “0”. After that, the CPU proceeds to step **895** and temporarily ends this routine.

(151) On the other hand, when the value of the third display flag Xdp3 is “0” when the CPU proceeds to step **855**, the CPU determines “No” in step **855**, proceeds to step **895**, and temporarily ends this routine.

(152) Distance-while-Lost Acquiring Subroutine

(153) When the CPU proceeds to step **845** shown in FIG. **8**, processing starts from step **900** shown in FIG. **9** and proceeds to step **905**. In step **905**, the CPU determines whether that the value of the lost flag Xlost is “0”.

(154) When the value of the lost flag Xlost is “0”, the CPU determines “Yes” in step **905** and proceeds to step **910**. Step **910**: The CPU sets the value of the lost flag Xlost to “1” and sets the traveling-distance-while-lost D to “0”. After that, the CPU proceeds to step **995**, temporarily ends this routine, and proceeds to step **850** shown in FIG. **8**.

(155) On the other hand, when the value of the lost flag Xlost is “1”, the CPU determines “No” in step **905**, and executes steps **915** to **920** in order.

(156) Step **915**: The CPU acquires the traveling distance Da of the vehicle VA in a period based on the number of wheel pulse signals generated by the wheel speed sensor **21** in the period from the previous execution of the end condition determination routine shown in FIG. **8** to the present time.

(157) Step **920**: The CPU adds the traveling distance Da to the traveling-distance-while-lost D.

(158) After that, the CPU proceeds to step **995**, temporarily ends this routine, and proceeds to step **850** shown in FIG. **8**.

(159) As described above, when the delete condition that the number of registrations N is equal to or greater than the threshold value Nth is established, the peripheral monitoring device **10** displays the “selection screen **320** including the registration time image of the registration position information stored in the registration position information storage unit **312**”. The peripheral monitoring device **10** deletes from the registration position information storage unit **312**, the registration position information corresponding to the registration time image selected on the selection screen **320**.

(160) Thereby, the driver makes it easy to identify which position the registration position information is at by visually viewing the selection screen **320**. Therefore, the driver can accurately select the unnecessary registration position information to be deleted. Furthermore, the peripheral monitoring device **10** can be applied to the vehicle VA that does not have map data.

(161) Furthermore, when the vehicle VA becomes located outside the second range AR2 that is wider than the first range AR1 centered on the registration position, the peripheral monitoring device **10** ends the display of the front mode screen **300**. Thereby, the possibility that the display of the front mode screen **300** starts and ends is repeated can be reduced.

(162) Furthermore, when the current position of the vehicle VA cannot be specified (that is, when the positioning signals cannot be received), when the traveling distance (traveling-distance-while-lost) D of the vehicle VA from that time becomes the threshold value distance Dth or more, the peripheral monitoring device **10** ends the display of the front mode screen **300**. For example, when the vehicle VA is positioned in an underground parking lot or the like, there is a case in which the

current position of the vehicle VA can not be specified. Even in such a case, the display of the front mode screen **300** can be appropriately ended.

(163) The present disclosure is not limited to the above embodiment, and various modifications can be adopted within the scope of the present disclosure.

(164) First Modification

(165) The front mode screen **300** should include at least one of the traveling direction image and the PV image. Similarly, the registration time image should include at least one of the traveling direction image and the PV image.

(166) Second Modification

(167) The display device **30** displays a delete switch (SW) image not shown. The delete SW image is touched when the driver wishes to delete the registration position information. In a case in which the delete SW image is touched, when the number of registrations N is equal to or more than the threshold value Nth the PVMECU **20** may establish the delete condition and display the selection screen **320**. As a result, by touching the delete SW image, the driver can select the registration position information to be deleted.

(168) Third Modification

(169) The first range AR1 and the second range AR2 may have a shape other than a circular shape if the second range AR2 is wider than the first range AR1 centered on the registration position.

(170) Fourth Modification

(171) When the peripheral monitoring device **10** can recognize obstacles around the vehicle VA based on the images taken by the cameras **22FR** to **22R**, the peripheral monitoring device **10** does not need to include the front sonar **23FR** and the rear sonar **23RR**.

(172) The front sonar **23FR** and the rear sonar **23RR** may be remote sensing devices that can transmit a wireless medium other than sound waves and detect objects by receiving the reflected wireless media. Furthermore, the number of front sonar **23FR** and rear sonar **23RR** is not limited to four, respectively.

(173) The number of cameras **22FR** to **22R** is not limited to four as long as the cameras **22FR** to **22R** can capture images of the area (peripheral area) around the vehicle VA (360 degrees).

(174) Fifth Modification

(175) When the PVMECU **20** according to the fifth modification displays the front mode screen **300**, the registration SW image **306** is displayed when the vehicle speed Vs is equal to or less than the second threshold value vehicle speed Vsth2, and the registration SW image **306** is not displayed when the vehicle speed Vs is greater than the second threshold value vehicle speed Vsth2.

(176) Sixth Modification

(177) The PVMECU **20** according to the sixth modification displays the registration SW image **306** on the front mode screen **300** regardless of the magnitude relationship between the vehicle speed Vs and the second threshold value vehicle speed Vsth2. However, the PVMECU **20** determines whether the registration SW image **306** is touched only when the vehicle speed Vs is the second threshold value vehicle speed Vsth2 or less. When the registration SW image **306** is touched, the process after step **710** shown in FIG. 7 is executed.

(178) Seventh Modification

(179) In the above-described embodiment, when the shift position SP is a position other than the parking (P) position and the reverse (R) position, the PVMECU **20** displays the front mode screen **300** including the traveling direction image generated based on the front image of the traveling direction of the vehicle VA. However, when the shift position SP is a reverse (R) position, the PVMECU **20** may display the rear mode screen including the traveling direction image generated based on the rear image of the traveling direction of the vehicle VA. The rear mode screen has the same configuration as the front mode screen **300** except that the traveling direction image is an image generated based on the rear direction image.

cl Eighth Modification

(180) The peripheral monitoring device **10** is used also for a hybrid electric vehicle (HEV), a plug-

in hybrid electric vehicle (PHEV), a fuel cell electric vehicle (FCEV), and a battery electric vehicle (BEV), in addition to the engine vehicle described above.

Claims

1. A peripheral monitoring device comprising: an image capturing device configured to capture an image of a peripheral area of a vehicle; and a processor configured to determine whether a predetermined display condition has been established, acquire the image from the image capturing device in response to determining the predetermined display condition has been established, generate a predetermined peripheral image based on the captured image of the peripheral area, display a periphery image screen on a display device mounted on the vehicle, the periphery image screen including the generated predetermined peripheral image; determine whether a driver of the vehicle has performed a registration operation to register a current position of the vehicle as a registered position, acquire the current position in response to determining that the driver has performed the registration operation, acquire the generated predetermined peripheral image at the acquired current position of the vehicle as a registration time image, store the current position associated with the registration time image as registration position information, wherein the processor is further configured to determine whether a position condition is established, the position condition being a condition that the vehicle is positioned within a predetermined first range centered on the registered position, display the periphery image screen on the display device in response to the position condition being established, determine whether a number of pieces of the stored registration position information is equal to or more than a predetermined threshold value, display on the display device, a selection screen including a stored registration time image of the registration position information in response to the number of pieces of the stored registration position information being equal to or more than a predetermined threshold value, determine whether the driver selected the registration time image on the selection screen, and delete registration position information of the selected registration time image.
2. The peripheral monitoring device according to claim 1, wherein the processor is configured to determine whether the vehicle is positioned outside a second range set to a range wider than the first range centered on the registered position, in a case in which the periphery image screen is displayed on the display device in response to determining that the position condition is established end display of the periphery image screen in response to determining that the vehicle is positioned outside the second range.
3. The peripheral monitoring device according to claim 1, wherein the processor is configured to identify the current position of the vehicle based on a positioning signal received from a plurality of artificial positioning satellites, and determine whether a traveling distance in which the vehicle has traveled from a time point at which the current position of the vehicle is not able to be identified is equal to or more than a predetermined threshold value distance, in a case in which the current position of the vehicle is not able to be identified while the periphery image screen is displayed on the display device in response to the position condition being established, end display of the periphery image screen in response to determining that the traveling distance in which the vehicle has traveled from the time point at which the current position of the vehicle is not able to be identified is equal to or more than a predetermined threshold distance.
4. The peripheral monitoring device according to claim 1, wherein the processor is configured to acquire as the predetermined peripheral image, at least one of an image of a traveling direction of the vehicle and an overhead view image of the peripheral area of the vehicle, and display on the display device, the periphery image screen that includes the predetermined peripheral image and the selection screen.
5. The peripheral monitoring device according to claim 1, wherein the processor is configured to determine whether either an operation condition that the driver performs a request operation

requesting display of the periphery image screen or an obstacle condition that an obstacle is detected in a vicinity of the vehicle is established, display the periphery image screen on the display device in response to determining that either the operation condition or the obstacle condition is established.

6. The peripheral monitoring device according to claim 5, wherein the display device is a touch screen style display device, and wherein the processor is configured to display a registration switch image on the display device together with the predetermined peripheral image in a case in which the periphery image screen is displayed on the display device, determine whether the driver touches the registration switch image, determine that the driver has performed the registration operation in response to determining that the driver touches the registration switch image, acquire the registration time image, and store the registration position information, in response to determining that the driver has performed the registration operation.

7. The peripheral monitoring device according to claim 6, wherein the processor is configured to determine whether a vehicle speed that is a speed of the vehicle is equal to or less than a predetermined threshold value vehicle speed, or is greater than the threshold value vehicle speed, determine that the driver has performed the registration operation in response to determining that the driver touches the registration switch image in a case in which the vehicle speed is equal to or less than the predetermined threshold value vehicle speed, and determine that the driver has not performed the registration operation in response to determining that the driver touches the registration switch image in a case in which the vehicle speed is greater than the threshold value vehicle speed.

8. The peripheral monitoring device according to claim 3, wherein the processor is configured to determine that the current position of the vehicle becomes unidentifiable in response to the positioning signal not being able to be received.
