

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402278
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Nagimov; Ruslan et al.

Waste cold recuperation in fuel cell based power generation systems for datacenters

Abstract

Examples described in this disclosure relate to waste cold recuperation in fuel cell based power generation systems for datacenters. An example waste cold recuperation system includes a liquefied gas storage for supplying liquefied gas as a coolant to cool a first set of compute resources configurable to operate in a first cryogenic environment. The system is configurable to supply at least some of the vapor phase of the liquefied gas as a coolant to cool a second set of compute resources configurable to operate in a second cryogenic environment, resulting in the at least some of the vapor phase of the liquefied gas becoming a super-heated vapor phase of the liquefied gas. The system is configurable to supply the super-heated vapor phase of the liquefied gas as fuel to fuel cells for providing electrical power to a datacenter load including compute resources configurable to operate in a non-cryogenic environment.

Inventors: Nagimov; Ruslan (Redmond, WA), Alissa; Husam A. (Snoqualmie, WA), Monroe; Mark Alan (Louisville, CO), James; Sean M. (Olympia, WA)

Applicant: Microsoft Technology Licensing, LLC (Redmond, WA)

Family ID: 1000008778536

Assignee: Microsoft Technology Licensing, LLC (Redmond, WA)

Appl. No.: 18/065254

Filed: December 13, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240206117 A1	Jun. 20, 2024

Publication Classification

Int. Cl.: **H05K7/20** (20060101); **G06F1/20** (20060101); **H01M8/04082** (20160101);
H01M8/04746 (20160101)

U.S. Cl.:

CPC **H05K7/20327** (20130101); **G06F1/206** (20130101); **H01M8/04208** (20130101);
H01M8/04753 (20130101); **H01M8/04776** (20130101); **H05K7/20009** (20130101);
H05K7/20372 (20130101); **H05K7/20381** (20130101); H01M2250/10 (20130101)

Field of Classification Search

CPC: H05K (7/20327); H05K (7/20009); H05K (7/20372); H05K (7/20381); G06F (1/206);
H01M (8/04208); H01M (8/04753); H01M (8/04776); H01M (2250/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10785891	12/2019	Monroe et al.	N/A	N/A
11266038	12/2021	Monroe et al.	N/A	N/A
2012/0216520	12/2011	Chen et al.	N/A	N/A
2013/0163193	12/2012	Ballantine et al.	N/A	N/A
2014/0183957	12/2013	Duchesneau	307/64	F01K 13/006
2019/0320557	12/2018	Christiansen	N/A	H05K 7/1427
2020/0263831	12/2019	Fu	N/A	N/A
2022/0352750	12/2021	Nagimov et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2644508	12/2012	EP	N/A
3346111	12/2017	EP	N/A
3673204	12/2021	EP	N/A
20220036025	12/2021	KR	N/A
20220077777	12/2021	KR	N/A
102560157	12/2022	KR	N/A
20230138230	12/2022	KR	N/A
9942706	12/1998	WO	N/A
2013066558	12/2012	WO	N/A
2013130557	12/2012	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion received for PCT Application No.

PCT/US2023/036971, Feb. 22, 2024, 28 pages. cited by applicant

“Thermal Energy Storage System”, In Book of Thermal Energy Storage Technologies for Sustainability, 2014, 8 Pages. cited by applicant

Huttermann, et al., “Investigation of a Liquid Air Energy Storage (LAES) System with Different Cryogenic Heat Storage Devices”, In Journal of Energy Procedia, vol. 158, Feb. 1, 2019, pp. 4410-4415. cited by applicant

International Preliminary Report on Patentability (Chapter I) received for PCT Application No. PCT/US2023/036971, mailed on Jun. 26, 2025, 22 Pages. cited by applicant

Primary Examiner: Diaz; Miguel A

Attorney, Agent or Firm: Singh Law, PLLC

Background/Summary

BACKGROUND

(1) Datacenter deployment is accelerating in order to meet rising demand for computing, communication, and storage resources. However, efficient scaling of datacenter capacity is being constrained by the traditional power generation architectures used for the distribution, delivery, and

storage of energy. In addition, datacenters face significant costs and inefficiencies related to both power generation and energy storage. In order to meet high availability requirements, uninterruptible power supply (UPS) systems and diesel generators are used for short-term and long-term energy storage, respectively. UPS systems are typically based on traditional rechargeable batteries and therefore have limited life due to their inherent capacity loss because of the charging and discharging cycles. Moreover, diesel generators, which are used for standby power generation, operate at low efficiencies, require regular maintenance, and negatively impact the environment because of the reliance of an external supply of diesel fuel.

(2) Some datacenters are using hydrogen fuel cells for power generation. Such hydrogen fuel cells use liquefied hydrogen, which has a very high energy density, resulting in compact storage systems. However, in traditional liquid hydrogen storage systems, the latent heat of hydrogen vaporization and the sensible heat of cold hydrogen gas are lost as “waste cold.” Thus, there is a need for improved power generation systems for use with modern datacenters.

SUMMARY

(3) In one example, the present disclosure relates to a waste cold recuperation system including a liquefied gas storage for supplying liquefied gas as a coolant to cool a first set of compute resources configurable to operate in a first cryogenic environment within a first temperature range from a first temperature value to a second temperature value higher than the first temperature value, resulting in at least some of the liquid phase of the liquefied gas becoming a vapor phase of the liquefied gas. The waste cold recuperation system may further be configurable to supply at least some of the vapor phase of the liquefied gas as a coolant to cool a second set of compute resources configurable to operate in a second cryogenic environment within a second temperature range from a third temperature value to a fourth temperature value higher than the third temperature value, where the third temperature value is equal to or higher than the second temperature value, resulting in the at least some of the vapor phase of the liquefied gas becoming a super-heated vapor phase of the liquefied gas.

(4) The waste cold recuperation system may further be configurable to supply at least some of the super-heated vapor phase of the liquefied gas as fuel to fuel cells for providing electrical power to a datacenter load including compute resources configurable to operate in a non-cryogenic environment.

(5) In another example, the present disclosure relates to a method for operating a waste cold recuperation system for recovering energy from liquefied gas. The method may include supplying the liquefied gas to a first set of compute resources configurable to operate in a first cryogenic environment within a first temperature range from a first temperature value to a second temperature value higher than the first temperature value, where the liquefied gas is supplied as a coolant to cool the first set of compute resources, resulting in at least some of the liquefied gas becoming a vapor phase of the liquefied gas.

(6) The method may further include supplying at least some of the vapor phase of the liquefied gas to a second set of compute resources configurable to operate in a second cryogenic environment within a second temperature range from a third temperature value to a fourth temperature value higher than the third temperature value, where the third temperature value is equal to or higher than the second temperature value, and where the at least some of the vapor phase of the liquefied gas is supplied as a coolant to cool the second set of compute resources, resulting in the at least some of the vapor phase of the liquefied gas becoming a super-heated vapor phase of the liquefied gas. The method may further include supplying at least some of the super-heated vapor phase of the liquefied gas as fuel to fuel cells for providing electrical power to a datacenter load including compute resources configurable to operate in a non-cryogenic environment.

(7) In yet another example, the present disclosure relates to a waste cold recuperation system including a first set of compute resources configured to operate in a first cryogenic environment within a first temperature range from 20 kelvin to 77 kelvin. The waste cold recuperation system

may further include a second set of compute resources configured to operate in a second cryogenic environment within a second temperature range from 77 kelvin to 100 kelvin.

(8) Liquefied hydrogen may be supplied as a coolant to cool the first set of compute resources, resulting in at least some of the liquefied hydrogen becoming a vapor phase of the liquefied hydrogen. At least the vapor phase of the liquefied hydrogen may be supplied as a coolant to cool the second set of compute resources, resulting in the vapor phase of the liquefied hydrogen becoming a super-heated vapor phase of the liquefied hydrogen. The super-heated vapor phase of the liquefied hydrogen may be fed as fuel to hydrogen fuel cells for providing electrical power to a datacenter load including compute resources configured to operate in a non-cryogenic environment.

(9) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure is illustrated by way of example and is not limited by the accompanying figures, in which like references indicate similar elements. Elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale.

(2) FIG. 1 shows a diagram of one example of waste cold recuperation in a fuel cell based power generation system environment including a datacenter load;

(3) FIG. 2 shows cross-section views of two different vacuum-insulated cryostat segments for use with the fuel cell based power generation system of FIG. 1 in accordance with one example;

(4) FIG. 3 shows a diagram of another example of waste cold recuperation in a fuel cell based power generation system environment including a datacenter load;

(5) FIG. 4 shows a diagram of another example of waste cold recuperation in a fuel cell based power generation system environment including a datacenter load;

(6) FIG. 5 shows a diagram of another example of waste cold recuperation in a fuel cell based power generation system environment including a datacenter load;

(7) FIG. 6 shows a diagram of another example of waste cold recuperation in a fuel cell based power generation system environment including a datacenter load;

(8) FIG. 7 shows a diagram of a control system for use in waste cold recuperation as part of a fuel cell based power generation system in accordance with one example;

(9) FIG. 8 shows a flowchart of a method associated with waste cold recuperation in a fuel cell based power generation system in accordance with one example; and

(10) FIG. 9 shows example dynamic control of waste cold recuperation in a fuel cell based power generation system environment including a datacenter load.

DETAILED DESCRIPTION

(11) Examples described in this disclosure relate to waste cold recuperation in fuel cell based power generation systems for datacenters. As explained earlier, traditional fuel cell based power generation systems for datacenters may use liquefied hydrogen. The liquefied hydrogen is traditionally vaporized and warmed up in a series of ambient vaporizers. A large portion of the liquid hydrogen energy is stored thermally as a cryogen, which is not recovered in such conventional fuel cell based power generation systems. This is because in such systems, the latent heat of hydrogen vaporization and the sensible heat of cold hydrogen gas are lost as waste cold. This constitutes an inefficiency in the energy supply chain for use with datacenter loads since hydrogen liquefaction is an energy-intensive process. Similar inefficiencies occur when liquefied gasses other than hydrogen are used as fuel for the fuel cells. As an example, fuel cells can be fed

methane. Any liquefied gas that requires storage at a low enough temperature, requiring heating prior to being fed as fuel to fuel cells, can be used as part of the waste cold recuperation systems described herein.

(12) To address the inefficiency in the energy supply chain for use with datacenter loads problems, the embodiments of the disclosed systems in this disclosure use cryogenically-cooled technologies (e.g., cryogenically cooled complimentary metal-oxide-semiconductor (CMOS) computing systems, high-temperature superconductors for power transmission, and quantum computing systems) as consumers of the “waste cold.” Various temperature levels associated with the different cryogenically-cooled technologies allow for full utilization of the recuperated waste cold. Thus, the integration of the proposed systems in the context of fuel cell powered datacenters allows for efficient recuperation of waste cold.

(13) FIG. 1 shows a diagram of one example of waste cold recuperation in a fuel cell based power generation system environment **100** including a datacenter load **190**. System environment **100** may include a liquefied hydrogen storage **110**, which may be supplied liquefied hydrogen via a fill port. A transport vehicle **102** for transporting liquefied hydrogen may be coupled to the fill port for receiving liquefied hydrogen for storage as part of liquefied hydrogen storage **110**. Other types of storage, including underground storage may also be used for storing energy in the form of liquefied hydrogen. Moreover, other means for transporting, including pipes, may be used for transporting liquefied hydrogen from another location to liquefied hydrogen storage **110**. As used herein the term “pipe” includes, but is not limited to, any pipe structures, connectors, joints, or other elements that may be used to move any gas, air, or any liquid between at least two or more components. Although not shown in FIG. 1, valves and pumps in combination with pipes may be used to control and regulate the movement and storage of hydrogen in liquefied hydrogen storage **110**. Liquefied hydrogen storage **110** may include both a liquid phase **112** and a vapor phase **114** of hydrogen. In addition, although not shown in FIG. 1, liquefied hydrogen storage **110** may include boil-off gas discharge lines and other mechanisms for ensuring proper operation of liquefied hydrogen storage **110**. Liquefied hydrogen storage **110** may be configured as a vacuum-insulated housing to ensure that the liquid hydrogen is maintained at approximately 20 kelvin with the vacuum having a pressure in a range of 10.sup.-3 Torr to 10.sup.-10 Torr.

(14) With continued reference to FIG. 1, system environment **100** may further include datacenter load **190** which may include compute, storage, and networking resources organized to offer various services via cloud computing models or other service models. Datacenter load **190** may include compute resources organized in groups of resources (e.g., compute resources **192**, compute resources **194**, compute resources **196**, and compute resources **198**). Such compute resources may correspond to racks of servers interconnected via high-speed networks, including high-speed switches and routers. In this example, these compute resources may be powered by hydrogen fuel cells **180**. As an example, without limitation, the compute resources may include at least one of (or any appropriate combination of) a central-processing functionality, a graphics-processing functionality, an artificial-intelligence functionality, a gate-array functionality, a memory functionality, or a bus-interface-management functionality. Datacenter load **190** may further include other equipment powered by hydrogen fuel cells **180**, including datacenter management hardware/software, storage resources, load balancers, networking switches, gateways, power supply units, and other equipment. Storage resources may comprise memory components, including any of non-volatile or volatile memory components. Hydrogen fuel cells **180** may supply power via cables (e.g., DC power lines **182**) to datacenter load **190**, including the compute resources. The compute resources powered by hydrogen fuel cells **180** may be configured to operate in a non-cryogenic environment. As used herein, the term “cryogenic environment” means an environment having a temperature between 20 kelvin to 100 kelvin and having a vacuum with a pressure in a range of 10.sup.-3 Torr to 10.sup.-10 Torr. The term “non-cryogenic environment” means an environment having a temperature above 250 kelvin and having atmospheric pressure.

(15) Still referring to FIG. 1, hydrogen fuel cells **180** may be implemented as proton exchange membrane cells. In one example, such hydrogen fuel cells **180** may include one or more anodes and one or more cathodes arranged around an electrolyte. Hydrogen may be fed as fuel to the anode and air may be fed to the cathode. A catalyst at the anode may separate the hydrogen molecules into protons and electrons. The electrons may create the flow of electricity and thus provide DC power to datacenter load **190**. The protons may migrate through the electrolyte to the cathode and produce water and heat after combining with oxygen. As explained earlier, in traditional use of hydrogen fuel cells, liquefied hydrogen is vaporized using heat and then the warm gaseous hydrogen is fed to fuel cells to generate power.

(16) As shown in FIG. 1, as part of the example system environment **100**, liquid hydrogen storage **110** may be coupled via a vacuum-insulated cryostat segment **120** to a vacuum-insulated cryostat **130** housing compute resources **132** that are configured to operate in a cryogenic environment. In this example, compute resources **132** may be configured to operate in an environment with a temperature of approximately 20 kelvin. Vacuum-insulated cryostat **130** housing compute resources **132** may be coupled via a vacuum-insulated cryostat segment **140** and a portion of another vacuum-insulated cryostat segment **160** to another vacuum-insulated cryostat **150** housing compute resources **152**, which are also configured to operate in a cryogenic environment. In this example, compute resources **152** may operate in an environment with a temperature of approximately 80 kelvin. Vacuum-insulated cryostat **150** may be coupled via vacuum-insulated cryostat segment **160** to hydrogen fuel cells **180** (located outside the cryogenic environment). Although FIG. 1 shows two different types of compute resources (e.g., compute resources **132** and compute resources **152**) that have different cooling requirements, system environment **100** is not limited to just these compute resources with certain cooling requirements. Other types of computing resources having cooling requirements different from the compute resources described herein may also be incorporated into system environment **100**. As an example, such compute resources may operate in a cryogenic environment having different temperature ranges than described with respect to compute resources **132** and compute resources **152**. Moreover, the temperature of the cryogenic environment for compute resources **152** can vary if compute resources **132** begin to consume more energy than originally anticipated. As a result, the temperature associated with the vapor phase of the liquefied gas can increase. As explained later, such variations in the temperature of the vapor phase can be sensed and then controlled by increasing or decreasing the flow rate of the liquefied gas. As an example, liquefied gas may be provided at a higher flow rate to compensate for the higher consumption of energy by compute resources **132** until the temperature associated with the cryogenic environment for compute resources **152** reaches the desired operating range or value. Other sources of cooling for compute resources **152** can also be deployed in certain circumstances.

(17) With continued reference to FIG. 1, the power generated by hydrogen fuel cells **180** may be supplied to the various compute resources via different types of DC power lines, depending on whether the compute resources are cold-compute resources or not. As an example, hydrogen fuel cells **180** may generate power that may be coupled via a set of DC power lines **182**, which are configured to operate at an ambient temperature, to compute resources in datacenter load **190**. Hydrogen fuel cells **180** may further be coupled via other types of DC power lines to compute resources **132** and compute resources **152** operating in the cryogenic environment. In one example, high-temperature superconductors-based interconnects may be used as DC power lines (e.g., DC power line **142**) to supply power to compute resources **132** and **152**. The HTS-based interconnects may include a high-temperature superconductor layer formed over a substrate layer. Any portions of the HTS-based interconnects coupled to a warm DC power line may further include a metallic layer. The substrate layer may be formed using yttria-stabilized zirconia (YSZ) or as a polyimide film, such as Kapton. YSZ may be coated on a glass substrate or another type of substrate to form the substrate layer. The high-temperature superconductor layer may be formed using certain copper oxides or rare-earth (Re) metal compounds. As an example, the high-temperature superconductor

layer may be formed using yttrium barium copper oxides (YBCOs), bismuth strontium calcium copper oxides (BSCCOs), or rare-earth metal oxides (REBCOs). The metallic layer may be formed using gold (Au), silver (Ag), or copper (Cu). Other appropriate combinations of materials may also be used to form the cold DC power lines that are used to interconnect the cold compute resources. (18) At least some of the liquefied hydrogen when used for cooling compute resources **132** boils and its phase changes from a liquid phase **136** to a vapor phase **138**. The vapor phase **138** is then used to cool compute resources **152**, which results in further warming up of the vapor phase **138** resulting in super-heated vapor phase **156**. Depending on the amount of warming caused as a result of the cooling, the super-heated vapor phase **156** may reach an ambient temperature. If it does, then the super-heated vapor phase **156** of the liquefied hydrogen is fed as fuel to hydrogen fuel cells **180**. Alternatively, in some circumstances, the super-heated vapor phase **156** may require further warming up to bring its temperature up to the ambient temperature before feeding the hydrogen gas as fuel to the fuel cells. Table 1 below shows an example calculation for one way of determining the amount of cooling, which otherwise would have been wasted, that can be provided to compute resources **132** and compute resources **152**, respectively. This example assumes that compute resources **132** that are removing heat from the saturated liquid phase of hydrogen are operating in a cryogenic environment at a temperature of 20 kelvin and that compute resources **152** that are removing heat from the saturated vapor phase of hydrogen are operating in a cryogenic environment at a temperature of 80 kelvin. In the example calculation shown below, the 20 kelvin temperature is referred to as LH2 temperatures and the 80 kelvin temperature is referred to as HTS temperatures.

(19) TABLE-US-00001 TABLE 21 Constants kJ := 1000 J, MJ := 10^{sup.6} J Atmospheric Pressure and p.sub.atm := 101325 Pa Temperature (ATM) T.sub.env := 300 K HTS Temperature T.sub.HTS := 80 K Density of the Saturated Vapor (SV) Phase of Hydrogen at ATM

$$\begin{aligned}
 H_{2.SV} &:= H_{2.SV} \cdot \text{calc} = 1.332 \frac{\text{kg}}{\text{m}^3} \text{ Enthalpy of the SV Phase of Hydrogen at ATM} \\
 h_{H2.SV} &:= h_{H2.SV} \cdot \text{calc} = 0.449 \frac{\text{MJ}}{\text{kg}} \text{ Density of the Saturated Liquid (SL) Phase of Hydrogen at ATM} \\
 H_{2.SL} &:= H_{2.SL} \cdot \text{calc} = 70.848 \frac{\text{kJ}}{\text{m}^3} \text{ Enthalpy of the SL Phase of Hydrogen at ATM} \\
 h_{H2.SL} &:= h_{H2.SL} \cdot \text{calc} = 3.715 \times 10^{-12} \frac{\text{MJ}}{\text{kg}} \text{ Temperature of the SL Phase of Hydrogen at ATM} \\
 T_{H2.SL} &:= h_{H2.SL} \cdot \text{calc} = 20.369 \frac{\text{MJ}}{\text{kg}} \text{ Latent Heat of Hydrogen at ATM} \\
 r_{H2} &:= h_{H2.SV} - h_{H2.SL} = 0.449 \frac{\text{MJ}}{\text{kg}} \text{ Enthalpy of Hydrogen at ATM} \\
 h_{H2.atm} &:= h_{H2.atm} \cdot \text{calc} = 3.958 \times 10^3 \cdot \text{Math.} \frac{\text{kJ}}{\text{kg}} \text{ Enthalpy of Hydrogen at HTS Temperature} \\
 h_{H2.BTS} &:= h_{H2.BTS} \cdot \text{calc} = 1.085 \frac{\text{MJ}}{\text{kg}} \text{ Hydrogen Energy Density} \\
 e_{H2} &:= 120 \frac{\text{MJ}}{\text{kg}} \cdot \text{Math.} 60\% = 72 \cdot \text{Math.} \frac{\text{MJ}}{\text{kg}} \text{ Cooling Available at the Liquefied Hydrogen} \\
 &\quad h_{H2.SB} - \\
 \text{Temperatures } 0 &\frac{h_{H2.SL}}{e_{H2}} = 0.623\% \text{ Cooling Available at the HTS Temperatures} \\
 \frac{h_{H2.HTS} - h_{H2.SV}}{e_{H2}} &= 0.884\%
 \end{aligned}$$

(20) In the context of table 1, some of the calculations include values that have been sourced from a database to ensure precision and accuracy. In the above table, enthalpy of hydrogen for calculation purposes is defined in a manner that the enthalpy value of hydrogen is approximately zero when hydrogen is at the atmospheric pressure and in a super-heated (e.g., boiling) condition. Latent heat in this calculation is the difference between the enthalpy of the saturated liquid phase of hydrogen and the saturated vapor phase of hydrogen. Enthalpy corresponds to the combination of the potential energy and the kinetic energy of the hydrogen molecules. In sum, enthalpy is a parameter that relates to the total usable internal energy of a gas like hydrogen at a certain temperature. The latent heat value in this example shows the amount of energy needed for converting 1 kilogram of liquefied hydrogen from the liquid phase to the vapor phase. Once the hydrogen energy density has been calculated, the cooling available at liquid hydrogen temperatures and the cooling available at

the HTS temperatures can be calculated as shown in the bottom two rows of table 1 above. From these equations, one can correlate the amount of waste cold recuperation for the respective compute resources (e.g., compute resources **132** and compute resources **152**) in relation to the amount of power generated by the hydrogen fuel cells.

(21) In other words, the percentages in the bottom two rows of table 1 above indicate how much cooling a given amount of hydrogen produces, while traversing through the system, as a fraction of energy produced by the hydrogen fuel cells when they are fed that same given amount of hydrogen. These percentages allow datacenter designers to ensure proper operation because the amount of deployed power that is consumed by the datacenter load is measured in megawatts. The calculations above indicate that a datacenter load will consume approximately 98% of all the power that hydrogen fuel cells produce. To maintain the balance and equilibrium of power, the cooling capacities of the compute resources (e.g., compute resources **132** and compute resources **152**) are expressed as a percentage of the power produced by the hydrogen fuel cells. This allows one to calculate the maximum amount of power that can be delivered to the cold compute resources (e.g., compute resources **132** and compute resources **152**) without disturbing the equilibrium. Thus, in system environment **100**, compute resources **132** (operating in a cryogenic environment having a temperature of 20 kelvin) could consume up to approximately 0.6% of the total power generated by the hydrogen fuel cells (e.g., hydrogen fuel cells **180**) and compute resources **152** (operating in a cryogenic environment having a temperature of 80 kelvin) could consume up to approximately 0.8% of the total power generated by the hydrogen fuel cells. All of the remaining power is routed to the datacenter load **190**.

(22) Still referring to FIG. **1**, vacuum-insulated cryostat **130** may include a fiber-optic feed-through **134** for optical communication between compute resources **132** and one or more of compute resources **192**, compute resources **194**, compute resources **196**, and compute resources **198** via optical network **162**. Similarly, vacuum-insulated cryostat **150** may include a fiber-optic feed-through **154** for optical communication between compute resources **152** and one or more of compute resources **192**, compute resources **194**, compute resources **196**, and compute resources **198** via optical network **162**. Fiber-optic feed-throughs may allow the coupling of optical fibers carrying signals from (or to) the cryogenic environment to (or from) the non-cryogenic environment. Fiber-optic feed-throughs may provide optical sub-systems and a vacuum seal such that the two environments can exchange signals without compromising the low pressure and the lower temperatures in the cryogenic environment.

(23) Although FIG. **1** shows a certain number of components of system environment **100** arranged in a certain manner, there could be more or fewer number of components arranged differently. As an example, although not shown in FIG. **1**, system environment **100** may include circulation pumps, temperature sensors, pressure sensors, level sensors, liquid/vapor fraction sensors, valves, pressure actuators, and/or other components, as needed. In addition, as described later with respect to FIG. **7** a control system may be used to control these components based on telemetry from the various sensors. The control system may provide set point values or other control information to enable control of system environment **100**. Moreover, instead of hydrogen, the fuel cells can be fed methane. Any liquefied gas that requires storage at a low enough temperature, requiring heating prior to being fed as fuel to fuel cells, can be used as part of the waste cold recuperation systems described herein. Another example of such liquefied gas is liquefied natural gas (LNG) and variants thereof. Moreover, compute resources **130** may be configured to operate at other temperatures, as well, as long as those temperatures are below both the ambient temperature and the temperature associated with compute resources **152**. In sum, as long as there is a certain thermal hierarchy in terms of the temperature of the cold liquefied gas to the temperature of the super-heated vapor phase of the gas fed as fuel to the fuel cells in a system environment **100** of FIG. **1** or the like, waste cold can be recuperated.

(24) FIG. **2** shows cross-section views of two different vacuum-insulated cryostat segments for use

with the fuel cell based power generation system of FIG. 1 in accordance with one example. Cross-section view **200** corresponds to a view of a cross-section of vacuum-insulated cryostat segment **120** along line AA-AA as shown in FIG. 1. Cross-section view **200** shows a cross-section of vacuum insulation layer **202**. Cross-section view **200** further shows a cross-section of a pipe **214** that acts as a return line for the hydrogen vapor. Cross-section view **200** further shows a cross-section of a pipe **212** that is used to supply liquid hydrogen. In addition, cross-section view **200** shows a cross-section of a high-temperature superconducting DC power cable **216**. As explained earlier, such a high-temperature superconducting DC power cable may be implemented using HTS-based interconnects.

(25) With continued reference to FIG. 2, cross-section view **250** corresponds to a view of a cross-section of vacuum-insulated cryostat segment **160** along line BB-BB as shown in FIG. 1. Cross-section view **250** shows a cross-section of vacuum insulation layer **252**. Cross-section view **250** further shows a cross-section of a pipe **264** that acts as a return line for the hydrogen vapor. Cross-section view **250** further shows a cross-section of a pipe **274** that also acts as a return line for the hydrogen vapor. In addition, cross-section view **250** shows a cross-section of a high-temperature superconducting DC power cable **262** enclosed by pipe **264** and a cross-section of another high-temperature superconducting DC power cable **272** enclosed by pipe **274**. As explained earlier, such high-temperature superconducting DC power cables may be implemented using HTS-based interconnects. Although FIG. 2 shows a certain number of components of the vacuum-insulated cryostat segments that are arranged in a certain manner, there could be more or fewer number of components arranged differently.

(26) FIG. 3 shows a diagram of another example of waste cold recuperation in a fuel cell based power generation system environment **300** including a datacenter load **190**. System environment **300** includes similar components as described earlier with respect to system environment **100** of FIG. 1. In those instances where the components are identical or substantially similar with respect to FIG. 1 and FIG. 3, the same reference numbers as used in FIG. 1 are used in FIG. 3. Accordingly, those components are not described in detail again with respect to system environment **300**. This example of waste cold recuperation in a fuel cell based power generation system environment **300** includes a superconducting magnetic energy storage (SMES) system **310**, which is also passively cooled by the waste cold. SMES system **310** includes a superconductor coil **320**, which is configured to store energy in the form of a magnetic field generated by the current flowing in superconductor coil **320**. The stored energy can be released by discharging the coil. In one example, the coil may be made of niobium-titanium (NbTi) alloy-based filaments. Other combinations of materials may also be used. SMES system **310** is configured to receive power generated by the fuel cells (e.g., hydrogen fuel cells **180**) and discharge the stored energy to power datacenter load **190**. Although FIG. 3 shows a certain number of components of system environment **300** arranged in a certain manner, there could be more or fewer number of components arranged differently.

(27) FIG. 4 shows a diagram of another example of waste cold recuperation in a fuel cell based power generation system environment **400** including a datacenter load **190**. System environment **400** includes similar components as described earlier with respect to system environment **100** of FIG. 1 and system environment **300** of FIG. 3. In those instances where the components are identical or substantially similar with respect to FIGS. 1 and 3 and FIG. 4, the same reference numbers as used in FIG. 1 and FIG. 3 are used in FIG. 4. Accordingly, those components are not described in detail again with respect to system environment **400**. This example of waste cold recuperation in a fuel cell based power generation system environment **400** includes additional liquefied nitrogen (LN.sub.2)-cooled compute resources that are cooled via a heat-exchanger coupled with liquefied hydrogen storage **110**. In this example, a vacuum-insulated cryostat **410** is coupled to liquefied hydrogen storage **110** via a vacuum-insulated cryostat segment **420**. Vacuum-insulated cryostat **410** includes liquefied nitrogen (LN.sub.2) **412** and gaseous nitrogen (GN.sub.2)

Liquefied nitrogen (LN.sub.2) **412** is used to cool compute resources **432** and **434**. Liquefied nitrogen (LN.sub.2) **412** is cooled by the liquefied hydrogen using a heat-exchanger **450**. This allows additional extraction of waste cold from the liquefied hydrogen. As shown in FIG. 4, some of the liquefied nitrogen (LN.sub.2) **412** changes from the liquid phase to a vapor phase and becomes gaseous nitrogen (GN.sub.2) **414**. Although FIG. 4 shows a certain number of components of system environment **400** arranged in a certain manner, there could be more or fewer number of components arranged differently.

(28) FIG. 5 shows a diagram of another example of waste cold recuperation in a fuel cell based power generation system environment **500** including a datacenter load **190**. System environment **500** includes similar components as described earlier with respect to system environment **100** of FIG. 1 and system environment **300** of FIG. 3. In those instances where the components are identical or substantially similar with respect to FIGS. 1 and 3 and FIG. 5, the same reference numbers as used in FIG. 1 and FIG. 3 are used in FIG. 5. Accordingly, those components are not described in detail again with respect to system environment **500**. This example of waste cold recuperation in a fuel cell based power generation system environment **500** includes additional liquefied natural gas (methane (LCH.sub.4))-cooled compute resources that are cooled via a heat-exchanger coupled with liquefied hydrogen storage **110**. In this example, a vacuum-insulated cryostat **510** is coupled to liquefied hydrogen storage **110** via a vacuum-insulated cryostat segment **520**. Vacuum-insulated cryostat **510** includes liquefied natural gas (methane (LCH.sub.4)) **512** and gaseous natural gas (methane (GCH.sub.4)) **514**. Liquefied methane (LCH.sub.4) **512** is used to cool compute resources **532** and **534**. Liquefied methane (LCH.sub.4) **512** is cooled by the liquefied hydrogen using a heat-exchanger **550**. This allows additional extraction of waste cold from the liquefied hydrogen. As shown in FIG. 5, some of the liquefied methane (LCH.sub.4) **512** changes from the liquid phase to a vapor phase and becomes gaseous natural gas (methane (GCH.sub.4)) **514**. Although FIG. 5 shows a certain number of components of system environment **500** arranged in a certain manner, there could be more or fewer number of components arranged differently.

(29) FIG. 6 shows a diagram of another example of waste cold recuperation in a fuel cell based power generation system environment **600** including a datacenter load **190**. System environment **600** includes similar components as described earlier with respect to system environment **100** of FIG. 1, system environment **300** of FIG. 3, and system environment **400** of FIG. 4. In those instances where the components are identical or substantially similar with respect to FIGS. 1, 3, and 4 and FIG. 6, the same reference numbers as used in FIGS. 1, 3, and 4 are used in FIG. 6. Accordingly, those components are not described in detail again with respect to system environment **600**. This example of waste cold recuperation in a fuel cell based power generation system environment **600** includes additional cold compute that is cooled by the vapor phase of liquefied hydrogen. This allows additional extraction of waste cold from the liquefied hydrogen. (30) In this example, the vacuum-insulated cryostat segment **140** of FIG. 1 is extended to allow for the connection with another vacuum-insulated cryostat segment **660**. Vacuum-insulated cryostat segment **660** may be coupled to vacuum-insulated cryostat **650** housing compute resources **652**. Compute resources **652** may be configured to operate in a cryogenic environment within a temperature range similar to the compute resources **152** of FIG. 1. As explained earlier with respect to FIG. 1, at least some of the liquefied hydrogen when used for cooling compute resources **132** boils and its phase changes from a liquid phase **136** to a vapor phase **138**. The vapor phase **138** is then used to cool compute resources **652** in a similar manner as it is used to cool compute resources **152**. Vacuum-insulated cryostat **650** may include a fiber-optic feed-through **654** for optical communication between compute resources **652** and one or more of compute resources **192**, compute resources **194**, compute resources **196**, and compute resources **198** via optical network **162**. Although FIG. 6 shows a certain number of components of system environment **600** arranged in a certain manner, there could be more or fewer number of components arranged differently.

(31) FIG. 7 shows a diagram of an example control system **700** for use in waste cold recuperation as part of the fuel cell based power generation systems described with respect to FIGS. 1-6. As an example, control system **700** may allow for the implementation of control actions associated with sensing and controlling circulation pumps, temperature sensors, pressure sensors, level sensors, flow sensors, liquid/vapor fraction sensors, valves, pressure actuators, and/or other components of the systems described herein, as needed. Control system **700** may include a processor(s) **702**, I/O component(s) **704**, memory **706**, presentation component(s) **708**, sensors **710**, database(s) **712**, networking interfaces **714**, and I/O port(s) **716**, which may be interconnected via one or more bus systems **720**.

(32) Processor(s) **702** may execute instructions stored in memory **706**. Processor(s) **702** may include CPUs, GPUs, ASICs, FPGAs, PLCs, DDCs, or other types of logic configured to execute instructions. I/O component(s) **704** may include components such as a keyboard, a mouse, a voice recognition processor, or touch screens. Memory **706** may be any combination of non-volatile storage or volatile storage (e.g., flash memory, DRAM, SRAM, ferro-magnetic memories, superconducting memories, or other types of memories). Presentation component(s) **708** may include displays, holographic devices, or other presentation devices. Displays may be any type of display, such as LCD, LED, or other types of display. Sensor(s) **710** may include telemetry or other types of sensors configured to detect, and/or receive, information (e.g., conditions associated with the components in the system environments described herein). Sensor(s) **710** may include sensors configured to sense conditions associated with the various components of the system environments described herein, such as system environment **100** of FIG. 1. As an example, sensors **710** may include temperature sensors, pressure sensors, level sensors, flow sensors, liquid/vapor fraction sensors, voltage sensors, current sensors, and other sensors needed to operate the systems and methods associated with waste cold recuperation in a safe and efficient manner.

(33) Still referring to FIG. 7, database(s) **712** may be used to store any of the data or files as needed for the performance of methods described herein. Database(s) **712** may be implemented as a collection of distributed databases or as a single database. Network interface(s) **714** may include communication interfaces, such as Ethernet, cellular radio, Bluetooth radio, UWB radio, or other types of wireless or wired communication interfaces. I/O port(s) **716** may include Ethernet ports, Fiber-optic ports, wireless ports, or other communication ports.

(34) Instructions corresponding to various control and management aspects related to waste cold recuperation and the system environments described herein may be stored in memory **706** or another memory. These instructions when executed by processor(s) **702**, or other processors, may provide at least some of the control and management functionality associated with the systems described herein. Other control functionality may be implemented using dedicated controllers and other lower level control systems. The instructions could be encoded as hardware or software that may be stored in memory **706**. Indeed, the functionality associated with control system **700** may be implemented using any appropriate combination of hardware, software, or firmware. Although FIG. 7 shows control system **700** as including a certain number of components arranged and coupled in a certain way, it may include fewer or additional components arranged and coupled differently. In addition, the functionality associated with control system **700** may be distributed or combined, as needed.

(35) FIG. 8 shows a flowchart **800** of a method associated with waste cold recuperation in a fuel cell based power generation system in accordance with one example. The various steps shown as part of flowchart **800** may be executed by in the system environments described earlier with respect to FIGS. 1 and 2-6 by at least the instructions associated with control system **700** described earlier. Other control functionality may be implemented using dedicated controllers and other lower level control systems. Step **810** may include supplying liquefied gas to a first set of compute resources configurable to operate in a first cryogenic environment within a first temperature range from a first temperature value to a second temperature value higher than the first temperature value, where

the liquefied gas is supplied as a coolant to cool the first set of compute resources, resulting in at least some of the liquefied gas becoming a vapor phase of the liquefied gas. As explained earlier with respect to FIGS. 1-7, any of the systems environments **100** and **300-600** may include components to allow for the execution of this step. As an example, with respect to system environment **100** of FIG. 1, liquefied gas may be liquefied hydrogen that may be supplied to compute resources **132** that are configured to operate in a cryogenic environment. Liquefied hydrogen may be used to cool these compute resources, resulting in some of the liquefied hydrogen becoming a vapor phase of the liquefied hydrogen. As explained earlier, aside from hydrogen other gasses, such as LNG may be used.

(36) Step **820** may include supplying at least some of the vapor phase of the liquefied gas to a second set of compute resources configurable to operate in a second cryogenic environment within a second temperature range from a third temperature value to a fourth temperature value higher than the third temperature value, wherein the third temperature value is equal to or higher than the second temperature value, and wherein the at least some of the vapor phase of the liquefied gas is supplied as a coolant to cool the second set of compute resources, resulting in the at least some of the vapor phase of the liquefied gas becoming a super-heated vapor phase of the liquefied gas. As explained earlier with respect to FIGS. 1-7, any of the systems environments **100** and **300-600** may include components to allow for the execution of this step. As an example, with respect to system environment **100** of FIG. 1, the vapor phase of the liquefied gas may be the vapor phase of the liquefied hydrogen that may be supplied to compute resources **152** that are configured to operate in a cryogenic environment. The vapor phase of the hydrogen may be used to cool these compute resources, resulting in the vapor phase of the liquefied hydrogen becoming a super-heated vapor phase of the liquefied hydrogen. As explained earlier, aside from hydrogen other gasses, such as LNG may be used.

(37) Step **830** may include supplying at least some of the super-heated vapor phase of the liquefied gas as fuel to fuel cells for providing electrical power to a datacenter load including compute resources configurable to operate in a non-cryogenic environment. As explained earlier with respect to FIGS. 1-7, any of the systems environments **100** and **300-600** may include components to allow for the execution of this step. As an example, with respect to system environment **100** of FIG. 1, the super-heated vapor phase of the liquefied gas may be the super-heated vapor phase of the liquefied hydrogen that may be fed as fuel to the hydrogen fuel cells for providing electrical power to a datacenter load **190** of FIG. 1, including compute resources configured to operate in a non-cryogenic environment. As explained earlier, unlike the waste cold recuperation systems and methods described herein, liquefied hydrogen is traditionally vaporized and warmed up in a series of ambient vaporizers. As a result, a large portion of the liquid hydrogen energy that is stored thermally as a cryogen is not recovered. This is because in such systems, the latent heat of hydrogen vaporization and the sensible heat of cold hydrogen gas are lost as waste cold. This constitutes an inefficiency in the energy supply chain for use with datacenter loads since hydrogen liquefaction is an energy-intensive process. The method described with respect to flow chart **800** of FIG. 8 alleviates some of these inefficiencies by operating the waste cold recuperation system for recovering energy from the liquefied hydrogen before it is fed as fuel to the fuel cells used for powering the datacenter load.

(38) FIG. 9 shows example dynamic control of waste cold recuperation in a fuel cell based power generation system environment including a datacenter load. This example of dynamic control relates to the waste cold recuperation in a fuel cell based power generation system described with respect to system environment **600** of FIG. 6. As an example, the various control and sensing operations associated with this example can be performed using control system **700** of FIG. 7. As shown in box **904**, the total power consumption in the system environment by the various loads is determined based on the total power consumed by datacenter load **190** of FIG. 6 (box **902**) and the power consumed by the various cold compute resources in system environment **600** of FIG. 6. In

this example, such power consumption includes the power consumption of compute resources **132** of FIG. **6** (box **912**), the power consumption of compute resources **152** of FIG. **6** (box **914**), and the power consumption of compute resources **652** of FIG. **6** (box **916**).

(39) With continued reference to FIG. **9**, the power consumption of the warm compute resources (e.g., compute resources associated with datacenter load **190** of FIG. **6**) and the cold compute resources (e.g., compute resources **132**, **152**, and **652** of FIG. **6**) can then be used to either calculate or look up the corresponding flow rate (e.g., mass flow rate) required to cool the respective warm and cold compute resources. As an example, calculation **1** shown in the box labeled as LEGEND can be used to determine the amount of liquefied gas (e.g., LH.sub.2) that is required to generate the given amount of power for the fuel cells. That amount can then be translated into a mass flow rate using a calculation or by looking up a table or another data structure. In this example, the required LH.sub.2 mass flow rate required to be supplied as fuel to the fuel cells (e.g., hydrogen fuel cells **180** of FIG. **6**) is labeled as A (box **906**). Similarly, using calculation **2** shown in the box labeled as LEGEND can be used to determine the amount of liquefied gas (e.g., LH.sub.2) that is required to cool compute resources **132** of FIG. **6** (e.g., by extracting the cold waste associated with latent heat from the liquefied gas). That amount can then be translated into a mass flow rate using a calculation or by looking up a table or another data structure. In this example, the required LH.sub.2 mass flow rate to cool compute resources **132** of FIG. **6** is labeled as B (box **922**).

Similarly, using calculation **3** shown in the box labeled as LEGEND can be used to determine the amount of liquefied gas (e.g., LH.sub.2) that is required to cool compute resources **152** of FIG. **6** (e.g., by extracting the cold waste associated with sensible heat from the liquefied gas). That amount can then be translated into a mass flow rate using a calculation or by looking up a table or another data structure. In this example, the required LH.sub.2 mass flow rate to cool compute resources **152** of FIG. **6** is labeled as C (box **924**). Finally, using calculation **4** shown in the box labeled as LEGEND can be used to determine the amount of liquefied gas (e.g., LH.sub.2) that is required to cool compute resources **652** of FIG. **6** (e.g., by extracting the cold waste associated with sensible heat from the liquefied gas). That amount can then be translated into a mass flow rate using a calculation or by looking up a table or another data structure. In this example, the required LH.sub.2 mass flow rate to cool compute resources **652** of FIG. **6** is labeled as D (box **926**).

(40) Still referring to FIG. **9**, the box labeled as DYNAMIC CONTROL shows example control logic that can be used for dynamically modifying the load presented by the cold compute resources to ensure a sufficient amount of fuel being supplied to datacenter load **190** of FIG. **6**. Modifications of the load presented by such compute resources may be accomplished by taking some of the cold compute resources offline, such that they are no longer operational. Alternatively, the load may be reduced by throttling the output of such cold compute resources. In one example, the control logic associated with the dynamic control may be implemented using control system **700** of FIG. **7**. Such control may allow for both fully automatic control, partially automatic control, or manual control. As an example, software or other instructions for implementing the dynamic control may reduce or increase load based on the values associated with respective mass flow rates. As an example, if the mass flow rate B is greater than the mass flow rate A, then the load associated with compute resources **132** of FIG. **6** may be reduced. Alternatively, if the mass flow rate B is lower than mass flow rate A, then the load associated with compute resources **132** of FIG. **6** may be increased, as needed. As another example, if the mass flow rate C is greater than the mass flow rate A, then the load associated with compute resources **152** of FIG. **6** may be reduced. Alternatively, if the mass flow rate C is lower than mass flow rate A, then the load associated with compute resources **152** of FIG. **6** may be increased, as needed. As yet another example, if the mass flow rate D is greater than the mass flow rate A, then the load associated with compute resources **652** of FIG. **6** may be reduced. Alternatively, if the mass flow rate D is lower than mass flow rate A, then the load associated with compute resources **652** of FIG. **6** may be increased, as needed. Similar dynamic control may be implemented with respect to any of the system environments described herein,

including system environment **100** of FIG. **1**, system environment **300** of FIG. **3**, system environment **400** of FIG. **4**, and system environment **500** of FIG. **5**. Although FIG. **9** describes a specific example of dynamic control for varying the load in response the mass flow rate, other types of dynamic control may also be implemented. As an example, the mass flow rates may be varied based on the changes in the load or the expected changes in the load.

(41) In conclusion, in one example, the present disclosure relates to a waste cold recuperation system including a liquefied gas storage for supplying liquefied gas as a coolant to cool a first set of compute resources configurable to operate in a first cryogenic environment within a first temperature range from a first temperature value to a second temperature value higher than the first temperature value, resulting in at least some of the liquid phase of the liquefied gas becoming a vapor phase of the liquefied gas. The waste cold recuperation system may further be configurable to supply at least some of the vapor phase of the liquefied gas as a coolant to cool a second set of compute resources configurable to operate in a second cryogenic environment within a second temperature range from a third temperature value to a fourth temperature value higher than the third temperature value, where the third temperature value is equal to or higher than the second temperature value, resulting in the at least some of the vapor phase of the liquefied gas becoming a super-heated vapor phase of the liquefied gas.

(42) The waste cold recuperation system may further be configurable to supply at least some of the super-heated vapor phase of the liquefied gas as fuel to fuel cells for providing electrical power to a datacenter load including compute resources configurable to operate in a non-cryogenic environment. The waste cold is related to the latent heat associated with a change in the form of the liquefied gas from a liquid phase to a vapor phase. The waste cold is further related to the sensible heat associated with a heating of the vapor phase of the liquefied gas to the super-heated vapor phase of the liquefied gas.

(43) The liquefied gas storage may be configured as a vacuum-insulated housing. The liquefied gas storage may be coupled via a first segment of a vacuum-insulated cryostat to the first set of compute resources. The first set of compute resources may be coupled via a second segment of the vacuum-insulated cryostat to the second set of compute resources. The second set of compute resources may be coupled via a third segment of the vacuum-insulated cryostat to a pipe for supplying the super-heated vapor phase of the liquefied gas to the fuel cells.

(44) The waste cold recuperation system may further be configurable to dynamically control an amount of the liquefied gas being supplied as the coolant in order to ensure a sufficient amount of fuel is being supplied to the fuel cells for providing the electrical power to the datacenter load including the compute resources configurable to operate in the non-cryogenic environment. In this example, the first set of compute resources may comprise at least quantum computing resources, and the second set of compute resources may comprise at least complimentary metal-oxide-semiconductor (CMOS) computing systems.

(45) In another example, the present disclosure relates to a method for operating a waste cold recuperation system for recovering energy from liquefied gas. The method may include supplying the liquefied gas to a first set of compute resources configurable to operate in a first cryogenic environment within a first temperature range from a first temperature value to a second temperature value higher than the first temperature value, where the liquefied gas is supplied as a coolant to cool the first set of compute resources, resulting in at least some of the liquefied gas becoming a vapor phase of the liquefied gas.

(46) The method may further include supplying at least some of the vapor phase of the liquefied gas to a second set of compute resources configurable to operate in a second cryogenic environment within a second temperature range from a third temperature value to a fourth temperature value higher than the third temperature value, where the third temperature value is equal to or higher than the second temperature value, and where the at least some of the vapor phase of the liquefied gas is supplied as a coolant to cool the second set of compute resources,

resulting in the at least some of the vapor phase of the liquefied gas becoming a super-heated vapor phase of the liquefied gas. The method may further include supplying at least some of the super-heated vapor phase of the liquefied gas as fuel to fuel cells for providing electrical power to a datacenter load including compute resources configurable to operate in a non-cryogenic environment.

(47) The waste cold is related to the latent heat associated with a change in the form of the liquefied gas from a liquid phase to a vapor phase. The waste cold is further related to the sensible heat associated with a heating of the vapor phase of the liquefied gas to the super-heated vapor phase of the liquefied gas.

(48) A liquefied gas storage may be configured to store the liquefied gas, and the liquefied gas storage may be configured as a vacuum-insulated housing. The liquefied gas storage may be coupled via a first segment of a vacuum-insulated cryostat to the first set of compute resources configured to operate in the first cryogenic environment. The first set of compute resources, configured to operate in the first cryogenic environment, may be coupled via a second segment of the vacuum-insulated cryostat to the second set of compute resources configured to operate in the second cryogenic environment. The second set of compute resources, configured to operate in the second cryogenic environment, may be coupled via a third segment of the vacuum-insulated cryostat to the hydrogen fuel cells. In this example, the first set of compute resources may comprise at least quantum computing resources, and the second set of compute resources may comprise at least complimentary metal-oxide-semiconductor (CMOS) computing systems.

(49) In yet another example, the present disclosure relates to a waste cold recuperation system including a first set of compute resources configured to operate in a first cryogenic environment within a first temperature range from 20 kelvin to 77 kelvin. The waste cold recuperation system may further include a second set of compute resources configured to operate in a second cryogenic environment within a second temperature range from 77 kelvin to 100 kelvin.

(50) Liquefied hydrogen may be supplied as a coolant to cool the first set of compute resources, resulting in at least some of the liquefied hydrogen becoming a vapor phase of the liquefied hydrogen. At least the vapor phase of the liquefied hydrogen may be supplied as a coolant to cool the second set of compute resources, resulting in the vapor phase of the liquefied hydrogen becoming a super-heated vapor phase of the liquefied hydrogen. The super-heated vapor phase of the liquefied hydrogen may be fed as fuel to hydrogen fuel cells for providing electrical power to a datacenter load including compute resources configured to operate in a non-cryogenic environment.

(51) The waste cold is related to the latent heat associated with a change in the form of the liquefied hydrogen from a liquid phase to a vapor phase. The waste cold is further related to the sensible heat associated with a heating of the vapor phase of the liquefied hydrogen to the super-heated vapor phase of the liquefied hydrogen.

(52) A liquefied hydrogen storage may be configured to store the liquefied hydrogen and supply the liquefied hydrogen, where the liquefied hydrogen storage is configured as a vacuum-insulated housing. The liquefied hydrogen storage may be coupled via a first segment of a vacuum-insulated cryostat to the first set of compute resources configured to operate in the first cryogenic environment. The first set of compute resources, configured to operate in the first cryogenic environment, may be coupled via a second segment of the vacuum-insulated cryostat to the second set of compute resources configured to operate in the second cryogenic environment. The second set of compute resources, configured to operate in the second cryogenic environment, may be coupled via a third segment of the vacuum-insulated cryostat to the hydrogen fuel cells.

(53) The waste cold recuperation system may further include a superconducting magnetic energy storage (SMES) system, which is also cooled using the waste cold. The waste cold recuperation system may further include a third set of compute resources, configured to operate in a cryogenic environment, that is cooled using liquefied nitrogen coupled to the liquefied hydrogen via a heat exchanger. Alternatively, or additionally, the waste cold recuperation system may further include

yet another set of compute resources, configured to operate in a cryogenic environment, that is cooled using liquefied natural gas coupled to the liquefied hydrogen via a heat exchanger.

(54) It is to be understood that the methods, modules, and components depicted herein are merely exemplary. Alternatively, or in addition, the functionality described herein can be performed, at least in part, by one or more hardware logic components. For example, and without limitation, illustrative types of hardware logic components that can be used include Field-Programmable Gate Arrays (FPGAs), Application-Specific Integrated Circuits (ASICs), Application-Specific Standard Products (ASSPs), System-on-a-Chip systems (SOCs), Complex Programmable Logic Devices (CPLDs), Programmable Logic Controllers (PLCs), etc. In an abstract, but still definite sense, any arrangement of components to achieve the same functionality is effectively “associated” such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as “associated with” each other such that the desired functionality is achieved, irrespective of architectures or inter-medial components. Likewise, any two components so associated can also be viewed as being “operably connected,” or “coupled,” to each other to achieve the desired functionality. Merely because a component, which may be an apparatus, a structure, a system, or any other implementation of a functionality, is described herein as being coupled to another component does not mean that the components are necessarily separate components. As an example, a component A described as being coupled to another component B may be a sub-component of the component B, or the component B may be a sub-component of the component A.

(55) The functionality associated with some examples described in this disclosure can also include instructions stored in a non-transitory media. The term “non-transitory media” as used herein refers to any media storing data and/or instructions that cause a machine to operate in a specific manner. Exemplary non-transitory media include non-volatile media and/or volatile media. Non-volatile media include, for example, a hard disk, a solid state drive, a magnetic disk or tape, an optical disk or tape, a flash memory, an EPROM, NVRAM, PRAM, or other such media, or networked versions of such media. Volatile media include, for example, dynamic memory such as DRAM, SRAM, a cache, or other such media. Non-transitory media is distinct from, but can be used in conjunction with transmission media. Transmission media is used for transferring data and/or instruction to or from a machine. Exemplary transmission media, include coaxial cables, fiber-optic cables, copper wires, and wireless media, such as radio waves.

(56) Furthermore, those skilled in the art will recognize that boundaries between the functionality of the above described operations are merely illustrative. The functionality of multiple operations may be combined into a single operation, and/or the functionality of a single operation may be distributed in additional operations. Moreover, alternative embodiments may include multiple instances of a particular operation, and the order of operations may be altered in various other embodiments.

(57) Although the disclosure provides specific examples, various modifications and changes can be made without departing from the scope of the disclosure as set forth in the claims below. Accordingly, the specification and figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of the present disclosure. Any benefits, advantages, or solutions to problems that are described herein with regard to a specific example are not intended to be construed as a critical, required, or essential feature or element of any or all the claims.

(58) Furthermore, the terms “a” or “an,” as used herein, are defined as one or more than one. Also, the use of introductory phrases such as “at least one” and “one or more” in the claims should not be construed to imply that the introduction of another claim element by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim element to inventions containing only one such element, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an.” The same holds true for the use of

definite articles.

(59) Unless stated otherwise, terms such as “first” and “second” are used to arbitrarily distinguish between the elements such terms describe. Thus, these terms are not necessarily intended to indicate temporal or other prioritization of such elements.

Claims

1. A waste cold recuperation system comprising: a liquefied gas storage for supplying liquefied gas as a coolant to cool a first set of compute resources configured to operate in a first cryogenic environment within a first temperature range from a first temperature value to a second temperature value higher than the first temperature value, resulting in at least some of the liquefied gas becoming a vapor phase of the liquefied gas; wherein the waste cold recuperation system is configured to supply at least some of the vapor phase of the liquefied gas as a coolant to cool a second set of compute resources configured to operate in a second cryogenic environment within a second temperature range from a third temperature value to a fourth temperature value higher than the third temperature value, wherein the third temperature value is equal to or higher than the second temperature value, resulting in the at least some of the vapor phase of the liquefied gas becoming a super-heated vapor phase of the liquefied gas; and wherein the waste cold recuperation system is further configured to supply at least some of the super-heated vapor phase of the liquefied gas as fuel to fuel cells for providing electrical power to a datacenter load including compute resources configured to operate in a non-cryogenic environment, wherein the liquefied gas storage is coupled via a first segment of a vacuum-insulated cryostat to the first set of compute resources, wherein the first set of compute resources is coupled via a second segment of the vacuum-insulated cryostat to the second set of compute resources, and wherein the second set of compute resources is coupled via a third segment of the vacuum-insulated cryostat to a pipe for supplying the super-heated vapor phase of the liquefied gas to the fuel cells.
2. The waste cold recuperation system of claim 1, wherein waste cold is related to latent heat associated with a change in the form of the liquefied gas from a liquid phase to a vapor phase.
3. The waste cold recuperation system of claim 2, wherein the waste cold is further related to sensible heat associated with a heating of the vapor phase of the liquefied gas to the super-heated vapor phase of the liquefied gas.
4. The waste cold recuperation system of claim 1, wherein the liquefied gas storage is configured as a vacuum-insulated housing.
5. The waste cold recuperation system of claim 1, wherein the waste cold recuperation system is further configured to dynamically control an amount of the liquefied gas being supplied as the coolant in order to ensure a sufficient amount of fuel is being supplied to the fuel cells for providing the electrical power to the datacenter load including the compute resources configured to operate in the non-cryogenic environment.
6. The waste cold recuperation system of claim 1, wherein the first set of compute resources comprises at least quantum computing resources, and wherein the second set of compute resources comprises at least complimentary metal-oxide-semiconductor (CMOS) computing systems.
7. The waste cold recuperation system of claim 1, wherein the first temperature value ranges between 20 kelvin to 77 kelvin and the second temperature value ranges between 77 kelvin to 100 kelvin.
8. The waste cold recuperation system of claim 7, further comprising a superconducting magnetic energy storage (SMES) system, which is also cooled using waste cold.
9. A method for operating a waste cold recuperation system for recovering energy from liquefied gas, the method comprising: supplying the liquefied gas to a first set of compute resources configured to operate in a first cryogenic environment within a first temperature range from a first temperature value to a second temperature value higher than the first temperature value, wherein

the liquefied gas is supplied as a coolant to cool the first set of compute resources, resulting in at least some of the liquefied gas becoming a vapor phase of the liquefied gas, and wherein a liquefied gas storage is coupled via a first segment of a vacuum-insulated cryostat to the first set of compute resources configured to operate in the first cryogenic environment; supplying at least some of the vapor phase of the liquefied gas to a second set of compute resources configured to operate in a second cryogenic environment within a second temperature range from a third temperature value to a fourth temperature value higher than the third temperature value, wherein the third temperature value is equal to or higher than the second temperature value, wherein at least some of the vapor phase of the liquefied gas is supplied as a coolant to cool the second set of compute resources, resulting in the at least some of the vapor phase of the liquefied gas becoming a super-heated vapor phase of the liquefied gas, wherein the first set of compute resources configured to operate in the first cryogenic environment is coupled via a second segment of the vacuum-insulated cryostat to the second set of compute resources configured to operate in the second cryogenic environment, and wherein the second set of compute resources configured to operate in the second cryogenic environment is coupled via a third segment of the vacuum-insulated cryostat to the hydrogen fuel cells; and supplying at least some of the super-heated vapor phase of the liquefied gas as fuel to fuel cells for providing electrical power to a datacenter load including compute resources configured to operate in a non-cryogenic environment.

10. The method of claim 9, wherein waste cold is related to latent heat associated with a change in the form of the liquefied gas from a liquid phase to a vapor phase, and wherein the waste cold is further related to sensible heat associated with a heating of the vapor phase of the liquefied gas to the super-heated vapor phase of the liquefied gas.

11. The method of claim 9, wherein the liquefied gas storage is configured to store the liquefied gas, and wherein the liquefied gas storage is configured as a vacuum-insulated housing.

12. The method of claim 9, wherein the first set of compute resources comprises at least quantum computing resources, and wherein the second set of compute resources comprises at least complimentary metal-oxide-semiconductor (CMOS) computing systems.

13. The method of claim 9, wherein the first temperature value ranges between 20 kelvin to 77 kelvin and the second temperature value ranges between 77 kelvin to 100 kelvin.

14. The method of claim 13, wherein the waste cold recuperation system further comprises a superconducting magnetic energy storage (SMES) system, and wherein the method further comprises cooling the SMES system using waste cold.

15. A waste cold recuperation system comprising: a first set of compute resources configured to operate in a first cryogenic environment within a first temperature range from 20 kelvin to 77 kelvin; a second set of compute resources configured to operate in a second cryogenic environment within a second temperature range from 77 kelvin to 100 kelvin, wherein liquefied hydrogen is supplied as a coolant to cool the first set of compute resources, resulting in at least some of the liquefied hydrogen becoming a vapor phase of the liquefied hydrogen, wherein at least the vapor phase of the liquefied hydrogen is supplied as a coolant to cool the second set of compute resources, resulting in the vapor phase of the liquefied hydrogen becoming a super-heated vapor phase of the liquefied hydrogen, and wherein the super-heated vapor phase of the liquefied hydrogen is fed as fuel to hydrogen fuel cells for providing electrical power to a datacenter load including compute resources configured to operate in a non-cryogenic environment, wherein a liquefied hydrogen storage is coupled via a first segment of a vacuum-insulated cryostat to the first set of compute resources configured to operate in the first cryogenic environment, wherein the first set of compute resources configured to operate in the first cryogenic environment is coupled via a second segment of the vacuum-insulated cryostat to the second set of compute resources configured to operate in the second cryogenic environment, and wherein the second set of compute resources configured to operate in the second cryogenic environment is coupled via a third segment of the vacuum-insulated cryostat to the hydrogen fuel cells.

16. The waste cold recuperation system of claim 15, wherein waste cold is related to latent heat associated with a change in the form of the liquefied hydrogen from a liquid phase to a vapor phase, and wherein the waste cold is further related to sensible heat associated with a heating of the vapor phase of the liquefied hydrogen to the super-heated vapor phase of the liquefied hydrogen.
 17. The waste cold recuperation system of claim 16, wherein the liquefied hydrogen storage is configured to store the liquefied hydrogen and supply the liquefied hydrogen.
 18. The waste cold recuperation system of claim 17, further comprising a superconducting magnetic energy storage (SMES) system, which is also cooled using the waste cold.
 19. The waste cold recuperation system of claim 18, further comprising a third set of compute resources, configured to operate in a cryogenic environment, that is cooled using liquefied nitrogen coupled to the liquefied hydrogen via a heat exchanger.
 20. The waste cold recuperation system of claim 18, further comprising a third set of compute resources, configured to operate in a cryogenic environment, that is cooled using liquefied natural gas coupled to the liquefied hydrogen via a heat exchanger.
-