

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409357
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Ji; Xiaoming

Fitness tool kit

Abstract

A fitness tool kit is provided. The fitness tool kit includes a plurality of fitness tools and a storage case. The storage case is configured to store/place the plurality of fitness tools. According to the fitness tool kit provided in the embodiments of the present disclosure, by the arrangement of the storage case, the plurality of fitness tools can be stored/placed. When the fitness tools are not used, an occupied space is reduced, and a user experience is enhanced.

Inventors:	Ji; Xiaoming (Shanghai, CN)
Applicant:	Mili YouHe Home Technology (Shanghai) Co, Ltd (Shanghai, CN)
Family ID:	94945791
Assignee:	Mili YouHe Home Technology (Shanghai) Co, Ltd (Shanghai, CN)
Appl. No.:	19/031421
Filed:	January 18, 2025

Prior Publication Data

Document Identifier	Publication Date
US 20250161738 A1	May. 22, 2025

Foreign Application Priority Data

CN	202411866016.0	Dec. 17, 2024
----	----------------	---------------

Publication Classification

Int. Cl.: A45C13/00 (20060101); A45C13/02 (20060101); A45C13/36 (20060101); A63B5/04 (20060101); A63B21/055 (20060101); A63B21/072 (20060101)

U.S. Cl.:

CPC **A63B21/0557** (20130101); **A45C13/001** (20130101); **A45C13/002** (20130101);
A45C13/005 (20130101); **A45C13/02** (20130101); **A45C13/36** (20130101); **A63B5/04**
(20130101); **A63B21/072** (20130101); A45C2013/025 (20130101); A63B2210/50
(20130101)

Field of Classification Search

CPC: A45C (13/001); A45C (13/002); A45C (13/005); A45C (13/02); A45C (2013/025); A63B
(21/0557); A63B (71/0036)

USPC: 206/579; 206/315.1

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2983367	12/1960	Parmater	312/351	A45C 5/03
7458920	12/2007	Hallar	482/910	A63B 21/072
7946970	12/2010	Garza, Jr.	482/40	A63B 71/0036
8550243	12/2012	Moore	224/650	A45C 5/00
8814759	12/2013	Goldy	482/90	A63B 71/0036
8997994	12/2014	Jung	206/541	A47B 81/00
9867440	12/2017	Lawrenson	N/A	A45C 13/02
10953260	12/2020	Weisz	N/A	A63B 21/0442
10960256	12/2020	Donnelly	N/A	A63B 21/4029
2002/0037792	12/2001	Smith	N/A	N/A
2003/0015445	12/2002	Levy	206/373	B25H 3/023
2008/0023355	12/2007	Reynolds	206/315.1	A63B 71/0036
2010/0101973	12/2009	Kim	482/121	A63B 23/08
2010/0184573	12/2009	Tucker et al.	N/A	N/A
2016/0001124	12/2015	Huang	N/A	N/A

Primary Examiner: Reynolds; Steven A.

Attorney, Agent or Firm: Hemisphere Law, PLLC

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to the technical field of fitness tool, and in particular, to a fitness tool kit.

BACKGROUND

(2) With the improvement of the living standard and the enhancement of health awareness, many people will engage in fitness exercises, such as doing sit ups and lifting dumbbells, which can not only enhance the abdominal strength, but also exercise the cardiovascular function, thus achieving an effect of strengthening the body.

(3) There are many types of existing fitness tools, which usually require a large occupation area and

cannot be stored. When the fitness tools are idle, a great waste of a space may be caused. In a fitness scenario of usage at home, in offices, and the like, the idle tools placed around may also affect normal work and life.

SUMMARY

(4) In view of this, it is necessary to provide a fitness tool kit convenient for storage.

(5) The embodiments of the present disclosure provide a fitness tool fit. The fitness tool kit includes a plurality of fitness tool; and a storage case. The storage case is configured to store/place the plurality of fitness tools.

(6) In an embodiment, the storage case includes: a first case body, and a second case body movably connected to the first case body. The first case body and the second case body can be in a storage state of being enclosed into a storage chamber and an open state of being stacked; in the storage state, at least one of the plurality of fitness tools is arranged in the storage chamber; and in the open state, at least one of the plurality of fitness tools can be exposed for being fetched by a user.

(7) In an embodiment, the first case body and the second case body are rotationally connected to each other; and the second case body can be switched from the storage state of being spliced and enclosed with the first case body to form the storage chamber to the open state of being stacked on one side of the first case body.

(8) In an embodiment, the first case body includes a bottom plate, a first side plate connected to the bottom plate, a second side plate connected to the bottom plate and opposite to each other, a first connecting plate connected to the bottom plate, the first side plate, and the second side plate, and a first top plate connected to the first side plate, the second side plate, and the first connecting plate and opposite to the bottom plate; and the first case body has a first storage space.

(9) The second case body includes a second top plate, a third side plate connected to the second top plate, a fourth side plate connected to the second top plate and opposite to the third side plate, and a second connecting plate connected to the second top plate, the third side plate, and the fourth side plate; the second top plate and the first top plate are rotationally connected to each other; the second case body has a second storage space; in the storage state, the second top plate and the first top plate are spliced with each other to form a top plate opposite to the bottom plate; the first side plate and the third side plate are spliced with each other to form a first side plate structure; the second side plate and the fourth side plate are spliced with each other to form a second side plate structure; the first side plate structure and the second side plate structure are opposite to each other; the first connecting plate and the second connecting plate are opposite to each other; and the second connecting plate is connected to the bottom plate.

(10) In an embodiment, a size of the first top plate is consistent with a size of the second top plate; and in the open state, the second top plate is turned over to a position above the first top plate for being stacked and aligned with the first top plate.

(11) In an embodiment, in the storage state, a width of the first side plate gradually decreases in a direction from the bottom plate to the first top plate, a width of the third side plate gradually increases in a direction from the bottom plate to the second top plate, and a width of the first side plate structure remains unchanged in a direction from the bottom plate to the top plate; and in the storage state, a width of the second side plate gradually decreases in the direction from the bottom plate to the first top plate, a width of the fourth side plate gradually increases in the direction from the bottom plate to the second top plate, and a width of the second side plate structure remains unchanged in the direction from the bottom plate to the top plate.

(12) In an embodiment, in the storage state, a storage groove is further provided in an outer surface of the top plate; the plurality of fitness tools include a push-up assembly; and the push-up assembly is arranged in the storage groove.

(13) In an embodiment, the push-up assembly includes a storage box and a push-up board; the push-up board can be stored in the storage box; the push-up board includes a first board body, a second board body, and a sliding connector connected between the first board body and the second

board body; and the sliding connector allows the first board body and the second board body to switch between a spliced state of being spliced and a separated state of being connected by the sliding connector.

(14) In an embodiment, each of the first board body and the second board body includes a sliding chute; the sliding chute of the first board body and the sliding chute of the second board body are opposite to each other; one end of the sliding connector is slidably connected to the sliding chute of the first board body; and the other end of the sliding connector is slidably connected to the sliding chute of the second board body.

(15) In an embodiment, each of the first board body and the second board body is provided with at least one first mounting part; the at least one first mounting portion is configured to mount a handle member; each of the first board body and the second board body is provided with a supporting pad arranged in a manner of being side-by-side with the at least one first mounting part; the at least one first mounting portion includes a plurality of mounting columns; the handle member includes a handle, a mounting seat opposite to the handle, and a connecting portion connected between the mounting seat and the handle; first mounting slots are provided in two ends of the handle; a second mounting slot is provided in one side of the mounting seat away from the handle; the first mounting slots or the second mounting slots cooperate with at least one of the plurality of mounting columns to mount the handle member on the first mounting part; each of the first board body and the second board body is provided with a groove; the at least one first mounting portion is arranged on a bottom wall of the groove; a reinforcing portion is further arranged at a middle position of the mounting seat, so that a width of the middle position of the mounting seat is greater than a width of each of two end positions; the connecting portion includes two connecting portions, and the two connecting portions are opposite to each other; and the handle, the two connecting portions, and the mounting seat are enclosed to form a holding space for allowing fingers to hold and pass through.

(16) In an embodiment, the plurality of fitness tools further include a skipping rope assembly; the skipping rope assembly is arranged in the second storage space; the second top plate is provided with a skipping rope fixing structure; the skipping rope assembly is configured to be mounted on the skipping rope fixing structure; the skipping rope fixing structure includes a skipping rope grip fixing element and a ball fixing element; the skipping rope grip fixing element is configured to bear a skipping rope grip of the skipping rope assembly; the ball fixing element includes a plurality of annularly arranged fixed spring piece; each fixed spring piece includes an arc-shaped portion protruding outwards and an end portion; the arc-shaped portion is connected between the second top plate and the end portion; and the plurality of fixed spring pieces are configured to fix a ball of the skipping rope assembly.

(17) In an embodiment, the plurality of fitness tools further include a leg clamp trainer; the leg clamp trainer is configured to be arranged in the second storage space; the at least one handle member includes two handle members; the two handle members are configured to be arranged in the second storage space; the leg clamp trainer is configured to be located above the two handle members; the leg clamp strainer includes a rotation connecting structure; a first connecting arm and a second connecting arm, connected to two sides of the rotation connecting structure; a first leg clamp plate connected to one end of the first connecting arm away from the rotation connecting structure; and a second leg clamp plate connected to one end of the second connecting arm away from the rotation connecting structure; and the first leg clamp plate and the second leg clamp plate are configured to be arranged above the two handle members and are located at two corners of the second storage space.

(18) In an embodiment, the plurality of fitness tools further include a gripper; the gripper is configured to be arranged in the second storage space; the gripper includes two grips movably connected to each other; the second connecting plate is provided with a grip fixing part; and the grip fixing portion is configured to be clamped with at least one of the two grips.

(19) In an embodiment, the plurality of fitness tools further include a sit-up device; the sit-up

device is configured to be arranged in the first storage space; the sit-up device include a supporting rod and a crossbeam; the supporting rod is movably connected to the bottom plate; the crossbeam is connected to one end of the supporting rod away from the bottom plate; the supporting rod is rotationally connected to the bottom plate, so that the sit-up device can be switched between a stacked state and a using state; a height of the sit-up device in the stacked state is less than a height of the sit-up device in the using state.

(20) In an embodiment, the plurality of fitness tools further include a dumbbell kit; the dumbbell kit is configured to be arranged in the first storage space; the dumbbell kit is arranged on the bottom plate; the dumbbell kit includes a storage tray; and a plurality of grip portions, a plurality of first dumbbell heads, and a plurality of second dumbbell heads, arranged on the storage tray; the first dumbbell heads are mounted at two ends of the grip portions; the plurality of first dumbbell heads are arranged in a middle portion of the storage tray; the plurality of second dumbbell heads are arranged at two ends of the storage tray and are located on two sides of the plurality of first dumbbell heads; the storage tray has a first storage portion for storing and fixing the first dumbbell heads, and a second storage portion for storing and fixing the second dumbbell heads; the fitness tool kit further includes an atmosphere light mounted on an inner side of the first case body; and the atmosphere light correspondingly irradiates the dumbbell kit.

(21) In an embodiment, the storage case is further provided with at least one resistance band fixing apparatus; the at least one resistance band fixing apparatus is configured to fix a resistance band; the resistance band fixing apparatus includes a fixing ring for fixing the resistance band, and a protective cap covering the fixing ring; the storage case is provided with a mounting portion; the fixing ring is arranged at the mounting portion; the protective cap is detachably connected to the mounting portion; the protective cap is a flexible protective cap; a material of the protective cap includes silica gel; and the mounting portion is located in an edge region of the bottom plate away from the first connecting plate.

(22) In an embodiment, the bottom plate is provided with a mounting port; the fitness tool kit further includes a suction cup and a suction cup operating member connected to the suction cup; the suction cup is mounted corresponding to the mounting opening and is located on an outer side of the bottom plate; the suction cup operating member is mounted corresponding to the mounting opening and is located on an inner side of the bottom plate; the suction cup operating member is connected to the suction cup; the suction cup operating member is configured to be operated by a user to drive the suction cup to switch between a protruding state of protruding out of an outer surface of the bottom plate and a retracting state of being stored in the mounting port; when the suction cup is in the protruding state, the suction cup can be in vacuum suction connection to an external bearing surface; when the suction cup is in the retracting state, the suction cup can be separated from the external bearing surface; and the suction cup operating member is rotationally connected to the mounting opening to drive the suction cup to switch between the protruding state and the retracting state.

(23) In an embodiment, the first case body further includes a partition; the partition divides the second storage space into a first portion and a second portion which are arranged up and down; the fitness tool kit further includes at least one drawer assembly; the at least one drawer assembly is slidably arranged in the first portion above; the at least one drawer assembly is configured to place at least one of a barbell bar, a massage ball, and a resistance band.

(24) In an embodiment, the second case body further includes a supporting plate; the supporting plate is opposite to the second top plate and is connected to one side of the second connecting plate away from the second top plate; a bracket member is further arranged at one end of the second connecting plate away from the second top plate; the bracket member is movably connected to the second connecting plate, to cooperate with the supporting plate to support a mobile phone or tablet computer; the bracket member is slidably connected to the second connecting plate; the bracket member includes a sliding main body, a supporting portion connected to one end of the sliding

main body, and a first supporting pad arranged on one side of the supporting portion close to the mobile phone or the tablet computer; the first supporting pad covers a side surface and top surface of the supporting part, and the first supporting pad has a plurality of first supporting structures; the plurality of first supporting structures are parallel to each other; the bracket member is slidably connected to the second connecting plate in a first preset direction; the second connecting plate is provided with a sliding chute; one end of the bracket member is located in the sliding chute; one end of the sliding main body away from the supporting portion is located in the sliding chute; the second case body further includes a second supporting pad; the second supporting pad is arranged on a surface of the supporting plate close to the bracket member; the second supporting pad is provided with a plurality of second supporting structures; the plurality of second supporting structures are parallel to each other; the first supporting structures and the second supporting structures are parallel to each other; the first supporting structures include strip-shaped protrusions or strip-shaped grooves; the second supporting structures include strip-shaped protrusions or strip-shaped grooves; both the first supporting structures and the second supporting structures extend in a second preset direction; and the first preset direction is perpendicular to the second preset direction.

(25) In an embodiment, a first fastening element is arranged on the first case body, and a second fastening element is arranged on the second case body; in the storage state, the first fastening element and the second fastening element are fastened and matched to connect and fix the first case body and the second case body; and the first buckle and the second buckle are further unfastened under a driving of an unlocking member, so that the second case body can be separated from the first case body and turned over to the open state.

(26) In an embodiment, the first top plate and the second top plate are connected by a high-damping rotating hinge.

(27) Compared with the prior art, the fitness tool kit provided in the embodiments of the present disclosure has the advantage that by the arrangement of the storage case, the plurality of fitness tools can be stored/placed. When the fitness tools are not used, an occupied space is reduced, and a user experience is enhanced.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) To describe the technical solutions in the embodiments of the present disclosure or in the related art more clearly, the following briefly introduces the accompanying drawings for describing the embodiments or the related art. Apparently, the accompanying drawings in the following description show merely the embodiments of the present disclosure, and a person of ordinary skill in the art may still derive other drawings from the provided accompanying drawings without creative efforts.

(2) FIG. 1 is a three-dimensional diagram of a fitness tool kit in a storage state, disclosed in an embodiment of the present disclosure.

(3) FIG. 2 is a three-dimensional diagram of the fitness tool kit shown in FIG. 1, which is in an open state.

(4) FIG. 3 is a three-dimensional diagram of the fitness tool kit shown in FIG. 1, from which a push-up assembly is removed.

(5) FIG. 4 is a three-dimensional exploded diagram of the push-up assembly of the fitness tool kit shown in FIG. 3.

(6) FIG. 5 is a schematic diagram of a changing state of a push-up board of the push-up assembly shown in FIG. 4.

(7) FIG. 6 is a schematic diagram of a state of mounting a handle member on the push-up board of

the push-up assembly shown in FIG. 4.

(8) FIG. 7 is a schematic diagram of another state of mounting a handle member on the push-up board of the push-up assembly shown in FIG. 4.

(9) FIG. 8 is a three-dimensional diagram of the handle member of the push-up assembly shown in FIG. 4.

(10) FIG. 9 is a schematic diagram of an internal structure of a second portion of a first case body of the fitness tool kit shown in FIG. 2.

(11) FIG. 10 is a schematic diagram of an internal structure of a second case body and a drawer assembly of the fitness tool kit shown in FIG. 2.

(12) FIG. 11 is a schematic diagram of an internal structure when a sit-up device of the fitness tool kit shown in FIG. 2 is in a using state.

(13) FIG. 12 is a schematic structural diagram of a resistance band fixing apparatus of the fitness tool kit shown in FIG. 2.

(14) FIG. 13 is a schematic structural diagram of a suction cup of the fitness tool kit shown in FIG. 2.

(15) FIG. 14 is an exploded view of a suction cup and a suction cup operating member of the fitness tool kit shown in FIG. 2.

(16) FIG. 15 is a schematic structural diagram of a bracket member of the fitness tool kit shown in FIG. 2, which is in a storage state.

(17) FIG. 16 is a schematic structural diagram of a bracket member of fitness tool kit shown in FIG. 2, which is in an exploded state.

(18) FIG. 17 is a schematic structural diagram of a bracket member of fitness tool kit shown in FIG. 2, which is in an exploded state, viewed in another angle.

(19) FIG. 18 is a schematic structural diagram of a leg clamp strainer of the fitness tool kit shown in FIG. 2.

(20) FIG. 19 is a schematic structural diagram of a griper of the fitness tool kit shown in FIG. 2.

(21) FIG. 20 is a schematic structural diagram of a skipping rope of the fitness tool kit shown in FIG. 2.

(22) FIG. 21 is a schematic structural diagram of a dumbbell kit of the fitness tool kit shown in FIG. 2.

(23) FIG. 22 is an exploded view of the dumbbell kit shown in FIG. 21.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(24) In order to facilitate understanding the present disclosure, the present disclosure will be described more comprehensively below with reference to related accompanying drawings. Preferred implementations of the present disclosure are provided in the drawings. However, the present disclosure can be implemented in many different forms, and are not limited to the implementations described herein. On the contrary, these implementations are provided to make the content disclosed in the present disclosure understood more thoroughly and comprehensively.

(25) It should be noted that when an element is referred to as being “fixed to” another element, the element can be directly on another component or there can be a centered element. When an element is considered to be “connected” to another element, the element can be directly connected to another element or there may be a centered element. The terms “inner”, “outer”, “left”, “right”, and similar expressions used herein are for illustrative purposes only and do not necessarily represent the only implementation.

(26) Unless otherwise defined, all technical and scientific terms used herein have the same meaning as those commonly understood by a person skilled in the art to which the present disclosure belongs. Terms used in the specification of the present disclosure herein are merely intended to describe objectives of the specific embodiments, but are not intended to limit the present disclosure. The term “and/or” used herein includes any and all combinations of one or more related listed items.

(27) Referring to FIG. 1 to FIG. 22, the embodiments of the present disclosure provide a fitness tool fit **10**. The fitness tool kit **10** includes a storage case **20** and a plurality of fitness tools. The storage case **20** is configured to store/place the plurality of fitness tools **30**.

(28) Compared with the prior art, the fitness tool kit **10** provided in the embodiments of the present disclosure has the advantage that by the arrangement of the storage case, the plurality of fitness tools **30** can be stored/placed. When the fitness tool is not used, an occupied space is reduced, and a user experience is enhanced.

(29) In an embodiment, the storage case **20** includes: a first case body **21**, and a second case body **22** movably connected to the first case body **21**. The first case body **21** and the second case body **22** can be in a storage state of being enclosed into a storage chamber **20a** and an open state of being stacked; in the storage state, at least one of the plurality of fitness tools is arranged in the storage chamber **20a**; and in the open state, at least one of the plurality of fitness tools **30** can be exposed for being fetched by a user. It can be understood that the first case body **21** is movably connected to the second case body **22**, so that the storage case **20** can have two using states, which is convenient for use by a user. Specifically, in the open state, the first case body **21** and the second case body **22** can be stacked, occupying a small space and having a height, making it more convenient for the user to fetch and place the plurality of fitness tools **30**.

(30) It can be understood that in the storage state, the storage case **20** is of a roughly square case structure, which not only has a beautiful appearance, but also is convenient for placement and carrying.

(31) In an embodiment, the first case body **21** and the second case body **22** are rotationally connected to each other; and the second case body **22** can be switched from the storage state of being spliced and enclosed with the first case body **21** to form the storage chamber to the open state of being turned over and stacked on one side of the first case body **21**. It can be understood that the above flipping and stacking mode is not only convenient for operation by a user, but also has an effect of occupying a small space and facilitating a user to fetch and place the plurality of fitness tools **30**.

(32) In an embodiment, the first case body **21** includes a bottom plate **210**, a first side plate **211** connected to the bottom plate **210**, a second side plate **212** connected to the bottom plate **210** and opposite to first side plate **211**, a first connecting plate **213** connected to the bottom plate **210**, the first side plate **211**, and the second side plate **212**, and a first top plate **214** connected to the first side plate **211**, the second side plate **212**, and the first connecting plate **213** and opposite to the bottom plate **210**; and the first case body **21** has a first storage space **21a**. The second case body **22** includes a second top plate **220**, a third side plate **221** connected to the second top plate **220**, a fourth side plate **222** connected to the second top plate **220** and opposite to the third side plate **221**, and a second connecting plate **223** connected to the second top plate **220**, the third side plate **221**, and the fourth side plate **222**; the second top plate **220** and the first top plate **214** are rotationally connected to each other; the second case body **22** has a second storage space **22a**; in the storage state, the second top plate **220** and the first top plate **214** are spliced with each other to form a top plate opposite to the bottom plate **210**; the first side plate **211** and the third side plate **221** are spliced with each other to form a first side plate structure; the second side plate **212** and the fourth side plate **222** are spliced with each other to form a second side plate structure; the first side plate structure and the second side plate structure are opposite to each other; the first connecting plate **213** and the second connecting plate **223** are opposite to each other; and the second connecting plate **223** is connected to the bottom plate **210**. It can be understood that through the above settings, both the first case body **21** and the second case body **22** have the storage spaces, which can facilitate a user to fetch and place the plurality of fitness tools **30**.

(33) In an embodiment, a size of the first top plate **214** is consistent with a size of the second top plate **220**; and in the open state, the second top plate **220** is turned over to a position above the first top plate **214** for being stacked and aligned with the first top plate **214**. It can be understood that

through the above settings, the second case body **22** can be stably arranged on the first case body **21**, and the first case body **21** supports the second case body **22**, which can avoid an unsafe state caused by the unstable gravity, so that the fitness tool kit **10** in the open state has high safety. However, it can be understood that in other embodiments, the sizes of the first top plate **214** and the second top plate **220** may not be consistent. By proper gravity configuration, a stable and safe technical effect can be obtained.

(34) In an embodiment, in the storage state, a width of the first side plate **211** gradually decreases in a direction from the bottom plate **210** to the first top plate **214**, a width of the third side plate **221** gradually increases in a direction from the bottom plate **210** to the second top plate **220**, and a width of the first side plate structure remains unchanged in a direction from the bottom plate **210** to the top plate; and in the storage state, a width of the second side plate **212** gradually decreases in the direction from the bottom plate **210** to the first top plate **214**, a width of the fourth side plate **222** gradually increases in the direction from the bottom plate **210** to the second top plate **220**, and a width of the second side plate structure remains unchanged in the direction from the bottom plate **210** to the top plate. Through the above design, the storage case **20** is of a roughly square case structure, which not only has a beautiful appearance, but also is convenient for placement and carrying.

(35) In an embodiment, in the storage state, a storage groove **201** is further provided in an outer surface of the top plate; the plurality of fitness tools **30** include a push-up assembly **31**; and the push-up assembly **31** is arranged in the storage groove **201**. It can be understood that through the above settings, it can be convenient to fetch the push-up assembly **31**.

(36) In an embodiment, the push-up assembly **31** includes a storage box **311** and a push-up board **312**; the push-up board **312** can be stored in the storage box **311**; the push-up board **312** includes a first board body **313**, a second board body **314**, and a sliding connector **315** connected between the first board body **313** and the second board body **314**; and the sliding connector **315** allows the first board body **313** and the second board body **314** to switch between a spliced state of being spliced and a separated state of being connected by the sliding connector **315**. It can be understood that the push-up board **312** has the spliced state and the separated state, which is also convenient for a user to store the push-up board when the push-up board is not in use. A small space is occupied, and a user experience is high.

(37) In an embodiment, each of the first board body **313** and the second board body **314** includes a sliding chute **316**; the sliding chute **316** of the first board body **313** and the sliding chute **316** of the second board body **314** are opposite to each other; one end of the sliding connector **315** is slidably connected to the sliding chute **316** of the first board body **313**; and the other end of the sliding connector **315** is slidably connected to the sliding chute **316** of the second board body **314**. It can be understood that the above sliding structure has a simple design, low costs, convenience of mounting, and high reliability.

(38) In an embodiment, each of the first board body **313** and the second board body **314** is provided with at least one first mounting portion **317**; the at least one first mounting portion **317** is configured to mount a handle member **319**; each of the first board body **313** and the second board body **314** is further provided with a supporting pad **318** arranged in a manner of being side-by-side with the at least one first mounting portion **317**; the at least one first mounting portion **317** includes a plurality of mounting columns **3171**; the handle member **319** includes a handle **3191**, a mounting seat **3192** opposite to the handle **3191**, and a connecting portion **3193** connected between the mounting seat **3192** and the handle **3191**; first mounting slots **3194** are provided in two ends of the handle **3191**; a second mounting slot **3195** is provided in one side of the mounting seat **3192** away from the handle **3191**; the first mounting slots **3194** or the second mounting slots **3195** cooperate with at least one of the plurality of mounting columns **3171** to mount the handle member **319** on the first mounting portion **317**; each of the first board body **313** and the second board body **314** is provided with a groove **3196**; the at least one first mounting portion **317** is arranged on a bottom

wall of the groove **3196**; a reinforcing portion **3197** is further arranged at a middle position of the mounting seat **3192**, so that a width of the middle position of the mounting seat **3192** is greater than a width of each of two end positions; the connecting portion **3193** includes two connecting portions **3193**, and the two connecting portions **3193** are opposite to each other; and the handle **3191**, the two connecting portions **3193**, and the mounting seat **3192** are enclosed to form a holding space **3198** for allowing fingers to hold and pass through. It can be understood that the supporting pad **318** can protect the elbow of a user to an extent, thus enhancing the user experience. By the arrangement of the plurality of mounting columns **3171** and the plurality of first and second mounting slots **3194**, **3195**, the handle member can be mounted according to different needs, which has rich application scenarios and a high user experience.

(39) In an embodiment, the plurality of fitness tools **30** further include a skipping rope assembly **32**; the skipping rope assembly **32** is arranged in the second storage space **22a**; the second top plate **220** is provided with a skipping rope fixing structure **224**; the skipping rope assembly **32** is configured to be mounted on the skipping rope fixing structure **224**; the skipping rope fixing structure **224** includes a skipping rope grip fixing element **2241** and a ball fixing element **2242**; the skipping rope grip fixing element is configured to bear a skipping rope grip **321** of the skipping rope assembly **32**; the ball fixing element **2242** includes a plurality of annularly arranged fixed spring piece **2243**; each fixed spring piece **2243** includes an arc-shaped portion **2244** protruding outwards and an end portion **2245**; the arc-shaped portion **2244** is connected between the second top plate **220** and the end portion **2245**; and the plurality of fixed spring pieces **2243** are configured to fix a ball **322** of the skipping rope assembly **32**. It can be understood that the above skipping rope fixing structure **224** can appropriately fix the skipping rope assembly **32**, thus avoiding the problem that a skipping rope is tangled.

(40) In an embodiment, the plurality of fitness tools **30** further include a leg clamp trainer **33**; the leg clamp trainer **33** is configured to be arranged in the second storage space **22a**; the at least one handle member **319** includes two handle members **319**; the two handle members **319** are configured to be arranged in the second storage space **22a**; the leg clamp trainer **33** is configured to be located above the two handle members **319**; the leg clamp strainer **33** includes a rotation connecting structure **330**; a first connecting arm **331** and a second connecting arm **332**, connected to two sides of the rotation connecting structure **330**; a first leg clamp plate **333** connected to one end of the first connecting arm **331** away from the rotation connecting structure **330**, and a second leg clamp plate **334** connected to one end of the second connecting arm **332** away from the rotation connecting structure **330**; and the first leg clamp plate **333** and the second leg clamp plate **334** are configured to be arranged above the two handle members **319** and are located at two corners of the second storage space **22a**. Through the above settings, the layout configuration of the second storage space **22A** can be appropriate and compact, which effectively saves the space and enhances the user experience.

(41) In an embodiment, the plurality of fitness tools **30** further include a gripper **34**; the gripper **34** is configured to be arranged in the second storage space **22a**; the gripper **34** includes two grips **341** movably connected to each other; the second connecting plate **223** is provided with a grip fixing portion **229**; and the grip fixing portion **229** is configured to be clamped with at least one of the two grips **341**. By fixing the grip **34** with the grip fixing portion **229**, the layout configuration of the second storage space **22a** is also appropriate and compact, which effectively saves the space and enhances the user experience.

(42) In an embodiment, the plurality of fitness tools **30** further include a sit-up device **35**; the sit-up device **35** is configured to be arranged in the first storage space **21a**; the sit-up device **35** include a supporting rod **351** and a crossbeam **352**; the supporting rod **351** is movably connected to the bottom plate **210**; the crossbeam **352** is connected to one end of the supporting rod **351** away from the bottom plate **210**; the supporting rod **351** is rotationally connected to the bottom plate **210**, so that the sit-up device **35** can be switched between a stacked state and a using state; a height of the

sit-up device **35** in the stacked state is less than a height of the sit-up device **35** in the using state. It can be understood that the sit-up device **35** is arranged on the bottom plate **210**, so that the layout is appropriate and highly reliable. In addition, the supporting rod **351** is movably connected to the bottom plate **210**, so that the sit-up device **35** can be switched between the stacked state and the using state, and can be stacked for storage when not in use. The user experience is high.

(43) In an embodiment, the plurality of fitness tools **30** further include a dumbbell kit **36**; the dumbbell kit **36** is configured to be arranged in the first storage space **21a**; the dumbbell kit **36** is arranged on the bottom plate **210**; the dumbbell kit **36** includes a storage tray **361**, and a plurality of grip portions **362**, a plurality of first dumbbell heads **363** and a plurality of second dumbbell heads **364** which are arranged on the storage tray **361**; the first dumbbell heads **363** are mounted at two ends of the grip portions **362**; the plurality of first dumbbell heads **363** are arranged in a middle portion of the storage tray **361**; the plurality of second dumbbell heads **364** are arranged at two ends of the storage tray **361** and are located on two sides of the plurality of first dumbbell heads **363**; the storage tray **361** has a first storage portion **3611** for storing and fixing the first dumbbell heads **363**, and a second storage portion **3612** for storing and fixing the second dumbbell heads **364**; the fitness tool kit **10** further includes an atmosphere light **219** mounted on an inner side of the first case body **21**; and the atmosphere light **219** can correspondingly irradiate the dumbbell kit **36**. It can be understood that the dumbbell kit **36** is configured to be arranged in the first storage space **21a**, so that the layout configuration of the first storage space **21a** is appropriate and compact, which effectively saves the space and enhances the user experience. The layout of the storage tray **361** is also appropriate and compact, and the user experience is further enhanced. Through the ambient light **219**, the dumbbell kit **36** on the inner side can be irradiated, making it convenient and safe to fetch the heavier dumbbell kits **36**, and further enhancing the user experience.

(44) In an embodiment, the storage case **20** is further provided with at least one resistance band fixing apparatus **37**; the at least one resistance band fixing apparatus **37** is configured to fix a resistance band; the resistance band fixing apparatus **37** includes a fixing ring **371** for fixing the resistance band, and a protective cap **372** covering the fixing ring **371**; the storage case **20** is provided with a mounting portion **373**; the fixing ring **371** is arranged at the mounting portion **373**; the protective cap **372** is detachably connected to the mounting portion **373**; the protective cap **372** is a flexible protective cap; a material of the protective cap **372** includes silica gel; and the mounting portion **373** is located in an edge region of the bottom plate **210** away from the first connecting plate **213**. The storage case **20** is further provided with the at least one resistance band fixing apparatus **37**, so that the fitness tool kit is integrated with a resistance band fitness function, and the user experience is high. In addition, through the protective cap **372**, the fixing ring **371** can be protected from being collided to be damaged, and the appearance is beautiful. In this embodiment, the resistance band fixing apparatus **37** includes at least two resistance band fixing apparatuses **37**, and two of the resistance band fixing apparatuses **37** are arranged on two opposite sides of the bottom plate **210**.

(45) In an embodiment, the bottom plate **210** is provided with a mounting opening **218**; the fitness tool kit **10** further includes a suction cup **41** and a suction cup operating member **42** connected to the suction cup **41**; the suction cup **41** is mounted corresponding to the mounting opening **218** and is located on an outer side of the bottom plate **210**; the suction cup operating member **42** is mounted corresponding to the mounting opening **218** and is located on an inner side of the bottom plate **210**; the suction cup operating member **42** is connected to the suction cup **41**; the suction cup operating member **42** is configured to be operated by a user to drive the suction cup **41** to switch between a protruding state of protruding out of an outer surface of the bottom plate **210** and a retracting state of being stored in the mounting opening **218**; when the suction cup **41** is in the protruding state, the suction cup **41** can be in vacuum suction connection to an external bearing surface; when the suction cup **41** is in the retracting state, the suction cup **41** can be separated from the external bearing surface; and the suction cup operating member **42** is rotationally connected to

the mounting opening **218** to drive the suction cup **41** to switch between the protruding state and the retracting state. It can be understood that the storage case **20** can be fixed on the external bearing surface through the suction cup **41** and the suction cup operating member **42**, thereby ensuring high safety during use of the fitness tool kit **10**.

(46) In an embodiment, the first case body **21** further includes a partition **215**; the partition **215** divides the second storage space **22a** into a first portion **21b** and a second portion **21c** which are arranged up and down; the fitness tool kit further includes at least one drawer assembly **43**; the at least one drawer assembly **43** is slidably arranged in the first portion **21b** above; the at least one drawer assembly **43** is configured to place at least one of a barbell bar, a massage ball, and a resistance band. Through the partition **215**, the layout of the second storage space **22a** can be more appropriate, and the drawer assembly **43** can also facilitate storage, fetching, and placement of other fitness tools, thereby enhancing the user experience. It can be understood that this embodiment mainly takes two drawer assemblies **43** arranged up and down as an example for illustration.

(47) In an embodiment, the second case body **22** further includes a supporting plate **225**; the supporting plate **225** is opposite to the second top plate **220** and is connected to one side of the second connecting plate **223** away from the second top plate **220**; a bracket member **44** is further arranged at one end of the second connecting plate **223** away from the second top plate **220**; the bracket member **44** is movably connected to the second connecting plate **223**, to cooperate with the supporting plate **225** to support a mobile phone or tablet computer; and the bracket member **44** can be slidably or rotationally connected to the second connecting plate **223**. By the arrangement of the bracket member **44** and the supporting plate **225**, the mobile phone or tablet computer can be placed on the supporting plate **225** and supported by both the bracket member **44** and the supporting plate **225**. This allows a user to watch an electronic device such as the mobile phone or the tablet computer when using the fitness tool kit **10**, such as doing exercise with a video played in the electronic device, thereby enhancing the exercise effect and the user experience.

(48) Specifically, in this embodiment, the bracket member **44** is slidably connected to the second connecting plate **223**, and at least a portion of the bracket member **44** can be slidably accommodated in the second connecting plate **223**. The bracket member **44** includes a sliding main body **441**, a supporting portion **442** connected to one end of the sliding main body **441**, and a first supporting pad **443** arranged on one side of the supporting portion **442** close to the mobile phone or the tablet computer; the first supporting pad **443** covers a side surface and top surface of the supporting portion **442**, and the first supporting pad **443** has a plurality of first supporting structures **4431**; the plurality of first supporting structures **4431** are parallel to each other; the bracket member **44** is slidably connected to the second connecting plate **223** in a first preset direction (e.g. a vertical direction); the second connecting plate **223** is provided with a sliding chute **2231**; one end of the bracket member **44** can be slidably accommodated in the sliding chute **2231**; one end of the sliding main body **441** away from the supporting portion **442** is located in the sliding chute **2231**; the second case body **22** further includes a second supporting pad **228**; the second supporting pad **228** is arranged on a surface of the supporting plate **225** close to the bracket member **44**; the second supporting pad **228** is provided with a plurality of second supporting structures **2281**; the plurality of second supporting structures **2281** are parallel to each other; the first supporting structures **4431** and the second supporting structures **2281** are parallel to each other; the first supporting structures **4431** include strip-shaped protrusions or strip-shaped grooves; the second supporting structures **2281** include strip-shaped protrusions or strip-shaped grooves; both the first supporting structures **4431** and the second supporting structures **2281** extend in a second preset direction; and the first preset direction is perpendicular to the second preset direction.

(49) It can be understood that the bracket member **44** is slidably connected to the second connecting plate **223**, so that the bracket member **44** can be stored in the second connecting plate **223** when not in use. The bracket member **44** is then pulled out when in use, which is convenient

for storage and use and achieves a high user experience. By the first supporting structures **4431** of the first supporting pad **443** and the second supporting structures **2281** of the second supporting pad **228**, an anti-skid effect or an angle adjustment effect can be achieved, thereby achieving the purpose of stably supporting an electronic device. In addition, the first preset direction is a vertical direction, which also facilitates a user to adjust an extension height of the bracket member **44** according to a size of the electronic device, thereby achieving a high user experience.

(50) In an embodiment, a first fastening element **216** is arranged on the first case body **21**, and a second fastening element **226** is arranged on the second case body **22**; in the storage state, the first fastening element **216** and the second fastening element **226** are fastened and matched to connect and fix the first case body **21** and the second case body **22**; and the first fastening element **216** and the second fastening element **226** can be further unfastened under a driving of an unlocking member **227**, so that the second case body **22** can be separated from the first case body **21** and turned over to the open state. It can be understood that the first fastening element **216** and the second fastening element **226** can make the fitness tool kit **10** more stable in the storage state, and it is also convenient for a user to operate the unlocking member **227**. It can be understood that the first fastening element **216** and the second fastening element **226** can be respectively a hook and a hook slot.

(51) In an embodiment, the first top plate **214** and the second top plate **220** are connected by a high-damping rotating hinge **45**. It can be understood that the high-damping rotating hinge **45** can improve the reliability of the rotational connection, prolong the service life of the fitness tool kit **10**, and improves the safety of the fitness tool kit **10**.

(52) The various technical features in the foregoing embodiments may be randomly combined. For concise description, not all possible combinations of the various technical features in the above embodiments are described. However, provided that combinations of these technical features do not conflict with each other, the combinations of the various technical features are considered as falling within the scope of this specification. The foregoing embodiments merely express several implementations of the present disclosure. The descriptions thereof are relatively specific and detailed, but are not understood as limitations on the scope of the utility model patent. A person of ordinary skill in the art can also make several transformations and improvements without departing from the idea of the present application. These transformations and improvements fall within the protection scope of the present application. Therefore, the protection scope of the patent of the present disclosure shall be subject to the appended claims.

Claims

1. A fitness tool kit, comprising: a plurality of fitness tools; and a storage case, configured to store/place the plurality of fitness tools; wherein the storage case comprises: a first case body; and a second case body movably connected to the first case body, wherein the first case body and the second case body are in a storage state of being enclosed into a storage chamber and an open state of being stacked; in the storage state, at least one of the plurality of fitness tool is arranged in the storage chamber; and in the open state, at least one of the plurality of fitness tools is exposed for being fetched by a user; wherein the first case body comprises: a bottom plate, a first side plate connected to the bottom plate, a second side plate connected to the bottom plate and opposite to the first side plate, a first connecting plate connected to the bottom plate, the first side plate, and the second side plate, and a first top plate connected to the first side plate, the second side plate, and the first connecting plate and opposite to the bottom plate; the first case body has a first storage space; the second case body comprises a second top plate, a third side plate connected to the second top plate, a fourth side plate connected to the second top plate and opposite to the third side plate, and a second connecting plate connected to the second top plate, the third side plate, and the fourth side plate; the second top plate and the first top plate are rotationally connected to each other; the

second case body has a second storage space; in the storage state, the second top plate and the first top plate are connected with each other to form a top plate opposite to the bottom plate; the first side plate and the third side plate are connected with each other to form a first side plate structure; the second side plate and the fourth side plate are connected with each other to form a second side plate structure; the first side plate structure and the second side plate structure are opposite to each other; the first connecting plate and the second connecting plate are opposite to each other; and the second connecting plate is connected to the bottom plate; wherein in the storage state, a storage groove is further provided in an outer surface of the top plate; the plurality of fitness tools comprise a push-up assembly; and the push-up assembly is arranged in the storage groove; wherein the push-up assembly comprises a storage box and a push-up board; the push-up board is stored in the storage box; the push-up board comprises a first board body, a second board body, and a sliding connector connected between the first board body and the second board body; and the sliding connector allows the first board body and the second board body to switch between a connected state of being connected and a separated state of being connected by the sliding connector.

2. The fitness tool kit according to claim 1, wherein the first case body and the second case body are rotationally connected to each other; and the second case body is switched from the storage state of being connected and enclosed with the first case body to form the storage chamber to the open state of being turned over and stacked on one side of the first case body.

3. The fitness tool kit according to claim 1, wherein a size of the first top plate is consistent with a size of the second top plate; and in the open state, the second top plate is turned over to a position above the first top plate for being stacked and aligned with the first top plate.

4. The fitness tool kit according to claim 1, wherein in the storage state, a width of the first side plate gradually decreases in a direction from the bottom plate to the first top plate, a width of the third side plate gradually increases in a direction from the bottom plate to the second top plate, and a width of the first side plate structure remains unchanged in a direction from the bottom plate to the top plate; and in the storage state, a width of the second side plate gradually decreases in the direction from the bottom plate to the first top plate, a width of the fourth side plate gradually increases in the direction from the bottom plate to the second top plate, and a width of the second side plate structure remains unchanged in the direction from the bottom plate to the top plate.

5. The fitness tool kit according to claim 1, wherein each of the first board body and the second board body comprises a sliding chute; the sliding chute of the first board body and the sliding chute of the second board body are opposite to each other; one end of the sliding connector is slidably connected to the sliding chute of the first board body; and the other end of the sliding connector is slidably connected to the sliding chute of the second board body.

6. The fitness tool kit according to claim 1, wherein each of the first board body and the second board body is provided with at least one first mounting portion; the at least one first mounting portion is configured to mount at least one handle member; each of the first board body and the second board body is provided with a supporting pad arranged in a manner of being side-by-side with the at least one first mounting portion; the at least one first mounting portion comprises a plurality of mounting columns; the at least one handle member comprises a handle, a mounting seat opposite to the handle, and a connecting portion connected between the mounting seat and the handle; first mounting slots are provided in two ends of the handle; a second mounting slot is provided in one side of the mounting seat away from the handle; the first mounting slots or the second mounting slots cooperate with at least one of the plurality of mounting columns to mount the at least one handle member on the first mounting portion; each of the first board body and the second board body is provided with a groove; the at least one first mounting portion is arranged on a bottom wall of the groove; a reinforcing portion is further arranged at a middle position of the mounting seat, so that a width of the middle position of the mounting seat is greater than a width of each of two end positions; the connecting portion comprises two connecting portions, and the two connecting portions are opposite to each other; and the handle, the two connecting portions, and the

mounting seat are enclosed to form a holding space for allowing fingers to hold and pass through.

7. The fitness tool kit according to claim 1, wherein the plurality of fitness tools further comprise a skipping rope assembly; the skipping rope assembly is arranged in the second storage space; the second top plate is provided with a skipping rope fixing structure; the skipping rope assembly is configured to be mounted on the skipping rope fixing structure; the skipping rope fixing structure comprises a skipping rope grip fixing element and a ball fixing element; the skipping rope grip fixing element is configured to bear a skipping rope grip of the skipping rope assembly; the ball fixing element comprises a plurality of annularly arranged fixed spring piece; each fixed spring piece comprises an arc-shaped portion protruding outwards and an end portion; the arc-shaped portion is connected between the second top plate and the end portion; and the plurality of fixed spring pieces are configured to fix a ball of the skipping rope assembly.

8. The fitness tool kit according to claim 6, wherein the plurality of fitness tools further comprise a leg clamp trainer; the leg clamp trainer is configured to be arranged in the second storage space; the at least one handle member comprises two handle members; the two handle members are configured to be arranged in the second storage space; the leg clamp trainer is configured to be located above the two handle members; the leg clamp trainer comprises a rotation connecting structure; a first connecting arm and a second connecting arm, connected to two sides of the rotation connecting structure; a first leg clamp plate connected to one end of the first connecting arm away from the rotation connecting structure; and a second leg clamp plate connected to one end of the second connecting arm away from the rotation connecting structure; and the first leg clamp plate and the second leg clamp plate are configured to be arranged above the two handle members and are located at two corners of the second storage space.

9. The fitness tool kit according to claim 1, wherein the plurality of fitness tools further comprise a gripper; the gripper is configured to be arranged in the second storage space; the gripper comprises two grips movably connected to each other; the second connecting plate is provided with a grip fixing part; and the grip fixing portion is configured to be clamped with at least one of the two grips.

10. The fitness tool kit according to claim 1, wherein the plurality of fitness tools further comprise a sit-up device; the sit-up device is configured to be arranged in the first storage space; the sit-up device comprises a supporting rod and a crossbeam; the supporting rod is movably connected to the bottom plate; the crossbeam is connected to one end of the supporting rod away from the bottom plate; the supporting rod is rotationally connected to the bottom plate, so that the sit-up device is switched between a stacked state and a using state; a height of the sit-up device in the stacked state is less than a height of the sit-up device in the using state.

11. The fitness tool kit according to claim 1, wherein the plurality of fitness tool further comprise a dumbbell kit; the dumbbell kit is configured to be arranged in the first storage space; the dumbbell kit is arranged on the bottom plate; the dumbbell kit comprises a storage tray; and a plurality of grip portions, a plurality of first dumbbell heads, and a plurality of second dumbbell heads, arranged on the storage tray; the first dumbbell heads are mounted at two ends of the grip portions; the plurality of first dumbbell heads are arranged in a middle portion of the storage tray; the plurality of second dumbbell heads are arranged at two ends of the storage tray and are located on two sides of the plurality of first dumbbell heads; the storage tray has a first storage portion for storing and fixing the first dumbbell heads, and a second storage portion configured for storing and fixing the second dumbbell heads; the fitness tool kit further comprises an atmosphere light mounted on an inner side of the first case body; and the atmosphere light is configure to provide light to the dumbbell kit.

12. The fitness tool kit according to claim 1, wherein the storage case is further provided with at least one resistance band fixing device; the at least one resistance band fixing device is configured to fix a resistance band; the resistance band fixing device comprises a fixing ring configured for fixing the resistance band, and a protective cap covering the fixing ring; the storage case is

provided with a mounting portion; the fixing ring is arranged at the mounting portion; the protective cap is detachably connected to the mounting portion; the protective cap is a flexible protective cap; a material of the protective cap comprises silicone; and the mounting portion is located in an edge region of the bottom plate away from the first connecting plate.

13. The fitness tool kit according to claim 1, wherein the bottom plate is provided with a mounting opening; the fitness tool kit further comprises a sucker and a sucker operating member connected to the sucker; the sucker is mounted corresponding to the mounting opening and is located on an outer side of the bottom plate; the sucker operating member is mounted corresponding to the mounting opening and is located on an inner side of the bottom plate; the sucker operating member is connected to the sucker; the sucker operating member is configured to be operated by a user to drive the sucker to switch between a protruding state of protruding out of an outer surface of the bottom plate and a retracting state of being stored in the mounting port; when the sucker is in the protruding state, the sucker is in vacuum suction connection to an external bearing surface; when the sucker is in the retracting state, the sucker is separated from the external bearing surface; and the sucker operating member is rotationally connected to the mounting opening to drive the sucker to switch between the protruding state and the retracting state.

14. The fitness tool kit according to claim 1, wherein the first case body further comprises a partition; the partition divides the second storage space into a first portion and a second portion, arranged up and down; the fitness tool kit further comprises at least one drawer assembly; the at least one drawer assembly is slidably arranged in the first portion; the at least one drawer assembly is configured to place at least one of a barbell bar, a massage ball, and a resistance band.

15. The fitness tool kit according to claim 1, wherein the second case body further comprises a supporting plate; the supporting plate is opposite to the second top plate and is connected to one side of the second connecting plate away from the second top plate; a bracket member is further arranged at one end of the second connecting plate away from the second top plate; the bracket member is movably connected to the second connecting plate, to cooperate with the supporting plate to support a mobile phone or tablet computer; the bracket member is slidably connected to the second connecting plate; the bracket member comprises a sliding main body, a supporting portion connected to one end of the sliding main body, and a first supporting pad arranged on one side of the supporting portion close to the mobile phone or the tablet computer; the first supporting pad covers a side surface and top surface of the supporting part, and the first supporting pad has a plurality of first supporting structures; the plurality of first supporting structures are parallel to each other; the bracket member is slidably connected to the second connecting plate in a first preset direction; the second connecting plate is provided with a sliding chute; one end of the bracket member is located in the sliding chute; one end of the sliding main body away from the supporting portion is located in the sliding chute; the second case body further comprises a second supporting pad; the second supporting pad is arranged on a surface of the supporting plate close to the bracket member; the second supporting pad is provided with a plurality of second supporting structures; the plurality of second supporting structures are parallel to each other; the first supporting structures and the second supporting structures are parallel to each other; the first supporting structures comprise strip-shaped protrusions or strip-shaped grooves; the second supporting structures comprise strip-shaped protrusions or strip-shaped grooves; both the first supporting structures and the second supporting structures extend in a second preset direction; and the first preset direction is perpendicular to the second preset direction.

16. The fitness tool kit according to claim 1, wherein a first fastening element is arranged on the first case body, and a second fastening element is arranged on the second case body; in the storage state, the first fastening element and the second fastening element are matched to connect and fix the first case body and the second case body; the first fastening element and the second fastening element are further unfastened under a driving of an unlocking member, so that the second case

body is separated from the first case body and turned over to the open state; and the first top plate and the second top plate are connected by a high-damping rotating hinge.
