

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409984
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Hanlon; Aaron

Reversible cap for adhesive containers

Abstract

A reversible cap configured to be removably secured to a dispensing nozzle of a container containing a substance includes a body with a first end and an opposite second end. The first end and the second end of the cap body are each configured to be removably secured to the dispensing nozzle. At least one aperture is formed in a sidewall of the body and is in fluid communication with the second end. The first end, when secured to the dispensing nozzle, is configured to prevent the substance in the container from being dispensed through the dispensing nozzle. The second end, when secured to the dispensing nozzle, is configured to allow the substance to be dispensed through the dispensing nozzle and through the at least one aperture in the body.

Inventors:	Hanlon; Aaron (Gilbert, AZ)
Applicant:	WELD-ON ADHESIVES, INC. (Compton, CA)
Family ID:	95400409
Assignee:	WELD-ON ADHESIVES, INC. (Compton, CA)
Appl. No.:	18/514722
Filed:	November 20, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250162767 A1	May. 22, 2025

Publication Classification

Int. Cl.: B65D47/06 (20060101); B65D47/42 (20060101)

U.S. Cl.:

Field of Classification Search**CPC:** B65D (47/06); B65D (47/42); B65D (2251/09)**References Cited****U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
104275	12/1869	Corell	222/538	B65D 83/303
2707968	12/1954	Efford	220/915	B65D 83/46
3168059	12/1964	Germann	114/67A	B65D 83/30
3865267	12/1974	Morris	215/214	B65D 50/061
3935974	12/1975	Weyn	222/182	B65D 83/30
4036385	12/1976	Morris	215/221	B65D 50/046
4226339	12/1979	Landsman	222/402.11	B65D 83/40
4484976	12/1983	Despins	N/A	N/A
5044803	12/1990	Kurosawa et al.	N/A	N/A
6948642	12/2004	Awad	N/A	N/A
7293674	12/2006	Abe et al.	N/A	N/A
8905264	12/2013	White et al.	N/A	N/A
9038866	12/2014	Nelson et al.	N/A	N/A
9333527	12/2015	Jurado Blazquez	N/A	N/A
9364849	12/2015	Uehara	N/A	N/A
9718586	12/2016	Yazdani	N/A	N/A
10603844	12/2019	Khosravani et al.	N/A	N/A
11472608	12/2021	Shields	N/A	B65D 41/04
2018/0186519	12/2017	Chang	N/A	B65D 47/06
2022/0266290	12/2021	Mcdonald	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102018009895	12/2018	BR	N/A
2825096	12/2018	CA	N/A
209156262	12/2018	CN	N/A
110976230	12/2019	CN	N/A
102010037504	12/2010	DE	N/A
202020002587	12/2019	DE	N/A
1500603	12/2010	EP	N/A
2361692	12/2013	EP	N/A
2586537	12/2014	EP	N/A
2702896	12/2017	EP	N/A
2553463	12/2014	ES	N/A
2014DN04200	12/2014	IN	N/A
5688640	12/2014	JP	N/A
337214	12/2015	MX	N/A
2014027762	12/2013	WO	N/A
2021000007	12/2020	WO	N/A

Background/Summary

FIELD OF THE INVENTION

(1) The present invention relates generally to containers and, more particularly, to caps for containers.

BACKGROUND OF THE INVENTION

(2) Adhesive products (bonding agents) have been developed for joining thermoplastic, thermoset, and metallic pipe and fittings for a multitude of applications (both pressure and non-pressure). These bonding agents are typically applied to a pipe end and/or fitting socket with a brush prior to assembly.

SUMMARY

(3) It should be appreciated that this Summary is provided to introduce a selection of concepts in a simplified form, the concepts being further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of this disclosure, nor is it intended to limit the scope of the invention.

(4) The present inventive concept is directed to a reversible cap for a container of adhesive used to join plastic pipes together. One end of the cap is a closed end and is threadingly secured to the container to prevent the adhesive from escaping from the container. When a user is ready to use the adhesive, the cap is unscrewed from the tube, flipped upside down, and threaded back onto the tube via an opposite end of the cap. The user then squeezes the tube and the adhesive flows through one or more apertures in the side of the cap. In some embodiments, the cap includes features that help spread the adhesive on a surface of a pipe or fitting. Once the user is done, they can throw the cap away if all the adhesive is used, or they can clean the cap and thread it back on the container using the closed end.

(5) According to some embodiments of the present inventive concept, a cap configured to be removably secured to a dispensing nozzle of a tube containing a substance (e.g., an adhesive, etc.) includes a body with a first end and an opposite second end. The cap body can have various shapes and configurations. For example, in some embodiments, the cap body is cylindrical. The cap body may be formed from various polymeric materials, and may have a Shore-A hardness value of at least 85.

(6) The first end and the second end of the cap body are each configured to be removably secured to the dispensing nozzle of the container. For example, in some embodiments, the dispensing nozzle is externally threaded, and the cap body first end and the cap body second end each include internal threads that are configured to engage the external threads of the dispensing nozzle. At least one aperture is formed in a sidewall of the body and is in fluid communication only with the second end. The first end is not in fluid communication with the at least one aperture and is a closed end. When secured to the dispensing nozzle, the first end is configured to prevent the substance in the tube from being dispensed through the dispensing nozzle. The second end, when secured to the dispensing nozzle, is configured to allow the substance to be dispensed through the dispensing nozzle and through the at least one aperture in the cap body.

(7) In some embodiments, the cap body includes a member that serves as a piercer configured to pierce a seal of the dispensing nozzle when the body second end is removably secured to the dispensing nozzle.

(8) In some embodiments, an exterior surface of the sidewall of the cap body includes features that

are configured to facilitate application of the substance onto a surface (e.g., a surface of a pipe or fitting, etc.) when the substance is dispensed through the at least one aperture in the cap body. For example, in some embodiments, the features include a plurality of grooves and ridges. The plurality of grooves and ridges may be spaced apart along a longitudinal direction of the body. In other embodiments, the features include a plurality of spaced apart nubs extending outward from the exterior surface of the sidewall.

(9) In some embodiments, the at least one aperture is a single, elongate aperture that extends along a longitudinal direction of the cap body. In some embodiments, an elongate recessed portion may be formed in an exterior surface of the sidewall adjacent to the elongate aperture. This recessed portion is configured to facilitate the distribution of a substance dispensed through the aperture, such as an adhesive, along the exterior surface of the cap body.

(10) According to some embodiments of the present inventive concept, a container includes a deformable tube configured to contain a substance and a reversible cap configured to be removably secured to a dispensing nozzle of the tube. Compressive deformation of the tube causes forced egress of the substance therewithin through the open dispensing nozzle.

(11) The cap includes a body having a first end and an opposite second end, wherein the first end and the second end are each configured to be removably secured to the dispensing nozzle. The cap body can have various shapes and configurations. For example, in some embodiments, the cap body is cylindrical. The cap body may be formed from various polymeric materials, and may have a Shore-A hardness value of at least 85.

(12) At least one aperture is formed in a sidewall of the body and is in fluid communication with the second end. The first end is not in fluid communication with the at least one aperture and is a closed end. When secured to the dispensing nozzle of the tube, the first end is configured to prevent the substance in the tube from being dispensed through the dispensing nozzle. The second end, when secured to the dispensing nozzle of the tube, is configured to allow the substance to be dispensed through the dispensing nozzle and through the at least one aperture in the cap body.

(13) In some embodiments, an exterior surface of the sidewall of the cap body includes features that are configured to facilitate application of the substance onto a surface (e.g., a surface of a pipe or fitting, etc.) when the substance is dispensed through the at least one aperture in the body. For example, in some embodiments, the features include a plurality of grooves and ridges. In other embodiments, the features include a plurality of nubs extending outward from the exterior surface of the sidewall.

(14) In some embodiments, the at least one aperture is a single, elongate aperture that extends along a longitudinal direction of the cap body. In some embodiments, an elongate recessed portion may be formed in an exterior surface of the sidewall adjacent to the elongate aperture. This recessed portion is configured to facilitate the distribution of a substance dispensed through the aperture, such as an adhesive, along the exterior surface of the cap body.

(15) It is noted that aspects of the present inventive concept described with respect to one embodiment may be incorporated in a different embodiment although not specifically described relative thereto. That is, all embodiments and/or features of any embodiment can be combined in any way and/or combination. Applicant reserves the right to change any originally filed claim or file any new claim accordingly, including the right to be able to amend any originally filed claim to depend from and/or incorporate any feature of any other claim although not originally claimed in that manner. These and other objects and/or aspects of the present inventive concept are explained in detail below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying drawings, which form a part of the specification, illustrate various embodiments of the present inventive concept. The drawings and description together serve to fully explain embodiments of the present inventive concept.
- (2) FIG. 1 illustrates a reversible cap for a container, according to some embodiments of the present inventive concept.
- (3) FIG. 2A illustrates the reversible cap of FIG. 1 secured to the dispensing nozzle of the container via the first end of the cap, and in which position a substance within the container is prevented from being dispensed through the dispensing nozzle.
- (4) FIG. 2B illustrates the reversible cap of FIG. 1 secured to the dispensing nozzle of the container via the second end of the cap, and in which position the substance within the container is allowed to be dispensed through the dispensing nozzle and through at least one aperture in the cap.
- (5) FIGS. 3-8 illustrate a reversible cap for a container according to other embodiments of the present inventive concept.
- (6) FIG. 9A illustrates the reversible cap of FIGS. 3-8 secured to the dispensing nozzle of a container via the first end of the cap, and in which position a substance within the container is prevented from being dispensed through the dispensing nozzle.
- (7) FIG. 9B illustrates the reversible cap of FIGS. 3-8 secured to the dispensing nozzle of the container via the second end of the cap, and in which position the substance within the container is allowed to be dispensed through the dispensing nozzle and through the aperture in the sidewall of the cap.
- (8) FIGS. 10-15 illustrate a reversible cap for a container according to other embodiments of the present inventive concept.
- (9) FIG. 16 illustrates a reversible cap for a container according to other embodiments of the present inventive concept.
- (10) FIG. 17 illustrates a reversible cap for a container according to other embodiments of the present inventive concept.
- (11) FIG. 18 illustrates a reversible cap for a container according to other embodiments of the present inventive concept.

DETAILED DESCRIPTION

- (12) The present inventive concept will now be described more fully hereinafter with reference to the accompanying figures, in which embodiments of the inventive concept are shown. This inventive concept may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Like numbers refer to like elements throughout. In the figures, certain components or features may be exaggerated for clarity, and broken lines illustrate optional features or operations unless specified otherwise. In addition, the sequence of operations (or steps) is not limited to the order presented in the figures and/or claims unless specifically indicated otherwise. Features described with respect to one figure or embodiment can be associated with another embodiment or figure although not specifically described or shown as such.
- (13) Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the specification and relevant art and should not be interpreted in an idealized or overly formal sense unless expressly so defined herein. Well-known functions or constructions may not be described in detail for brevity and/or clarity.
- (14) When an element is referred to as being “connected”, “coupled”, “responsive”, or variants thereof to another element, it can be directly connected, coupled, or responsive to the other element

or intervening elements may be present. In contrast, when an element is referred to as being “directly connected”, “directly coupled”, “directly responsive”, or variants thereof to another element, there are no intervening elements present. Like numbers refer to like elements throughout. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. Well-known functions or constructions may not be described in detail for brevity and/or clarity. The term “and/or” includes any and all combinations of one or more of the associated listed items.

(15) As used herein, the terms “comprise”, “comprising”, “comprises”, “include”, “including”, “includes”, “have”, “has”, “having”, or variants thereof are open-ended, and include one or more stated features, integers, elements, steps, components or functions but does not preclude the presence or addition of one or more other features, integers, elements, steps, components, functions or groups thereof. Furthermore, as used herein, the common abbreviation “e.g.,” which derives from the Latin phrase “*exempli gratia*,” may be used to introduce or specify a general example or examples of a previously mentioned item, and is not intended to be limiting of such item. The common abbreviation “i.e.,” which derives from the Latin phrase “*id est*,” may be used to specify a particular item from a more general recitation.

(16) It will be understood that although the terms first, second, third, etc., may be used herein to describe various elements/operations, these elements/operations should not be limited by these terms. These terms are only used to distinguish one element/operation from another element/operation. Thus, a first element/operation in some embodiments could be termed a second element/operation in other embodiments without departing from the teachings of the present inventive concept. The same reference numerals or the same reference designators denote the same or similar elements throughout the specification.

(17) The terms “about” and “approximately”, as used herein with respect to a value or number, means that the value or number can vary by up to $\pm$ twenty percent (20%).

(18) Referring initially to FIGS. 1 and 2A-2B, a container **10** for a substance, such as adhesive used to join plastic pipes together, is illustrated. In the illustrated embodiment, the container includes a deformable tube **20** that contains the substance, and a reversible cap **40** that is removably secured to a dispensing nozzle **30** of the tube **20**. With the cap **40** removed from the dispensing nozzle **30**, compressive deformation of the tube **20**, for example via a user's hand, etc., causes forced egress of the substance from the tube **20** and through the open dispensing nozzle **30**.

(19) The reversible cap **40** includes a body **42** having a first end **42a** and an opposite second end **42b**. The first end and the second end are each configured to be removably secured to the dispensing nozzle **30**. The dispensing nozzle **30** contains external threads, and both the first end **42a** and second end **42b** of the cap body **42** have internal threads that are configured to engage the external threads of the dispensing nozzle **30**. As such, the cap **40** is reversible in that the first end **42a** of the cap body **42** and the second end **42b** of the cap body **42** can be removably secured to the dispensing nozzle **30**.

(20) The cap body **42** can have various shapes and configurations. For example, in the illustrated embodiment, the cap body **42** has a cylindrical configuration. However, in other embodiments, the cap body **42** may have an oval configuration or a polygonal configuration, such as a square shape, a rectangular shape, a hexagonal shape, etc. Embodiments of the present inventive concept are not limited to the cap body **42** having a specific shape, however. The cap body **42** may be formed from various polymeric materials, such as silicone and polypropylene. However, other polymeric materials may be utilized, also. In some embodiments, the polymeric material of the cap body **42** has a Shore-A hardness value of at least 85.

(21) A sidewall **44** of the cap body **42** includes at least one aperture **46** formed therethrough. The at least one aperture **46** is in fluid communication with the second end **42** of the cap body **42**. In the illustrated embodiment of FIGS. 1 and 2A-2B, the at least one aperture **46** is a plurality of spaced apart apertures **46**. In the embodiments of FIGS. 3-18, described below, the at least one aperture is

a single, elongated aperture **46**.

(22) The first end **42a** of the cap body **42** is a “closed end” because the at least one aperture **46** is not in fluid communication with the first end **42a**. As such, the first end **42a**, when secured to the dispensing nozzle **30**, is configured to prevent the substance in the tube **20** from being dispensed through the dispensing nozzle **30**. Typically, the tube **20** may be shipped and stored with the first end **42a** of the cap body **42** secured thereto. However, the second end **42b**, when secured to the dispensing nozzle, is configured to allow the substance S to be dispensed through the dispensing nozzle **30** and through the at least one aperture **46** in the sidewall **44** of the cap body **42**.

(23) The operation of the reversible cap **40** is illustrated in FIGS. **1** and **2A-2B**. In FIG. **1**, the first end **42a** of the cap body **42** is secured to the dispensing nozzle **30**, for example, for shipping and storage of the tube. The arrows A in FIG. **1** represent the reversibility of the cap (i.e., the cap **40** can be flipped upside down so that the second end **42b** can be secured to the dispensing nozzle **30**.)

FIG. **2A** illustrates the cap **40** secured to the dispensing nozzle **30** of the tube **20** via the first end **42a** of the cap body **42**, as in FIG. **1**. FIG. **2B** illustrates the cap **40** reversed and secured to the dispensing nozzle **30** of the tube **20** via the second end **42b** of the cap body **42**. Compressive deformation of the tube **20** in FIG. **2B** causes the substance S in the tube **20** to flow through the dispensing nozzle **30**, into the second end **42b** of the cap body **42**, and out through the apertures **46** formed in the sidewall **44** of the cap body **42**. The cap **40** can then be used as an applicator to apply the substance S to a surface of another object, e.g., a pipe or fitting, etc.

(24) In the illustrated embodiment of FIGS. **1** and **2A-2B**, the exterior surface **48** of the sidewall **44** of the cap body **42** includes features that are configured to facilitate application of the substance S onto a surface when the substance S is dispensed through the at least one aperture **46** in the cap body **42**. These features in the embodiment illustrated in FIGS. **1** and **2A-2B** are a plurality of grooves G and ridges R. These grooves and ridges G, R facilitate the even application of the substance S onto a surface of an object as the substance S is dispensed from the tube **20**. In other embodiments, as illustrated in FIGS. **10-17**, the features include a plurality of nubs N extending outward from the exterior surface **48** of the sidewall **44** of the cap body **42**.

(25) Thus, embodiments of the present inventive concept provide a reversible cap **40** that is configured to prevent a substance, such as an adhesive, within a tube **20** from being dispensed when the first end **42a** of the cap **40** is secured to the tube **20**. When a user is ready to dispense the substance S from the tube **20**, the cap **40** is unscrewed from the tube **20**, flipped upside down, and the second end **42b** is threaded onto the tube **20**. The user then squeezes the tube **20** and the substance S flows through the one or more apertures **46** in the sidewall **44** of the cap **40**. The cap **40** further operates as an applicator with features configured to help evenly apply the substance S to a surface of another object.

(26) Referring now to FIGS. **3-8**, a reversible cap **40** for a container, according to other embodiments of the present inventive concept, is illustrated. The illustrated cap **40** is similar to the cap **40** of FIGS. **1** and **2A-2B** and includes a body **42** having a first end **42a** and an opposite second end **42b**. The first end **42a** and the second end **42b** are each configured to be removably secured to the dispensing nozzle of a container. Both the first end **42a** and second end **42b** of the cap body **42** have internal threads **60**, **62** that are configured to engage the external threads of the dispensing nozzle of the container, such as the tube **20** illustrated in FIGS. **9A-9B**.

(27) A sidewall **44** of the cap body **42** includes a single aperture **46** formed therethrough that is in fluid communication with the second end **42b** of the cap body **42**. The illustrated aperture **46** has an elongated configuration that extends along a longitudinal direction L of the cap body **42**. However, the aperture **46** may have various shapes and configurations. The illustrated aperture **46** has a length that is approximately one third of the length of the cap body **43**. However, the aperture **46** may have other lengths, including a length that is greater than one third of the length of the cap body **43**, and a length that is less than one third of the length of the cap body **43**. Moreover, the aperture **46** may be oriented transverse to the longitudinal direction L of the cap body **42**, in other

embodiments.

(28) The illustrated aperture **46** is located in a central portion of the sidewall **44**. However, in other embodiments, the aperture **46** may be located closer to one of the ends **42a**, **42b** of the cap body **42**.

(29) The illustrated aperture **46** has an angled or tapered peripheral edge **47**, as illustrated. The angled/tapered configuration of the peripheral edge helps direct the flow of a substance, such as an adhesive, that is being dispensed through the aperture **46** onto the exterior surface **48** of the sidewall **44** of the cap body **42**.

(30) The first end **42a** of the cap body **42** defines a closed internal chamber **50** (FIGS. 7-8) that is not in fluid communication with the aperture **46**. As such, the first end **42a**, when secured to a dispensing nozzle of a container, is configured to prevent a substance in the container from being dispensed through the dispensing nozzle. The first end **42a** includes internal threads **60** that are configured to engage external threads on the dispensing nozzle of the container.

(31) The second end **42b** of the cap body **42** defines an internal chamber **52** that is in fluid communication with the aperture **46**. As such, the second end **42b**, when secured to the dispensing nozzle of the container, is configured to allow the substance in the container to be dispensed through the dispensing nozzle, into the internal chamber **52**, and out through the aperture **46** in the sidewall **44** of the cap body **42**. The second end **42b** includes internal threads **62** that are configured to engage external threads on the dispensing nozzle.

(32) The exterior surface **48** of the sidewall **44** of the cap body **42** includes grooves **G** and ridges **R** to facilitate the application of a substance, such as an adhesive material, onto a surface of an object as the substance is dispensed from the container to which the cap **140** is attached.

(33) FIG. 9A illustrates the cap **40** of FIGS. 3-8 secured to the dispensing nozzle of a tube **20** via the first end **42a** of the cap **40**, and in which position a substance within the tube **20** is prevented from being dispensed through the dispensing nozzle of the tube **20**. FIG. 9B illustrates the cap **40** of FIGS. 3-8 secured to the dispensing nozzle of the tube **20** via the second end **42b** of the cap **40**, and in which position the substance within the tube **20** is allowed to be dispensed through the dispensing nozzle of the tube **20** and out through the aperture **46** in the cap.

(34) In some embodiments, the second end **42b** of the cap body **42** includes a member **70** that is configured to pierce a seal of the dispensing nozzle of a container when the cap body second end **42b** is removably secured to the dispensing nozzle.

(35) Referring now to FIGS. 10-15, a reversible cap **140** for a container of a substance, such as an adhesive, according to other embodiments of the present inventive concept, is illustrated. The illustrated cap **140** is similar to the cap **40** of FIGS. 1 and 2A-2B and includes a body **142** having a first end **142a** and an opposite second end **142b**. The first end **142a** and the second end **142b** are each configured to be removably secured to the dispensing nozzle of a container. Both the first end **142a** and second end **142b** of the cap body **142** have internal threads **60**, **62** that are configured to engage the external threads of the dispensing nozzle of the container.

(36) A sidewall **144** of the cap body **142** includes a single aperture **146** formed therethrough that is in fluid communication with the second end **142b** of the cap body **142**. The illustrated aperture **146** has an elongated configuration that extends along a longitudinal direction **L** of the body **142**. However, the aperture **146** may have various shapes and configurations, and may be oriented transverse to the longitudinal direction **L** of the cap body **142** in other embodiments.

(37) The first end **142a** of the cap body **142** defines a closed internal chamber **50** (FIGS. 14-15) that is not in fluid communication with the aperture **146**. As such, the first end **142a**, when secured to a dispensing nozzle of a container, is configured to prevent the substance in the container from being dispensed through the dispensing nozzle. The first end **142a** includes internal threads **60** that are configured to engage external threads on the dispensing nozzle of a container.

(38) The second end **142b** of the cap body **142** defines an internal chamber **52** that is in fluid communication with the aperture **146**. As such, the second end **142b**, when secured to a dispensing nozzle of a container, is configured to allow the substance in the container to be dispensed through

the dispensing nozzle, into the internal chamber **52**, and out through the aperture **146** in the sidewall **144** of the cap body **142**. The second end **142b** includes internal threads **62** that are configured to engage external threads on the dispensing nozzle of a container.

(39) The exterior surface **148** of the sidewall **144** of the cap body **142** includes a plurality of nubs **N** extending outward therefrom that are configured to facilitate the application of a substance, such as an adhesive material, onto a surface of an object as the substance is dispensed from a container to which the cap **140** is attached. The nubs **N** extend radially outward from the exterior surface **148** and are positioned circumferentially around the cap body **142**, as illustrated. In the illustrated embodiment, substantially the entire exterior surface **148** of the cap body **142** has nubs extending outwardly therefrom. However, in other embodiments, only a portion of the exterior surface **148**, may have nubs **N** extending outwardly therefrom.

(40) Referring to FIGS. **16** and **17**, a reversible cap **240** according to other embodiments of the present inventive concept is illustrated. The illustrated cap **240** is similar to the cap **40** of FIGS. **3-8** and includes a body **242** having a first end **142a** and an opposite second end **242b**. The first end **242a** and the second end **242b** have internal threads **60**, **62** that are configured to engage an externally threaded dispensing nozzle of a container. A sidewall **244** of the cap body **242** includes a single aperture **246** formed therethrough that is in fluid communication with the second end **242b** of the cap body **142**. Nubs **N** extend outwardly from a portion of the exterior surface **248** immediately adjacent to the aperture **246**. The remaining portion of the exterior surface **248** includes grooves **G** and ridges **R**. The nubs **N** in the embodiment of FIG. **16** are longer than the nubs **N** in the embodiment of FIG. **17**.

(41) Referring to FIG. **18**, a reversible cap **340** according to other embodiments of the present inventive concept is illustrated. The illustrated cap **340** is similar to the cap **40** of FIGS. **3-8** and includes a body **342** having a first end **342a** and an opposite second end **342b**. The first end **342a** and the second end **342b** have internal threads **60**, **62** that are configured to engage an externally threaded dispensing nozzle of a container. A sidewall **344** of the cap body **342** includes a single aperture **346** formed therethrough that is in fluid communication with the second end **342b** of the cap body **342**. The exterior surface **348** includes grooves **G** and ridges **R**.

(42) An elongate, recessed portion **350** is formed in the exterior surface **348** of the sidewall adjacent to the elongate aperture **346**, as illustrated. The recessed portion **350** facilitates the spreading of a substance, such as an adhesive, being dispensed through the aperture **346** along the exterior surface **348** of the cap body **342**. This helps facilitate the application of the substance to a surface of another object, such as a pipe. Embodiments of the present inventive concept are not limited to the illustrated configuration of the recessed portion **350**. The recessed portion **350** may have various shapes and configurations. In addition, another recessed portion may be formed in the exterior surface **348** of the sidewall adjacent the opposite end of the illustrated aperture **346**.

(43) Although a tube **20** is illustrated in FIGS. **1**, **2A-2B** and **9A-9B** as a container for a substance, it is to be understood that the reversible cap **40**, **140**, **240**, **340**, according to embodiments of the present inventive concept, can be utilized with various other types of containers. Embodiments of the present inventive concept are not limited to the use of the reversible cap **40**, **140**, **240**, **340** only with tubes.

(44) The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although a few exemplary embodiments of this invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as defined in the claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

Claims

1. A cap configured to be removably secured to an externally threaded dispensing nozzle of a container, the cap comprising: a body having a first end and an opposite second end, wherein the first end and the second end are each configured to be removably secured to the dispensing nozzle, wherein the body first end and the body second end each comprise internal threads configured to engage the externally threaded dispensing nozzle; and at least one aperture in a sidewall of the body that is in fluid communication with the second end, wherein the first end, when secured to the dispensing nozzle, is configured to prevent a substance in the container from being dispensed through the dispensing nozzle, and wherein the second end, when secured to the dispensing nozzle, is configured to allow the substance to be dispensed through the dispensing nozzle and through the at least one aperture in the body.
2. The cap of claim 1, wherein the body comprises a piercer that is configured to pierce a seal of the dispensing nozzle when the body second end is removably secured to the dispensing nozzle.
3. The cap of claim 1, wherein an exterior surface of the sidewall comprises a plurality of grooves and ridges that are configured to facilitate application of the substance onto a surface when the substance is dispensed through the at least one aperture in the body.
4. The cap of claim 3, wherein the plurality of grooves and ridges are spaced apart along a longitudinal direction of the body.
5. The cap of claim 1, wherein at least a portion of an exterior surface of the sidewall comprises a plurality of nubs extending outward therefrom that are configured to facilitate application of the substance onto a surface when the substance is dispensed through the at least one aperture in the body.
6. The cap of claim 1, wherein the at least one aperture comprises a single, elongate aperture that extends along a longitudinal direction of the body.
7. The cap of claim 6, further comprising an elongate recessed portion formed in an exterior surface of the sidewall adjacent to the elongate aperture.
8. The cap of claim 1, wherein the body is cylindrical.
9. The cap of claim 1, wherein the body comprises a polymeric material having a Shore-A hardness value of at least 85.
10. A cap configured to be removably secured to a dispensing nozzle of a container, the cap comprising: a body having an internally threaded first end and an opposite internally threaded second end, wherein the first end and the second end are each configured to engage external threads on the dispensing nozzle; and at least one aperture in a sidewall of the body that is in fluid communication with the second end, wherein the first end, when secured to the dispensing nozzle, is configured to prevent a substance in the container from being dispensed through the dispensing nozzle, wherein the second end, when secured to the dispensing nozzle, is configured to allow the substance to be dispensed through the dispensing nozzle and through the at least one aperture in the body, and wherein at least a portion of an exterior surface of the sidewall comprises features that are configured to facilitate application of the substance onto a surface when the substance is dispensed through the at least one aperture in the body.
11. The cap of claim 10, wherein the features comprise a plurality of grooves and ridges.
12. The cap of claim 11, wherein the plurality of grooves and ridges are spaced apart along a longitudinal direction of the body.
13. The cap of claim 10, wherein the features comprise a plurality of nubs extending outward from the exterior surface of the sidewall.
14. The cap of claim 10, wherein the at least one aperture comprises a single, elongate aperture that extends along a longitudinal direction of the body.
15. The cap of claim 14, further comprising an elongate recessed portion formed in an exterior

surface of the sidewall adjacent to the elongate aperture.

16. A container, comprising: a deformable tube configured to contain a substance, the tube comprising a dispensing nozzle, and wherein compressive deformation of the tube causes forced egress of the substance therewithin through the dispensing nozzle; and a cap, comprising: a body having a first end and an opposite second end, wherein the first end and the second end are each configured to be removably secured to the dispensing nozzle; and at least one aperture in a sidewall of the body that is in fluid communication with the second end, wherein the first end, when secured to the dispensing nozzle, is configured to prevent the substance in the tube from being dispensed through the dispensing nozzle, and wherein the second end, when secured to the dispensing nozzle, is configured to allow the substance to be dispensed through the dispensing nozzle and out through the at least one aperture in the body.

17. The container of claim 16, wherein at least a portion of an exterior surface of the sidewall comprises features that are configured to facilitate application of the substance onto a surface when the substance is dispensed through the at least one aperture in the body.

18. The container of claim 17, wherein the features comprise a plurality of grooves and ridges.

19. The container of claim 18, wherein the plurality of grooves and ridges are spaced apart along a longitudinal direction of the body.

20. The container of claim 17, wherein the features comprise a plurality of nubs extending outward from the exterior surface of the sidewall.

21. The container of claim 16, wherein the at least one aperture comprises a single, elongate aperture that extends along a longitudinal direction of the body.

22. The container of claim 16, wherein the body of the cap is cylindrical.

23. The container of claim 16, wherein the body of the cap comprises a polymeric material having a Shore-A hardness value of at least 85.

24. A cap configured to be removably secured to a dispensing nozzle of a container, the cap comprising: a body having a first end and an opposite second end, wherein the first end and the second end are each configured to be removably secured to the dispensing nozzle; and at least one aperture in a sidewall of the body that is in fluid communication with the second end, wherein the first end, when secured to the dispensing nozzle, is configured to prevent a substance in the container from being dispensed through the dispensing nozzle, wherein the second end, when secured to the dispensing nozzle, is configured to allow the substance to be dispensed through the dispensing nozzle and through the at least one aperture in the body, and wherein the body comprises a piercer that is configured to pierce a seal of the dispensing nozzle when the body second end is removably secured to the dispensing nozzle.

25. A cap configured to be removably secured to a dispensing nozzle of a container, the cap comprising: a body having a first end and an opposite second end, wherein the first end and the second end are each configured to be removably secured to the dispensing nozzle; and at least one aperture in a sidewall of the body that is in fluid communication with the second end, wherein the first end, when secured to the dispensing nozzle, is configured to prevent a substance in the container from being dispensed through the dispensing nozzle, wherein the second end, when secured to the dispensing nozzle, is configured to allow the substance to be dispensed through the dispensing nozzle and through the at least one aperture in the body, and wherein an exterior surface of the sidewall comprises a plurality of grooves and ridges that are configured to facilitate application of the substance onto a surface when the substance is dispensed through the at least one aperture in the body.

26. A cap configured to be removably secured to a dispensing nozzle of a container, the cap comprising: a body having a first end and an opposite second end, wherein the first end and the second end are each configured to be removably secured to the dispensing nozzle; and at least one aperture in a sidewall of the body that is in fluid communication with the second end, wherein the first end, when secured to the dispensing nozzle, is configured to prevent a substance in the

container from being dispensed through the dispensing nozzle, wherein the second end, when secured to the dispensing nozzle, is configured to allow the substance to be dispensed through the dispensing nozzle and through the at least one aperture in the body, and wherein at least a portion of an exterior surface of the sidewall comprises a plurality of nubs extending outward therefrom that are configured to facilitate application of the substance onto a surface when the substance is dispensed through the at least one aperture in the body.
