

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410730
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	MacManus; Katherine Courtlyn et al.

Turbine shroud and turbomachine with cooling circuit

Abstract

The present disclosure provides a turbine shroud with a cooling circuit and turbomachine with the subject turbine shroud. The turbine shroud includes a body with a structural member thereon. The body is coupled to a turbomachine casing or an intermediate component for coupling the body to the turbomachine casing. A cooling circuit within the body is in fluid communication with a cooling chamber adjacent the body. The cooling circuit includes an inlet passage extending through the structural member of the body, and an outlet passage fluidly coupled to the inlet passage and extending through an external surface of the body.

Inventors: MacManus; Katherine Courtlyn (Greenville, SC), Burnos; Daniel Robert (Greer, SC), Sezer; Ibrahim (Greenville, SC), Miller; Bradley James (Simpsonville, SC), Wallen; Johnathan Ray (Greenville, SC)

Applicant: GE Infrastructure Technology LLC (Greenville, SC)

Family ID: 95251160

Assignee: GE Infrastructure Technology, LLC (Greenville, SC)

Appl. No.: 18/642882

Filed: April 23, 2024

Publication Classification

Int. Cl.: F01D25/12 (20060101); F01D25/24 (20060101)

U.S. Cl.:

CPC F01D25/12 (20130101); F01D25/246 (20130101); F05D2240/11 (20130101); F05D2260/201 (20130101)

Field of Classification Search

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5071313	12/1990	Nichols	415/173.3	F01D 11/08
5584651	12/1995	Pietraszkiewicz	415/173.1	F01D 25/12
5957657	12/1998	Akita et al.	N/A	N/A
6139257	12/1999	Proctor	415/115	F01D 9/04
6354795	12/2001	White	415/170.1	F01D 25/14
7284954	12/2006	Parker	415/173.1	F01D 11/08
7670108	12/2009	Liang	N/A	N/A
8651805	12/2013	Lacy et al.	N/A	N/A
9015944	12/2014	Lacy et al.	N/A	N/A
9995172	12/2017	Dutta et al.	N/A	N/A
10385727	12/2018	Dutta et al.	N/A	N/A
10443437	12/2018	Lacy et al.	N/A	N/A
10975724	12/2020	Sezer et al.	N/A	N/A
11371702	12/2021	Berry et al.	N/A	N/A
2006/0140753	12/2005	Romanov	415/173.1	F01D 25/12
2013/0011238	12/2012	Liang	415/115	F01D 11/24
2017/0122562	12/2016	Berry	N/A	N/A
2020/0131929	12/2019	Lacy et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2184446	12/2018	EP	N/A

Primary Examiner: Brockman; Eldon T

Attorney, Agent or Firm: Hoffman Warnick LLC

Background/Summary**TECHNICAL FIELD**

(1) The disclosure relates generally to turbomachines and, more particularly, to turbine shrouds.

BACKGROUND

(2) Conventional turbomachines, such as gas turbine systems, generate power for electric utilities. In general, gas turbine systems generate power by passing a fluid (e.g., hot gas) through a turbine component of the gas turbine system. More specifically, inlet air may be drawn into a compressor to be compressed and subsequently mixed with fuel to be ignited by a combustor to form the operational fluid (e.g., hot gas) of the gas turbine system. The fluid then flows through a fluid flow path for rotating a plurality of rotating blades and a rotor or shaft of the turbine component for generating the power. The fluid may be directed through the turbine component via the plurality of rotating blades and a plurality of stationary nozzles or vanes positioned between the rotating blades. As the plurality of rotating blades rotate the rotor of the gas turbine system, a generator,

which is coupled to the rotor, may generate power from the rotation of the rotor.

(3) To improve operational efficiency, rotating blades may include tip shrouds on radially outer ends thereof. Tip shrouds interact with an inner surface of a stationary casing to direct the operational fluid (e.g., hot gas). During operation over the lifespan of a turbomachine, tip shrouds may weaken due to stress of rotational forces exerted on rotating blades or extended exposure to temperatures.

(4) In further embodiments, turbine shrouds may be mounted to the stationary casing in a position radially outboard of the tips of the rotating blades. The turbine shrouds form an annular ring about the rotating blades. Due to their extended exposure to high temperatures from the combustion gases, turbine shrouds require efficient cooling to achieve the desired component life.

SUMMARY

(5) All aspects, examples and features mentioned below can be combined in any technically possible way.

(6) An aspect of the disclosure provides a turbine shroud including: a body including a structural member thereon, wherein the body is configured for coupling to a turbomachine casing; and a cooling circuit within the body and in fluid communication with a cooling chamber defined radially outward of the body, the cooling circuit including: an inlet passage extending through the structural member of the body, and an outlet passage fluidly coupled to the inlet passage and extending through an external surface of the body.

(7) Another aspect of the disclosure provides any of the preceding aspects, and wherein the structural member includes a rib on a radially outward surface of the body, and the cooling circuit includes a first plenum extending within the rib of the body and in fluid communication with the inlet passage.

(8) Another aspect of the disclosure provides any of the preceding aspects, and wherein the cooling circuit further includes a second plenum fluidly coupled to the first plenum and within a different structural member of the body, wherein the second plenum fluidly couples the first plenum to the outlet passage.

(9) Another aspect of the disclosure provides any of the preceding aspects, and wherein the inlet passage is shaped to direct a cooling air onto an underside of the structural member within the first plenum.

(10) Another aspect of the disclosure provides any of the preceding aspects, and further comprising an impingement panel positioned between the structural member of the body and cooling chamber, wherein the impingement panel includes a plurality of impingement holes fluidly coupling the cooling chamber to the inlet passage of the cooling circuit.

(11) Another aspect of the disclosure provides any of the preceding aspects, and wherein the impingement panel extends between a first hook and a second hook extending outward from the body.

(12) Another aspect of the disclosure provides any of the preceding aspects, and further comprising an intermediate component disposed between the body and the turbomachine casing; and wherein the first hook and the second hook engage respective recesses in the intermediate component.

(13) Another aspect of the disclosure provides any of the preceding aspects, and wherein the first hook and the second hook are configured to engage respective recesses in the turbomachine casing.

(14) Another aspect of the disclosure provides any of the preceding aspects, and wherein the body further includes: a forward end positioned opposite an aft end; a first sidewall extending between the forward end and the aft end; a second sidewall extending between the forward end and the aft end, opposite the first sidewall; an outer surface extending between the first sidewall and the second sidewall, the outer surface oriented toward the cooling chamber and having the structural member thereon; and an inner surface oriented toward a blade structure and a hot gas flow path for the turbomachine.

(15) Another aspect of the disclosure provides any of the preceding aspects, and wherein the

structural member is a first rib and a second rib, each of the first rib and the second rib extending between the forward end and the aft end and including the inlet passage into a respective cooling circuit.

(16) Another aspect of the disclosure provides any of the preceding aspects, and wherein the cooling circuit further includes a second plenum fluidly coupled to the first plenum and within a different structural member of the body, wherein the second plenum fluidly couples the first plenum to the outlet passage defined in one of the forward end or the aft end.

(17) Another aspect of the disclosure provides any of the preceding aspects, and wherein the cooling circuit further includes at least two second plenums fluidly coupled to respective first plenums and within different structural members of the body, wherein the at least two second plenums fluidly couple the respective first plenums to outlet passages defined in the forward end and the aft end.

(18) Another aspect of the disclosure provides any of the preceding aspects, and wherein the structural member is a first rib extending between the first sidewall and the second sidewall, the first rib defining at least one first plenum in fluid communication with the inlet passage.

(19) Another aspect of the disclosure provides any of the preceding aspects, and wherein the cooling circuit further includes a second plenum fluidly coupled to the at least one first plenum and within a different structural member of the body, wherein the second plenum fluidly couples the at least one first plenum to the outlet passage defined in at least one of the first sidewall or the second sidewall.

(20) Another aspect of the disclosure provides a turbomachine including: a blade structure configured to rotate about a rotation axis of a rotor; and a turbine shroud oriented toward the blade structure and coupled to a turbomachine casing, the turbine shroud including: a body including a structural member thereon, wherein the body is coupled to one of a turbomachine casing or an intermediate component for coupling the body to the turbomachine casing; and a cooling circuit within the body and in fluid communication with a cooling chamber adjacent the body, the cooling circuit including: an inlet passage extending through the structural member of the body, and an outlet passage fluidly coupled to the inlet passage and extending through an external surface of the body.

(21) Another aspect of the disclosure provides any of the preceding aspects, and wherein the structural member includes a rib on a surface of the body, and the cooling circuit includes a first plenum extending within the rib of the body and in fluid communication with the inlet passage.

(22) Another aspect of the disclosure provides any of the preceding aspects, and wherein the cooling circuit further includes a second plenum fluidly coupled to the first plenum and within a different structural member of the body, wherein the second plenum fluidly couples the first plenum to the outlet passage.

(23) Another aspect of the disclosure provides any of the preceding aspects, and further comprising an impingement panel positioned between the structural member of the body and cooling chamber, wherein the impingement panel includes a plurality of impingement holes fluidly coupling the cooling chamber to the inlet passage of the cooling circuit.

(24) Another aspect of the disclosure provides any of the preceding aspects, and wherein the impingement panel extends between a first hook and a second hook extending outward from the body.

(25) Another aspect of the disclosure provides any of the preceding aspects, and wherein the body further includes: a forward end positioned opposite an aft end; a first sidewall extending between the forward end and the aft end; a second sidewall extending between the forward end and the aft end, opposite the first sidewall; an outer surface extending between the first sidewall and the second sidewall, the outer surface oriented toward the cooling chamber and having the structural member thereon; and an inner surface oriented toward a blade structure and a hot gas flow path for the turbomachine.

(26) Two or more aspects described in this disclosure, including those described in this summary section, may be combined to form implementations not specifically described herein. That is, all embodiments described herein can be combined with each other.

(27) The details of one or more implementations are set forth in the accompanying drawings and the description below. Other features, objects and advantages will be apparent from the description and drawings, and from the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) These and other features of this disclosure will be more readily understood from the following detailed description of the various aspects of the disclosure taken in conjunction with the accompanying drawings that depict various embodiments of the disclosure, in which:
- (2) FIG. 1 shows a schematic diagram of a gas turbine system, according to embodiments of the disclosure.
- (3) FIGS. 2A and 2B show side views of a portion of a turbine of the gas turbine system of FIG. 1 according to different example configurations.
- (4) FIGS. 3A and 3B show exploded and assembled cross-section side views of an outer shroud, an inner shroud, and an impingement panel of a turbine shroud according to embodiments of the disclosure.
- (5) FIG. 3C shows a cross-section side view of an outer shroud, an inner shroud, and an impingement panel of a turbine shroud according to further embodiments of the disclosure.
- (6) FIG. 4 shows a top view of an inner shroud according to some embodiments of the disclosure.
- (7) FIGS. 5-7 show various cross-section top views of the inner shroud of FIG. 4 including various cooling circuit configurations, according to embodiments of the disclosure.
- (8) FIG. 8 shows a top view of a turbine shroud according to embodiments of the disclosure.
- (9) FIG. 9 shows a cross-section top view of the turbine shroud of FIG. 8 according to embodiments of the disclosure.
- (10) FIG. 10 shows a top view of a turbine shroud according to embodiments of the disclosure.
- (11) FIG. 11 shows a cross-section top view of the turbine shroud of FIG. 10 according to embodiments of the disclosure.
- (12) FIG. 12 shows a top view of a turbine shroud according to embodiments of the disclosure.
- (13) FIGS. 13-16 show various cross-section top views of the turbine shroud of FIG. 12 in various configurations according to embodiments of the disclosure.
- (14) FIG. 17 shows a top view of a turbine shroud according to another embodiment of the disclosure.
- (15) FIGS. 18-20 show various cross-section top views of the turbine shroud of FIG. 17 including various configurations, according to embodiments of the disclosure.
- (16) FIGS. 21 and 22 show top views of a turbine shroud according to another embodiment of the disclosure.
- (17) FIGS. 23A, 23B, 23C, 23D, and 23E illustrate cross-sectional side views of several non-limiting embodiments of collection plenums, according to various embodiments of the disclosure.
- (18) FIG. 24 shows a schematic block diagram of an illustrative additive manufacturing system for additive manufacturing components according to various embodiments of the disclosure.
- (19) It is noted that the drawings of the disclosure are not necessarily to scale. The drawings are intended to depict only typical aspects of the disclosure and therefore should not be considered as limiting the scope of the disclosure. In the drawings, like numbering represents like elements between the drawings.

DETAILED DESCRIPTION

(20) As an initial matter, in order to clearly describe the current technology, it will become necessary to select certain terminology when referring to and describing relevant machine components within the illustrative application of a turbomachine. When doing this, if possible, common industry terminology will be used and employed in a manner consistent with its accepted meaning. Unless otherwise stated, such terminology should be given a broad interpretation consistent with the context of the present application and the scope of the appended claims. Those of ordinary skill in the art will appreciate that often a particular component may be referred to using several different or overlapping terms. What may be described herein as being a single part may include and be referenced in another context as consisting of multiple components. Alternatively, what may be described herein as including multiple components may be referred to elsewhere as a single part.

(21) In addition, several descriptive terms may be used regularly herein, and it should prove helpful to define these terms at the onset of this section. These terms and their definitions, unless stated otherwise, are as follows. As used herein, “downstream” and “upstream” are terms that indicate a direction relative to the flow of a fluid, such as the working fluid through a combustor of the turbomachine or, for example, the flow of air through the combustor or coolant through one of the turbomachine's component systems. The term “downstream” corresponds to the direction of flow of the fluid, and the term “upstream” refers to the direction opposite to the flow. The terms “forward” and “aft,” without any further specificity, refer to directions, with “forward” referring to the front or compressor end of the turbomachine, and “aft” referring to the rearward or turbine end of the turbomachine.

(22) The term “axial” refers to movement or position parallel to an axis, e.g., an axis of a combustor or turbomachine. The term “radial” refers to movement or position perpendicular to an axis, e.g., an axis of a combustor or a turbomachine. In cases such as this, if a first component resides closer to the axis than a second component, it will be stated herein that the first component is “radially inward” or “inboard” of the second component. If, on the other hand, the first component resides further from the axis than the second component, it may be stated herein that the first component is “radially outward” or “outboard” of the second component. Finally, the term “circumferential” refers to movement or position around an axis, e.g., a circumferential interior surface of a combustion liner or a circumferential interior of casing extending about a turbine section. As indicated above and depending on context, it will be appreciated that such terms may be applied in relation to the axis of the combustor or the axis of the turbomachine.

(23) In addition, several descriptive terms may be used regularly herein, as described below. The terms “first,” “second,” and “third,” may be used interchangeably to distinguish one component from another and are not intended to signify location or importance of the individual components.

(24) The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the disclosure. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. “Optional” or “optionally” means that the subsequently described event may or may not occur or that the subsequently described feature may or may not be present and that the description includes instances where the event occurs, or the feature is present and instances where the event does not occur, or the feature is not present.

(25) Where an element or layer is referred to as being “on,” “engaged to,” “connected to,” “coupled to,” or “mounted to” another element or layer, it may be directly on, engaged, connected, coupled, or mounted to the other element or layer, or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly on,” “directly engaged to,” “directly

connected to,” or “directly coupled to” another element or layer, there are no intervening elements or layers present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” etc.). As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. The verb forms of “couple” and “mount” may be used interchangeably herein.

(26) Embodiments of the disclosure provide turbine shrouds for turbine systems and, more particularly, turbine shrouds that include a plurality of conduits in fluid communication with a multi-stage plenum formed therein. These and other embodiments are discussed herein with reference to FIGS. 1-25. However, it will be readily appreciated by those skilled in the art that the detailed description provided herein is for explanatory purposes and non-limiting.

(27) FIG. 1 shows a schematic view of an illustrative gas turbine system **10**. Gas turbine system **10** may include a compressor **12** which compresses an incoming flow of air **18** and delivers a flow of compressed air **20** to at least one combustor **22** of gas turbine system **10**. Combustor **22** mixes the flow of compressed air **20** with a pressurized flow of fuel **24** and ignites the mixture to create a flow of combustion gases **26**. In turn, flow of combustion gases **26** is typically delivered to a turbine **28** (e.g., an expansion turbine) including a plurality of turbine blades having one or more airfoils (see FIG. 2), which are driven by flow of combustion gases **26** to produce mechanical work. This mechanical work in turn drives compressor **12** via a rotor **30** extending through turbine **28** and may be used to drive an external load **32**, such as an electrical generator and/or the like.

(28) Gas turbine system **10** may further include an exhaust frame **34** that is positioned adjacent to (that is, downstream of) turbine **28** of gas turbine system **10** and that is positioned to receive the flow of combustion gases **26** after the expansion of the same within turbine **28**. As discussed herein, a portion (e.g., outer casing) of exhaust frame **34** may be coupled directly to an enclosure, shell, or a casing **36** of turbine **28**.

(29) Subsequent to combustion gases **26** flowing through and driving turbine **28**, combustion gases **26** may be exhausted and/or discharged through exhaust frame **34** in a flow direction (D). In the non-limiting example shown in FIG. 1, combustion gases **26** may flow through exhaust frame **34** in the flow direction (D) and may be discharged from gas turbine system **10** (e.g., to the atmosphere). In another non-limiting example where gas turbine system **10** is part of a combined cycle power plant (e.g., including gas turbine system **10** and a steam turbine system), combustion gases **26** may discharge from exhaust frame **34** and may flow in the flow direction (D) into a heat recovery steam generator of the combined cycle power plant.

(30) Turning to FIGS. 2A and 2B, a portion of turbine **28** is shown in alternative configurations. FIGS. 2A and 2B each show a side view of a portion of turbine **28** including turbine blades **38** (one shown) coupled to rotor **30** and stator vanes **40** (one shown) coupled to casing **36** of turbine **28**. As discussed herein, turbine blades **38** and stator vanes **40** may be arranged in multiple stages, e.g., a first stage, a second stage, a third stage. Each stage may include a plurality of turbine blades **38** that may be coupled to and positioned circumferentially around rotor **30** and may be driven by combustion gases **26** to rotate rotor **30**. Similarly, each stage may include a plurality of stator vanes **40** that may be coupled to and positioned circumferentially about casing **36** of turbine **28**. In the non-limiting example herein, stator vanes **40** may include an outer platform **42** positioned adjacent and/or coupling stator vanes **40** to casing **36** of turbine **28**, an inner platform **44** positioned opposite the outer platform **42**, and an airfoil **45** positioned between outer platform **42** and inner platform **44**. Outer platform **42** and inner platform **44** of stator vanes **40** may define a flow path (FP) for the combustion gases **26** flowing over stator vanes **40**.

(31) Each turbine blade **38** of turbine **28** may include an airfoil **46** extending radially from rotor **30** and positioned within the flow path (FP) of combustion gases **26** flowing through turbine **28**. Each airfoil **46** may include a tip portion **48** positioned radially opposite rotor **30**. Turbine blades **38** and stator vanes **40** may also be positioned axially adjacent to one another within casing **36**. In the non-

limiting example shown in FIG. 2, stator vanes **40** may be positioned axially adjacent and downstream of turbine blades **38**. Some turbine blades **38**, stator vanes **40** and/or portions of rotor **30** of turbine **28** are omitted for clarity of illustration. Additionally, although only a portion of the of turbine blades **38** and stator vanes **40** of turbine **28** are shown in FIG. 2, turbine **28** may include a plurality of stages of turbine blades and stator vanes, positioned axially throughout casing **36** of turbine **28**.

(32) Turbine **28** of gas turbine system **10** (see FIG. 1) may also include a plurality of turbine shrouds **100**. For example, turbine **28** may include a circumferential array of turbine shrouds **100** (one shown). Turbine shrouds **100** may correspond with turbine blades **38** and/or stator vanes **40**. That is, and as discussed herein, turbine shrouds **100** may be positioned within turbine **28** adjacent (i.e., radially outward of) turbine blades **38** and/or stator vanes **40** to interact with and provide a seal in the flow path (FP) of combustion gases **26** flowing through turbine **28**. In the non-limiting example shown in FIG. 2, turbine shrouds **100** may be positioned radially adjacent turbine blades **38** and/or may substantially surround or encircle turbine blades **38**. Turbine shrouds **100** may be positioned radially adjacent tip portion **48** of airfoil **46** for turbine blade **38**. Additionally, turbine shrouds **100** may also be positioned axially adjacent and/or upstream of the stator vanes **40** of turbine **28** (i.e., between turbine blades **38** and stator vanes **40**).

(33) Similar to stator vanes **40**, turbine shrouds **100** may include a plurality of turbine shrouds **100**, each of which may be coupled to and positioned circumferentially about casing **36** of turbine **28**. In one example shown in FIG. 2A, turbine shrouds **100** may be coupled to casing **36** via coupling component **50** extending radially inward from casing **36** of turbine **28**. Coupling component **50** may be configured to be coupled to and/or receive fasteners or hooks of turbine shrouds **100** to couple, position, and/or secure turbine shrouds **100** to casing **36** of turbine **28**. In the FIG. 2A example, coupling component **50** may be coupled and/or fixed to casing **36** of turbine **28**. In another example shown in FIG. 2B, coupling component **50** (FIG. 2A) is omitted, and turbine shroud **100** is directly coupled to casing **36**. Similar to turbine blades **38** and/or stator vanes **40**, although only a portion of turbine shrouds **100** of turbine **28** is shown in FIG. 2, turbine **28** may include a plurality of stages of turbine shrouds **100**, positioned axially throughout casing **36** of turbine **28**.

(34) Additional details related to turbine shrouds and gas turbine systems, generally, can be found in U.S. Pat. No. 10,837,315 B2 (application Ser. No. 16/170,331), the entirety of which is incorporated by reference herein.

(35) FIGS. 3A and 3B show exploded cross-section and assembled cross-section views, respectively, of turbine shroud **100** according to embodiments of the present disclosure. As shown, turbine shroud **100** includes a body **102** coupled to an intermediate component **101**. Turbine shroud **100** further may include an impingement panel **200** coupled to body **102**, e.g., such that impingement panel **200** is between body **102** and intermediate component **101**. Turbine shroud **100** may include various cooling circuits extending within body **102**, intermediate component **101**, and/or impingement panel **200**.

(36) As shown, intermediate component **101** includes a component body **103**. Component body **103** may be configured to be coupled with body **102** such as by one or more mechanical fasteners or hooks. Component body **103** may be coupled to casing **36** (FIG. 2A). During operation, component body **103** may be in fluid communication with a cooling fluid (e.g., air, coolant, etc.) and thereby transmits the cooling fluid to body **102** of turbine shroud **100**. For example, as further shown in FIG. 3A, component body **103** includes a component cooling circuit **105** extending therein. Component cooling circuit **105** includes an inlet passage **107** extending through one or more exterior surfaces of intermediate component **101** (e.g., feed holes). Inlet passage **107** may be oriented axially, or substantially axially, with respect to a rotation axis of turbomachine. Component cooling circuit **105** includes an outlet passage **109** in fluid communication with inlet passage **107**. Outlet passage **109** may be oriented in any direction, e.g., radially inward with respect

to the rotation axis. As further shown, outlet passage **109** includes a portion adjacent to body **102** which defines a cooling chamber **111** adjacent body **102** of turbine shroud **100**. During operation, cooling fluid (e.g., compressed air **20** (FIG. **1**) from compressor **12** (FIG. **1**) of gas turbine system **10** (FIG. **1**)) flows through inlet passage **107** of component cooling circuit **105** and into cooling chamber **111**. As further discussed herein, cooling fluid may collect within cooling chamber **111**, which in turn flows through impingement panel **200**, and in turn through a cooling circuit **106** extending within body **102**.

(37) FIG. **3C** depicts a further example where body **102** and/or impingement panel **200** are coupled directly to casing **36** having inlet passage **107**, outlet passage **109**, and/or cooling chamber **111** defined at least partially therein. In this case, intermediate component **101** may be omitted entirely because body **102** is coupled directly to an internal portion of casing **36** via one or more fasteners, hooks, mechanical components, adhesives, etc. Regardless of whether intermediate component **101** is present, body **102** and portions thereof may be provided according to any embodiment discussed herein.

(38) Referring to FIGS. **3A-3C** together, turbine shroud **100** may extend axially between a forward end **115** and an aft end **117** and may extend circumferentially between a first sidewall **126** and a second sidewall **128**. Forward end **115** may be positioned upstream of aft end **117**, such that combustion gases **26** flowing through the flow path (FP) defined within turbine **28** may flow adjacent to forward end **115** before flowing by aft end **117** of turbine shroud **100**.

(39) During operation of gas turbine system **10**, a cooling fluid (e.g., air, coolant) flows through one or more cooling circuits to dissipate heat from turbine shroud **100**. As discussed herein, cooling fluid may flow through casing **36**, intermediate component **101**, impingement panel **200**, body **102**, and/or an exterior surface of body **102** of turbine shroud **100**.

(40) Optionally, impingement panel **200** may be coupled to body **102**. In this case, impingement panel **200** may direct a cooling fluid (e.g., air) from cooling chamber **111** in discrete jets which impinge upon (or strike) body **102**. As shown in FIG. **3A**, impingement panel **200** may be spaced radially outward from a radially outer surface **112** of body **102** along the radial direction **R**. Impingement panel **200** may include a first surface **202** positioned opposite a second surface **204**. First surface **202** and second surface **204** may be radially separated a distance which defines a radial thickness therebetween. First surface **202** may be configured to face toward casing **36** and/or intermediate component **101** to partially define cooling chamber **111**. Second surface **204** may be configured to face body **102** to partially define an air chamber **113** therebetween. Air chamber **113** may be positioned radially between second surface **204** and body **102**. Impingement panel **200** may extend axially and/or circumferentially between two or more surfaces of body **102** and/or intermediate component **101**. For example, impingement panel **200** may extend between a pair of fasteners/hooks **116**, **118** extending radially outward from body **102** relative to a rotation axis of turbomachine.

(41) Impingement panel **200** may further include a plurality of impingement holes **206** extending radially through first surface **202** and second surface **204**. Each impingement hole **206** may be sized and oriented to direct cooling fluid in discrete jets which impinge upon one or more surfaces of radially inner body **102** of turbine shroud **100**. The discrete jets of air impinge (or strike) surfaces of inner body **102** of turbine shroud **100** and create a thin boundary layer of air over these surfaces, which increases heat transfer between turbine shroud **100** and the air. Each impingement hole **206** may include an inlet formed within first surface **202** and an outlet formed within second surface **204** of impingement panel **200**. One or more outlets for plurality of impingement holes **206** may partially define air chamber **113**.

(42) Additional details related to impingement panels for gas turbine systems, generally, can be found in U.S. Pat. No. 11,371,702 B2 (U.S. application Ser. No. 17/007,068), the entirety of which is incorporated by reference herein.

(43) During operation of gas turbine system **10**, cooling fluid flows from cooling chamber **111** and

through impingement panel **200** via plurality of impingement holes **206**, which in turn impinges on body **102**. After cooling fluid impinges on body **102**, cooling fluid collects within air chamber **113**, which in turn flows through a cooling circuit **106** of body **102** extending within body **102**.

(44) As further shown in FIG. **4**, body **102** extends axially between forward end **115** and aft end **117**. Body **102** may include various ends, sides, and/or surfaces. For example, body **102** may include first sidewall **126** extending opposite second sidewall **128**. First sidewall **126** and/or second sidewall **128** may extend and/or be formed between forward end **115** and aft end **117**. In some implementations, first sidewall **126** and/or second sidewall **128** may be substantially closed and/or may include solid end walls or caps. As such, during operation, solid end walls of first sidewall **126** and/or second sidewall **128** may substantially prevent fluid within turbine **28** (e.g., combustion gases **26**, cooling fluids) from entering turbine shroud **100**, and/or cooling fluid from exiting internal portions (e.g., passages, plenums) formed within turbine shroud **100** via first sidewall **126** and/or second sidewall **128**. In other implementations, first sidewall **126** and/or second sidewall **128** include one or more outlet passages (e.g., one or more exhaust holes) extending through one or more exterior portions of turbine shroud **100**. As such, during operation, cooling fluid exhausts from turbine shroud **100** via one or more exhaust holes formed therein, which in turn may cool one or more exterior portions of body **102** and/or surrounding components of gas turbine system **10**.

(45) Referring to FIGS. **3A**, **3B**, **3C**, and **4** together, body **102** may further include one or more fasteners/hooks extending radially outward from one or more exterior portions thereof. For example, body **102** may include a first hook **116** positioned at the forward end **115** and a second hook **118** positioned at the aft end **117**. First hook **116** and/or second hook **118** may be configured to be coupled to and/or engage casing **36** or intermediate component **101** to couple, position, and/or secure body **102** with casing **36** or intermediate component **101**. As shown, first hook **116** and second hook **118** extend radially outward from an outer surface **112** of body **102**. In an example embodiment, first hook **116** may be oriented toward a forward axial direction, while second hook **118** may be oriented toward an aft axial direction. Other orientations may be possible.

(46) Body **102** may further include various structural members on its outer surface. As used herein, the term “structural member” refers to any load bearing component of turbine shroud **100** and/or body **102** for structurally supporting and/or otherwise mechanically engaging other portions of a turbomachine structure. In various examples, a structural member may include one or more ribs on various surfaces of body **102**, sidewalls of body **102** for structurally supporting adjacent components and/or other components coupled to body **102**, mechanical fastening elements (e.g., hooks **116**, **118** discussed herein) and/or other mechanical members for coupling body **102** to other components such as intermediate component **101** and/or casing **36**. The example of a rib **124**, as shown in FIGS. **4-23**, is used herein to discuss features and/or subcomponents formed within a structural member, but it is understood that any references to rib **124** may be substituted for any or all types of structural members in various further embodiments. Structural members, e.g., rib(s) **124**, may form part of and/or may be positioned on outer surface **112**. Rib **124**, as discussed, may structurally support body **102** against shroud deflection during the operation of a turbine machine. However, the presence of rib **124** or other structural members also creates additional mass that may experience significant heat transfer during operation.

(47) Embodiments of the disclosure include features to cool body **102** and interconnected components via rib **124** (or other structural members), while maintaining the presence and structural advantages of rib **124** (or other structural members) in body **102**. Rib **124**, or any other structural member, may protrude radially outward from outer surface **112**. In some implementations, as shown in FIGS. **4-17**, rib **124** may extend axially between forward end **115** and aft end **117**. In other implementations, as shown in FIGS. **18-23**, rib **124** may extend circumferentially between first sidewall **126** and second sidewall **128**. In some implementations, inner body **124** includes a plurality of ribs **124** positioned on outer surface **112**. Plurality of ribs **124** may extend circumferentially and/or axially along outer surface **112**. For example, in the top-down

view of body **102** of turbine shroud **100** as shown in FIG. 4, body **102** includes multiple structural members in the form of multiple ribs **124** positioned on outer surface **112**, respectively extending axially between first hook **116** and second hook **118**.

(48) Outer surface **112** may be formed and/or positioned between forward end **115** and aft end **117**, as well as first sidewall **126** and second sidewall **128**, respectively. During operation, outer surface **112** may be positioned, formed, facing, and/or otherwise in fluid communication with cooling chamber **111** formed between body **102** and casing **36** or intermediate component **101**. As discussed herein, cooling chamber **111** may receive and/or provide cooling fluid to turbine shroud **100** during operation of turbine **28**. For example, body **102** may include a cooling circuit **106** extending within body **102** and in fluid communication with cooling chamber **111**.

(49) As shown in FIGS. 3A-3C, turbine shroud **100** includes cooling circuit **106** which may include an inlet passage **108** extending through outer surface **112**, and fluidly connected to an outlet passage **110** extending through one or more exterior surfaces of body **102**. Inlet passage **108** may extend in a predetermined direction (e.g., radially or substantially radially) through rib **124** (or other structural members) of body **102** (e.g., in the same direction as radial direction R, e.g., rotation axis of turbomachine). Outlet passage **110** may extend in a predetermined direction (e.g., axially, or substantially axially) through one or more external surfaces of body **102**. During operation, cooling fluid flows through inlet passage **108**, through one or more plenums **120**, **122** of cooling circuit **106**, and exhausts through outlet passage **110**. While the inlet passage **108** and the outlet passage **110** are introduced above as singular items, it should be appreciated that a plurality of inlet passages **108** and a plurality of outlet passages **110** may be used. The plurality of inlet passages **108** may be different in number from the plurality of outlet passages **110**.

(50) Turning now to FIG. 4, illustrating a top-down view of body **102** of turbine shroud **100** according to some embodiments of the present disclosure. Portions of body **102** extend between forward end **115** and aft end **117**, as discussed above with reference to FIGS. 1, 2, 3A, 3B, and 3C, duplicative details of which are omitted with reference to FIGS. 4-22 for brevity. Body **102** includes cooling circuit **106** (FIGS. 5-7) including inlet passages **108** extending axially between forward end **115** and aft end **117** and extending radially through outer surface **112**.

(51) FIGS. 5-7 illustrate various configurations of cooling circuit **106** for body **102** of FIG. 4, according to some embodiments of the disclosure.

(52) FIG. 5 shows a cross-section top-down view of cooling circuit **106** according to further embodiments. Inlet passages **108** are in fluid communication with a first plenum **120** extending within a respective structural member. According to an example, first plenum(s) **120** may be “rib plenums” in which each plenum **120** extends within one rib **124**. As shown, cooling circuit **106** includes inlet passages **108** extending through one of first rib **124** and second rib **124**, extending into a respective first plenum **120**. Inlet passages **108** may extend radially, or substantially radially, through rib(s) **124** (or other structural members) into body **102**. During operation, cooling fluid flows from cooling chamber **111**, through impingement panel **200**, through inlet passages **108**, and into plenum **120**. Cooling fluid from first plenum **120** flows into one or more second plenums **122** extending within body **102**. Each second plenum **122** may be defined within another structural element of body **102** (that is, within a structure other than ribs **124**). For instance, second plenums **122** are shown as being defined within hook(s) **116**, **118**. In further implementations, second plenum(s) **122** may be within various structural elements other than rib(s) **124**.

(53) In some embodiments, cooling circuit **106** includes one or more second plenums **122** in fluid communication with first plenum **120**. Within cooling circuit **106**, one or more inlets may be formed in fluid communication with first plenum(s) **120**, and one or more outlets may be formed in fluid communication with one or more second plenums **122**. As shown, second plenums **122** are fluidly coupled between outlet passages **110** and one or more first plenums **120** extending within rib **124** (or other structural members). In some embodiments, for example, second plenum **122** extends partially within at least one of a leading edge (i.e., an edge of body **102** facing toward

incoming working fluid flow) or a trailing edge (i.e., an edge of body **102** facing away from incoming working fluid flow) of body **102**, first sidewall **126**, and second sidewall **128**, etc. In some implementations, cooling circuit **106** includes one or more collection plenums extending in a predetermined direction (e.g., circumferentially relative to the rotor axis) within body **102**.

(54) In some embodiments, cooling fluids may flow through and/or be exhausted from one or more exhaust holes in one or more outer surfaces of turbine shroud **100**. It should be understood that the formation and/or position of exhaust holes in turbine shroud **100** is illustrative and non-limiting. Exhaust holes, which may be formed in or through various portions of turbine shroud **100**, define the terminal end of outlet passages **110**. Cooling fluid may discharge through one or more exhaust holes and pass into a space formed between circumferentially adjacent turbine shrouds **100** and/or used for cooling circumferentially adjacent turbine shrouds **100**, or other axially adjacent turbine components.

(55) As further shown in FIG. 5, outlet passage **110** may be defined partially within, and thus extend through, an edge of body **102**. For example, as shown in FIG. 5, outlet passage **110** may include a plurality of outlet passages **110** defined partially within various edges, and/or extending through various surfaces, of body **102**. Arrows indicate the flow of cooling air exhausted from body **102** via outlet passages **110**.

(56) In some embodiments, cooling circuit **106** includes outlet passages defined partially within a leading edge at forward end **115**, such that outlet passages **110** extend through a leading edge surface of body **102**. Cooling circuit **106** further includes outlet passages **110** defined partially within a trailing edge at aft end **117**, such that outlet passages **110** extend through a trailing edge surface of body **102**. Cooling circuit **106** further includes outlet passages **110** defined partially within first sidewall **126** and second sidewall **128**, such that outlet passages **110** extend through respective sidewall surfaces of body **102**.

(57) FIGS. 6 and 7 respectively illustrate cross-section views for different embodiments of body **102** of FIG. 4. Body **102** as shown in FIGS. 6 and 7 is substantially similar to body **102**, except for a different configuration of cooling circuit **106** extending therein.

(58) FIG. 6 shows cooling circuit **106** including second plenums **122** extending proximate to forward end **115** beneath first hook **116**, and second plenums **122** extending proximate to aft end **117** beneath second hook **118**. In contrast to body **102** of FIG. 5, body **102** of FIG. 6 does not include plenums **122** extending within or along first sidewall **126** or second sidewall **128**.

(59) FIG. 7 shows cooling circuit **106** including second plenums **122** extending proximate to aft end **117** beneath second hook **118**. Cooling circuit **106** further includes outlet passages **110** fluidly coupling ribs **124** (or other structural members) with leading edge surface at forward end **115**. In contrast to inner shrouds **102** of FIGS. 5 and 6, body **102** of FIG. 7 does not include second plenums **122** extending within or along first sidewall **126** or second sidewall **128**, or beneath first hook **116**.

(60) FIGS. 8 and 9 show various views of another non-limiting example of body **102** of turbine shroud **100** according to embodiments of the present disclosure. The non-limiting example of body **102** shown in FIGS. 8 and 9 may include similar features as discussed herein with respect to FIGS. 4-7, oriented and/or positioned in a distinct manner.

(61) FIG. 8 shows a top view of turbine shroud **100** including body **102** extending axially between forward end **115** and aft end **117**. Body **102** includes outer surface **112** extending between first sidewall **126** and second sidewall **128** and positioned opposite inner surface **114** configured to face the hot gas flow path (FP, FIGS. 2A and 2B) of gas turbine system **10** (see, FIGS. 3A and 3B). As shown, body **102** includes a pair of ribs **124** (optionally with other structural members) extending axially between forward end **115** and aft end **117**. Inlet passages **108** of cooling circuit **106** include a first set of inlet passages **108** axially separated from a second set of inlet passages **108** (that is, a first set is proximate to forward end **115**, and a second set is proximate to aft end **117**).

(62) FIG. 9 shows a cross-section top view of body **102** of FIG. 8. As shown, second circuit **106**

includes four first plenums **120** extending within pair of ribs **124**, and which are in fluid communication with cooling chamber **111** by inlet passages **108**. Each plenum **120** of the four first plenums **120** shown in FIG. **9**, is fluidly uncoupled from other first plenums **120** extending within body **102**. In the present embodiment, each first plenum **120** is in fluid communication with a corresponding second plenum **122** extending beneath first hook **116** or second hook **118** where applicable. Outlet passages **110** are partially defined within body **102** proximate to forward end **115** or aft end **117**, as previously discussed herein regarding FIGS. **4-7**. During operation, cooling fluid flows from cooling chamber **111**, through impingement panel **200**, through inlet passages **108**, through plenums **120**, through plenums **122**, and through outlet passages **110**. It should be understood that alternative configurations for cooling circuit **106** are contemplated within the scope of the present disclosure.

(63) FIGS. **10** and **11** show various views of another non-limiting example of body **102** of turbine shroud **100** according to embodiments of the present disclosure. The non-limiting example of body **102** shown in FIGS. **10** and **11** may include similar features as discussed herein with respect to FIGS. **4-9**, oriented and/or positioned in a distinct manner.

(64) FIG. **10** shows a top view of turbine shroud **100** including body **102** extending between forward end **115** and aft end **117**. Body **102** includes outer surface **112** extending between first sidewall **126** and second sidewall **128** and positioned opposite inner surface **114** configured to face the hot gas flow path for turbomachine (see, FIGS. **3A** and **3B**). As shown, body **102** includes a pair of ribs **124** extending axially between forward end **115** and aft end **117**. Inlet passages **108** of cooling circuit **106** extend axially along, and radially through, a portion of rib **124**.

(65) FIG. **11** shows a cross-section top view of body **102** of FIG. **10**. As shown, each rib **124** includes one first plenum **120** extending therein, between outer surface **112** and inner surface **114**. Each first plenum **120** is respectively coupled with one second plenum **122** extending circumferentially within body **102** beneath first hook **116** proximate to leading edge at forward end **115**. Each first plenum **120** is fluidly uncoupled with respect to the other first plenum **120**, and each second plenum **122** is fluidly uncoupled with respect to the other second plenum **122**. One or more outlet passages **110** are partially defined within body **102** proximate to forward end **115**, as previously discussed herein regarding FIGS. **4-9**. It should be understood that alternative configurations for cooling circuit **106** are contemplated within the scope of the present disclosure.

(66) FIGS. **12-16** show various views of other non-limiting examples of body **102** of turbine shroud **100** according to embodiments of the present disclosure. The non-limiting examples of body **102** shown in FIGS. **12-16** may include similar features as discussed herein with respect to FIGS. **4-11**, oriented and/or positioned in a distinct manner.

(67) FIG. **12** shows a top view of body **102** extending axially between forward end **115** and aft end **117** and extending circumferentially between first sidewall **126** and second sidewall **128**. Body **102** includes outer surface **112** extending between first sidewall **126** and second sidewall **128** and positioned opposite inner surface **114**, facing the hot gas flow path for turbomachine (see, FIGS. **3A** and **3B**). As shown, body **102** includes a pair of ribs **124** (which may be substituted for, or provided with, other structural members) extending axially between forward end **115** and aft end **117**. Inlet passages **108** of cooling circuit **106** extend axially along, and radially through, a portion of rib **124**.

(68) FIGS. **13-16** illustrate various configurations of cooling circuit **106** for body **102** of FIG. **12**.

(69) FIG. **13** shows a cross-section top view of body **102** of FIG. **12**, according to one embodiment. As shown, each rib **124** (or other structural member) includes one first plenum **120** extending therein, between outer surface **112** and inner surface **114**. Each first plenum **120**, respectively, is coupled with one second plenum **122** extending circumferentially within body **102**. One or more outlet passages **110** are partially defined within body **102**, as previously discussed herein regarding FIGS. **4-11**. In the present embodiment, two cooling circuits **106** are provided with each including one first plenum **120** fluidly coupled to a respective second plenum **122**, which extends beneath

second hook **118** in the trailing edge proximate to aft end **117**.

(70) FIG. **14** shows a cross-section top view of body **102** of FIG. **12**, according to another embodiment. As shown, each rib **124** includes one first plenum **120** extending therein, between outer surface **112** and inner surface **114**. Each first plenum **120**, respectively, is coupled to a respective second plenum **122** extending circumferentially within body **102**. One or more outlet passages **110** are partially defined within body **102**, as previously discussed herein regarding FIGS. **4-13**. Outlet passages **110** may be fluidly coupled to second plenum **122**, but alternatively may be directly fluidly coupled to first plenum **120**. In the present embodiment, cooling circuit **106** includes two second plenums **122** extending beneath second hook **118** in the trailing edge proximate to aft end **115**. Body **102** further includes an additional cooling circuit **130** extending through an exterior surface of second hook **118** proximate to aft end **117**. Additional cooling circuit **130** may include cooling passages extending through one or more of first hook **116**, second hook **118**, first sidewall **126**, and/or second sidewall **128**. For instance, FIG. **15** shows a cross-section top view of body **102** of FIG. **12** according to another embodiment. As shown, additional cooling circuit **130** includes cooling passages extending through first sidewall **126**, second sidewall **128**, and first hook **116**.

(71) FIG. **16** illustrates a cross-section top-down view of another configuration of cooling circuit **106** for body **102** of FIG. **12**. As shown, cooling circuit **106** further includes two additional first plenums **120**, also coupled to cooling chamber **113** yet fluidly uncoupled from the other first plenums **120**. These additional first plenums **120** are in fluid communication with outlet passages **110** extending through leading edge surface proximate to forward end **115**.

(72) It should be understood that alternative configurations for cooling circuit **106** are contemplated within the scope of the present disclosure.

(73) FIGS. **17-20** show various views of another non-limiting example of body **102** for turbine shroud **100**. The non-limiting example of body **102** shown in FIGS. **17-20** may include similar features as discussed herein with respect to FIGS. **4-16** oriented and/or positioned in a distinct manner. FIG. **17** shows a top view of turbine shroud **100** including rib **124** extending circumferentially between first sidewall **126** and second sidewall **128**. FIG. **18** shows a cross-section top-down view of body **102** of FIG. **17**, according to one embodiment. As shown, turbine shroud **100** includes cooling circuit **106** extending within body **102** between forward end **115** and aft end **117**. Cooling circuit **106** includes first plenum **120** extending circumferentially within rib **124** between first sidewall **126** and second sidewall **128**. First plenum **120** is fluidly coupled to second plenums **122** that extend between forward end **115** and aft end **117**. Cooling circuit **106** exhausts through outlet passages **110** in first sidewall **126** and second sidewall **128**. FIG. **19** shows a cross-section top-down view of body **102** of FIG. **17** according to another embodiment. Cooling circuit **106** includes first plenum **120** extending circumferentially within rib **124** between first sidewall **126** and second sidewall **128**. First plenum **120** is fluidly coupled to second plenums **122** that extend between rib **124** and aft end **117** and that extend along a portion of aft end **117**. Cooling circuit **106** exhausts through outlet passages **110** in an aft portion of first sidewall **126**, an aft portion of second sidewall **128**, and at least a portion of aft end **117**. FIG. **20** shows a cross-section top-down view of body **102** of FIG. **17** according to another embodiment. Cooling circuit **106** includes first plenum **120** extending circumferentially within rib **124** between first sidewall **126** and second sidewall **128**. First plenum **120** is fluidly coupled to second plenums **122** that extend between rib **124** and forward end **115** and that extend along a portion of forward end **115**. Cooling circuit **106** exhausts through outlet passages **110** in a forward portion of first sidewall **126**, a forward portion of second sidewall **128**, and at least a portion of forward end **115**.

(74) FIGS. **21** and **22** show various views of another non-limiting example of body **102** according to some embodiments. The non-limiting example of turbine shroud **100** shown in FIGS. **21** and **22** may include similar features as discussed herein with respect to FIGS. **4-20** oriented and/or positioned in a distinct manner. FIG. **21** shows a top view of body **102** including rib **124** extending

circumferentially between first sidewall **126** and second sidewall **128**. FIG. **22** shows a cross-section top-down view of body **102** of FIG. **21**. As shown, body **102** includes cooling circuit **106** extending within body **102** between forward end **115** and aft end **117**. FIG. **22** is similar to the embodiment shown in FIG. **18**, although the FIG. **22** embodiment includes two first plenums **120**, which are fluidly isolated from one another. Each first plenum **120** is fluidly coupled to a respective second plenum **122**, which extends from forward end **115** to aft end **117**. Cooling circuit **106** exhausts through outlet passages **110** along first sidewall **126** and second sidewall **128**, although outlet passages in other locations may also be employed.

(75) FIGS. **23A**, **23B**, **23C**, **23D**, and **23E** illustrate various cross-sectional views of several non-limiting embodiments of a collection plenum of cooling circuit **106** such as first plenum **120** and/or second plenum **122**. As shown, in some embodiments, first plenum **120** is shaped and dimensioned such that the cross-section of first plenum **120** is circular, or substantially circular, as shown in FIG. **23A**. In other embodiments, first plenum **120** is shaped and dimensioned such that the cross-section of first plenum **120** is rectangular, or substantially rectangular, as shown in FIG. **23B**. In other embodiments, first plenum **120** is shaped and dimensioned such that the cross-section of first plenum **120** is oval or elliptical, or substantially oval or elliptical, as shown in FIG. **23C**. In other embodiments, first plenum **120** is shaped and dimensioned such that the cross-section of first plenum **120** includes one or more rounded corners (e.g., fillets) as shown in FIG. **23D**. In other embodiments, first plenum **120** is shaped and dimensioned such that the cross-section of plenum **120** is triangular, or substantially triangular, as shown in FIG. **23E**. In another embodiment, cooling circuit **106** includes two or more collection plenums that each have a distinct cross-section shape and dimension. For example, first plenum **120** may have a circular cross-section, and second plenum **120** may have a rectangular cross-section or a polygonal cross-section with rounded corners.

(76) FIG. **24** shows a schematic/block view of an illustrative computerized metal powder additive manufacturing system **310** (hereinafter ‘AM system **310**’) for generating turbine shroud **100**, of which only a single layer is shown. Turbine shroud **100** can be made separately or as an integral unitary piece. The teachings of the disclosure will be described relative to building turbine shroud **100** using multiple melting beam sources **312**, **314**, **316**, **318**, but it is emphasized and will be readily recognized that the teachings of the disclosure are equally applicable to build turbine shroud **100** using any number of melting beam sources. In this example, AM system **310** is arranged for direct metal laser melting (DMLM). It is understood that the general teachings of the disclosure are equally applicable to other forms of metal powder additive manufacturing such as but not limited to selective laser melting (SLM), and perhaps other forms of additive manufacturing (i.e., other than metal powder applications). The layer of turbine shroud **100** in build platform **320** is illustrated as a generally rectangular element in FIG. **24**; however, it is understood that the additive manufacturing process can be readily adapted to manufacture any shaped part of shroud **100** on build platform **320**.

(77) AM system **310** generally includes an additive manufacturing control system **330** (“control system”) and an AM printer **332**. As will be described, control system **330** executes set of computer-executable instructions or code **334** to generate turbine shroud **100** using multiple melting beam sources **312**, **314**, **316**, **318**. In the example shown, four melting beam sources may include four lasers. However, the teachings of the disclosures are applicable to any melting beam source, e.g., an electron beam, laser, etc. Control system **330** is shown implemented on computer **336** as computer program code. To this extent, computer **336** is shown including a memory **338** and/or storage system **340**, a processor unit (PU) **344**, an input/output (I/O) interface **346**, and a bus **348**. Further, computer **336** is shown in communication with an external I/O device/resource **350**. In general, processor unit (PU) **344** executes computer program code **334** that is stored in memory **338** and/or storage system **340**. While executing computer program code **334**, processor unit (PU) **344** can read and/or write data to/from memory **338**, storage system **340**, I/O device **350** and/or

AM printer **332**. Bus **348** provides a communication link between each of the components in computer **336**, and I/O device **350** can comprise any device that enables a user to interact with computer **336** (e.g., keyboard, pointing device, display, etc.).

(78) Computer **336** is only representative of various possible combinations of hardware and software. For example, processor unit (PU) **344** may comprise a single processing unit or be distributed across one or more processing units in one or more locations, e.g., on a client and server. Similarly, memory **338** and/or storage system **340** may reside at one or more physical locations. Memory **338** and/or storage system **340** can comprise any combination of various types of non-transitory computer readable storage medium including magnetic media, optical media, random access memory (RAM), read only memory (ROM), etc. Computer **336** can comprise any type of computing device such as an industrial controller, a network server, a desktop computer, a laptop, a handheld device, etc.

(79) As noted, AM system **310** and, in particular control system **330**, executes code **334** to generate turbine shroud **100**. Code **334** can include, among other things, a set of computer-executable instructions **334S** (herein also referred to as 'code **334S**') for operating AM printer **332**, and a set of computer-executable instructions **3340** (herein also referred to as 'code **3340**') defining turbine shroud **100** to be physically generated by AM printer **332**. As described herein, additive manufacturing processes begin with a non-transitory computer readable storage medium (e.g., memory **338**, storage system **340**, etc.) storing code **334**. Set of computer-executable instructions **334S** for operating AM printer **332** may include any now known or later developed software code capable of operating AM printer **332**.

(80) The set of computer-executable instructions **3340** defining turbine shroud **100** may include a precisely defined 3D model of turbine shroud **100** and can be generated from any of a large variety of well-known computer aided design (CAD) software systems such as AutoCAD®, TurboCAD®, DesignCAD 3D Max, etc. In this regard, code **3340** can include any now known or later developed file format. Furthermore, code **3340** representative of turbine shroud **100** may be translated between different formats. For example, code **3340** may include Standard Tessellation Language (STL) files which was created for stereolithography CAD programs of 3D Systems, or an additive manufacturing file (AMF), which is an American Society of Mechanical Engineers (ASME) standard that is an extensible markup-language (XML) based format designed to allow any CAD software to describe the shape and composition of any three-dimensional object to be fabricated on any AM printer. Code **3340** representative of turbine shroud **100** may also be converted into a set of data signals and transmitted, received as a set of data signals and converted to code, stored, etc., as necessary. Code **3340** may be configured according to embodiments of the disclosure to allow for formation of border and internal sections in overlapping field regions, as will be described. In any event, code **3340** may be an input to AM system **310** and may come from a part designer, an intellectual property (IP) provider, a design company, the operator or owner of AM system **310**, or from other sources. In any event, control system **330** executes code **334S** and **3340**, dividing turbine shroud **100** into a series of thin slices that assembles using AM printer **332** in successive layers of material.

(81) AM printer **332** may include a processing chamber **360** that is sealed to provide a controlled atmosphere for turbine shroud **100** printing. A build platform **320**, upon which turbine shroud **100** is built, is positioned within processing chamber **360**. A number of melting beam sources **312**, **314**, **316**, **318** are configured to melt layers of metal powder on build platform **320** to generate turbine shroud **100**. While four melting beam sources **312**, **314**, **316**, **318** are illustrated, it is emphasized that the teachings of the disclosure are applicable to a system employing any number of sources, e.g., 1, 2, 3, or 5 or more. As understood in the field, each melting beam source **312**, **314**, **316**, **318** may have a field including a non-overlapping field region, respectively, in which it can exclusively melt metal powder, and may include at least one overlapping field region in which two or more sources can melt metal powder. In this regard, each melting beam source **312**, **314**, **316**, **318** may

generate a melting beam, respectively, that fuses particles for each slice, as defined by code 3340. For example, in FIG. 25, melting beam source 312 is shown creating a layer of turbine shroud 100 using melting beam 362 in one region, while melting beam source 314 is shown creating a layer of turbine shroud 100 using melting beam 362' in another region. Each melting beam source 312, 314, 316, 318 is calibrated in any now known or later developed manner. That is, each melting beam source 312, 314, 316, 318 has had its laser or electron beam's anticipated position relative to build platform 320 correlated with its actual position in order to provide an individual position correction (not shown) to ensure its individual accuracy. In one embodiment, each of plurality melting beam sources 312, 314, 316, 318 may create melting beams, e.g., 362, 362', having the same cross-sectional dimensions (e.g., shape and size in operation), power and scan speed.

(82) Continuing with FIG. 24, an applicator (or re-coater blade) 370 may create a thin layer of raw material 372 spread out as the blank canvas from which each successive slice of the final turbine shroud 100 will be created. Various parts of AM printer 332 may move to accommodate the addition of each new layer, e.g., a build platform 320 may lower and/or chamber 360 and/or applicator 370 may rise after each layer. The process may use different raw materials in the form of fine-grain metal powder, a stock of which may be held in a powder reservoir 368 accessible by applicator 370.

(83) Processing chamber 360 is filled with an inert gas such as argon or nitrogen and controlled to minimize or eliminate oxygen. Control system 330 is configured to control a flow of a gas mixture 374 within processing chamber 360 from a source of inert gas 376. In this case, control system 330 may control a pump 380, and/or a flow valve system 382 for inert gas to control the content of gas mixture 374. Flow valve system 382 may include one or more computer controllable valves, flow sensors, temperature sensors, pressure sensors, etc., capable of precisely controlling flow of the particular gas. Pump 380 may be provided with or without valve system 382. Where pump 380 is omitted, inert gas may simply enter a conduit or manifold prior to introduction to processing chamber 360. Source of inert gas 376 may take the form of any conventional source for the material contained therein, e.g., a tank, reservoir or other source. Any sensors (not shown) required to measure gas mixture 374 may be provided. Gas mixture 374 may be filtered using a filter 386 in a conventional manner.

(84) In operation, build platform 320 with metal powder thereon is provided within processing chamber 360, and control system 330 controls flow of gas mixture 374 within processing chamber 360 from source of inert gas 376. Control system 330 also controls AM printer 332, and in particular, applicator 370 and melting beam sources 312, 314, 316, 318 to sequentially melt layers of metal powder on build platform 320 to generate turbine shroud 100 according to embodiments of the disclosure. While a particular AM system 310 has been described herein, it is emphasized that the teachings of the disclosure are not limited to any particular additive manufacturing system or method.

(85) The disclosure provides various technical and commercial advantages, examples of which are discussed herein. Turbine shroud 100 may provide a series of impingement cooling passages which cool large ribs via impingement cooling. Turbine shroud 100 may provide a cascading cooling circuit, which directs air through a series of collection plenums within turbine shroud 100. Turbine shroud 100 may reuse cooling air by directing cooling air exiting the series of impingement cooling passages onto one or more regions along the perimeter of turbine shroud 100.

(86) Approximating language, as used herein throughout the specification and claims, may be applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it is related. Accordingly, a value modified by a term or terms, such as "about," "approximately" and "substantially," are not to be limited to the precise value specified. In at least some instances, the approximating language may correspond to the precision of an instrument for measuring the value. Here and throughout the specification and claims, range limitations may be combined and/or interchanged; such ranges are identified and

include all the sub-ranges contained therein unless context or language indicates otherwise. “Approximately” or “about,” as applied to a particular value of a range, applies to both end values and, unless otherwise dependent on the precision of the instrument measuring the value, may indicate $\pm 10\%$ of the stated value(s).

(87) The corresponding structures, materials, acts, and equivalents of all means or step plus function elements in the claims below are intended to include any structure, material, or act for performing the function in combination with other claimed elements as specifically claimed. The description of the present disclosure has been presented for purposes of illustration and description but is not intended to be exhaustive or limited to the disclosure in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the disclosure. The embodiments were chosen and described in order to best explain the principles of the disclosure and its practical application and to enable others of ordinary skill in the art to understand the disclosure for contemplating various embodiments with modifications as are suited to the particular given use.

Claims

1. A turbine shroud comprising: a body including a structural member thereon, and a forward end positioned opposite an aft end, wherein the body is configured for coupling to a turbomachine casing; and a cooling circuit within the body and in fluid communication with a cooling chamber defined radially outward of the body, the cooling circuit including: a plurality of inlet passages extending through the structural member of the body and spaced along a length thereof, and an outlet passage fluidly coupled to the inlet passages and extending through an external surface of the body, wherein the structural member includes a rib on a radially outward surface of the body, the rib extending between the forward end and the aft end, and the cooling circuit includes at least one first plenum extending within the rib of the body and in fluid communication with the plurality of inlet passages, wherein the plurality of inlet passages are shaped to direct a cooling air into the first plenum and toward an underside surface of the structural member.
2. The turbine shroud of claim 1, wherein the cooling circuit further includes a second plenum fluidly coupled to the first plenum and within a different structural member of the body, wherein the second plenum fluidly couples the first plenum to the outlet passage.
3. The turbine shroud of claim 1, further comprising an impingement panel positioned between the rib and the cooling chamber, wherein the impingement panel includes a plurality of impingement holes fluidly coupling the cooling chamber to the plurality of inlet passages of the cooling circuit.
4. The turbine shroud of claim 3, wherein the impingement panel extends between a first hook and a second hook extending outward from the body.
5. The turbine shroud of claim 4, further comprising an intermediate component disposed between the body and the turbomachine casing; and wherein the first hook and the second hook engage respective recesses in the intermediate component.
6. The turbine shroud of claim 4, wherein the first hook and the second hook are configured to engage respective recesses in the turbomachine casing.
7. The turbine shroud of claim 1, wherein the body further includes: a first sidewall extending between the forward end and the aft end; a second sidewall extending between the forward end and the aft end, opposite the first sidewall; an outer surface extending between the first sidewall and the second sidewall, the outer surface oriented toward the cooling chamber and having the rib thereon; and an inner surface oriented toward a blade structure and a hot gas flow path for the turbomachine.
8. The turbine shroud of claim 7, wherein the rib is a first rib, and the body further includes a second rib on the radially outward surface, each of the first rib and the second rib extending between the forward end and the aft end and including the plurality of inlet passages into a respective cooling circuit.

9. The turbine shroud of claim 8, wherein the cooling circuit further includes at least two second plenums fluidly coupled to respective first plenums and within different structural members of the body, wherein the at least two second plenums fluidly couple the respective first plenums to outlet passages defined in the forward end and the aft end.

10. The turbine shroud of claim 7, wherein the rib extends between the first sidewall and the second sidewall.

11. The turbine shroud of claim 10, wherein the cooling circuit further includes a second plenum fluidly coupled to the at least one first plenum and within a different structural member of the body, wherein the second plenum fluidly couples the at least one first plenum to the outlet passage defined in at least one of the first sidewall or the second sidewall.

12. A turbomachine comprising: a blade structure configured to rotate about a rotation axis of a rotor; and a turbine shroud oriented toward the blade structure and coupled to a turbomachine casing, the turbine shroud including: a body including a structural member thereon and a forward end positioned opposite an aft end, wherein the body is coupled to one of a turbomachine casing or an intermediate component for coupling the body to the turbomachine casing; and a cooling circuit within the body and in fluid communication with a cooling chamber adjacent the body, the cooling circuit including: a plurality of inlet passages extending through the structural member of the body and spaced along a length thereof, and an outlet passage fluidly coupled to the inlet passages and extending through an external surface of the body, at least one first plenum extending within the structural member and in fluid communication with the plurality of inlet passages; and at least one second plenum fluidly coupled to the first plenum and within a different structural member of the body, wherein the second plenum fluidly couples the first plenum to the outlet passage defined in the aft end.

13. The turbomachine of claim 12, further comprising an impingement panel positioned between the structural member of the body and cooling chamber, wherein the impingement panel includes a plurality of impingement holes fluidly coupling the cooling chamber to the plurality of inlet passages of the cooling circuit.

14. The turbomachine of claim 13, wherein the impingement panel extends between a first hook and a second hook extending outward from the body.

15. The turbomachine of claim 12, wherein the body further includes: a first sidewall extending between the forward end and the aft end; a second sidewall extending between the forward end and the aft end, opposite the first sidewall; an outer surface extending between the first sidewall and the second sidewall, the outer surface oriented toward the cooling chamber and having the structural member thereon; and an inner surface oriented toward a blade structure and a hot gas flow path for the turbomachine.

16. A turbine shroud comprising: a body including a structural member thereon, and a forward end positioned opposite an aft end, wherein the body is configured for coupling to a turbomachine casing; and a cooling circuit within the body and in fluid communication with a cooling chamber defined radially outward of the body, the cooling circuit including: an inlet passage extending through the structural member of the body, an outlet passage fluidly coupled to the inlet passage and extending through an external surface of the body, at least one first plenum extending within the structural member and in fluid communication with the inlet passage, and at least one second plenum fluidly coupled to the first plenum and within a different structural member of the body, wherein the second plenum fluidly couples the first plenum to the outlet passage defined in the aft end.

17. The turbine shroud of claim 16, wherein the body further includes: a first sidewall extending between the forward end and the aft end; a second sidewall extending between the forward end and the aft end, opposite the first sidewall; an outer surface extending between the first sidewall and the second sidewall, the outer surface oriented toward the cooling chamber and having the structural member thereon; and an inner surface oriented toward a blade structure and a hot gas flow path for

the turbomachine.

18. The turbine shroud of claim 17, wherein the structural member is a first rib extending between the forward end and the aft end, the first rib defining the at least one first plenum in fluid communication with the inlet passage.

19. The turbine shroud of claim 18, wherein the outlet passage is a first outlet passage of a plurality of outlet passages; and wherein a second outlet passage of the plurality of outlet passages is defined in at least one of the first sidewall or the second sidewall.

20. The turbine shroud of claim 16, further comprising an impingement panel positioned between the structural member of the body and the cooling chamber, wherein the impingement panel includes a plurality of impingement holes fluidly coupling the cooling chamber to the inlet passage of the cooling circuit.
