

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411386
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Nishi; Shuji et al.

Liquid crystal display device

Abstract

A liquid crystal display device includes a first substrate, a second substrate, and a liquid crystal layer provided between the first substrate and the second substrate, and has pixels. Each pixel includes a reflective region in which to perform a display in a reflective mode. The first substrate includes a substrate, gate lines extending in a row-wise direction, source lines extending in a column-wise direction, thin-film transistors provided separately in correspondence with each pixel, pixel electrodes each electrically connected to a thin-film transistor, and a reflective layer provided between the pixel electrodes and the substrate. The first substrate further includes touch sensor electrodes and touch lines each electrically connected to a touch sensor electrode. The touch lines are formed from a conducting film that is identical to that from which the source lines are formed, and are provided between the reflective layer and the substrate.

Inventors:	Nishi; Shuji (Kameyama, JP), Ina; Keiichi (Kameyama, JP)
Applicant:	Sharp Display Technology Corporation (Kameyama, JP)
Family ID:	94833161
Assignee:	Sharp Display Technology Corporation (Kameyama, JP)
Appl. No.:	18/791409
Filed:	July 31, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250085599 A1	Mar. 13, 2025

Foreign Application Priority Data

JP	2023-145981	Sep. 08, 2023
----	-------------	---------------

Publication Classification

Int. Cl.: G02F1/1362 (20060101); G02F1/1333 (20060101); G02F1/1337 (20060101);
G02F1/1368 (20060101)

U.S. Cl.:

CPC G02F1/136286 (20130101); G02F1/13338 (20130101); G02F1/133738 (20210101);
G02F1/1368 (20130101); G02F2203/02 (20130101)

Field of Classification Search

CPC: G02F (1/136286); G02F (1/13338); G02F (1/133738); G02F (1/1368); G02F (1/133555);
G02F (1/133553); G02F (2203/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2012/0138922	12/2011	Yamazaki et al.	N/A	N/A
2013/0320334	12/2012	Yamazaki et al.	N/A	N/A
2014/0286076	12/2013	Aoki et al.	N/A	N/A
2022/0146874	12/2021	Yoshida	N/A	G06F 3/04164

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2000-122094	12/1999	JP	N/A
3394926	12/2002	JP	N/A
2003-131268	12/2002	JP	N/A
2012-134475	12/2011	JP	N/A
2014-007399	12/2013	JP	N/A
2014-209727	12/2013	JP	N/A

Primary Examiner: Green; Tracie Y

Assistant Examiner: Diaz; Jose M

Attorney, Agent or Firm: ScienBiziP, P.C.

Background/Summary

BACKGROUND

1. Field

(1) The present disclosure relates to a liquid crystal display device.

2. Description of the Related Art

(2) Liquid crystal display devices are broadly divided into transmissive liquid crystal display devices and reflective liquid crystal display devices. A transmissive liquid crystal display device performs a transmissive mode of display with light emitted by a backlight. A reflective liquid

crystal display device performs a reflective mode of display with ambient light. Further, there has been proposed a liquid crystal display device in which each pixel includes a reflective region in which to perform a display in a reflective mode and a transmissive region in which to perform a display in a transmissive mode. Such liquid crystal display device is called a “transflective or transmissive and reflective liquid crystal display device”.

(3) Reflective or transflective liquid crystal display devices are suitably used, for example, as small-and-medium-sized display devices for use in mobiles for outdoor use. A reflective liquid crystal display device is disclosed, for example, in Japanese Unexamined Patent Application Publication No. 2000-122094. A transflective liquid crystal display device is disclosed, for example, in Japanese Unexamined Patent Application Publication No. 2003-131268.

(4) Liquid crystal display devices that are used in smartphones, tablets, or other devices are equipped with touch sensor functions. Known various types of touch sensor include resistive touch sensors, capacitive touch sensors, and optical touch sensors.

(5) Liquid crystal display devices (hereinafter called “touch panels”) provided with touch sensors are broadly divided into a type (“external type”) of liquid crystal display device with a touch sensor externally attached thereto and a type (“built-in type”) of liquid crystal display device with a touch sensor built therein. A built-in touch panel has an advantage over an external touch panel, for example, in terms of reductions in thickness and weight and has the advantage in its capability to increase light transmittance.

(6) A built-in touch panel is of either an “on-cell type” or an “in-cell type”. The term “cell” here refers to a display panel. The display panel includes an active matrix substrate (TFT substrate), a counter substrate placed opposite the TFT substrate, and a liquid crystal layer provided between the TFT substrate and the counter substrate. In the “in-cell type”, a layer responsible for a touch sensor function is placed within the display panel. In the “on-cell type”, a layer responsible for a touch sensor function is placed between the display panel and a polarizing plate provided on a side of the display panel that faces a viewer.

(7) The in-cell type can achieve, in principal, the thinnest and lightest touch panel. Further, as already mentioned, a liquid crystal display device capable of a reflective mode of display is suitable for outdoor use. Therefore, there has been demand for an in-cell touch panel capable of a reflective mode of display, although such a touch panel is yet to be achieved.

(8) It is desirable to provide a liquid crystal display device that is capable of a reflective mode of display and that can be suitably used as an in-cell touch panel.

SUMMARY

(9) According to an aspect of the disclosure, there is provided a liquid crystal display device including a first substrate, a second substrate placed closer to a viewer than the first substrate, and a liquid crystal layer provided between the first substrate and the second substrate. The liquid crystal display device has a plurality of pixels arranged in a matrix including a plurality of rows and a plurality of columns. Each of the plurality of pixels includes a reflective region in which to perform a display in a reflective mode. The first substrate includes a substrate, a plurality of gate lines extending in a row-wise direction, a plurality of source lines extending in a column-wise direction, a plurality of thin-film transistors provided separately in correspondence with each of the plurality of pixels, a plurality of pixel electrodes each electrically connected to a corresponding one of the plurality of thin-film transistors, and a reflective layer formed from an electrical conducting material, located within at least the reflective region, and provided between the pixel electrodes and the substrate. The first substrate further includes a plurality of touch sensor electrodes to which different signals are applied and a plurality of touch lines each electrically connected to a corresponding one of the plurality of touch sensor electrodes. The plurality of touch lines are formed from a conducting film that is identical to that from which the plurality of source lines are formed, and are provided between the reflective layer and the substrate.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a cross-sectional view schematically showing a liquid crystal display device according to an embodiment of the present disclosure;
- (2) FIG. 2 is an equivalent circuit diagram of a plurality of pixels of the liquid crystal display device;
- (3) FIG. 3 is a plan view schematically showing the liquid crystal display device;
- (4) FIG. 4 is a cross-sectional view schematically showing the liquid crystal display device as taken along line IV-IV in FIG. 3;
- (5) FIG. 5 is a plan view illustrating a positional relationship between touch sensor electrodes and touch lines in the liquid crystal display device;
- (6) FIG. 6 is a plan view schematically showing a liquid crystal display device of a comparative example;
- (7) FIG. 7 is a cross-sectional view schematically showing the liquid crystal display device;
- (8) FIG. 8 is a cross-sectional view schematically showing a liquid crystal display device according to another embodiment of the present disclosure;
- (9) FIG. 9 is a cross-sectional view schematically showing a liquid crystal display device according to still another embodiment of the present disclosure;
- (10) FIG. 10 is a cross-sectional view schematically showing a liquid crystal display device according to still another embodiment of the present disclosure;
- (11) FIG. 11 is a cross-sectional view schematically showing a liquid crystal display device according to still another embodiment of the present disclosure; and
- (12) FIG. 12 is a diagram showing a reflective region and a transmissive region that each pixel of the liquid crystal display device includes.

DESCRIPTION OF THE EMBODIMENTS

(13) The following describes embodiments of the present disclosure with reference to the drawings. Embodiments of the present disclosure are not limited to those illustrated below.

Embodiment 1

(14) A liquid crystal display device **100** according to the present embodiment is described with reference to FIGS. 1 and 2. The liquid crystal display device **100** is a reflective liquid crystal display device that performs a display in a normally black mode. FIG. 1 is a cross-sectional view schematically showing the liquid crystal display device **100**. FIG. 2 is an equivalent circuit diagram of a plurality of pixels P of the liquid crystal display device **100**.

(15) As shown in FIG. 1, the liquid crystal display device **100** includes an active matrix substrate (hereinafter called a “TFT substrate”) **10**, a counter substrate (hereinafter sometimes called a “color filter substrate”) **20** placed closer to a viewer than the TFT substrate **10**, and a liquid crystal layer **30** provided between the TFT substrate **10** and the counter substrate **20**. The liquid crystal display device **100** further includes a polarizing plate **40** placed closer to the viewer than the liquid crystal layer **30** and a phase difference layer **50** placed between the polarizing plate **40** and the liquid crystal layer **30**. In this embodiment, the polarizing plate **40** is placed closer to the viewer than the counter substrate **20**, and the phase difference layer **50** is placed between the polarizing plate **40** and the counter substrate **20**. Specifically, the polarizing plate **40** is an absorptive linear polarizing plate. In the illustrated example, the phase difference layer **50** includes a half-wavelength plate **51** and a quarter-wavelength plate **52**.

(16) Further, as shown in FIG. 2, the liquid crystal display device **100** has a plurality of pixels P. The plurality of pixels P are arranged in a matrix including a plurality of rows and a plurality of columns. Typically, the plurality of pixels P includes red pixels that display red, green pixels that display green, and blue pixels that display blue. As already mentioned, the liquid crystal display

device **100** is a reflective liquid crystal display device. Therefore, each pixel P includes a reflective region Rf in which to perform a display in a reflective mode.

(17) The TFT substrate **10** includes a plurality of gate lines (scanning lines) GL, a plurality of source lines (signal lines) SL, a plurality of thin-film transistors (TFTs) **11**, a plurality of pixel electrodes PE, and a common electrode CE.

(18) The plurality of gate lines GL extend in a row-wise direction. Each gate line GL supplies a corresponding TFT **11** with a gate signal (scanning signal). The plurality of source lines SL extend in a column-wise direction intersecting (e.g. orthogonal to) the row-wise direction. Each source line SL supplies a corresponding TFT **11** with a source signal (display signal).

(19) The plurality of TFTs **11** are provided separately in correspondence with each pixel P. Each TFT **11** has its gate electrode electrically connected to a corresponding gate line GL and has its source electrode electrically connected to a corresponding source line SL. Each of the plurality of pixel electrodes PE is electrically connected to a corresponding TFT **11** (more specifically, to a drain electrode DE of the corresponding TFT **11**).

(20) The common electrode CE is provided to face the pixel electrodes PE across a dielectric layer **15** and can generate transverse electric fields (fringe electric fields) in the liquid crystal layer **30** together with the pixel electrodes PE. As will be described later, the common electrode CE is divided into a plurality of segments.

(21) Next, configurations of the TFT substrate **10** and the counter substrate **20** are more specifically described with reference to FIGS. **3** and **4**. FIG. **3** is a plan view schematically showing the liquid crystal display device **100**. FIG. **4** is a cross-sectional view schematically showing the liquid crystal display device **100** as taken along line IV-IV in FIG. **3**.

(22) The TFT substrate **10** includes a substrate **10a**, the TFTs **11**, a first interlayer insulating layer **12**, and a reflective layer **13**. Further, the TFT substrate **10** further includes a second interlayer insulating layer **14**, the common electrode CE, the dielectric layer **15**, the pixel electrodes PE, and a first horizontal alignment film **19**.

(23) The substrate **10a** supports the TFTs **11** or other components. The substrate **10a** is transparent and has insulation properties. The substrate **10a** is, for example, a glass substrate or a plastic substrate.

(24) The TFTs **11** are provided on top of the substrate **10a**. The TFTs **11** are provided separately in correspondence with each of the plurality of pixels P. Each of the TFTs **11** includes a semiconductor layer SC, a gate insulating layer GI, a gate electrode GE, a source electrode SE, and a drain electrode DE. The gate electrode GE is electrically connected to a corresponding gate line GL, and the source electrode SE is electrically connected to a corresponding source line SL. The drain electrode DE is electrically connected to a pixel electrode PE. A circuit including the TFTs **11**, the gate lines GL, the source lines SL, or other components for driving the plurality of pixels P is sometimes called a “backplane circuit”.

(25) The TFT **11** illustrated has a top-gate structure. The semiconductor layer SC is provided on top of the substrate **10a**. The semiconductor layer SC here is a polycrystalline silicon layer (e.g. a low-temperature polysilicon (LTPS) layer).

(26) The gate insulating layer GI is formed so as to cover the semiconductor layer SC, and the gate electrode GE is provided on top of the gate insulating layer GI. The gate electrode GE faces part (channel region) of the semiconductor layer SC across the gate insulating layer GI. In this embodiment, the gate electrode GE is formed integrally with the gate line GL.

(27) A lower insulating layer **16** is formed so as to cover the gate electrode GE, and the source electrode SE and the drain electrode DE are provided on top of the lower insulating layer **16**. The source electrode SE and the drain electrode DE are formed from the same conducting film as the source line SL (i.e. at the same layer as the source line SL). Further, in this embodiment, the source electrode SE is formed integrally with the source line SL. The source electrode SE is electrically connected to the semiconductor layer SC in a source contact hole CH.sub.S formed in the lower

insulating layer **16** and the gate insulating layer **GI**. The drain electrode **DE** is electrically connected to the semiconductor layer **SC** in a drain contact hole **CH.sub.D** formed in the lower insulating layer **16** and the gate insulating layer **GI**.

(28) The first interlayer insulating layer **12** is provided so as to cover the backplane circuit including the TFT **11**. The first interlayer insulating layer **12** is a layer formed from an organic insulating material and, for example, can be formed with photosensitive resin.

(29) The reflective layer **13** is provided on top of the first interlayer insulating layer **12** so as to be located within at least the reflective region **Rf**. That is, the reflective layer **13** is placed on top of the backplane circuit with the first interlayer insulating layer **12** sandwiched therebetween, and in other words, the first interlayer insulating layer **12** is provided between the reflective layer **13** and the TFT **11**. Furthermore, in other words, the reflective layer **13** is adjacent to the TFT **11** across at least the first interlayer insulating layer **12**.

(30) The reflective layer **13** is formed from an electrical conducting material that reflects light. More specifically, the reflective layer **13** is formed from a high-reflectance metal material. The reflective layer **13** can be made of a material such as a silver alloy, aluminum, or an aluminum alloy.

(31) In the illustrated example, the reflective layer **13** includes a first portion **13a**, a second portion **13b**, and a third portion **13c**.

(32) The first portion **13a** of the reflective layer **13** occupies a large part of the reflective layer **13** and has asperities on a surface thereof. That is, the first portion **13a** of the reflective layer **13** has an uneven surface structure. This uneven surface structure is sometimes called a “micro reflective structure (MRS)”, and is provided to diffusely reflect ambient light to achieve a display that is close to paper white. The uneven surface structure can be constituted, for example, by a plurality of projections **p** randomly arranged so that a center-to-center spacing between adjacent projections **p** is larger than or equal to 5 μm and smaller than or equal to 50 μm or, preferably, larger than or equal to 10 μm and smaller than or equal to 20 μm . The projections **p** have substantially circular or polygonal shapes when seen from a direction normal to the substrate **10a**. The projections **p** occupy an area of, for example, 20% to 40% of the pixels **P**. The projections **p** have a height, for example, greater than or equal to 1 μm and less than or equal to 5 μm .

(33) Any method can be employed to form an uneven surface structure in at least part of the reflective layer **13**. For example, as illustrated, by forming a first interlayer insulating layer **12** having an uneven surface structure and forming a reflective layer **13** on top of the first interlayer insulating layer **12**, an uneven shape reflecting the uneven surface structure of the first interlayer insulating layer **12** can be imparted to a surface of at least part of the reflective layer **13**. A first interlayer insulating layer **12** having an uneven surface structure can be formed, for example, by a method disclosed in Japanese Patent No. 3394926.

(34) As will be described later, the second portion **13b** of the reflective layer **13** functions as a “first contact electrode” for electrically connecting the drain electrode **DE** of the TFT **11** and the pixel electrode **PE**. Further, the third portion **13c** of the reflective layer **13** functions as a “second contact electrode” for electrically connecting a touch line **TL** and a touch sensor electrode **TX** that will be described later. The first portion **13a**, second portion (first contact electrode) **13b**, and third portion (second contact electrode) **13c** of the reflective layer **13** are electrically separated from one another.

(35) In the illustrated example, a transparent conductive layer **17** is sandwiched between the reflective layer **13** and the first interlayer insulating layer **12**. Usable examples of transparent conductive materials for forming the transparent conductive layer **17** include indium tin oxide (ITO), indium zinc oxide (IZO (registered trademark)), and a mixture thereof. Portions **17a**, **17b**, and **17c** of the transparent conductive layer **17** located immediately below the first portion **13a**, second portion **13b**, and third portion **13c** of the reflective layer **13** are called a “first portion”, a “second portion”, and a “third portion”, respectively, of the transparent conductive layer **17**. The transparent conductive layer **17** may be omitted.

(36) The second interlayer insulating layer **14** is provided on top of the first interlayer insulating layer **12** so as to cover the reflective layer **13**. Accordingly, it can be said that the reflective layer **13** is provided between the first interlayer insulating layer **12** and the second interlayer insulating layer **14**. The second interlayer insulating layer **14** is a planarizing layer formed from an organic insulating material and, for example, can be formed with photosensitive resin.

(37) The common electrode CE is provided on top of the second interlayer insulating layer **14**. The common electrode CE is formed from a transparent conductive material. The common electrode CE can be formed of a transparent conductive material that is similar to the material of the transparent conductive layer **17**.

(38) The dielectric layer **15** is provided so as to cover the common electrode CE. The dielectric layer **15** can be formed, for example, from an inorganic insulating material.

(39) The pixel electrodes PE are provided separately in each of the plurality of pixels P. Further, the pixel electrodes PE are provided on top of the dielectric layer **15**. Accordingly, it can be said that the second interlayer insulating layer **14** is provided between the pixel electrodes PE and the reflective layer **13**. Further, it can be said that the reflective layer **13** is adjacent to the pixel electrodes PE across at least the second interlayer insulating layer **14** and is located opposite the liquid crystal layer **30** behind the pixel electrodes PE (i.e. between the pixel electrodes PE and the substrate **10a**).

(40) The pixel electrodes PE are formed from a transparent conductive material. The pixel electrodes PE can be formed of a transparent conductive material that is similar to the material of the transparent conductive layer **17**. Each of the pixel electrodes PE is electrically connected to a corresponding one of the TFTs **11**.

(41) In the illustrated example, the pixel electrode PE is electrically connected to the drain electrode DE of the TFT **11** via the first contact electrode **13b**. The first interlayer insulating layer **12** has formed therein a first pixel contact hole CH.sub.P1 through which at least part of the drain electrode DE of the TFT **11** is exposed, and the first contact electrode **13b** is electrically connected to the drain electrode DE of the TFT **11** in the first pixel contact hole CH.sub.P1. In this embodiment, the second portion **17b** of the transparent conductive layer **17** is sandwiched between the first contact electrode **13b** and the drain electrode DE. Further, the second interlayer insulating layer **14** has formed therein a second pixel contact hole CH.sub.P2 through which part of the first contact electrode **13b** is exposed, and the pixel electrode PE is electrically connected to the first contact electrode **13b** in the second pixel contact hole CH.sub.P2. In this embodiment, a third contact electrode **18** formed from the same transparent conductive film as the common electrode CE is sandwiched between the pixel electrode PE and the first contact electrode **13b**. The third contact electrode **18** may be omitted.

(42) The pixel electrode PE has at least one (in this embodiment, a plurality of) slit s. The formation of a slit s in the pixel electrode PE causes a potential difference between the pixel electrode PE and the common electrode CE, generating a fringe electric field (transverse electric field) in the liquid crystal layer **30**.

(43) The first horizontal alignment film **19** is provided on top of the pixel electrode PE and the dielectric layer **15** and is in contact with the liquid crystal layer **30**. Accordingly, it can be said that the pixel electrode PE and the common electrode CE are provided between the second interlayer insulating layer **14** and the first horizontal alignment film **19**. Further, it can also be said that the dielectric layer **15** is provided between the second interlayer insulating layer **14** and the first horizontal alignment film **19**, and in this embodiment, the common electrode CE is provided between the second interlayer insulating layer **14** and the dielectric layer **15**, and the pixel electrode PE is provided between the dielectric layer **15** and the first horizontal alignment film **19**.

(44) The counter substrate **20** includes a substrate **20a**, a color filter layer **21**, an overcoat layer **22**, and a second horizontal alignment film **29**. Further, although not illustrated here, the counter substrate **20** further includes a plurality of columnar spacers.

(45) The substrate **20a** supports the color filter layer **21** or other components. The substrate **20a** is transparent and has insulation properties. The substrate **20a** is, for example, a glass substrate or a plastic substrate.

(46) Typically, the color filter layer **21** includes red color filters provided in regions that correspond to the red pixels, green color filters provided in regions that correspond to the green pixels, and blue color filters provided in regions that correspond to the blue pixels. The red color filters, the green color filters, and the blue color filters transmit red light, green light, and blue light, respectively. In a case where a color display is not performed, the color filter layer **21** is omitted.

(47) The overcoat layer (planarizing layer) **22** is provided so as to cover the color filter layer **21**. A white display may have a yellowish tint depending on the transparent conductive material used (for the transparent conductive layer **17**, the pixel electrodes PE, and the common electrode CE), the organic insulating material used (for the first interlayer insulating layer **12** and the second interlayer insulating layer **14**), the inorganic insulating material used (for the dielectric layer **15**), and the alignment film material used (for the first horizontal alignment film **19** and the second horizontal alignment film **29**). In that case, the chromaticity of the white display may be brought close to the chromaticity of, for example, a D65 light source by making a chromaticity adjustment (blue shift) by forming the overcoat layer **22** with a blue resist.

(48) The columnar spacers define the thickness (cell gap) of the liquid crystal layer **30**. The columnar spacers can be formed from photosensitive resin.

(49) The second horizontal alignment film **29** is provided on top of the overcoat layer **22** and is in contact with the liquid crystal layer **30**.

(50) The liquid crystal layer **30** contains a nematic liquid crystal material that is positive (i.e. of a positive type) in dielectric anisotropy $\Delta\epsilon$ or a nematic liquid crystal material that is positive (i.e. of a positive type) in dielectric anisotropy $\Delta\epsilon$. The dielectric anisotropy $\Delta\epsilon$ is a difference between a dielectric constant $\epsilon_{\text{sub.}\parallel}$ of a liquid crystal molecule **31** in a long axis direction and a dielectric constant $\epsilon_{\text{sub.}\perp}$ of the liquid crystal molecule **31** in a short axis direction (i.e. $\epsilon_{\text{sub.}\parallel} - \epsilon_{\text{sub.}\perp}$). The liquid crystal layer **30** may further contain a chiral agent. The liquid crystal layer **30** can be formed, for example, by a falling-drop method. The thickness of the liquid crystal layer **30** is not limited to particular values.

(51) Each of the first and second horizontal alignment films **19** and **29** is subjected to an alignment process and defines the orientation of liquid crystal molecules **31** contained in the liquid crystal layer **30**. The orientation defined by the first horizontal alignment film **19** and the orientation defined by the second horizontal alignment film **29** are different from each other.

(52) Since the first horizontal alignment film **19** and the second horizontal alignment film **29** are provided on both sides, respectively, of the liquid crystal layer **30**, the liquid crystal molecules **31** of the liquid crystal layer **30** are horizontally aligned (that is, at a pretilt angle of substantially 0 degree) in the absence of the application of a voltage to at least the liquid crystal layer **30**. As already mentioned, the orientation defined by the first horizontal alignment film **19** and the orientation defined by the second horizontal alignment film **29** are different from each other. Therefore, as shown in FIG. 4, the liquid crystal layer **30** assumes twist alignment when no voltage is applied. When a voltage is applied to the liquid crystal layer **30**, i.e. when transverse electric fields (fringe electric fields) are generated in the liquid crystal layer **30** by the pixel electrodes PE and the common electrode CE, the transverse electric fields cause a change in the alignment of the liquid crystal layer **30**.

(53) In the liquid crystal display device **100** of the present embodiment, the common electrode CE is divided into a plurality of segments TX. Since different signals (voltages) can be applied to the plurality of segments TX, the plurality of segments TX can function as “touch sensor electrodes” in an in-cell touch panel. That is, the TFT substrate **10** of the liquid crystal display device **100** includes a plurality of touch sensor electrodes TX. Each touch sensor electrodes TX is provided in correspondence with two or more pixels P.

(54) Further, the TFT substrate **10** further includes a plurality of touch lines TL. Each of the plurality of touch lines TL is electrically connected to a corresponding one of the plurality of touch sensor electrodes TX. The plurality of touch lines TL extend in the column-wise direction (i.e. in the same direction as the source lines SL), and each touch line TL is placed between source lines SL that are adjacent to each other. Further, the plurality of touch lines TL are formed from the same conducting film as the plurality of source lines SL (i.e. at the same layer as the plurality of source lines SL). Therefore, the plurality of touch lines TL are covered by the first interlayer insulating layer **12** and located between the reflective layer **13** and the substrate **10a**.

(55) In the illustrated example, each touch line TL and a corresponding touch sensor electrode TC are electrically connected to each other via the second contact electrode **13c**. The first interlayer insulating layer **12** has formed therein a first touch contact hole CH.sub.T1 through which part of the touch line TL is exposed, and the second contact electrode **13c** is electrically connected to the touch line TL in the first touch contact hole CH.sub.T1. In this embodiment, the third portion **17c** of the transparent conductive layer **17** is sandwiched between the second contact electrode **13c** and the touch line TL. Further, the second interlayer insulating layer **14** has formed therein a second touch contact hole CH.sub.T2 through which part of the second contact electrode **13c** is exposed, and the touch sensor electrode TX is electrically connected to the second contact electrode **13c** in the second touch contact hole CH.sub.T2.

(56) FIG. 5 is a plan view illustrating a positional relationship between the touch sensor electrodes TX and the touch lines TL. As shown in FIG. 5, the liquid crystal display device **100** has a display region DR and a non-display region FR. The display region DR is defined by the matrix arrangement of pixels P (see FIG. 2). The non-display region FR is located around the display region DR and sometimes called a “peripheral region” or a “frame region”.

(57) In the display region DR, the common electrode CE is divided into the plurality of segments (touch sensor electrodes) TX. Each touch sensor electrode TX is electrically connected to a corresponding touch line TL. A connection TC between the touch sensor electrode TX and the touch line TL is called a “touch line contact”.

(58) The touch lines TL are connected to a touch drive unit TD provided in the non-display region FR. The touch drive unit TD is configured to switch in a time-sharing manner, for example, between a display mode in which the plurality of touch sensor electrodes TX function as the common electrode CE and a touch detection mode in which the plurality of touch sensor electrodes TX function as touch sensor electrodes TX. For example, in the display mode, the touch drive unit TD applies a common signal to the touch sensor electrodes TX (common electrode CE) via the touch lines TL. On the other hand, in the touch detection mode, the touch drive unit TD applies touch driving signals to the touch sensor electrodes TX via the touch lines TL.

(59) To the first portion **13a** (portion having an uneven surface structure) of the reflective layer **13**, a common signal (common voltage) that is different from the common signal that is applied to the touch sensor electrodes TX can be inputted from the non-display region FR. Note, however, that such an aspect is not intended to impose any limitation, but any voltage can be applied to the first portion **13a** of the reflective layer **13**. Further, the first portion **13a** of the reflective layer **13** may, for example, be electrically floating.

(60) The plurality of touch lines TL extend in the column-wise direction (i.e. in the same direction as the source lines SL). Some touch lines TL each extend across another one or more touch sensor electrodes TX to a corresponding touch sensor electrode TX.

(61) With a focus on a certain touch sensor electrode TX, a first touch line TL1 that supplies a signal to the touch sensor electrode TX extends to the touch line contact TC, and a second touch line TL2 for supplying a signal to another touch sensor electrode TX extends across the touch sensor electrode TX. Depending on the position of a touch sensor electrode TX, two touch lines TL may be placed so as to extend across the touch sensor electrode TX, or no touch line TL may be placed across the touch sensor electrode TX.

(62) Although not illustrated, in the non-display region FR, peripheral circuits including driving circuits such as a gate driver that supplies gate signals to the gate lines GL and a source driver that supplies source signals to the source lines SL are provided in addition to the touch drive unit TD. These driving circuits may be mounted, for example, in the TFT substrate **10** or may be integrally (monolithically) formed. In the non-display region FR, a semiconductor chip including some or all of the driving circuits may be mounted.

(63) As mentioned above, in the liquid crystal display device **100** of the present embodiment, the touch lines TL are formed from the same conducting film as the source lines SL (i.e. at the same layer as the source lines SL) and provided between the reflective layer **13** and the substrate **10a** (i.e. opposite the liquid crystal layer **30** behind the reflective layer **13**). This makes it possible to achieve simpler manufacturing processes and lower manufacturing costs than in a case where a configuration of a conventional in-cell touch panel is simply applied to a reflective liquid crystal display device. The following explains why such advantages are brought.

(64) FIGS. **6** and **7** are a plan view and a cross-sectional view schematically showing a liquid crystal display device **900** of a comparative example. The liquid crystal display device **900** of the comparative example can be said to be one obtained by simply applying a configuration of a conventional in-cell touch panel to a reflective liquid crystal display device.

(65) The liquid crystal display device **900** of the comparative example differs from the liquid crystal display device **100** in that the touch lines TL are formed from a conducting film that is different from that from which the source lines SL are formed (i.e. at a layer that is different from that at which the source lines SL are formed). In the liquid crystal display device **900**, the touch lines TL are provided on top of a second insulating layer **14**, and an upper insulating layer **61** is formed so as to cover the touch lines TL. The upper insulating layer **61** can be an organic insulating layer formed from photosensitive resin or an inorganic insulating layer formed from silicon nitride (SiNx). The upper insulating layer **61** has formed therein a touch contact hole CH.sub.T through which part of a touch line TL is exposed, and the touch line TL and a touch sensor electrode TX located on top of the upper insulating layer **61** are electrically connected to each other in the touch contact hole CH.sub.T. The touch lines TL are located between the reflective layer **13** and the liquid crystal layer **30** (i.e. closer to the liquid crystal layer **30** than the reflective layer **13**). Further, the touch lines TL overlap the source lines SL in a plan view.

(66) In a case where the liquid crystal display device **900** of the comparative example is manufactured, there is a need to add a step of depositing and patterning a new conducting film for forming the touch lines TL, a step of depositing and patterning a new insulating layer (upper insulating layer **61**) that covers the touch lines TL, or other steps. This results in more manufacturing processes and higher manufacturing costs.

(67) On the other hand, in manufacturing the liquid crystal display device **100** of the present embodiment, in which the touch lines TL are formed from the same conducting film as the source lines SL (i.e. at the same layer as the source lines SL), there is no need to add a step of depositing and patterning a new conducting film for forming the touch lines TL, a step of depositing and patterning a new insulating layer that covers the touch lines TL, or other steps. This makes it possible to achieve simpler manufacturing processes and lower manufacturing costs than does the liquid crystal display device **900** of the comparative example.

(68) Further, in the liquid crystal display device **100** of the present embodiment, in which the touch lines TL are provided between the reflective layer **13** and the substrate **10a** (i.e. opposite the liquid crystal layer **30** behind the reflective layer **13**), there are only slight decreases in reflection aperture ratio and reflectance due to the touch lines TL. In an in-cell touch panel using a transmissive liquid crystal display device, forming touch lines from the same conducting film as source lines is considered to make it possible to achieve simpler manufacturing processes and lower manufacturing costs. However, in that case, regions in which the touch lines are provided are not usable for a transmissive display, as the touch lines are not able to be placed over the source lines.

This results in a decrease in transmittance, i.e. a decrease in optical performance. On the other hand, in the liquid crystal display device **100** of the present embodiment, in which the touch lines TL are located between the reflective layer **13** and the substrate **10a**, there are almost no decreases in reflection aperture ratio and reflectance, and it can therefore be said that there is almost no such decrease in optical performance as that mentioned above.

(69) While the foregoing description has illustrated a configuration in which the pixel electrodes PE are provided above the common electrode CE, the common electrode CE may be provided above the pixel electrodes PE. In the following, of each of the pixel electrodes PE and the common electrode CE, an electrode located relatively above is sometimes called an “upper electrode”, and an electrode located relatively below is called a “lower electrode”. The upper electrode and the lower electrode are adjacent to each other across the dielectric layer **15**. To generate a transverse electric field, at least the upper electrode includes at least one slit in each pixel P.

(70) In a liquid crystal display device of a comparatively large size (i.e. in which the pixels P are comparatively large in area), it is preferable that the pixel electrodes PE be provided above the common electrode CE. In the configuration in which the pixel electrodes PE are provided above the common electrode CE, there is no need to form a slit in the common electrode CE. This further suppresses a rise in resistivity (surface resistivity) of the common electrode CE than in a configuration in which the common electrode CE is provided above the pixel electrodes CE. A rise in resistivity of the common electrode CE results in a decrease in speed of supply of electric charge to the common electrode CE, increasing the likelihood of failure (such as flicker or shadow) in display of an image (such as a checkered pattern, a stripe pattern, or an image whose display is partly composed of these patterns, with imbalances in the polarity of pixel) that needs a large amount of electric charge to be supplied to the common electrode CE.

(71) In the configuration in which the pixel electrodes PE are provided above the common electrode CE, there is a need to form a slit in each of the pixel electrodes PE. This causes a rise in resistivity of each of the pixel electrodes PE. However, the area of each of the pixel electrodes PE is sufficiently smaller than (e.g. smaller than or equal to one-millionth) the area of the common electrode CE. Therefore, the pixel electrodes PE are to be supplied with smaller amounts of electric charge and are supplied with electric charge from the TFTs **11** connected on a pixel-by-pixel basis. This reduces susceptibility to a display image and also reduces the likelihood of display defects.

(72) In the configuration in which the pixel electrodes PE are provided above the common electrode CE, slits for generating fringe electric fields are not able to be provided in the pixel electrodes PE in regions in which pixel contact holes are formed, and furthermore, there is a need to provide openings in the common electrode CE in those regions. Therefore, effective fringe electric fields are not generated in those regions, and those regions no longer contribute to a reflection display. This can result in lower reflectance than in the configuration in which the common electrode CE is provided above the pixel electrodes PE. Regardless of whether the pixels P are large or small in area, there is a need for a certain area of regions such as contact holes that do not contribute to a reflection display. Therefore, the proportion of regions in the pixels P that do not contribute to a reflection display becomes higher as the pixels P become smaller in area (i.e. become higher in definition), and the aforementioned decrease in reflectance becomes greater. On the other hand, in a liquid crystal display device of a comparatively large size, the proportion of regions in the pixels P that do not contribute to a reflection display is easily reduced, so that the aforementioned decrease in reflectance is easily reduced. For these reasons, in a liquid crystal display device of a comparatively large size (i.e. in which the pixels P are comparatively large in area), the configuration in which the pixel electrodes PE are provided above the common electrode CE is favorable.

(73) Further, as already mentioned, the decrease in reflectance caused when regions in which pixel contact holes are formed do not contribute to a reflection display becomes greater as the pixels P become smaller in area (i.e. become higher in definition); therefore, in a liquid crystal display

device of comparatively high definition (i.e. in which the pixels P are comparatively small in area), it is preferable that the common electrode CE be provided above the pixel electrodes PE.

(74) Further, in the liquid crystal display device **100** of the present embodiment, a display is performed in a transverse electric field mode in which the liquid crystal layer **30** assumes twist alignment when no voltage is applied. More specifically, a display is performed in an FFS mode (referred to as a “TW-FFS mode”) in which the liquid crystal layer **30** assumes twist alignment when no voltage is applied. This makes it possible to further improve the contrast ratio of a reflection display than in a case where a display is performed in a common FFS mode in which the liquid crystal layer **30** does not assume twist alignment (that is, the liquid crystal layer **30** has a twist angle of 0 degree) when no voltage is applied. It is preferable, from a point of view of improvement in contrast ratio, that the liquid crystal layer **30** have a twist angle larger than or equal to 45 degrees and smaller than or equal to 90 degrees when no voltage is applied.

Embodiment 2

(75) A liquid crystal display device **200** according to the present embodiment is described with reference to FIG. 8. FIG. 8 is a cross-sectional view schematically showing the liquid crystal display device **200**. The following gives a description with a focus on points in which the liquid crystal display device **200** according to the present embodiment is different from the liquid crystal display device **100** of Embodiment 1.

(76) The liquid crystal display device **200** of the present embodiment differs from the liquid crystal display device **100** of Embodiment 1 in that the semiconductor layer SC of each of the TFTs **11** is an oxide semiconductor layer. The oxide semiconductor layer can be formed, for example, from an In—Ga—Zn—O semiconductor.

(77) In the configuration illustrated in FIG. 8, the TFT **11** has a bottom-gate structure. The gate electrode GE is provided on top of the substrate **10a**, and the gate insulating layer GI is formed so as to cover the gate electrode GE. The semiconductor layer SC, which is an oxide semiconductor layer, is provided on top of the gate insulating layer GI. The source electrode SE and the drain electrode DE are provided on top of the semiconductor layer SC and on top of the gate insulating layer GI. In the configuration illustrated in FIG. 8, the first interlayer insulating layer **12** has a laminated structure including an inorganic insulating layer **12a** and an organic insulating layer **12b** formed on top of the inorganic insulating layer **12a**.

(78) Also in the liquid crystal display device **200** of the present embodiment, the touch lines TL are formed from the same conducting film as the source lines SL (i.e. at the same layer as the source lines SL). Therefore, the touch lines TL are provided at the gate insulating layer GI and located between the reflective layer **13** and the substrate **10a** (i.e. opposite the liquid crystal layer **30** behind the reflective layer **13**).

(79) The liquid crystal display device **200** of the present embodiment too makes it possible to achieve simpler manufacturing processes and lower manufacturing costs than in a case where a configuration of a conventional in-cell touch panel is simply applied to a reflective liquid crystal display device.

Embodiment 3

(80) A liquid crystal display device **300** according to the present embodiment is described with reference to FIG. 9. FIG. 9 is a cross-sectional view schematically showing the liquid crystal display device **300**. The following gives a description with a focus on points in which the liquid crystal display device **300** according to the present embodiment is different from the liquid crystal display device **100** of Embodiment 1.

(81) The liquid crystal display device **300** of the present embodiment differs from the liquid crystal display device **100** of Embodiment 1 in that the first portion **13a** of the reflective layer **13** does not have an uneven surface structure. In the liquid crystal display device **300**, as shown in FIG. 9, the first interlayer insulating layer **12** does not have an uneven surface structure; therefore, the liquid crystal display device **300** does not have an uneven surface structure, either (i.e. has a substantially

flat surface).

(82) Also in the liquid crystal display device **300** of the present embodiment, the touch lines TL are formed from the same conducting film as the source lines SL (i.e. at the same layer as the source lines SL). This makes it possible to achieve simpler manufacturing processes and lower manufacturing costs.

(83) The liquid crystal display device **300** of the present embodiment may further include a light scattering layer. By using a combination of the reflective layer **13** and the light scattering layer, a display that is close to paper white can be achieved. The light scattering layer can be, for example, a light scattering sheet placed on a side of the counter substrate **20** that faces the viewer.

Embodiment 4

(84) A liquid crystal display device **400** according to the present embodiment is described with reference to FIG. **10**. FIG. **10** is a cross-sectional view schematically showing the liquid crystal display device **400**. The following gives a description with a focus on points in which the liquid crystal display device **400** according to the present embodiment is different from the liquid crystal display device **200** of Embodiment 2.

(85) In the liquid crystal display device **200** of Embodiment 2, the source lines SL and the touch lines TL are located closer to the liquid crystal layer **30** than the gate lines GL. On the other hand, as will be described below, in the liquid crystal display device **400** of the present embodiment, the source lines SL and the touch lines TL are located closer to the substrate **10a** than the gate lines GL.

(86) As shown in FIG. **10**, the TFT substrate **10** of the liquid crystal display device **400** further includes a light-shielding layer LS. The light-shielding layer LS is provided on top of the substrate **10a**. The source lines SL and the source electrode SE and drain electrode DE of each of the TFTs **11** are formed from the same conducting film as the light-shielding layer LS (i.e. at the same layer as the light-shielding layer LS).

(87) A lower insulating layer **16'** is formed so as to cover the light-shielding layer LS or other components. The semiconductor layer SC, which is an oxide semiconductor layer, is provided on top of the lower insulating layer **16'**. The light-shielding layer LS faces at least a channel region of the semiconductor layer SC across the lower insulating layer **16'**. The semiconductor layer SC is electrically connected to the source electrode SE and the drain electrode DE in a source contact hole CH.sub.S and a drain contact hole CH.sub.D, respectively, formed in the lower insulating layer **16'**.

(88) The gate insulating layer GI is formed so as to cover the semiconductor layer SC, and the gate electrode GE and the gate line GL are provided on top of the gate insulating layer GI. The gate electrode GE faces the channel region of the semiconductor layer SC across the gate insulating layer GI. The first pixel contact hole CH.sub.P1 is formed across the first interlayer insulating layer **12**, the gate insulating layer GI, and the lower insulating layer **16'**.

(89) Also in the liquid crystal display device **400** of the present embodiment, the touch lines TL are formed from the same conducting film as the source lines SL (i.e. at the same layer as the source lines SL). Therefore, the touch lines TL are covered with the lower insulating layer **16'**, and the first touch contact hole CH.sub.T1 is formed across the first interlayer insulating layer **12**, the gate insulating layer GI, and the lower insulating layer **16'**.

(90) A common top-gate oxide semiconductor TFT is usually configured such that a gate electrode is placed on top of part of an oxide semiconductor layer with a gate insulating layer sandwiched therebetween and a source electrode, a drain electrode, and a source line are placed on top of an insulating layer covering the gate electrode. That is, a source metal layer including the source lines or other components is located above a gate metal layer including the gate electrode. Such a configuration is called an "upper source structure" here.

(91) On the other hand, in the TFT substrate **10** of the liquid crystal display device **400**, the source metal layer is located below (i.e. closer to the substrate **10a** than) the gate metal layer. Such a

configuration is called a “lower source structure” here.

(92) Also in the liquid crystal display device **400** of the present embodiment, in which the lower source structure is adopted, the touch lines TL are formed from the same conducting film as the source lines SL (i.e. at the same layer as the source lines SL). This makes it possible to achieve simpler manufacturing processes and lower manufacturing costs.

(93) Oxide Semiconductor TFT

(94) As a TFT **11** to be provided in each pixel P, an oxide semiconductor TFT can be suitably used as illustrated in the liquid crystal display device **200** of Embodiment 2 and the liquid crystal display device **400** of Embodiment 4. In the oxide semiconductor TFT, an oxide semiconductor is used as a material of an active layer. That is, the oxide semiconductor TFT includes an oxide semiconductor layer as the active layer. The oxide semiconductor is a material that has recently drawn attention as an active layer material that replaces amorphous silicon and polycrystalline silicon.

(95) The oxide semiconductor is higher in mobility than amorphous silicon. For this reason, the oxide semiconductor TFT can operate at higher speed than can an amorphous silicon. Further, the oxide semiconductor layer can also be applied to a large-area device, as the oxide semiconductor is formed by a simpler process than is a polycrystalline silicon layer.

(96) Furthermore, since the oxide semiconductor TFT is superior in off-leak characteristic, it is also possible to utilize a driving scheme of performing a display with a reduction in the frequency of refreshing of an image. For example, when a still image is displayed, an operation can be performed such that image data is refreshed once a second. Such a driving scheme is called “intermittent driving” or “low-frequency driving” and makes it possible to achieve a drastic cut in the amount of electricity that is consumed by a liquid crystal display device.

(97) Adopting intermittent driving to perform touch detection in a period during which the image is not refreshed makes it possible to reduce deterioration in sensitivity of a touch operation due to noise from a driving circuit and make the S/N ratio (signal-to-noise ratio) approximately ten times higher than has conventionally been the case.

(98) Further, since the oxide semiconductor TFT is also favorable to reduction in TFT size, it is also possible to suitably achieve a configuration (called “memory-in-pixel (MIP)”) in which a memory circuit is provided for each pixel P. A specific MIP configuration is not described here, as it is publicly known.

(99) The oxide semiconductor contained in the active layer (oxide semiconductor layer) of the oxide semiconductor TFT may be an amorphous oxide semiconductor or may be a crystalline oxide semiconductor having a crystalline portion. Examples of the crystalline oxide semiconductor include a polycrystalline oxide semiconductor, a microcrystalline oxide semiconductor, and a crystalline oxide semiconductor whose c axis is aligned substantially perpendicularly to a layer surface.

(100) The oxide semiconductor layer may have a laminated structure of two or more layers. An oxide semiconductor layer having a laminated structure may include an amorphous oxide semiconductor layer and a crystalline oxide semiconductor layer or may include a plurality of crystalline oxide semiconductor layers of different crystal structures. Further, an oxide semiconductor layer having a laminated structure may include a plurality of amorphous oxide semiconductor layers. In a case where the oxide semiconductor layer has a two-layer structure including an upper layer and a lower layer, the energy gap of an oxide semiconductor contained in the lower layer and the energy gap of an oxide semiconductor contained in the upper layer may be different from each other.

(101) An amorphous oxide semiconductor, a material of, a structure of, and a method for forming each of the aforementioned crystalline oxide semiconductors, a configuration of an oxide semiconductor layer having a laminated structure, or other features are disclosed, for example, in Japanese Unexamined Patent Application Publication No. 2014-007399, the entire contents of which are hereby incorporated by reference.

(102) The oxide semiconductor layer may contain at least one of metallic elements In, Ga, and Zn. In the present embodiment, the oxide semiconductor layer contains an In—Ga—Zn—O semiconductor (e.g. indium-gallium-zinc oxide). The In—Ga—Zn—O semiconductor here is a ternary oxide of In (indium), Ga (gallium), and Zn (zinc), and the proportions (composition ratios) of In, Ga, and Zn are not limited to particular values. Examples of the proportions include In:Ga:Zn=2:2:1, In:Ga:Zn=1:1:1, and In:Ga:Zn=1:1:2. Such an oxide semiconductor layer can be formed from an oxide semiconductor film containing the In—Ga—Zn—O semiconductor.

(103) The In—Ga—Zn—O semiconductor may be amorphous or may be crystalline. As a crystalline In—Ga—Zn—O semiconductor, a crystalline In—Ga—Zn—O semiconductor whose c axis is aligned substantially perpendicularly to a layer surface is preferable.

(104) A crystal structure of a crystalline In—Ga—Zn—O semiconductor is disclosed, for example, in the aforementioned Japanese Unexamined Patent Application Publication No. 2014-007399, Japanese Unexamined Patent Application Publication No. 2012-134475, and Japanese Unexamined Patent Application Publication No. 2014-209727, the entire contents of which are hereby incorporated by reference. A TFT having an In—Ga—Zn—O semiconductor layer has high mobility (more than twenty times higher than the mobility of an a-Si TFT) and a low leak current (less than one-hundredth the leak current of an a-Si TFT) and can therefore be suitably used as a driving TFT (TFT that is included in a driving circuit provided, for example, near a display region including a plurality of pixels and on the same substrate as the display region) and a pixel TFT (TFT that is provided in a pixel).

(105) The oxide semiconductor layer may contain another oxide semiconductor instead of the In—Ga—Zn—O semiconductor. For example, the oxide semiconductor layer may contain an In—Sn—Zn—O semiconductor (e.g. In.sub.2O.sub.3—SnO.sub.2—ZnO; InSnZnO). The In—Sn—Zn—O semiconductor is a ternary oxide of In (indium), Sn (tin), and Zn (zinc). Alternatively, the oxide semiconductor layer may contain an In—Al—Zn—O semiconductor, an In—Al—Sn—Zn—O semiconductor, a Zn—O semiconductor, an In—Zn—O semiconductor, a Zn—Ti—O semiconductor, a Cd—Ge—O semiconductor, a Cd—Pb—O semiconductor, CdO (oxide cadmium), a Mg—Zn—O semiconductor, an In—Ga—Sn—O semiconductor, an In—Ga—O semiconductor, a Zr—In—Zn—O semiconductor, a Hf—In—Zn—O semiconductor, an Al—Ga—Zn—O semiconductor, a Ga—Zn—O semiconductor, an In—Ga—Zn—Sn—O semiconductor, or other semiconductors.

(106) Transflective Liquid Crystal Display Device

(107) While the reflective liquid crystal display devices **100**, **200**, **300**, and **400** have been described so far, a liquid crystal display device according to an embodiment of the present disclosure may be a transflective liquid crystal display device. A configuration of a transflective liquid crystal display device **500** is described with reference to FIG. **11**.

(108) The liquid crystal display device **500** differs from the liquid crystal display devices **100**, **200**, **300**, and **400** in that the liquid crystal display device **500** includes a further polarizing plate **40'**, a further phase difference layer **50'**, and a lighting device (backlight) **70**.

(109) The polarizing plate **40'** is placed further backward than the liquid crystal layer **30**. More specifically, the polarizing plate **40'** is placed further backward than the TFT substrate **10**.

(110) The phase difference layer **50'** is placed between the polarizing plate **40'** and the liquid crystal layer **30**. More specifically, the phase difference layer **50'** is placed between the polarizing plate **40'** and the TFT substrate **10**. The phase difference layer **50'** can include a half-wavelength plate and a quarter-wavelength plate.

(111) The lighting device **70** is placed at the back of the polarizing plate **40'** (i.e. at the back of the TFT substrate **10**). In the illustrated example, the lighting device **70** includes a light source (e.g. an LED) **71** that emits light, a light guide plate **72** that guides the light from the light source **71** toward the polarizing plate **40'**, and a reflective plate **73** placed on the back of the light guide plate **72**. The lighting device **70** may further include a prism sheet and a diffusion sheet placed on the front (or

back) of the light guide plate 72.

(112) As shown in FIG. 12, each pixel P of the liquid crystal display device 500 includes a reflective region Rf in which to perform a display in a reflective mode and a transmissive region Tr in which to perform a display in a transmissive mode. The reflective layer 13 of the TFT substrate 10 has an opening 130 formed in the transmissive region Tr. The proportion of the area of the transmissive region Tr to the area of the pixel P can be set as appropriate depending, for example, on the intended use and ranges, for example, from 20% to 90%. Further, the position and shape of the transmissive region Tr in the pixel P can also be set as appropriate depending, for example, on the intended use.

(113) An embodiment of the present disclosure makes it possible to provide a liquid crystal display device that is capable of a reflective mode of display and that can be suitably used as an in-cell touch panel. An embodiment of the present disclosure is suitably used in reflective and transfective liquid crystal display devices.

(114) The present disclosure contains subject matter related to that disclosed in Japanese Priority Patent Application JP 2023-145981 filed in the Japan Patent Office on Sep. 8, 2023, the entire contents of which are hereby incorporated by reference.

(115) It should be understood by those skilled in the art that various modifications, combinations, sub-combinations and alterations may occur depending on design requirements and other factors insofar as they are within the scope of the appended claims or the equivalents thereof.

Claims

1. A liquid crystal display device comprising: a first substrate; a second substrate placed closer to a viewer than the first substrate; and a liquid crystal layer provided between the first substrate and the second substrate, the liquid crystal display device having a plurality of pixels arranged in a matrix including a plurality of rows and a plurality of columns, wherein each of the plurality of pixels includes a reflective region in which to perform a display in a reflective mode, the first substrate includes a substrate, a plurality of gate lines extending in a row-wise direction, a plurality of source lines extending in a column-wise direction, a plurality of thin-film transistors provided separately in correspondence with each of the plurality of pixels, a plurality of pixel electrodes each electrically connected to a corresponding one of the plurality of thin-film transistors, and a reflective layer formed from an electrical conducting material, located within at least the reflective region, and provided between the pixel electrodes and the substrate, the first substrate further includes a plurality of touch sensor electrodes to which different signals are applied, and a plurality of touch lines each electrically connected to a corresponding one of the plurality of touch sensor electrodes, and the plurality of touch lines are formed from a conducting film that is identical to that from which the plurality of source lines are formed, and are provided between the reflective layer and the substrate.
2. The liquid crystal display device according to claim 1, wherein each of the plurality of touch lines is placed between ones of the plurality of source lines that are adjacent to each other.
3. The liquid crystal display device according to claim 1, wherein the first substrate has a first horizontal alignment film in contact with the liquid crystal layer, the second substrate has a second horizontal alignment film in contact with the liquid crystal layer, and the liquid crystal layer assumes twist alignment when no voltage is applied.
4. The liquid crystal display device according to claim 3, wherein the liquid crystal layer has a twist angle larger than or equal to 45 degrees and smaller than or equal to 90 degrees when no voltage is applied.
5. The liquid crystal display device according to claim 1, wherein the reflective layer includes a portion electrically connecting any one of the plurality of touch sensor electrodes and one of the plurality of touch lines that corresponds to the one touch sensor electrode.

6. The liquid crystal display device according to claim 1, wherein at least part of the reflective layer has an uneven surface structure.
 7. The liquid crystal display device according to claim 1, wherein the first substrate further includes a first interlayer insulating layer provided between the reflective layer and the thin-film transistors and a second interlayer insulating layer provided between the pixel electrodes and the reflective layer.
 8. The liquid crystal display device according to claim 1, wherein the first substrate further includes a common electrode provided to face the pixel electrodes across a dielectric layer, the common electrode is divided into a plurality of segments that function as the plurality of touch sensor electrodes, and at least either each of the pixel electrodes or the common electrode includes at least one slit.
 9. The liquid crystal display device according to claim 1, wherein the plurality of source lines and the plurality of touch lines are located closer to the liquid crystal layer than the plurality of gate lines.
 10. The liquid crystal display device according to claim 1, wherein the plurality of source lines and the plurality of touch lines are located closer to the substrate than the plurality of gate lines.
 11. The liquid crystal display device according to claim 1, wherein each of the plurality of pixels includes a transmissive region in which to perform a display in a transmissive mode, and the reflective layer has an opening formed in the transmissive region.
-