

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411532
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	He; Qinghong

Fan apparatus for an information handling system

Abstract

A fan apparatus for an information handling system, including a fan having a first side and a second side, the second side positioned opposite to the first side, the fan including: a shaft; a plurality of blades coupled to the shaft; and a rib coupled to one or more of the plurality of blades at the first side of the fan; a fan housing, including: an opening; and an emboss surrounding the opening; wherein the fan is coupled to the fan housing with the first side of the fan in superimposition with the opening of the fan housing such that the rib of the fan is positioned within the emboss of the fan housing.

Inventors:	He; Qinghong (Austin, TX)
Applicant:	Dell Products L.P. (Round Rock, TX)
Family ID:	94689560
Assignee:	Dell Products L.P. (Round Rock, TX)
Appl. No.:	18/455709
Filed:	August 25, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250068217 A1	Feb. 27, 2025

Publication Classification

Int. Cl.: G06F1/20 (20060101); H05K7/20 (20060101)

U.S. Cl.:

CPC G06F1/20 (20130101); H05K7/20172 (20130101);

Field of Classification Search

CPC: F04D (29/281); F04D (25/0613); F04D (29/30); F04D (17/025); F04D (29/325); F04D (29/326); F04D (29/329); F04D (29/4226); F04D (19/002); F04D (25/064); F04D (25/08); F04D (29/164); F04D (29/263); F04D (29/34); F04D (29/38); H05K (7/20172); H05K (7/20145); G06F (1/20); G06F (2200/201); F05D (2240/304); F01D (5/147); F01D (5/225)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5423660	12/1994	Sortor	416/247R	F04D 29/164
5489186	12/1995	Yapp	415/58.7	F01D 5/141
6508624	12/2002	Nadeau	415/173.6	F01D 11/08
9909485	12/2017	Hong	N/A	F04D 29/164
11959489	12/2023	Cote	N/A	F04D 29/384
2007/0098571	12/2006	Nagamatsu	417/354	F04D 29/281
2007/0224044	12/2006	Hong	415/211.2	F04D 29/547
2009/0060730	12/2008	Hwang	415/203	F04D 29/30
2010/0149753	12/2009	Lin	361/695	H05K 7/20172
2012/0301277	12/2011	Chang	415/119	F04D 29/051
2020/0003222	12/2019	Kennedy	N/A	F04D 29/023
2020/0173336	12/2019	Hong	N/A	B60K 11/00
2022/0025899	12/2021	Hong	N/A	F04D 29/526
2022/0136520	12/2021	He	416/175	F04D 29/327
2023/0228279	12/2022	Cote	416/189	F04D 29/023
2024/0426317	12/2023	He	N/A	F04D 29/4226

Primary Examiner: Matey; Michael A

Attorney, Agent or Firm: McDermott Will & Schulte LLP

Background/Summary

BACKGROUND

Field of the Disclosure

(1) The disclosure relates generally to fan apparatus for an information handling system.

Description of the Related Art

(2) As the value and use of information continues to increase, individuals and businesses seek additional ways to process and store information. One option available to users is information handling systems. An information handling system generally processes, compiles, stores, and/or communicates information or data for business, personal, or other purposes thereby allowing users to take advantage of the value of the information. Because technology and information handling needs and requirements vary between different users or applications, information handling systems may also vary regarding what information is handled, how the information is handled, how much information is processed, stored, or communicated, and how quickly and efficiently the information

may be processed, stored, or communicated. The variations in information handling systems allow for information handling systems to be general or configured for a specific user or specific use such as financial transaction processing, airline reservations, enterprise data storage, or global communications. In addition, information handling systems may include a variety of hardware and software components that may be configured to process, store, and communicate information and may include one or more computer systems, data storage systems, and networking systems.

SUMMARY

(3) Innovative aspects of the subject matter described in this specification may be embodied in a fan apparatus for an information handling system, including a fan having a first side and a second side, the second side positioned opposite to the first side, the fan including: a shaft; a plurality of blades coupled to the shaft; and a rib coupled to one or more of the plurality of blades at the first side of the fan; a fan housing, including: an opening; and an emboss surrounding the opening; wherein the fan is coupled to the fan housing with the first side of the fan in superimposition with the opening of the fan housing such that the rib of the fan is positioned within the emboss of the fan housing.

(4) Other embodiments of these aspects include corresponding systems and apparatus.

(5) These and other embodiments may each optionally include one or more of the following features. For instance, the opening is circular. The emboss is circular. The rib is circular. The emboss includes a first wall spaced-apart from a second wall, wherein the rib is positioned within the emboss such that the rib is spaced-apart from the first wall and the second wall. The emboss further includes a surface positioned between the first wall and the second wall, wherein the rib is positioned within the emboss such that the rib is spaced-apart from the surface. The fan further includes an additional rib coupled to each of the plurality of blades at the first side of the fan, the fan housing further includes an additional emboss surrounding the opening, the fan is coupled to the fan housing with the first side of the fan in superimposition with the opening of the fan housing such that the additional rib of the fan is positioned within the additional emboss of the fan housing. The emboss surrounds the additional emboss. The fan further includes an additional rib coupled to each of the plurality of blades at the second side of the fan, the fan housing having a first side and a second side, the second side positioned opposite to the first side, the fan housing further including an additional opening positioned on the second side and an additional emboss surrounding the additional opening, the fan is coupled to the fan housing with the second side of the fan in superimposition with the additional opening of the fan housing such that the additional rib of the fan is positioned within the additional emboss of the fan housing. The opening of the fan housing is positioned on the first side of the fan housing.

(6) The details of one or more embodiments of the subject matter described in this specification are set forth in the accompanying drawings and the description below. Other potential features, aspects, and advantages of the subject matter will become apparent from the description, the drawings, and the claims.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a block diagram of selected elements of an embodiment of an information handling system.

(2) FIG. 2 illustrates a block diagram of an information handling system including a fan apparatus.

(3) FIG. 3 illustrates a cutaway side view of the fan apparatus.

(4) FIG. 4A illustrates a cutaway side view of the fan apparatus.

(5) FIG. 4B illustrates a cutaway perspective view of the fan apparatus.

(6) FIG. 5A illustrates a cutaway side view of the fan apparatus including multiple ribs and

multiple embosses on a same side.

(7) FIG. 5B illustrates a cutaway perspective view of the fan apparatus including multiple ribs and multiple embosses on a same side.

(8) FIG. 6A illustrates a cutaway side view of the fan apparatus including multiple ribs and multiple embosses on opposite sides.

(9) FIG. 6B illustrates a perspective view of the fan apparatus including multiple ribs and multiple embosses on opposite sides.

DESCRIPTION OF PARTICULAR EMBODIMENT(S)

(10) This disclosure discusses a fan apparatus of an information handling system. In short, an air gap is maintained between a fan and a fan housing to account for several factors that could drive fan blades of the fan to come into contact with the fan housing—wobble of the fan blades, mechanical tolerance in dimensions of the fan blades, and fan housing deformation. However, such an air cap can create an air flow path for recirculation of air back to the fan.

(11) Specifically, this disclosure discusses a fan apparatus for an information handling system, including: a fan having a first side and a second side, the second side positioned opposite to the first side, the fan including: a shaft; a plurality of blades coupled to the shaft; and a rib coupled to each of the plurality of blades at the first side of the fan; a fan housing, including: an opening; and an emboss surrounding the opening; wherein the fan is coupled to the fan housing with the first side of the fan in superimposition with the opening of the fan housing such that the rib of the fan is positioned within the emboss of the fan housing.

(12) In the following description, details are set forth by way of example to facilitate discussion of the disclosed subject matter. It should be apparent to a person of ordinary skill in the field, however, that the disclosed embodiments are exemplary and not exhaustive of all possible embodiments.

(13) For the purposes of this disclosure, an information handling system may include an instrumentality or aggregate of instrumentalities operable to compute, classify, process, transmit, receive, retrieve, originate, switch, store, display, manifest, detect, record, reproduce, handle, or utilize various forms of information, intelligence, or data for business, scientific, control, entertainment, or other purposes. For example, an information handling system may be a personal computer, a PDA, a consumer electronic device, a network storage device, or another suitable device and may vary in size, shape, performance, functionality, and price. The information handling system may include memory, one or more processing resources such as a central processing unit (CPU) or hardware or software control logic. Additional components of the information handling system may include one or more storage devices, one or more communications ports for communicating with external devices as well as various input and output (I/O) devices, such as a keyboard, a mouse, and a video display. The information handling system may also include one or more buses operable to transmit communication between the various hardware components.

(14) For the purposes of this disclosure, computer-readable media may include an instrumentality or aggregation of instrumentalities that may retain data and/or instructions for a period of time. Computer-readable media may include, without limitation, storage media such as a direct access storage device (e.g., a hard disk drive or floppy disk), a sequential access storage device (e.g., a tape disk drive), compact disk, CD-ROM, DVD, random access memory (RAM), read-only memory (ROM), electrically erasable programmable read-only memory (EEPROM), and/or flash memory (SSD); as well as communications media such wires, optical fibers, microwaves, radio waves, and other electromagnetic and/or optical carriers; and/or any combination of the foregoing.

(15) Particular embodiments are best understood by reference to FIGS. 1-6 wherein like numbers are used to indicate like and corresponding parts.

(16) Turning now to the drawings, FIG. 1 illustrates a block diagram depicting selected elements of an information handling system 100 in accordance with some embodiments of the present

disclosure. In various embodiments, information handling system **100** may represent different types of portable information handling systems, such as, display devices, head mounted displays, head mount display systems, smart phones, tablet computers, notebook computers, media players, digital cameras, 2-in-1 tablet-laptop combination computers, and wireless organizers, or other types of portable information handling systems. In one or more embodiments, information handling system **100** may also represent other types of information handling systems, including desktop computers, server systems, controllers, and microcontroller units, among other types of information handling systems. Components of information handling system **100** may include, but are not limited to, a processor subsystem **120**, which may comprise one or more processors, and system bus **121** that communicatively couples various system components to processor subsystem **120** including, for example, a memory subsystem **130**, an I/O subsystem **140**, a local storage resource **150**, and a network interface **160**. System bus **121** may represent a variety of suitable types of bus structures, e.g., a memory bus, a peripheral bus, or a local bus using various bus architectures in selected embodiments. For example, such architectures may include, but are not limited to, Micro Channel Architecture (MCA) bus, Industry Standard Architecture (ISA) bus, Enhanced ISA (EISA) bus, Peripheral Component Interconnect (PCI) bus, PCI-Express bus, HyperTransport (HT) bus, and Video Electronics Standards Association (VESA) local bus.

(17) As depicted in FIG. **1**, processor subsystem **120** may comprise a system, device, or apparatus operable to interpret and/or execute program instructions and/or process data, and may include a microprocessor, microcontroller, digital signal processor (DSP), application specific integrated circuit (ASIC), or another digital or analog circuitry configured to interpret and/or execute program instructions and/or process data. In some embodiments, processor subsystem **120** may interpret and/or execute program instructions and/or process data stored locally (e.g., in memory subsystem **130** and/or another component of information handling system). In the same or alternative embodiments, processor subsystem **120** may interpret and/or execute program instructions and/or process data stored remotely (e.g., in network storage resource **170**).

(18) Also in FIG. **1**, memory subsystem **130** may comprise a system, device, or apparatus operable to retain and/or retrieve program instructions and/or data for a period of time (e.g., computer-readable media). Memory subsystem **130** may comprise random access memory (RAM), electrically erasable programmable read-only memory (EEPROM), a PCMCIA card, flash memory, magnetic storage, opto-magnetic storage, and/or a suitable selection and/or array of volatile or non-volatile memory that retains data after power to its associated information handling system, such as system **100**, is powered down.

(19) In information handling system **100**, I/O subsystem **140** may comprise a system, device, or apparatus generally operable to receive and/or transmit data to/from/within information handling system **100**. I/O subsystem **140** may represent, for example, a variety of communication interfaces, graphics interfaces, video interfaces, user input interfaces, and/or peripheral interfaces. In various embodiments, I/O subsystem **140** may be used to support various peripheral devices, such as a touch panel, a display adapter, a keyboard, an accelerometer, a touch pad, a gyroscope, an IR sensor, a microphone, a sensor, or a camera, or another type of peripheral device.

(20) Local storage resource **150** may comprise computer-readable media (e.g., hard disk drive, floppy disk drive, CD-ROM, and/or other type of rotating storage media, flash memory, EEPROM, and/or another type of solid state storage media) and may be generally operable to store instructions and/or data. Likewise, the network storage resource may comprise computer-readable media (e.g., hard disk drive, floppy disk drive, CD-ROM, and/or other type of rotating storage media, flash memory, EEPROM, and/or other type of solid state storage media) and may be generally operable to store instructions and/or data.

(21) In FIG. **1**, network interface **160** may be a suitable system, apparatus, or device operable to serve as an interface between information handling system **100** and a network **110**. Network interface **160** may enable information handling system **100** to communicate over network **110** using

a suitable transmission protocol and/or standard, including, but not limited to, transmission protocols and/or standards enumerated below with respect to the discussion of network **110**. In some embodiments, network interface **160** may be communicatively coupled via network **110** to a network storage resource **170**. Network **110** may be a public network or a private (e.g. corporate) network. The network may be implemented as, or may be a part of, a storage area network (SAN), personal area network (PAN), local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), a wireless local area network (WLAN), a virtual private network (VPN), an intranet, the Internet or another appropriate architecture or system that facilitates the communication of signals, data and/or messages (generally referred to as data). Network interface **160** may enable wired and/or wireless communications (e.g., NFC or Bluetooth) to and/or from information handling system **100**.

(22) In particular embodiments, network **110** may include one or more routers for routing data between client information handling systems **100** and server information handling systems **100**. A device (e.g., a client information handling system **100** or a server information handling system **100**) on network **110** may be addressed by a corresponding network address including, for example, an Internet protocol (IP) address, an Internet name, a Windows Internet name service (WINS) name, a domain name or other system name. In particular embodiments, network **110** may include one or more logical groupings of network devices such as, for example, one or more sites (e.g. customer sites) or subnets. As an example, a corporate network may include potentially thousands of offices or branches, each with its own subnet (or multiple subnets) having many devices. One or more client information handling systems **100** may communicate with one or more server information handling systems **100** via any suitable connection including, for example, a modem connection, a LAN connection including the Ethernet or a broadband WAN connection including DSL, Cable, Ti, T3, Fiber Optics, Wi-Fi, or a mobile network connection including GSM, GPRS, 3G, or WiMax.

(23) Network **110** may transmit data using a desired storage and/or communication protocol, including, but not limited to, Fibre Channel, Frame Relay, Asynchronous Transfer Mode (ATM), Internet protocol (IP), other packet-based protocol, small computer system interface (SCSI), Internet SCSI (iSCSI), Serial Attached SCSI (SAS) or another transport that operates with the SCSI protocol, advanced technology attachment (ATA), serial ATA (SATA), advanced technology attachment packet interface (ATAPI), serial storage architecture (SSA), integrated drive electronics (IDE), and/or any combination thereof. Network **110** and its various components may be implemented using hardware, software, or any combination thereof.

(24) Turning to FIG. 2, FIG. 2 illustrates an environment **200** including an information handling system **202**. The information handling system **202** can include a fan apparatus **210**. The fan apparatus **210** can include a fan **212** and a fan housing **214**. In some examples, the information handling system **202** is similar to, or includes, the information handling system **100** of FIG. 1. The fan **212** can be coupled to the fan housing **214**.

(25) FIG. 3 is a cutaway side view of the fan **212** and the fan housing apparatus **214** (or fan housing **214**). The fan **212** can include a shaft **302**, a first fan blade **304a**, a second fan blade **304b** (collectively referred to as fan blades **304**), a bearing **306**, stators **310**, magnets **312**, and a control printed circuit board (PCB) **318**. The fan housing apparatus **214** (or fan housing **214**) can include an opening **350**.

(26) The bearing **306** surrounds the shaft **302**. The bearing **306** can extend from the fan housing **214**.

(27) The stators **310** can substantially surround the bearing **306**.

(28) The fan blades **304** can be connected/coupled to the shaft **302**. The first fan blade **304a** can extend away from the shaft **302** in a first direction; and the second fan blade **304b** can extend away from the shaft **302** in a second direction opposite to the first direction. In some examples, the fan blades **304** can be considered a single fan blade **304**. In some examples, the first fan blade **304a** and the second fan blade **304b** are connected, forming a congruent fan blade. The fan blades **304**

can rotate about the shaft **302**.

(29) The magnets **312** can be coupled to respective fan blades **304** and positioned adjacent to the stators **310**. The magnets **312** can substantially surround the stators **310** and the bearing **306**. The magnets **312** and the stators **310** facilitate rotation of the fan blades **304** with respect to the shaft **302** (e.g., clockwise rotation and/or counter-clockwise rotation).

(30) The PCB **318** can provide control/management of the fan **214**, and in particular, rotation of the fan blades **304**.

(31) In short, an air gap is maintained between the fan **212** and the fan housing **214** to account for several factors that could drive the fan blades **304** to come into contact with the fan housing **214**—wobble of the fan blades **304**, mechanical tolerance in dimensions of the fan blades **304**, and fan housing **214** deformation. Such an air gap can create an air flow path for recirculation of air back to the fan **212**.

(32) FIG. **4A** illustrates a cutaway side view of a fan apparatus **210**; and FIG. **4B** illustrates a cutaway perspective view of the fan apparatus **210**. Referring to FIGS. **4A**, **4B**; the fan **212** can include a first side **402** and a second side **404**. The second side **404** is positioned opposite to the first side **402**. The fan **212** can include the shaft **302**, and the blades **304** coupled to the shaft **302**. The fan **212** can further include a rib **410**. In some examples, the rib **410** is coupled to each of the blades **304** at the first side **402** of the fan **212**. In some examples, the rib **410** is coupled to a subset of the blades **304** at the first side **402** of the fan **212**. In some examples, the rib **410** is circular.

(33) The fan housing **214** includes the opening **350** and an emboss **420** surrounding the opening **350**. The emboss **420** includes a first wall **422** spaced-part from a second wall **424**. The emboss **420** can include a surface **426** positioned between the first wall **422** and the second wall **424**. The first wall **422**, the second wall **424**, and the surface **426** define a recess **428** of the emboss **420**. In some examples, the opening **350** is circular. In some examples, the emboss **420** is circular.

(34) To that end, the fan **212** is coupled to the fan housing **214** with the first side **402** of the fan **212** in superimposition with the opening **350** of the fan housing **214**. Furthermore, the fan **212** is coupled to the fan housing **214** with the first side **402** of the fan **212** in superimposition with the opening **350** of the fan housing **214** such that the rib **410** of the fan **212** is positioned within the emboss **420** of the fan housing **214**. Specifically, at least a portion of the rib **410** of the fan **212** is positioned within the emboss **420** of the fan housing **214**. In other words, at least a portion of the rib **410** of the fan **212** extends within the recess **428** of the emboss **420** of the fan housing **214**.

(35) To that end, positioning of the rib **410** of the fan **212** within the emboss **420** of the fan housing **214** reduces and/or minimizes air recirculation with an air gap **460** between the fan blades **304** and the fan housing **214**. In other words, the rib **410** of the fan **212** positioned within the emboss **420** of the fan housing **214** acts or serves as an air dam to partially or wholly block, prevent, and/or minimize recirculation of air within the air gap **460** between the fan blades **304** and the fan housing **214**.

(36) For example, air that recirculated by the fan **212** to the air gap **460** encounters multiple inflection points to access of the first side **402** of the fan **212** and the fan blades **304**. Specifically, the rib **410** positioned within the emboss **420** creates multiple 90 degree (or substantially 90 degree) “turns” for the path of air to travel from the gap **460** to the first side **402** of the fan **212**. That is, the first wall **422**, the second wall **424**, and the surface **426** of the emboss **420**, when the rib **410** is positioned within the emboss **420**, creates four turns (four 90 degree turns) to provide restriction of air movement from the gap **460** to the first side **402** of the fan **212**.

(37) In some examples, the rib **410** is positioned within the emboss **420** such that the rib **410** is spaced-apart from the first wall **422** and the second wall **424**. That is, the rib **410** is positioned between the first wall **422** and the second wall **424** and does not contact either of the first wall **422** and the second wall **424**. Moreover, in some examples, the rib **410** is positioned within the emboss **420** such that the rib **410** is spaced-apart from the surface **426**. That is, the rib **410** is positioned within the emboss **420** such that the rib **410** does not contact the surface **426**. As a result of the rib

410 being spaced-apart from the first wall **422**, the second wall **424**, and the surface **426**, clearance to account for wobbling of the fan **212**, tolerance deviations of the fan **212**, and POGO of the fan **212** is minimized and/or reduced.

(38) FIG. 5A illustrates a cutaway side view of the fan apparatus **210** including multiple ribs and multiple embosses on a same side; and FIG. 5B illustrates a cutaway perspective view of the fan apparatus **210** including multiple ribs and multiple embosses on a same side. Referring to FIGS. 5A, 5B, the fan **212** can further include an additional rib **510**. The additional rib **510** is coupled to each of the blades **304** at the first side **402** of the fan **212**. In some examples, the additional rib **510** is circular.

(39) The fan housing **214** includes an additional emboss **520** surrounding the opening **350**. The additional emboss **520** further surrounds the emboss **420**. The additional emboss **520** includes a first wall **522** spaced-part from a second wall **524**. The additional emboss **520** can include a surface **526** positioned between the first wall **522** and the second wall **524**. The first wall **522**, the second wall **524**, and the surface **526** define a recess **528** of the additional emboss **520**. In some examples, the additional emboss **520** is circular.

(40) To that end, the fan **212** is coupled to the fan housing **214** with the first side **402** of the fan **212** in superimposition with the opening **350** of the fan housing **214**. Furthermore, the fan **212** is coupled to the fan housing **214** with the first side **402** of the fan **212** in superimposition with the opening **350** of the fan housing **214** such that the additional rib **510** of the fan **212** is positioned within the additional emboss **520** of the fan housing **214**. Specifically, at least a portion of the additional rib **510** of the fan **212** is positioned within the additional emboss **420** of the fan housing **214**. In other words, at least a portion of the additional rib **510** of the fan **212** extends within the recess **528** of the additional emboss **520** of the fan housing **214**.

(41) To that end, positioning of the rib **410** of the fan **212** within the emboss **420** of the fan housing **214** and positioning of the additional rib **510** of the fan **212** within the additional emboss **520** of the fan housing **214** reduces and/or minimizes air recirculation with the air gap **460** between the fan blades **304** and the fan housing **214**. In other words, the rib **410** of the fan **212** positioned within the emboss **420** of the fan housing **214** and the additional rib **510** of the fan **212** positioned within the additional emboss **520** of the fan housing **214** acts or serves as an air dam to partially or wholly block, prevent, and/or minimize recirculation of air within the air gap **460** between the fan blades **304** and the fan housing **214**.

(42) For example, air that is recirculated by the fan **212** to the air gap **460** encounters multiple inflection points to access of the first side **402** of the fan **212** and the fan blades **304**. Specifically, the rib **410** is positioned within the emboss **420** and the additional rib **510** is positioned within the additional emboss **520** to create multiple 90 degree (or substantially 90 degree) “turns” for the path of air to travel from the gap **460** to the first side **402** of the fan **212**. That is, the first wall **424**, the second wall **424**, and the surface **426** of the emboss **420**, when the rib **410** is positioned within the emboss **420**, creates four turns (90 degree turns) to provide restriction of air movement from the gap **460** to the first side **402** of the fan **212**; and the first wall **524**, the second wall **524**, and the surface **526** of the additional emboss **520**, when the additional rib **510** is positioned within the additional emboss **520**, creates an additional four turns (90 degree turns) to provide restriction of air movement from the gap **460** to the first side **402** of the fan **212**.

(43) In some examples, the additional rib **510** is positioned within the additional emboss **520** such that the additional rib **510** is spaced-apart from the first wall **522** and the second wall **524**. That is, the additional rib **510** is positioned between the first wall **522** and the second wall **524** and does not contact either of the first wall **522** and the second wall **524**. Moreover, in some examples, the additional rib **510** is positioned within the additional emboss **520** such that the additional rib **510** is spaced-apart from the surface **526**. That is, the additional rib **510** is positioned within the additional emboss **520** such that the additional rib **510** does not contact the surface **526**. As a result of the additional rib **510** being spaced-apart from the first wall **522**, the second wall **524**, and the surface

526, clearance to account for wobbling of the fan 212, tolerance deviations of the fan 212, and POGO of the fan 212 is minimized and/or reduced.

(44) FIG. 6A illustrates a cutaway side view of the fan apparatus 210 including multiple ribs and multiple embosses on opposite sides; and FIG. 6B illustrates a perspective view of the fan apparatus 210 including multiple ribs and multiple embosses on opposite sides. Referring to FIGS. 6A, 6B, the fan 212 can further include an additional rib 610. The additional rib 610 is coupled to each of the blades 304 at the second side 404 of the fan 212. In some examples, the additional rib 610 is circular.

(45) The fan housing 214 includes an additional opening 660 and an additional emboss 620 surrounding the additional opening 660. The additional emboss 620 includes a first wall 622 spaced-part from a second wall 624. The additional emboss 620 can include a surface 626 positioned between the first wall 622 and the second wall 624. The first wall 622, the second wall 624, and the surface 626 define a recess 628 of the additional emboss 620. In some examples, the additional emboss 620 is circular.

(46) To that end, the fan 212 is coupled to the fan housing 214 with the first side 402 of the fan 212 in superimposition with the opening 360 of the fan housing 214 and the second side 404 of the fan 212 in superimposition with the additional opening 660 of the fan housing 214. Furthermore, the fan 212 is coupled to the fan housing 214 with the second side 404 of the fan 212 in superimposition with the additional opening 660 of the fan housing 214 of the fan housing 214 such that the additional rib 610 of the fan 212 is positioned within the additional emboss 620 of the fan housing 214. Specifically, at least a portion of the additional rib 610 of the fan 212 is positioned within the additional emboss 620 of the fan housing 214. In other words, at least a portion of the additional rib 610 of the fan 212 extends within the recess 628 of the additional emboss 620 of the fan housing 214.

(47) To that end, positioning of the additional rib 610 of the fan 212 within the additional emboss 620 of the fan housing 214 reduces and/or minimizes air recirculation with an air gap 660 between the fan blades 304 and the fan housing 214. In other words, the additional rib 610 of the fan 212 positioned within the additional emboss 620 of the fan housing 214 acts or serves as an air dam to partially or wholly block, prevent, and/or minimize recirculation of air within the air gap 660 between the fan blades 304 and the fan housing 214.

(48) For example, air that is recirculated by the fan 212 to the air gap 660 encounters multiple inflection points to access to the second side 404 of the fan 212 and the fan blades 304. Specifically, the additional rib 610 positioned within the additional emboss 620 creates multiple 90 degree (or substantially 90 degree) “turns” for the path of air to travel from the gap 660 to the second side 404 of the fan 212. That is, the first wall 624, the second wall 624, and the surface 626 of the additional emboss 620, when the additional rib 610 is positioned within the additional emboss 620, creates four turns (90 degree turns) to provide restriction of air movement from the gap 660 to the second side 404 of the fan 212.

(49) In some examples, the additional rib 610 is positioned within the additional emboss 620 such that the additional rib 610 is spaced-apart from the first wall 622 and the second wall 624. That is, the additional rib 610 is positioned between the first wall 622 and the second wall 624 and does not contact either of the first wall 622 and the second wall 624. Moreover, in some examples, the additional rib 610 is positioned within the additional emboss 620 such that the additional rib 610 is spaced-apart from the surface 626. That is, the additional rib 610 is positioned within the additional emboss 620 such that the additional rib 610 does not contact the surface 626. As a result of the additional rib 610 being spaced-apart from the first wall 622, the second wall 624, and the surface 626, clearance to account for wobbling of the fan 212, tolerance deviations of the fan 212, and POGO of the fan 212 is minimized and/or reduced.

(50) The above disclosed subject matter is to be considered illustrative, and not restrictive, and the appended claims are intended to cover all such modifications, enhancements, and other

embodiments which fall within the true spirit and scope of the present disclosure. Thus, to the maximum extent allowed by law, the scope of the present disclosure is to be determined by the broadest permissible interpretation of the following claims and their equivalents, and shall not be restricted or limited by the foregoing detailed description.

(51) Herein, “or” is inclusive and not exclusive, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A or B” means “A, B, or both,” unless expressly indicated otherwise or indicated otherwise by context. Moreover, “and” is both joint and several, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A and B” means “A and B, jointly or severally,” unless expressly indicated otherwise or indicated otherwise by context.

(52) The scope of this disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments described or illustrated herein that a person having ordinary skill in the art would comprehend. The scope of this disclosure is not limited to the example embodiments described or illustrated herein. Moreover, although this disclosure describes and illustrates respective embodiments herein as including particular components, elements, features, functions, operations, or steps, any of these embodiments may include any combination or permutation of any of the components, elements, features, functions, operations, or steps described or illustrated anywhere herein that a person having ordinary skill in the art would comprehend. Furthermore, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative.

Claims

1. A fan apparatus for an information handling system, including: a fan having a first side and a second side, the second side positioned opposite to the first side, the fan including: a shaft; a plurality of blades coupled to the shaft; and a rib coupled to one or more of the plurality of blades at the first side of the fan; a fan housing, including: an opening; and an emboss surrounding the opening; wherein the fan is coupled to the fan housing with the first side of the fan in superimposition with the opening of the fan housing such that the rib of the fan is positioned within the emboss of the fan housing.
2. The fan apparatus of claim 1, wherein the opening is circular.
3. The fan apparatus of claim 2, wherein the emboss is circular.
4. The fan apparatus of claim 3, wherein the rib is circular.
5. The fan apparatus of claim 1, wherein the emboss includes a first wall spaced-apart from a second wall, wherein the rib is positioned within the emboss such that the rib is spaced-apart from the first wall and the second wall.
6. The fan apparatus of claim 5, wherein the emboss further includes a surface positioned between the first wall and the second wall, wherein the rib is positioned within the emboss such that the rib is spaced-apart from the surface.
7. The fan apparatus of claim 1, wherein the fan further includes an additional rib coupled to each of the plurality of blades at the first side of the fan, the fan housing further includes an additional emboss surrounding the opening, the fan is coupled to the fan housing with the first side of the fan in superimposition with the opening of the fan housing such that the additional rib of the fan is positioned within the additional emboss of the fan housing.
8. The fan apparatus of claim 7, wherein the emboss surrounds the additional emboss.
9. The fan apparatus of claim 1, wherein the fan further includes an additional rib coupled to each

of the plurality of blades at the second side of the fan, the fan housing having a first side and a second side, the second side positioned opposite to the first side, the fan housing further including an additional opening positioned on the second side and an additional emboss surrounding the additional opening, the fan is coupled to the fan housing with the second side of the fan in superimposition with the additional opening of the fan housing such that the additional rib of the fan is positioned within the additional emboss of the fan housing.

10. The fan apparatus of claim 9, wherein the opening of the fan housing is positioned on the first side of the fan housing.

11. An information handling system, including: a fan apparatus, including: a fan having a first side and a second side, the second side positioned opposite to the first side, the fan including: a shaft; a plurality of blades coupled to the shaft; and a rib coupled to one or more of the plurality of blades at the first side of the fan; a fan housing, including: an opening; and an emboss surrounding the opening; wherein the fan is coupled to the fan housing with the first side of the fan in superimposition with the opening of the fan housing such that the rib of the fan is positioned within the emboss of the fan housing.

12. The information handling system of claim 11, wherein the opening is circular.

13. The information handling system of claim 12, wherein the emboss is circular.

14. The information handling system of claim 13, wherein the rib is circular.

15. The information handling system of claim 11, wherein the emboss includes a first wall spaced-apart from a second wall, wherein the rib is positioned within the emboss such that the rib is spaced-apart from the first wall and the second wall.

16. The information handling system of claim 15, wherein the emboss further includes a surface positioned between the first wall and the second wall, wherein the rib is positioned within the emboss such that the rib is spaced-apart from the surface.

17. The information handling system of claim 11, wherein the fan further includes an additional rib coupled to each of the plurality of blades at the first side of the fan, the fan housing further includes an additional emboss surrounding the opening, the fan is coupled to the fan housing with the first side of the fan in superimposition with the opening of the fan housing such that the additional rib of the fan is positioned within the additional emboss of the fan housing.

18. The information handling system of claim 17, wherein the emboss surrounds the additional emboss.

19. The information handling system of claim 11, wherein the fan further includes an additional rib coupled to each of the plurality of blades at the second side of the fan, the fan housing having a first side and a second side, the second side positioned opposite to the first side, the fan housing further including an additional opening positioned on the second side and an additional emboss surrounding the additional opening, the fan is coupled to the fan housing with the second side of the fan in superimposition with the additional opening of the fan housing such that the additional rib of the fan is positioned within the additional emboss of the fan housing.

20. The information handling system of claim 19, wherein the opening of the fan housing is positioned on the first side of the fan housing.
