

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413177
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Runser; Rory

Photovoltaic modules and roofing shingles with nail zones

Abstract

A system, including: a roof deck; a plurality of photovoltaic modules installed on the roof deck, each of the plurality of photovoltaic modules having: a solar cell, and a backsheet, where the solar cell is positioned on the backsheet, where the backsheet has a headlap portion, where the headlap portion has a first longitudinal groove and a second longitudinal groove, where the first longitudinal groove is spaced apart from the second longitudinal groove on the backsheet, to define a nail zone between the first longitudinal groove and the second longitudinal groove; and a plurality of fasteners installed so as to penetrate the nail zones of the plurality of photovoltaic modules and the roof deck.

Inventors:	Runser; Rory (Palo Alto, CA)
Applicant:	GAF Energy LLC (Parsippany, NJ)
Family ID:	94772315
Assignee:	GAF Energy LLC (Parsippany, NJ)
Appl. No.:	18/819476
Filed:	August 29, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250080037 A1	Mar. 06, 2025

Related U.S. Application Data

us-provisional-application US 63579858 20230831

Publication Classification

Int. Cl.: E04D1/34 (20060101); **H02S20/25** (20140101)

U.S. Cl.:

CPC **H02S20/25** (20141201); **E04D1/34** (20130101); E04D2001/3423 (20130101)

Field of Classification Search

CPC: E04D (1/34); E04D (2001/3423); E04D (2001/3452); E04D (2001/3458); E04D (2001/3467); E04D (2001/3491); H02S (20/25)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1981467	12/1933	Radtke	N/A	N/A
3156497	12/1963	Lessard	N/A	N/A
3581779	12/1970	Gilbert, Jr.	N/A	N/A
3927501	12/1974	Allen	52/555	E04D 1/26
4258948	12/1980	Hoffmann	N/A	N/A
4349220	12/1981	Carroll et al.	N/A	N/A
4499702	12/1984	Turner	N/A	N/A
4636577	12/1986	Peterpaul	N/A	N/A
5167579	12/1991	Rotter	N/A	N/A
5224318	12/1992	Kemerer	52/546	E04F 13/0864
5437735	12/1994	Younan et al.	N/A	N/A
5590495	12/1996	Bressler et al.	N/A	N/A
5642596	12/1996	Waddington	N/A	N/A
6008450	12/1998	Ohtsuka et al.	N/A	N/A
6033270	12/1999	Stuart	N/A	N/A
6046399	12/1999	Kapner	N/A	N/A
6199338	12/2000	Hudson, Jr.	52/518	E04D 1/29
6201180	12/2000	Meyer et al.	N/A	N/A
6220329	12/2000	King et al.	N/A	N/A
6308482	12/2000	Strait	N/A	N/A
6320114	12/2000	Kuechler	N/A	N/A
6320115	12/2000	Kataoka et al.	N/A	N/A
6336304	12/2001	Mimura et al.	N/A	N/A
6341454	12/2001	Koleoglou	N/A	N/A
6407329	12/2001	Iino et al.	N/A	N/A
6576830	12/2002	Nagao et al.	N/A	N/A
6928781	12/2004	Desbois et al.	N/A	N/A
6972367	12/2004	Federspiel et al.	N/A	N/A
6990779	12/2005	Kiik	52/518	B32B 13/14
7138578	12/2005	Komamine	N/A	N/A
7155870	12/2006	Almy	N/A	N/A
7178295	12/2006	Dinwoodie	N/A	N/A
7487771	12/2008	Eiffert et al.	N/A	N/A

7587864	12/2008	McCaskill et al.	N/A	N/A
7678990	12/2009	McCaskill et al.	N/A	N/A
7678991	12/2009	McCaskill et al.	N/A	N/A
7748191	12/2009	Podirsky	N/A	N/A
7819114	12/2009	Augenbraun et al.	N/A	N/A
7824191	12/2009	Podirsky	N/A	N/A
7832176	12/2009	McCaskill et al.	N/A	N/A
8118109	12/2011	Hacker	N/A	N/A
8168880	12/2011	Jacobs et al.	N/A	N/A
8173889	12/2011	Kalkanoglu et al.	N/A	N/A
8210570	12/2011	Railkar et al.	N/A	N/A
8276329	12/2011	Lenox	N/A	N/A
8312693	12/2011	Cappelli	N/A	N/A
8319093	12/2011	Kalkanoglu et al.	N/A	N/A
8333040	12/2011	Shiao et al.	N/A	N/A
8371076	12/2012	Jones et al.	N/A	N/A
8375653	12/2012	Shiao et al.	N/A	N/A
8404967	12/2012	Kalkanoglu et al.	N/A	N/A
8410349	12/2012	Kalkanoglu et al.	N/A	N/A
8418415	12/2012	Shiao et al.	N/A	N/A
8438796	12/2012	Shiao et al.	N/A	N/A
8468754	12/2012	Railkar et al.	N/A	N/A
8468757	12/2012	Krause et al.	N/A	N/A
8505249	12/2012	Geary	N/A	N/A
8512866	12/2012	Taylor	N/A	N/A
8513517	12/2012	Kalkanoglu et al.	N/A	N/A
8586856	12/2012	Kalkanoglu et al.	N/A	N/A
8601754	12/2012	Jenkins et al.	N/A	N/A
8629578	12/2013	Kurs et al.	N/A	N/A
8646228	12/2013	Jenkins	N/A	N/A
8656657	12/2013	Livsey et al.	N/A	N/A
8671630	12/2013	Lena et al.	N/A	N/A
8677702	12/2013	Jenkins	N/A	N/A
8695289	12/2013	Koch et al.	N/A	N/A
8713858	12/2013	Xie	N/A	N/A
8713860	12/2013	Railkar et al.	N/A	N/A
8733038	12/2013	Kalkanoglu et al.	N/A	N/A
8776455	12/2013	Azoulay	N/A	N/A
8789321	12/2013	Ishida	N/A	N/A
8793940	12/2013	Kalkanoglu et al.	N/A	N/A
8793941	12/2013	Bosler et al.	N/A	N/A
8826607	12/2013	Shiao et al.	N/A	N/A
8835751	12/2013	Kalkanoglu et al.	N/A	N/A
8863451	12/2013	Jenkins et al.	N/A	N/A
8898970	12/2013	Jenkins et al.	N/A	N/A
8925262	12/2014	Railkar et al.	N/A	N/A
8943766	12/2014	Gombarick et al.	N/A	N/A
8946544	12/2014	Jabos et al.	N/A	N/A
8950128	12/2014	Kalkanoglu et al.	N/A	N/A
8959848	12/2014	Jenkins et al.	N/A	N/A

8966838	12/2014	Jenkins	N/A	N/A
8966850	12/2014	Jenkins et al.	N/A	N/A
8994224	12/2014	Mehta et al.	N/A	N/A
9032672	12/2014	Livsey et al.	N/A	N/A
9153950	12/2014	Yamanaka et al.	N/A	N/A
9166087	12/2014	Chihlas et al.	N/A	N/A
9169646	12/2014	Rodrigues et al.	N/A	N/A
9170034	12/2014	Bosler et al.	N/A	N/A
9178465	12/2014	Shiao et al.	N/A	N/A
9202955	12/2014	Livsey et al.	N/A	N/A
9212832	12/2014	Jenkins	N/A	N/A
9217584	12/2014	Kalkanoglu et al.	N/A	N/A
9270221	12/2015	Zhao	N/A	N/A
9273885	12/2015	Rodrigues et al.	N/A	N/A
9276141	12/2015	Kalkanoglu et al.	N/A	N/A
9331224	12/2015	Koch et al.	N/A	N/A
9356174	12/2015	Duarte et al.	N/A	N/A
9359014	12/2015	Yang et al.	N/A	N/A
9412890	12/2015	Meyers	N/A	N/A
9528270	12/2015	Jenkins et al.	N/A	N/A
9605432	12/2016	Robbins	N/A	N/A
9711672	12/2016	Wang	N/A	N/A
9755573	12/2016	Livsey et al.	N/A	N/A
9786802	12/2016	Shiao et al.	N/A	N/A
9831818	12/2016	West	N/A	N/A
9912284	12/2017	Svec	N/A	N/A
9923515	12/2017	Rodrigues et al.	N/A	N/A
9938729	12/2017	Coon	N/A	N/A
9991412	12/2017	Gonzalez et al.	N/A	N/A
9998067	12/2017	Kalkanoglu et al.	N/A	N/A
10027273	12/2017	West et al.	N/A	N/A
10115850	12/2017	Rodrigues et al.	N/A	N/A
10128660	12/2017	Apte et al.	N/A	N/A
10156075	12/2017	McDonough	N/A	N/A
10187005	12/2018	Rodrigues et al.	N/A	N/A
10256765	12/2018	Rodrigues et al.	N/A	N/A
10284136	12/2018	Mayfield et al.	N/A	N/A
10454408	12/2018	Livsey et al.	N/A	N/A
10530292	12/2019	Cropper et al.	N/A	N/A
10560048	12/2019	Fisher et al.	N/A	N/A
10563406	12/2019	Kalkanoglu et al.	N/A	N/A
D879031	12/2019	Lance et al.	N/A	N/A
10579028	12/2019	Jacob	N/A	N/A
10784813	12/2019	Kalkanoglu et al.	N/A	N/A
D904289	12/2019	Lance et al.	N/A	N/A
11012026	12/2020	Kalkanoglu et al.	N/A	N/A
11085187	12/2020	Grubka	N/A	E04D 1/20
11177639	12/2020	Nguyen et al.	N/A	N/A
11217715	12/2021	Sharenko et al.	N/A	N/A
11251744	12/2021	Bunea et al.	N/A	N/A

11258399	12/2021	Kalkanoglu et al.	N/A	N/A
11283394	12/2021	Perkins et al.	N/A	N/A
11309828	12/2021	Sirski et al.	N/A	N/A
11394344	12/2021	Perkins et al.	N/A	N/A
11424379	12/2021	Sharenko et al.	N/A	N/A
11431280	12/2021	Liu et al.	N/A	N/A
11431281	12/2021	Perkins et al.	N/A	N/A
11444569	12/2021	Clemente et al.	N/A	N/A
11454027	12/2021	Kuiper et al.	N/A	N/A
11459757	12/2021	Nguyen et al.	N/A	N/A
11486144	12/2021	Bunea et al.	N/A	N/A
11489482	12/2021	Peterson	N/A	H01L 31/0481
11496088	12/2021	Sirski et al.	N/A	N/A
11508861	12/2021	Perkins et al.	N/A	N/A
11512480	12/2021	Achor et al.	N/A	N/A
11527665	12/2021	Boitnott	N/A	N/A
11545927	12/2022	Abra et al.	N/A	N/A
11545928	12/2022	Perkins et al.	N/A	N/A
11658470	12/2022	Nguyen et al.	N/A	N/A
11661745	12/2022	Bunea et al.	N/A	N/A
11689149	12/2022	Clemente et al.	N/A	N/A
11705531	12/2022	Sharenko et al.	N/A	N/A
11728759	12/2022	Nguyen et al.	N/A	N/A
11732490	12/2022	Achor et al.	N/A	N/A
11811361	12/2022	Farhangi et al.	N/A	N/A
11824486	12/2022	Nguyen et al.	N/A	N/A
11824487	12/2022	Nguyen et al.	N/A	N/A
11843067	12/2022	Nguyen et al.	N/A	N/A
11927014	12/2023	Graziano	N/A	E04D 1/20
2002/0053360	12/2001	Kinoshita et al.	N/A	N/A
2002/0129849	12/2001	Heckeroth	N/A	N/A
2003/0101662	12/2002	Ullman	N/A	N/A
2003/0132265	12/2002	Villela et al.	N/A	N/A
2003/0217768	12/2002	Guha	N/A	N/A
2004/0000334	12/2003	Ressler	N/A	N/A
2005/0030187	12/2004	Peress et al.	N/A	N/A
2005/0115603	12/2004	Yoshida et al.	N/A	N/A
2005/0144870	12/2004	Dinwoodie	N/A	N/A
2005/0178428	12/2004	Laaly et al.	N/A	N/A
2005/0193673	12/2004	Rodrigues et al.	N/A	N/A
2006/0042683	12/2005	Gangemi	N/A	N/A
2006/0046084	12/2005	Yang et al.	N/A	N/A
2007/0074757	12/2006	Mellott et al.	N/A	N/A
2007/0181174	12/2006	Ressler	N/A	N/A
2007/0193618	12/2006	Bressler et al.	N/A	N/A
2007/0249194	12/2006	Liao	N/A	N/A
2007/0295385	12/2006	Sheats et al.	N/A	N/A
2008/0006323	12/2007	Kalkanoglu et al.	N/A	N/A
2008/0035140	12/2007	Placer et al.	N/A	N/A

2008/0078440	12/2007	Lim et al.	N/A	N/A
2008/0185748	12/2007	Kalkanoglu	N/A	N/A
2008/0271774	12/2007	Kalkanoglu et al.	N/A	N/A
2008/0302030	12/2007	Stancel et al.	N/A	N/A
2008/0315061	12/2007	Fath	N/A	N/A
2009/0000222	12/2008	Kalkanoglu et al.	N/A	N/A
2009/0014057	12/2008	Croft et al.	N/A	N/A
2009/0014058	12/2008	Croft et al.	N/A	N/A
2009/0019795	12/2008	Szacsvay et al.	N/A	N/A
2009/0044850	12/2008	Kimberley	N/A	N/A
2009/0114261	12/2008	Stancel et al.	N/A	N/A
2009/0133340	12/2008	Shiao et al.	N/A	N/A
2009/0159118	12/2008	Kalkanoglu et al.	N/A	N/A
2009/0178350	12/2008	Kalkanoglu et al.	N/A	N/A
2009/0229652	12/2008	Mapel et al.	N/A	N/A
2009/0275247	12/2008	Richter et al.	N/A	N/A
2010/0019580	12/2009	Croft et al.	N/A	N/A
2010/0095618	12/2009	Edison et al.	N/A	N/A
2010/0101634	12/2009	Frank et al.	N/A	N/A
2010/0116325	12/2009	Nikoonahad	N/A	N/A
2010/0131108	12/2009	Meyer	N/A	N/A
2010/0139184	12/2009	Williams et al.	N/A	N/A
2010/0146878	12/2009	Koch et al.	N/A	N/A
2010/0159221	12/2009	Kourtakis et al.	N/A	N/A
2010/0170169	12/2009	Railkar et al.	N/A	N/A
2010/0186798	12/2009	Tormen et al.	N/A	N/A
2010/0242381	12/2009	Jenkins	N/A	N/A
2010/0313499	12/2009	Gangemi	N/A	N/A
2010/0325976	12/2009	Degenfelder	52/173.3	E04D 1/30
2010/0326488	12/2009	Aue et al.	N/A	N/A
2010/0326501	12/2009	Zhao et al.	N/A	N/A
2011/0030761	12/2010	Kalkanoglu et al.	N/A	N/A
2011/0036386	12/2010	Browder	N/A	N/A
2011/0036389	12/2010	Hardikar et al.	N/A	N/A
2011/0048507	12/2010	Livsey et al.	N/A	N/A
2011/0058337	12/2010	Han et al.	N/A	N/A
2011/0061326	12/2010	Jenkins	N/A	N/A
2011/0100436	12/2010	Cleereman et al.	N/A	N/A
2011/0104488	12/2010	Muessig et al.	N/A	N/A
2011/0132427	12/2010	Kalkanoglu et al.	N/A	N/A
2011/0168238	12/2010	Metin et al.	N/A	N/A
2011/0239555	12/2010	Cook et al.	N/A	N/A
2011/0302859	12/2010	Crasnianski	N/A	N/A
2011/0314753	12/2010	Farmer et al.	N/A	N/A
2012/0034799	12/2011	Hunt	N/A	N/A
2012/0060434	12/2011	Jacobs	N/A	N/A
2012/0060902	12/2011	Drake	N/A	N/A
2012/0085392	12/2011	Albert et al.	N/A	N/A
2012/0137600	12/2011	Jenkins	N/A	N/A
2012/0176077	12/2011	Oh et al.	N/A	N/A

2012/0212065	12/2011	Cheng et al.	N/A	N/A
2012/0233940	12/2011	Perkins et al.	N/A	N/A
2012/0240490	12/2011	Gangemi	N/A	N/A
2012/0260977	12/2011	Stancel	N/A	N/A
2012/0266942	12/2011	Komatsu et al.	N/A	N/A
2012/0279150	12/2011	Pislkak et al.	N/A	N/A
2012/0282437	12/2011	Clark et al.	N/A	N/A
2012/0291848	12/2011	Sherman et al.	N/A	N/A
2013/0008499	12/2012	Verger et al.	N/A	N/A
2013/0014455	12/2012	Grieco	N/A	N/A
2013/0118558	12/2012	Sherman	N/A	N/A
2013/0193769	12/2012	Mehta et al.	N/A	N/A
2013/0247988	12/2012	Reese et al.	N/A	N/A
2013/0284267	12/2012	Plug et al.	N/A	N/A
2013/0306137	12/2012	Ko	N/A	N/A
2014/0090697	12/2013	Rodrigues et al.	N/A	N/A
2014/0150843	12/2013	Pearce et al.	N/A	N/A
2014/0173997	12/2013	Jenkins	N/A	N/A
2014/0179220	12/2013	Railkar et al.	N/A	N/A
2014/0182222	12/2013	Kalkanoglu et al.	N/A	N/A
2014/0208675	12/2013	Beerer et al.	N/A	N/A
2014/0254776	12/2013	O'Connor et al.	N/A	N/A
2014/0266289	12/2013	Della Sera et al.	N/A	N/A
2014/0311556	12/2013	Feng et al.	N/A	N/A
2014/0352760	12/2013	Haynes et al.	N/A	N/A
2014/0366464	12/2013	Rodrigues et al.	N/A	N/A
2015/0089895	12/2014	Leitch	N/A	N/A
2015/0162459	12/2014	Lu et al.	N/A	N/A
2015/0340516	12/2014	Kim et al.	N/A	N/A
2015/0349173	12/2014	Morad et al.	N/A	N/A
2016/0105144	12/2015	Haynes et al.	N/A	N/A
2016/0142008	12/2015	Lopez et al.	N/A	N/A
2016/0254776	12/2015	Rodrigues et al.	N/A	N/A
2016/0276508	12/2015	Huang et al.	N/A	N/A
2016/0359451	12/2015	Mao et al.	N/A	N/A
2017/0159292	12/2016	Chihlas et al.	N/A	N/A
2017/0179319	12/2016	Yamashita et al.	N/A	N/A
2017/0179726	12/2016	Garrity et al.	N/A	N/A
2017/0237390	12/2016	Hudson et al.	N/A	N/A
2017/0331415	12/2016	Koppi et al.	N/A	N/A
2018/0094438	12/2017	Wu et al.	N/A	N/A
2018/0097472	12/2017	Anderson et al.	N/A	N/A
2018/0115275	12/2017	Flanigan et al.	N/A	N/A
2018/0254738	12/2017	Yang et al.	N/A	N/A
2018/0294765	12/2017	Friedrich et al.	N/A	N/A
2018/0351502	12/2017	Almy et al.	N/A	N/A
2018/0367089	12/2017	Stutterheim et al.	N/A	N/A
2019/0030867	12/2018	Sun et al.	N/A	N/A
2019/0081436	12/2018	Onodi et al.	N/A	N/A
2019/0123679	12/2018	Rodrigues et al.	N/A	N/A

2019/0253022	12/2018	Hardar et al.	N/A	N/A
2019/0305717	12/2018	Allen et al.	N/A	N/A
2020/0109320	12/2019	Jiang	N/A	N/A
2020/0144958	12/2019	Rodrigues et al.	N/A	N/A
2020/0220819	12/2019	Vu et al.	N/A	N/A
2020/0224419	12/2019	Boss et al.	N/A	N/A
2020/0343397	12/2019	Hem-Jensen	N/A	N/A
2021/0083619	12/2020	Hegedus	N/A	N/A
2021/0115223	12/2020	Bonekamp et al.	N/A	N/A
2021/0159353	12/2020	Li et al.	N/A	N/A
2021/0301536	12/2020	Baggs et al.	N/A	N/A
2021/0343886	12/2020	Sharenko et al.	N/A	N/A
2022/0149213	12/2021	Mensink et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2829440	12/2018	CA	N/A
700095	12/2009	CH	N/A
202797032	12/2012	CN	N/A
217150978	12/2021	CN	N/A
1958248	12/1970	DE	N/A
1039361	12/1999	EP	N/A
1837162	12/2006	EP	N/A
1774372	12/2010	EP	N/A
244648	12/2011	EP	N/A
2784241	12/2013	EP	N/A
3772175	12/2020	EP	N/A
10046767	12/1997	JP	N/A
2002-106151	12/2001	JP	N/A
2001-098703	12/2001	JP	N/A
2017-027735	12/2016	JP	N/A
2018053707	12/2017	JP	N/A
20090084060	12/2008	KR	N/A
10-1348283	12/2013	KR	N/A
10-2019-0000367	12/2018	KR	N/A
10-2253483	12/2020	KR	N/A
2026856	12/2021	NL	N/A
2010/151777	12/2009	WO	N/A
2011/049944	12/2010	WO	N/A
2015/133632	12/2014	WO	N/A
2018/000589	12/2017	WO	N/A
2019/201416	12/2018	WO	N/A
2020-159358	12/2019	WO	N/A
2021-247098	12/2020	WO	N/A

OTHER PUBLICATIONS

Sunflare, Procduts: “Sunflare Develops Prototype For New Residential Solar Shingles”; 2019 <<sunflaresolar.com/news/sunflare-develops-prototype-for-new-residential-solar-shingles>> retrieved Feb. 2, 2021. cited by applicant

RGS Energy, 3.5kW Powerhouse 3.0 system installed in an afternoon; Jun. 7, 2019
<<facebook.com/RGSEnergy/>> retrieved Feb. 2, 2021. cited by applicant
Tesla, Solar Roof <<tesla.com/solarroof>> retrieved Feb. 2, 2021. cited by applicant
“Types of Roofing Underlayment”, Owens Corning Roofing;
<<https://www.owenscorning.com/en-us/roofing/tools/how-roofing-underlayment-helps-protect-your-home>> retrieved Nov. 1, 2021. cited by applicant

Primary Examiner: Figueroa; Adriana

Attorney, Agent or Firm: GREENBERG TRAURIG, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Section 111(a) application relating to and claiming the benefit of commonly-owned, U.S. Provisional Patent Application Ser. No. 63/579,858, filed Aug. 31, 2023, entitled “ROOFING MODULE, AND ASSOCIATED SYSTEM AND METHOD,” the contents of which are incorporated herein by reference in its entirety.

FIELD

(1) The present invention relates to roofing modules including photovoltaic modules and roofing shingles and, more particularly, photovoltaic modules and roofing shingles with nail zones.

BACKGROUND

(2) In a roofing system, a technician may install a number of roofing modules, including both photovoltaic modules and non-photovoltaic modules, above a roof deck. For example, the technician may fasten a number of fasteners through a nail zone of each of the roofing modules, and into the roof deck.

SUMMARY

(3) The Claims, rather than the Summary, define covered embodiments of the present invention. The Summary is a high-level overview of various aspects of the invention, and introduces some concepts that are further described in the Detailed Description below. The Summary is not intended to identify key or essential features of the claimed subject matter, and also is not intended to be used in isolation to determine the scope of the claimed subject matter. Instead, the claimed subject matter should be understood by reference to appropriate portions of the Specification and drawings, as well as to each claim.

(4) In some embodiments, a system includes a plurality of photovoltaic modules installed on a roof deck, each of the plurality of photovoltaic modules comprising at least one solar cell, and a backsheet, wherein the at least one solar cell is above the backsheet, and wherein the backsheet includes a headlap portion, wherein the headlap portion comprises a first longitudinal groove and a second longitudinal groove, wherein the first longitudinal groove is spaced apart from the second longitudinal groove to define a nail zone between the first longitudinal groove and the second longitudinal groove, and wherein each of the photovoltaic modules is configured to receive at least one fastener within the nail zone for installing the photovoltaic module to the roof deck.

(5) In some embodiments, a depth of at least one of the first longitudinal groove or the second longitudinal groove is 0.1 mm to 0.2 mm. In some embodiments, a width of the nail zone between the first longitudinal groove and the second longitudinal groove is 3 cm to 6 cm. In some embodiments, each of the first longitudinal groove and the second longitudinal groove extends from one end of the backsheet to an opposite end of the backsheet.

(6) In some embodiments, the backsheet is composed of thermoplastic polyolefin (TPO). In some

embodiments, the headlap portion an integral portion of the backsheet. In some embodiments, the backsheet includes a base portion, and wherein the headlap portion is attached to the base portion. In some embodiments, the at least one solar cell and the base portion are laminated, and wherein the headlap portion is not laminated. In some embodiments, the headlap portion does not include a pigment.

(7) In some embodiments, a photovoltaic module includes at least one solar cell, and a backsheet, wherein the at least one solar cell is above the backsheet, wherein the backsheet comprises a headlap portion, wherein the headlap portion comprises a first longitudinal groove and a second longitudinal groove, wherein the first longitudinal groove is spaced apart from the second longitudinal groove on the backsheet to define a nail zone between the first longitudinal groove and the second longitudinal groove, and wherein the nail zone is configured to receive at least one fastener that penetrates the photovoltaic module to secure the photovoltaic module to a roof deck.

(8) In some embodiments, the backsheet comprises thermoplastic polyolefin (TPO). In some embodiments, a depth of at least one of the first longitudinal groove or the second longitudinal groove is 0.1 mm to 0.2 mm. In some embodiments, a width of the nail zone between the first longitudinal groove and the second longitudinal groove is 3 cm to 6 cm. In some embodiments, each of the first longitudinal groove and the second longitudinal groove extends from one end of the backsheet to an opposite end of the backsheet. In some embodiments, the headlap portion an integral portion of the backsheet. In some embodiments, the backsheet includes a base portion, and wherein the headlap portion is attached to the base portion. In some embodiments, the at least one solar cell and the base portion are laminated, and wherein the headlap portion is not laminated. In some embodiments, the headlap portion does not include a pigment.

(9) In some embodiments, a method comprises obtaining a first sheet; forming a first longitudinal groove in the first sheet; forming a second longitudinal groove in the first sheet, the first longitudinal groove spaced apart from the second longitudinal groove to define a first nail zone between the first longitudinal groove and the second longitudinal groove; forming a third longitudinal groove in the first sheet; forming a fourth longitudinal groove in the first sheet, the third longitudinal groove spaced apart from the fourth longitudinal groove to define a second nail zone between the third longitudinal groove and the fourth longitudinal groove, wherein the first nail zone is spaced apart from the second nail zone; cutting the sheet to form a first backsheet and a second backsheet, wherein the first backsheet includes the first nail zone, and wherein the second backsheet includes the second nail zone; and laminating a first solar cell with the first backsheet to form a first photovoltaic module, wherein the first photovoltaic module includes a headlap portion, and wherein the first nail zone is on the headlap portion.

(10) In some embodiments, the method further includes laminating a second solar cell with the second backsheet to form a second photovoltaic module, wherein the second photovoltaic module includes a headlap portion, and where the second nail zone is on the headlap portion of the second photovoltaic module.

(11) In some embodiments, the forming the first longitudinal groove and the forming the second longitudinal groove occur simultaneously. In some embodiments, the forming the first longitudinal groove occurs before the forming the second longitudinal groove.

(12) In some embodiments, the forming the third longitudinal groove and the forming the fourth longitudinal groove occur simultaneously. In some embodiments, the forming the third longitudinal groove occurs before the forming the fourth longitudinal groove.

(13) In some embodiments, the forming the first longitudinal groove, the forming the second longitudinal groove, the forming of the third longitudinal groove, and the forming of the fourth longitudinal groove occur simultaneously. In some embodiments, the forming the first longitudinal groove, the forming the second longitudinal groove, the forming of the third longitudinal groove, and/or the forming of the fourth longitudinal groove occurs at different periods.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) This section refers to the drawings that form a part of this disclosure, and which illustrate some of the embodiments of structure, materials, and/or methods of the present invention described herein.
- (2) FIG. 1 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (3) FIG. 2 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (4) FIG. 3 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (5) FIG. 4 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (6) FIG. 5 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (7) FIG. 6 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (8) FIG. 7 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (9) FIG. 8 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (10) FIG. 9 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (11) FIG. 10 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (12) FIG. 11 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (13) FIG. 12 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (14) FIG. 13 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (15) FIG. 14 is a schematic top view of a roofing module, in accordance with some embodiments of the invention.
- (16) FIG. 15 is a schematic top view of a roofing system including a plurality of roofing modules, in accordance with some embodiments of the invention.
- (17) FIG. 16 is a photograph of a backsheet material, in accordance with embodiments of the invention.
- (18) FIG. 17 is a photograph of the backsheet material of FIG. 16, over which a top layer has been laminated, in accordance with some embodiments of the invention.
- (19) FIG. 18 is a photograph illustrating an embodiment of a method of forming a groove in a photovoltaic module.
- (20) FIG. 19 illustrates an embodiment of a method of making a roofing module.
- (21) FIGS. 20A and 20B are photographs of some embodiments of backsheets including nail zones for roofing module.
- (22) FIG. 21 illustrates an embodiment of a method of making a photovoltaic module.
- (23) FIG. 22 is a photograph of some embodiments of a photovoltaic module.
- (24) FIG. 23 are photographs of some embodiments of backsheets including nail zones for roofing modules.

DETAILED DESCRIPTION

(25) In addition to the benefits and improvements that the Specification discloses, other objects and advantages that the Specification provides will become apparent from the following description taken in conjunction with the accompanying figures. Although the description discloses and describes detailed embodiments of the present disclosure, the disclosed embodiments are merely illustrative of the disclosure that may be embodied in various forms. In addition, each of the examples given regarding the various embodiments of the disclosure is intended to be illustrative, and not restrictive.

(26) As used herein, a “steep slope” roof or roof deck is a roof or roof deck having a pitch of Y/X , where Y and X are in a ratio of 4:12 to 20:12, where Y corresponds to the “rise” of the roof or roof deck, and where X corresponds to the “run” of the roof or roof deck.

(27) As used herein, a “sloped” roof or roof deck is a roof or roof deck that is not flat, but has a pitch that is less than the pitch of a steep slope roof or roof deck.

(28) As used herein, a “flat” roof or roof deck is a roof or roof deck that is substantially flat.

(29) In some embodiments, the present invention provides a roofing module comprising a pair of grooves defining a nail zone therebetween.

(30) In some embodiments, the grooves comprise a pair of longitudinal grooves. In some embodiments, the longitudinal grooves are spaced apart from one another, thereby defining the nail zone.

(31) In some embodiments, the roofing module comprises a photovoltaic module. In some embodiments, the roofing module is a photovoltaic module shown and described in either or both of U.S. application Ser. No. 17/831,307, filed Jun. 2, 2022, titled “Roofing Module System,” and published under U.S. Patent Application Publication No. 2022-0393637 on Dec. 8, 2022; and/or U.S. application Ser. No. 18/169,718, filed Feb. 15, 2023, titled “Roofing Module System,” and published under U.S. Patent Application Publication No. 2023-0203815 on Jun. 29, 2023, the disclosures of each of which are incorporated by reference herein in their entireties. In some embodiments, the photovoltaic module includes a structure, composition, components, and/or function similar to those of one or more embodiments of the photovoltaic modules and shingles disclosed in PCT International Patent Publication No. WO 2022/051593, Application No. PCT/US2021/049017, published Mar. 10, 2022, titled “Building Integrated Photovoltaic System,” owned by GAF Energy LLC; U.S. Pat. No. 11,251,744 to Bunea et al., issued Feb. 15, 2022, titled “Photovoltaic Shingles and Methods of Installing Same, owned by GAF Energy LLC;” and U.S. Pat. No. 11,870,227, issued Jan. 9, 2024, entitled “Building Integrated Photovoltaic System,” owned by GAF Energy LLC, the disclosures of each of which are incorporated by reference herein in their entireties.

(32) In some embodiments, the roofing module is a non-photovoltaic module. In some embodiments, the non-photovoltaic module is a cuttable roofing module. In some embodiments, the roofing module includes a cap layer and a core layer. In some embodiments, the cuttable roofing module, the cap layer, and/or the core layer, are as shown and described in U.S. application Ser. No. 17/831,307, filed Jun. 2, 2022, titled “Roofing Module System,” and published under U.S. Patent Application Publication No. 2022-0393637 on Dec. 8, 2022, owned by GAF Energy LLC; U.S. application Ser. No. 18/169,718, filed Feb. 15, 2023, titled “Roofing Module System,” and published under U.S. Patent Application Publication No. 2023-0203815 on Jun. 29, 2023, owned by GAF Energy LLC; and/or U.S. application Ser. No. 18/352,894, filed Jul. 14, 2023, titled “Solar Roofing System with Fiber Composite Roofing Shingles,” owned by GAF Energy LLC, the disclosures of each of which are incorporated by reference herein in their entireties.

(33) In some embodiments, the photovoltaic module comprises at least one solar cell. In some embodiments, the at least one solar cell is electrically active—that is, the solar cell and/or associated electronics convert light, such as sunlight, into electricity by the photovoltaic effect. In some embodiments, the at least one solar cell is electrically inactive—that is, the solar cell and/or

associated electronics do not convert light into electricity.

(34) In some embodiments, one or more of the solar cells of the photovoltaic module are electrically active. In some embodiments, all of the solar cells of the photovoltaic module are electrically active. In some embodiments, one or more of the solar cells of the photovoltaic module are electrically inactive. In some embodiments, all of the solar cells of the photovoltaic module are electrically inactive. In some embodiments, at least one of the solar cells of the photovoltaic module is active while at least one of the solar cells of the photovoltaic module is electrically inactive.

(35) In some of the embodiments, the solar cells of the roofing module are positioned above a backsheet. In some embodiments, the solar cells are laminated to the backsheet. In some embodiments, the backsheet comprises one or more of ethylene propylene diene monomer (EPDM) rubber, polymethyl methacrylate (PMMA), polyethylene terephthalate (PET), ethylene tetrafluoroethylene (ETFE), thermoplastic polyolefin (TPO), and/or combinations of two or more thereof.

(36) In some embodiments, the backsheet is a single layer. In some embodiments, the backsheet is multiple layers.

(37) In some embodiments, the groove or grooves are formed on a cap layer. In some embodiments, the groove or grooves are formed on the cap layer, which is on a core layer.

(38) In some embodiments, the roofing module is configured to be installed above a roof deck with one or more fasteners. In some embodiments, the fasteners comprise one or more of nails, screws, staples, rivets, and/or combinations thereof.

(39) In some embodiments, the backsheet comprises a headlap portion. In some embodiments, the headlap portion defines the nail zone. In some embodiments, the headlap portion defines the nail zone between the longitudinal grooves that are formed on the backsheet.

(40) In some embodiments, the headlap portion comprises a first longitudinal groove, and a second longitudinal groove spaced apart from the first longitudinal groove on the backsheet, thereby to define the nail zone between the first longitudinal groove and the second longitudinal groove. In some embodiments, the nail zone is configured to receive at least one fastener that penetrates the backsheet of the photovoltaic module when the photovoltaic module is installed above the roof deck in a roofing system, as well as the roof deck, thereby to secure the photovoltaic module to the roof deck.

(41) In some embodiments, a depth of at least one of the first longitudinal groove and/or the second longitudinal groove is 0.01 mm. In some embodiments, the depth is 0.05 mm. In some embodiments, the depth is 0.1 mm. In some embodiments, the depth is 0.2 mm. In some embodiments, the depth is 0.3 mm. In some embodiments, the depth is 0.4 mm. In some embodiments, the depth is 0.5 mm. In some embodiments, the depth is 0.6 mm. In some embodiments, the depth is 0.7 mm. In some embodiments, the depth is 0.8 mm. In some embodiments, the depth is 0.9 mm. In some embodiments, the depth is 1.0 mm. In some embodiments, the depth is 1.1 mm. In some embodiments, the depth is 1.2 mm. In some embodiments, the depth is 1.3 mm. In some embodiments, the depth is 1.4 mm. In some embodiments, the depth is 1.5 mm. In some embodiments, the depth is 1.6 mm. In some embodiments, the depth is 1.7 mm. In some embodiments, the depth is 1.8 mm. In some embodiments, the depth is 1.9 mm. In some embodiments, the depth is 2.0 mm. In some embodiments, the depth is 3.0 mm. In some embodiments, the depth is 4.0 mm. In some embodiments, the depth is 5.0 mm.

(42) In some embodiments, the depth is more than 0.01 mm. In some embodiments, the depth is more than 0.05 mm. In some embodiments, the depth is more than 0.1 mm. In some embodiments, the depth is more than 0.2 mm. In some embodiments, the depth is more than 0.3 mm. In some embodiments, the depth is more than 0.4 mm. In some embodiments, the depth is more than 0.5 mm. In some embodiments, the depth is more than 0.6 mm. In some embodiments, the depth is

thickness. In some embodiments, the depth is 70% to 95% of the thickness. In some embodiments, the depth is 80% to 95% of the thickness. In some embodiments, the depth is 90% to 95% of the thickness.

(56) In some embodiments, the depth is 1% to 90% of the thickness of the layer or layers in which the groove is made (e.g., a backsheet). In some embodiments, the depth is 5% to 90% of the thickness. In some embodiments, the depth is 10% to 90% of the thickness. In some embodiments, the depth is 20% to 90% of the thickness. In some embodiments, the depth is 30% to 90% of the thickness. In some embodiments, the depth is 40% to 90% of the thickness. In some embodiments, the depth is 50% to 90% of the thickness. In some embodiments, the depth is 60% to 90% of the thickness. In some embodiments, the depth is 70% to 90% of the thickness. In some embodiments, the depth is 80% to 90% of the thickness.

(57) In some embodiments, the depth is 1% to 50% of the thickness of the layer or layers in which the groove is made (e.g., a backsheet). In some embodiments, the depth is 5% to 50% of the thickness. In some embodiments, the depth is 10% to 50% of the thickness. In some embodiments, the depth is 20% to 50% of the thickness. In some embodiments, the depth is 30% to 50% of the thickness. In some embodiments, the depth is 40% to 50% of the thickness.

(58) In some embodiments, the depth is 1% to 10% of the thickness of the layer or layers in which the groove is made (e.g., a backsheet). In some embodiments, the depth is 5% to 10% of the thickness. In some embodiments, the depth is 1% to 5% of the thickness.

(59) In some embodiments, a width of the nail zone between the first longitudinal groove and the second longitudinal groove is 0.5 inch. In some embodiments, the width is 0.6 inch. In some embodiments, the width is 0.7 inch. In some embodiments, the width is 0.8 inch. In some embodiments, the width is 0.9 inch. In some embodiments, the width is 1.0 inch. In some embodiments, the width is 1.1 inches. In some embodiments, the width is 1.2 inches. In some embodiments, the width is 1.3 inches. In some embodiments, the width is 1.4 inches. In some embodiments, the width is 1.5 inches. In some embodiments, the width is 1.6 inches. In some embodiments, the width is 1.7 inches. In some embodiments, the width is 1.8 inches. In some embodiments, the width is 1.9 inches. In some embodiments, the width is 2.0 inches.

(60) In some embodiments, the width is more than 0.5 inch. In some embodiments, the width is more than 0.6 inch. In some embodiments, the width is more than 0.7 inch. In some embodiments, the width is more than 0.8 inch. In some embodiments, the width is more than 0.9 inch. In some embodiments, the width is more than 1.0 inch. In some embodiments, the width is more than 1.1 inches. In some embodiments, the width is more than 1.2 inches. In some embodiments, the width is more than 1.3 inches. In some embodiments, the width is more than 1.4 inches. In some embodiments, the width is more than 1.5 inches. In some embodiments, the width is more than 1.6 inches. In some embodiments, the width is more than 1.7 inches. In some embodiments, the width is more than 1.8 inches. In some embodiments, the width is more than 1.9 inches. In some embodiments, the width is more than 2.0 inches.

(61) In some embodiments, the width is less than 0.5 inch. In some embodiments, the width is less than 0.6 inch. In some embodiments, the width is less than 0.7 inch. In some embodiments, the width is less than 0.8 inch. In some embodiments, the width is less than 0.9 inch. In some embodiments, the width is less than 1.0 inch. In some embodiments, the width is less than 1.1 inches. In some embodiments, the width is less than 1.2 inches. In some embodiments, the width is less than 1.3 inches. In some embodiments, the width is less than 1.4 inches. In some embodiments, the width is less than 1.5 inches. In some embodiments, the width is less than 1.6 inches. In some embodiments, the width is less than 1.7 inches. In some embodiments, the width is less than 1.8 inches. In some embodiments, the width is less than 1.9 inches. In some embodiments, the width is less than 2.0 inches.

(62) In some embodiments, the width is 0.5 inch to 2.0 inches. In some embodiments, the width is 0.6 inch to 2.0 inches. In some embodiments, the width is 0.7 inch to 2.0 inches. In some

400 mm. In some embodiments, the width is less than 500 mm. In some embodiments, the width is less than 600 mm. In some embodiments, the width is less than 700 mm.

(79) In some embodiments, the width of the nail zone is 10 mm to 70 mm. In some embodiments, the width of the nail zone is 10 mm to 60 mm. In some embodiments, the width of the nail zone is 10 mm to 50 mm. In some embodiments, the width of the nail zone is 10 mm to 40 mm. In some embodiments, the width of the nail zone is 10 mm to 30 mm. In some embodiments, the width of the nail zone is 10 mm to 20 mm. In some embodiments, the width of the nail zone is 10 mm to 100 mm. In some embodiments, the width of the nail zone is 10 mm to 50 mm.

(80) In some embodiments, the width of the nail zone is 20 mm to 70 mm. In some embodiments, the width of the nail zone is 20 mm to 60 mm. In some embodiments, the width of the nail zone is 20 mm to 50 mm. In some embodiments, the width of the nail zone is 20 mm to 40 mm. In some embodiments, the width of the nail zone is 20 mm to 30 mm. In some embodiments, the width of the nail zone is 20 mm to 100 mm. In some embodiments, the width of the nail zone is 20 mm to 50 mm.

(81) In some embodiments, the width of the nail zone is 30 mm to 70 mm. In some embodiments, the width of the nail zone is 30 mm to 60 mm. In some embodiments, the width of the nail zone is 30 mm to 50 mm. In some embodiments, the width of the nail zone is 30 mm to 40 mm.

(82) In some embodiments, the width of the nail zone is 40 mm to 70 mm. In some embodiments, the width of the nail zone is 40 mm to 60 mm. In some embodiments, the width of the nail zone is 40 mm to 50 mm.

(83) In some embodiments, the width of the nail zone is 50 mm to 70 mm. In some embodiments, the width of the nail zone is 50 mm to 60 mm. In some embodiments, the width of the nail zone is 60 mm to 70 mm.

(84) In some embodiments, the width of the nail zone is 50 mm to 700 mm. In some embodiments, the width of the nail zone is 50 mm to 600 mm. In some embodiments, the width of the nail zone is 50 mm to 500 mm. In some embodiments, the width of the nail zone is 50 mm to 400 mm. In some embodiments, the width of the nail zone is 50 mm to 300 mm. In some embodiments, the width of the nail zone is 50 mm to 200 mm. In some embodiments, the width of the nail zone is 50 mm to 100 mm.

(85) In some embodiments, the width of the nail zone is 100 mm to 700 mm. In some embodiments, the width of the nail zone is 100 mm to 600 mm. In some embodiments, the width of the nail zone is 100 mm to 500 mm. In some embodiments, the width of the nail zone is 100 mm to 400 mm. In some embodiments, the width of the nail zone is 100 mm to 300 mm. In some embodiments, the width of the nail zone is 100 mm to 200 mm.

(86) In some embodiments, the width of the nail zone is 200 mm to 700 mm. In some embodiments, the width of the nail zone is 200 mm to 600 mm. In some embodiments, the width of the nail zone is 200 mm to 500 mm. In some embodiments, the width of the nail zone is 200 mm to 400 mm. In some embodiments, the width of the nail zone is 200 mm to 300 mm.

(87) In some embodiments, the width of the nail zone is 300 mm to 700 mm. In some embodiments, the width of the nail zone is 300 mm to 600 mm. In some embodiments, the width of the nail zone is 300 mm to 500 mm. In some embodiments, the width of the nail zone is 300 mm to 400 mm. In some embodiments, the width of the nail zone is 400 mm to 500 mm.

(88) In some embodiments, both of the grooves extend from one end of the roofing module to the other end of the roofing module, along a major dimension of the roofing module. In some embodiments, only one of the grooves extends from one end of the roofing module to the other end of the roofing module. In some embodiments, neither of the grooves extends from one end of the roofing module to the other end of the roofing module.

(89) In some embodiments, both of the grooves extend from one end of the roofing module to a location spaced apart the other end of the roofing module, such that neither of the grooves extends from one end to the other end. In some embodiments, only one of the grooves extends from one

end of the roofing module to a location spaced apart from the other end of the roofing module, such that only one of the grooves extends from one end to the other end.

(90) In some embodiments, the photovoltaic module further comprises an encapsulant encapsulating the at least one solar cell. In some embodiments, the encapsulant encapsulates one side of the at least one solar cell. In some embodiments, the encapsulant encapsulates at least one side of the at least one solar cell. In some embodiments, the encapsulant fully encapsulates the at least one solar cell. In some embodiments, the encapsulant contacts the backsheet.

(91) In some embodiments, the photovoltaic module further comprises a frontsheet. In some embodiments, the frontsheet contacts the encapsulant. In some embodiments, the frontsheet is an uppermost layer of the photovoltaic module when the photovoltaic module is installed on or above a roof deck in a roofing system.

(92) In some embodiments, the frontsheet is a single layer. In some embodiments, the frontsheet is multiple layers.

(93) In some embodiments, there is an adhesive between the frontsheet and the encapsulant.

(94) In some embodiments, a roofing system includes a roof deck, and at least one roofing module installed on or above the roof deck. In some embodiments, the roof deck is a steep slope roof deck. In some embodiments, the roof deck is a sloped roof deck. In some embodiments, the roof deck is a flat roof deck.

(95) In some embodiments, the at least one roofing module comprises one roofing module. In some embodiments, the at least one roofing module comprises two roofing modules. In some embodiments, the at least one roofing module comprises three roofing modules. In some embodiments, the at least one roofing module comprises four roofing modules. In some embodiments, the at least one roofing module comprises five roofing modules. In some embodiments, the at least one roofing module comprises more than five roofing modules. In some embodiments, at least one of the roofing modules is a photovoltaic module. In some embodiments, at least one of the roofing modules is a non-photovoltaic module. In some embodiments, at least one of the roofing modules is a photovoltaic module, and at least one of the roofing modules is a non-photovoltaic module.

(96) In some embodiments, when the roofing modules are installed on or above the roof deck in the roofing system, at least some of the roofing modules are installed next to one another in a same row on the roof deck. In some embodiments, when the roofing modules are installed on or above the roof deck, at least some of the roofing modules are installed in multiple, different rows, where one row is above the other row on the roof deck. In some embodiments, when the roofing modules are installed on or above the roof deck in multiple rows, at least some of the roofing modules in one row overlap at least some of the roofing modules in another row. In some embodiments, when the roofing modules are installed on or above the roof deck in multiple rows, at least some of the roofing modules in one row overlap headlap portions of at least some of the roofing modules in another row (e.g., such that a part of one roofing module covers at least a part of the headlap portion of another roofing module).

(97) In some embodiments, one or more fasteners are installed through the nail zone of one or more of the roofing modules, thereby to fasten the roofing module to the roof deck. In some embodiments, the one or more fasteners penetrate the nail zone. In some embodiments, the one or more fasteners penetrate the roof deck. In some embodiments, the one or more fasteners penetrate an underlayment between the roof deck and the roofing module (e.g., when the roofing module is installed above the roof deck). In some embodiments, an underlayment is not installed or otherwise disposed between the roof deck and the roofing module.

(98) In some embodiments, the present invention provides a method. In some embodiments, the method comprises obtaining a backsheet material. In some embodiments, the method comprises forming the first groove in the headlap portion of the backsheet material (e.g., in a portion of the backsheet material that will be the headlap when the backsheet material is used to form a

photovoltaic module). In some embodiments, the method comprises forming the second groove in the headlap portion of the backsheet material. In some embodiments, the grooves are formed simultaneously (e.g., the forming of the first groove occurs at a same time as the forming of the second groove). In some embodiments, one groove is formed prior to the other groove.

(99) In some embodiments, either or both of the grooves are formed in the backsheet material to which no other layers are added. In some embodiments, either or both of the grooves are formed in the backsheet material to which one or more other layers are laminated before formation of the backsheet.

(100) In some embodiments, at least one groove is formed by a tool. In some embodiments, the tool is an awl. In some embodiments, the tool is a bit. In some embodiments, the tool is a blade. In some embodiments, the tool is a cutter. In some embodiments, the tool is knife. In some embodiments, the tool is a blade. In some embodiments, the tool is a razor. In some embodiments, the tool includes a sharp tip. In some embodiments, the tool is disposed in a fixture. In some embodiments, the fixture is disposed within a manufacturing line. In some embodiments, the manufacturing line is a manufacturing line for a backsheet material. In some embodiments, the backsheet material is cut into backsheets. In some embodiments, the backsheet material is cut into one or more backsheets in a same manufacturing line. In some embodiments, the backsheet material is cut into one or more backsheets in a different manufacturing line.

(101) In some embodiments, after forming one or both of the grooves, the grooved backsheet material is cut, thereby to form a grooved backsheet. In some embodiments, the frontsheet, encapsulant and/or the at least one solar cell are laminated with the backsheet, thereby to form the photovoltaic module. In some embodiments, before the backsheet material is cut, one or more layers are laminated to the grooved backsheet material.

(102) With reference to the figures, FIG. 1 shows a schematic view of a roofing module, according to some embodiments of the invention. As shown in the figure, in some embodiments, the roofing module **100** comprises a photovoltaic module. In some embodiments, the roofing module **100** comprises at least one solar cell **200**, and a backsheet **300**. In some embodiments, the solar cell **200** is positioned on the backsheet **300**. In some embodiments, the solar cell **200** is laminated to the backsheet **300**. In some embodiments, the roofing module **100** is a non-photovoltaic module. In some embodiments, the roofing module **100** includes a cap layer over a core layer.

(103) As shown in FIG. 1, in some embodiments, the backsheet **300** includes a headlap portion **310**. In some embodiments, the headlap portion **310** includes two longitudinal grooves **320** (e.g., a first groove and a second groove) formed thereon. As shown in the figure, in some embodiments, the longitudinal grooves **320** are spaced apart from one another, thereby to define a nail zone **330** between the longitudinal grooves **320**. In some embodiments, the nail zone **330** is configured to receive at least one fastener that penetrates the roofing module **100**, thereby to secure or fasten the roofing module **100** to a roof deck.

(104) As shown in FIGS. 1 and 2, in some embodiments, the longitudinal grooves **320** extend between a first end **340** of the backsheet **300** and a second end **350** of the backsheet **300**, the first end **340** spaced apart from and opposite to the second end **350** along a major dimension of the shingle, such that the longitudinal grooves **320** extend an entire length of the roofing module **100** (e.g., the longitudinal grooves extend an entire distance between the first end **340** and the second end **350**). In some embodiments, as shown in FIG. 1, each of the longitudinal grooves **320** is a single, continuous line segment. However, as shown in FIG. 2, either or both of the longitudinal grooves **320** may be two or more line segments (e.g., a discontinuous line).

(105) In some embodiments, as shown in FIGS. 3-14, one or both of the longitudinal grooves **320** do not extend from end **340** to end **350** of the backsheet **300** (e.g., one or both of the longitudinal grooves **320** do not extend an entire length of the roofing module). In some embodiments, either or both of the longitudinal grooves **320** may be two or more lines segments (e.g., a discontinuous line as shown in FIG. 2).

(106) Referring to FIG. 3, in some embodiments, one of the grooves 320 extends from the first end 340 to a location between the first end 340 and the second end 350, while the other of the grooves 320 extends from the first end 340 to the second end 350.

(107) Referring to FIG. 4, in some embodiments, one of the grooves 320 extends from the first end 340 to a location between the first end 340 and the second end 350, while the other of the grooves 320 extends from the second end 350 to a location between the first end 340 and the second end 350.

(108) Referring to FIG. 5, in some embodiments, one of the grooves 320 extends from the first end 340 to a location between the first end 340 and the second end 350, while the other of the grooves 320 extends from the first end 340 to a location between the first end 340 and the second end 350.

(109) Referring to FIG. 6, in some embodiments, one of the grooves 320 extends from the first end 340 to a location between the first end 340 and the second end 350, while the other of the grooves 320 extends from a first location between the first end 340 and the second end 350 to a second location between the first end 340 and the second end 350.

(110) Referring to FIG. 7, in some embodiments, one of the grooves 320 extends from the second end 350 to a location between the first end 340 and the second end 350, while the other of the grooves 320 extends from the first end 340 to the second end 350.

(111) Referring to FIG. 8, in some embodiments, one of the grooves 320 extends from the second end 350 to a location between the first end 340 and the second end 350, while the other of the grooves 320 extends from the second end 350 to a location between the first end 340 and the second end 350.

(112) Referring to FIG. 9, in some embodiments, one of the grooves 320 extends from the second end 350 to a location between the first end 340 and the second end 350, while the other of the grooves 320 extends from the first end 340 to a location between the first end 340 and the second end 350.

(113) Referring to FIG. 10, in some embodiments, one of the grooves 320 extends from the second end 350 to a location between the first end 340 and the second end 350, while the other of the grooves 320 extends from a first location between the first end 340 and the second end 350 to a second location between the first end 340 and the second end 350.

(114) Referring to FIG. 11, in some embodiments, one of the grooves 320 extends from a first location between the first end 340 and the second end 350 to a second location between the first end 340 and the second end 350, while the other of the grooves 320 extends from the first end 340 to the second end 350.

(115) Referring to FIG. 12, in some embodiments, one of the grooves 320 extends from a first location between the first end 340 and the second end 350 to a second location between the first end 340 and the second end 350, while the other of the grooves 320 extends from the second end 350 to a location between the first end 340 and the second end 350.

(116) Referring to FIG. 13, in some embodiments, one of the grooves 320 extends from a first location between the first end 340 and the second end 350 to a second location between the first end 340 and the second end 350, while the other of the grooves 320 extends from the first end 340 to a location between the first end 340 and the second end 350.

(117) Referring to FIG. 14, in some embodiments, one of the grooves 320 extends from a first location between the first end 340 and the second end 350 to a second location between the first end 340 and the second end 350, while the other of the grooves 320 extends from a third location between the first end 340 and the second end 350 to a fourth location between the first end 340 and the second end 350.

(118) FIG. 15 is a schematic view of a roofing system including a plurality of roofing modules, installed above a roof deck, in accordance with some embodiments of the invention. As shown in the figure, the roofing system 400 includes a plurality of roofing modules 100 installed above a roof deck 500. As shown, one or more fasteners 502 penetrate the nail zones 330 of the roofing

modules **100**, and penetrate the roof deck **500**, thereby to install the roofing modules **100** to the roof deck **500**. In some embodiments, the roofing system **400** includes an underlayment **504** installed between the roofing modules and the roof deck **500**. In some embodiments, the roofing system **400** does not include an underlayment installed between the roofing modules and the roof deck **500**.

(119) FIG. **16** is a photograph of a backsheet material including two longitudinal grooves—a grooved backsheet material—in accordance with embodiments of the invention. FIG. **17** is a photograph of the grooved backsheet material over which a top layer has been laminated, in accordance with some embodiments of the invention. As shown, the longitudinal grooves, and thus the nail zone therebetween, remains visible before and after lamination, such that the nail zone will be visible in a roofing module in accordance with the above-described embodiments of the invention. In some embodiments, the term “visible” means visible to a human eye without the aid of magnifying equipment.

(120) FIG. **18** is a photograph of some embodiments of a method of forming one or more grooves **620** in a surface **622** of a roofing shingle **600** to form a nail zone. In some embodiments, the surface **622** is an upper surface of the roofing shingle **600**. In some embodiments, the grooves **620** are formed by one or more tools **630**. In some embodiments, the tool **630** includes a tip **632**. In some embodiments, the tip **632** is a sharp tip. In some embodiments, the tip **632** is a pointed tip. In some embodiments, the tool **630** is a knife, a razor, or cutting tip. In some embodiments, the tool **630** creates the groove **620** by cutting, digging, or scratching.

(121) Referring to FIG. **19**, in some embodiments, a method of forming one or more roofing shingles **700** with nail zones is illustrated. In some embodiments, the roofing shingle **700** is a photovoltaic shingle or solar shingle. In some embodiments, the roofing shingle **700** is a non-photovoltaic shingle. In some embodiments, a first sheet **702** is provided. In some embodiments, the first sheet **702** is composed of a polymer. In some embodiments, the first sheet **702** is composed of one or more of ethylene propylene diene monomer (EPDM) rubber, polymethyl methacrylate (PMMA), polyethylene terephthalate (PET), ethylene tetrafluoroethylene (ETFE), thermoplastic polyolefin (TPO), and/or combinations of two or more thereof. In some embodiments, the first sheet **702** includes an upper surface **704**. In some embodiments, one or more sets of grooves **706** are formed in the upper surface **704** of the first sheet **702**. In some embodiments, the grooves **706** are formed by one or more of the instruments and/or methods as described herein. In some embodiments, each set of grooves **706** includes a pair of the grooves **706**. In some embodiments, each pair of grooves **706** forms a nail zone **708**. In some embodiments, the first sheet **702** is cut into dimensions at one or more cut lines **703** to form a plurality of backsheets **710**. In some embodiments, the first sheet **702** is cut into desired dimensions such that one portion of each of the backsheets **710** is configured to receive other layers of the roofing shingle **700**, such as a layer of one or more solar cells **712**, and another portion of each of the backsheets **710** is a headlap portion **714**. In some embodiments, the headlap portion **714** includes the nail zone **708** formed by the grooves **706**. In some embodiments, the grooves **706** are visible in the headlap portion **714** to a user, such as a roofing installer.

(122) In some embodiments, the backsheet **710** undergoes lamination with one or more other layers to fabricate the roofing shingle **700**. In some embodiments, lamination of the roofing shingle **700** occurs at 165° C. In some embodiments, lamination of the roofing shingle **700** occurs from 150° C. to 180° C. In some embodiments, lamination of the roofing shingle **700** occurs at a pressure of 14 psi. In some embodiments, lamination of the roofing shingle **700** occurs at a pressure of 10 psi to 20 psi. In some embodiments, lamination of the roofing shingle **700** occurs for 20 minutes. In some embodiments, lamination of the roofing shingle **700** occurs for 15 minutes to 25 minutes. In some embodiments, the grooves **706** do not disappear or diminish during lamination of the roofing shingle **700**. In some embodiments, material of the backsheet **710** or other layers of the roofing shingle **700** do not fill in or substantially fill in the grooves **706** during lamination of the roofing

shingle **700** so as to diminish, substantially diminish, or eliminate their visibility.

(123) FIGS. **20A** and **20B** illustrate embodiments of backsheets **710** composed of TPO formulations with different base resins that were tested and evaluated to determine which include nail zone grooves that are visible after lamination. In some embodiments, referring to Table 1 below and FIG. **20A**, the results indicate that a melting point within 2° C. of a lamination temperature of 165° C., coupled with a high flexural modulus of 480 MPa for P7 TPO with a base resin of Q402F resulted in visible grooves. In some embodiments, referring to Table 1 below and FIG. **20B**, the results indicate that a melting point within 2° C. of the lamination temperature of 165° C., coupled with a lower flexural modulus of 150 MPa for P26 TPO with a base resin of Adflex Q200F resulted in visible grooves, but with lower visibility than that of the embodiment of FIG. **20A**.

(124) TABLE-US-00001 TABLE 1 Resin Resin melt Flexural TPO Base point Modulus
Formulation Resin (° C.) (MPa) Result P26 Adflex 163 150 Visibility Q200F of Grooves P7 Q402F
163 480 Visibility of Grooves

(125) In some embodiments, a method includes: obtaining a first sheet; forming a first longitudinal groove in the first sheet; forming a second longitudinal groove in the first sheet, the first longitudinal groove spaced apart from the second longitudinal groove to define a first nail zone between the first longitudinal groove and the second longitudinal groove; forming a third longitudinal groove in the first sheet; forming a fourth longitudinal groove in the first sheet, the third longitudinal groove spaced apart from the fourth longitudinal groove to define a second nail zone between the third longitudinal groove and the fourth longitudinal groove, wherein the first nail zone is spaced apart from the second nail zone; cutting the sheet to form a first backsheet and a second backsheet, wherein the first backsheet includes the first nail zone, and wherein the second backsheet includes the second nail zone; laminating a first solar cell with the first backsheet to form a first photovoltaic module, wherein the first photovoltaic module includes a headlap portion, and wherein the first nail zone is on the headlap portion; and in some embodiments, laminating a second solar cell with the second backsheet to form a second photovoltaic module, wherein the second photovoltaic module includes a headlap portion, and where the second nail zone is on the headlap portion of the second photovoltaic module.

(126) Referring to FIGS. **21** through **23**, in some embodiments, a method of forming one or more roofing shingles **800** with nail zones is illustrated. In some embodiments, the roofing shingle **800** is a photovoltaic shingle or solar shingle. In some embodiments, the roofing shingle **800** is a non-photovoltaic shingle. In some embodiments, a first sheet **802** and a second sheet **803** are provided. In some embodiments, the first sheet **802** is composed of a polymer. In some embodiments, the first sheet **802** is composed of one or more of ethylene propylene diene monomer (EPDM) rubber, polymethyl methacrylate (PMMA), polyethylene terephthalate (PET), ethylene tetrafluoroethylene (ETFE), thermoplastic polyolefin (TPO), and/or combinations of two or more thereof.

(127) In some embodiments, the second sheet **803** is composed of a polymer. In some embodiments, the second sheet **803** is composed of one or more of ethylene propylene diene monomer (EPDM) rubber, polymethyl methacrylate (PMMA), polyethylene terephthalate (PET), ethylene tetrafluoroethylene (ETFE), thermoplastic polyolefin (TPO), and/or combinations of two or more thereof.

(128) Referring to FIG. **23**, in some embodiments, the second sheet **803** is composed of TPO with a P3 formulation and Hifax™ CA10A base resin. In some embodiments, the second sheet **803** is composed of TPO with a P26 formulation and an Adflex™ Q200F base resin. In some embodiments, the second sheet **803** is composed of TPO with a P7 formulation and Adflex™ Q402F base resin. In some embodiments, the second sheet **803** is composed of TPO with a P22 formulation and ProFax™ base resin. In some embodiments, the second sheet **803** is composed of TPO with a C12 formulation and Hifax™ CA10A base resin. In some embodiments, the second sheet **803** includes a dark color. In some embodiments, the second sheet **803** includes a black color.

In some embodiments, the second sheet **803** includes a color that enables grooves **814** formed therein to be visible.

(129) In some embodiments, the first sheet **802** and the second sheet **803** are separate from one another. In some embodiments, the first sheet **802** is cut to desired dimensions at one or more cut lines **801** to produce one or more base portions **804** that are configured to receive other layers of the roofing shingle **800**, such as a layer of one or more solar cells **806** in a reveal portion, and side lap portions **808**, **810**. In some embodiments, the base portion **804** and the solar cells **806** are laminated.

(130) In some embodiments, the second sheet **803** includes an upper surface **812**. In some embodiments, one or more sets of grooves **814** are formed in the upper surface **812** of the second sheet **803**. In some embodiments, the grooves **814** are formed by one or more of the instruments and methods as described herein. In some embodiments, each set of grooves **814** includes a pair of the grooves **814**. In some embodiments, each pair of grooves **814** forms a nail zone **816**. In some embodiments, the second sheet **803** is cut into dimensions at one or more cut lines **801** to form a plurality of headlap portions **818**. In some embodiments, the headlap portion **818** is not laminated. In some embodiments, the grooves **814** of the nail zone **816** are not subjected to lamination.

(131) In some embodiments, the headlap portion **818** is attached to the base portion **804**. In some embodiments, a lower edge **820** of the headlap portion **818** is attached to an upper edge **822** of the base portion **804**. In some embodiments, the headlap portion **818** is attached to the base portion **804** by heat pressure. In some embodiments, the headlap portion **818** is attached to the base portion **804** by welding. In some embodiments, the headlap portion **818** is attached to the base portion **804**. In some embodiments, the headlap portion **818** is attached to the base portion **804** by ultrasonic welding. In some embodiments, the headlap portion **818** is attached to the base portion **804** by an adhesive. In some embodiments, the headlap portion **818** does not include a UV stabilizer. In some embodiments, the headlap portion **818** does not include a pigment. In some embodiments, the base portion **804** includes a pigment. In some embodiments, the base portion **804** includes a UV stabilizer.

(132) In some embodiments, a method includes: obtaining a first sheet; forming a first longitudinal groove in the first sheet; forming a second longitudinal groove in the first sheet, the first longitudinal groove spaced apart from the second longitudinal groove to define a first nail zone between the first longitudinal groove and the second longitudinal groove; forming a third longitudinal groove in the first sheet; forming a fourth longitudinal groove in the first sheet, the third longitudinal groove spaced apart from the fourth longitudinal groove to define a second nail zone between the third longitudinal groove and the fourth longitudinal groove, wherein the first nail zone is spaced apart from the second nail zone; cutting the first sheet to form a first headlap portion and a second headlap portion, wherein the first headlap portion includes the first nail zone, and wherein the second headlap portion includes the second nail zone; obtaining a second sheet; laminating a first solar cell with the second sheet; attaching the first headlap portion to the second sheet to form a first photovoltaic module; in some embodiments, obtaining a third sheet; laminating a second solar cell with the third sheet; and attaching the second headlap portion to the third sheet to form a second photovoltaic module.

(133) Variations, modifications, and alterations to embodiments of the present disclosure described above will make themselves apparent to those skilled in the art. All such variations, modifications, alterations, and the like are intended to fall within the spirit and scope of the present disclosure, limited solely by the appended claims.

(134) While several embodiments of the present disclosure have been described, it is understood that these embodiments are illustrative only, and not restrictive, and that many modifications may become apparent to those of ordinary skill in the art. For example, all dimensions discussed herein are provided as examples only, and are intended to be illustrative and not restrictive.

(135) Any feature or element that is positively identified in this description may also be specifically

excluded as a feature or element of an embodiment of the present as defined in the claims.
(136) The disclosure described herein may be practiced in the absence of any element or elements, limitation or limitations, which is not specifically disclosed herein. The terms and expressions which have been employed are used as terms of description and not of limitation, and there is no intention in the use of such terms and expressions of excluding any equivalents of the features shown and described or portions thereof, but it is recognized that various modifications are possible within the scope of the disclosure.

Claims

1. A system, comprising: a plurality of photovoltaic modules installed on a roof deck, each of the plurality of photovoltaic modules comprising: at least one solar cell, and a backsheet, wherein the at least one solar cell is above the backsheet, and wherein the backsheet includes a headlap portion, wherein the headlap portion comprises a first surface, and a first longitudinal groove in the first surface and a second longitudinal groove in the first surface, wherein the first longitudinal groove is spaced apart from the second longitudinal groove to define a nail zone between the first longitudinal groove and the second longitudinal groove, and wherein each of the photovoltaic modules is configured to receive at least one fastener within the nail zone for installing the photovoltaic module to the roof deck, and wherein each of the plurality of photovoltaic modules does not include granules on at least the first surface of the headlap portion.
2. The system of claim 1, wherein a depth of at least one of the first longitudinal groove or the second longitudinal groove is 0.1 mm to 0.2 mm.
3. The system of claim 1, wherein a width of the nail zone between the first longitudinal groove and the second longitudinal groove is 3 cm to 6 cm.
4. The system of claim 1, wherein each of the first longitudinal groove and the second longitudinal groove extends from one end of the backsheet to an opposite end of the backsheet.
5. The system of claim 1, wherein the backsheet is composed of thermoplastic polyolefin (TPO).
6. The system of claim 1, wherein the headlap portion is an integral portion of the backsheet.
7. The system of claim 1, wherein the backsheet includes a base portion, and wherein the headlap portion is attached to the base portion.
8. The system of claim 7, wherein the at least one solar cell and the base portion are laminated, and wherein the headlap portion is not laminated.
9. The system of claim 8, wherein the headlap portion does not include a pigment.
10. A photovoltaic module, comprising: at least one solar cell, and a backsheet, wherein the at least one solar cell is above the backsheet, wherein the backsheet comprises a headlap portion, wherein the headlap portion comprises a first surface, and a first longitudinal groove in the first surface and a second longitudinal groove in the first surface, wherein the first longitudinal groove is spaced apart from the second longitudinal groove on the backsheet to define a nail zone between the first longitudinal groove and the second longitudinal groove, and wherein the nail zone is configured to receive at least one fastener that penetrates the photovoltaic module to secure the photovoltaic module to a roof deck, and wherein each of the plurality of photovoltaic modules does not include granules on at least the first surface of the headlap portion.
11. The photovoltaic module of claim 10, wherein the backsheet comprises thermoplastic polyolefin (TPO).
12. The photovoltaic module of claim 10, wherein a depth of at least one of the first longitudinal groove or the second longitudinal groove is 0.1 mm to 0.2 mm.
13. The photovoltaic module of claim 10, wherein a width of the nail zone between the first longitudinal groove and the second longitudinal groove is 3 cm to 6 cm.
14. The photovoltaic module of claim 10, wherein each of the first longitudinal groove and the second longitudinal groove extends from one end of the backsheet to an opposite end of the

backsheet.

15. The photovoltaic module of claim 10, wherein the headlap portion an integral portion of the backsheet.

16. The photovoltaic module of claim 10, wherein the backsheet includes a base portion, and wherein the headlap portion is attached to the base portion.

17. The photovoltaic module of claim 16, wherein the at least one solar cell and the base portion are laminated, and wherein the headlap portion is not laminated.

18. The photovoltaic module of claim 16, wherein the headlap portion does not include a pigment.

19. A method, comprising: obtaining a first sheet wherein the first sheet includes a first surface; forming a first longitudinal groove in the first surface of the first sheet; forming a second longitudinal groove in the first surface of the first sheet, the first longitudinal groove spaced apart from the second longitudinal groove to define a first nail zone between the first longitudinal groove and the second longitudinal groove; forming a third longitudinal groove in the first surface of the first sheet; forming a fourth longitudinal groove in the first surface of the first sheet, the third longitudinal groove spaced apart from the fourth longitudinal groove to define a second nail zone between the third longitudinal groove and the fourth longitudinal groove, wherein the first nail zone is spaced apart from the second nail zone; cutting the first sheet to form a first backsheet and a second backsheet, wherein the first backsheet includes the first nail zone, and wherein the second backsheet includes the second nail zone; and laminating a first solar cell with the first backsheet to form a first photovoltaic module, wherein the first photovoltaic module includes a headlap portion, and wherein the first nail zone is on the headlap portion, and wherein each of the plurality of photovoltaic modules does not include granules on at least the first surface of the headlap portion.

20. The method of claim 19, further comprising laminating a second solar cell with the second backsheet to form a second photovoltaic module, wherein the second photovoltaic module includes a headlap portion, and where the second nail zone is on the headlap portion of the second photovoltaic module.
