

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413910
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Ren; Zhang et al.

Speaker device

Abstract

The present application provides a speaker device including a casing and a sounding driver. The casing has an accommodating space and a sound-conducting channel, and the sounding driver is accommodated in the accommodating space. The sounding driver comprises a first frame, a first vibration system, a magnetic circuit system, a second frame, a second vibration system, and a conductive insert. An end of the second frame separates the front sound cavity into a first front sound cavity and a second front sound cavity. The sound-conducting channel is connected to the first front sound cavity; the second frame is provided with a first notch and a second notch. The first and the second notches are connected the second front sound cavity to the first front sound cavity. Compared with the related art, the speaker device of the present application has better acoustic performance and drainage performance.

Inventors: Ren; Zhang (Changzhou, CN), Zhong; Zhiwei (Changzhou, CN), Li; Qiaoling (Changzhou, CN)

Applicant: AAC Microtech (Changzhou) Co., Ltd. (Jiangsu, CN)

Family ID: 95400789

Assignee: AAC Microtech (Changzhou) Co., Ltd. (Changzhou, CN)

Appl. No.: 18/533247

Filed: December 08, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250133350 A1	Apr. 24, 2025

Related U.S. Application Data

continuation parent-doc WO PCT/CN2023/125905 20231023 PENDING child-doc US 18533247

Publication Classification

Int. Cl.: H04R9/06 (20060101)

U.S. Cl.:

CPC H04R9/06 (20130101);

Field of Classification Search

CPC: H04R (1/2834); H04R (9/025); H04R (1/22); H04R (1/26); H04R (1/023); H04R (1/2826); H04R (1/025); H04R (9/06); H04R (9/02); H04R (1/2857); H04R (7/127); H04R (1/24); H04R (2400/01); H04R (2400/11); H04R (7/16); H04R (9/046); H04R (7/04); H04R (9/063)

USPC: 381/400-412

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8300876	12/2011	Xu	381/431	H04R 31/006
2004/0071303	12/2003	Furuya	379/433.02	H04M 1/035
2005/0254680	12/2004	Kitamura	381/396	H04R 1/06
2020/0213741	12/2019	Shen	N/A	H04R 1/345
2020/0213761	12/2019	Xiao	N/A	H04R 7/04
2023/0292037	12/2022	Xu	N/A	H04R 1/24

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201781608	12/2010	CN	N/A

Primary Examiner: Edwards; Carolyn R

Assistant Examiner: Dang; Julie X

Attorney, Agent or Firm: Wiersch Law Group

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/CN2023/125905, filed Oct. 23, 2023, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The present application relates to the field of electroacoustic conversion, in particular to a speaker device.

BACKGROUND

(2) The speaker device is a transducer that converts electrical signals into sound signals. It is

primarily categorized into two modes: the single vibration system and the dual vibration system. In the dual vibration system mode, the speaker device includes a first vibration system fixed to a frame for producing low-frequency sounds and a second vibration system fixed to the magnetic circuit for producing high-frequency sounds.

(3) In the speaker device with the dual vibration system mode in the related art, the first vibration system and the second vibration system produce sounds through sound-conducting channels formed by the closed structure, which are isolated from each other, and the first vibration system, which produces the high-frequency sounds tends to use the smaller sound-conducting channel. On the other hand, the closed structure also makes the drainage performance of the speaker device decrease, so that the high-frequency sound band produced by the speaker device in the related art is too narrow, and the drainage performance is insufficient, which results in the acoustic performance of the speaker device in the water-entry environment being reduced.

(4) Therefore, it is necessary to provide a new speaker device to solve the above technical problem.

SUMMARY

(5) An object of the present application is to provide a speaker device with better acoustic performance in dual vibration system mode.

(6) In order to achieve the above object, the present application provides a speaker device, comprising: a casing having an accommodating space and formed by a top cover, an upper cover and a bottom cover; a sound-conducting channel formed in the casing; and a sounding driver accommodated in the accommodating space; wherein the sounding driver is fixed to the casing and separates the accommodating space into a front sound cavity and a rear cavity; the sound-conducting channel connects the front sound cavity to the outside world, and the sound-conducting channel and the front sound cavity together form a front cavity; the sounding driver comprises: a first frame, fixedly supported on the casing; a first vibration system, comprising a first diaphragm fixed at its outer periphery to the first frame and a first voice coil configured to drive the first diaphragm to vibrate to produce sounds; a magnetic circuit system, fixed to the first frame, wherein a side of the magnetic circuit system close to the first vibration system is provided with a first magnetic gap and a second magnetic gap; the first magnetic gap is arranged around the second magnetic gap and spaced apart from each other; and the first voice coil is inserted and suspended within the first magnetic gap; a second frame, fixed to a top of the magnetic circuit system; a second vibration system, comprising a second diaphragm fixed at its outer periphery to a side of the second frame away from the magnetic circuit system, and a second voice coil configured to drive the first diaphragm to vibrate to produce sounds; wherein the second voice coil is inserted and suspended within the second magnetic gap; and a conductive insert, extended from a bottom of the magnetic circuit system to the top of the magnetic circuit system and extended below the second diaphragm, and electrically connected to the second voice coil; wherein one end of the second frame away from the magnetic circuit system is abutted against the casing and separates the front sound cavity into a first front sound cavity and a second front sound cavity, wherein the upper cover of the casing, a side wall of the bottom cover, and the sounding driver together enclose the first front sound cavity; the upper cover of the casing and the sounding driver together enclose the second front sound cavity; the sound-conducting channel is in communication with the first front sound cavity; the second frame is provided with a first notch and a second notch, wherein the first notch and the second notch are arranged through the second frame in a direction perpendicular to a vibration direction of the second diaphragm; the first notch is spaced opposite the second notch and the first notch is smaller than the second notch; the first notch and the second notch both connect the second front sound cavity to the first front sound cavity.

(7) In one embodiment, the first notch is located on a side of the second frame close to the sound-conducting channel, and the second notch is located on a side of the second frame away from the sound-conducting channel.

(8) In one embodiment, the first notch and the second notch are both formed by a downward

depression of one end of the second frame away from the magnetic circuit system; a depth of the first notch is less than a depth of the second notch, and a width of the first notch is less than a width of the second notch.

(9) In one embodiment, an end of the conductive insert away from the second diaphragm is arranged through the casing and at least partially exposed outside the casing.

(10) In one embodiment, the magnetic circuit system comprises an upper splint in the shape of an annulus, a lower splint, a main magnetic steel, a first sub-magnetic steel, a pole core, and a second sub-magnetic steel; wherein the upper splint is fixedly stacked on the first sub-magnetic steel and fixedly connected to the first frame; the main magnetic steel is in the shape of an annulus and fixedly stacked on the lower splint; the first sub-magnetic steel is fixedly stacked on the lower splint and arranged around the main magnetic steel, and the main magnetic steel and the first sub-magnetic steel are spaced apart to form the first magnetic gap; the pole core comprises a core body in the shape of an annulus and fixedly fixed to the main magnetic steel and a core extension in the shape of an annulus and bent and extended from an inner periphery of the core body along a direction away from the lower splint, wherein the core extension is arranged around the conductive insert; the second sub-magnetic steel is fixedly stacked on a side of the core body close to the first vibration system, the second sub-magnetic steel is arranged around the core extension and spaced apart from the core extension to form the second magnetic gap

(11) In one embodiment, the magnetic circuit system further comprises a secondary pole core fixedly stacked on a side of the second sub-magnetic steel close to the first vibration system, wherein the secondary pole core is in the shape of an annulus and arranged around the conductive insert, and the second frame is connected to an outer periphery of the secondary pole core.

(12) In one embodiment, the first vibration system further comprises a first skeleton, comprising a skeleton body in the shape of an annulus and used as the first vibration portion and a skeleton fixing portion bent downwardly and extended from an outer periphery of the skeleton body.

(13) In one embodiment, the first diaphragm comprises a first folded ring in the shape of an annulus, a second folded ring in the shape of an annulus, which is spaced apart from the first folded ring and arranged on an inner side of the first folded ring, and a first vibration portion in the shape of an annulus, which is bent and extended from an inner periphery of the first folded ring to be connected to the outer periphery of the second folded ring; an outer periphery of the first folded ring is fixed to the first skeleton; an inner periphery of the second folded ring being fixed to the second skeleton body; an inner periphery of the second folded ring is fixed to a side of the first sub-magnetic steel away from the main magnetic steel; and the first voice coil is fixed to a side of the first vibration portion close to the magnetic circuit system.

(14) In one embodiment, the inner periphery of the second folded ring is fixedly sandwiched between the second frame and the main magnetic steel.

(15) In one embodiment, the second diaphragm comprises a second vibration portion, a third folded ring in the shape of an annulus and extended outwardly from an outer periphery of the second vibration portion, and a second dome covered on the second vibration portion, wherein an outer periphery of the third folded ring is fixed to a side of the second frame away from the first sub-magnetic steel, and the second voice coil is fixed to the second vibration portion.

(16) Compared with the prior art, the speaker device of the present application includes a casing having an accommodating space and formed by a top cover, an upper cover and a bottom cover; a sound-conducting channel formed in the casing, and a sounding driver accommodated in the accommodating space. The sounding driver is fixed to the casing and separates the accommodating space into a front sound cavity and a rear cavity. The sound-conducting channel connects the front sound cavity to the outside world, and the sound-conducting channel and the front sound cavity together form a front cavity. The sounding driver includes: a first frame, fixedly supported on the casing; a first vibration system, including a first diaphragm fixed at its outer periphery to the first frame and a first voice coil configured to drive the first diaphragm to vibrate to produce sounds; a

magnetic circuit system, fixed to the first frame, in which a side of the magnetic circuit system close to the first vibration system is provided with a first magnetic gap and a second magnetic gap; the first magnetic gap is arranged around the second magnetic gap and spaced apart from each other; and the first voice coil is inserted and suspended within the first magnetic gap; a second frame, fixed to a top of the magnetic circuit system; a second vibration system, including a second diaphragm fixed at its outer periphery to a side of the second frame away from the magnetic circuit system, and a second voice coil configured to drive the first diaphragm to vibrate to produce sounds, in which the second voice coil is inserted and suspended within the second magnetic gap; and a conductive insert, extended from a bottom of the magnetic circuit system to the top of the magnetic circuit system and extended below the second diaphragm, and electrically connected to the second voice coil. One end of the second frame away from the magnetic circuit system is abutted against the casing and separates the front sound cavity into a first front sound cavity and a second front sound cavity. The upper cover of the casing, a side wall of the bottom cover, and the sounding driver together enclose the first front sound cavity. The upper cover of the casing and the sounding driver together enclose the second front sound cavity. The sound-conducting channel is in communication with the first front sound cavity. The second frame is provided with a first notch and a second notch, in which the first notch and the second notch are arranged through the second frame in a direction perpendicular to a vibration direction of the second diaphragm. The first notch is spaced opposite the second notch and the first notch is smaller than the second notch. The first notch and the second notch both connect the second front sound cavity to the first front sound cavity. The speaker device is provided with the second frame having two side notches in the treble vibration system, wherein the larger second notch is connected to the front sound cavity, so that the treble airflow comes out from the direction of being backed up against the sound-conducting channel and then converges with the front cavity, so as to lengthen the conduction channel of the treble airflow, thereby raising the treble frequency band of the speaker device, and improving the high-frequency sounds. The smaller first notch is provided squarely opposite to the sound-conducting channel, so that the speaker device can improve the drainage efficiency through the first notch, thereby improving the acoustic performance and usability of the speaker device in the water ingress environment.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In order to illustrate the technical solutions in the embodiments of the present application more clearly, the accompanying drawings to be used in the description of the embodiments will be briefly introduced below. Obviously, the accompanying drawings in the following description are only some embodiments of the present application, and for those of ordinary skill in the field, other accompanying drawings may be obtained based on these drawings without creative labor.
- (2) FIG. 1 shows a three-dimensional structural diagram of a speaker device of an embodiment of the present application.
- (3) FIG. 2 shows a three-dimensional exploded view of the speaker device according to an embodiment of the present application.
- (4) FIG. 3 shows a sectional view of line A-A in FIG. 1.
- (5) FIG. 4 shows a sectional view of line B-B in FIG. 1.
- (6) FIG. 5 shows a structural diagram of a second frame in the speaker device according to an embodiment of the present application.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (7) The technical solutions in the embodiments of the present application will be described clearly and completely in the following in conjunction with the accompanying drawings in the

embodiments of the present application. Obviously, the described embodiments are only a part of the embodiments of the present application and not all of the embodiments. Based on the embodiments in the present application, all other embodiments obtained by those of ordinary skill in the art without making creative labor are within the protection scope of the present application.

(8) As shown in FIGS. 1-5, embodiments of the present application provide a speaker device **100**, including a casing **1** and a sounding driver **2**.

(9) The casing **1** has an accommodating space, and a sound-conducting channel **14** formed within the casing. In this embodiment, in order to facilitate the assembly of the speaker device **100**, the casing **1** specifically includes a top cover **11**, a upper cover **12**, the sound-conducting channel **14**, and a bottom cover **13**.

(10) The sounding driver **2** is accommodated in the accommodating space. The sounding driver **2** is fixed to the casing **1** and separates the accommodating space into a front sound cavity and a rear cavity. The sound-conducting channel **14** connects the front sound cavity to the outside world, and the sound-conducting channel **14** and the front sound cavity together form a front cavity. The sounding driver **2** is fixed to the casing **1**, and the sounding driver **2** and the bottom cover **13** together form the rear cavity. The sounding driver **2** includes a first frame **21**, a first vibration system **22**, a magnetic circuit system **23**, a second frame **24**, a second vibration system **25**, and a conductive insert **26**.

(11) The first frame **21** is fixedly supported on the casing **1** and is configured to support the first vibration system **22** and the magnetic circuit system **23**. In this embodiment, the first frame **21** is a ring-like structure surrounded by metal sheets.

(12) The first vibration system **22** includes a first diaphragm **221** fixed at its outer periphery to the first frame **21** and a first voice coil **222** configured to drive the first diaphragm **221** to vibrate to produce sounds. In this embodiment, the first vibration system **22** is configured to produce low-frequency sounds.

(13) The magnetic circuit system **23** is fixed to the first frame **21**, and a side of the magnetic circuit system **23** close to the first vibration system **22** is provided with a first magnetic gap **236** and a second magnetic gap **237**. The first magnetic gap **236** is arranged around the second magnetic gap **237** and spaced apart from the second magnetic gap **237**. The first voice coil **222** is inserted and suspended within the first magnetic gap **236**.

(14) The second frame **24** is fixed to the top of the magnetic circuit system **23** for supporting the second vibration system **25**.

(15) The second vibration system **25** includes a second diaphragm **251** fixed at its outer periphery to a side of the second frame **24** away from the magnetic circuit system **23**, and a second voice coil **252** configured to drive the second diaphragm **251** to vibrate to produce sounds. The second voice coil **252** is inserted and suspended within the second magnetic gap **237**. In this embodiment, the second vibration system **25** is configured to produce high-frequency sounds.

(16) That is, the first vibration system **22** and the second vibration system **25** share the magnetic circuit system **23**, and are driven by the magnetic circuit system **23** to produce sounds of different frequency bands, respectively.

(17) The conductive insert **26** is provided with a conductive terminal **261** throughout, and the conductive insert **26** is extended from the bottom of the magnetic circuit system **23** to the top of the magnetic circuit system **23** and extended to the second diaphragm **251**, and electrically connected to the second voice coil **252** through the conductive terminal **261**. The electrical signal of the first voice coil **222** is electrically powered through a conductive member **224** fixed to the first frame **21**.

(18) Specifically, in this embodiment, one end of the second frame **24** away from the magnetic circuit system **23** is abutted against the casing **1** and separates the front sound cavity into a first front sound cavity and a second front sound cavity. The upper cover **12**, a side wall of the bottom cover **13** of the casing **1** and the sounding driver **2** together enclose the first front sound cavity, and the top cover **11** of the casing **1** and the sounding driver **2** together enclose the second front sound

cavity. The sound-conducting channel **14** is in communication with the first front sound cavity. The second frame **24** is provided with a first notch **241** and a second notch **242**, in which the first notch **241** and the second notch **242** are arranged through the second frame **24** in a direction perpendicular to the vibration direction of the second diaphragm **251**. The first notch **241** is spaced opposite the second notch **242**. A size of the first notch **241** is smaller than a size of the second notch **242**. Both the first notch **241** and the second notch **242** connect the second front sound cavity to the first front sound cavity.

(19) Specifically, in this embodiment, in the case where the second voice coil **252** drives the second diaphragm **251** to vibrate to produce high-frequency sounds, the high-frequency airflow generated by the second front sound cavity is conducted into the first front sound cavity through the first notch **241**, the second notch **242** and thus emits the high-frequency sounds through the sound-conducting channel **14**. In order to realize such a design, when a notch is provided on the second frame **24**, the circumference of the second diaphragm **251** (the fixing portion of the second diaphragm **24**) needs to be adaptively shaped as a notch, so as to realize a fixed fit of the circumference of the second diaphragm **251** to the second frame **24**.

(20) Specifically, in this embodiment, the first notch **241** is located on a side of the second frame **24** close to the sound-conducting channel **14**, and the second notch **242** is located on a side of the second frame **24** away from the sound-conducting channel **14**. The first notch **241** and the second notch **242** are provided at different positions to produce different effects. The first notch **241** is arranged through a side of the second frame **24** close to the sound-conducting channel **14**, enabling the treble airflow to be transmitted through the first notch **241** to the sound-conducting channel **14** without being conducted through the first front sound cavity. In the event of water ingress into the second front sound cavity, such a design allows water vapor to be carried out of the second front sound cavity by the action of the treble airflow and discharged through the sound-conducting channel **14**, so as to improve the water drainage performance of the speaker device **100** and to optimize the acoustic effect in the water ingress environment. the second notch **242** is arranged through a side of the second frame **24** away from the sound-conducting channel **14**, and the first front sound cavity is in communication with the second front sound cavity, so that the treble airflow can be conducted to the first front sound cavity through the second notch **242**. Since the space of the first front sound cavity is much larger than the space of the second front sound cavity, the frequency band of the treble airflow is extended, and the high-frequency effect of the speaker device **100** can be improved when the sound airflow is ultimately transmitted out to the sound-conducting channel **14**.

(21) Specifically, in this embodiment, the first notch **241** and the second notch **242** are both formed by a downward depression of one end of the second frame **24** away from the magnetic circuit system **23**. The depth of the first notch **241** is less than the depth of the second notch **241**, and the width of the first notch **241** is less than the width of the second notch **242**. By such design, the size of the opening of the first notch **241** is smaller than the second notch **242**. In this embodiment, the first notch **241** and the second notch **242** are provided at different positions to produce different effects, in which the first notch **241** is configured to assist in draining water and the second notch **242** is configured to widen the treble band of the front sound cavity, in order to ensure that the opening of the first notch **241** does not excessively affect the acoustic performance of the speaker device. In this embodiment, the opening of the first notch **241** is arranged to be smaller than the second notch **242**, so that the treble airflow can be conducted to the front sound cavity more through the second notch **242** with a larger opening, while the first notch **241** having a smaller opening can satisfy the water draining performance requirements of the speaker device **100** without excessively leaking the high-frequency airflow.

(22) Specifically, in this embodiment, the magnetic circuit system **23** is arranged around the conductive insert **26**. One end of the conductive insert **26** is connected to the second voice coil **252**, and the other end of the conductive insert **26** away from the second diaphragm **24** is arranged

through the casing **1** and is at least partially exposed outside the casing **1**.

(23) Specifically, in this embodiment, the casing **1** is provided with a through-hole, which is arranged through the casing **1**. The sounding driver **2** further includes a lower splint **27** fixed to the casing **1** and arranged around the conductive insert **26**. The lower splint **27** is covered on the through-hole and exposed outside the casing **1**. This structure is set up in such a way as to allow the magnetic circuit system **23** to make full use of the space in the thickness of the casing **1**, while guaranteeing the same volume of the rear chamber, which allows the speaker device to be made thinner;

(24) The magnetic circuit system **23** further includes a main magnetic steel **231**, a first sub-magnetic steel **232**, a pole core **233**, a second sub-magnetic steel **234**, and an upper splint **235**. The upper splint **235** is fixedly stacked on the first sub-magnetic steel **232** and fixedly connected to the first frame **21**. The main magnetic steel **231** is in the shape of an annulus and fixedly stacked on the lower splint **27**. The first sub-magnetic steel **232** is fixedly stacked on the lower splint **27** and arranged around the main magnetic steel **231**. The main magnetic steel **231** and the second sub-magnetic steel **234** are spaced from the first sub-magnetic steel **232** to form the first magnetic gap **236**.

(25) The pole core **233** includes a core body **2331** in the shape of an annulus and fixedly stacked on the main magnetic steel **231** and a core extension **2332** in the shape of an annulus, which is bent and extended in a direction away from the lower splint **27** from an inner periphery of the core body **2331**. The core extension **2332** is arranged around the conductive insert **26**.

(26) The second sub-magnetic steel **234** is fixedly stacked on the side of the core body **2331** close to the vibration system. The second sub-magnetic steel **234** are arranged around the core extension **2332** and spaced apart from the core extension **2332** to form the second magnetic gap **237**.

(27) Specifically, in this embodiment, in order to further improve the magnetic field performance of the magnetic circuit system **23**, the magnetic circuit system **23** further includes a secondary pole core **238** fixedly stacked on the side of the second sub-magnetic steel **234** close to the first vibration system **22**. The secondary pole core **238** is in the shape of an annulus and arranged around the conductive insert **26**, and the second frame **24** is connected to an outer periphery of the secondary pole core **238**. This structure effectively reduces the loss of magnetic lines of force from the second sub-magnetic steel **234**. The inner periphery of the second frame **24** is fixedly connected to the outer periphery of the secondary pole core **238**, thereby improving the structural stability of the second frame **24**.

(28) Specifically, in this embodiment, the first vibration system **22** further includes a first skeleton **223**. The first skeleton **223** includes a skeleton body **2231** in the shape of an annulus and used as the first vibration portion **2213**, and a skeleton fixing portion **2232** bent downwardly and extended from an outer periphery of the skeleton body **2231**.

(29) Specifically, in this embodiment, the first diaphragm **221** includes a first folded ring **2211** in the shape of an annulus, a second folded ring **2212** in the shape of an annulus and spaced apart from the first folded ring **2211** and arranged on the inner side of the first folded ring **2211**, and a first vibration portion **2213** bent and extent from the inner periphery of the first folded ring **2211** to be connected to the outer periphery of the second folded ring **2212**. The outer periphery of the first folded ring **2211** is fixed to the first frame **21**, and the inner periphery of the second folded ring **2212** is fixed to the side of the first sub-magnetic steel **232** away from the main magnetic steel **231**. The first voice coil **222** is fixed to the side of the first vibration portion **2213** close to the magnetic circuit system **23**. The top of the first diaphragm **221** is further provided with an annular first dome **2214**. The inner periphery of the second folded ring **2212** is sandwiched between the second frame **24** and the main magnetic steel **231**.

(30) Specifically, in this embodiment, the second diaphragm **251** includes a second vibration portion **2511**, a third folded ring **2512** in the shape of an annulus and extended outwardly from an outer periphery of the second vibration portion **2511**, and a second dome **2513** covered on the

second vibration portion **2511**. An outer periphery of the third folded ring **2512** is fixed to a side of the second frame **24** away from the first sub-magnetic steel **232**, and the second voice coil **252** is fixed to the second vibration portion **2511**.

(31) Compared with the prior art, the speaker device of the present application includes a casing having an accommodating space and formed by a top cover, an upper cover and a bottom cover; a sound-conducting channel formed in the casing, and a sounding driver accommodated in the accommodating space. The sounding driver is fixed to the casing and separates the accommodating space into a front sound cavity and a rear cavity. The sound-conducting channel connects the front sound cavity to the outside world, and the sound-conducting channel and the front sound cavity together form a front cavity. The sounding driver includes: a first frame, fixedly supported on the casing; a first vibration system, including a first diaphragm fixed at its outer periphery to the first frame and a first voice coil configured to drive the first diaphragm to vibrate to produce sounds; a magnetic circuit system, fixed to the first frame, in which a side of the magnetic circuit system close to the first vibration system is provided with a first magnetic gap and a second magnetic gap; the first magnetic gap is arranged around the second magnetic gap and spaced apart from each other; and the first voice coil is inserted and suspended within the first magnetic gap; a second frame, fixed to a top of the magnetic circuit system; a second vibration system, including a second diaphragm fixed at its outer periphery to a side of the second frame away from the magnetic circuit system, and a second voice coil configured to drive the first diaphragm to vibrate to produce sounds, in which the second voice coil is inserted and suspended within the second magnetic gap; and a conductive insert, extended from a bottom of the magnetic circuit system to the top of the magnetic circuit system and extended below the second diaphragm, and electrically connected to the second voice coil. One end of the second frame away from the magnetic circuit system is abutted against the casing and separates the front sound cavity into a first front sound cavity and a second front sound cavity. The upper cover of the casing, a side wall of the bottom cover, and the sounding driver together enclose the first front sound cavity. The upper cover of the casing and the sounding driver together enclose the second front sound cavity. The sound-conducting channel is in communication with the first front sound cavity. The second frame is provided with a first notch and a second notch, in which the first notch and the second notch are arranged through the second frame in a direction perpendicular to a vibration direction of the second diaphragm. The first notch is spaced opposite the second notch and the first notch is smaller than the second notch. The first notch and the second notch both connect the second front sound cavity to the first front sound cavity. The speaker device is provided with the second frame having two side notches in the treble vibration system, wherein the larger second notch is connected to the front sound cavity, so that the treble airflow comes out from the direction of being backed up against the sound-conducting channel and then converges with the front cavity, so as to lengthen the conduction channel of the treble airflow, thereby raising the treble frequency band of the speaker device, and improving the high-frequency sounds. The smaller first notch is provided squarely opposite to the sound-conducting channel, so that the speaker device can improve the drainage efficiency through the first notch, thereby improving the acoustic performance and usability of the speaker device in the water ingress environment.

(32) Described above are only some embodiments of the present application, and it should be noted herein that improvements may be made by those of ordinary skill in the art without departing from the inventive conception of the present application, but all of these fall within the protection scope of the present application.

Claims

1. A speaker device, comprising: a casing having an accommodating space and formed by a top cover, an upper cover and a bottom cover; a sound-conducting channel formed in the casing; and a

sounding driver accommodated in the accommodating space; wherein the sounding driver is fixed to the casing and separates the accommodating space into a front sound cavity and a rear cavity; the sound-conducting channel connects the front sound cavity to the outside world, and the sound-conducting channel and the front sound cavity together form a front cavity; the sounding driver comprises: a first frame, fixedly supported on the casing; a first vibration system, comprising a first diaphragm fixed at its outer periphery to the first frame and a first voice coil configured to drive the first diaphragm to vibrate to produce sounds; a magnetic circuit system, fixed to the first frame, wherein a side of the magnetic circuit system close to the first vibration system is provided with a first magnetic gap and a second magnetic gap; the first magnetic gap is arranged around the second magnetic gap and spaced apart from each other; and the first voice coil is inserted and suspended within the first magnetic gap; a second frame, fixed to a top of the magnetic circuit system; a second vibration system, comprising a second diaphragm fixed at its outer periphery to a side of the second frame away from the magnetic circuit system, and a second voice coil configured to drive the first diaphragm to vibrate to produce sounds; wherein the second voice coil is inserted and suspended within the second magnetic gap; and a conductive insert, extended from a bottom of the magnetic circuit system to the top of the magnetic circuit system and extended below the second diaphragm, and electrically connected to the second voice coil; wherein one end of the second frame away from the magnetic circuit system is abutted against the casing and separates the front sound cavity into a first front sound cavity and a second front sound cavity, wherein the upper cover of the casing, a side wall of the bottom cover, and the sounding driver together enclose the first front sound cavity; the upper cover of the casing and the sounding driver together enclose the second front sound cavity; the sound-conducting channel is in communication with the first front sound cavity; the second frame is provided with a first notch and a second notch, wherein the first notch and the second notch are arranged through the second frame in a direction perpendicular to a vibration direction of the second diaphragm; the first notch is spaced opposite the second notch and the first notch is smaller than the second notch; the first notch and the second notch both connect the second front sound cavity to the first front sound cavity; the first notch is located on a side of the second frame close to the sound-conducting channel, and the second notch is located on a side of the second frame away from the sound-conducting channel.

2. The speaker device of claim 1, wherein the first notch and the second notch are both formed by a downward depression of one end of the second frame away from the magnetic circuit system; a depth of the first notch is less than a depth of the second notch, and a width of the first notch is less than a width of the second notch.

3. The speaker device of claim 1, wherein an end of the conductive insert away from the second diaphragm is arranged through the casing and at least partially exposed outside the casing.

4. The speaker device of claim 3, wherein the magnetic circuit system comprises an upper splint in the shape of an annulus, a lower splint, a main magnetic steel, a first sub-magnetic steel, a pole core, and a second sub-magnetic steel; wherein the upper splint is fixedly stacked on the first sub-magnetic steel and fixedly connected to the first frame; the main magnetic steel is in the shape of an annulus and fixedly stacked on the lower splint; the first sub-magnetic steel is fixedly stacked on the lower splint and arranged around the main magnetic steel, and the main magnetic steel and the first sub-magnetic steel are spaced apart to form the first magnetic gap; the pole core comprises a core body in the shape of an annulus and fixedly fixed to the main magnetic steel and a core extension in the shape of an annulus and bent and extended from an inner periphery of the core body along a direction away from the lower splint, wherein the core extension is arranged around the conductive insert; the second sub-magnetic steel is fixedly stacked on a side of the core body close to the first vibration system, the second sub-magnetic steel is arranged around the core extension and spaced apart from the core extension to form the second magnetic gap.

5. The speaker device of claim 4, wherein the magnetic circuit system further comprises a secondary pole core fixedly stacked on a side of the second sub-magnetic steel close to the first

vibration system, wherein the secondary pole core is in the shape of an annulus and arranged around the conductive insert, and the second frame is connected to an outer periphery of the secondary pole core.

6. The speaker device of claim 4, wherein the first vibration system further comprises a first skeleton, comprising a skeleton body in the shape of an annulus and used as the first vibration portion and a skeleton fixing portion bent downwardly and extended from an outer periphery of the skeleton body.

7. The speaker device of claim 1, wherein the first diaphragm comprises a first folded ring in the shape of an annulus, a second folded ring in the shape of an annulus, which is spaced apart from the first folded ring and arranged on an inner side of the first folded ring, and a first vibration portion in the shape of an annulus, which is bent and extended from an inner periphery of the first folded ring to be connected to the outer periphery of the second folded ring; an outer periphery of the first folded ring is fixed to the first skeleton; an inner periphery of the second folded ring being fixed to the second skeleton body; an inner periphery of the second folded ring is fixed to a side of the first sub-magnetic steel away from the main magnetic steel; and the first voice coil is fixed to a side of the first vibration portion close to the magnetic circuit system.

8. The speaker device of claim 7, wherein the inner periphery of the second folded ring is fixedly sandwiched between the second frame and the main magnetic steel.

9. The speaker device of claim 1, wherein the second diaphragm comprises a second vibration portion, a third folded ring in the shape of an annulus and extended outwardly from an outer periphery of the second vibration portion, and a second dome covered on the second vibration portion, wherein an outer periphery of the third folded ring is fixed to a side of the second frame away from the first sub-magnetic steel, and the second voice coil is fixed to the second vibration portion.
