

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415630
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Yoshida; Jun et al.

Detection device

Abstract

A detection device includes a generation unit that generates feature values representing features of a plurality of pieces of orbit data, on the basis of the orbit data representing a state of each flying object included in a flying object group, an inference unit that acquires a value corresponding to a state of the flying object group on the basis of the feature values generated by the generation unit, and a detection unit that detects an abnormality having occurred in the flying object group on the basis of the value corresponding to the state of the flying object group acquired by the inference unit.

Inventors: Yoshida; Jun (Tokyo, JP), Taya; Katsuaki (Tokyo, JP), Sano; Taichiro (Tokyo, JP)

Applicant: NEC Corporation (Tokyo, JP)

Family ID: 1000008821022

Assignee: NEC CORPORATION (Tokyo, JP)

Appl. No.: 18/526783

Filed: December 01, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240190591 A1	Jun. 13, 2024

Foreign Application Priority Data

JP	2022-195753	Dec. 07, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: B64G3/00 (20060101)

U.S. Cl.:

CPC B64G3/00 (20130101);

Field of Classification Search

CPC: B64G (3/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2011/0227786	12/2010	Ono	342/357.23	G01S 19/20
2012/0137367	12/2011	Dupont	726/25	G06F 21/00
2013/0305357	12/2012	Ayyagari	726/22	H04L 41/069
2015/0175028	12/2014	Fukui	701/22	B61B 13/00
2020/0326190	12/2019	Miyao	N/A	G01C 21/28
2021/0263164	12/2020	Gunning	N/A	G01S 19/07
2023/0003907	12/2022	Grayson	N/A	G01S 19/423
2023/0130388	12/2022	Reid	342/357.44	G01S 19/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2021-126910	12/2020	JP	N/A

Primary Examiner: Lonsberry; Hunter B

Assistant Examiner: Coduroglu; Jalal C

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

INCORPORATION BY REFERENCE

(1) The present invention is based upon and claims the benefit of priority from Japanese patent application No. 2022-195753, filed on Dec. 7, 2022, the disclosure of which is incorporated herein in its entirety by reference.

TECHNICAL FIELD

(2) The present invention relates to a detection device, a detection method, and a storage medium.

BACKGROUND ART

(3) Art to be used for detecting an abnormality having occurred in a flying object has been known.

(4) For example, Patent Literature 1 describes a flying device having an abnormality detection unit. According to Patent Literature 1, the abnormality detection unit monitors a detection result of a sensor unit, the state of a battery, and an operating state of a lift generation unit to thereby determine whether or not the flying device is in an abnormal state. Patent Literature 1: JP 2021-126910 A

SUMMARY

- (5) In the case of operating a service utilizing a plurality of flying objects such as mega-constellations in which a plurality of satellites constitute a satellite group, it is necessary to take coordinated operations among the flying objects constituting the flying object group. When operating a service utilizing such a plurality of flying objects, it is desirable to find an abnormality such as uncoordinated operations in the entire flying objects. However, the art described in Patent Literature 1 detects an abnormal state while focusing on a single flying object. Therefore, it is difficult to perform appropriate monitoring, and further, the cost of monitoring is high. This causes a problem that it is difficult to detect an abnormality such as uncoordinated operations occurred in a flying object group including a plurality of flying objects.
- (6) In view of the above, an example of an object of the present invention is to provide a detection device, a detection method, and a storage medium capable of solving the above-described problem.
- (7) In order to achieve the object, a detection device according to one aspect of the present disclosure is configured to include at least one memory configured to store instructions and at least one processor configured to execute instructions to generate feature values representing features of a plurality of pieces of orbit data, on the basis of the orbit data representing a state of each of flying objects included in a flying object group; acquire a value corresponding to a state of the flying object group on the basis of the generated feature values; and detect an abnormality having occurred in the flying object group on the basis of the acquired value corresponding to the state of the flying object group.
- (8) Further, a detection method according to another aspect of the present disclosure is configured to include, by an information processing device, generating feature values representing features of a plurality of pieces of orbit data, on the basis of the orbit data representing a state of each of flying objects included in a flying object group; acquiring a value corresponding to a state of the flying object group on the basis of the generated feature values; and detecting an abnormality having occurred in the flying object group on the basis of the acquired value corresponding to the state of the flying object group.
- (9) Further, a storage medium according to another aspect of the present disclosure is a non-transitory computer-readable medium storing thereon a program comprising instructions for causing an information processing device to execute processing to: generate feature values representing features of a plurality of pieces of orbit data, on the basis of the orbit data representing a state of each of flying objects included in a flying object group; acquire a value corresponding to a state of the flying object group on the basis of the generated feature values; and detect an abnormality having occurred in the flying object group on the basis of the acquired value corresponding to the state of the flying object group.
- (10) Further, a learning device according to another aspect of the present disclosure is configured to include at least one memory configured to store instructions and at least one processor configured to execute instructions to generate feature values representing features of a plurality of pieces of orbit data, on the basis of the orbit data representing a state of each of flying objects included in a flying object group; and on the basis of the generated feature values, train a model so as to output a value corresponding to a state of the flying object group in response to an input of the feature values.
- (11) With the configurations described above, the problem described above can be solved.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a diagram for explaining the outline of the present disclosure.
- (2) FIG. 2 is a block diagram illustrating an example of a configuration of a detection device.
- (3) FIG. 3 illustrates an example of orbit data information.

- (4) FIG. 4 illustrates an example of formatted data information.
- (5) FIG. 5 illustrates an example of feature value information.
- (6) FIG. 6 illustrates an example of inference result information.
- (7) FIG. 7 is a flowchart illustrating an example of operation of a detection device at the time of learning.
- (8) FIG. 8 is a flowchart illustrating an example of operation of a detection device at the time of detecting abnormality.
- (9) FIG. 9 illustrates an example of a hardware configuration of a detection device according to a second example embodiment of the present disclosure.
- (10) FIG. 10 is a block diagram illustrating an example of a configuration of a detection device.
- (11) FIG. 11 is a block diagram illustrating an example of a configuration of a learning device.

EXAMPLE EMBODIMENTS

First Example Embodiment

(12) A first example embodiment of the present disclosure will be described with reference to FIGS. 1 to 8. FIG. 1 is a diagram for explaining the outline of the present disclosure. FIG. 2 is a block diagram illustrating an example of a configuration of a detection device **100**. FIG. 3 illustrates an example of orbit data information **141**. FIG. 4 illustrates an example of formatted data information **142**. FIG. 5 illustrates an example of feature value information **143**. FIG. 6 illustrates an example of inference result information **145**. FIGS. 7 and 8 are flowcharts illustrating an example of operation of the detection device **100**.

(13) A first example embodiment of the present disclosure describes a detection device **100** that detects an abnormality such as uncoordinated operations occurred in a flying object group including a plurality of flying objects as illustrated in FIG. 1. As described below, the detection device **100** acquires orbit data representing the state of each flying object included in the flying object group, for each flying object. Moreover, the detection device **100** generates a plurality of feature values on the basis of orbit data of each flying object included in the flying object group. Then, the detection device **100** learns a model by using the generated feature values. For example, the detection device **100** learns a model by training a deep neural network (DNN) with use of the feature values generated based on the orbit data of the respective flying objects at the normal time having no abnormality.

(14) The detection device **100** also detects an abnormality using the learned model. For example, when the detection device **100** acquires, from each flying object, orbit data in which whether it is in a normal state or an abnormal state is unknown, the detection device **100** inputs the feature values generated based on the unknown orbit data to thereby acquire an output from the model according to the state of the flying object group. Then, the detection device **100** detects an abnormality based on the acquired output. For example, the detection device **100** can detect an abnormality by comparing an output obtained when inputting a feature value based on the orbit data at the normal time into the model with an output obtained when inputting a feature value based on unknown orbit data into the model. The detection device **100** may output the detection result to an external device or the like.

(15) Note that in the present embodiment, a flying object represents an object flying on a predetermined orbit such as a satellite. A flying object is not limited to the aforementioned example. For example, a flying object may be an unmanned aircraft such as a drone or another flying vehicle. A flying object group includes a plurality of flying objects. For example, a flying object group includes flying objects in units of several hundreds to several tens of thousands. The flying objects included in a flying object group may be in any number other than that described above as an example.

(16) The detection device **100** is an information processing device that detects an abnormality such as uncoordinated operations occurred in a flying object group. For example, the detection device **100** acquires orbit data representing the state of each flying object included in a flying object

group, from the flying object and other external devices. Then, on the basis of the acquired orbit data of each flying object, the detection device **100** checks whether or not an abnormal state that is a state different from a normal state has occurred in the flying object group.

(17) FIG. 2 illustrates an example of a configuration of the detection device **100**. Referring to FIG. 2, the detection device **100** includes, for example, an operation input unit **110**, a screen display unit **120**, a communication I/F unit **130**, a storage unit **140**, and an arithmetic processing unit **150**, as main constituent elements.

(18) FIG. 2 illustrates the case of implementing the function of the detection device **100** by using one information processing device, as an example. However, the detection device **100** may be implemented by using a plurality of information processing devices such as implemented on the cloud, for example. For example, the detection device **100** may be configured of a learning device having a configuration for learning a model and a detection device that detects an abnormality by using the learned model among the constituent elements described with reference to FIG. 2. The detection device **100** may not include part of the above-mentioned constituent elements such as not including the operation input unit **110** or the screen display unit **120**, or may include a constituent element other than those described above.

(19) The operation input unit **110** is configured of operation input devices such as a keyboard and a mouse. The operation input unit **110** detects operation by an operator who operates the detection device **100**, and outputs it to the arithmetic processing unit **150**.

(20) The screen display unit **120** is a screen display device such as a liquid crystal display (LCD). The screen display unit **120** can display, on the screen, various types of information stored in the storage unit **140**, in response to an instruction from the arithmetic processing unit **150**.

(21) The communication I/F unit **130** is configured of a data communication circuit. The communication I/F unit **130** performs data communication with an external device connected over a communication network.

(22) The storage unit **140** is a storage device such as a hard disk or a memory. The storage unit **140** stores therein processing information and a program **146** required for various types of processing performed in the arithmetic processing unit **150**. The program **146** is read and executed by the arithmetic processing unit **150** to thereby implement various processing units. The program **146** is read in advance from an external device or a storage medium via a data input/output function of the communication I/F unit **130** and the like, and is stored in the storage unit **140**. The main information stored in the storage unit **140** includes, for example, orbit data information **141**, formatted data information **142**, feature value information **143**, learned model information **144**, inference result information **145**, and the like.

(23) The orbit data information **141** includes orbit data representing the state of each flying object included in the flying object group. For example, the orbit data information **141** is acquired in advance by using a method of acquiring it from an external device or the flying object via the communication I/F unit **130**, inputting it by using the operation input unit **110**, or the like, and is stored in the storage unit **140**.

(24) FIG. 3 illustrates an example of the orbit data information **141**. Referring to FIG. 3, in the orbit data information **141**, time information and a plurality of pieces of orbit data are associated with each other. Here, the time information shows the time when the associated orbit data is acquired by the flying object or other external devices. For example, on the first row of FIG. 3, the time information shows that orbit data is acquired at “2018-02-12 1:32:44”. The orbit data includes data showing the state of each flying object. For example, the orbit data may include location information such as coordinate values indicating the location of the flying object, flying condition information such as moving speed and acceleration of the flying object, and the like. The orbit data may also include information representing orbit elements such as an orbit inclination angle, longitude of ascending node, eccentricity, argument of perigee, mean anomaly, and mean motion, and other types of information representing the state of the flying object.

(25) Note that the orbit data information **141** may include information in which time information and orbit data are associated with each other for each flying object in the flying object group. For example, in the example illustrated in FIG. 3, in the orbit data information **141**, a table in which time information and orbit data are associated with each other is prepared for each flying object. Depending on the type of a flying object such as the case where the flying object is a satellite, the time at which the orbit data is acquired may not be uniform. In other words, orbit data may be acquired at different timing for each flying object. Therefore, even in the orbit data information **141**, the time indicated by the time information may be different for each flying object.

(26) The formatted data information **142** includes information generated by formatting the orbit data information **141** into uniform data. For example, the formatted data information **142** is updated in response to execution of a formatting process or the like. The formatting process is a process of sorting the respective pieces of data included in the orbit data information **141** according to the time, by the data formatting unit **152** to be described below.

(27) FIG. 4 illustrates an example of the formatted data information **142**. Referring to FIG. 4, in the formatted data information **142**, time information and pieces of orbit data for each flying object included in the orbit data information **141** are associated with each other. As illustrated in FIG. 4 as an example, the formatted data information **142** includes orbit data of each predetermined time such as every hours, for example.

(28) The feature value information **143** includes at least part of the feature values representing the features of a plurality of pieces of orbit data included in the formatted data information **142**. For example, the feature value information **143** is updated in response to extraction of at least part of a plurality of feature values generated based on the formatted data information **142** by a dimension reduction unit **154** to be described below.

(29) FIG. 5 illustrates an example of the feature value information **143**. Referring to FIG. 5, in the feature value information **143**, a moving window and a plurality of feature values are associated with each other. Here, the moving window shows a main range for generating feature values. For example, “2018-02-12 1:00-2.59” on the first row of FIG. 5 indicates that related feature values are generated based on the orbit data from 1:00 to 2:59 on Feb. 12, 2018 in the formatted data information **142**. Further, the feature values are values representing the feature of the entire orbit data within the range shown by the moving window or at least part thereof among the orbit data of each flying object constituting the flying object group. For example, the feature value information **143** includes at least partial feature values of the feature values generated by the feature value generation unit **153**.

(30) Here, feature values may include statistical values that can be generated from a plurality of pieces of orbit data such as a maximum value, a minimum value, a variance, an average, a mean value, a skewness, a kurtosis, a rate of change, a difference, a peak value, and the like, for example. The feature values may include a value obtained by performing a transform process such as Fourier transform on the generated statistical value or the like, an absolute total value of the statistical values, a value obtained by applying a predetermined process to a statistical value such as covariance. Feature values may include a value according to the past statistical values generated from past related orbit data, tendency fluctuation, or the like. As described above, feature values may include statistical values or values according to the statistical values, for example. Feature values may include values representing the feature of orbit data other than those illustrated above.

(31) The learned model information **144** includes information showing a model trained by using the feature values included in the feature value information **143** so as to output a value corresponding to the state of the flying object group. In other words, the learned model information **144** includes information showing a model trained so as to output a value that can be used for detecting an abnormality having occurred in the flying object group. For example, the learned model information **144** includes information showing a model trained by using feature values based on the orbit data at the normal time in which no abnormality occurs. As an example, the learned model

information **144** may include values of various types of parameters included in the DNN. For example, the learned model information **144** is updated corresponding to execution of training based on the feature values included in the feature value information **143** by a learning unit **155** to be described below.

(32) The inference result information **145** includes an abnormal value that is a value corresponding to the state of the flying object group, output by the model in response to input of the feature values to the learned model. In other words, the inference result information **145** includes an abnormal value that is a value that can be used for detecting an abnormality having occurred in the flying object group. The inference result information **145** may include time-series abnormal values corresponding to the feature values for each moving window. For example, the inference result information **145** is updated in response to input of the feature values by an inference unit **156**, to be described below, to the model shown by the learned model information **144** and acquisition of an abnormal value that is an output value.

(33) The arithmetic processing unit **150** includes an arithmetic unit such as a central processing unit (CPU) and the peripheral circuits thereof. The arithmetic processing unit **150** reads, from the storage unit **140**, and executes the program **146** to implement various processing units through cooperation between the hardware and the program **146**. Main processing units to be implemented by the arithmetic processing unit **150** include, for example, the data acquisition unit **151**, the data formatting unit **152**, the feature value generation unit **153**, the dimension reduction unit **154**, the learning unit **155**, the inference unit **156**, a comparison unit **157**, an output unit **158**, and the like.

(34) Note that the arithmetic processing unit **150** may include a Graphic Processing Unit (GPU), a Digital Signal Processor (DSP), an Micro Processing Unit (MPU), a Floating point number Processing Unit (FPU), a Physics Processing Unit (PPU), a Tensor Processing Unit (TPU), a quantum processor, a microcontroller, or a combination thereof, instead of the CPU.

(35) The data acquisition unit **151** acquires orbit data and the acquisition time of the orbit data from flying objects and other external devices. The data acquisition unit **151** may acquire orbit data and the like together with information indicating that it is confirmed that the state of the flying object group is normal, the state of the flying object group is unknown, or the like. Further, the data acquisition unit **151** stores the acquired orbit data and the like in the storage unit **140** as the orbit data information **141**.

(36) For example, the data acquisition unit **151** can acquire orbit data at the normal time in which no abnormality has occurred, as data for learning by the learning unit **155** or the like. The data acquisition unit **151** can also acquire orbit data in a state where it is unknown whether or not an abnormality has occurred, and the like.

(37) The data formatting unit **152** performs a formatting process that is a process of sorting pieces of data included in the orbit data information **141** according to the time. For example, the data formatting unit **152** can perform a formatting process at any timing such as performing the process at predetermined intervals. Further, the data formatting unit **152** stores the result of the formatting process in the storage unit **140** as the formatted data information **142**.

(38) As described above, the time of acquiring orbit data by each flying object may be nonuniform. For example, in the example illustrated in FIG. 3, the time at which orbit data of a flying object is acquired is “1:32:44”, and the next time is “4:13:00”. There is about two hours and forty minutes interval. Therefore, the data formatting unit **152** sorts the orbit data at predetermined time such as “1:00:00”, “2:00:00”, “3:00:00”, and the like. For example, in the example illustrated in FIG. 3, as orbit data of a flying object related to “1:00:00”, the data formatting unit **152** adopts orbit data acquired at “1:32:44”.

(39) There is a case where orbit data cannot be acquired within a predetermined time by the flying objects. For example, in the example illustrated in FIG. 3, no orbit data is acquired related to “2:00:00” and “3:00:00”. In the case where such missing values exist, the data formatting unit **152** can fill the missing values by using an interpolation technique such as linear interpolation. The data

formatting unit **152** may fill the missing values by using any interpolation technique. Note that the data formatting unit **152** may be configured to handle the missing values just as missing values. (40) Further, there is a case where flying objects or the like acquire a plurality of pieces of orbit data in a predetermined period of time such as the case where a plurality of pieces of orbit data are acquired between “1:00:00” and “2:00:00”. In that case, the data formatting unit **154** can calculate any statistical values such as calculating an average value or a mean value of the pieces of orbit data and adopt the calculated statistical value as formatted orbit data. The data formatting unit **152** may adopt orbit data selected by any means instead of calculating statistical values.

(41) For example, as described above, by filling missing values or processing overlapped values, the data formatting unit **152** sorts the pieces of data included in the orbit data information **141** according to the predetermined time. Since the data formatting unit **152** performs the formatting process, for example, it is possible to combine the tables for the respective flying objects into one table as illustrated in FIG. 4.

(42) The feature value generation unit **153** generates feature values representing the features of a plurality of pieces of orbit data included in the formatted data information **142**. For example, the feature value generation unit **153** extracts orbit data from the formatted data information **142** by using a moving window in predetermined time unit such as one hour or two hours. Then, the feature value generation unit **153** generates feature values on the basis of the extracted orbit data. The feature value generation unit **153** may generate time-series feature values by generating feature values based on the orbit data extracted while shifting the moving window at predetermined time intervals such as every hour.

(43) For example, as feature values of the extracted orbit data, the feature value generation unit **153** generates at least part of the statistical values that can be generated from pieces of orbit data such as a maximum value, a minimum value, a variance, an average, a mean value, a skewness, a kurtosis, a rate of change, a difference, a peak value, and the like of the extracted orbit data. Moreover, the feature value generation unit **153** can generate a value obtained by applying a predetermined process to a generated statistical value such as Fourier transform. The feature value generation unit **153** may generate statistical values from the extracted orbit data and generate statistical values from past related orbit data. Furthermore, when generating feature values, the feature value generation unit **153** may generate feature values representing the feature of the whole of the extracted orbit data and also generate feature values of part of the extracted orbit data. For example, the feature value generation unit **153** can generate a statistical value with respect to the whole of the extracted orbit data. Further, the feature value generation unit **153** can divide the extracted orbit data into a plurality of categories based on a predetermined criteria, and generate a statistical value for each category. Note that the categorizing method is not particularly limited in the present disclosure.

(44) For example, by the method as described above, the feature value generation unit **153** can extract a plurality of feature values based on the orbit data extracted using a moving window. For example, the feature value generation unit **153** may generate feature values in 10 to 100 units based on the orbit data extracted using a moving window. Note that the feature value generation unit **153** may generate feature values representing the feature of the extracted orbit data by means of a method other than that described above.

(45) The dimension reduction unit **154** performs a dimension reduction process of extracting at least part of the feature values generated by the feature value generation unit **153**. Moreover, the dimension reduction unit **154** can store the extracted feature value in the storage unit **140** as the feature value information **143**.

(46) For example, the dimension reduction unit **154** can perform a dimension reduction process by using a technique such as principal component analysis (PCA), T-distributed Stochastic Neighbor Embedding (t-SNE), Uniform Manifold Approximation and Projection (UMAP), or the like. The dimension reduction unit **154** may perform the dimension reduction process by using a method

other than that illustrated above as an example.

(47) The learning unit **155** trains the DNN or the like by performing learning using the feature values included in the feature value information **143**. For example, the learning unit **155** performs learning using feature values generated based on orbit data at the normal time in which it is confirmed that no abnormality has occurred. Further, the learning unit **155** stores a model generated as a result of learning in the storage unit **140** as the learned model information **144**.

(48) For example, the learning unit **155** trains the DNN or the like by using feature values in unit of a moving window such that an abnormal value that is a value corresponding to a state of the flying object group is output in response to an input of the feature value in unit of a moving window. The learning unit **155** may train the DNN or the like such that an abnormal value is output in response to an input of the feature values related to a plurality of moving windows.

(49) The inference unit **156** acquires an abnormal value that is a value corresponding to a state of the flying object group on the basis of the feature values. For example, the inference unit **156** acquires an abnormal value that is an output from a model, in response to an input of a feature value in which a dimension reduction process has been performed by the dimension reduction unit **154** on the model shown by the learned model information **144**. The inference unit **156** may acquire time-series abnormal values in response to inputs input of feature values related to respective moving windows. Further, the inference unit **156** stores the acquired abnormal value in the storage unit **140** as the inference result information **145**.

(50) In the case of the present disclosure, the inference unit **156** acquires an abnormal value from a feature value generated based on the orbit data in an unknown state that is subject to abnormality detection, and also acquires an abnormal value from a feature value for comparison. For example, the inference unit **156** inputs a feature value generated based on the orbit data in which whether or not there is an abnormality is unknown, to the model, to thereby acquire an abnormal value in the unknown state. Further, the inference unit **156** inputs, to the model, a feature value generated based on the orbit data at the normal time in which no abnormality has occurred for comparison, to thereby acquire an abnormal value in the normal state. The inference unit **156** may acquire an abnormal value based on the feature value generated based on the orbit data in the abnormal time for comparison.

(51) Note that the orbit data from which a feature value for comparison is generated may be one acquired at the same timing as unknown data, or one acquired at different timing. For example, the orbit data from which a feature value for comparison is generated is orbit data acquired in the past from the same flying object group as the flying object group that is subject to abnormality detection. As an example, the orbit data from which a feature value for comparison is generated may be orbit data in a period that it is confirmed to be normal, acquired from the same flying object group as the flying object group that is subject to abnormality detection. Further, the orbit data from which a feature value for comparison is generated may be data acquired from a flying object group different from the flying object group that is subject to abnormality detection. For example, the orbit data from which a feature value for comparison is generated may be orbit data acquired from a different flying object group determined to fly as similar to the flying object group that is subject to abnormality detection.

(52) The comparison unit **157** functions as a detection unit that detects an abnormality having occurred in the flying object group on the basis of the abnormal value acquired by the inference unit **156**. For example, the comparison unit **157** compares the abnormal value acquired by the inference unit **156** to detect an abnormality having occurred in the flying object group that is subject to detection. The comparison unit **157** may compare the abnormal value itself, or compare a statistical value calculated from time-series abnormal values.

(53) For example, the comparison unit **157** can calculate a distance between an abnormal value in an unknown state and an abnormal value in a normal state, and determine the abnormality based on whether or not the calculated distance is equal to or larger than a predetermined threshold. For

example, when the calculated distance is equal to or larger than the threshold, the comparison unit **157** can determine that an abnormality has occurred in the flying object group. Note that the distance may be a typical one such as Euclidean distance or Mahalanobis distance.

(54) Further, the comparison unit **157** may determine whether or not an abnormality has occurred by checking whether or not the distance between statistical values or the like calculated from time-series abnormal values is equal to or larger than a predetermined threshold. For example, as illustrated in FIG. **6** as an example, the inference unit **156** can acquire time-series abnormal values in an unknown state and time-series abnormal values in a normal state for comparison. Therefore, the comparison unit **157** may calculate statistical values such as an average, a standard deviation, a minimum value, and a maximum value for the respective time-series abnormal values and compare the calculated statistical values to determine whether or not an abnormality has occurred. For example, when the distance between the calculated statistical values is equal to or larger than a threshold, the comparison unit **157** can determine that an abnormality has occurred in the flying object group.

(55) The output unit **158** outputs a result of comparison by the comparison unit **157**, and the like. For example, the output unit **158** transmits a comparison result to an external device via the communication I/F unit **130**, or displays it on the screen display unit **120**. The output unit **158** may be configured to output the fact that an abnormality has occurred when the comparison unit **157** determines that an abnormality has occurred.

(56) Note that the information to be output by the output unit **158** is not limited to those illustrated above. For example, the output unit **158** may be configured to output time-series inference result information **145** as illustrated in FIG. **6** and the like, together with a comparison result or the like.

(57) An example of the configuration of the detection device **100** is as described above. Next, an example of operation of the detection device **100** will be described with reference to FIGS. **7** and **8**.

(58) FIG. **7** is a flowchart illustrating an example of operation of the detection device **100** at the time of learning a model. Referring to FIG. **7**, the data acquisition unit **151** acquires orbit data and information such as acquisition time of the orbit data from flying objects and other external devices (step **S101**). For example, the data acquisition unit **151** acquires orbit data at the normal time in which no abnormality has occurred, as data for learning.

(59) The data formatting unit **152** performs a formatting process that is a process of sorting data according to the time, on the pieces of data acquired by the data acquisition unit **151** (step **S102**). For example, the data formatting unit **152** may fill the missing values or process the overlapping values.

(60) The feature value generation unit **153** generates feature values representing the features of the orbit data included in the formatted data information **142** (step **S103**). For example, the feature value generation unit **153** extracts orbit data from the formatted data information **142** by using a moving window in a predetermined time unit such as one hour or two hours. Then, the feature value generation unit **153** generates feature values based on the extracted orbit data. The feature value generation unit **153** may generate time-series feature values by generating feature values based on the orbit data extracted while shifting the moving window at predetermined time intervals such as every hour.

(61) The dimension reduction unit **154** performs a dimension reduction process of extracting at least part of the feature values generated by the feature value generation unit **153** (step **S104**). The dimension reduction unit **154** may perform the dimension reduction process by using a technique such as main component analysis.

(62) The learning unit **155** performs learning using the feature values on which the dimension reduction process has been performed by the dimension reduction unit **154** to train the DNN or the like (step **S105**). For example, the learning unit **155** trains the DNN or the like so as to output an abnormal value that can be used for detecting an abnormality having occurred in the flying object group in response to an input of a feature value in unit of a moving window.

(63) The example of operation at the time of learning is as described above. Next, an example of operation at the time of detecting an abnormality will be described with reference to FIG. 8.

(64) FIG. 8 is a flowchart illustrating an example of operation of the detection device **100** at the time of detecting an abnormality. Referring to FIG. 8, the data acquisition unit **151** acquires orbit data and information such as acquisition time of the orbit data from flying objects and other external devices (step **S201**). For example, the data acquisition unit **151** acquires orbit data in an unknown state. Besides the orbit data in an unknown state, the data acquisition unit **151** may acquire orbit data at the normal time in which no abnormality has occurred, or the like.

(65) The data formatting unit **152** performs a formatting process that is a process of sorting data according to the time, on the pieces of data acquired by the data acquisition unit **151** (step **S202**). For example, the data formatting unit **152** may fill the missing values or process the overlapping values.

(66) The feature value generation unit **153** generates feature values representing the features of the orbit data included in the formatted data information **142** (step **S203**). For example, the feature value generation unit **153** extracts orbit data from the formatted data information **142** by using a moving window in a predetermined time unit such as one hour or two hours. Then, the feature value generation unit **153** generates feature values based on the extracted orbit data. The feature value generation unit **153** may generate time-series feature values by generating feature values based on the orbit data extracted while shifting the moving window at predetermined time intervals such as every hour.

(67) The dimension reduction unit **154** performs a dimension reduction process of extracting at least part of the feature values generated by the feature value generation unit **153** (step **S204**). The dimension reduction unit **154** may perform the dimension reduction process by using a technique such as main component analysis.

(68) The inference unit **156** acquires an abnormal value that is an output from a model, in response to an input of a feature value in which a dimension reduction process has been performed by the dimension reduction unit **154** on the model shown by the learned model information **144** (step **S205**). The inference unit **156** may acquire time-series abnormal values in response to inputs of feature values related to respective moving windows. For example, the inference unit **156** acquires an abnormal value from a feature value generated based on the orbit data in an unknown state that is subject to abnormality detection, and also acquires an abnormal value from a feature value for comparison.

(69) The comparison unit **157** compares the abnormal values acquired by the inference unit **156** to thereby detect an abnormality having occurred in the flying object group that is subject to detection (step **S206**). For example, the comparison unit **157** may calculate a distance between an abnormal value in an unknown state and an abnormal value in a normal state, and determine abnormality based on whether or not the calculated distance is equal to or larger than a predetermined threshold. The comparison unit **157** may compare the abnormal values themselves, or compare statistical values calculated from the time-series abnormal values or the like.

(70) Note that when the comparison unit **157** detects an abnormality, the output unit **158** may output the fact that an abnormality is detected.

(71) An example of operation of the detection device **100** at the time of detecting an abnormality is as described above.

(72) As described above, the detection device **100** includes the feature value generation unit **153** and the learning unit **155**. With this configuration, the learning unit **155** can train the model of outputting an abnormal value that is a value capable of being used for detecting an abnormality having occurred in the flying object group, by using the feature values based on the orbit data by the feature value generation unit **153**. As a result, by using the trained model, it is possible to easily detect an abnormality having occurred in the flying object group.

(73) Further, the detection device **100** includes the dimension reduction unit **154**. With this

configuration, the learning unit **155** can learn the model by using part of the feature values generated by the feature value generation unit **153** based on the orbit data. Thereby, since it is possible to learn the model by using a result of performing dimension reduction after generating a large amount of feature values, it is possible to perform learning by using feature values more suitable for learning of the model.

(74) Further, the detection device **100** includes the data formatting unit **152**. As described above, orbit data may be acquired at different timing for each flying object. By generating feature values by using a result of the formatting process performed by the data formatting unit **152**, even when there are variations in the acquisition timing of the orbit data, it is possible to generate feature values more appropriately.

(75) Further, the detection device **100** includes the inference unit **156** and the comparison unit **157**. With this configuration, by comparing the abnormal values acquired by the inference unit **156**, the comparison unit **157** can detect an abnormality having occurred in the flying object group that is subject to detection. That is, according to the configuration described above, it is possible to easily detect an abnormality by using the model learned by the learning unit **155**.

(76) Note that the present disclosure describes an example of the configuration of the detection device **100**. However, the configuration of the detection device **100** is not limited to the case illustrated in the present disclosure. For example, the detection device **100** may not include the data formatting unit **152**. Moreover, the detection device **100** may not include the dimension reduction unit **154**. For example, as described above, the detection device **100** may be configured of part of the configuration described in the present disclosure.

(77) Further, the present disclosure illustrates, as an example, the case where the detection device **100** detects an abnormality based on the result of comparison by the comparison unit **157**. However, the detection device **100** may be configured to determine whether or not there is an abnormality by, for example, checking whether or not the abnormal value acquired by the inference unit **156** is equal to or larger than a predetermined threshold, or the like. For example, as described above, the detection device **100** may detect an abnormality based on the feature values by a method other than that illustrated as an example in the present disclosure.

Second Example Embodiment

(78) Next, a second example embodiment of the present disclosure will be described with reference to FIGS. **9** to **11**. FIG. **9** is a diagram illustrating an example of a hardware configuration of a detection device **200**. FIG. **10** is a block diagram illustrating an example of a configuration of the detection device **200**. FIG. **11** is a block diagram illustrating an example of a configuration of a learning device **300**.

(79) The second example embodiment of the present disclosure describes an example of a configuration of the detection device **200** that is an information processing device that detects an abnormality having occurred in a flying object group, on the basis of orbit data representing a state of each flying object included in the flying object group. The second example embodiment also describes an example of a configuration of the learning device **300** that performs training of a model on the basis of orbit data representing a state of each flying object included in the flying object group. FIG. **9** illustrates an example of a hardware configuration of the detection device **200**. Referring to FIG. **9**, the detection device **200** has a hardware configuration as described below, as an example. Central Processing Unit (CPU) **201** (arithmetic device) Read Only Memory (ROM) **202** (storage device) Random Access Memory (RAM) **203** (storage device) Program group **204** to be loaded to the RAM **203** Storage device **205** storing therein the program group **204** Drive **206** that performs reading and writing on a storage medium **210** outside the information processing device Communication interface **207** connecting to a communication network **211** outside the information processing device Input/output interface **208** for performing input/output of data Bus **209** connecting the respective constituent elements

(80) Further, the detection device **200** can realize functions as a generation unit **221**, an inference

unit **222**, and a detection unit **223** illustrated in FIG. **10** through acquisition of the program group **204** by the CPU **201** and execution of the program by the CPU **201**. Note that the program group **204** is stored in the storage device **205** or the ROM **202** in advance for example, and is loaded to the RAM **203** or the like by the CPU **201** as needed. Further, the program group **204** may be provided to the CPU **201** via the communication network **211**, or may be stored on a storage medium **210** in advance and read out by the drive **206** and supplied to the CPU **201**.

(81) FIG. **9** illustrates an example of a hardware configuration of the detection device **200**. The hardware configuration of the detection device **200** is not limited to that described above. For example, the detection device **200** may be configured of part of the configuration described above, such as without the drive **206**. Moreover, the CPU **201** may be a GPU or the like illustrated in the first example embodiment.

(82) The generation unit **221** generates feature values representing the features of a plurality of pieces of orbit data, on the basis of the orbit data representing the state of each flying object included in the flying object group.

(83) The inference unit **222** acquires a value corresponding to the state of the flying object group on the basis of the feature values generated by the generation unit **221**.

(84) The detection unit **223** detects an abnormality having occurred in the flying object group on the basis of the value corresponding to the state of the flying object group acquired by the inference unit **222**.

(85) As described above, the detection device **200** includes the generation unit **221**, the inference unit **222**, and the detection unit **223**. With this configuration, the detection unit **223** can detect an abnormality having occurred in the flying object group on the basis of a value corresponding to a state of the flying object group acquired by the inference unit **222** on the basis of the feature values generated by the generation unit **221**. As a result, it is possible to easily detect an abnormality having occurred in the flying object group.

(86) Note that the detection device **200** described above can be realized by incorporating a predetermined program in an information processing device such as the detection device **200**. Specifically, a program that is another aspect of the present invention is a program for causing an information processing device such as the detection device **200** to execute processing to generate feature values representing features of a plurality of pieces of orbit data on the basis of the orbit data representing a state of each flying object included in a flying object group, acquire a value corresponding to a state of the flying object group on the basis of the generated feature values, and detect an abnormality having occurred in the flying object group on the basis of the acquired value corresponding to the flying object group.

(87) Further, a processing method to be executed by an information processing device such as the detection device **200** is a method of generating feature values representing features of a plurality of pieces of orbit data on the basis of the orbit data representing a state of each flying object included in a flying object group, acquiring a value corresponding to a state of the flying object group on the basis of the generated feature values, and detecting an abnormality having occurred in the flying object group on the basis of the acquired value corresponding to the flying object group.

(88) Even an invention of a program, a computer-readable storage medium storing thereon a program, or a processing method having the above-described configuration also exhibits the same actions and effects as those of the detection device **200**. Therefore, the above-described object of the present disclosure can also be achieved by such an invention.

(89) Moreover, even the learning device **300** that learns a model usable in the detection device **200**, a learning method to be performed by the learning device **300**, or a program can achieve the same object. For example, the learning device **300** includes a generation unit **321** that generates feature values representing features of a plurality of pieces of orbit data on the basis of the orbit data representing a state of each flying object included in a flying object group, and a learning unit **322** that, on the basis of the feature values generated by the generation unit **321**, trains a model so as to

output a value corresponding to a state of the flying object group in response to an input of the feature values. Note that the hardware configuration of the learning device **300** may be similar to the configuration of the detection device **200** described with reference to FIG. **9**.

Supplementary Notes

(90) The whole or part of the example embodiments disclosed above can be described as the following supplementary notes. Hereinafter, the outlines of a detection device and the like of the present invention will be described. However, the present invention is not limited to the configurations described below.

(91) (Supplementary Note 1)

(92) A detection device comprising: a generation unit that generates feature values representing features of a plurality of pieces of orbit data, on the basis of the orbit data representing a state of each of flying objects included in a flying object group; an inference unit that acquires a value corresponding to a state of the flying object group on the basis of the feature values generated by the generation unit; and a detection unit that detects an abnormality having occurred in the flying object group on the basis of the acquired value corresponding to the state of the flying object group.

(Supplementary Note 2)

(93) The detection device according to supplementary note 1, wherein the inference unit acquires a value corresponding to the state of the flying object group from feature values generated on the basis of orbit data in an unknown state that is subject to abnormality detection, and acquires a value corresponding to the state of the flying object group from feature values for comparison; and the detection unit detects an abnormality according to a comparison result of the values acquired by the inference unit.

(Supplementary Note 3)

(94) The detection device according to supplementary note 2, wherein the detection unit detects that an abnormality has occurred when a distance between the values corresponding to the state of the flying object group, acquired by the inference unit, is equal to or larger than a predetermined threshold.

(Supplementary Note 4)

(95) The detection device according to any one of supplementary notes 1 to 3, further comprising a dimension reduction unit that extracts at least part of the feature values generated by the generation unit; wherein the inference unit acquires a value corresponding to the state of the flying object group on the basis of the feature values extracted by the dimension reduction unit.

(Supplementary Note 5)

(96) The detection device according to any one of supplementary notes 1 to 4, further comprising a formatting unit that performs a formatting process to sort orbit data according to time, on the orbit data of each of the flying objects acquired at different time, wherein the generation unit generates the feature values on the basis of a result of the formatting process by the formatting unit.

(Supplementary Note 6)

(97) The detection device according to any one of supplementary notes 1 to 5, wherein the inference unit inputs the feature values, generated by the generation unit, to a model trained to output a value corresponding to the state of the flying object group in response to an input of the feature values, to thereby acquire a value corresponding to the state of the flying object group on the basis of the feature values generated by the generation unit.

(Supplementary Note 7)

(98) The detection device according to any one of supplementary notes 1 to 6, wherein the generation unit extracts orbit data in a predetermined time unit and, on the basis of the extracted orbit data, generates a feature value representing a feature of the whole of the extracted orbit data.

(Supplementary Note 8)

(99) A detection method comprising, by an information processing device: generating feature values representing features of a plurality of pieces of orbit data, on the basis of the orbit data

representing a state of each of flying objects included in a flying object group; acquiring a value corresponding to a state of the flying object group on the basis of the generated feature values; and detecting an abnormality having occurred in the flying object group on the basis of the acquired value corresponding to the state of the flying object group.

(Supplementary Note 9)

(100) A program for implementing, on an information processing device, processing to: generate feature values representing features of a plurality of pieces of orbit data, on the basis of the orbit data representing a state of each of flying objects included in a flying object group; acquire a value corresponding to a state of the flying object group on the basis of the generated feature values; and detect an abnormality having occurred in the flying object group on the basis of the acquired value corresponding to the state of the flying object group.

(Supplementary Note 10)

(101) A learning device comprising: a generation unit that generates feature values representing features of a plurality of pieces of orbit data, on the basis of the orbit data representing a state of each of flying objects included in a flying object group; and a learning unit that, on the basis of the generated feature values, trains a model so as to output a value corresponding to a state of the flying object group in response to an input of the feature values.

(Supplementary Note 11)

(102) A learning method comprising, by an information processing device: generating feature values representing features of a plurality of pieces of orbit data, on the basis of the orbit data representing a state of each of flying objects included in a flying object group; and on the basis of the generated feature values, training a model so as to output a value corresponding to a state of the flying object group in response to an input of the feature values.

(Supplementary Note 12)

(103) A program for implementing, on an information processing device, processing to: generate feature values representing features of a plurality of pieces of orbit data, on the basis of the orbit data representing a state of each of flying objects included in a flying object group; and on the basis of the generated feature values, train a model so as to output a value corresponding to a state of the flying object group in response to an input of the feature values.

(104) It should be noted that the program described in the example embodiments and the supplementary notes may be stored in a storage device or stored on a storage medium readable by a computer. For example, a storage medium is a portable medium such as a flexible disk, an optical disk, a magneto-optical disk, or a semiconductor memory.

(105) While the present invention has been described with reference to the example embodiments described above, the present invention is not limited to the above-described embodiments. The form and details of the present invention can be changed within the scope of the present invention in various manners that can be understood by those skilled in the art.

REFERENCE SIGNS LIST

(106) **100** detection device **110** operation input unit **120** screen display unit **130** communication I/F unit **140** storage unit **141** orbit data information **142** formatted data information **143** feature value information **144** learned model information **145** inference result information **146** program **150** arithmetic processing unit **151** data acquisition unit **152** data formatting unit **153** feature value generation unit **154** dimension reduction unit **155** learning unit **156** inference unit **157** comparison unit **158** output unit **200** detection device **201** CPU **202** ROM **203** RAM **204** program group **205** storage device **206** drive **207** communication interface **208** input/output interface **209** bus **210** storage medium **211** communication network **221** generation unit **222** inference unit **223** detection unit **300** learning device **321** generation unit **322** learning unit

Claims

1. A detection device comprising: at least one memory configured to store instructions; and at least one processor configured to execute instructions to: generate feature values representing features of a plurality of pieces of orbit data, on a basis of the orbit data representing a state of each of flying objects included in a flying object group; acquire a value corresponding to a state of the flying object group on a basis of the generated feature values; and detect an abnormality having occurred in the flying object group on a basis of the acquired value corresponding to the state of the flying object group.
 2. The detection device according to claim 1, wherein the at least one processor is configured to execute the instructions to: acquire a value corresponding to the state of the flying object group from feature values generated on a basis of orbit data in an unknown state that is subject to abnormality detection, and acquire a value corresponding to the state of the flying object group from feature values for comparison; and detect an abnormality according to a comparison result of the acquired values.
 3. The detection device according to claim 2, wherein the at least one processor is configured to execute the instructions to detect that an abnormality has occurred when a distance between the acquired values corresponding to the state of the flying object group is equal to or larger than a predetermined threshold.
 4. The detection device according to claim 1, wherein the at least one processor is configured to execute the instructions to: perform a dimension reduction process of extracting at least part of the generated feature values; and acquire a value corresponding to the state of the flying object group on a basis of the feature values extracted by the dimension reduction process.
 5. The detection device according to claim 1, wherein the at least one processor is configured to execute the instructions to: perform a formatting process to sort orbit data according to time, on the orbit data of each of the flying objects acquired at different time; and generate the feature values on a basis of a result of the formatting process.
 6. The detection device according to claim 1, wherein the at least one processor is configured to execute the instructions to by inputting the generated feature values to a model trained to output a value corresponding to the state of the flying object group in response to an input of the feature values, acquire a value corresponding to the state of the flying object group on the basis of the generated feature values.
 7. The detection device according to claim 1, wherein the at least one processor is configured to execute the instructions to extract orbit data in a predetermined time unit and, on a basis of the extracted orbit data, generate a feature value representing a feature of whole of the extracted orbit data.
 8. A detection method comprising, by an information processing device: generating feature values representing features of a plurality of pieces of orbit data, on a basis of the orbit data representing a state of each of flying objects included in a flying object group; acquiring a value corresponding to a state of the flying object group on a basis of the generated feature values; and detecting an abnormality having occurred in the flying object group on a basis of the acquired value corresponding to the state of the flying object group.
 9. A non-transitory computer-readable medium storing thereon a program comprising instructions for causing an information processing device to execute processing to: generate feature values representing features of a plurality of pieces of orbit data, on a basis of the orbit data representing a state of each of flying objects included in a flying object group; acquire a value corresponding to a state of the flying object group on a basis of the generated feature values; and detect an abnormality having occurred in the flying object group on a basis of the acquired value corresponding to the state of the flying object group.
-