

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417485
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Nelson; Ted et al.

System for facilitating drive up order fulfillment

Abstract

A network based order fulfillment systems having an improved user interface at both a customer device and at an order fulfillment location employee device. Both customer and employee devices scan collect user input and other information using one or more sensors of the user devices to provide proper notifications to both the customer and the employee based on the actions of each. Location information for a customer computing device can be used to continually update ETA and time since arrival information displayed at the employee's computing device.

Inventors: Nelson; Ted (Minneapolis, MN), Jayan; Jathin (Minneapolis, MN), Tewalt; Roy (Minneapolis, MN), Rudge; Andy (Minneapolis, MN), May; Adam (Eden Prairie, MN), Gulden; Josiah (Minneapolis, MN), Carlson; Dan (Minnetonka, MN)

Applicant: Target Brands, Inc. (Minneapolis, MN)

Family ID: 1000008820915

Assignee: Target Brands, Inc. (Minneapolis, MN)

Appl. No.: 18/382920

Filed: October 23, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240054551 A1	Feb. 15, 2024

Related U.S. Application Data

continuation parent-doc US 18105666 20230203 US 11836786 child-doc US 18382920
continuation parent-doc US 16913218 20200626 US 11574265 20230207 child-doc US 18105666
us-provisional-application US 62866834 20190626

Publication Classification

Int. Cl.: G06Q30/0601 (20230101); G06F3/0482 (20130101); G06F3/0484 (20220101); G06F40/109 (20200101); G06Q10/0836 (20230101); G06F3/04817 (20220101)

U.S. Cl.:

CPC G06Q30/0635 (20130101); G06F3/0482 (20130101); G06F3/0484 (20130101); G06F40/109 (20200101); G06Q10/0836 (20130101); G06F3/04817 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9633389	12/2016	Carr et al.	N/A	N/A
10482421	12/2018	Ducrou et al.	N/A	N/A
11574265	12/2022	Nelson et al.	N/A	N/A
2002/0128850	12/2001	Chen	705/301	G06Q 10/103
2006/0076397	12/2005	Langos	N/A	N/A
2006/0178943	12/2005	Rollinson et al.	N/A	N/A
2009/0228325	12/2008	Simmons et al.	N/A	N/A
2013/0030955	12/2012	David	N/A	N/A
2014/0074743	12/2013	Rademaker	705/334	G06Q 30/0601
2015/0262119	12/2014	Santo	N/A	N/A
2016/0148300	12/2015	Carr et al.	N/A	N/A
2016/0247113	12/2015	Rademaker	N/A	N/A
2017/0024805	12/2016	Tepfenhart et al.	N/A	N/A
2017/0262929	12/2016	Degraeve	N/A	N/A
2017/0337523	12/2016	Roach et al.	N/A	N/A
2017/0372388	12/2016	Branham et al.	N/A	N/A
2018/0082356	12/2017	Wilkinson et al.	N/A	N/A
2018/0121992	12/2017	Agarwal	N/A	H04W 4/029

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO 2016/036501	12/2015	WO	N/A

OTHER PUBLICATIONS

CNBC.com [online], "Like it or not, 'click and collect' is here to stay," Jan. 14, 2016, retrieved on Dec. 12, 2018, retrieved from URL <<https://www.cnbc.com/2016/01/13/like-it-or-not-click-and-collect-is-here-to-stay.html>>, 11 pages. cited by applicant

Mobilepaymentstoday.com [online], "Instacart expands mobile app-based grocery pickup and delivery nationwide," Nov. 7, 2018, retrieved on Dec. 12, 2018, retrieved from URL <<https://www.mobilepaymentstoday.com/news/instacart-expands-mobile-app-based-grocery->

pickup-and-delivery-nationwide/> 2 pages. cited by applicant
Shop.Cub.com [online], "Introducing Store Pickup," 2018, retrieved on Dec. 12, 2018, retrieved from URL <<https://www.cub.com/online-ordering/store-pick-up.html>>, 4 pages. cited by applicant
Walmart.com [online], "Store Pickup Mobile Check-in," 2018, retrieved on Dec. 12, 2018, retrieved from URL <https://help.walmart.com/app/answers/detail/a_id/4/~store-pickup-mobile-check-in>, 5 pages. cited by applicant
Walmart.com [online], "Walmart Online Grocery Pickup," Jun. 3, 2016, retrieved on Dec. 12, 2018, retrieved from URL <<https://news.walmart.com/2016/06/03/walmart-online-grocery-pickup>>, 5 pages. cited by applicant

Primary Examiner: Eskridge; Cory W

Attorney, Agent or Firm: Fish & Richardson P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. Utility application Ser. No. 18/105,666, filed Feb. 3, 2023, which is a continuation of U.S. Utility application Ser. No. 16/913,218, filed Jun. 26, 2020 (now U.S. Pat. No. 11,574,65), which claims the benefit of U.S. Provisional Application Ser. No. 62/866,834, filed Jun. 26, 2019. The disclosures of the prior applications are considered part of (and are incorporated by reference in) the disclosure of this application.

TECHNICAL FIELD

(1) This document generally relates to architecture of computer systems, communications between computing devices, and graphic user interfaces for eliciting user input.

BACKGROUND

(2) Computing devices are devices that accept data input, process the data, and provide data output using hardware and software. Computing devices can communicate with other computing devices using wired or wireless networks or a combination thereof. For example, computing devices can communicate over the Internet. User interactions with a computing device can cause the computing device to transmit communications to a second computing device, which can cause the second computing device to provide output such as changes to a visual display, sounds, or tactile output. Such output at the second computing device can elicit user input from a user of the second computing device which can in turn cause the second computing device to transmit one or more communications to the first computing device thereby causing the first computing device to generate additional output.

SUMMARY

(3) This document generally describes a network based order fulfillment systems that provides information to one or more user devices that allow users of the user devices located at a fulfillment location (such as a physical store location, a restaurant, a warehouse, or other location) to fulfill orders placed by users of other user devices. For example, a first user device can collect user input and other information using one or more sensors of the user device to identify items that a first user wishes to purchase from a store, the first user's progress in traveling to the store, and other information about the first user and the first user's order. The first user's device can provide this information to a user device of a worker at a fulfillment location to allow the worker to fulfill the order in a timely manner and provide the items in the order to the first user upon arrival of the first user at the fulfillment location. The worker can interact with her user device to cause the worker's device to update a status of the order and provide information to the first user's device which can

cause the first user's device to provide additional information to the first user. In one aspect, the first user's device can provide a user interface that includes a unique optically recognizable code (e.g., a barcode or a matrix barcode) that can be used to verify the first user's identity, the first user's order number, or other information associated with the first user or the order. The worker's device can provide instructions to the first user for scanning, or otherwise verifying, the optically recognizable code. The worker can then use her device to scan the optically recognizable code displayed by the first user's device to verify the first user's identity or an aspect of the first user's order.

(4) In another aspect, information collected at the first user's device (e.g., from user input or via a location detection unit such as a GPS unit of the user's device) can be transmitted to the worker's device to cause the worker's device to provide an indication that the first user has begun to travel to the fulfillment location. The worker's device can also display an estimated arrival time or estimated time until arrival at the fulfillment location for the first user. For example, the first user's device can determine that the first user has begun to travel to the fulfillment location. The first user's device can transmit a communication to the worker's device indicating that the first user has begun traveling to the fulfillment location. The worker's device can provide an estimated time until arrival at the fulfillment location for the first user. Upon the user arriving at or near the fulfillment location, the first user's device can transmit a communication to the worker's device indicating that the user has arrived. This can cause the worker's device to display a count up timer indicating how long the first user has been waiting for her order after arriving at the fulfillment location. In some implementations, if the count up timer reaches a preset threshold, a customized notification can be provided to the first user's device to indicate a status of the order, indicate additional instructions for the first user, or communicate another message to the first user.

(5) In another aspect, a user interface provided at the first user's device can provide one or more controls for altering aspects of an order after the first user has placed the order. For example, the user interface can allow the first user to add additional items to the order or remove items from the order. As another example, the user interface can allow the first user to indicate substitute items for items from the original order that are not available. As another example, the user interface can allow the first user to switch the order type from a drive-up type order to an in-store pick up order.

(6) In one aspect, in general, a method includes receiving, by a first computing device, a first communication indicating that a second computing device has begun to travel toward an order fulfillment location; receiving, by the first computing device, information indicating an estimated time until arrival at the order fulfillment location by the second computing device; providing, by the first computing device and in response to receiving the first communication indicating that the second computing device has begun to travel toward the order fulfillment location, a user interface that includes a timer indicating the received estimated time until arrival; receiving, by the first computing device, a second communication indicating that the second computing device has arrived at the order fulfillment location; and updating, by the first computing device and in response to receiving the second communication indicating that the second computing device has arrived at the order fulfillment location, the timer included as part of the user interface to indicate a time since arrival of the second computing device at the fulfillment location.

(7) The method can further include, after receiving the information indicating the estimated time until arrival and prior to receiving the second communication, receiving, by the first computing device, a third communication indicating a new estimated time until arrival at the order fulfillment location by the second computing device. In some cases, the first computing device can, in response to receiving the third communication, update the timer included as part of the user interface to indicate the new estimated time until arrival.

(8) The method can further include after updating the timer to indicate the time since arrival of the second computing device at the fulfillment location, determining that the timer has reached a predetermined time. The method can also include in response to determining that the timer has

reached a predetermined time, changing a visual appearance of the timer on the user interface. The method can include, in response to determining that the timer has reached a predetermined time, causing a communication indicating an order status to be transmitted to the second computing device.

(9) In some cases, the user interface can further include an indication of an order fulfillment type for an order associated with the second computing device, wherein the order fulfillment type has previously been indicated by a user of the second computing device. The method can further include receiving, by the first computing device, a third communication indicating a change in order fulfillment type for the order associated with the second computing device. The first computing device can update the user interface to indicate the change in order fulfillment type for the order associated with the second computing device. In some cases, the change in order fulfillment type can be a change from a drive-up order to an in-store pickup order. In some cases, the indication of an order fulfillment type can take the form of an order fulfillment type icon and indicating the change in order fulfillment type can include changing the order fulfillment type icon.

(10) The systems, devices, program products, and processes described throughout this document can, in some instances, provide one or more of the following advantages. By providing streamlined communications between mobile devices operated by users/customers and employees working at fulfillment locations, an order fulfillment system can reduce the amount of time spent interacting with the mobile devices, thereby reducing power consumption and improving battery life of the computing devices. Additionally, by streamlining communications while providing for computer network based ordering and pick-up facilitation, the computing system can reduce the amount of communications to and from mobile computing devices, thereby reducing bandwidth usage of one or more communications networks and freeing up communications bandwidth for other purposes. Additionally, unique user interface elements at mobile computing devices of both users/customers and employees of fulfillment locations can improve user experience thereby leading to improved outcomes with respect to efficiency and accuracy of both user interactions with the mobile computing devices and fulfillment of orders. Other benefits and advantages will be apparent from the following descriptions.

Description

DESCRIPTION OF DRAWINGS

(1) FIG. 1 is diagram of an example system for facilitating drive-up order fulfillment.

(2) FIGS. 2A-2N show example user interface displays for computing devices in a drive-up order fulfillment system.

(3) FIG. 3 is a flowchart of an example process to be performed by a computing device in a drive-up order fulfillment system.

(4) FIG. 4 is a schematic diagram that shows an example of a computing system.

(5) Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

(6) FIG. 1 is a diagram of an example system **100** for facilitating order fulfillment for drive-up pickup by user's. In the system **100**, a user, such as a customer who wishes to complete an online order for items by picking up the items using a drive-up service, can access a dedicated application executing on a mobile device **102**. The mobile device **102** can be, for example, a mobile phone, a tablet device, a touch screen computer, a laptop computer, a PDA, a smart watch, or other mobile device. In some implementations, instead of accessing a dedicated application executing on the mobile device **102**, the user can use a browser of the mobile device **102** to access a website that provides the below described functionality and therefore all descriptions related to use of the dedicated application apply equally to a web-based implementation.

(7) The user logs into the dedicated application by entering a user name or other identifier and a password. Alternatively, the user can log into the dedicated application by providing biometric information using one or more sensors of the mobile device **102** such as by scanning a fingerprint using a fingerprint scanner of the mobile device **102** or using a retina scanner of the mobile device **102** to scan the user's retina information. In some implementations, the user may be already logged into the dedicated application from a previous session.

(8) The user can use the dedicated application to select items for purchase from a store using an online shopping interface. For example, the dedicated application can be a grocery shopping application that can permit the user to search and/or browse for grocery items, add desired items to a virtual shopping cart, and place an order for the selected items by entering payment information. The user can also use the dedicated application to access one or more previously entered orders. For example, a user may have previously logged into an online account for a retailer associated with the dedicated application and placed an on-line order for one or more items using either the mobile device **102** or a different computing device such as a home or laptop computer. As another example, the user may have previously placed an on-line order using the dedicated application. The user can access and review the previously placed orders after logging into the dedicated application. This can include reviewing items included in the orders, estimated time until the order is ready, payment used for the order (e.g., "card ending in 123"), a fulfillment location for the order, and other information associated with the orders.

(9) The mobile device **102** can communicate with other computing devices through a network **114**, such as, for example, the Internet. For example, the mobile device **102** can communicate with a network access point such as a WiFi router or a cellular communication tower to access the network **114** and communicate with other computing devices. For example, the mobile device **102** can communicate with a server system **116** consisting of one or more servers to place the order. Alternatively, or additionally, the user can use a different computer to place the order and the different computer can communicate through the network **114** with the server system **116**. The server system **116** can be affiliated with a retailer and process the on-line order received from the mobile device **102** or another computing device. The server system **116** can facilitate fulfillment of the order by providing details of the order, such as ordered items, identity of the user, an order number, time that the order was placed, etc. to one or more computing devices located at a fulfillment center such as a store **106**. For example, the store **106** can be part of a chain of affiliated stores associated with a retailer and the server system **116** can be a server system associated with the retailer. Upon receiving an on-line order from the user, the server system **116** can identify the store **106** as an appropriate fulfillment location for the order based on information such as, an indication of a preferred location for fulfillment indicated by the user at the mobile device **102** or another computing device, a current location of the mobile device **102**, another location associated with the user (e.g., home or work address information entered by the user into a customer profile), based on item availability (e.g., by identifying a store where all or a majority of the items in the order are in stock), or based on a combination of these and one or more other factors.

(10) For example, the server system **116** can identify the store **106** as an appropriate location for fulfilling the user's order. The server system **116** can transmit information on the order to a computing device **118** in the possession of, or being used by, an employee of the store **106**. The computing device **118** can be a mobile computing device, such as, for example, a mobile phone, a tablet device, a touch screen computer, a laptop computer, a PDA, a smart watch, or other mobile device. In some implementations, the computing device **118** can be a non-mobile or semi-mobile device such as a server, a desktop computer, a cash register, a smart TV, or other computing device. The server system **116** can provide appropriate information for the order to the computing device **118** such as items in the order, identifying information for the user who placed the order, time the order was placed, a desired pickup time for the order (e.g., as indicated by the user at the time of placing the order), an order number, and other relevant information.

(11) At the time of placing the order, or at a different time, such as when logging into the dedicated application, the user of the mobile device **102** can indicate a desired order fulfillment method for the order. For example, the user can specify that the order is for drive-up fulfillment. A drive-up fulfillment allows the user to drive to a fulfillment location, such as a retail store location, a warehouse, or another location where an employee of the retailer can meet the user at the user's vehicle **104**, verify that the user is receiving the proper order, and provide the items to the user without the user being required to exit his vehicle. For example, the user can travel to the store **106**, park in a designated area of the parking lot of the store **106**, notify an employee that they have arrived (as described in more detail below), and then receive the purchased items from the employee when the employee brings the items to the user's vehicle **104**.

(12) As another example, the user can specify that the order is for in-store pickup fulfillment. In-store pickup fulfillment can allow the user to travel to a fulfillment location, such as the store **106**, and enter the store to pickup the purchased items from a designated location within the fulfillment location. Such a fulfillment method can allow the user greater flexibility by allowing the user to shop for additional items within the store **106** (e.g., items that the user wishes to see in-person before purchasing, such as clothing or produce) and then pickup the items from the on-line order at the designated location after completing his in-store shopping. Alternatively, the user can pickup the order items without also shopping for items at the store **106** in person.

(13) As another example, the user can specify that the order is for delivery. An employee of the retailer or a third-party service can travel to the user's home or another drop-off location designated by the user to deliver the items in the order to the user.

(14) In some cases, when the user has indicated drive-up or in-store pickup type order fulfillment, the dedicated application can provide navigation directions, such as driving directions, to the fulfillment location (e.g., store **106**). For example, the dedicated application can communicate with a native routing application installed on the mobile device **102** or with one or more remote routing servers to identify a route from either the user's current location or a specified starting location to the store **106**. As another example, the mobile device **102** can communicate with the server system **116** through the network **114** to receive routing information from either the user's current location or the specified starting location to the store **106**. The dedicated application can then, for example, provide a map display **108** showing a route **110** to the store **106**. As another example, the dedicated application can provide turn by turn directions to the store **106** using text and/or icons in addition to or in place of the map display **108**.

(15) In some implementations, the user can permit the dedicated application to access location information for the mobile device **102**. For example, the user can set a permissions setting permitting the dedicated application to access location information for the mobile device **102**. In some implementations, the user can specify that the dedicated application is only permitted to access location information for the mobile device **102** when the dedicated application is executing or can specify that the dedicated application is always permitted to access location information for the mobile device **102** even when a user interface for the dedicated application is not open. The mobile device **102** can determine its own location using one or more well-known techniques, such as by using a GPS module for receiving GPS signals from GPS satellites to determine the location of the mobile device **102**. The mobile device **102** can also use a wireless communication triangulation technique to determine the location of the mobile device **102**. As another example, the mobile device **102** can determine its location based on the location of a network access point that the mobile device **102** is in short range wireless communication with (e.g., a WiFi router). The dedicated application can use the location information to identify a starting location for the route **110**, such as the current location of the mobile device **102**.

(16) In the case of both drive-up and in-store pickup type order fulfillments, the user can begin to travel to the fulfillment location, such as by driving the vehicle **104** to the store **106**. In some implementations, information collected or generated by the mobile device **102** can be used to

determine that the user has begun to travel to the order fulfillment location. For example, location information determined by the mobile device **102**, as described above, can be used to determine that the mobile device **102** has begun to travel along the route **110**. For example, the dedicated application can receive location information for the mobile device **102** over sequential periods of time (e.g., every 2 seconds) and compare the movement of the mobile device **102** based on the changing location information to the route **110** to determine that the user has begun to travel the route **110**. Alternatively or additionally, the user can select a user interface control **112** provided by the dedicated application to indicate that he has begun traveling toward the store **106**. For example, the user may have selected a permissions setting to not allow the dedicated application to access location information for the mobile device **102**. In some implementations, the dedicated application will only display the user interface control **112** in situations in which the user has not permitted the dedicated application to access location information for the mobile device **102**. As another example, the mobile device **102** may be unable to accurately determine its location, for example, due to tall buildings interfering with GPS signals or due to lack of wireless communications access points in the area around the mobile device **102**. The dedicated application can provide the user interface control **112** when the mobile device **102** is unable to accurately determine the location of the mobile device **102** so that the user can indicate that he has begun to travel toward the store **106**.

(17) Upon determining that the user has begun to travel toward the store **106** (e.g., based on location information collected by the mobile device **102** or based on user interaction with the user interface control **112**), the mobile device **102** can communicate with one or more computing devices located at and affiliated with the store **106**, either directly through the network **114** or by communicating with the server system **116** which in turn communicates appropriate information and instructions to the one or more computing devices located at the store **106**. For example, an employee of the store **106** can use the computing device **118**, which can receive information relevant to the order from the server system **116**. The mobile device **102** can communicate with the server system **116** over the network **114** to indicate to the server system **116** that the user has begun to travel toward the store **106**. The server system **116** can then provide a communication to the computing device **118** of the store employee to indicate that the user of the mobile device **102** is on the way. The server system **118** may communicate directly with the computing device **118** through the network **114** or may communicate with a computing device/system located at the store **106** which then communicates with the computing device **118**, e.g., through a wireless or wired local area network (LAN). In some implementations, the server system **116** or a central computing device located at the store **106** can communicate with the computing device **118** and one or more other computing devices in possession of other employees of the store **106** to allow multiple employees to receive information on on-line orders placed by customers and coordinate efforts to fulfill such orders.

(18) The server system **116** can provide additional information along with this notification or prior to sending the notification that the user is on the way. For example, the server system **116** can access user profile information to identify a make and model for the user's vehicle **104**, a color for the user's vehicle **104**, and/or other identifying information for the user's vehicle **104** (such as a whole or partial license plate number) and provide this vehicle identification information to the computing device **118** to allow the employee to more easily identify the user's vehicle **104** when the user has arrived at the designating drive-up fulfillment location at the store **106**. The server system **116** can store this vehicle identification information as part of a customer profile for the user or the user can provide the information at the time of placing the order (e.g., in situations where the user is part of a multi-car family and may use different vehicles on different occasions). In some implementations, the user can be prompted to enter such vehicle identification information at the time of placing the order, at the time of selecting drive-up fulfillment for the order, or at the time of indicating that they are on their way. For example, the dedicated application can present a GUI for eliciting vehicle identification information to the user at the time of placing the order, or in

response to the user selecting drive up fulfillment or indicating that he is on his way. The GUI can provide user selectable graphics that allow the user to indicate different aspects of the vehicle such as color or vehicle type (e.g., SUV, sedan, mini-van, etc.). The GUI can also provide one or more text fields that allow the user to enter information on the vehicle such as a make and model for the user's vehicle **104**, a color for the user's vehicle **104**, and/or other identifying information for the user's vehicle **104** (such as a whole or partial license plate number).

(19) The server system **116** can also provide information on an estimated time of arrival and/or an estimated time until arrival for the user. For example, the mobile device **102** can calculate an estimated time until arrival for the user based on the estimated time for traversing the route **110** and provide this information to the server system **116** which can then provide the estimated time until arrival information to the computing device **118**. As another example, the server system **116** can receive location information from the mobile device **102** and use this location information to calculate an estimated time until arrival for the user. For example, the user can give the dedicated application permission to access location information for the mobile device **102**. A GPS unit or other location detection unit of the mobile device **102** can regularly determine the location for the mobile device **102**. At the time of indicating to the server system **116** that the user has begun to travel along the route **110** to the store **106**, the mobile device **102** can also indicate the current location of the mobile device **102**. The server system **116** can then use either an internal time estimation routine, or communicate with an external routing system to identify an estimated time required for the user to travel from the current location of the mobile device **102** to the store **106** using any one of many known techniques. The server system **116** can then provide this estimated time until arrival information to the computing device **118**, which can then provide this information to the employee.

(20) As the user travels along the route **110** (or another route) to the store **106**, the server system **116** can periodically receive updated location information from the mobile device **102** (e.g., by periodically querying the dedicated application running on the mobile device **102** for current location information for the mobile device **102**). Each time the server system **116** receives updated location information for the mobile device **102**, the server system **116** can calculate or otherwise identify (e.g., by communicating with the external routing system) an updated estimated time until arrival for the user, based on the new location information. The server system **116** can then provide the updated estimated time until arrival for the user to the computing device **118**. In some implementations, the server system **116** will only provide the updated estimated time until arrival for the user to the computing device **118** if the updated estimated time until arrival differs from the previous estimated time until arrival adjusted for the change in time between the time the initial or previous estimated time until arrival was calculated and the time the updated estimated time until arrival was calculated.

(21) In some implementations, the user may take a different route to the store **106** than the map display **108** indicated by the map display **108**. For example, the user may wish to make a stop along the way to store **106** to run a different errand, the user may have a preferred route to the store **106** that is not necessarily the quickest route, the user may wish to take a more scenic route to the store **106**, or the user may wish to a sudden change in traffic conditions due to, e.g., an accident. In such scenarios, the server system **116** can continue to receive periodic location information from the mobile device **102** and update the estimated time until arrival for the user based on the new location information for the user along the new route. In some implementations, if the location of the mobile device **102** has strayed from the route **110**, the server system **116**, a remote mapping system, or a mapping application installed on the mobile device **102** can update the route **110** to indicate a new route from the current location of the mobile device **102** to the store **106** and communicate the updated route to the dedicated application. The dedicated application can then display this updated route on the map display **108**.

(22) In some implementations, the user interface of the dedicated application can include one or

more additional controls. For example, the user may travel part way to the store **106** and then decide to pick up the order at a different time. The user can select a control indicating that they are no longer enroute to the store **106**. The mobile device **102** can then communicate to the server system **116** that the user is no longer on the way to the store **106**. The server can then communicate to the computing device **118** that the user is no longer on the way to the store **106** which can allow the employee to focus efforts on fulfilling a different order or performing other tasks.

(23) The computing device **118** includes a user interface **120**. The user interface **120** can, for example, be a user interface for another dedicated application executing on the computing device **118** or another instance of the same dedicated application that is executing on the mobile device **102**. The user interface **120** includes a user selectable control **122** that allows the employee to view all arriving orders (e.g., orders for which the user is on the way). The employee can select the control **122** by, for example, using a touch screen interface of the computing device **118** or one or more other input devices of or in communication with the computing device **118**. The user interface **120** further includes a control **124** to allow the employee to view all placed orders. This could include all orders placed for fulfillment at the store **106** or all orders assigned specifically to the employee for fulfillment. Selection of the all orders control **124** can cause the user interface **120** to display all orders that have been placed for fulfillment regardless of the user's status (e.g., orders for users that are on the way and orders for users that are not yet on the way).

(24) In the example depicted in FIG. 1, the control **122** is selected and the user interface **120** is displaying a list **126** of orders for which the user is currently on the way and/or has already arrived. For example, an order listing **128** in the list **126** includes the user's name associated with the order, an estimated time until the indicated user is predicted to arrive at the store **106** (15 minutes) and an icon **130** indicating that the user associated with the order listing **128** has selected drive-up order fulfillment. Similarly, an order listing **132** indicates that a user named "Cindy L." is estimated to arrive at the store **106** in 23 minutes and includes an icon **134** indicating that Cindy L. has selected drive-up order fulfillment.

(25) The user interface **120** further includes an order listing **136** indicating that a user named "Brent F." is estimated to arrive at the store **106** in 26 minutes and includes an icon **138** indicating that Brent F. has selected in-store pickup order fulfillment. In some implementations, in place of or in addition to the indication of an estimated time until arrival, each order listing can include a time indicator indicating the predicated time of arrival for the customer (e.g., 3:15 pm). In some implementations, the order listings in the list **126** can include less or more details with respect to each order. For example, each order listing can include an order number. As another example, each order listing can include vehicle identification information.

(26) In some implementations, order listings in the list **126** are user selectable to allow the employee to view additional information about each order (as explained in greater detail below). For example, the employee can select the order listing **128** to cause the user interface **120** to display additional information about the order placed by Ted H. (which can be, for example, the user of mobile device **102**). Additional details that can be displayed by the user interface **120** in response to selection of the order listing **128** can include an order number, a listing of items in the order, vehicle identification information, special instructions or requests entered by the customer, location information for bag containing the items for the order (e.g., one or more shelf or bin locations at a drive-up order fulfillment staging area), a number of bags for the order, an indication as to whether or not the order includes age restricted items (e.g., cold medicine, alcohol, etc.), and other information for the order.

(27) Additional user interactions with the user interfaces of the mobile device **102** and the computing device **118** and communications between the mobile device **102** and computing device **118** will now be described with respect to FIGS. 2A-2N. FIG. 2A shows a user interface **202** of the mobile device **102** while FIG. 2B shows a corresponding user interface **204** of the computing device **118**. The user interface **202** includes the map display **108** displaying the route **110** from the

user's origin location **140** to the location **142** of the store **106**. In this example, the user interface **202** further includes an icon **144** displayed on the map display **108** showing the user's progress along the route **110**. As previously described, the mobile device **102** can provide location information to the server system **116** (e.g., in situations in which the user has granted the dedicated application permission to access location information for the mobile device **102**). The server system **116** can use a series of received location information communications to identify that the user has begun to travel along the route **110** toward the store **106**.

(28) For example, the server system **116** can identify that first received location information indicates that the mobile device **102** is located at the origin location **140**, then identify that second received location information indicates that the mobile device **102** has moved to a second location that is along the route **110**, and subsequently identify that third received location information indicates that the mobile device **102** is currently located at the location indicated by the icon **144**, which is even further along the route **110**. Based on these changes in location of the mobile device **102** along the route **110** to the store **106**, the server system **116** determines that the user has begun to travel toward the store **106**. The server system **116** can also receive ETA information from the mobile device **102** along with one or more of the location information communications, can calculate an ETA for the user based on most recently received location information, or can communicate with a mapping system to determine an ETA. For example, the server system **116** can provide the most recently received location information for the mobile device **102** to a mapping system along with an indication of the location of the store **106**. The mapping system can provide routing information to the server system **116** and/or an estimated time until arrival at the store **106** for the mobile device **102** (i.e., an estimated time for the user to complete travel along the route **110** to the location **142**).

(29) In response to determining that the user has begun to travel toward the store **106**, the server system **116** provides a notification to the computing device **118** to prompt the computing device **118** to provide a notification to the employee that the user is on the way via the user interface **204**. The notification from the server system **116** communicated to the computing device **118** can include additional information such as the ETA for the user, an identifier for the user (e.g., name, user id, customer number, etc.), an identifier for the order (e.g., an order number), information on the type of fulfillment for the order (e.g., drive-up fulfillment or in-store pickup fulfillment) and/or other information associated with the order. As discussed above, the server system **116** can communicate directly with the computing device **118** via the network **114** or, in some implementations, can communicate with a central computer located at the store **106** which in turn relays information to the computing device **118**. For purposes of brevity, further communications will be described as being directly between the server system **116** and the computing device **118** but should be understood to also to cover communications of information that are relayed to the computing device **118** through one or more other computing devices from the server system **116**.

(30) In response to receiving the notification that the user has begun to travel toward the store **106**, the computing device **118** causes the user interface **204** to display a notification to the employee. The computing device **118** can also provide audio (e.g., ringing, text to speech) or tactile (e.g., vibration) output to notify the employee that the user is on the way. In the example depicted in FIG. 2B, the user interface **204** is displaying a lock screen for the computing device **118**. The computing device **118** can provide a notification **206** on the lock screen that indicates that a new user is on the way to the store **106**. The notification **206** includes an indicator **208** that a guest is on the way (i.e., the user has begun to travel toward the store **106**). The notification **206** further includes an order identifier **210** that includes an order number for the user's order and an indicator **212** of the estimated time until the user arrives at the store **106**. In this example, the notification **206** indicates that the user is estimated to arrive in 23 minutes. In some implementations, the notification **206** can indicate a time that the user is estimated to arrive. For example, the notification **206** can indicate "arriving at 5:24 pm." In some implementations, the employee can select the notification **206** or a

control displayed as part of the notification **206** to cause the computing device **118** to display a page of the order fulfillment application that includes additional details on the order, customer, or related info. In some implementations, the notification does not include an estimated time of arrival or estimated time until arrival. For example, the notification **206** can indicate “guest is on the way” or a similar notification while linking to order details included in a display of the order fulfillment application.

(31) The notification **206** further includes an icon **214** indicating that the user has selected drive-up order fulfillment for the order. In some implementations, the notification **206** can include more or less information. For example, the notification can include the user's name, vehicle identification information, an indication of a location for the order (e.g., one or more bins in a staging area), an indication that perishable goods for the order need to be collected, or other information related to the order.

(32) FIG. 2C shows an alternate version of the user interface **202**. The version of user interface **202** shown in FIG. 2C can be employed, for example, when the user has not permitted the dedicated application to access location information for the mobile device **102** or in situations in which the mobile device **102** is unable to determine a location (e.g., tall buildings blocking GPS signals). The user interface **202** can include instructions to the user to indicate when they have begun to travel toward the store **106** and other relevant information, such as store hours for the store **106**. The user interface **202** further includes a user selectable icon **216** that allows the user to indicate that they have begun to travel toward the store **106**. Upon selection of the icon **216** by the user, the mobile device **102** communicates with the server system **116** to indicate that the user has begun to travel toward the store **106**. In some implementations, the server system **116** can determine an estimated time of arrival for the user based on an initial location for the route to the store **106** (such as the user's home address, which can be stored as part of the user's profile information) as described above (e.g., by performing calculations or by communicating with a mapping system). The server system **116** can then communicate with the computing device **118** to notify the employee that the user is on the way, as described above.

(33) In some implementations, in response to the user opening the dedicated application or in response to the user selecting the icon **216**, the dedicated application can request temporary access to location information for the mobile device **102**. If the user permits the dedicated application temporary access to location information (e.g., only while the dedicated application is open), the dedicated application can provide the mobile device **102** location information to the server system **116** to assist the server system **116** in identifying the estimated time of arrival of the user at the store **106**, as described above.

(34) In some implementations, the user interface **202** includes a control **217** that allows the user to change the order fulfillment type. In the example shown in FIG. 2C, the control **217** indicates that the user has selected drive-up order fulfillment and further includes an option to change the order fulfillment type to in-store pickup. For example, the user may have indicated drive-up order fulfillment at the time of placing the order and now that the user has begun to travel toward the store **106**, the control **217** now indicates that the user's order is designated for drive-up order fulfillment. The user can interact with the control **217** to change the order fulfillment type to in-store pickup, e.g., by selecting a selection area **215** next to an indication for “In-Store Pickup.” For example, the user may decide after initially placing the order that they would like to enter the store **106** to shop for additional items in person and then retrieve the online order when exiting the store **106**. Selection of the selection area **215** by the user can cause the user interface **202** to change to indicate that the user has changed the order fulfillment type to in-store pickup.

(35) As another example, the user may have initially selected in-store pickup order fulfillment at the time of placing the order. For example, the user may have initially placed the order using a home computer such as a laptop or desktop computer and selected an option for in-store pickup fulfillment at the time of placing the order. Later on, the user accesses the previously placed order

using the dedicated application executing on the mobile device **102**. The user may then decide to change the order fulfillment type from in-store pickup (the originally selected fulfillment type) to drive-up order fulfillment. For example, it may have started raining, so the user may not wish to exit their vehicle, or the user may be in a hurry and not want to take the time to enter the store. As another example, the user may have intended to utilize drive-up fulfillment when placing the order but inadvertently selected in-store pickup fulfillment (e.g., in-store pickup fulfillment may have been the default option). The user can change the order fulfillment type by interacting with the control **217** to change the order fulfillment type to drive-up fulfillment. Selection of the control **217** to change the order fulfillment type can cause the dedicated application to provide additional information, such as through display of a different user interface triggered by selection of the control **217**.

(36) For example, FIG. 2E shows a user interface **219** for the mobile device **102** that is displayed in response to selection of the selection area **215** of the control **217** on the user interface **202** of FIG. 2C to change the order fulfillment type from drive-up fulfillment to in-store pickup fulfillment. As shown, the user interface **219** includes the control **217** with the selection area **215** shown as selected, indicating that the user has selected in-store pickup fulfillment for the order. The user interface **219** includes a barcode **221** that the user can use to facilitate an in-store pickup order. The barcode **221** can be a unique barcode that is associated with the user. In other implementations, the barcode **221** can be a unique barcode that is associated with the user's order or associated with all active orders for the user. In such implementations, the barcode **221** can change between each order for the same user. In some implementations, the barcode **221** is tied to a specific payment method. In some implementations, another verification method can be used, such as a matrix barcode, a unique character string, or other unique indicator.

(37) The barcode **221** can be scanned by the employee, e.g., using the computing device **118**, to verify the user's identity and verify that the order was provided to the user at, for example, an in-store pickup kiosk or counter. For example, the employee can retrieve the bags for the user's order from appropriate storage bins located at or near the in-store pickup fulfillment location and provide the bags containing the user's order to the user. The employee can then scan the barcode **221**. The computing device **118** can then provide a notification indicating that the scanned barcode **221** matches the user or the user's order to ensure that the employee has provided the correct order to the user. Scanning of the barcode can also cause the computing device **118** to display information indicating that the user has already paid for the order.

(38) Continuing with FIG. 2E, the user can interact with the control **217** displayed as part of the user interface **219** to change the order fulfillment type from in-store pickup to drive-up fulfillment. In some implementations, the user may select the control **217** as many times as desired to switch between drive-up and in-store pickup fulfillment up until the time that the order is fulfilled. For example, the user may initially select in-store pickup fulfillment, then change the fulfillment type to drive-up upon getting into her vehicle because it has started raining, and then change the fulfillment type back to in-store pickup when approaching the store because the rain has stopped. Selection of the control **217** on the user interface **219** can cause the order fulfillment type to switch from in-store pickup to drive-up fulfillment and can further cause the dedicated application to display the user interface **202** of FIG. 2C.

(39) Selection of the control **217** to change the fulfillment type from in-store pickup to drive-up fulfillment can, in some implementations, cause the dedicated application to provide additional user interface displays to the user. For example, selection of the control **217** by the user to change the fulfillment type from in-store pickup to drive-up fulfillment can trigger the dedicated application to display a user interface that prompts the user to enter vehicle identification information such as color, vehicle type, vehicle make, vehicle model, or a full or partial license plate number. For example, selection of the control **217** by the user to change the fulfillment type from in-store pickup to drive-up fulfillment can trigger the dedicated application to display a number of icons

with different colors to allow the user to easily select a vehicle color. As another example, selection of the control **217** by the user to change the fulfillment type from in-store pickup to drive-up fulfillment can trigger the dedicated application to display a number of icons each displaying a different vehicle type (e.g., SUV, sedan, mini-van, motorcycle, bicycle), to allow the user to easily indicate her vehicle type. In some implementations, the user selectable icons for vehicle color and vehicle type are displayed simultaneously by the dedicated application. In some implementations, the dedicated application is triggered to display the above described user interfaces for prompting the user to enter vehicle information by user selection of the “I’m on my way” user selectable icon **216**.

(40) Additionally, in response to the user changing the order fulfillment type, the mobile device **102** will communicate with the server system **116** to indicate that the user has changed the order fulfillment type. The server system **116** can access a database storing information about the order and change the order fulfillment type for the order in response to receiving the communication. The server system **116** can also communicate with the computing device **118** to indicate to the computing device **118** that the order fulfillment type for the order has been changed. In some implementations, the control **217** can be included as a part of other user interface displays, such as the version of user interface **202** shown in FIG. 2A or as part of other user interface displays for mobile device **102** described with respect to later figures. In some implementations, the user can interact with another control, such as a menu control or action item control to access a user interface screen that includes the control **217**.

(41) FIG. 2D shows the computing device **118** displaying the user interface **120** of FIG. 1. In this example, the user selectable control **122** is selected to cause the user interface **120** to display the list **126** orders for which the user is currently on the way and/or has already arrived. As previously described, the order listings **128**, **132**, and **136** provide identification information for users who are on the way to the store **106**, information on ETA for each user, and icons indicating fulfillment type for each order. The user interface **120** can be displayed by the computing device **118**, for example, in response to the employee selecting the notification **206** of FIG. 2B and then unlocking the computing device **118**, such as by entering a security code or scanning a fingerprint. As another example, the employee may already have unlocked the computing device **118** and be viewing the application executing on the computing device **118**. In response to the computing device **118** receiving the notification from the server system **116** that the user has begun to the travel toward the store **106**, the computing device **118** updates the user interface **120** to include the user's order in the arriving orders list **126**.

(42) For example, the user of the mobile device **102** may be Cindy L. Upon the server system **116** detecting that that Cindy has begun to travel the route **110** toward the store **106** and/or upon selection of the icon **216** by Cindy, the server system **116** provides a notification to the computing device **118** indicating that Cindy is on the way. This can cause the computing device **118** to update the user interface **120** to include the order listing **132** for Cindy's order, which had not previously been displayed as part of the user interface **120**. As each of the user's associated with the orders indicated by the order listings **128**, **132**, and **136** continue to travel toward the store **106**, the ETA for each user can be periodically updated on the user interface **120** to keep the employee updated on the status of each user.

(43) As described above, in some implementations, the user can interact with the mobile device **102** to change the order fulfillment type after an order has already been placed, such as, for example, by interacting with the control **217**. When a user changes the order fulfillment type, the mobile device **102** communicates with the server system **116** which in turn communicates with the computing device **118** to indicate to the computing device **118** that the order fulfillment type for the order has changed. The computing device **118** can then update the user interface **120** to reflect the change in order fulfillment type and notify the employee of the change. For example, in the example shown in FIG. 2D, if Cindy L. uses the control **217** to change her desired order fulfillment type from

drive-up to in-store pickup, the icon **134** displayed for order listing **132** will change from a car (as shown in FIG. 2D) to a grocery bag, such as that displayed for icon **138**. In some implementations, when the order fulfillment type for an order changes, the computing device **118** can cause the associated icon (e.g., the icon **134**) to blink, change color (e.g., black to red), or otherwise change visually to alert the employee to the change in order fulfillment type. The computing device **118** can also provide a notification to the employee indicating that the order fulfillment type has changed in response to receiving a communication from the computing device **118** that the order fulfillment type has changed.

(44) FIG. 2F shows a user interface **218** for the mobile device **102**. In this example, the user interface **218** is a lock screen for the mobile device **102**. The user interface **218** is an example user interface for situations in which the user has granted permission for the dedicated application to continually access location information for the mobile device **102** (e.g., “always on”). The user interface **218** includes a notification **220** that is displayed in response to a determination that the mobile device **102** has arrived at the store **106**. For example, the mobile device **102** can be identified as having arrived at the store **106** upon the location of the mobile device **102** indicating that the mobile device **102** is located within the parking lot of the store **106**. As another example, the mobile device **102** can be identified as having arrived at the store **106** upon the location of the mobile device **102** indicating that the mobile device **102** is located within a specified distance of the store **106** (e.g., 300 meters).

(45) The determination that the mobile device **102** has reached the store **106** can be made by the mobile device **102** or by the server system **116**. For example, as the user progresses along the route **110**, the mobile device **102** can continue to provide location information for the mobile device **102** to the server system **116**. Upon the server system **116** receiving location information indicating that the mobile device **102** has arrived at the store **106** (e.g., is located in the parking lot of the store **106**), the server sends a notification to the mobile device **102** which causes the dedicated application to provide the notification **220** to the user. As another example, the dedicated application can perform the determination by comparing location information for the mobile device **102** to information indicating the location of the store **106** and/or location information for the parking lot of the store **106** to determine when the user has arrived at the store **106**. Upon determining that the user has arrived at the store **106**, the dedicated application causes the mobile device **102** to display the notification **220**. The dedicated application can further cause the mobile device **102** to transmit a communication to the server system **116** indicating that the user has arrived at the store **106**.

(46) The notification **220** includes an indication **222** of the dedicated application (e.g., text and/or an icon) to help the user to readily distinguish that the notification **220** is related to drive-up order fulfillment from notifications related to other applications installed on the mobile device **102**. The notification **220** further includes a greeting **224** and instructions **226** for next steps for the user. In the example shown in FIG. 2F, the instructions **226** indicate that the user can select the notification **220** (and subsequently unlock the mobile device **102**) to cause the dedicated application to display a barcode to be scanned by the employee to complete the order. As another example, the instructions **226** can instruct the user where to park for drive-up fulfillment.

(47) FIG. 2G shows an example user interface **228** of the computing device **118** containing a notification **230** that is displayed in response to the user arriving at the store **106**. For example, upon the server system **116** determining that the user has arrived at the store **106** or receiving a communication from the mobile device **102** indicating that the user has arrived at the store **106**, the server system **116** sends a communication to the computing device **118** to cause the computing device **118** to display the notification **230**.

(48) The computing device **118** can also provide audio (e.g., ringing, text to speech) or tactile (e.g., vibration) output to notify the employee that the user has arrived. In the example depicted in FIG. 2G, the user interface **228** is displaying a lock screen for the computing device **118**. The computing

device **118** can provide the notification **230** on the lock screen that indicates that the user has recently arrived at the store **106**. The notification **230** includes an indicator **232** that a guest has arrived (i.e., the user has arrived in the parking lot). The notification **230** further includes an order identifier **234** that includes an order number for the user's order.

(49) The notification **230** further includes the icon **214** indicating that the user has selected drive-up order fulfillment for the order. In some implementations, the notification **230** can include more or less information. For example, the notification can include the user's name, vehicle identification information, an indication of a location for the order (e.g., one or more bins in a staging area), an indication that perishable goods for the order need to be collected, or other information related to the order.

(50) FIG. 2H shows an alternate arrival user interface **236** for the mobile device **102**. The user interface **236** shown in FIG. 2H can be employed, for example, when the user has not permitted the dedicated application to access location information for the mobile device **102** or in situations in which the mobile device **102** is unable to determine a location (e.g., tall buildings blocking GPS signals). The user interface **236** can include instructions to the user on where to park for drive-up fulfillment and can also provide instructions to prompt the user to indicate when they have arrived. The user interface **236** includes a user selectable icon **238** that allows the user to indicate that they have arrived at the store **106**. Upon selection of the icon **238** by the user, the mobile device **102** communicates with the server system **116** to indicate that the user has arrived at the store **106**. In some implementations, the user interface **236** includes a user selectable control **240** that allows the user to view details on the order.

(51) In some implementations, the user interfaces provided by the mobile device **102** can include an indication of the user's progress in completing order fulfillment. For example, the user interface **236** can include indicators for various steps of the order fulfillment process for the user and indicate which steps have already been completed by the user and the current step that the user is engaged in. For example, the user interface **236** can include indications of steps for "order successfully submitted," "order is ready for pickup," "you're on your way," "you've arrived at the store," "team member is walking to your vehicle," and "order complete." As each step in the process is completed, the user interface indicates that the step has been completed by, for example, placing a checkmark next to the step. Such a visualization can help to reassure the user that the order is being fulfilled and that the system is aware of the user's progress in fulfilling the order.

(52) FIG. 2I shows the computing device **118** displaying an updated version of the user interface **120** of FIG. 1 and FIG. 2D. In this example, the user selectable control **122** is selected to cause the user interface **120** to display the list **126** orders for which the user is currently on the way and/or has already arrived. The list **126** has been updated such that the order listing **128** is no longer present, indicating that fulfillment of the order associated with the order listing **128** has been completed (e.g., the associated user has received their order). The order listings **132** and **136** have been updated to indicate updated statuses for the users associated with those respective orders. For example, the order listing **136** indicates that Brent F. is now 2 minutes away.

(53) Furthermore, the user interface **120** has updated to indicate that Cindy L. has now arrived at the store and has switched the estimated time of arrival indication for the order listing **132** to a time since arrival timer **242**. In other words, the timer **242** in the order listing **132** has switched from a count-down timer indicating an estimated time until arrival of Cindy to a count-up timer indicating the amount of time since Cindy arrived at the store **106**. In some implementations, when the timer **242** switches from a count-down, ETA timer to a count-up, time since arrival timer, the user interface **120** will change the appearance of the timer **242**. For example, the user interface **120** changes the color of the timer **242** when it transitions from a count-down, ETA timer to a count-up, time since arrival timer. For example, the timer **242** can be displayed in grey during count-down, ETA timer mode and then can be displayed in green when the timer **242** switches to a count-up, time since arrival timer. In the example shown in FIG. 2I, in response to switching from a count-

down, ETA timer to a count-up, time since arrival timer, the timer **242** has switched from a regular font to an underlined, bold font. Other appearance changes, such as italics, flashing, change in size, change in location, change in background color for the order listing **132**, a box or circle around the timer **242**, or other display change can be used to visually indicate to the employee that the user (Cindy) has arrived and that timer **242** has switched to a time since arrival timer.

(54) In a preferred implementation, the timer **242** does not transition from a count-down, ETA timer to a count-up, time since arrival timer in response to the count-down timer reaching zero, but rather the timer **242** transitions from a count-down, ETA timer to a count-up, time since arrival timer upon the computing device **118** receiving a communication from the server system **116** indicating that the user has arrived at the store **106**. The timer **242** therefore transitions from a count-down, ETA timer to a count-up, time since arrival timer in response to the received notification regardless of if a previous ETA timer indicated additional time until the user was estimated to arrive and regardless of if the ETA timer had previously reached zero. In such implementations, the transition of the **242** from a count-down, ETA timer to a count-up, time since arrival timer is solely dependent upon the computing device **118** receiving a notification that the user associated with the order listing **132** has arrived at the store **106**.

(55) In some implementations, the user interface **120** as shown in FIG. **2I** can be displayed by the computing device **118**, for example, in response to the employee selecting the notification **230** of FIG. **2G** and then unlocking the computing device **118**, such as by entering a security code or scanning a fingerprint. As another example, the employee may already have unlocked the computing device **118** and may be viewing the application executing on the computing device **118**. In response to the computing device **118** receiving the notification from the server system **116** that the user has arrived at the store **106**, the computing device **118** updates the user interface **120** to transition the timer **242** from a count-down, ETA timer to a count-up, time since arrival timer.

(56) For example, the user of the mobile device **102** may be Cindy L. Upon the server system **116** determining that Cindy has arrived at the store **106** (e.g., based on location data of the mobile device **102** or based on receiving a communication from the mobile device **102** indicating arrival at the store **106**), the server system **116** provides a notification to the computing device **118** indicating that Cindy has arrived. This can cause the computing device **118** to update the user interface **120** to transition the timer **242** from a count-down, ETA timer to a count-up, time since arrival timer, regardless of the previously displayed ETA for Cindy. Additionally, the user interface **120** can be updated to indicate an updated ETA for Brent.

(57) In some implementations, the timer **242** can change appearance again after a predetermined amount of time has elapsed since arrival of the user at the store **106**. For example, upon reaching 3:00, the timer **242** can change to red and begin to blink. Additionally, the computing device **118** can emit an audible, tactile, or additional visual alarm (e.g., a blinking light) upon the timer **242** reaching the predetermined time. Such alarms and change in appearance of the timer **242** can help to catch the employee's attention and inform the employee that the user has been waiting for a period of time determined to be longer than usual or longer than is desirable.

(58) In some implementations, upon the timer **242** reaching the predetermined time, the computing device **118** can communicate with the mobile device **102** (e.g., through the server system **116**) to cause the mobile device **102** to display a customized notification to the user. For example, the computing device **118** can communicate with the mobile device **102** to inform the mobile device **102** that the customized notification can be displayed and the mobile device **102** can display a notification having an apology for the wait, indicating a status of the order (e.g., perishable items being retrieved), or offering a discount or coupon to compensate the user for the wait. In some implementations, the user interface **120** can allow the employee to provide additional information which can be communicated to the user by the mobile device **102**. For example, the employee can enter a message indicating that a certain item is unavailable or indicating that the employee will bring out the user's order in a specified amount of time. For example, the employee can utilize the

user interface **120** to send a message for display at the mobile device **102** stating “Sorry for the delay, your order will be out within two minutes.”

(59) Providing an updated notification to the user upon the timer **242** reaching the predetermined time can give the user confidence that one or more employees of the store **106** are aware of the user's arrival at the store **106** and that they are still working on completing the user's order and bringing it to the user's vehicle **104**.

(60) In some implementations, the count-up timer is stopped or cleared in response to an event. For example, the employee can use one or more controls of one of the user interface screens of the computing device **118** to indicate that the order has been fulfilled. Completion of the order fulfillment can cause the timer to stop or be cleared.

(61) FIG. 2J shows an example user interface **244** that can be displayed in response to a determination that the user has arrived at the store **106**. For example, upon the dedicated application determining that the user has arrived at the store, the dedicated application displays the user interface **244**. As another example, the server system **116** can determine that the user has arrived at the store **106** and send a communication to the mobile device **102** to cause the mobile device **102** to display the user interface **244**. The user interface **244** can include a greeting and information such as an indication that an employee of the store will arrive with the user's order soon. In some implementations, the user interface **244** can include a timer (not shown) that indicates an amount of time since the user has arrived at the store **106**. In some implementations, the user interface **244** includes a user selectable icon **246** that, when selected, causes the dedicated application to display a barcode that can be scanned by the employee using the computing device **118** to verify the order.

(62) FIG. 2K shows an example user interface **248** that can be displayed by the computing device **118** in response to selection of the order listing **132** (FIG. 2I) by the employee. For example, the employee can select the order listing **132** (or another order listing) to view details on the associated order and/or other orders associated with the user. For example, upon the employee selecting the order listing **132** displayed as part of the user interface **120**, the computing device **118** displays the user interface **248** containing details on active orders placed by Cindy L.

(63) The user interface **248** includes a header **250** containing a customer identifier, such as the customer's name. The header **250** includes user selectable controls **251** and **253** that can be used to perform additional actions or view additional information. For example, selection of the control **251** can cause the computing device **118** to display information about the customer indicated in the header **250**. As another example, selection of the control **253** can allow the employee to take actions with respect to one or more selected orders associated with the customer, such as cancel an order, indicate an unavailable item, delay an order, or other actions. As another example, selection of the control **251** or the control **253** can cause the user interface **248** to display a list of items included in one or more selected active orders associated with the customer.

(64) A field **252** of the user interface **248** indicates that the customer indicated in the header **250** has arrived and includes a timer **254** indicating the amount of time that has elapsed since the customer has arrived. In some implementations, prior to arrival of the customer, the field **252** will include an indicator of “order placed” or “on the way” to indicate the customer's status. For example, the field **252** can indicate that the customer is on the way and the timer **254** can indicate an ETA for the customer. The field **252** further includes vehicle identification information for the customer to allow the employee to more easily identify the customer's vehicle when bringing the customer's order items to the drive-up fulfillment location in the parking lot of the store **106**. The field **252** further includes an icon **258** indicating that the order(s) for the customer are drive-up fulfillment orders (rather than in-store pickup, delivery, etc.).

(65) The user interface **248** includes a field **260** indicating a first order for the customer, along with an order number for the order. The field **260** can include a checkbox **262** that can be selected when the employee wants to take an action with respect to the order indicated by the field **260**. For

example, the employee can select the checkbox **262** and then select the control **254** to take one or more actions with respect to the selected order, such as indicating that the employee has taken ownership of completing the order and delivering it to the customer's vehicle.

(66) Sub-fields **264** and **266** nested under the field **260** indicate where the purchased items for the order are located. For example, the field **264** includes an indication of "FOS-A002," which can indicate that part of the order is located at the Front of Store staging area in bin A002. The field **264** includes an indicator **268** indicating the number of bags at the indicated location. In the example depicted, the field **264** indicates that there are four bags for the order located at bin FOS-A002. Similarly, field **266** includes an indicator **270** indicating that there are two bags for the order located at the bin FOA-A003. The information in the fields **264** and **266** can ensure that the employee gathers the correct number of bags for fully completing the customer's order.

(67) In some implementations, multiple active orders can be associated with a single customer. For example, a customer may place a first order for drive-up fulfillment and later realize that they would like to purchase additional items and make a second order for drive-up fulfillment. The field **272** indicates a second active order associated with the customer. The field **272** includes a checkbox **274** that functions in a similar manner to the checkbox **262**. For example, the employee can select both checkboxes **262** and **274** to take actions with respect to both orders for the customer. The sub-field **276** nested under the field **272** indicates that the second order is located at storage location "SD-A023," which can be, for example, an indication of bin A023 at a secondary staging area (e.g., for use when the front of store staging area is full, or a staging area for refrigerated and/or frozen items). The sub-field **276** includes an indicator **278** indicating that there are four bags for the second order located at storage bin SD-A023.

(68) FIG. 2L shows an example user interface **280** for the user's mobile device **102** that includes a barcode **282**. The user interface **280** having the barcode can be displayed, for example, in response to selection by the user of the icon **246** of FIG. 2J, selection of the notification **220** of FIG. 2E, or selection of the icon **238** of FIG. 2H. In some implementations, the user interface **280** having the barcode **282** is automatically displayed in response to a determination that the user has arrived at the store **106**. In some implementations, the barcode **282** can be displayed as part of a notification on a lock screen of the mobile device **102**. The barcode **282** can be a unique barcode that is associated with the user. In other implementations, the barcode **282** can be a unique barcode that is associated with the user's order or associated with all active orders for the user. In such implementations, the barcode **282** can change between each order for the same user. In some implementations, the barcode **282** is tied to a specific payment method. In some implementations, another verification method can be used, such as a matrix barcode, a unique character string, or other unique indicator.

(69) The barcode **282** can be scanned by the employee, e.g., using the computing device **118**, to verify the user's identity and verify that the order was provided to the user at the user's vehicle **104**. For example, the employee can retrieve the bags for the user's order from appropriate storage bins (as indicated by the user interface **248**, for example), and bring the bags out to the user's vehicle. The employee can then scan the barcode **282**. The computing device **118** can then provide a notification indicating that the scanned barcode **282** matches the user or the user's order to ensure that the employee has provided the correct order to the user.

(70) FIG. 2M shows an example user interface **284** for the computing device **118** for facilitating scanning of the barcode **282** by the employee using the computing device **118** to verify and complete the user's order. For example, the user interface **284** can prompt the employee to scan the barcode **282** displayed on the user's mobile device **102** using a camera of the computing device **118**, an infrared scanner of the computing device **118**, or other scanning functionality of the computing device **118**. In some implementations, the user interface **284** can allow the employee to select a mechanism for scanning the barcode **282**. In some implementations, the employee can select one or more input buttons of the computing device **118** to scan the barcode **282** using the

camera of the computing device **118** and can select one or more other different buttons of the computing device **118** to scan the barcode **282** using the infrared scanner.

(71) Upon scanning the barcode **282**, the computing device **118** can compare identifying information (e.g., for the user or the order) associated with the barcode **282** to identifying information for the user or the order to verify that the employee is providing the correct order to the user. In some implementations, such a determination is made at a central computer of the store **106** in communication with the computing device **118** or at the server system **116**.

(72) FIG. 2N shows an example user interface **286** for the computing device **118** for collecting a signature from the user. The user interface **286** can be displayed, for example, in response to a successful match of the barcode **282** scanned by the computing device **118**. The user interface **286** includes a signature line **288** where the user can sign using touchscreen functionality of the computing device **118**. The user interface **286** further includes a control **290** to clear the signature line **288** and a control **292** for the user to submit their signature when done signing. The computing device **118** can communicate an image of the user's signature to the server system **116** for storage in a database for later verification that the user signed for the order.

(73) In some implementations, upon receiving the user's signature (or upon successfully scanning the barcode **282** displayed on the mobile device **102**), the computing device **118** can remove the order listing associated with the user's (now completed) order from one or more user interface screens. In some implementations, reception of the user's signature and/or successful scanning of the barcode **282** causes the count-up timer indicating the time since arrival for the user to be stopped or cleared.

(74) FIG. 3 is a flowchart of an example process **300** to be performed by a computing device in a drive-up order fulfillment system. For example, the process **300** can be performed by the computing device **118** of an employee of a store. The process **300** includes receiving a notification that a first computing device has begun to travel toward a fulfillment location (**302**). The notification includes information an estimated time until arrival (ETA) for the first computing device. For example, the first computing device can provide location information to a remote server system. The remote server system can use the received location information to determine that the first computing device has begun to travel toward the fulfillment location. As another example, a user of the first computing device can interact with one or more user interface controls to indicate that the user has begun to travel toward the fulfillment location.

(75) The computing device that received the notification then provides a user interface display that includes a countdown timer indicating ETA for the first computing device (**304**). For example, the computing device can display a timer, such as the timer shown in order listing **128** by the user interface **120** in FIG. 2D. The timer indicates an amount of time until the user of the first computing device is predicted to arrive at the fulfillment location. Alternatively, or in addition, the user interface can include a time that the user is predicted to arrive at the fulfillment location (e.g., 5:24 pm).

(76) Next, the process **300** includes receiving a notification of a new ETA for the first computing device (**306**). For example, the user of the first computing device may have been delayed by traffic, may have made a stop along the way, or may have decided to take a different route. As another example, traffic congestion that was present when the original ETA was determined may have cleared up. Any of these occurrences or other factors can cause the original ETA to be incorrect. In such situations, a server system can provide a notification to the employee's computing device of the new ETA.

(77) The employee's computing device then updates the countdown timer in response to receiving the new ETA (**308**). For example, prior to receiving the new ETA, the employee's computing device can continually update the countdown timer based on the original ETA and the passage of time. Upon receiving the new, updated ETA, the employee's computing device updates the countdown timer to reflect the changed condition.

(78) The employee's computing device then receives a notification that the first computing device has arrived at the fulfillment location (310). For example, the server system can use location information for the first computing device to determine that the first computing device is located in a parking lot of the fulfillment location or another designated fulfillment area associated with the fulfillment location (e.g., designated street parking spots near the fulfillment location). As another example, the user of the first computing device can interact with a user interface of the first computing device to indicate that they have arrived at the fulfillment location. The first computing device communicates this updated status to the server system which in turn provides the notification to the employee's computing device.

(79) The employee's computing device then displays a count-up timer indicating the amount of time since the first computing device has arrived at the fulfillment location (312). This display of the count-up timer can be performed in response to receiving the notification that the first computing device has arrived at the fulfillment location. For example, the timer 254 of FIG. 2K can be displayed in response to the computing device 118 receiving a notification that the mobile device 102 has arrived at the store 106. The displayed count-up timer can take the same form as the previously displayed countdown timer indicating the ETA for the first computing device. In some implementations, the count-up timer replaces the countdown timer and has a similar or identical appearance to the countdown timer.

(80) In some implementations, the count-up timer can change appearance after a predetermined amount of time has elapsed since arrival of the first computing device at the fulfillment location. For example, upon reaching 4:00, the count-up timer can change color. Alternatively, or additionally, the count-up timer can begin to flash upon reaching the predetermined time. Additionally, the employee's computing device can emit an audible, tactile, or additional visual alarm (e.g., a blinking light) upon the count-up timer reaching the predetermined time. Such alarms and change in appearance of the count-up timer can help to catch the employee's attention and inform the employee that the user has been waiting for a period of time determined to be longer than usual or longer than is desirable.

(81) FIG. 4 shows an example of a computing device 400 and an example of a mobile computing device that can be used to implement the techniques described here. The computing device 400 is intended to represent various forms of digital computers, such as laptops, desktops, workstations, personal digital assistants, servers, blade servers, mainframes, and other appropriate computers. The mobile computing device is intended to represent various forms of mobile devices, such as personal digital assistants, cellular telephones, smart-phones, and other similar computing devices. The components shown here, their connections and relationships, and their functions, are meant to be exemplary only, and are not meant to limit implementations of the inventions described and/or claimed in this document.

(82) The computing device 400 includes a processor 402, a memory 404, a storage device 406, a high-speed interface 408 connecting to the memory 404 and multiple high-speed expansion ports 410, and a low-speed interface 412 connecting to a low-speed expansion port 414 and the storage device 406. Each of the processor 402, the memory 404, the storage device 406, the high-speed interface 408, the high-speed expansion ports 410, and the low-speed interface 412, are interconnected using various busses, and may be mounted on a common motherboard or in other manners as appropriate. The processor 402 can process instructions for execution within the computing device 400, including instructions stored in the memory 404 or on the storage device 406 to display graphical information for a GUI on an external input/output device, such as a display 416 coupled to the high-speed interface 408. In other implementations, multiple processors and/or multiple buses may be used, as appropriate, along with multiple memories and types of memory. Also, multiple computing devices may be connected, with each device providing portions of the necessary operations (e.g., as a server bank, a group of blade servers, or a multi-processor system).

(83) The memory 404 stores information within the computing device 400. In some

implementations, the memory **404** is a volatile memory unit or units. In some implementations, the memory **404** is a non-volatile memory unit or units. The memory **404** may also be another form of computer-readable medium, such as a magnetic or optical disk.

(84) The storage device **406** is capable of providing mass storage for the computing device **400**. In some implementations, the storage device **406** may be or contain a computer-readable medium, such as a floppy disk device, a hard disk device, an optical disk device, or a tape device, a flash memory or other similar solid state memory device, or an array of devices, including devices in a storage area network or other configurations. A computer program product can be tangibly embodied in an information carrier. The computer program product may also contain instructions that, when executed, perform one or more methods, such as those described above. The computer program product can also be tangibly embodied in a computer- or machine-readable medium, such as the memory **404**, the storage device **406**, or memory on the processor **402**.

(85) The high-speed interface **408** manages bandwidth-intensive operations for the computing device **400**, while the low-speed interface **412** manages lower bandwidth-intensive operations. Such allocation of functions is exemplary only. In some implementations, the high-speed interface **408** is coupled to the memory **404**, the display **416** (e.g., through a graphics processor or accelerator), and to the high-speed expansion ports **410**, which may accept various expansion cards (not shown). In the implementation, the low-speed interface **412** is coupled to the storage device **406** and the low-speed expansion port **414**. The low-speed expansion port **414**, which may include various communication ports (e.g., USB, Bluetooth, Ethernet, wireless Ethernet) may be coupled to one or more input/output devices, such as a keyboard, a pointing device, a scanner, or a networking device such as a switch or router, e.g., through a network adapter.

(86) The computing device **400** may be implemented in a number of different forms, as shown in the figure. For example, it may be implemented as a standard server **420**, or multiple times in a group of such servers. In addition, it may be implemented in a personal computer such as a laptop computer **422**. It may also be implemented as part of a rack server system **424**. Alternatively, components from the computing device **400** may be combined with other components in a mobile device (not shown), such as a mobile computing device **450**. Each of such devices may contain one or more of the computing device **400** and the mobile computing device **450**, and an entire system may be made up of multiple computing devices communicating with each other.

(87) The mobile computing device **450** includes a processor **452**, a memory **464**, an input/output device such as a display **454**, a communication interface **466**, and a transceiver **468**, among other components. The mobile computing device **450** may also be provided with a storage device, such as a micro-drive or other device, to provide additional storage. Each of the processor **452**, the memory **464**, the display **454**, the communication interface **466**, and the transceiver **468**, are interconnected using various buses, and several of the components may be mounted on a common motherboard or in other manners as appropriate.

(88) The processor **452** can execute instructions within the mobile computing device **450**, including instructions stored in the memory **464**. The processor **452** may be implemented as a chipset of chips that include separate and multiple analog and digital processors. The processor **452** may provide, for example, for coordination of the other components of the mobile computing device **450**, such as control of user interfaces, applications run by the mobile computing device **450**, and wireless communication by the mobile computing device **450**.

(89) The processor **452** may communicate with a user through a control interface **458** and a display interface **456** coupled to the display **454**. The display **454** may be, for example, a TFT (Thin-Film-Transistor Liquid Crystal Display) display or an OLED (Organic Light Emitting Diode) display, or other appropriate display technology. The display interface **456** may comprise appropriate circuitry for driving the display **454** to present graphical and other information to a user. The control interface **458** may receive commands from a user and convert them for submission to the processor **452**. In addition, an external interface **462** may provide communication with the processor **452**, so

as to enable near area communication of the mobile computing device **450** with other devices. The external interface **462** may provide, for example, for wired communication in some implementations, or for wireless communication in other implementations, and multiple interfaces may also be used.

(90) The memory **464** stores information within the mobile computing device **450**. The memory **464** can be implemented as one or more of a computer-readable medium or media, a volatile memory unit or units, or a non-volatile memory unit or units. An expansion memory **474** may also be provided and connected to the mobile computing device **450** through an expansion interface **472**, which may include, for example, a SIMM (Single In Line Memory Module) card interface. The expansion memory **474** may provide extra storage space for the mobile computing device **450**, or may also store applications or other information for the mobile computing device **450**.

Specifically, the expansion memory **474** may include instructions to carry out or supplement the processes described above and may include secure information also. Thus, for example, the expansion memory **474** may be provide as a security module for the mobile computing device **450**, and may be programmed with instructions that permit secure use of the mobile computing device **450**. In addition, secure applications may be provided via the SIMM cards, along with additional information, such as placing identifying information on the SIMM card in a non-hackable manner.

(91) The memory may include, for example, flash memory and/or NVRAM memory (non-volatile random access memory), as discussed below. In some implementations, a computer program product is tangibly embodied in an information carrier. The computer program product contains instructions that, when executed, perform one or more methods, such as those described above. The computer program product can be a computer- or machine-readable medium, such as the memory **464**, the expansion memory **474**, or memory on the processor **452**. In some implementations, the computer program product can be received in a propagated signal, for example, over the transceiver **468** or the external interface **462**.

(92) The mobile computing device **450** may communicate wirelessly through the communication interface **466**, which may include digital signal processing circuitry where necessary. The communication interface **466** may provide for communications under various modes or protocols, such as GSM voice calls (Global System for Mobile communications), SMS (Short Message Service), EMS (Enhanced Messaging Service), MMS messaging (Multimedia Messaging Service), CDMA (code division multiple access), TDMA (time division multiple access), PDC (Personal Digital Cellular), WCDMA (Wideband Code Division Multiple Access), CDMA2000, or GPRS (General Packet Radio Service), among others. Such communication may occur, for example, through the transceiver **468** using a radio-frequency. In addition, short-range communication may occur, such as using a Bluetooth, WiFi, or other such transceiver (not shown). In addition, a GPS (Global Positioning System) receiver module **470** may provide additional navigation- and location-related wireless data to the mobile computing device **450**, which may be used as appropriate by applications running on the mobile computing device **450**.

(93) The mobile computing device **450** may also communicate audibly using an audio codec **460**, which may receive spoken information from a user and convert it to usable digital information. The audio codec **460** may likewise generate audible sound for a user, such as through a speaker, e.g., in a handset of the mobile computing device **450**. Such sound may include sound from voice telephone calls, may include recorded sound (e.g., voice messages, music files, etc.) and may also include sound generated by applications operating on the mobile computing device **450**.

(94) The mobile computing device **450** may be implemented in a number of different forms, as shown in the figure. For example, it may be implemented as a cellular telephone **480**. It may also be implemented as part of a smart-phone **482**, personal digital assistant, or other similar mobile device.

(95) Various implementations of the systems and techniques described here can be realized in digital electronic circuitry, integrated circuitry, specially designed ASICs (application specific

integrated circuits), computer hardware, firmware, software, and/or combinations thereof. These various implementations can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which may be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device.

(96) These computer programs (also known as programs, software, software applications, or code) include machine instructions for a programmable processor and can be implemented in a high-level procedural and/or object-oriented programming language and/or in assembly/machine language. As used herein, the terms machine-readable medium and computer-readable medium refer to any computer program product, apparatus and/or device (e.g., magnetic discs, optical disks, memory, Programmable Logic Devices (PLDs)) used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term machine-readable signal refers to any signal used to provide machine instructions and/or data to a programmable processor.

(97) To provide for interaction with a user, the systems and techniques described here can be implemented on a computer having a display device (e.g., a CRT (cathode ray tube) or LCD (liquid crystal display) monitor) for displaying information to the user and a keyboard and a pointing device (e.g., a mouse or a trackball) by which the user can provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback (e.g., visual feedback, auditory feedback, or tactile feedback); and input from the user can be received in any form, including acoustic, speech, or tactile input.

(98) The systems and techniques described here can be implemented in a computing system that includes a back end component (e.g., as a data server), or that includes a middleware component (e.g., an application server), or that includes a front end component (e.g., a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of the systems and techniques described here), or any combination of such back end, middleware, or front end components. The components of the system can be interconnected by any form or medium of digital data communication (e.g., a communication network). Examples of communication networks include a local area network (LAN), a wide area network (WAN), and the Internet.

(99) The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

Claims

1. A computer-implemented method comprising: receiving, by a first computing device, a first communication indicating that a user of a second computing device has begun to travel toward an order fulfillment location; receiving, by the first computing device, first information indicating an estimated time until arrival at the order fulfillment location by the user of the second computing device; receiving, by the first computing device, a second communication indicating that a user of a third computing device has begun to travel toward an order fulfillment location; receiving, by the first computing device, second information indicating an estimated time until arrival at the order fulfillment location by the user of the third computing device; providing, by the first computing device and in response to receiving the first information and the second information, a graphical user interface (GUI) that includes: a first field including an indication of the estimated time until arrival by the user of the second computing device and an indication of a fulfillment type for an

order associated with the user of the second computing device; a second field including an indication of the estimated time until arrival by the user of the third computing device and an indication of a fulfillment type for an order associated with the user of the third computing device; receiving a selection by a user of the first computing device, the selection indicating the first field displayed as part of the GUI; and in response to receiving the selection indicating the first field; displaying additional details for the order associated with the user of the second computing device.

2. The computer-implemented method of claim 1, wherein the first field further includes an identifier for the user of the second computing device, and wherein the second field further includes an identifier for the user of the third computing device.
3. The computer-implemented method of claim 1, wherein the fulfillment type for the order associated with the user of the second computing device is different from the fulfillment type for the order associated with the user of the third computing device.
4. The computer-implemented method of claim 3, wherein the fulfillment type for the order associated with the user of the second computing device is a drive-up order fulfillment type and the fulfillment type for the order associated with the user of the third computing device is an in-store pickup order fulfillment type.
5. The computer-implemented method of claim 1, wherein the first field and the second field are indicative of orders that have been prepared by one or more employees at the order fulfillment location before the user of the second computing device and the user of the third computing device arrive at the order fulfillment location.
6. The computer-implemented method of claim 1, further comprising: periodically and repeatedly receiving, by the first computing device, information indicating an updated estimated time until arrival at the order fulfillment location by the user of the second computing device; and updating, by the first computing device, the first field based on the periodically and repeatedly received information indicating the updated estimated time until arrival to display an indication of the updated estimated time until arrival by the user of the second computing device, until the first computing device receives an indication that the user of the second computing device has arrived at the order fulfillment location.
7. The computer-implemented method of claim 1, further comprising: receiving, by the first computing device, a third communication indicating that the user of the second computing device has arrived at the order fulfillment location; presenting, by the first computing device, a notification indicating that the user of the second computing device has arrived at the order fulfillment location; receiving, by the first computing device, user input indicating selection of the notification; and presenting, by the first computing device in response to receiving the user input indicating selection of the notification, a second GUI that includes an indication of one or more locations of items for the order associated with the user of the second computing device and a number of containers located at each of the one or more indicated locations.
8. The computer-implemented method of claim 1, further comprising: receiving, by the first computing device, a third communication indicating that the user of the second computing device has arrived at the order fulfillment location; and actuating, by the first computing device, an alarm based on a predetermined amount of time elapsing since the user of the second computing device arrived at the order fulfillment location, wherein the alarm is at least one of an audible alarm, a tactile alarm, or a visual alarm.
9. The computer-implemented method of claim 1, further comprising transmitting, to the second computing device, a notification indicating a status of preparing the order associated with the user of the second computing device, the status of preparing the order being based at least in part on user input received at the first computing device.
10. The computer-implemented method of claim 1, wherein a determination that the user of the second computing device has begun to travel toward the order fulfillment location is made based on receiving information indicating a plurality of locations for the second computing device

determined using a GPS unit of the second computing device, identifying a first location from the plurality of locations, identifying a second location from the plurality of locations that occurred after the first location, and determining that the second location is along a route to the order fulfillment location with respect to the first location.

11. The computer-implemented method of claim 10, wherein the second communication is generated, by the second computing device using the GPS unit of the second computing device, based on identifying a third location amongst the plurality of locations that corresponds to a GPS location of the order fulfillment location.

12. The computer-implemented method of claim 1, wherein the additional details for the order associated with the user of the second computing device comprise information indicative of one or more locations of items for the order associated with the user of the second computing device.

13. The computer-implemented method of claim 12, wherein the additional details for the order associated with the user of the second computing device comprise a number of containers located at each of the one or more indicated locations.

14. The computer-implemented method of claim 12, wherein the additional details for the order associated with the user of the second computing device comprise information for multiple distinct orders placed by the user of the second computing device.

15. The computer-implemented method of claim 12, wherein the additional details for the order associated with the user of the second computing device comprise information identifying items included in the order associated with the user of the second computing device.

16. The computer-implemented method of claim 1, further comprising: receiving, by the first computing device, a third communication indicating a change in the order fulfillment type for the order associated with the user of the second computing device, wherein the change in the order fulfillment type is initiated in response to selection of a user selectable control displayed on the second computing device; and updating, by the first computing device, the GUI to indicate the change in the fulfillment type for the order associated with the user of the second computing device.

17. A system comprising: one or more processors; computer memory containing instructions that, when executed by the one or more processors, cause the system to perform operations comprising: receiving, by a first computing device, a first communication indicating that a user of a second computing device has begun to travel toward an order fulfillment location; receiving, by the first computing device, first information indicating an estimated time until arrival at the order fulfillment location by the user of the second computing device; receiving, by the first computing device, a second communication indicating that a user of a third computing device has begun to travel toward an order fulfillment location; receiving, by the first computing device, second information indicating an estimated time until arrival at the order fulfillment location by the user of the third computing device; providing, by the first computing device and in response to receiving the first information and the second information, a graphical user interface (GUI) that includes: a first field including an indication of the estimated time until arrival by the user of the second computing device and an indication of a fulfillment type for an order associated with the user of the second computing device; a second field including an indication of the estimated time until arrival by the user of the third computing device and an indication of a fulfillment type for an order associated with the user of the third computing device; receiving a selection by a user of the first computing device, the selection indicating the first field displayed as part of the GUI; and in response to receiving the selection indicating the first field; displaying additional details for the order associated with the user of the second computing device.

18. A non-transitory computer-readable medium containing instructions that, when executed by one or more processors, cause the performance of operations comprising: receiving, by a first computing device, a first communication indicating that a user of a second computing device has begun to travel toward an order fulfillment location; receiving, by the first computing device, first

information indicating an estimated time until arrival at the order fulfillment location by the user of the second computing device; receiving, by the first computing device, a second communication indicating that a user of a third computing device has begun to travel toward an order fulfillment location; receiving, by the first computing device, second information indicating an estimated time until arrival at the order fulfillment location by the user of the third computing device; providing, by the first computing device and in response to receiving the first information and the second information, a graphical user interface (GUI) that includes: a first field including an indication of the estimated time until arrival by the user of the second computing device and an indication of a fulfillment type for an order associated with the user of the second computing device; a second field including an indication of the estimated time until arrival by the user of the third computing device and an indication of a fulfillment type for an order associated with the user of the third computing device; receiving a selection by a user of the first computing device, the selection indicating the first field displayed as part of the GUI; and in response to receiving the selection indicating the first field; displaying additional details for the order associated with the user of the second computing device.

19. The non-transitory computer-readable medium of claim 18, wherein the fulfillment type for the order associated with the user of the second computing device is different from the fulfillment type for the order associated with the user of the third computing device.

20. The non-transitory computer-readable medium of claim 18, wherein the additional details for the order associated with the user of the second computing device comprise information indicative of one or more locations of items for the order associated with the user of the second computing device.
