

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417500
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Lane; Richard et al.

Visual depiction of warnings and errors

Abstract

Methods, systems and computer-readable storage media disclosed herein provide visual depictions of warnings and errors. An example method includes detecting, using a computing device, a change in a design of a trading algorithm. The trading algorithm is defined by a user-specified arrangement of blocks representing trading functionality. The example method includes determining, using the computing device, whether the trading algorithm complies with a trading algorithm rule. The example method includes facilitating, using the computing device, at least one of warning handling or error handling when the trading algorithm does not comply with the trading algorithm rule. Facilitating warning handling or error handling includes displaying a warning or an error to the user in connection with the trading algorithm before the trading algorithm is available for execution.

Inventors:	Lane; Richard (Chicago, IL), DeArment; Gregory (New York, NY)
Applicant:	TRADING TECHNOLOGIES INTERNATIONAL, INC. (Chicago, IL)
Family ID:	1000008820937
Assignee:	Trading Technologies International, Inc. (Chicago, IL)
Appl. No.:	18/538128
Filed:	December 13, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240112263 A1	Apr. 04, 2024

Related U.S. Application Data

continuation parent-doc US 17956240 20220929 US 11887190 child-doc US 18538128
continuation parent-doc US 16985706 20200805 US 11501372 20221115 child-doc US 17956240

Publication Classification

Int. Cl.: **G06Q40/00** (20230101); **G06Q20/10** (20120101); **G06Q40/04** (20120101); **G06Q40/06** (20120101)

U.S. Cl.:

CPC **G06Q40/04** (20130101);

Field of Classification Search

CPC: G06Q (40/04); G06Q (40/00)

USPC: 705/37

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7680721	12/2009	Cutler	705/37	G06Q 40/04
7702569	12/2009	Tanpoco	705/37	G06Q 40/00
7882014	12/2010	Shapiro	705/37	G06Q 40/03
8156036	12/2011	Waelbroeck	705/37	G06Q 40/03
8442885	12/2012	Carrie et al.	N/A	N/A
10007949	12/2017	Lane et al.	N/A	N/A
10789646	12/2019	Lane et al.	N/A	N/A
2006/0129485	12/2005	Badenhorst et al.	N/A	N/A
2011/0093378	12/2010	Lane et al.	N/A	N/A
2011/0093379	12/2010	Lane	705/37	G06Q 40/04
2012/0233054	12/2011	O'Connor	705/37	G06Q 40/00
2018/0276752	12/2017	Lane et al.	N/A	N/A
2020/0364792	12/2019	Lane et al.	N/A	N/A

OTHER PUBLICATIONS

International Search Report of International Application No. PCT/US2013/035641 dated May 15, 2013 (mailed Jun. 3, 2013). cited by applicant

Google NPL Search dated Jan. 13, 2022. cited by applicant

Google Scholar Search dated Jan. 13, 2022. cited by applicant

Dialog Search Results, dated Jun. 17, 2022. cited by applicant

Primary Examiner: Tran; Hai

Attorney, Agent or Firm: MCDONNELL BOEHNEN HULBERT & BERGHOFF LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/956,240, filed Sep. 29, 2022, which is a continuation of U.S. patent application Ser. No. 16/985,706 filed Aug. 5, 2020, now U.S. Pat. No. 11,501,372, which is a continuation of U.S. patent application Ser. No. 15/989,851, filed May 25, 2018, now U.S. Pat. No. 10,789,646, which is a continuation of U.S. patent application Ser. No. 13/655,926, filed Oct. 19, 2012, now U.S. Pat. No. 10,007,949, each of which is herein incorporated herein by reference in its entirety for all purposes.

BACKGROUND

(1) An electronic trading system generally includes a trading device in communication with an electronic exchange. The electronic exchange sends information about a market, such as prices and quantities, to the trading device. The trading device sends messages, such as messages related to orders, to the electronic exchange. The electronic exchange attempts to match quantity of an order with quantity of one or more contra-side orders.

(2) In some electronic trading systems, the trading device receives and processes market data without displaying the market data on a display device. For example, a “black box” algorithmic trading system may run automatically and without displaying market data. However, in other electronic trading systems, the trading device displays processed market data on a display device. The trading device may include software that creates a trading interface. In general, a trading interface is a tool that enables a user to interact and exchange information with the electronic exchange. For example, a trading interface may enable a user to view market data, submit a trade order to the electronic exchange, obtain a market quote, monitor a position, and/or combinations thereof.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) Certain embodiments are disclosed with reference to the following drawings.

(2) FIG. 1 illustrates a block diagram of an example electronic trading system in which certain embodiments may be employed.

(3) FIG. 2 illustrates a block diagram of another exemplary electronic trading system in which certain embodiments may be employed.

(4) FIG. 3 illustrates a block diagram of an example computing device which may be used to implement certain embodiments.

(5) FIG. 4 illustrates a block diagram of another exemplary electronic trading system in which certain embodiments may be employed.

(6) FIG. 5 illustrates a trading interface according to certain embodiments.

(7) FIG. 6 illustrates examples of blocks that may be used in the trading interface of certain embodiments.

(8) FIG. 7 illustrates another example trading interface according to certain embodiments.

(9) FIG. 8 illustrates another example trading interface according to certain embodiments.

(10) FIG. 9 illustrates another example trading interface according to certain embodiments.

(11) FIG. 10 illustrates another example trading interface according to certain embodiments.

(12) FIG. 11 illustrates a block diagram of the example warning and error manager of FIG. 4.

(13) FIG. 12 illustrates a flow diagram of an example method for managing warnings and errors in an electronic trading system.

(14) FIG. 13 illustrates a flow diagram of another example method for managing warnings and errors in an electronic trading system.

(15) FIG. 14 illustrates a flow diagram of another example method for managing warnings and

errors in an electronic trading system.

(16) Certain embodiments will be better understood when read in conjunction with the provided drawings, which illustrate examples. It should be understood, however, that the embodiments are not limited to the arrangements and instrumentality shown in the attached drawings.

DESCRIPTION

I. Brief Description of Certain Embodiments

(17) Embodiments disclosed herein provide systems, methods, and computer-readable media to detect problems within a trading algorithm and to visually identify these problems in a trading interface to assist a user in the evaluation and/or correction of the detected problems. The trading interface as used herein includes the processes and programs to interact with an exchange, create trading strategies, and analyze information. In certain examples, the trading interface may include one or more blocks or objects that can be configured and arranged to define a trading algorithm. For example, the trading interface may include a design canvas area configured to allow a user to visually define a trading algorithm by selecting various algorithm blocks and connecting the inputs and outputs of those blocks to create a trading algorithm that may be implemented to execute trades at an exchange. Often times, such visually designed trading algorithms may be extensive and complex making it difficult for a user to detect the presence of problems and/or errors. Problems and/or errors within a trading algorithm may be, for example, logic-based (e.g., an infinite loop) or trading-based (e.g., connecting a particular input to a particular output may result in an unintended trade).

(18) Certain embodiments disclosed herein provide a verification tool to continually analyze trading algorithms according to rules designed to detect various logic-based and trading-based problems and/or errors that may exist within trading algorithms. In certain embodiments, when a user makes a change to a trading algorithm (e.g., selecting a new algorithm block and connecting it to other algorithm blocks), the verification tool checks the trading algorithm blocks and/or their associated connections with other trading algorithm blocks against the rules to detect any problems and/or errors within the trading algorithm.

(19) In certain embodiments, the verification tool, upon detection of a violation of one or more rules may generate an error to be displayed to a user via the trading interface. In such an embodiment, the error may include a visual depiction of the error (e.g., the algorithm blocks and/or connections in violation of a rule may be highlighted), text related to the error (e.g., an explanation of the violation, a suggestion to remedy the violation, etc.), or other information related to the error. In certain embodiments, providing an error to a user prevents the trading algorithm from being executed (e.g., the trading algorithm may not be implemented to execute a trade at an exchange).

(20) In certain embodiments, upon detection of a violation of one or more rules by the verification tool, the trading interface may display a warning on the design canvas that indicates existence of a problem associated with a trading algorithm block and/or connection. In such an embodiment, the displayed warning may include a visual depiction of the source of the warning (e.g., the algorithm blocks and/or connections in violation of a rule may be highlighted), text related to the warning (e.g., an explanation of the violation, a suggestion to remedy the violation, etc.), or other information related to the warning. In certain embodiments, providing a warning to a user does not prevent the trading algorithm from being executed (e.g., the trading algorithm may be implemented to execute a trade at an exchange).

(21) In certain embodiments, a warning may be ignored by a user (e.g., the user may select an ignore button that removes the warning from display). In certain embodiments, a log of ignored warnings is kept such that an ignored warning is not displayed again. In certain embodiments, if a warning is remedied by a user (e.g., the user alters the trading algorithm such that the trading algorithm complies with the rules), the warning is removed from the ignored warnings log.

(22) Although the description discloses embodiments including, among other components, software executed on hardware, it should be noted that the embodiments are merely illustrative and should

not be considered as limiting. For example, it is contemplated that any or all of these hardware and software components may be embodied exclusively in hardware, exclusively in software, exclusively in firmware, or in any combination of hardware, software, and/or firmware. Accordingly, certain embodiments may be implemented in other ways.

(23) Certain embodiments provide methods, systems and computer-readable storage media to provide visual depictions of warnings and errors.

(24) Certain embodiments provide a method including detecting, using a computing device, a change in a design of a trading algorithm. The trading algorithm is defined by a user-specified arrangement of blocks representing trading functionality. The example method includes determining, using the computing device, whether the trading algorithm complies with a trading algorithm rule. The example method includes facilitating, using the computing device, at least one of warning handling or error handling when the trading algorithm does not comply with the trading algorithm rule. Facilitating warning handling or error handling includes displaying a warning or an error to the user in connection with the trading algorithm before the trading algorithm is available for execution.

(25) Certain embodiments provide a system including a change detector to detect a change in a design of a trading algorithm. The trading algorithm is defined by a user-specified arrangement of blocks representing trading functionality. The example system includes a rules applier to determine whether the trading algorithm complies with a trading algorithm rule. The example system includes a facilitator to facilitate at least one of warning handling or error handling when the trading algorithm does not comply with the trading algorithm rule. Facilitating warning handling or error handling includes displaying a warning or an error to the user in connection with the trading algorithm before the trading algorithm is available for execution.

(26) Certain embodiments provide a tangible computer-readable storage medium including instructions that, when executed, cause a computing device to at least detect a change in a design of a trading algorithm. The trading algorithm is defined by a user-specified arrangement of blocks representing trading functionality. The example computer-readable medium includes instructions that, when executed, cause the computing device to determine whether the trading algorithm complies with a trading algorithm rule. The example computer-readable medium includes instructions that, when executed, cause the computing device to facilitate at least one of warning handling or error handling when the trading algorithm does not comply with the trading algorithm rule. Facilitating warning handling or error handling includes displaying a warning or an error to the user in connection with the trading algorithm before the trading algorithm is available for execution.

II. Example Electronic Trading System

(27) FIG. 1 illustrates a block diagram representative of an exemplary electronic trading system **100** in which certain embodiments may be employed. The system **100** includes a trading device **110**, a gateway **120**, and an exchange **130**. The trading device **110** is in communication with the gateway **120**. The gateway **120** is in communication with the exchange **130**. As used herein, the phrase “in communication” encompasses direct communication and/or indirect communication through one or more intermediary components. The exemplary electronic trading system **100** depicted in FIG. 1 may be in communication with additional components, subsystems, and elements to provide additional functionality and capabilities without departing from the teaching and disclosure provided herein.

(28) In operation, the trading device **110** may receive market data from the exchange **130** through the gateway **120**. A user may utilize the trading device **110** to monitor this market data and/or base a decision to send an order message to buy or sell one or more tradeable objects to the exchange **130**.

(29) Market data may include data about a market for a tradeable object. For example, market data may include the inside market, market depth, last traded price (“LTP”), a last traded quantity

(“LTQ”), or a combination thereof. The inside market is the lowest available ask price (best offer) and the highest available bid price (best bid) in the market for a particular tradable object at a particular point in time (since the inside market may vary over time). Market depth refers to quantities available at the inside market and at other prices away from the inside market. Due to the quantity available, there may be “gaps” in market depth.

(30) A tradeable object is anything which may be traded. For example, a certain quantity of the tradeable object may be bought or sold for a particular price. A tradeable object may include financial products, stocks, options, bonds, future contracts, currency, warrants, funds derivatives, securities, commodities, swaps, interest rate products, index-based products, traded events, goods, or a combination thereof. A tradeable object may include a product listed and/or administered by an exchange (for example, the exchange **130**), a product defined by the user, a combination of real or synthetic products, or a combination thereof. There may be a synthetic tradeable object that corresponds and/or is similar to a real tradeable object.

(31) An order message is a message that includes a trade order. A trade order may be, for example, a command to place an order to buy or sell a tradeable object, a command to initiate managing orders according to a defined trading strategy, a command to change or cancel a previously submitted order (for example, modify a working order), an instruction to an electronic exchange relating to an order, or a combination thereof.

(32) The trading device **110** may include one or more electronic computing platforms. For example, the trading device **110** may include a desktop computer, hand-held device, laptop, server, a portable computing device, a trading terminal, an embedded trading system, a workstation, an algorithmic trading system such as a “black box” or “grey box” system, cluster of computers, or any combination thereof. As another example, the trading device **110** may include a single or multi-core processor in communication with a memory or other storage medium configured to accessibly store one or more computer programs, applications, libraries, computer readable instructions, and the like, for execution by the processor.

(33) As used herein, the phrases “configured to” and “adapted to” encompass that an element, structure, or device has been modified, arranged, changed, or varied to perform a specific function or for a specific purpose.

(34) By way of example, the trading device **110** may be implemented as a personal computer running a copy of X_TRADER®, an electronic trading platform provided by Trading Technologies International, Inc. of Chicago, Illinois (hereinafter referred to as “Trading Technologies”). As another example, the trading device **110** may be a server running a trading application providing automated trading tools such as ADL™, AUTOSPREADER®, and/or AUTOTRADER™, also provided by Trading Technologies. In yet another example, the trading device **110** may include a trading terminal in communication with a server, where collectively the trading terminal and the server are the trading device **110**.

(35) The trading device **110** is generally owned, operated, controlled, programmed, configured, or otherwise used by a user. As used herein, the phrase “user” may include, but is not limited to, a human (for example, a trader), trading group (for example, group of traders), or an electronic trading device (for example, an algorithmic trading system). One or more users may be involved in the ownership, operation, control, programming, configuration, or other use, for example.

(36) The trading device **110** may include one or more trading applications. As used herein, a trading application is an application that facilitates or improves electronic trading. A trading application provides one or more electronic trading tools. For example, a trading application stored by a trading device may be executed to arrange and display market data in one or more trading windows. In another example, a trading application may include an automated spread trading application providing spread trading tools. In yet another example, a trading application may include an algorithmic trading application that automatically processes an algorithm and performs certain actions, such as placing an order, modifying an existing order, deleting an order. In yet

another example, a trading application may provide one or more trading screens. A trading screen may provide one or more trading tools that allow interaction with one or more markets. For example, a trading tool may allow a user to obtain and view market data, set order entry parameters, submit order messages to an exchange, deploy trading algorithms, and/or monitor positions while implementing various trading strategies. The electronic trading tools provided by the trading application may always be available or may be available only in certain configurations or operating modes of the trading application.

(37) A trading application may include computer readable instructions that are stored in a computer readable medium and executable by a processor. A computer readable medium may include various types of volatile and non-volatile storage media, including, for example, random access memory, read-only memory, programmable read-only memory, electrically programmable read-only memory, electrically erasable read-only memory, flash memory, any combination thereof, or any other tangible data storage device. As used herein, the term non-transitory or tangible computer readable medium is expressly defined to include any type of computer readable storage media and to exclude propagating signals.

(38) One or more components or modules of a trading application may be loaded into the computer readable medium of the trading device **110** from another computer readable medium. For example, the trading application (or updates to the trading application) may be stored by a manufacturer, developer, or publisher on one or more CDs or DVDs, which are then loaded onto the trading device **110** or to a server from which the trading device **110** retrieves the trading application. As another example, the trading device **110** may receive the trading application (or updates to the trading application) from a server, for example, via the Internet or an internal network. The trading device **110** may receive the trading application or updates when requested by the trading device **110** (for example, “pull distribution”) and/or un-requested by the trading device **110** (for example, “push distribution”).

(39) The trading device **110** may be adapted to send order messages. For example, the order messages may be sent to through the gateway **120** to the exchange **130**. As another example, the trading device **110** may be adapted to send order messages to a simulated exchange in a simulation environment which does not effectuate real-world trades.

(40) The order messages may be sent at the request of a user. For example, a trader may utilize the trading device **110** to send an order message or manually input one or more parameters for a trade order (for example, an order price and/or quantity). As another example, an automated trading tool provided by a trading application may calculate one or more parameters for a trade order and automatically send the order message. In some instances, an automated trading tool may prepare the order message to be sent but not actually send it without confirmation from a user.

(41) An order message may be sent in one or more data packets or through a shared memory system. For example, an order message may be sent from the trading device **110** to the exchange **130** through the gateway **120**. The trading device **110** may communicate with the gateway **120** using a local area network, a wide area network, a wireless network, a virtual private network, a T1 line, a T3 line, an integrated services digital network (“ISDN”) line, a point-of-presence, the Internet, and/or a shared memory system, for example.

(42) The gateway **120** may include one or more electronic computing platforms. For example, the gateway **120** may implemented as one or more desktop computer, hand-held device, laptop, server, a portable computing device, a trading terminal, an embedded trading system, workstation with a single or multi-core processor, an algorithmic trading system such as a “black box” or “grey box” system, cluster of computers, or any combination thereof.

(43) The gateway **120** may facilitate communication. For example, the gateway **120** may perform protocol translation for data communicated between the trading device **110** and the exchange **130**. The gateway **120** may process an order message received from the trading device **110** into a data format understood by the exchange **130**, for example. Similarly, the gateway **120** may transform

market data in an exchange-specific format received from the exchange **130** into a format understood by the trading device **110**, for example.

(44) The gateway **120** may include a trading application, similar to the trading applications discussed above, that facilitates or improves electronic trading. For example, the gateway **120** may include a trading application that tracks orders from the trading device **110** and updates the status of the order based on fill confirmations received from the exchange **130**. As another example, the gateway **120** may include a trading application that coalesces market data from the exchange **130** and provides it to the trading device **110**. In yet another example, the gateway **120** may include a trading application that provides risk processing, calculates implieds, handles order processing, handles market data processing, or a combination thereof.

(45) In certain embodiments, the gateway **120** communicates with the exchange **130** using a local area network, a wide area network, a virtual private network, a T1 line, a T3 line, an ISDN line, a point-of-presence, the Internet, and/or a shared memory system, for example.

(46) The exchange **130** may be owned, operated, controlled, or used by an exchange entity.

Example exchange entities include the CME Group, the London International Financial Futures and Options Exchange, the IntercontinentalExchange, and Eurex. The exchange **130** may include an electronic matching system, such as a computer, server, or other computing device, which is adapted to allow tradeable objects, for example, offered for trading by the exchange, to be bought and sold. The exchange **130** may include separate entities, some of which list and/or administer tradeable objects and others which receive and match orders, for example. The exchange **130** may include an electronic communication network (“ECN”), for example.

(47) The exchange **130** may be an electronic exchange. The exchange **130** is adapted to receive order messages and match contra-side trade orders to buy and sell tradeable objects. Unmatched trade orders may be listed for trading by the exchange **130**. The trade orders may include trade orders received from the trading device **110** or other devices in communication with the exchange **130**, for example. For example, typically the exchange **130** will be in communication with a variety of other trading devices (which may be similar to trading device **110**) which also provide trade orders to be matched.

(48) The exchange **130** is adapted to provide market data. Market data may be provided in one or more messages or data packets or through a shared memory system. For example, the exchange **130** may publish a data feed to subscribing devices, such as the trading device **110** or gateway **120**. The data feed may include market data.

(49) The system **100** may include additional, different, or fewer components. For example, the system **100** may include multiple trading devices, gateways, and/or exchanges. In another example, the system **100** may include other communication devices, such as middleware, firewalls, hubs, switches, routers, servers, exchange-specific communication equipment, modems, security managers, and/or encryption/decryption devices.

III. Expanded Example Electronic Trading System

(50) FIG. 2 illustrates a block diagram of another exemplary electronic trading system **200** in which certain embodiments may be employed. In this example, a trading device **210a** is in communication with an exchange **230a** through a gateway **220a**. The following discussion mainly focuses on the trading device **210a**, gateway **220a**, and the exchange **230a**. However, the trading device **210a** may also be connected to and communicate with any number of gateways **220n** connected to exchanges **230n**. The communication between the trading device **110a** and other exchanges **230n** may be the same, similar, or different than the communication between the trading device **210a** and exchange **230a**. Generally, each exchange has its own preferred techniques and/or formats for communicating with a trading device, a gateway, the user, or another exchange.

(51) The trading device **210a**, which may be similar to the trading device **110** in FIG. 1, may include a server **212a** in communication with a trading terminal **214a**. The server **212a** may be located geographically closer to the gateway **120** than the trading terminal **214a**. As a result, the

server **212a** latency benefits that are not afforded to the trading terminal **214a**. In operation, the trading terminal **214a** may provide a trading screen to a user and communicate commands to the server **212a** for further processing. For example, a trading algorithm may be deployed to the server **212a** for execution based on market data. The server **212a** may execute the trading algorithm without further input from the user. In another example, the server **212a** may include a trading application providing automated trading tools and communicate back to the trading terminal **214a**. The trading device **210a** may include, additional, different, or fewer components.

(52) The trading device **210a** may communicate with the gateway **220a** using one or more communication networks. As used herein, a communication network is any network, including the Internet, which facilitates or enables communication between, for example, the trading device **210a**, the gateway **220a** and the exchange **230a**. For example, as shown in FIG. 2, the trading device **210a** may communicate with the gateway **220a** across a multicast communication network **202a**. The data on the network **202a** may be logically separated by subject (for example, prices, orders, or fills). As a result, the server **212a** and trading terminal **214a** can subscribe to and receive data (for example, data relating to prices, orders, or fills) depending on their individual needs.

(53) The gateway **220a**, which may be similar to the gateway **120** of FIG. 1, may include a price server **222a**, order server **224a**, and fill server **226a**. The gateway **220a** may include additional, different, or fewer components. The price server **222a** may process price data. Price data includes data related to a market for one or more tradeable objects. The order server **224a** may process order data. Order data is data related to a user's trade orders. For example, order data may include order messages, confirmation messages, or other types of messages. The fill server collects and provides fill data. Fill data includes data relating to one or more fills of trade orders. For example, the fill server **226a** may provide a record of trade orders, which have been routed through the order server **224a**, that have and have not been filled. The servers **222a**, **224a**, **226a** may run on the same machine or separate machines.

(54) The gateway **220a** may communicate with the exchange **230a** using one or more communication networks. For example, as shown in FIG. 2, there may be two communication networks connecting the gateway **220a** and the exchange **230a**. The network **204a** may be used to communicate market data to the price server **222a**. In some instances, the exchange **230a** may include this data in a data feed that is published to subscribing devices. The network **206a** may be used to communicate order data.

(55) The exchange **230a**, which may be similar to the exchange **130** of FIG. 1, may include an order book **232a** and a matching engine **234a**. The exchange **230a** may include additional, different, or fewer components. The order book **232a** is a database that includes data relating to unmatched quantity of trade orders. For example, an order book may include data relating to a market for a tradeable object, such as the inside market, market depth at various price levels, the last traded price, and the last traded quantity. The matching engine **234a** may match contra-side bids and offers. For example, the matching engine **234a** may execute one or more matching algorithms that match contra-side bids and offers. A sell order is contra-side to a buy order with the same price. Similarly, a buy order is contra-side to a sell order with the same price.

(56) In operation, the exchange **230a** may provide price data from the order book **232a** to the price server **222a** and order data and/or fill data from the matching engine **234a** to the order server **224a**. Servers **222a**, **224a**, **226a** may translate and communicate this data back to the trading device **210a**. The trading device **210a**, for example, using a trading application, may process this data. For example, the data may be displayed to a user. In another example, the data may be utilized in a trading algorithm to determine whether a trade order should be submitted to the exchange **230a**. The trading device **210a** may prepare and send an order message to the exchange **230a**.

(57) In certain embodiments, the gateway **220a** is part of the trading device **210a**. For example, the components of the gateway **220a** may be part of the same computing platform as the trading device **210a**. As another example, the functionality of the gateway **220a** may be performed by components

of the trading device **210a**. In certain embodiments, the gateway **220a** is not present. Such an arrangement may occur when the trading device **210a** does not need to utilize the gateway **220a** to communicate with the exchange **230a**, for example. For example, if the trading device **210a** has been adapted to communicate directly with the exchange **230a**.

(58) Additional trading devices **210b-210e**, which are similar to trading device **210a**, may be connected to one or more of the gateways **220a-220n** and exchanges **230a-230n**. Furthermore, additional gateways, similar to the gateway **220a**, may be in communication with multiple exchanges, similar to the exchange **230a**. Each gateway may be in communication with one or more different exchanges, for example. Such an arrangement may, for example, allow one or more trading devices **210a** to trade at more than one exchange (and/or provide redundant connections to multiple exchanges).

IV. Example Computing Device

(59) FIG. 3 illustrates a block diagram of an example computing device **300** which may be used to implement the disclosed embodiments. The trading device **110** of FIG. 1 may include one or more computing devices **300**, for example. The gateway **120** of FIG. 1 may include one or more computing devices **300**, for example. The exchange **130** of FIG. 1 may include one or more computing devices **300**, for example. The computing device **300** may include additional, different, or fewer components.

(60) The computing device **300** includes a communication network **310**, a processor **312**, a memory **314**, an interface **316**, an input device **318**, and an output device **320**. The computing device **200** may include additional, different, or fewer components. For example, multiple communication networks, multiple processors, multiple memory, multiple interfaces, multiple input devices, multiple output devices, or any combination thereof, may be provided. As another example, the computing device **300** may not include an input device **318** or output device **320**.

(61) As shown in FIG. 3, the computing device **300** may include a processor **312** coupled to a communication network **310**. The communication network **310** may include a communication bus, channel, network, circuit, switch, fabric, or other mechanism for communicating data between components in the computing device **300**. The communication network **310** may be communicatively coupled with and transfer data between any of the components of the computing device **300**.

(62) The processor **312** may be any suitable processor, processing unit, or microprocessor. The processor **312** may include one or more general processors, digital signal processors, application specific integrated circuits, field programmable gate arrays, analog circuits, digital circuits, programmed processors, and/or combinations thereof, for example. The processor **312** may be a single device or a combination of devices, such as one or more devices associated with a network or distributed processing. Any processing strategy may be used, such as multi-processing, multi-tasking, parallel processing, and/or remote processing. Processing may be local or remote and may be moved from one processor to another processor. In certain embodiments, the computing device **300** is a multi-processor system and, thus, may include one or more additional processors which are communicatively coupled to the communication network **310**.

(63) The processor **312** may be operable to execute logic and other computer readable instructions encoded in one or more tangible media, such as the memory **314**. As used herein, logic encoded in one or more tangible media includes instructions which may be executable by the processor **312** or a different processor. The logic may be stored as part of software, hardware, integrated circuits, firmware, and/or micro-code, for example. The logic may be received from an external communication device via a communication network such as the network **340**. The processor **312** may execute the logic to perform the functions, acts, or tasks illustrated in the figures or described herein.

(64) The memory **314** may be one or more tangible media, such as computer readable storage media, for example. Computer readable storage media may include various types of volatile and

non-volatile storage media, including, for example, random access memory, read-only memory, programmable read-only memory, electrically programmable read-only memory, electrically erasable read-only memory, flash memory, any combination thereof, or any other tangible data storage device. As used herein, the term non-transitory or tangible computer readable medium is expressly defined to include any type of computer readable medium and to exclude propagating signals. The memory **314** may include any desired type of mass storage device including hard disk drives, optical media, magnetic tape or disk, etc.

(65) The memory **314** may include one or more memory devices. For example, the memory **314** may include local memory, a mass storage device, volatile memory, non-volatile memory, or a combination thereof. The memory **314** may be adjacent to, part of, programmed with, networked with, and/or remote from processor **312**, so the data stored in the memory **314** may be retrieved and processed by the processor **312**, for example. The memory **314** may store instructions which are executable by the processor **312**. The instructions may be executed to perform one or more of the acts or functions described herein or shown in the figures.

(66) The memory **314** may store a trading application **330**. In certain embodiments, the trading application **330** may be accessed from or stored in different locations. The processor **312** may access the trading application **330** stored in the memory **314** and execute computer-readable instructions included in the trading application **330**.

(67) In certain embodiments, during an installation process, the trading application may be transferred from the input device **318** and/or the network **340** to the memory **314**. When the computing device **300** is running or preparing to run the trading application **330**, the processor **312** may retrieve the instructions from the memory **314** via the communication network **310**.

V. Example Embodiments to Provide Visual Depictions of Warnings and Errors

(68) FIG. 4 illustrates a block diagram representative of an exemplary electronic trading system **400** in which certain embodiments may be employed. The system **400** includes the trading device **110**, the gateway **120**, and the exchange **130** of FIG. 1. The trading device **120** may include hardware and software configured to generate an exemplary trading interface **402** having a trading algorithm design tool **500** (see FIG. 5). The gateway **120** and the exchange **130** of FIG. 4 have been described above with reference to FIG. 1 and, thus, will not be described in detail with reference to FIG. 4. The system **400** further includes an algorithm (“algo”) server **404** in communication with the trading device **110** and the gateway **120**. The exemplary electronic trading system **400** depicted in FIG. 4 may be in communication with additional components, subsystems, and elements to provide additional functionality and capabilities without departing from the teaching and disclosure provided herein.

(69) In operation, a user may interact with the trading interface **402** operable on the trading device **110** to send orders to buy or sell tradeable objects at the exchange **130**. For example, a user may utilize the trading interface **402** to specify the details (e.g., buy/sell, contract, price, quantity) of an order and the trading device **110** transmits the orders. The orders may be routed through the algorithm server **404** and/or the gateway **120** to the exchange **130**. In addition, market data is broadcast from the exchange **130** through the gateway **120** and/or the algorithm server **404** to the trading device **110**. The user may further utilize the trading interface **402** operable on the trading device **110** to monitor market data and/or base a decision to send an order for a tradeable object based on conditions described in the market data.

(70) In certain embodiments, the algorithm server **404**, among other things, is configured to execute programming code corresponding to trading algorithms received from the trading device **110**. In certain embodiments, the algorithm server **404** is located at the same site as the trading device **110**. In certain embodiments, the algorithm server **404** is physically located at a site separate from both the trading device **110** and the gateway **120**.

(71) The algorithm server **404** is configured to receive, compile, store and execute one or more trading algorithms, programming code corresponding to the trading algorithms, one or more

identifiers corresponding to the programming code and/or trading algorithms, or any combination thereof. The algorithm server **404** may, in one example, include one or more processors and one or more processor-readable media for storing such information.

(72) In certain embodiments, the gateway **120** facilitates communication between the trading device **110** and/or the algorithm server **404** and the exchange **130**. For example, the gateway **120** may receive orders from the trading device **110** and/or the algorithm server **404** and transmit the orders to the exchange **130**. As another example, the gateway **120** may receive market data from the exchange **130** and transmit the market data to the algorithm server **404** and/or the trading device **110**.

(73) In certain embodiments, the algorithm server **404** is part of the trading device **110**. For example, the components of the algorithm server **404** may be part of the same computing platform as the trading device **110**. As another example, the functionality of the algorithm server **404** may be performed by components of the trading device **110**.

(74) In operation, a trading algorithm for autonomous or semi-autonomous electronic trading may be designed via the trading interface **402** operable on the trading device **110**. The trading algorithm may, in turn, be communicated to the algorithm server **404** for compiling and/or execution. The trading algorithm may be designed and/or configured utilizing the trading algorithm design tool **500** (“the tool **500**”) and the trading interface **402** operable on the trading device **110**. For example, a visual trading algorithm design program such as Algo Design Lab (“ADLTM”) provided by Trading Technologies of Chicago, Illinois may be utilized to construct one or more trading algorithms. The visual trading algorithm design program may include trading algorithm design tool **500** of the trading interface **402**. The tool **500** provides an area (see the design canvas area **511** shown in FIG. 5) in which one or more blocks or objects can be configured and arranged to define a trading algorithm. In some examples, blocks are graphical representations of trading-related logic. In some examples, the blocks represent complex functionality for use in a trading algorithm. In some examples, the trading algorithm design tool **500** provides for grouping blocks placed in the design canvas area **511** (see FIG. 5). In some examples, the tool **500** provides for virtualized group blocks enabling dynamic instantiation of portions of an algorithm to handle particular discrete events. In some examples, the tool **500** allows for rapidly adjusting both the parameters and the logic of a trading algorithm, even during a single trading session. In some examples, the tool **500** provides live feedback for blocks as the trading algorithm is being designed. In some examples, the tool **500** provides for operation of some or all portions of a trading algorithm when a connection between the client device **110** and the algorithm server **404** terminates.

(75) In some examples, the tool **500** provides safety features to reduce potential errors when a trading algorithm is designed. In some examples, the tool **500** reduces the risks of traditionally programmed algorithms such as syntax errors, unclear logic, and the need for a non-trader programmer to develop the algorithm as specified by a trader by reducing or eliminating the writing of programming code by a user. In some examples, the tool **500** provides a single application for building, debugging, and simulating (with real market data) a trading algorithm all at the same time. In addition, the trading interface **402**, with or without the tool **500**, may also provide for initiating the placement of orders using the trading algorithm. The trading interface **402** in general and the tool **500** are described in greater detail below with reference to FIGS. 4-6.

(76) In certain embodiments, the tool **500** and/or the trading interface **402** include or incorporate a warning and error manager **406** to detect potential problems and/or errors within a trading algorithm designed at the trading device **110**. In certain embodiments, the warning and error manager **406** identifies problems within a trading algorithm to facilitate identification and correction of a problem for the user. The warning and error manager **406** detects problems and/or errors within a trading algorithm that are logic-based and/or trading-based. For example, some problems may relate to structural components of a trading algorithm (e.g., an infinite loop) and some problems may relate to semantics of the trading algorithm (e.g., connecting a particular input

to a particular output may result in an unintended trade, a particular connection may place an order at an incorrect price, etc.).

(77) In certain embodiments, the warning and error manager **406** stores various rules related to problems and/or errors within trading algorithms. For example, patterns and/or scenarios related to problems within a trading algorithm are identified and rules are created to define those problems. In certain embodiments, rules are stored in the warning and error manager **406** for specific types of trading algorithm blocks. For example, a first trading algorithm block may be a single order block associated with a variety of logic-based rules and/or trading-based rules, while a second trading algorithm block may be a spread fill generator block associated with the same or different logic-based rules and/or trading-based rules. Moreover, some trading algorithm blocks may not have any rules associated with them. The logic-based rules and/or trading-based rules may be based on the type of algorithm block they are associated with and/or the connections that are made with the algorithm block. For example, a particular output may not be connected with a particular input of certain trading algorithm blocks. In some examples, a first trading algorithm block may not be connected to a second trading algorithm block. In some examples, certain connections may violate a rule even where there are intervening blocks contained in the trading algorithm (e.g., an unrelated block may be connected between two blocks that violate a rule).

(78) In certain embodiments, when a user makes a change to a trading algorithm (e.g., selecting a new algorithm block and connecting it to other algorithm blocks) at the trading device **110**, the warning and error manager **406** checks the trading algorithm blocks and/or their associated connections with other trading algorithm blocks against the rules to detect any problems and/or errors within the trading algorithm.

(79) In certain embodiments, if the warning and error manager **406** detects a violation of a rule by a trading algorithm block and/or connection, the warning and error manager **406** causes an error to be displayed via the trading interface **402**. The error may include a visual depiction of the error (e.g., the algorithm blocks and/or connections in violation of a rule may be highlighted), text related to the error (e.g., an explanation of the violation, a suggestion to remedy the violation, etc.), or other information related to the error. In certain embodiments, when the warning and error manager **406** detects an error in the trading algorithm, the warning and error manager **406** prevents execution of the trading algorithm (e.g., the trading algorithm may not be implemented to execute a trade at the exchange **130**) until the detected error is remedied (e.g., the trading algorithm no longer violates a rule).

(80) In certain embodiments, if the warning and error manager **406** detects a violation of a rule by a trading algorithm block and/or connection, the warning and error manager **406** causes a warning to be displayed to the user via the trading interface **402**. The warning may include a visual depiction of the warning (e.g., the algorithm blocks and/or connections in violation of a rule may be highlighted), text related to the warning (e.g., an explanation of the violation, a suggestion to remedy the violation, etc.), or other information related to the warning. In certain embodiments, when the warning and error manager **406** detects a warning in the trading algorithm, the warning and error manager **406** allows the trading algorithm to be executed (e.g., the trading algorithm may be implemented to execute a trade at the exchange **130**). Thus, in certain embodiments, a warning may be ignored by a user at the trading device **110** (e.g., the user may select an ignore button that removes the warning from display).

(81) In certain embodiments, the warning and error manager **406** stores a list of ignored warnings. If a warning has been actively ignored by the user, the warning and error manager **406** does not display the warning again. In certain embodiments, if a warning is remedied by the user (e.g., the user alters the trading algorithm such that the trading algorithm complies with the rules), the warning and error manager **406** removes the warning from the ignored warnings list. Thus, if the trading algorithm is later altered such that it violates the same rule and creates the same warning, the warning and error manager **406** will cause the warning to again be displayed on the trading

interface **402** for the user. Warnings and errors within a trading interface are described in greater detail below with reference to FIGS. **8-10**.

(82) The warning and error manager **406** of the illustrated example is located within the trading device **110** as a part of the trading interface **402** and/or the design tool **500**. In other examples, the warning and error manager **404** may be located in the algorithm server **404** or any other component of the system **400** in communication with the trading device **110** and/or the trading interface **402**.

(83) FIG. 5 illustrates a specific example of the trading algorithm design tool **500** that may be implemented as a part of the trading interface **402** executed by the trading device **110** (see FIGS. 1 and 4). In certain examples, the trading algorithm design tool **500** may be implemented independent of the trading interface **402**. In certain examples, the trading algorithm design tool **500** may be an add-in or upgrade to the trading interface **402**. The trading algorithm design tool **500** allows a trader to design a trading algorithm for electronic trading. In one example, the trading algorithm design tool **500** is the ADL™ program provided by Trading Technologies of Chicago, Illinois. Example trading algorithm design tools are disclosed in U.S. patent application Ser. No. 12/905,709, entitled "User-Defined Algorithm Electronic Trading," which was filed Oct. 15, 2010, and U.S. patent application Ser. No. 12/905,726, entitled "Virtualizing for User-Defined Algorithm Electronic Trading," which was filed Oct. 15, 2010, both of which are hereby incorporated by reference in their entireties.

(84) The trading algorithm design tool **500** includes a design canvas area **511**, a block list area **512**, a variable area **513**, and a control area **514**. In certain embodiments one or more of these areas may be in separate windows or toolbars. For example, the block list area **512** may be in a separate window from the design canvas area **511**.

(85) In operation, a trading algorithm is defined in the design canvas area **511** by utilizing one or more block from the block list area **512**. Default values for user-defined variables in the algorithm may be specified using the variable area **513**. Once the trading algorithm has been defined, the trading algorithm may be simulated using controls in the control area **514** to indicate how the logic of the algorithm will behave. An order to be managed according to the defined trading algorithm may then be initiated using the trading interface.

(86) The design canvas area **511** provides for defining an algorithm. The design canvas area **511** may also be referred to as a whiteboard area. The design canvas area **511** provides a visual programming environment for designing the algorithm. Designing an algorithm includes building, testing, simulating, and/or evaluating the algorithm.

(87) In the design canvas area **511**, blocks may be arranged according to the preference of the user. In certain embodiments, the design canvas area **511** includes an overview display or map that may be used to navigate through a large algorithm with many blocks. In certain embodiments, the design canvas area **511** may be zoomed in or out so that a user may see more or less of the algorithm at a time.

(88) Blocks are placed in the design canvas area **511** and connected to define the algorithm. The blocks to be placed may be selected from the block list area **512**. Once a block has been placed, it may then be connected to other placed blocks.

(89) The block list area **512** includes one or more blocks which may be selected and placed in the design canvas area **511**. Blocks represent different functionalities that may be combined according to user preference to build an algorithm.

(90) In general, blocks have inputs and outputs. However, certain blocks may have only inputs and others may have only outputs. For example, a pause block may have only an input. As another example, a number block may have only an output.

(91) Inputs and outputs of blocks are of one of two primary types: continuous or discrete. A continuous type input/output, at any particular point in time (hence continuous), has a value. A discrete type input/output receives/provides discrete events (individual messages/objects) corresponding to specific actions/events that occur at some particular point in time. When a

specific action/event occurs, a corresponding discrete event may be generated.

(92) In addition to the primary type of the input/output, an input/output may have a particular value types. For example, a continuous input might have a value type of Boolean, number, integer, floating point number, or instrument. As another example, a block may have two continuous inputs of a variable value type, where the value type for the two inputs may be Boolean or numeric, for example, but must match. As another example, a discrete output might have a value type of fill confirmation. That is, the discrete output might provide fill confirmation discrete events. As another example, a discrete output might provide more than one type of discrete event for actions such as order request confirmations (indicating an order was placed), fill confirmations (indicating an order was filled or partially filled), order change confirmations (indicating a working order parameters such as price or quantity was changed), order deletion confirmations (indicating a working order was deleted or cancelled), or trade confirmations (indicating a trade has occurred). A discrete event of a particular type may include different information than a discrete event of another type. For example, an order confirmation may include information such as an order identifier and/or an instrument. As another example, a fill confirmation discrete event may include information such as an order identifier, price, quantity, instrument, and/or time of a fill. A discrete event may include user-defined information. For example, a discrete event for a fill confirmation for a filled order for instrument A may include user-defined market information such as a bid price in instrument B at the time of the fill in instrument A.

(93) In certain embodiments, a block includes indicators of the primary type for its inputs/outputs. For example, continuous inputs/outputs may be indicated with a particular background color, foreground color, background pattern, border color, border style, shape, symbol, number, text, and/or font and discrete inputs/outputs might be indicated with another color, pattern, border, shape, symbol, number, text, and/or font.

(94) In certain embodiments, a block includes indicators of the value type for its inputs/outputs. For example, inputs/outputs with a particular value type may be indicated with a particular background color, foreground color, background pattern, border color, border style, shape, symbol, number, text, and/or font and inputs/outputs with a different value type may be indicated with another color, pattern, border, shape, symbol, number, text, and/or font.

(95) In certain embodiments, the primary type and/or the value type of an input or output is displayed in a pop-up window when a cursor is positioned near the block. In certain embodiments, information about the configuration of a block is displayed in a pop-up window when a cursor is positioned near the block.

(96) Blocks represent different functionality. In the tool **500**, blocks have been separated into four general categories of functionality: basic blocks, trading blocks, discrete blocks, and miscellaneous blocks. However, these groupings are for convenient organization and utilization by a user; blocks do not need to be grouped and a block's group does not necessitate particular features. Some blocks may appropriately fit in more than one category and other organizations or groupings of blocks may also be employed.

(97) Basic blocks generally have continuous inputs and outputs and provide arithmetic operations (for example, addition, subtraction, multiplication, and division), logical operations (for example, AND, OR, and comparison such as equality, greater than, and less than), constant values (for example, number and Boolean), and if-then-else constructs.

(98) Trading blocks generally provide more complex functionality related to manipulating an order (for example, placing an order, modifying an existing order, or deleting an order) or order-related information (for example, a fill confirmation). Trading blocks may have both continuous and discrete inputs and outputs. For example, a market maker block may have continuous inputs for specifying an instrument, price, quantity, and condition for quoting an order and may have a continuous output of the working quantity and a discrete output for providing notification of fills. Trading blocks allow users, including non-programmers (such as traders), to utilize a visual design

environment (such as that provided by the ADL™) to create, configure and deploy trading algorithms. The trading blocks may allow for more rapid and accurate design of an algorithm as compared to a typical programmer with fewer steps or instructions as compared to other visual programming platforms.

(99) Discrete blocks generally have discrete inputs and outputs and provide operations based on the occurrence of discrete events. For example, a generator block may generate an occurrence of a discrete event. As another example, a value extractor block may extract a value from a discrete event and make it available as a continuous value to another portion of the algorithm. As another example, a sequencer block may be used to control the sequence in which subsequent blocks are processed in response to a discrete event. Certain discrete blocks may store data to be referenced at a subsequent time. For example, a value accumulator block may receive a discrete event and extract a user-specified value from it. The extracted value may be accumulated with values extracted from each received discrete event.

(100) Miscellaneous blocks provide a variety of functionality that may not necessary fit into the above-discussed categories. For example, these blocks may provide special purpose or more complex calculations or may add additional control to the execution of the algorithm itself. Further, miscellaneous blocks may provide more precise tools to control risk, convert numbers into tradeable values, or use time (either precise or elapsed) as an input or variable.

(101) FIG. 6 illustrates examples of blocks **620** that may be used to construct a trading algorithm in the trading algorithm design tool **500** of FIG. 5 according to certain embodiments. Example blocks from each of the categories identified above are illustrated. Example basic blocks include the add block **621** and the if-then-else block **622**. Example trading blocks include the market maker block **623**, the conditional buy/sell block **624**, and the order handler block **625**. Example discrete blocks include the value extractor block **626** and the branch block **627**. Example miscellaneous blocks include the note block **628** and the pause block **629**.

(102) Basic blocks may include add, subtract, multiply, divide, greater than, less than, greater than or equal, less than or equal, AND, OR, equals, IF-THEN-ELSE, number, Boolean, and constant blocks, for example.

(103) Trading blocks may include instrument, instrument attribute, market maker, logger, custom spread, responsive buy/sell, conditional buy/sell, order handler, IF-THEN-ELSE instrument, instrument attribute at price, spread between, trade, order, fill calculator, and fill accumulator blocks, for example.

(104) Discrete blocks may include generator, value extractor, value accumulator, value bucket, discrete moving average, state, branch, multiplexer, funnel, sequencer, discrete min, and discrete max blocks, for example.

(105) Miscellaneous blocks may include min, max, rounding, display to decimal, not, once true, is number, moving average, conditional f(x), numeric f(x), average, timer, note, random number, square root, log, and pause blocks, for example.

(106) FIG. 7 illustrates an example of the trading algorithm design tool **500** generally indicated by the reference numeral **700**. The example trading algorithm design tool **700** includes various algorithm blocks connected to define a simple trading algorithm **702**. The trading algorithm **702** provides a mechanism to buy ten (10) instruments (i.e., instruments represented by the GCJ1 identifier) at a price of 12954 and return the price at which those instruments were purchased. In this example, the trading algorithm design tool **500** (**700** in the present example) provides a live feedback feature that provides a display of a value for the particular block.

(107) Instructions or logic (herein referred to as programming code) representing the algorithm are generated based on the definition of the algorithm. In some examples, the programming code is source code (such as human and/or compiler readable text) which may subsequently be compiled. In some examples, the programming code is in an intermediate language. In some examples, the programming code includes machine-executable instructions. In some examples, generation of

programming code includes compilation of generated source code and/or intermediate language code. In some examples, generation of programming code does not include compilation of generated source code and/or intermediate language code and such compilation is a separate process. The generated programming code (after compilation, if appropriate) may then be simulated and/or used to trade according to the defined algorithm. As used herein, where programming code is discussed to be run, executed, and/or simulated, it is assumed that the generated programming code has additionally been compiled, if appropriate to be run, executed, and/or simulated.

(108) In some examples, the programming code is generated as the algorithm is being designed. Note that while the algorithm is being designed and/or configured, the definition of the algorithm may be changing as blocks and/or connections are added, modified, and/or removed. In some examples, the programming code is generated automatically when a change is made to the algorithm definition. In some examples, the programming code is generated at the request of a user.

(109) In some examples, the programming code is generated when the trading algorithm **702** is compiled by the tool **500** of FIG. 5 at a client device (e.g., the trading device **110** of FIGS. 1 and/or 4). In some examples, the programming code is generated by a component of the algorithmic trading application at another device, such as a algorithm generation device, an algorithm server similar to the algorithm server **404** discussed above with reference to FIG. 4, and/or a gateway similar to the gateway **120** discussed above with reference to FIGS. 1 and/or 4, for example. In some examples, the programming code is generated by more than one component. For example, multiple components of the algorithmic trading application may work together to generate the code. Such components may be specialized to generate different aspects or functionalities of the programming code, for example. In some examples, the generated programming code is done in an object-oriented manner using a programming language such as C# and the .NET 4.0 framework. In some examples, the programming code is generated by traversing each block and connection in the algorithm definition. For each block, programming code is generated.

(110) Continuous connections between blocks specify how the connected output values and input values relate. Discrete connections between blocks are used to generate event generators and event handlers so that the proper method (the handler) is invoked when a discrete event is generated. The discrete event is passed from the event generator to the event handler to be processed. When running, the algorithm responds to actions that cause the state of the algorithm to change. The actions may include external events such as market events (for example, a price update, quantity update, order confirmation, trade confirmation, fill confirmation, or trade notification) or timer events (for example, from a system clock or alarm). These external events may result in discrete events being generated such as order confirmation discrete events, trade confirmation discrete events, fill confirmation discrete events, or trade notification discrete events and/or continuous values such as price or quantity values for an instrument being updated. The actions may also include internal events such as discrete events generated by blocks in the algorithm or continuous values changing.

(111) FIG. 8 illustrates an example of the trading algorithm design tool **500** generally indicated by the reference numeral **800**. The example trading algorithm design tool **800** is displayed via the trading interface **402** operable on a trading device (e.g., the trading device **110** of FIGS. 1 and/or 4) when a warning and/or an error is detected by the warning and error manager **406** of FIG. 4. While the example trading algorithm design tool **800** depicts both a single warning and a single error present in a trading algorithm **801**, any number of warnings and/or errors may be detected by the warning and error manager **406** and displayed in the design canvas area **511** (see FIG. 5) of the example trading algorithm design tool **800**.

(112) Generally, the trading algorithm **801** of the illustrated example provides mechanisms to place an order for a particular amount of instruments at a particular price when certain conditions are met and to modify the order when other conditions are met. The trading block **801a** is a single order

block to place a single order in the market at a specified price (defined by block **801b**) and quantity (defined by block **801c**) for a particular commodity (defined by block **801d**). The trading block **801a** will place the single order if a particular condition is true (defined by block **801e**). Specifically, the trading block **801a** will place the single order if a quantity (defined by block **801f**) is greater than zero (defined by block **801g**). If the quantity (defined by block **801f**) is not greater than zero (defined by block **801g**), the particular condition will be false (defined by block **801e**) and the trading block **801a** will not place the single order.

(113) Single order container blocks **801h**, **801i** are used to modify orders placed by the trading block **801a**. The blocks **801h**, **801i** may modify quantity and/or prices of orders after they have been placed by the trading block **801a**. The blocks **801h**, **801i** may also delete orders after they have been placed by the trading block **801a**. Specifically, the trading block **801h** will delete an order if a quantity (defined by block **801f**) is greater than zero (defined by block **801g**) according to block **801e**. Thus, in the illustrated example, the same input from trading block **801e** is connected to both the trading block **801a** to cause the trading block **801a** to place orders and the trading block **801h** to cause the trading block **801h** to delete orders. Such a configuration or layout may cause the trading algorithm **801** to violate a trading rule according to the warning and error manager **406** because the trading algorithm **801** may constantly add and delete orders, requiring many messages to be sent to an exchange, which may result in fined from the exchange.

(114) The trading blocks **801h**, **801i** receive an input to identify the order to be modified and/or deleted. The order input to the trading blocks **801h**, **801i** is to be connected to an “Add OK” port of the trading block **801a**. The “Add OK” port of the trading block **801a** outputs a message identifying the order placed by the trading block **801a** once the order has been sent to the exchange and a confirmation message has been received from the exchange in response to the order being placed. In the illustrated example, the order input of the trading block **801i** is connected to the “Chg OK” port of the trading block **801a** rather than the “Add OK” port of the trading block **801a**. Such a configuration or layout may cause the trading algorithm **801** to violate a trading rule according to the warning and error manager **406**. Design flaws in the trading algorithm **801** result in a variety of warnings and errors to be displayed by the example trading algorithm design tool **800**.

(115) In the illustrated example, a warning **802** is indicated in the design canvas area **511** of the example trading algorithm design tool **800** with a dashed yellow line surrounding the trading blocks (e.g., blocks **801a**, **801e**, **801h**) that are found to violate a trading rule by the warning and error manager **406**. Warning information **804** associated with the warning **802** is also displayed in the example trading algorithm design tool **800**. The warning information **804** explains the connection that has caused the warning **802** to be detected by the warning and error manager **406**. Specifically, the warning information **804** explains that a single order condition block (block **801e**) is also connected to a single order delete (block **801h**) and that this connection may cause an order to be placed and then to be immediately deleted. In the illustrated example, the warning **802** is shown as a dashed yellow line surrounding the trading blocks **801a**, **801e**, **801h**. In other examples, the warning **802** may provide any other visual indication of a violation of a rule by particular trading blocks. In the illustrated example, the warning information **804** provides text related to the warning **802**. In other examples, the warning information **804** may provide any other text, visual, or audio information related to the warning **802**. For example, the warning information **804** may provide a suggested solution to correct the trading algorithm.

(116) In the example of FIG. 8, an error **806** indicated in the design canvas area **511** (see FIG. 5) of the example trading algorithm design tool **800** with a dashed red line surrounding the trading blocks (e.g., blocks **801a**, **801i**) that are found to violate a trading rule by the warning and error manager **406**. Error information **808** associated with the error **806** is also displayed in the example trading algorithm design tool **800**. The error information **808** explains the connection that has caused the error **806** to be detected by the warning and error manager **406**. Specifically, the error information **808** explains that only an “Add OK” port on a single order block (block **801a**) may be

connected to a single order container block (block **801i**). In the illustrated example, the error **806** is shown as a dashed red line surrounding the trading blocks **801a**, **801i**. In other examples, the error **806** may provide any other visual indication of a violation of a rule by particular trading blocks. In the illustrated example, the error information **808** provides text related to the error **806**. In other examples, the error information **808** may provide any other text, visual, or audio information related to the error **806**. For example, the error information **808** may provide a suggested solution to correct the trading algorithm.

(117) FIG. **9** illustrates the example trading algorithm design tool **800** in accordance with certain embodiments. The example of FIG. **9** illustrates the example trading algorithm design tool **800** when the warning **802** of FIG. **8** in the design canvas area **511** has been selected by a user. Once selected, the warning **802** appears as a warning **902** in FIG. **9**. The warning **902** is depicted in the trading interface **800** with a solid yellow line surrounding the trading blocks (e.g., blocks **801a**, **801e**, **801h**) that are found to violate a trading rule by the warning and error manager **406**. The text of the warning information **804** associated with the warning **802** is also displayed within the warning **902** of FIG. **9**. The warning **902** shows the trading blocks found to violate the trading rule on a solid white background to further highlight the affected blocks. However, the warning **902** does not obstruct the trading algorithm as a whole from being manipulated by a user. For example, the trading blocks remain interactive (e.g., the blocks **801a**, **801e**, **801h** may be selected by a user) and may be manipulated within and/or outside of the warning **902**. In some examples, the warning **902** may obstruct the trading algorithm (e.g., the user may not manipulate the trading algorithm **801**).

(118) The warning **902** also includes an ignore button **904** that allows the user to actively ignore the warning **902**. If the warning **902** is actively ignored by the user, the warning and error manager **406** of FIG. **4** adds the warning **902** to an ignored warning list so that the warning and error manager **406** will not display the warning **902** again. The warning and error manager **406** allows the trading algorithm **801** to be executed even where the trading algorithm **801** contains warnings (e.g., the warning **902**). In the illustrated example, the warning **902** is shown as a solid yellow line surrounding the trading blocks **801a**, **801e**, **801h**. In other examples, the warning **902** may provide any other visual indication of a violation of a rule by particular trading blocks. In the illustrated example, the warning **902** provides text related to the warning (e.g., the warning information **804**). In other examples, the warning **902** may provide any other text, visual, or audio information related to the warning.

(119) FIG. **10** illustrates the example trading algorithm design tool **800** in accordance with certain embodiments. The example of FIG. **10** illustrates the trading algorithm design tool **800** when the error **806** of FIG. **8** in the design canvas area **511** has been selected by a user. Once selected, the error **806** appears as an error **1006** in FIG. **10**. The error **1006** is depicted in the trading algorithm design tool **800** with a solid red line surrounding the trading blocks (e.g., blocks **801a**, **801i**) that are found to violate a trading rule by the warning and error manager **406**. The text of the error information **808** associated with the error **806** is also displayed within the error **1006** of FIG. **10**. The error **806** shows the trading blocks found to violate the trading rule on a solid white background to further highlight the effected blocks. However, the error **806** does not obstruct the trading algorithm as a whole from being manipulated by a user. For example, the trading blocks remain interactive (e.g., blocks **801**, **801i** may be selected by a user) and may be manipulated within and/or outside of the error **806**. In some examples, the error **806** may obstruct the trading algorithm (e.g., the user may not manipulate the trading algorithm **801**).

(120) The warning and error manager **406** does not allow the trading algorithm **801** to be executed when the trading algorithm **801** contains errors (e.g., the error **1006**). In the illustrated example, the error **1006** is shown as a solid red line surrounding the trading blocks **801a**, **801i**. In other examples, the error **1006** may provide any other visual indication of a violation of a rule by particular trading blocks. In the illustrated example, the error **1006** provides text related to the

warning (e.g., the warning information **808**). In other examples, the error **1006** may provide any other text, visual, or audio information related to the warning.

(121) FIG. **11** is a block diagram of an example warning and error manager, such as the warning and error manager **406** of FIG. **4**. In certain embodiments, the warning and error manager **406** detects problems within a trading algorithm designed at a trading device (e.g., the trading device **110** of FIGS. **1** and/or **4**). In certain embodiments, the warning and error manager **406** identifies problems within a trading algorithm for a user to facilitate correction of such problems. In certain embodiments, the warning and error manager **406** includes a change detector **1102**, a rules applier **1104**, a warning facilitator **1106**, and an error facilitator **1108**.

(122) In certain embodiments, the change detector **1102** detects structural changes within a trading algorithm designed by a user at the trading device **110**. For example, a structural change detected by the change detector **1102** may include an addition of a trading block and/or an added connection to a trading block. In some examples, other changes to a trading algorithm are detected by the change detector **1102**.

(123) In certain embodiments, the rules applier **1104** stores various rules related to problems and/or errors within trading algorithms. In certain embodiments, rules are stored in the rules applier **1104** for specific types of trading algorithm blocks. For example, a first trading algorithm block may have a variety of logic-based rules and/or trading-based rules associated with it. A second trading algorithm block may have the same or different logic-based rules and/or trading-based rules associated with it. Some trading algorithm blocks may not have any rules associated with them. The rules may be logic-based (e.g., identification of an infinite loop) and/or trading-based (e.g., connecting a particular input to a particular output may result in an unintended trade). The logic-based rules and/or trading-based rules may be based on the type of algorithm block they are associated with and/or the connections that are made with the algorithm block. For example, a particular output may not be connected with a particular input of certain trading algorithm blocks. In some examples, a first trading algorithm block may not be connected to a second trading algorithm block. In some examples, certain connections may violate a rule even where there are intervening blocks contained in the trading algorithm (e.g., an unrelated block may be connected between two blocks that violate a rule).

(124) In certain embodiments, the rules are identified as creating either warnings or errors. For example, the violation of certain rules may result in display of a warning while the violation of other rules may result in display of an error. In certain embodiments, the rules define the manner in which warnings and/or errors are implemented. For example, the rules may define the manner in which warnings and/or errors are displayed (e.g., color, font, highlighting, etc.) and/or text associated with the warnings and/or errors that is displayed. As described above, a warning may not prevent a trading algorithm from executing while an error may prevent a trading algorithm from executing. In certain embodiments, the rules applier **1104** includes a database to store the rules. In other embodiments, a separate database may be used to store the rules.

(125) Once the change detector **1102** has detected a change in a trading algorithm, the rules applier **1104** checks the trading algorithm blocks and/or their associated connections with other trading algorithm blocks against the rules to detect any problems and/or errors within the trading algorithm. To check the trading blocks and/or their associated connections for rules violations, the rules applier **1104** iterates through each trading block and each connection within a trading algorithm. In certain embodiments, the rules applier **1104** selects a trading block and determines if there are any rules associated with that particular trading block. As explained above, certain rules may apply to certain types of trading blocks. If rules are associated with the selected trading block, those rules are accessed by the rules applier **1104**.

(126) In certain embodiments, the rules applier **1104** selects an input to the selected trading block. The rules applier **1104** determines if a direct connection and/or an indirect connection (e.g., with intervening blocks) to the selected input violates any rules associated with the trading block. If any

such connection violates a rule, the warning facilitator **1106** and/or the error facilitator **1108** facilitate warning and/or error handling. The rules applier **1104** iterates through each input of the selected trading block to check for rules violations.

(127) In certain embodiments, the rules applier **1104** selects an output of the selected trading block. The rules applier **1104** determines if a direct connection and/or an indirect connection (e.g., with intervening blocks) to the selected output violates any rules associated with the trading block. If any such connection violates a rule, the warning facilitator **1106** and/or the error facilitator **1108** facilitate warning and/or error handling. The rules applier **1104** iterates through each output of the selected trading block to check for rules violations.

(128) In certain embodiments, once the rules applier **1104** has iterated through each input and output of the selected trading block, the rules applier **1104** selects another trading block in the trading algorithm and checks the newly selected trading block for rules violations in a similar manner as that described above.

(129) In certain embodiments, if the rules applier **1104** detects a violation of a rule resulting in a warning, the warning facilitator **1106** causes a warning to be displayed to the user at the trading device **110**. The warning may include a visual depiction of the warning (e.g., the algorithm blocks and/or connections in violation of a rule may be highlighted), text related to the warning (e.g., an explanation of the violation, a suggestion to remedy the violation, etc.), or other information related to the warning. In certain embodiments, the warning facilitator **1106** identifies the trading blocks in violation of the rules and implements a display of a box around those trading blocks. In certain embodiments, when the rules applier **1104** detects a warning in the trading algorithm, the warning facilitator **1106** allows the trading algorithm to be executed (e.g., the trading algorithm may be implemented to execute a trade at an exchange). In certain embodiments, the warning facilitator **1106** saves a list of warnings for future use and/or deployment of the trading algorithm.

(130) In certain embodiments, a warning may be ignored by a user at the trading device **110** (e.g., the user may select an ignore button that removes the warning from display). In certain embodiments, the warning facilitator **1106** stores a list of ignored warnings. The list of ignored warnings may include unique identifiers for the trading blocks associated with the warnings. If a warning has been actively ignored by the user, the warning facilitator **1106** does not display the warning again. However, in certain examples, if the trading blocks associated with the warning are duplicated in the trading algorithm, those trading blocks will have a different identifier than the original trading blocks associated with the warning, and a separate warning will be generated for the duplicated trading blocks. In certain embodiments, if a warning is remedied by the user (e.g., the user alters the trading algorithm such that the trading algorithm complies with the rules), the warning facilitator **1106** removes the warning from the ignored warnings list. Thus, if the trading algorithm is later altered such that it violates the same rule and creates the same warning, the warning facilitator **1106** will cause the warning to again be displayed on the trading device **110** for the user.

(131) In certain embodiments, if the rules applier **1104** detects a violation of a rule resulting in an error, the error facilitator **1108** causes an error to be displayed to the user at the trading device **110**. The error may include a visual depiction of the error (e.g., the algorithm blocks and/or connections in violation of a rule may be highlighted), text related to the error (e.g., an explanation of the violation, a suggestion to remedy the violation, etc.), or other information related to the error. In certain embodiments, the error facilitator **1108** identifies the trading blocks in violation of the rules and implements a display of a box around those trading blocks. In certain embodiments, when the rules applier **1104** detects an error in the trading algorithm, the error facilitator **1108** prevents the trading algorithm from being executed (e.g., the trading algorithm may not be implemented to execute a trade at an exchange) until the error is remedied (e.g., the trading algorithm no longer violates a rule). In certain embodiments, the error facilitator **1108** saves a list of errors such that, when the trading algorithm is deployed, the trading algorithm is not allowed to execute until the list

of errors is cleared. In such an example, the list of errors is saved for future use and/or deployment of the trading algorithm.

(132) In certain embodiments, a warning and/or an error may be overridden at the trading device **110**. In some examples, to override a warning and/or an error, a user may need authorization to perform such an override function (e.g., a supervisor may be given permission to perform an override of a warning and/or an error). In some examples, to override a warning and/or an error, a user may need to provide verification of the user's identity (e.g., the user may be required to input a password associated with a username).

(133) FIG. **12** illustrates a flow diagram of an example method **1200** to manage warnings and/or errors in a trading algorithm. In certain embodiments, the change detector **1102** detects structural changes within a trading algorithm designed by a user at a trading device (e.g., the trading device **110** of FIGS. **1** and/or **4**) (**1202**). For example, a structural change detected by the change detector **1102** may include an addition of a trading block and/or an added connection to a trading block. Control remains at **1202** until a structural change is detected. In some examples, other changes to a trading algorithm are detected by the change detector **1102**.

(134) In certain embodiments, the rules applier **1104** applies rules to the trading algorithm (**1204**). The rules applier **1104** stores various rules related to problems and/or errors within trading algorithms. The rules applier **1104** applies these rules to each trading block within the trading algorithm to detect warnings and/or errors. To check the trading blocks and/or their associated connections for rules violations, the rules applier **1104** iterates through each trading block and each connection within a trading algorithm. An example method for applying rules to trading blocks is described below in connection with FIG. **13**. If the rules applier **1104** detects a warning within the trading algorithm (e.g., a trading block and/or connection violates a rule that results in a warning) (**1206**), the warning facilitator **1106** facilitates warning handling (**1208**). If the rules applier **1104** does not detect a warning within the trading algorithm (**1206**), control proceeds to the error detection portion of the method **1200** beginning at **1214**.

(135) To facilitate warning handling, in certain embodiments, the warning facilitator **1106** causes a warning to be displayed to the user at the trading device **110**. The warning may include a visual depiction of the warning (e.g., the algorithm blocks and/or connections in violation of a rule may be highlighted). In certain embodiments, the warning facilitator **1106** identifies the trading blocks in violation of the rules and implements a display of a box around those trading blocks. In certain embodiments, when the rules applier **1104** detects a warning in the trading algorithm, the warning facilitator **1106** allows the trading algorithm to be executed (e.g., the trading algorithm may be implemented to execute a trade at an exchange). If the warning is selected by a user (**1210**), the warning facilitator **1106** provides text related to the warning (e.g., an explanation of the violation, a suggestion to remedy the violation, etc.), or other information related to the warning (**1212**). If the warning is not selected by the user (**1210**), control proceeds to the error detection portion of the method **1200** beginning at **1214**.

(136) If the rules applier **1104** detects an error within the trading algorithm (e.g., a trading block and/or connection violates a rule that results in an error) (**1214**), the error facilitator **1108** facilitates error handling (**1216**). If the rules applier **1104** does not detect an error within the trading algorithm (**1214**), control returns to **1202** to await detection of further changes in the structural design of the trading algorithm.

(137) To facilitate error handling, in certain embodiments, the error facilitator **1108** causes an error to be displayed to the user at the trading device **110**. The error may include a visual depiction of the error (e.g., the algorithm blocks and/or connections in violation of a rule may be highlighted). In certain embodiments, the error facilitator **1108** identifies the trading blocks in violation of the rules and implements a display of a box around those trading blocks. In certain embodiments, when the rules applier **1104** detects an error in the trading algorithm, the error facilitator **1108** does not allow the trading algorithm to be executed (e.g., the trading algorithm may not be implemented to execute

a trade at an exchange) If the error is selected by the user (**1218**), the error facilitator **1108** provides text related to the error (e.g., an explanation of the violation, a suggestion to remedy the violation, etc.), or other information related to the error (**1220**). If the error is not selected by the user (**1218**), control returns to **1202** to await detection of further changes in the structural design of the trading algorithm.

(138) FIG. **13** illustrates a flow diagram of an example method **1300** to apply rules to a trading algorithm. In certain embodiments, rules are stored in the rules applier **1104** for specific types of trading algorithm blocks. The rules may be logic-based (e.g., an infinite loop) and/or trading-based (e.g., connecting a particular input to a particular output may result in an unintended trade). The logic-based rules and/or trading-based rules may be based on the type of algorithm block they are associated with and/or the connections that are made with the algorithm block. In some examples, certain connections may violate a rule even where there are intervening blocks contained in the trading algorithm (e.g., an unrelated block may be connected between two blocks that violate a rule). In certain embodiments, the rules are identified as creating either warnings or errors. For examples, the violation of certain rules may result in display of a warning while the violation of other rules may result in display of an error. In certain embodiments, the rules define the manner in which warnings and/or errors are implemented.

(139) In certain embodiments, the rules applier **1104** checks the trading algorithm blocks and/or their associated connections with other trading algorithm blocks against the rules to detect any problems and/or errors within the trading algorithm. To check the trading blocks and/or their associated connections for rules violations, the rules applier **1104** iterates through each trading block and each connection within a trading algorithm. In certain embodiments, the rules applier **1104** selects a trading block (**1302**) and determines if there are any rules associated with that particular trading block (**1304**). As explained above, certain rules may apply to certain types of trading blocks. If rules are associated with the selected trading block, those rules are accessed by the rules applier **1104**. If there are no rules associated with the selected trading block, control returns to **1302**.

(140) In certain embodiments, the rules applier **1104** selects an input to the selected trading block (**1306**). The rules applier **1104** determines if the selected input violates the rules (**1308**). For example, the rules applier **1104** determines if a direct connection and/or an indirect connection (e.g., with intervening blocks) to the selected input violates any rules associated with the trading block. If any such connection violates a rule, the warning facilitator **1106** and/or the error facilitator **1108** generates a warning and/or error (**1310**). If the selected input does not violate the rules, control proceeds to **1312**. The rules applier **1104** determines if there is another input of the selected trading block to be checked (**1312**). If there is another input of the selected trading block to be checked (**1312**), control returns to **1306**. If there is not another input of the selected trading block to be checked (**1312**), control proceeds to **1314**.

(141) In certain embodiments, the rules applier **1104** selects an output of the selected trading block (**1314**). The rules applier **1104** determines if the selected output violates the rules (**1316**). For example, the rules applier **1104** determines if a direct connection and/or an indirect connection (e.g., with intervening blocks) to the selected output violates any rules associated with the trading block. If any such connection violates a rule, the warning facilitator **1106** and/or the error facilitator **1108** generate a warning and/or error (**1318**). If the selected input does not violate the rules, control proceeds to **1320**. The rules applier **1104** determines if there is another output of the selected trading block to be checked (**1320**). If there is another output of the selected trading block to be checked (**1320**), control returns to **1314**. If there is not another output of the selected trading block to be checked (**1320**), control proceeds to **1322**. The rules applier **1104** determines if there is another trading block within the trading algorithm to be checked for rules compliance (**1322**). If there is another trading block to be checked (**1322**), control returns to **1302**. If there is not another trading block within the trading algorithm to be checked for rules compliance (**1322**), the example

method **1300** ends.

(142) FIG. **14** is a flow diagram of an example method **1400** to track warnings associated with trading algorithms. The warning facilitator **1106** causes a warning to be displayed to a user at a trading device (e.g., the trading device **110**) (**1402**). The warning facilitator **1106** determines if the warning is remedied (**1404**). The warning is remedied if, for example, the trading algorithm is altered such that the rule associated with the warning is no longer violated. If the warning is remedied (**1404**), the example method **1400** ends. If the warning is not remedied (**1404**), the warning facilitator **1106** determines if the warning is actively ignored by the user (**1406**). In certain embodiments, a warning may be ignored by a user at the trading device **110** (e.g., the user may select an ignore button that removes the warning from display). If the warning is not ignored (**1406**), the example method **1400** ends. If the warning is ignored (**1406**), the warning facilitator **1106** adds the warning to an ignored warnings list (**1408**). The ignored warnings list may include the warning and a unique identifier of the trading blocks producing the warning. The warning facilitator **1106** determines if the ignored warning is remedied (**1410**). If the ignored warning is not remedied (**1410**), the example method **1400** ends. If the ignored warning is remedied (**1410**), the warning facilitator **1106** removes the ignored warning from the ignored warnings list (**1412**). The warning facilitator **1106** determines if the warning is recreated (**1414**). For example, the warning facilitator **1106** determines if the trading blocks are arranged as to violate the rule associated with the warning again. If the warning is not recreated (**1414**), the example method **1400** ends. If the warning is recreated (**1414**), control returns to **1408**.

(143) Some of the described figures depict example block diagrams, systems and/or flow diagrams representative of methods that may be used to implement all or part of certain embodiments. One or more of the components, elements, blocks, and/or functionality of the example block diagrams, systems, and/or flow diagrams may be implemented alone or in combination in hardware, firmware, discrete logic, as a set of computer readable instructions stored on a tangible computer readable medium, or any combination thereof, for example.

(144) The example block diagrams, systems, and/or flow diagrams may be implemented using any combination(s) of application specific integrated circuit(s) (“ASIC”(s)), programmable logic device(s) (“PLD”(s)), field programmable logic device(s) (“FPLD”(s)), discrete logic, hardware, and/or firmware, for example. Also, some or all of the example methods may be implemented manually or in combination with the foregoing techniques, for example.

(145) The example block diagrams, systems, and/or flow diagrams may be performed using one or more processors, controllers, and/or other processing devices, for example. For example, the examples may be implemented using coded instructions, for example, computer readable instructions, stored on a tangible computer readable medium. A tangible computer readable medium may include various types of volatile and non-volatile storage media, including, for example, random access memory (“RAM”), read-only memory (“ROM”), programmable read-only memory (“PROM”), electrically programmable read-only memory (“EPROM”), electrically erasable read-only memory (“EEPROM”), flash memory, a hard disk drive, optical media, magnetic tape, a file server, any other tangible data storage device, or any combination thereof. The tangible computer readable medium is non-transitory. As used herein, the term non-transitory or tangible computer readable medium is expressly defined to include any type of computer readable storage media and to exclude propagating signals.

(146) Further, although the example block diagrams, systems, and/or flow diagrams are described above with reference to the figures, other implementations may be employed. For example, the order of execution of the components, elements, blocks and/or other functionality may be changed, and/or some of the components, elements, blocks and/or other functionality described may be changed, eliminated, sub-divided, or combined. Additionally, any or all of the components, elements, blocks, and/or other functionality may be performed sequentially and/or in parallel by, for example, separate processing threads, processors, devices, discrete logic, and/or circuits.

(147) While embodiments have been disclosed, various changes may be made and equivalents may be substituted. In addition, many modifications may be made to adapt a particular situation or material. Therefore, it is intended that the disclosed technology not be limited to the particular embodiments disclosed, but will include all embodiments falling within the scope of the appended claims.

Claims

1. A non-transitory computer readable medium having stored therein instructions executable by a processor, including instructions executable to: display, by a computing device including the processor, a design area for a visual programming environment in a graphical user interface, wherein the design area includes a plurality of blocks arranged to specify a definition for an algorithm being designed in the visual programming environment; receive, by the computing device, a change command via the graphical user interface to change the arrangement of the plurality of blocks; detect, by the computing device, a change in the arrangement of the plurality of blocks, wherein the change in the arrangement of the plurality of blocks includes a change with respect to a changed block; in response to the detected change in the arrangement of the plurality of blocks, determine, by the computing device, that the algorithm does not comply with an algorithm rule that defines a problem associated with a block type of the changed block; in response determining that the algorithm does not comply with the algorithm rule, display, by the computing device, in the design area for the visual programming environment in the graphical user interface a highlight identifying at least one block of the plurality of blocks, wherein the highlight identifies the at least one block that does not comply with the algorithm rule; receive, by the computing device, a selection command via the graphical user interface selecting the displayed highlight; and display, by the computing device, in response to receiving the selection command via the graphical user interface, in the design area for the visual programming environment in the graphical user interface the highlight with an opaque background, wherein the opaque background is behind the at least one block of the plurality of blocks and obscures the remaining blocks in the plurality of blocks.
2. The non-transitory computer readable medium of claim 1, wherein the plurality of blocks are graphical representations of trading-related logic.
3. The non-transitory computer readable medium of claim 1, wherein each input and output of the changed block is checked for compliance with the algorithm rule.
4. The non-transitory computer readable medium of claim 1, further including instructions executable to: prevent, by the computing device, the algorithm from executing when the algorithm does not comply with the algorithm rule.
5. The non-transitory computer readable medium of claim 1, further including instructions executable to: display, by the computing device, information related to the algorithm rule and the changed block.
6. The non-transitory computer readable medium of claim 1, further including instructions executable to: receive, by the computing device, an ignore command via the graphical user interface and, in response to the ignore command, no longer displaying the highlight.
7. The non-transitory computer readable medium of claim 1, wherein the change with respect to the changed block includes at least one of: (i) adding the changed block to the design area, (ii) removing the changed block from the design area, (iii) a change to a configuration of the changed block, (iv) a connection to an input of the changed block, or (v) a connection to an output of the changed block.
8. The non-transitory computer readable medium of claim 1, wherein the algorithm rule defines at least one of: (i) a logic-based problem, (ii) a trading-based problem, (iii), a disallowed parameter for a configuration of the changed block, (iv) a disallowed connection for an input or an output of

the changed block, (v) an infinite loop, or (vi) a connection that may result in an unintended trade.

9. A system including: a computing device, wherein the computing device is configured to display a design area for a visual programming environment in a graphical user interface, wherein the design area includes a plurality of blocks arranged to specify a definition for an algorithm being designed in the visual programming environment; wherein the computing device is configured to receive a change command via the graphical user interface to change the arrangement of the plurality of blocks; wherein the computing device is configured to detect a change in the arrangement of the plurality of blocks, wherein the change in the arrangement of the plurality of blocks includes a change with respect to a changed block; wherein the computing device is configured to, in response to the detected change in the arrangement of the plurality of blocks, determine that the algorithm does not comply with an algorithm rule that defines a problem associated with a block type of the changed block; wherein the computing device is configured to, in response determining that the algorithm does not comply with the algorithm rule, display in the design area for the visual programming environment in the graphical user interface a highlight identifying at least one block of the plurality of blocks, wherein the highlight identifies the at least one block that does not comply with the algorithm rule; wherein the computing device is configured to receive a selection command via the graphical user interface selecting the displayed highlight; and wherein the computing device is configured to display, in response to receiving the selection command via the graphical user interface, in the design area for the visual programming environment in the graphical user interface the highlight with an opaque background, wherein the opaque background is behind the at least one block of the plurality of blocks and obscures the remaining blocks in the plurality of blocks.

10. The system of claim 9, wherein the plurality of blocks are graphical representations of trading-related logic.

11. The system of claim 9, wherein each input and output of the changed block is checked for compliance with the algorithm rule.

12. The system of claim 9, wherein the computing device is configured to prevent the algorithm from executing when the algorithm does not comply with the algorithm rule.

13. The system of claim 9, wherein the computing device is configured to display information related to the algorithm rule and the changed block.

14. The system of claim 9, wherein the computing device is configured to receive an ignore command via the graphical user interface and, in response to the ignore command, no longer displaying the highlight.

15. A method including: displaying, by a computing device including the processor, a design area for a visual programming environment in a graphical user interface, wherein the design area includes a plurality of blocks arranged to specify a definition for an algorithm being designed in the visual programming environment; receiving, by the computing device, a change command via the graphical user interface to change the arrangement of the plurality of blocks; detecting, by the computing device, a change in the arrangement of the plurality of blocks, wherein the change in the arrangement of the plurality of blocks includes a change with respect to a changed block; in response to the detected change in the arrangement of the plurality of blocks, determining, by the computing device, that the algorithm does not comply with an algorithm rule that defines a problem associated with a block type of the changed block; in response determining that the algorithm does not comply with the algorithm rule, displaying, by the computing device, in the design area for the visual programming environment in the graphical user interface a highlight identifying at least one block of the plurality of blocks, wherein the highlight identifies the at least one block that does not comply with the algorithm rule; receiving, by the computing device, a selection command via the graphical user interface selecting the displayed highlight; and displaying, by the computing device, in response to receiving the selection command via the graphical user interface, in the design area for the visual programming environment in the graphical

user interface the highlight with an opaque background, wherein the opaque background is behind the at least one block of the plurality of blocks and obscures the remaining blocks in the plurality of blocks.

16. The method of claim 15, wherein the plurality of blocks are graphical representations of trading-related logic.

17. The method of claim 15, wherein each input and output of the changed block is checked for compliance with the algorithm rule.

18. The method of claim 15, further including: preventing, by the computing device, the algorithm from executing when the algorithm does not comply with the algorithm rule.

19. The method of claim 15, further including: displaying, by the computing device, information related to the algorithm rule and the changed block.

20. The method of claim 15, further including: receiving, by the computing device, an ignore command via the graphical user interface and, in response to the ignore command, no longer displaying the highlight.
