

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                            |
|----------------------|----------------------------|
| United States Patent | 12415272                   |
| Kind Code            | B2                         |
| Date of Patent       | September 16, 2025         |
| Inventor(s)          | Takahashi; Yuutarou et al. |

---

### Teaching device

---

#### Abstract

A teaching device for creating a program using icons representing functions that form a control program for an industrial machine, the teaching device being provided with: a screen display generation unit that generates a program creation screen which has a predetermined region for arranging multiple icons to create a control program; and a relationship display generation unit that, on the basis of information related to multiple icons, extracts two or more icons which are related to each other in terms of processing contents from among the multiple icons arranged on the predetermined region, and displays the relationships between the extracted two or more icons so as to be visibly recognized.

---

|                              |                                                                          |
|------------------------------|--------------------------------------------------------------------------|
| <b>Inventors:</b>            | <b>Takahashi; Yuutarou (Yamanashi, JP), Namiki; Yuta (Yamanashi, JP)</b> |
| <b>Applicant:</b>            | <b>FANUC CORPORATION (Yamanashi, JP)</b>                                 |
| <b>Family ID:</b>            | <b>1000008818659</b>                                                     |
| <b>Assignee:</b>             | <b>FANUC CORPORATION (Yamanashi, JP)</b>                                 |
| <b>Appl. No.:</b>            | <b>18/553201</b>                                                         |
| <b>Filed (or PCT Filed):</b> | <b>May 31, 2021</b>                                                      |
| <b>PCT No.:</b>              | <b>PCT/JP2021/020728</b>                                                 |
| <b>PCT Pub. No.:</b>         | <b>WO2022/254543</b>                                                     |
| <b>PCT Pub. Date:</b>        | <b>December 08, 2022</b>                                                 |

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20240165801 A1          | May. 23, 2024           |

---

## Publication Classification

**Int. Cl.:** G06F16/9538 (20190101); B25J9/00 (20060101); B25J9/16 (20060101)

**U.S. Cl.:**

**CPC** B25J9/1656 (20130101); B25J9/0081 (20130101);

## Field of Classification Search

**CPC:** G06F (16/248); G06F (16/9577); G06F (9/445); G06F (9/50); B25J (9/1656); B25J (9/0081)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl. | CPC          |
|--------------|-------------|---------------|----------|--------------|
| 5341458      | 12/1993     | Kaneko        | 901/3    | G05B 19/425  |
| 6522949      | 12/2002     | Ikeda         | 700/262  | G05B 19/425  |
| 10300609     | 12/2018     | Jackowski     | N/A      | H02K 11/215  |
| 2005/0065990 | 12/2004     | Allen         | 708/495  | G06F 9/45504 |
| 2011/0153076 | 12/2010     | Noro          | 700/245  | B25J 9/1664  |

### FOREIGN PATENT DOCUMENTS

| Patent No.  | Application Date | Country | CPC |
|-------------|------------------|---------|-----|
| 2001-088068 | 12/2000          | JP      | N/A |
| 2007-242054 | 12/2006          | JP      | N/A |
| 4673058     | 12/2010          | JP      | N/A |
| 5271344     | 12/2012          | JP      | N/A |
| 6498366     | 12/2018          | JP      | N/A |

---

*Primary Examiner:* Tran; Dalena

*Attorney, Agent or Firm:* HAUPTMAN HAM, LLP

---

## Background/Summary

### RELATED APPLICATIONS

(1) The present application is a National Phase of International Application No. PCT/JP2021/020728 filed May 31, 2021.

### FIELD

(2) The present invention relates to a teaching device.

### BACKGROUND

(3) A teaching device that can perform programming using an icon representing each command of robot control in order to support an intuitive input by an operator of a control program of a robot is proposed (for example, PTL 1).

(4) It should be noted that, in regard to a display system for performing display for supporting a series of pieces of work related to an industrial system, PTLs 2 and 3 describe a configuration for

“providing a superior icon group display region 320, a subordinate icon group display region 322, an alternative figure display region 324, a processing content display region 326, and a tag instruction figure display region 328 on a display screen 312 of a display device 300 in a printed-circuit board work system” (paragraph 0030 in PTL 2 and paragraph 0031 in PTL 3).

## CITATION LIST

### Patent Literature

(5) [PTL 1] Japanese Patent No. 6498366B [PTL 2] Japanese Patent No. 4673058B [PTL 3] Japanese Patent No. 5271344B

### Technical Problem

## SUMMARY

(6) In a programming device using an icon, an operator creates a control program by arranging a desired icon in a processing order in a program creation region and performing parameter setting on an icon as necessary. Herein, the control program is realized by a mutual connection between pieces of processing by many icons. However, each of icons arranged in the program creation region is generally displayed in a completed manner with one icon. The operator often wishes to confirm a relationship between the icons.

### Solution to Problem

(7) One aspect of the present disclosure is a teaching device for performing program creation by an icon representing a function constituting a control program of an industrial machine, and the teaching device includes: a screen display creation unit that generates a program creation screen including a predetermined region for creating the control program by arranging a plurality of the icons; and a relationship display creation unit that extracts two or more icons having a mutual relationship with a processing content among the plurality of icons arranged in the predetermined region, based on information about each of the plurality of icons, and performs display in which the relationship between the two or more extracted icons can be visually recognized.

### Advantageous Effects of Invention

(8) According to the configuration described above, a relationship between icons arranged in a predetermined region of a program creation screen can be visually recognized, and creation of a program can efficiently proceed.

(9) The objects, the features, and the advantages, and other objects, features, and advantages of the present invention will become more apparent from the detailed description of typical embodiments of the present invention illustrated in accompanying drawings.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a diagram illustrating an overall configuration of a robot system including a teaching device according to one embodiment.
- (2) FIG. 2 is a diagram illustrating a hardware configuration example of a robot controller and a teach pendant.
- (3) FIG. 3 is a functional block diagram of the robot controller and the teach pendant.
- (4) FIG. 4 is a diagram illustrating a configuration of a program creation screen.
- (5) FIG. 5 is a diagram illustrating a detailed setting screen displayed on a lower portion of a screen when a detail tab is selected while a view icon is selected.
- (6) FIG. 6 is a diagram illustrating a detailed setting screen displayed on the lower portion of the screen when the detail tab is selected while a pick/arrange icon is selected.
- (7) FIG. 7 is a diagram illustrating a detailed setting screen displayed on the lower portion of the screen when the detail tab is selected while a jump label icon is selected.
- (8) FIG. 8 is a diagram illustrating a detailed setting screen displayed on the lower portion of the

screen when the detail tab is selected while a label icon is selected.

(9) FIG. **9** is a diagram illustrating a detailed setting screen displayed on the lower portion of the screen when the detail tab is selected while a hand open icon is selected.

(10) FIG. **10** is a diagram illustrating a detailed setting screen displayed on the lower portion of the screen when the detail tab is selected while a hand close icon is selected.

(11) FIG. **11** is a diagram illustrating an example in which icons having a relationship are provided with the same identification symbol and displayed.

(12) FIG. **12** is a diagram illustrating an example in which icons having a relationship are emphasized and displayed in a display manner of the same kind.

(13) FIG. **13** is a diagram illustrating an example in which a relationship is expressed by coupling and displaying icons having the relationship.

(14) FIG. **14** is a diagram illustrating an example in which a mutual relationship between icons is displayed when a plurality of the same icons are mixed.

(15) FIG. **15** is a diagram illustrating an example of warning display when an icon having a relationship with an icon is not found.

#### DESCRIPTION OF EMBODIMENTS

(16) Next, embodiments of the present disclosure will be described with reference to drawings. A similar configuration portion or a similar functional portion is denoted by the same reference sign in the referred drawings. A scale is appropriately changed in the drawings in order to facilitate understanding. An aspect illustrated in the drawing is one example for implementing the present invention, and the present invention is not limited to the illustrated aspect.

(17) FIG. **1** is a diagram illustrating an overall configuration of a robot system **100** including a teaching device **40** according to one embodiment. In the present embodiment, a robot controller **50** and a teach pendant **10** constitute the teaching device **40** for teaching a robot **30**. The teaching device **40** is a teaching device that can perform programming using an icon representing a function constituting a control program of the robot **30** (i.e., representing a command of robot control). As described below in detail, the teaching device **40** makes programming work by a user efficient by displaying, in a visually recognizable manner, a mutual relationship between icons arranged in a program creation region of a program creation screen.

(18) Various configuration examples are possible as a robot system including such a teaching device **40**, but, in the present embodiment, the robot system **100** illustrated in FIG. **1** is assumed as an exemplification. The robot system **100** includes the robot **30** including a hand **33** mounted on an arm tip portion, the robot controller **50** that controls the robot **30**, the teach pendant **10** connected to the robot controller **50**, a visual sensor **70** attached to the arm tip portion of the robot **30**, and a visual sensor controller **20** that controls the visual sensor **70**. The robot system **100** can detect a target object **1** on a worktable **2** by the visual sensor **70**, and can perform handling of the target object **1** with the hand **33** mounted on the robot **30**.

(19) The visual sensor controller **20** has a function of controlling the visual sensor **70** and a function of performing image processing on an image captured by the visual sensor **70**. The visual sensor controller **20** detects a position of the target object **1** from the image captured by the visual sensor **70**, and provides the detected position of the target object **1** to the robot controller **50**. In this way, the robot controller **50** can correct a teaching position, and perform picking-up and the like of the target object **1**. The visual sensor **70** may be a camera that captures a gray-scale image and a color image, or may be a stereo camera or a three-dimensional sensor that can acquire a distance image and a three-dimensional point group. In the robot system **100**, a plurality of visual sensors may be arranged. The visual sensor controller **20** holds a model pattern of a target object, and performs image processing of detecting a target object by pattern matching between an image **20**) of the target object in a captured image and the model pattern. It should be noted that, in FIG. **1**, the visual sensor controller **20** is formed as a device separately from the robot controller **50**, but a function as the visual sensor controller **20** may be mounted in the robot controller **50**.

(20) FIG. 2 is a diagram illustrating a hardware configuration example of the robot controller **50** and the teach pendant **10**. The robot controller **50** may have a configuration as a general computer in which a memory **52** (such as a ROM, a RAM, and a non-volatile memory), an input/output interface **53**, an operating unit **54** including various operation switches, and the like are connected to a processor **51** via a bus. The teach pendant **10** is used as a device for performing an operation input and a screen display for teaching the robot **30** (i.e., creating a control program). The teach pendant **10** may have a configuration as a general computer in which a memory **12** (such as a ROM, a RAM, and a non-volatile memory), a display unit **13**, an operating unit **14** formed of an input device such as a keyboard (or a software key), an input/output interface **15**, and the like are connected to a processor **11** via a bus. It should be noted that various information processing devices such as a tablet terminal, a smartphone, and a personal computer can be used instead of the teach pendant **10**.

(21) FIG. 3 is a functional block diagram illustrating a functional configuration of the teaching device **40** formed of the robot controller **50** and the teach pendant **10**. As illustrated in FIG. 3, the robot controller **50** includes a robot operation control unit **151** and a control program creation unit **152**.

(22) The robot operation control unit **151** controls an operation of the robot **30** according to a control program or an operation input from the teach pendant **10**.

(23) The control program creation unit **152** provides various functions when a user operates the teach pendant **10** and performs programming using icons. The control program creation unit **152** includes, as components that provide such functions, an icon control unit **153**, a relationship display creation unit **154**, a screen display creation unit **155**, and an icon data storage unit **156**.

(24) The icon data storage unit **156** stores various types of information about an icon such as data about a shape (image) of each icon and a setting parameter. The icon data storage unit **156** is formed in, for example, a non-volatile memory of the memory **52**.

(25) The screen display creation unit **155** generates various screens used for performing programming using icons, and displays the various screens on the display unit **13** of the teach pendant **10**.

(26) FIG. 4 is an example of a program creation screen **400** created by the screen display creation unit **155** and displayed on the display unit **13** of the teach pendant **10**. As illustrated in FIG. 4, the program creation screen **400** includes an icon display region **200** for displaying a list of various icons that can be used for programming, and a program creation region **300** for creating a control program by arranging the icons in an order. In the example in FIG. 4, the icon display region **200** includes a hand close icon **201** representing a command for closing a hand, a hand open icon **202** representing a command for opening the hand, a linear movement icon **203**, an arc movement icon **204**, a way point addition icon **205**, and a rotation icon **206** that rotates the hand.

(27) A user can select an icon by, for example, putting a cursor on the icon. The user performs programming by selecting a desired icon from the icon display region **200** and arranging the icon in the program creation region **300** by, for example, a drag-and-drop operation. In the example in FIG. 4, in the program creation region **300**, the hand close icon **201**, the arc movement icon **204**, two linear movement icons **203**, and the hand open icon **202** are arranged in order. When the number of icons arranged in the program creation region **300** increases, the user can arrange an icon by scrolling the screen in a horizontal direction.

(28) In the program creation screen **400**, the user selects a programming tab **261** when the user performs programming. Meanwhile, by selecting an icon in the program creation region **300** and selecting a detail tab **262**, the user can open a detailed setting screen for performing detailed setting (parameter setting) on the icon. The user can execute a control program by performing a predetermined operation while icons are arranged in the program creation region **300**.

(29) The icon control unit **153** has control over a user operation when the user operates the operating unit **14** of the teach pendant **10** and performs various operations on an icon, a tab, and the

like on the program creation screen **400**. Under support by the icon control unit **153**, the user successively selects a desired icon from a list of icons arranged in the icon display region **200**, arranges the icon in the program creation region **300**, and creates a control program. Further, by selecting an icon arranged in the program creation region **300** and selecting the detail tab **262** as necessary, the user can display a detailed setting screen and perform detailed setting on the selected icon.

(30) The relationship display creation unit **154** extracts two or more icons having a mutual relationship in regard to processing contents among a plurality of icons arranged in the program creation region **300**, based on information about each of the plurality of icons, and performs display in which the relationship between the two or more extracted icons can be visually recognized. Herein, presence of the relationship in the processing contents between the icons may include a relationship in various manners such as processing in cooperation, a common processing purpose, and a common processing target. With such a function by the relationship display creation unit **154**, the user can visually instantly recognize a mutual relationship between icons arranged in the program creation region **300**, and can efficiently proceed with programming.

(31) As an exemplification, the relationship display creation unit **154** may determine that icons satisfying any of the following conditions (a1) and (a2) have a relationship. (a1) Icons using the same data (a2) Icons using the same hardware

Herein, the same data includes various types of data, such as, a register, a label or a variable that may be referred to in a control program.

(32) With reference to FIGS. **5** and **6**, a first operation example when icons using the same data are extracted as icons having a relationship is illustrated. Herein, as an exemplification of the icons using the same data, a view icon **211** and a pick/arrange icon **212** are adopted. It should be noted that FIGS. **5** and **6** illustrate, for convenience of description, a state where only the view icon **211** and the pick/arrange icon **212** are arranged in the program creation region **300**, but actual programming normally includes many icons in the program creation region **300**, and the view icon **211** and the pick/arrange icon **212** are arranged away from each other. Herein, the view icon **211** corresponds to a function of detecting a position of a target object by a visual detection function (function of detecting a position of a target object by using a visual sensor), and the pick/arrange icon **212** corresponds to a function of picking up or arranging the target object while performing correction of a teaching point by using the position of the target object detected by the visual detection function.

(33) FIG. **5** illustrates a state where a detailed setting screen **500A** of the view icon **211** is displayed on a lower portion of the screen by selecting the detail tab **262** while the view icon **211** is selected. FIG. **6** illustrates a state where a detailed setting screen **500B** of the pick/arrange icon **212** is displayed on the lower portion of the screen by selecting the detail tab **262** while the pick/arrange icon **212** is selected.

(34) As illustrated in FIG. **5**, the detailed setting screen **500A** of the view icon **211** includes “initial setting of camera”, “detection setting”, and “teaching of capturing position”. The user sets the setting items as necessary. It should be noted that a default value may be set in advance in the setting items of the detailed setting screen. “Detection setting” includes a specification (reference sign **501**) of a detection program name (macro name), a specification (reference sign **502**) of a register of an output destination of a detection number, and a specification (reference sign **503**) of a register of an output destination of a detection result (position information in which a target object is detected). In the example in FIG. **5**, No. 1 of a vision register is specified as an output destination of a detection result. In the register that holds the detection result, position information about a target object detected by the visual detection function is stored.

(35) As illustrated in FIG. **6**, the detailed setting screen **500B** of the pick/arrange icon **212** includes setting for teaching a position (teaching point) in which a target object is picked up or arranged, a specification of a height between the pick/arrange position and an approach point, a movement

speed between the pick/arrange position and the approach point, and a specification (reference sign **513**) of a register that holds a position of the target object being used when the position of the target object is corrected and a pick/arrange operation is performed. In the example in FIG. **6**, No. 1 of a vision register is specified as a register used for correcting a position of a target object.

(36) In this way, since the view icon **211** and the pick/arrange icon **212** refer to No. 1 of the vision register being the same register, the position information about the target object detected by the view icon **211** is used when a position of the target object is corrected in the pick/arrange icon **212**. In this way, the view icon **211** and the pick/arrange icon **212** have a connection in regard to operation contents. The relationship display creation unit **154** refers to setting information about the view icon **211** and the pick/arrange icon **212**, and determines that the icons mutually have a relationship since the icons refer to the same register as the register that holds the detection result. As described above, icons having a mutual connection in regard to processing contents are appropriately extracted.

(37) Even in a situation where there are a plurality of pairs of view icons and pick/arrange icons in a program and register numbers of an output destination of a detection result are different among the plurality of pairs, each of the pairs of the view icon and the pick/arrange icon having a connection in regard to the processing can be appropriately extracted by the above-described technique for extracting icons using the same data as icons having a relationship.

(38) Next, with reference to FIGS. **7** and **8**, a second operation example when icons using the same data are extracted as icons having a relationship is illustrated. Herein, as an exemplification of the icons using the same data, a jump label icon **221** and a label icon **222** are adopted. It should be noted that FIGS. **7** and **8** illustrate, for convenience of description, a state where only the jump label icon **221** and the label icon **222** are arranged in the program creation region **300**, but actual programming normally includes many icons in the program creation region **300**, and the jump label icon **221** and the label icon **222** are arranged away from each other. The jump label icon **221** is a command for jumping to a label with a number specified as a label number serving as a detailed setting parameter. The label icon **222** is an icon arranged at a jump destination of the jump label icon **221**.

(39) FIG. **7** illustrates a state where a detailed setting screen **500C** of the jump label icon **221** is displayed on the lower portion of the screen by selecting the detail tab **262** while the jump label icon **221** arranged in the program creation region **300** is selected. FIG. **8** illustrates a state where a detailed setting screen **500D** of the label icon **222** is displayed on the lower portion of the screen by selecting the detail tab **262** while the label icon **222** is selected.

(40) As illustrated in FIG. **7**, the jump label icon **221** includes a label number (reference sign **521**) of a jump destination as a detailed setting parameter. Further, as illustrated in FIG. **8**, the label icon **222** includes a label number (reference sign **522**) as a detailed setting parameter. In the present example, the label number of the jump label icon **221** and the label number of the label icon **222** are common and “1”. In other words, the jump label icon **221** and the label icon **222** use the same data (label number). Therefore, the jump destination of the jump label icon **221** is the label icon **222**, and the icons have a connection in regard to the processing.

(41) In this case, the relationship display creation unit **154** recognizes that the jump label icon **221** and the label icon **222** use the same data by referring to the label numbers of the icons as the detailed setting parameters, and determines that the icons have a relationship. In this way, icons having a mutual connection in regard to processing contents are appropriately extracted. In this way, by extracting the jump label icon being a jump source and the label icon being a jump destination and visually displaying a relationship between the icons, the user can instantly recognize the connection between the jump label icon **221** and the label icon **222** on the program creation screen **400**, and can efficiently proceed with creation of a program.

(42) It should be noted that, normally, a plurality of pairs of the jump label icon and the label icon having a common label number may intricately overlap each other in a program in some cases.

Even in such a case, each of the pairs of the jump label icon and the label icon that are mutually related (that are a jump source and a jump destination) can be appropriately extracted by the above-described technique.

(43) Next, with reference to FIGS. **9** and **10**, an operation example when icons using the same hardware are extracted as icons having a relationship is illustrated. Herein, as an exemplification of the icons using the same hardware, a hand open icon **202** and a hand close icon **201** are adopted. It should be noted that FIGS. **9** and **10** illustrate, for convenience of description, a state where only the hand open icon **202** and the hand close icon **201** are arranged in the program creation region **300**, but actual programming normally includes many icons in the program creation region **300**, and the hand open icon **202** and the hand close icon **201** are arranged away from each other. The hand open icon **202** is an icon of a command for opening a hand. The hand close icon **201** is an icon of a command for closing the hand.

(44) FIG. **9** illustrates a state where a detailed setting screen **500E** of the hand open icon **202** is displayed on the lower portion of the screen by selecting the detail tab **262** while the hand open icon **202** arranged in the program creation region **300** is selected. FIG. **10** illustrates a state where a detailed setting screen **500F** of the hand close icon **201** is displayed on the lower portion of the screen by selecting the detail tab **262** while the hand close icon **201** is selected.

(45) As illustrated in FIG. **9**, the hand open icon **202** includes, as detailed setting parameters, an input field (reference sign **531**) for specifying a macro name of a macro command (sub-program) that needs to be executed, a load number for specifying a load, and a waiting time. Further, as illustrated in FIG. **10**, the hand close icon **201** includes, as detailed setting parameters, an input field (reference sign **532**) for specifying a macro name of a macro command that needs to be executed, a load number, and a waiting time. In the present example, both of the hand open icon **202** and the hand close icon **201** specify “select\_macro” as a macro name. A program of a macro command of the macro name “select\_macro” includes the number of an input/output apparatus indicating a hand device. Herein, it is assumed that an apparatus number of the hand device specified in the macro command of the hand open icon **202** and an apparatus number of the hand device specified in the macro command of the hand close icon **201** are common. Therefore, in this case, the hand open icon **202** and the hand close icon **201** operate the same hand device in cooperation with each other.

(46) In this case, the relationship display creation unit **154** recognizes that the hand open icon **202** and the hand close **201** use the same hardware by referring to the programs of the macro commands of the icons as the detailed setting items, and determines that the icons have a relationship. In this way, icons having a mutual connection in regard to processing contents are appropriately extracted. In this way, by extracting a relationship between icons corresponding to a command for the same hand device, and performing display of the relationship, the user can instantly recognize the connection between the hand open icon **202** and the hand close icon **201** that operate the same hand device on the program creation screen **400**, and can efficiently proceed with creation of a program.

(47) Depending on a robot system, a plurality of hand devices may be mounted on one robot. For example, a configuration in which two hand devices (a hand #1 and a hand #2) are mounted on one robot is assumed. In such a case, command icons for two hand devices are mixed in a control program, but, according to the present embodiment, the relationship display creation unit **154** can extract a hand open icon and a hand close icon for the hand #1 as icons having a relationship, and can extract a hand open icon and a hand close icon for the hand #2 as icons having a relationship. Therefore, also in a situation where a plurality of hand devices are mounted on a robot system, icons having a relationship can be associated for each of the plurality of hand devices.

(48) It should be noted that a hand device is described herein as an example of hardware used for a robot system, but icons using the same hardware can be extracted by a technique similar to the above-described technique in regard to various hardware apparatuses connected to a robot system other than a hand device.



(49) Next, an example of display of a relationship performed by the relationship display creation unit **154** on icons determined as icons having a relationship will be described. Examples of relationship display performed by the relationship display creation unit **154** are indicated as follows. (b1) An image representing the same identification symbol is added to icons having a relationship. (b2) Icons having a relationship are displayed in such a way as to be more emphasized than another icon. (b3) An image that connects icons having a relationship to each other is added. (50) FIG. **11** is an example of displaying a relationship between icons by “(b1) An image representing the same identification symbol is added to icons having a relationship” described above. In FIG. **11**, a state where the view icon **211** and the pick/arrange icon **212** are extracted as icons having a relationship among the icons **211**, **213**, **212**, and **201** arranged in the program creation region **300** is assumed. In FIG. **11**, an alphabet “A” (reference sign **251**) with a circle is provided and displayed as the same identification symbol on the view icon **211** and the pick/arrange icon **212** having a relationship. Since the same identification symbol is provided and displayed on the view icon **211** and the pick/arrange icon **212**, the user can visually instantly recognize that the icons have a relationship. It should be noted that numbers **1** to **5** with a circle being provided to each of the icons in FIG. **11** represents a number of a teaching point (the same also applies to other FIGS. **12** to **15**).

(51) FIG. **12** is an example of displaying a relationship between icons by “(b2) Icon having a relationship are displayed in such a way as to be more emphasized than another icon” described above. In FIG. **12**, a state where the view icon **211** and the pick/arrange icon **212** are extracted as icons having a relationship among the icons **211**, **213**, **212**, and **201** arranged in the program creation region **300** is assumed. In FIG. **12**, display frames (reference sign **252**) of the same color are added to the view icon **211** and the pick/arrange icon **212**, which are extracted as icons having a relationship, so that these icons are emphasized. In this way, the user can visually instantly recognize that the icons have a relationship.

(52) Herein, the example of emphasizing the icons having a relationship by the frame of the same color is described, but various ways of emphasis in such a way as to set the same color for a color of the entire icons, represent the icons by the same pattern, and the like are possible in addition to the above-described example as a way of emphasizing the icons having a relationship.

Alternatively, a way of relatively emphasizing the icons having a relationship in such a way as to tone down or gray out an icon other than the icons having a relationship is also possible. Further, the ways may be used in combination.

(53) FIG. **13** is an example of displaying a relationship between icons by “(b3) An image that connects icons having a relationship to each other is added” described above. Herein, as an exemplification, a display example in which the view icon **211** and the pick/arrange icon **212** are extracted as icons having a relationship is indicated. In FIG. **13**, a state where the view icon **211** and the pick/arrange icon **212** are extracted as icons having a relationship among the icons **211**, **213**, **212**, and **201** arranged in the program creation region **300** is assumed. In FIG. **13**, the view icon **211** and the pick/arrange icon **212** extracted as icons having a relationship are connected by a line **253**. In this way, it is obvious that the view icon **211** and the pick/arrange icon **212** are related.

(54) FIG. **14** illustrates a display example of a relationship when a plurality of the same icons are present in the program creation region **300**. Specifically, in FIG. **14**, it is assumed that a pair of a view icon **211a** and a pick/arrange icon **212a** is extracted as icons having a relationship since the pair refers to a register of the same number (for example, No. 1 of a vision register) as a vision register of an output destination of a detection result, and a pair of a view icon **211b** and a pick/arrange icon **212b** is extracted as icons having a relationship since the pair refers to a register of the same number (for example, No. 2 of a vision register) as a vision register of an output destination of a detection result.

(55) The relationship display creation unit **154** displays a connection between the view icon **211a** and the pick/arrange icon **212a** by a line **253a**, and displays a connection between the view icon

**211b** and the pick/arrange icon **212b** by a line **253b**. In this way, the user can instantly recognize that the view icon **211a** and the pick/arrange icon **212a** have a connection in regard to the processing, and simultaneously instantly recognize that the view icon **211b** and the pick/arrange icon **212b** have a connection in regard to the processing.

(56) In this way, even in a situation where a plurality of the same icons (pairs of the same icons) are present in a program, the technique for displaying a relationship according to the present embodiment can appropriately establish a relationship between icons having a connection in regard to the processing and allow a user to recognize the relationship.

(57) Various examples of a timing at which the relationship display creation unit **154** extracts icons having a relationship and displays the relationship are possible. For example, examples such as (c1) to (c4) described below are possible. (c1) The extraction and display are performed in response to a predetermined operation by a user (for example, a user operation of selecting one of icons arranged in the program creation region **300**). (c2) The extraction and display are performed every time an icon is arranged in the program creation region. (c3) The extraction and display are performed every time detailed setting is performed on an icon arranged in the program creation region. (c4) Two or more of (c1) to (c3) described above are used in combination.

(58) It should be noted that, FIG. **12** illustrates, as an exemplification, a state where, when the view icon **211** is selected, the relationship display creation unit **154** displays a relationship between the view icon **211** and the pick/arrange icon **212**.

(59) It should be noted that, when relationships are extracted for all icons arranged in the program creation region **300** and the relationships are displayed, a case where a screen becomes complicated and difficult to see is also assumed. In order to avoid such complicatedness of display and perform display of a relationship being intended by a user, the relationship display creation unit **154** may display a relationship by any of (d1) to (d3) below. (d1) When a user selects any of icons arranged in the program creation region **300**, a relationship of only the selected icon (only the selected icon and an icon having a relationship with the selected icon) is displayed. (d2) A relationship of only an icon belonging to a category specified by a user in advance (icon belonging to a category specified in advance and having a relationship) is displayed. (d3) When a user selects any of icons arranged in the program creation region **300**, a relationship of only an icon in a category to which the selected icon belongs (icon belonging to a category to which the one selected icon belongs and having a relationship) is displayed.

(60) The specification by the user in (d2) described above includes a specification of a category by various user operations. The category in (d2) and (d3) described above classifies icons of the same kind, and, for example, categorization as follows may be applied. In this case, the icon data storage unit **156** categorizes and stores data about icons as in Table 1 below.

(61) TABLE-US-00001  
TABLE 1 CATEGORY ICON OPERATION LINEAR MOVEMENT  
ICON, EACH AXIS MOVEMENT ICON, ARC MOVEMENT ICON, HAND OPEN ICON,  
HAND CLOSE ICON CONTROL JUMP ICON, LABEL ICON VISION VIEW ICON,  
PICK/ARRANGE ICON

(62) In Table 1 described above, a category “operation” includes icons related to an operation of a robot, a hand, and the like, a category “control” includes icons related to program control, such as a jump and the like, and a category “vision” includes icons related to a visual detection function. By performing categorization in such a way that icons of the same kind belong to the same category as in Table 1 described above, for example, when a user puts a cursor on an icon belonging to the category “operation” and selects the icon, a relationship of only an icon belonging to the category “operation” of the selected icon is displayed.

(63) By displaying a relationship of only an icon belonging to a category selected by a user in such a manner, complicatedness of the program creation screen **400** due to display of a relationship can be avoided, and the relationship can also be displayed in a manner intended by the user.

(64) There may be a case where the relationship display creation unit **154** is not able to extract a

relationship due to, for example, a fact that a user fails to input or makes a mistake to input a parameter setting item in regard to an icon that originally needs to be extracted as an icon having a relationship. For example, it is a case where there is a mistake in an input of a register name of an output destination of a detection result by a user in regard to the view icon **211** and the pick/arrange icon **212**, and the register name of the output destination of the detection result of the view icon **211** and the register name of the output destination of the detection result of the pick/arrange icon **212** do not match. When the relationship display creation unit **154** cannot extract a relationship in such a manner, the relationship display creation unit **154** may perform warning display of the failure in extraction for an icon whose relationship cannot be extracted. As an example of the warning display, notification of a warning or an error message by a pop-up manner and the like, emphasized display of an icon, and other various examples are possible. In this way, a user can instantly recognize an error in programming.

(65) FIG. **15** illustrates, as an exemplification, an example in which, when the relationship display creation unit **154** cannot find an icon having a relationship with the view icon **211** while illustrated icons are arranged in the program creation region **300**, a warning message of the failure to find the icon is displayed on a pop-up screen **260**. When such warning display is performed, for example, a user opens a detailed setting screen of the view icon **211** or the pick/arrange icon **212**, can confirm whether there is an error in a register number of an output destination of a detection result, and can quickly correct a program.

(66) As described above, according to the present embodiment, a relationship between icons arranged in a predetermined region of a program creation screen can be visually recognized, and creation of a program can efficiently be performed.

(67) The present invention has been described above by using the typical embodiments, but it will be understood by those of ordinary skill in the art that changes, other various changes, omission, and addition may be made in each of the embodiments described above without departing from the scope of the present invention.

(68) Distribution of the functions of the robot controller **50** and the teach pendant **10** in the functional block diagram illustrated in FIG. **3** is an exemplification, and various manners can be adopted for distribution of the functions assigned to the robot controller **50** and the teach pendant **10**. For example, a part of the function included in the robot controller **50** in FIG. **3** may be assigned to the teach pendant **10**.

(69) Alternatively, all of the functions as the control program creation unit **152** being assigned to the robot controller **50** may be assigned to the teach pendant **10**. In this case, the teach pendant **10** may function as the teaching device **40** (i.e., a program creation device) alone. Further, in this case, various information processing devices such as a tablet terminal, a smartphone, and a personal computer may be used as the teaching device **40**.

(70) The configuration of the teaching device described in the above embodiment can be applied to programming using an icon in not only an industrial robot, but also a machine tool and other various industrial machines.

(71) The functional block of the teaching device illustrated in FIG. **3** may be achieved by executing various types of software stored in a storage device by the CPU of the apparatus constituting the teaching device, or may be achieved by a configuration in which hardware such as an application specific integrated circuit (ASIC) is a main body.

#### REFERENCE SIGNS LIST

(72) **1** Target object **2** Worktable **10** Teach pendant **11** Processor **12** Memory **13** Display unit **14** Operating unit **15** Input/output interface **20** Visual sensor controller **30** Robot **33** Hand **40** Teaching device **50** Robot controller **51** Processor **52** Memory **53** Input/output interface **54** Operating unit **70** Visual sensor **100** Robot system **151** Robot operation control unit **152** Control program creation unit **153** Icon control unit **154** Relationship display creation unit **155** Screen display creation unit **156** Icon data storage unit **200** Icon display region **261** Programming tab **262** Detail tab **300**

## Claims

1. A teaching device for performing program creation by an icon representing a function constituting a control program of an industrial machine, the teaching device comprising: a screen display creation unit configured to generate a program creation screen including a predetermined region for creating the control program by arranging a plurality of the icons; and a relationship display creation unit configured to extract two or more icons having a mutual relationship in regard to processing contents among the plurality of icons arranged in the predetermined region, based on information about each of the plurality of icons, and perform display in which the relationship between the two or more extracted icons can be visually recognized.
  2. The teaching device according to claim 1, wherein the relationship display creation unit extracts, as icons regarded to have the relationship, two or more icons that satisfy at least any of conditions of (1) using the same data, and (2) using the same hardware among the plurality of icons arranged in the predetermined region.
  3. The teaching device according to claim 1, wherein the relationship display creation unit adds an image representing the same identification symbol to two or more icons having the relationship in the predetermined region.
  4. The teaching device according to claim 1, wherein the relationship display creation unit displays two or more icons having the relationship in such a way that the two or more icons are more emphasized than another icon in the predetermined region.
  5. The teaching device according to claim 1, wherein the relationship display creation unit adds an image that connects two or more icons having the relationship in the predetermined region.
  6. The teaching device according to claim 1, wherein the relationship display creation unit performs display in which the relationship can be visually recognized, in response to a selection operation being performed on one of the plurality of icons arranged in the predetermined region.
  7. The teaching device according to claim 6, wherein the relationship display creation unit performs display in which the relationship can be visually recognized, only for the one selected icon and one or more icons having the relationship with the one icon.
  8. The teaching device according to claim 1, further comprising an icon data storage unit configured to store the information about the plurality of icons in such a manner that the information is categorized into a plurality of categories, wherein the relationship display creation unit performs display in which the relationship can be visually recognized, for two or more icons belonging to a category specified in advance and having the relationship among the plurality of icons arranged in the predetermined region.
  9. The teaching device according to claim 8, wherein the relationship display creation unit performs, in response to a selection operation being performed on one of the plurality of icons arranged in the predetermined region, display in which the relationship can be visually recognized, for two or more icons belonging to a category to which the one selected icon belongs and having the relationship among the plurality of icons arranged in the predetermined region.
  10. The teaching device according to claim 1, wherein the relationship display creation unit performs warning display for an icon with which no icon has the relationship, among the plurality of icons arranged in the predetermined region.
-