

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415674
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Chen; Shifeng et al.

Lawn refuse bag insert

Abstract

A lawn refuse bag insert includes a rear wall disposed at a rear end of the lawn refuse bag insert; a first side wall hingedly coupled to the rear wall at a first side of the lawn refuse bag insert; and a second side wall hingedly coupled to the rear wall at a second side of the lawn refuse bag insert opposite the first side wherein a top edge of the lawn refuse bag insert is disposed at a top end of the lawn refuse bag insert, and wherein the top edge is substantially U-shaped.

Inventors: Chen; Shifeng (Newport News, VA), Sollie; Greg (Sharpsburg, GA), Waltermire; Jamie (Peachtree City, GA)

Applicant: Pratt Corrugated Holdings, Inc. (Brookhaven, GA)

Family ID: 1000008818724

Assignee: Pratt Corrugated Holdings, Inc. (Brookhaven, GA)

Appl. No.: 18/600208

Filed: March 08, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240208722 A1	Jun. 27, 2024

Related U.S. Application Data

continuation parent-doc US 16703184 20191204 US 11634277 20230425 child-doc US 18051746
division parent-doc US 18051746 20221101 US 11958685 child-doc US 18600208
us-provisional-application US 62896935 20190906

Publication Classification

Int. Cl.: **B65F1/14** (20060101); **B65B3/04** (20060101); B65B51/04 (20060101); B65D33/06 (20060101); B65D33/12 (20060101); B65D33/16 (20060101); B65F1/00 (20060101); B65F1/16 (20060101)

U.S. Cl.:

CPC **B65F1/1415** (20130101); **B65F1/14** (20130101); B65B3/04 (20130101); B65B51/04 (20130101); B65D33/06 (20130101); B65D33/12 (20130101); B65D33/1608 (20130101); B65F1/002 (20130101); B65F2001/1653 (20130101); B65F2220/106 (20130101); B65F2220/1063 (20130101); B65F2240/138 (20130101)

Field of Classification Search

CPC: B65F (1/14); B65F (1/141); B65F (1/1415); B65F (1/1426); B65F (1/1436); B65B (3/04)

USPC: 383/127; 383/4; 383/33; 383/34; 383/34.1; 248/95; 248/97; 248/99

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
398908	12/1888	Stevens	N/A	N/A
474382	12/1891	Haines	N/A	N/A
645544	12/1899	Bissell	N/A	N/A
672657	12/1900	Vautrot	N/A	N/A
1088633	12/1913	Simmons	N/A	N/A
1234057	12/1916	McIntyre	N/A	N/A
1305199	12/1918	Deubener	N/A	N/A
1571608	12/1925	Stillman	N/A	N/A
1601566	12/1925	Elliott	N/A	N/A
1846542	12/1931	Budd	N/A	N/A
1858793	12/1931	Archibald	N/A	N/A
1879410	12/1931	Morris et al.	N/A	N/A
1879950	12/1931	Read, Jr.	N/A	N/A
1898838	12/1932	Katz	N/A	N/A
1916519	12/1932	Madsen	N/A	N/A
1986898	12/1934	Smithwick	N/A	N/A
2307659	12/1942	Avery	N/A	N/A
D136086	12/1942	Hudson	N/A	N/A
2353311	12/1943	Karlson	N/A	N/A
2430155	12/1946	Buttery	N/A	N/A
2550959	12/1950	Bowman	N/A	N/A
2580796	12/1951	Kleiss et al.	N/A	N/A
2939614	12/1959	Hill	N/A	N/A
2985355	12/1960	Read	N/A	N/A
3021767	12/1961	Hamilton	N/A	N/A
3023946	12/1961	Steen	N/A	N/A
3034699	12/1961	Steen	N/A	N/A
3257068	12/1965	Wright	N/A	N/A
3324906	12/1966	Chu	N/A	N/A

3335769	12/1966	Ilg	N/A	N/A
D220420	12/1970	Rothwell	N/A	N/A
3578236	12/1970	Masayuki	N/A	N/A
3734340	12/1972	Ippolito et al.	N/A	N/A
3746240	12/1972	Flynn	N/A	N/A
3891136	12/1974	Woeste	N/A	N/A
3938731	12/1975	Ross et al.	N/A	N/A
3977594	12/1975	Swan	N/A	N/A
3983914	12/1975	Benson	N/A	N/A
3986744	12/1975	Krogstad et al.	N/A	N/A
D243438	12/1976	Batley	N/A	N/A
4037778	12/1976	Boyle	N/A	N/A
4103952	12/1977	Thompson	N/A	N/A
4115909	12/1977	Corella	N/A	N/A
4139029	12/1978	Geraci	N/A	N/A
4196928	12/1979	Spangler	N/A	N/A
4258842	12/1980	Falkstein	N/A	N/A
4268081	12/1980	Hawkinson	N/A	N/A
4272116	12/1980	Tufte, Jr.	N/A	N/A
4273167	12/1980	Stillwell	N/A	N/A
4338979	12/1981	Dow	N/A	N/A
4361267	12/1981	Wozniacki	N/A	N/A
4366916	12/1982	Guido et al.	N/A	N/A
4386729	12/1982	Schmidt	N/A	N/A
4457483	12/1983	Gagne	N/A	N/A
4530533	12/1984	Dieter	N/A	N/A
4628007	12/1985	Ledsham	N/A	N/A
4643380	12/1986	Copeland	N/A	N/A
4659045	12/1986	Flynn	N/A	N/A
4669689	12/1986	Jones	N/A	N/A
4697771	12/1986	Majors	N/A	N/A
4749011	12/1987	Rylander	N/A	N/A
4760982	12/1987	Cooke	141/390	B65B 67/1238
4836970	12/1988	Robbins, III	N/A	N/A
4884603	12/1988	Simpson	N/A	N/A
4890652	12/1989	Hoerner	N/A	N/A
4895456	12/1989	Morita	N/A	N/A
4909553	12/1989	Hantover	N/A	N/A
4940200	12/1989	Sawyer	N/A	N/A
4955496	12/1989	Nelson	N/A	N/A
4979547	12/1989	Hoerner	N/A	N/A
5018637	12/1990	Miller	N/A	N/A
5033780	12/1990	Wootten	N/A	N/A
5048778	12/1990	Wright	N/A	N/A
5054724	12/1990	Hutcheson	N/A	N/A
5056679	12/1990	Lonczak	N/A	N/A
5065965	12/1990	Aulabaugh	N/A	N/A
5080308	12/1991	Franks	N/A	N/A
5090756	12/1991	Pfisterer	N/A	N/A

5125459	12/1991	Richards	N/A	N/A
5129609	12/1991	Tobin	N/A	N/A
5186384	12/1992	Nelson	N/A	N/A
5271589	12/1992	Belous	N/A	N/A
5285988	12/1993	Bogren	N/A	N/A
5292093	12/1993	Shumake	N/A	N/A
5316060	12/1993	Hogdon et al.	N/A	N/A
5372269	12/1993	Sutton et al.	N/A	N/A
D355102	12/1994	Fridlind	N/A	N/A
5400989	12/1994	Gaskill	N/A	N/A
D359666	12/1994	Richards	N/A	N/A
D361185	12/1994	Seiler et al.	N/A	N/A
D374382	12/1995	Smith	N/A	N/A
5593117	12/1996	Alexander	N/A	N/A
5610230	12/1996	Yoshida et al.	N/A	N/A
D384867	12/1996	Willis	N/A	N/A
D390762	12/1997	Douglas	N/A	N/A
5716033	12/1997	Gibson	N/A	N/A
D391722	12/1997	Sheppard	N/A	N/A
D393299	12/1997	Hunt	N/A	N/A
5765614	12/1997	Kardosh	N/A	N/A
5816431	12/1997	Giannopoulos	N/A	N/A
5865486	12/1998	Bussani	N/A	N/A
5868364	12/1998	Macmillan	N/A	N/A
5871037	12/1998	Feldt	N/A	N/A
5897084	12/1998	Judge	N/A	N/A
5915768	12/1998	Young	N/A	N/A
5918651	12/1998	Gazdy et al.	N/A	N/A
5979842	12/1998	Fan	N/A	N/A
6007030	12/1998	Judge	141/390	B65F 1/1415
6035908	12/1999	Hoffman	N/A	N/A
6045263	12/1999	Keller et al.	N/A	N/A
6073943	12/1999	Serrault	N/A	N/A
6085647	12/1999	Burow	N/A	N/A
6116548	12/1999	Oleson	N/A	N/A
6116549	12/1999	Santa Cruz et al.	N/A	N/A
6131759	12/1999	Young	N/A	N/A
6135518	12/1999	Holthaus	N/A	N/A
6179306	12/2000	Maxwell	N/A	N/A
6189841	12/2000	Lapoint et al.	N/A	N/A
6202718	12/2000	Innocenti	N/A	N/A
6273156	12/2000	Carillo	N/A	N/A
6296212	12/2000	Monahan	N/A	N/A
6340037	12/2001	Stafford	N/A	N/A
6367747	12/2001	Mulle	N/A	N/A
6415713	12/2001	Abrams	N/A	N/A
6431435	12/2001	Jones et al.	N/A	N/A
6450461	12/2001	Lohmann	N/A	N/A
6481617	12/2001	Yang	N/A	N/A
6536488	12/2002	Pochobradsky	N/A	N/A

6554810	12/2002	Wilk et al.	N/A	N/A
6659407	12/2002	Asaro	N/A	N/A
D485166	12/2003	Clark	N/A	N/A
6708742	12/2003	Weathers et al.	N/A	N/A
D494853	12/2003	Chan	N/A	N/A
D494873	12/2003	Junod	N/A	N/A
D498667	12/2003	Clark	N/A	N/A
D500457	12/2004	Peeples et al.	N/A	N/A
D502582	12/2004	Boles	N/A	N/A
6860094	12/2004	Abrams	N/A	N/A
6866070	12/2004	King	N/A	N/A
6896015	12/2004	Beveridge	N/A	N/A
D513352	12/2004	Weathers et al.	N/A	N/A
6983965	12/2005	Bergell	N/A	N/A
D519007	12/2005	Lin	N/A	N/A
7066220	12/2005	Take et al.	N/A	N/A
7066379	12/2005	McLeod et al.	N/A	N/A
7152894	12/2005	Weathers et al.	N/A	N/A
7159761	12/2006	Abshire et al.	N/A	N/A
7246641	12/2006	Blessman	N/A	N/A
7302978	12/2006	Kolarik	N/A	N/A
D567464	12/2007	Dullum	N/A	N/A
7367600	12/2007	Lew et al.	N/A	N/A
7398913	12/2007	McClure	N/A	N/A
7407139	12/2007	Dolan	N/A	N/A
D576500	12/2007	Kim et al.	N/A	N/A
D578409	12/2007	Clark	N/A	N/A
7434721	12/2007	Feltz	N/A	N/A
D581754	12/2007	Vodrey	N/A	N/A
7494096	12/2008	Paloian et al.	N/A	N/A
D593721	12/2008	Koll	N/A	N/A
7604156	12/2008	Clohessy	N/A	N/A
7625026	12/2008	Lau	N/A	N/A
7651024	12/2009	Barner	N/A	N/A
7694838	12/2009	Yang	N/A	N/A
7712623	12/2009	Wentz et al.	N/A	N/A
7736057	12/2009	Vanbost	N/A	N/A
7810766	12/2009	Blessman	N/A	N/A
7815153	12/2009	Campbell et al.	N/A	N/A
D633268	12/2010	Bottita	N/A	N/A
D639519	12/2010	Gomez	N/A	N/A
8020686	12/2010	Babineau et al.	N/A	N/A
D648912	12/2010	Cantu	N/A	N/A
D676726	12/2012	Davis	N/A	N/A
D699014	12/2013	Lohrke et al.	N/A	N/A
8757563	12/2013	Muse	N/A	N/A
8840072	12/2013	Muse	N/A	N/A
D718584	12/2013	Seehoff et al.	N/A	N/A
8978964	12/2014	Ruggiere, Sr.	N/A	N/A
9056715	12/2014	Muse	N/A	N/A

9102432	12/2014	Muse	N/A	N/A
D738743	12/2014	Galmarini	N/A	N/A
9352870	12/2015	Muse	N/A	N/A
9517884	12/2015	Muse	N/A	N/A
9550623	12/2016	Muse	N/A	N/A
D785463	12/2016	Akana et al.	N/A	N/A
9701470	12/2016	Muse	N/A	N/A
D799294	12/2016	Burkman	N/A	N/A
D807717	12/2017	Tia	N/A	N/A
9896266	12/2017	Muse	N/A	N/A
D832066	12/2017	Takemura	N/A	N/A
D860000	12/2018	Baldelomar Bernardin	N/A	N/A
10563346	12/2019	Barre et al.	N/A	N/A
D889220	12/2019	Amundson	N/A	N/A
D899723	12/2019	Boyea	N/A	N/A
D900629	12/2019	Milos	N/A	N/A
D909211	12/2020	Bornmiller et al.	N/A	N/A
D919432	12/2020	Muse et al.	N/A	N/A
D929238	12/2020	Chen et al.	N/A	N/A
D935124	12/2020	Chen et al.	N/A	N/A
D941677	12/2021	Chen et al.	N/A	N/A
D956494	12/2021	Chen et al.	N/A	N/A
D957081	12/2021	Chen et al.	N/A	N/A
11634277	12/2022	Chen et al.	N/A	N/A
D984867	12/2022	Chen et al.	N/A	N/A
D985224	12/2022	Chen et al.	N/A	N/A
11851272	12/2022	Chen et al.	N/A	N/A
11858729	12/2023	Chen et al.	N/A	N/A
D1017174	12/2023	Chen et al.	N/A	N/A
11958685	12/2023	Chen et al.	N/A	N/A
D1054263	12/2023	Chen et al.	N/A	N/A
12172829	12/2023	Chen et al.	N/A	N/A
12312164	12/2024	Chen et al.	N/A	N/A
2002/0074247	12/2001	Tremblay	N/A	N/A
2002/0130224	12/2001	Asaro	N/A	N/A
2003/0173471	12/2002	Weathers et al.	N/A	N/A
2003/0218104	12/2002	Klotz	N/A	N/A
2004/0026578	12/2003	King	248/95	B65F 1/1415
2006/0011785	12/2005	McLean	N/A	N/A
2006/0032991	12/2005	Gaines	N/A	N/A
2006/0144467	12/2005	Butzer	N/A	N/A
2006/0273143	12/2005	Finch	N/A	N/A
2008/0023595	12/2007	Armaly, Jr.	248/97	B65F 1/1415
2008/0128479	12/2007	Bates et al.	N/A	N/A
2008/0134981	12/2007	Selenke et al.	N/A	N/A
2009/0121502	12/2008	Lau	N/A	N/A
2010/0108826	12/2009	Fernandez et al.	N/A	N/A
2010/0111447	12/2009	Vergo	N/A	N/A
2010/0142860	12/2009	Mincozzi	N/A	N/A

2010/0237202	12/2009	Minicozzi	493/162	B65B 67/1205
2010/0243650	12/2009	Manley	N/A	N/A
2010/0276247	12/2009	Babineau et al.	N/A	N/A
2011/0011921	12/2010	Sorensen	N/A	N/A
2011/0309208	12/2010	Muse	N/A	N/A
2011/0309209	12/2010	Muse	N/A	N/A
2011/0309210	12/2010	Muse	N/A	N/A
2012/0110959	12/2011	Serago, Jr.	N/A	N/A
2013/0019995	12/2012	Muse	N/A	N/A
2013/0020449	12/2012	Muse	N/A	N/A
2013/0092726	12/2012	McMahon	229/126	B29C 66/1122
2013/0140308	12/2012	Stowers	N/A	N/A
2013/0156350	12/2012	Turner	N/A	N/A
2014/0190850	12/2013	Glass	206/232	G09F 1/06
2014/0331616	12/2013	Muse	N/A	N/A
2014/0339379	12/2013	Muse	N/A	N/A
2015/0232222	12/2014	Muse	N/A	N/A
2015/0291354	12/2014	Muse	N/A	N/A
2016/0001975	12/2015	Muse	N/A	N/A
2016/0236864	12/2015	Muse	N/A	N/A
2016/0244243	12/2015	Durow	N/A	B65D 85/34
2017/0057699	12/2016	Lin	N/A	N/A
2017/0088350	12/2016	Muse	N/A	N/A
2017/0275095	12/2016	Muse	N/A	N/A
2018/0022546	12/2017	Wells	N/A	N/A
2021/0070541	12/2020	Chen et al.	N/A	N/A
2021/0070542	12/2020	Chen et al.	N/A	N/A
2023/0089585	12/2022	Chen et al.	N/A	N/A
2023/0166906	12/2022	Chen et al.	N/A	N/A
2023/0174299	12/2022	Chen et al.	N/A	N/A
2023/0192399	12/2022	Chen et al.	N/A	N/A
2024/0208723	12/2023	Chen et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202005016813	12/2005	DE	N/A
202006003095	12/2005	DE	N/A
202013007170	12/2012	DE	N/A
2687641	12/1992	FR	N/A
2004024200	12/2003	JP	N/A
2007029272	12/2006	WO	N/A
2016182492	12/2015	WO	N/A

OTHER PUBLICATIONS

US 11,597,594 B2, 03/2023, Chen et al. (withdrawn) cited by applicant
Chen, Shifeng; Corrected Notice of Allowance for U.S. Appl. No. 29/715,742, filed Dec. 4, 2019,
mailed Aug. 31, 2021, 6 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for Design U.S. Appl. No. 29/175,742, filed Dec. 4, 2019,

mailed Jun. 29, 2021, 42 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for Design U.S. Appl. No. 29/809,463, filed Sep. 28, 2021, mailed Feb. 24, 2022, 40 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for Design U.S. Appl. No. 29/809,466, filed Sep. 28, 2021, mailed Feb. 24, 2022, 39 pgs. cited by applicant
Google search Feb. 17, 2022, ebay.com, Jardineer garden leaf scoops yard, leaf grabber claws, <https://www.ebay.com/itm/144411174223> (Year: 2022). cited by applicant
Chen, Shifeng; Notice of Allowance for U.S. Appl. No. 29/840,177, filed May 26, 2022, mailed Jan. 24, 2023, 52 pgs. cited by applicant
lowes.com retrieved Jan. 9, 2022, leafeasy46.75 inX15 in bag insert, <https://www.lowes.com/pd/LeafEasy-46-in-x-16-75-in-Trash-Bag-Insert/50049703> (Year: 2022). cited by applicant
Lowe's.com retrieved on Jan. 9, 2022, leafEasy 39 gallon outdoor plastic lawn and leaf trash bag, <https://www.lowes.com/pd/LeafEasy-39-Gallon-Green-Plastic-Lawn-and-Leaf-Trash-Bag/1001315000> (Year: 2022). cited by applicant
Chen, Shifeng; Notice of Allowance for U.S. Appl. No. 29/840,178, filed May 26, 2022, mailed Jan. 25, 2023, 52 pgs. cited by applicant
Google search Jan. 9, 2023, ebay.com, Jardineer garden leaf scoops yard, leaf grabber claws, <https://www.ebay.com/itm/364100256621> (Year: 2022). cited by applicant
Chen, Shifeng; Notice of Allowance for Design U.S. Appl. No. 29/886,422, filed Mar. 8, 2023, mailed Oct. 12, 2023, 49 pgs. cited by applicant
Muse, John Richard; Applicant Initiated Interview Summary for U.S. Appl. No. 13/164,464, filed Jun. 20, 2011, mailed Mar. 11, 2014, 5 pgs. cited by applicant
Muse, John Richard; Final Office Action for U.S. Appl. No. 13/164,464, filed Jun. 20, 2011, mailed Jan. 10, 2014, 8 pgs. cited by applicant
Muse, John Richard; Final Office Action for U.S. Appl. No. 13/164,464, filed Jun. 20, 2011, mailed Sep. 23, 2013, 8 pgs. cited by applicant
Muse, John Richard; Final Office Action for U.S. Appl. No. 13/164,464, filed Jun. 20, 2011; mailed Feb. 22, 2013, 6 pgs. cited by applicant
Muse, John Richard; Issue Notification for U.S. Appl. No. 13/164,464, filed Jun. 20, 2011, mailed Sep. 3, 2014, 1 pg. cited by applicant
Muse, John Richard; Non-Final Office Action for U.S. Appl. No. 13/164,464, filed Jun. 20, 2011, mailed May 29, 2013, 12 pgs. cited by applicant
Muse, John Richard; Non-Final Office Action for U.S. Appl. No. 13/164,464, filed Jun. 20, 2011; mailed Nov. 16, 2012, 17 pgs. cited by applicant
Muse, John Richard; Notice of Allowance for U.S. Appl. No. 13/164,464, filed Jun. 20, 2011, mailed Apr. 29, 2014, 11 pgs. cited by applicant
Muse, John Richard; Restriction Requirement for U.S. Appl. No. 13/164,464, filed Jun. 20, 2011, mailed Oct. 19, 2012; 6 pgs. cited by applicant
Muse, John Richard; Non-Final Office Action for U.S. Appl. No. 14/447,043, filed Jul. 30, 2014, mailed Mar. 31, 2015, 32 pgs. cited by applicant
Muse, John Richard; Notice of Allowance for U.S. Appl. No. 14/447,043, filed Jul. 30, 2014, mailed Jul. 23, 2015, 12 pgs. cited by applicant
Muse, John Richard; Corrected Notice of Allowability for U.S. Appl. No. 14/447,058, filed Jul. 30, 2014, mailed Jul. 8, 2015, 4 pgs. cited by applicant
Muse, John Richard; Issue Notification for U.S. Appl. No. 14/447,058, filed Jul. 30, 2014, mailed Jul. 22, 2015, 1 pg. cited by applicant
Muse, John Richard; Notice of Allowance for U.S. Appl. No. 14/447,058, filed Jul. 30, 2014, mailed Mar. 30, 2015, 34 pgs. cited by applicant
Muse, John Richard; Non-Final Office Action for U.S. Appl. No. 14/748,772, filed Jun. 24, 2015,

mailed Oct. 2, 2015, 30 pgs. cited by applicant
Muse, John Richard; Applicant Initiated Interview Summary for U.S. Appl. No. 13/164,473, filed Jun. 20, 2011, mailed Dec. 2, 2013, 3 pgs. cited by applicant
Muse, John Richard; Final Office Action for U.S. Appl. No. 13/164,473, filed Jun. 20, 2011, mailed Dec. 13, 2013, 28 pgs. cited by applicant
Muse, John Richard; Issue Notification for U.S. Appl. No. 13/164,473, filed Jun. 20, 2011, mailed Jun. 4, 2014, 1 pg. cited by applicant
Muse, John Richard; Notice of Allowance for U.S. Appl. No. 13/164,473, filed Jun. 20, 2011, mailed Mar. 13, 2014, 12 pgs. cited by applicant
Muse, John Richard; Supplemental Notice of Allowability for U.S. Appl. No. 13/164,473, filed Jun. 20, 2011, mailed May 27, 2014, 6 pgs. cited by applicant
Muse, John; Final Office Action for U.S. Appl. No. 13/164,473, filed Jun. 20, 2011, mailed Mar. 13, 2013, 16 pgs. cited by applicant
Muse; Non-Final Office Action for U.S. Appl. No. 13/164,473, filed Jun. 20, 2011, mailed Dec. 3, 2012; 19 pgs. cited by applicant
Muse; Non-Final Office Action for U.S. Appl. No. 13/164,473, filed Jun. 20, 2011, mailed Jun. 25, 2013, 14 pgs. cited by applicant
Muse, John Richard; Final Office Action for U.S. Appl. No. 13/164,481, filed Jun. 20, 2011, mailed Apr. 5, 2013, 17 pgs. cited by applicant
Muse, John Richard; Non-Final Office Action for U.S. Appl. No. 13/164,481, filed Jun. 20, 2011, mailed Dec. 5, 2012; 18 pgs. cited by applicant
Muse, John Richard; Notice of Allowance for U.S. Appl. No. 13/164,481, filed Jun. 20, 2011, mailed Oct. 23, 2013, 11 pgs. cited by applicant
Muse; Non-Final Office Action for U.S. Appl. No. 13/164,481, filed Jun. 20, 2011, mailed Jul. 11, 2013, 11 pgs. cited by applicant
Muse, John Richard; Advisory Action for U.S. Appl. No. 13/551,575, filed Jul. 17, 2012, mailed Dec. 4, 2014, 3 pgs. cited by applicant
Muse, John Richard; Applicant-Initiated Interview Summary for U.S. Appl. No. 13/551,575, filed Jul. 17, 2012, mailed Dec. 19, 2014, 3 pgs. cited by applicant
Muse, John Richard; Final Office Action for U.S. Appl. No. 13/551,575, filed Jul. 17, 2012, Mailed Sep. 30, 2014, 22 pgs. cited by applicant
Muse, John Richard; Issue Notification for U.S. Appl. No. 13/551,575, filed Jul. 17, 2012, mailed May 27, 2015, 1 pg. cited by applicant
Muse, John Richard; Non-Final Office Action for U.S. Appl. No. 13/551,575, filed Jul. 17, 2012, mailed Dec. 6, 2013, 45 pgs. cited by applicant
Muse, John Richard; Non-Final Office Action for U.S. Appl. No. 13/551,575, filed Jul. 17, 2012, mailed May 16, 2014, 12 pgs. cited by applicant
Muse, John Richard; Notice of Allowance for U.S. Appl. No. 13/551,575, filed Jul. 17, 2012, mailed Feb. 2, 2015, 12 pgs. cited by applicant
Muse, John Richard; Advisory Action for U.S. Appl. No. 14/701,022, filed Apr. 30, 2015, mailed Jan. 21, 2016, 4 pgs. cited by applicant
Muse, John Richard; Applicant Interview Summary for U.S. Appl. No. 14/701,022, filed Apr. 30, 2015, mailed Dec. 22, 2015, 3 pgs. cited by applicant
Muse, John Richard; Final Office Action for U.S. Appl. No. 14/701,022, filed Apr. 30, 2015, mailed Oct. 22, 2015, 27 pgs. cited by applicant
Muse, John Richard; Issue Notification for U.S. Appl. No. 14/701,022, filed Apr. 30, 2015, mailed May 11, 2016, 1 pg. cited by applicant
Muse, John Richard; Non-Final Office Action for U.S. Appl. No. 14/701,022, filed Apr. 30, 2015, mailed Jun. 3, 2015, 12 pgs. cited by applicant
Muse, John Richard; Notice of Allowance for U.S. Appl. No. 14/701,022, filed Apr. 30, 2015,

mailed Feb. 8, 2016, 12 pgs. cited by applicant
Muse, John Richard; Issue Notification for U.S. Appl. No. 15/139,375, filed Apr. 27, 2016, mailed Jan. 4, 2017; 1 pg. cited by applicant
Muse, John Richard; Notice of Allowance for U.S. Appl. No. 15/139,375, filed Apr. 27, 2016; mailed Sep. 28, 2016; 35 pgs. cited by applicant
Muse, John, R.; Applicant Initiated Interview Summary for U.S. Appl. No. 15/139,375, filed Apr. 27, 2016, mailed Jun. 6, 2016, 3 pgs. cited by applicant
Muse, John Richard; Issue Notification for U.S. Appl. No. 15/373,103, filed Dec. 8, 2016, mailed Jun. 21, 2017; 1 page. cited by applicant
Muse, John Richard; Non-final Office Action for U.S. Application No. 15/373, 103, filed Dec. 8, 2016, mailed Feb. 7, 2017; 9 pgs. cited by applicant
Muse, John Richard; Notice of Allowance for Application No. 15/373, 103, filed Dec. 8, 2016, mailed Mar. 16, 2017; 6 pgs. cited by applicant
Muse, John Richard, Notice of Allowance for U.S. Appl. No. 14/854,777, filed Sep. 15, 2015, mailed Sep. 19, 2016, 10 pgs. cited by applicant
Muse, John Richard; Advisory Action for U.S. Appl. No. 14/854,777, filed Sep. 15, 2015, mailed Jul. 25, 2016, 3 pgs. cited by applicant
Muse, John Richard; Applicant Initiated Interview Summary for U.S. Appl. No. 14/854,777, filed Sep. 15, 2015, mailed Jun. 16, 2016, 3 pgs. cited by applicant
Muse, John Richard; Applicant-Initiated Interview Summary for U.S. Appl. No. 14/854,777, filed Sep. 15, 2015, mailed Aug. 26, 2016; 3 pgs. cited by applicant
Muse, John Richard; Final Office Action for U.S. Appl. No. 14/854,777, filed Sep. 15, 2015, mailed May 24, 2016, 12 pgs. cited by applicant
Muse, John Richard; Issue Notification for U.S. Appl. No. 14/854,777, filed Sep. 15, 2015, mailed Nov. 22, 2016; 1 pg. cited by applicant
Muse, John Richard; Non-Final Office Action for U.S. Appl. No. 14/854,777, filed Sep. 15, 2015, mailed Dec. 22, 2015, 38 pgs. cited by applicant
Muse, John Richard; Issue Notification for U.S. Appl. No. 15/615,895, filed Jun. 7, 2017, mailed Jan. 31, 2018, 1 pg. cited by applicant
Muse, John Richard; Notice of Allowance for U.S. Appl. No. 15/615,895, filed Jun. 7, 2017, mailed Dec. 8, 2017, 13 pgs. cited by applicant
Muse; Non-Final Office Action U.S. Appl. No. 15/615,895, filed Jun. 7, 2017, mailed Sep. 14, 2017; 38 pgs. cited by applicant
Muse, John Richard; Final Office Action for U.S. Appl. No. 13/551,583, filed Jul. 17, 2012, mailed Dec. 31, 2014, 16 pgs. cited by applicant
Muse, John Richard; Non-Final Office Action for U.S. Appl. No. 13/551,583, filed Jul. 17, 2012, mailed Jul. 15, 2014, 38 pgs. cited by applicant
Muse, John Richard; Non-Final Office Action for U.S. Appl. No. 13/551,583, filed Jul. 17, 2012, mailed Apr. 1, 2015, 12 pgs. cited by applicant
Muse, John Richard; Notice of Allowance for U.S. Appl. No. 13/551,583, filed Jul. 17, 2012, mailed Sep. 28, 2015, 13 pgs. cited by applicant
Muse, John Richard; Supplemental Notice of Allowability for U.S. Appl. No. 13/551,583, filed Jul. 17, 2012, mailed Oct. 15, 2015, 5 pgs. cited by applicant
alibaba.com; Article entitled: "Heavy Duty 32 Gallon Reusable Collapsible Yard Waste Container", publicly available prior to Aug. 19, 2019, 4 pgs. cited by applicant
Chen, Shifeng; Final Office Action for U.S. Appl. No. 16/703,272, filed Dec. 4, 2019, mailed Oct. 28, 2022, 19 pgs. cited by applicant
Chen, Shifeng; Final Office Action for U.S. Appl. No. 16/703,272, filed Dec. 4, 2019, mailed Feb. 18, 2022, 14 pgs. cited by applicant
Chen, Shifeng; Final Office Action for U.S. Appl. No. 16/703,272, filed Dec. 4, 2019, mailed Feb.

29, 2024, 26 pgs. cited by applicant
Chen, Shifeng; Final Office Action for U.S. Appl. No. 16/703,272, filed Dec. 4, 2019, mailed Jul. 19, 2023, 23 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 16/703,272, filed Dec. 4, 2019, mailed Nov. 3, 2023, 20 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 16/703,272, filed Dec. 4, 2019, mailed Feb. 9, 2023, 19 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 16/703,272, filed Dec. 4, 2019, mailed May 20, 2022, 19 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 16/703,272, filed Dec. 4, 2019, mailed Sep. 17, 2021, 49 pgs. cited by applicant
donthuntmenow.club; Article entitled: "Paper Leaf Bag", Dec. 1, 2018, 23 pgs. cited by applicant
knowledgeboard.co; Article entitled: "Leaf Bag Holder", Apr. 21, 2019, 23 pgs. cited by applicant
The Home Depot; Article entitled: "Leaf Easy Plastic Leaf and Lawn Chute", publicly available prior to Aug. 19, 2019, 3 pgs. cited by applicant
Chen, Shifeng; Final Office Action for U.S. Appl. No. 18/109,533, filed Feb. 14, 2023, mailed Mar. 7, 2024, 27 pgs. cited by applicant
Chen, Shifeng; Final Office Action for U.S. Appl. No. 18/109,533, filed Feb. 14, 2023, mailed Aug. 16, 2023, 57 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 18/109,533, filed Feb. 14, 2023, mailed Nov. 29, 2023, 34 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 18/109,533, filed Feb. 14, 2023, mailed Apr. 24, 2023, 14 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 16/703,184, filed Dec. 4, 2019, mailed Jan. 14, 2022, 49 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 16/703,184, filed Dec. 4, 2019, mailed May 27, 2022, 12 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for U.S. Appl. No. 16/703,184, filed Dec. 4, 2019, mailed Nov. 3, 2022, 17 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for U.S. Appl. No. 16/703,184, filed Dec. 4, 2019, mailed Mar. 15, 2023, 11 pgs. cited by applicant
Chen, Shifeng; Requirement for Restriction/Election for U.S. Appl. No. 16/703,184, filed Dec. 4, 2019, mailed Dec. 3, 2021, 6 pgs. cited by applicant
Chen, Shifeng; Final Office Action for U.S. Appl. No. 18/051,746, filed Nov. 1, 2022, mailed May 31, 2023, 8 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 18/051,746, filed Nov. 1, 2022, mailed Feb. 14, 2023, 42 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 18/051,746, filed Nov. 1, 2022, mailed Aug. 22, 2023, 18 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for U.S. Appl. No. 18/051,746, filed Nov. 1, 2022, mailed Dec. 11, 2023, 12 pgs. cited by applicant
Chen, Shifeng; Requirement for Restriction/Election for U.S. Appl. No. 18/051,746, filed Nov. 1, 2022, mailed Feb. 6, 2023, 8 pgs. cited by applicant
Chen, Shifeng; Certificate of Correction for U.S. Appl. No. 18/103,235, filed Jan. 30, 2023, mailed Feb. 13, 2024, 1 pg. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 18/103,235, filed Jan. 30, 2023, mailed May 17, 2023, 50 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for U.S. Appl. No. 18/103,235, filed Jan. 30, 2023, mailed Oct. 27, 2023, 16 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 18/600,227, filed Mar. 8, 2024, mailed

May 7, 2024, 10 pgs. cited by applicant
Chen, Shifeng; Certificate of Correction for U.S. Appl. No. 18/103,508, filed Jan. 31, 2023, mailed Feb. 13, 2024, 1 pg. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 18/103,508, filed Jan. 31, 2023, mailed May 17, 2023, 46 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for U.S. Appl. No. 18/103,508, filed Jan. 31, 2023, mailed Oct. 18, 2023, 12 pgs. cited by applicant
Chen, Shifeng; Corrected Notice of Allowance for Design U.S. Appl. No. 29/715,749, filed Dec. 4, 2019, mailed Jun. 8, 2021, 6 pgs. cited by applicant
Chen, Shifeng; Corrected Notice of Allowance for Design U.S. Appl. No. 29/715,749, filed Dec. 4, 2019, mailed Jul. 26, 2021, 6 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for Design U.S. Appl. No. 29/715,749, filed Dec. 4, 2019, mailed Apr. 21, 2021, 36 pgs. cited by applicant
Chen, Shifeng; Corrected Notice of Allowance for U.S. Appl. No. 29/800,663, filed Jul. 22, 2021, mailed Oct. 18, 2021, 34 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for U.S. Appl. No. 29/800,663, filed Jul. 22, 2021, mailed Oct. 4, 2021, 6 pgs. cited by applicant
Chen, Shifeng; Corrected Notice of Allowance for Design U.S. Appl. No. 29/715,742, filed Dec. 4, 2019, mailed Oct. 4, 2021, 6 pgs. cited by applicant
Chen, Shifeng; Final Office Action for U.S. Appl. No. 16/703,272, filed Dec. 4, 2019, mailed Sep. 12, 2024, 14 pgs. cited by applicant
Chen, Shifeng; Final Office Action for U.S. Appl. No. 18/109,533, filed Feb. 14, 2023, mailed Oct. 22, 2024, 29 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 16/703,272, filed Dec. 4, 2019, mailed Jun. 7, 2024, 29 pgs. cited by applicant
Chen, Shifeng; Non-Final Office Action for U.S. Appl. No. 18/109,533, filed Feb. 14, 2023, mailed Jun. 27, 2024, 35 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for U.S. Appl. No. 18/600,227, filed Mar. 8, 2024, mailed Aug. 28, 2024, 49 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for Design U.S. Appl. No. 29/907,439, filed Jan. 5, 2024, mailed Aug. 7, 2024, 56 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for U.S. Appl. No. 16/703,272, filed Dec. 4, 2019, mailed Jan. 15, 2025, 9 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for U.S. Appl. No. 18/109,533, filed Feb. 14, 2023, mailed Feb. 5, 2025, 12 pgs. cited by applicant
Chen, Shifeng; Notice of Allowance for Design U.S. Appl. No. 29/978,731, filed Dec. 13, 2024, mailed Jun. 11, 2025, 13 pgs. cited by applicant

Primary Examiner: Wujciak; Alfred J

Attorney, Agent or Firm: Taylor Duma LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a divisional of U.S. application Ser. No. 18/051,746, filed Nov. 1, 2022, which is a continuation of U.S. application Ser. No. 16/703,184, filed Dec. 4, 2019, which issued into U.S. Pat. No. 11,634,277 on

TECHNICAL FIELD

(1) This disclosure relates to lawn refuse disposal. More specifically, this disclosure relates to a lawn refuse bag insert for holding open a lawn refuse bag.

BACKGROUND

(2) Lawn refuse (e.g., leaves, grass clippings, dirt, sticks, etc.) is typically bagged for removal from a lawn. Lawn refuse bags define a cavity for receiving lawn refuse, and are often formed from a flexible material, such as paper or plastic, and are discarded along with the lawn refuse. However, flexible refuse bags can be prone to collapsing or tipping over, and can therefore be difficult to fill. Furthermore, a user's hands are typically occupied with carrying and dumping the lawn refuse in the cavity of the refuse bag, and cannot be used to provide needed support to the refuse bag.

(3) Typically, closing the refuse bag after filling the refuse bag requires folding and rolling a top end of the refuse bag. As such, a sufficient amount of space must be left within the cavity at the top end of the refuse bag to facilitate closing the top end of the bag. A user must be aware of how much lawn refuse is in the refuse bag and take care not to fill the refuse bag too fully. In instances where the refuse bag is too full to close the top end, lawn refuse must be removed from the refuse bag to allow for proper closure.

(4) A rake can be used to facilitate gathering lawn refuse and lifting the refuse into the refuse bag. Rakes typically comprise a long handle and are operated with two hands. Some users may not own a rake for facilitating the disposal of lawn refuse. Other users who do own a rake must use both hands to navigate the long-handled rake when lifting the refuse from the yard and dumping it into the refuse bag.

SUMMARY

(5) It is to be understood that this summary is not an extensive overview of the disclosure. This summary is exemplary and not restrictive, and it is intended neither to identify key or critical elements of the disclosure nor delineate the scope thereof. The sole purpose of this summary is to explain and exemplify certain concepts of the disclosure as an introduction to the following complete and extensive detailed description.

(6) Disclosed is a lawn refuse bag insert comprising a bag stand defining a top stand end and a bottom stand end and comprising an end wall and a first side wall, the first side wall hingedly coupled to the end wall; and a first rake detachably coupled to the bag stand, wherein the lawn refuse bag insert is formed as a blank.

(7) A lawn refuse disposal assembly is also disclosed, the lawn refuse disposal assembly comprising a lawn refuse bag comprising a bag body defining a top end, a first handle assembly coupled to the bag body at the top end, and a second handle assembly coupled to the bag body at the top end; and a lawn refuse bag insert comprising a bag stand and a rake detachably coupled to the bag stand, the bag stand configured to engage an interior cavity of the lawn refuse bag.

(8) Also disclosed is a method for using a lawn refuse disposal assembly comprising providing a lawn refuse bag insert comprising a bag stand and a rake, the bag stand comprising an end wall and a side wall; detaching the rake from the bag stand; engaging the bag stand with a lawn refuse bag; shifting lawn refuse with the rake into the lawn refuse bag; disengaging the bag stand from the lawn refuse bag; and tying a first handle assembly of the lawn refuse bag with a second handle assembly of the lawn refuse bag.

(9) Additionally, disclosed is a lawn refuse bag insert comprising a rear wall disposed at a rear end of the lawn refuse bag insert; a first side wall hingedly coupled to the rear wall at a first side of the lawn refuse bag insert; and a second side wall hingedly coupled to the rear wall at a second side of the lawn refuse bag insert opposite the first side; wherein the lawn refuse bag insert further defines a front end opposite the rear end, and wherein the lawn refuse bag insert is unobstructed at the front

end from a top end of the lawn refuse bag insert to a bottom end of the lawn refuse bag insert.

(10) Also disclosed is a lawn refuse bag insert comprising a rear wall disposed at a rear end of the lawn refuse bag insert; a first side wall hingedly coupled to the rear wall at a first side of the lawn refuse bag insert; and a second side wall hingedly coupled to the rear wall at a second side of the lawn refuse bag insert opposite the first side; wherein a top edge of the lawn refuse bag insert is disposed at a top end of the lawn refuse bag insert, and wherein the top edge is substantially U-shaped.

(11) Furthermore, disclosed is a lawn refuse bag insert comprising a bag stand defining a top stand end and a bottom stand end, the bag stand comprising an end wall and a first side wall, the first side wall hingedly coupled to the end wall, the first side wall defining a slot, the slot defining a retainer tab, a finger opening defined between the retainer tab and the top stand end; and a first rake detachably coupled to the bag stand; wherein the lawn refuse bag is configurable in a blank configuration and an erected configuration, and wherein each of the end wall and the first side wall are disposed in a vertical orientation in the erected configuration.

(12) Various implementations described in the present disclosure may include additional systems, methods, features, and advantages, which may not necessarily be expressly disclosed herein but will be apparent to one of ordinary skill in the art upon examination of the following detailed description and accompanying drawings. It is intended that all such systems, methods, features, and advantages be included within the present disclosure and protected by the accompanying claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The features and components of the following figures are illustrated to emphasize the general principles of the present disclosure. Corresponding features and components throughout the figures may be designated by matching reference characters for the sake of consistency and clarity.

(2) FIG. 1A is a top perspective view of a lawn refuse bag in an upright, open, and assembled orientation, in accordance with one aspect of the present disclosure.

(3) FIG. 1B is a detail view of a handle assembly of the lawn refuse bag of FIG. 1.

(4) FIG. 1C is a top view of the lawn refuse bag of FIG. 1A.

(5) FIG. 1D is a bottom perspective view of the lawn refuse bag of FIG. 1A.

(6) FIG. 2 is a bag blank in an unassembled orientation that can be assembled to form the lawn refuse bag of FIG. 1A.

(7) FIG. 3A is a top perspective view of the lawn refuse bag of FIG. 1A in a partially folded orientation.

(8) FIG. 3B is a front view of the lawn refuse bag of FIG. 1A in a folded orientation.

(9) FIG. 4A is a front view of the lawn refuse in the partially folded orientation, according to another aspect of the present disclosure.

(10) FIG. 4B is a front view of the lawn refuse bag of FIG. 4A in the folded orientation, according to another aspect of the present disclosure.

(11) FIG. 5 is a top perspective view of the lawn refuse bag of FIG. 1A in a closed orientation.

(12) FIG. 6 is a detail view of a pair of handle assemblies of the lawn refuse bag of FIG. 1A in a tied configuration.

(13) FIG. 7 is a top perspective view of a refuse bag insert comprising a bag stand and a pair of rakes, in accordance with one aspect of the present disclosure.

(14) FIG. 8A is a top perspective view of the bag stand of FIG. 7.

(15) FIG. 8B is a perspective view illustrating a stand bend line of the bag stand of FIG. 7.

(16) FIG. 8C is a perspective view illustrating a corrugated paper sheet material of the bag stand of FIG. 7.

(17) FIG. 9 is a front view of the pair of rakes of FIG. 7.

(18) FIG. 10 is a top perspective view of the bag stand of FIG. 7 assembled with the lawn refuse bag of FIG. 1 to define a lawn refuse disposal assembly.

(19) FIG. 11 illustrates the lawn refuse disposal assembly of FIG. 10 in a sideways orientation.

(20) FIG. 12 illustrates the refuse bag insert comprising indicia printed thereon, according to another aspect of the present disclosure.

(21) FIG. 13A illustrates the lawn refuse disposal assembly of FIG. 10 in use in an upright orientation.

(22) FIG. 13B illustrates the lawn refuse disposal assembly of FIG. 10 in use in a sideways orientation.

DETAILED DESCRIPTION

(23) The present disclosure can be understood more readily by reference to the following detailed description, examples, drawings, and claims, and the previous and following description. However, before the present devices, systems, and/or methods are disclosed and described, it is to be understood that this disclosure is not limited to the specific devices, systems, and/or methods disclosed unless otherwise specified, and, as such, can, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular aspects only and is not intended to be limiting.

(24) The following description is provided as an enabling teaching of the present devices, systems, and/or methods in its best, currently known aspect. To this end, those skilled in the relevant art will recognize and appreciate that many changes can be made to the various aspects of the present devices, systems, and/or methods described herein, while still obtaining the beneficial results of the present disclosure. It will also be apparent that some of the desired benefits of the present disclosure can be obtained by selecting some of the features of the present disclosure without utilizing other features. Accordingly, those who work in the art will recognize that many modifications and adaptations to the present disclosure are possible and can even be desirable in certain circumstances and are a part of the present disclosure. Thus, the following description is provided as illustrative of the principles of the present disclosure and not in limitation thereof.

(25) As used throughout, the singular forms “a,” “an” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “an element” can include two or more such elements unless the context indicates otherwise.

(26) Ranges can be expressed herein as from “about” one particular value, and/or to “about” another particular value. When such a range is expressed, another aspect includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by use of the antecedent “about,” it will be understood that the particular value forms another aspect. It will be further understood that the endpoints of each of the ranges are significant both in relation to the other endpoint, and independently of the other endpoint.

(27) For purposes of the current disclosure, a material property or dimension measuring about X or substantially X on a particular measurement scale measures within a range between X plus an industry-standard upper tolerance for the specified measurement and X minus an industry-standard lower tolerance for the specified measurement. Because tolerances can vary between different materials, processes and between different models, the tolerance for a particular measurement of a particular component can fall within a range of tolerances.

(28) As used herein, the terms “optional” or “optionally” mean that the subsequently described event or circumstance can or cannot occur, and that the description includes instances where said event or circumstance occurs and instances where it does not.

(29) The word “or” as used herein means any one member of a particular list and also includes any combination of members of that list. Further, one should note that conditional language, such as, among others, “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain aspects include,

while other aspects do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more particular aspects or that one or more particular aspects necessarily include logic for deciding, with or without user input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular aspect.

(30) Disclosed are components that can be used to perform the disclosed methods and systems. These and other components are disclosed herein, and it is understood that when combinations, subsets, interactions, groups, etc. of these components are disclosed that while specific reference of each various individual and collective combinations and permutations of these may not be explicitly disclosed, each is specifically contemplated and described herein, for all methods and systems. This applies to all aspects of this application including, but not limited to, steps in disclosed methods. Thus, if there are a variety of additional steps that can be performed it is understood that each of these additional steps can be performed with any specific aspect or combination of aspects of the disclosed methods.

(31) Disclosed in the present application is a refuse bag insert for holding open a lawn refuse bag, and associated methods, systems, devices, and various apparatus. Example aspects of the refuse bag insert can comprise at least one side wall and an end wall and at least one detachable rake. It would be understood by one of skill in the art that the disclosed refuse bag insert is described in but a few exemplary aspects among many. No particular terminology or description should be considered limiting on the disclosure or the scope of any claims issuing therefrom.

(32) FIG. 1A illustrates a first aspect of a lawn refuse bag **100** according to the present disclosure. The lawn refuse bag **100** is depicted in an upright, assembled, and unfolded orientation, such that it is ready for use. As shown, the lawn refuse bag **100** can comprise a bag body **110** and a pair of handle assemblies **170a,170b** extending from the bag body **110**. Example aspects of the bag body **110** can be formed from a single bag blank **200** (shown in FIG. 2); however, in other aspects, the bag body **110** can be formed from multiple bag blanks. As shown, the bag body **110** can comprise a first end panel, such as a front sidewall panel **112**, a second end panel, such as a rear sidewall panel **114**, a first sidewall panel, such as a right sidewall panel **116**, and a second sidewall panel, such as a left sidewall panel **118**. Example aspects of the rear sidewall panel **114** can define a first rear sidewall subpanel **120** and a second rear sidewall subpanel **122** which can be joined together to retain the lawn refuse bag **100** in the assembled orientation, as shown. In various aspects, a joining seam **124** can be formed where the first rear sidewall subpanel **120** can be joined with the second rear sidewall subpanel **122**. In other aspects, the joining seam **124** can be formed elsewhere on the side or end panels. For example, in another aspect, the front sidewall panel **112** may define first and second front sidewall subpanels that can be joined together to retain the lawn refuse bag **110** in the assembled orientation and to define the joining seam **124**. In another example aspect, the joining seam **124** may be formed between any pair of adjacent panels, such as, for example, between the left sidewall panel **118** and the rear sidewall panel **120**.

(33) According to example aspects, the front sidewall panel **112**, rear sidewall panel **114**, right sidewall panel **116**, and left sidewall panel **118** can define a sidewall enclosure **150** of the bag body **110** in the assembled orientation. An inner sidewall surface **152** of the sidewall enclosure **150** can define an interior cavity **160**, as shown, which can be configured to receive lawn refuse (e.g., grass clippings, dirt, sticks, leaves **1310** (shown in FIG. 13A), etc.), as described in further detail below. Example aspects of the sidewall enclosure **150**, such as the aspect depicted in FIG. 1A, can define a substantially rectangular cross-section. However, other aspects of the bag body **110** can define any other suitable cross-sectional shape, such as, for example, a square, circle, triangle, pentagon, and the like. As shown, the sidewall enclosure **150** can define four vertical corners **154**, relative to the orientation shown, wherein each of the vertical corners **154** can be defined at an intersection of adjacent sidewall panels **112,114,116,118**.

(34) According to example aspects, the bag body **110** can define a top end **102**, relative to the

orientation shown, at a first end **156** of the sidewall enclosure **150**, and a bottom end **104**, relative to the orientation shown, at a second end **158** of the sidewall enclosure **150** opposite the first end **156**. Example aspects of the bag body **110** can further comprise a base panel, such as a bottom panel **130**, positioned at the bottom end **104** of the bag body **110** and oriented about perpendicular to the sidewall panels **112,114,116,118**. The bottom panel **130** can extend fully between the sidewall panels **112,114,116,118**, such that the bottom end **104** of the bag body **110** can be closed and access to the interior cavity **160** can be prohibited at the bottom end **104**. As such, an inner bottom panel surface **132** of the bottom panel **130** can further define the interior cavity **160**. However, as shown, the top end **102** of the bag body **110** can define a top opening **106** that can allow access to the interior cavity **160**. In the present aspect, the top end **102** of the bag body **110** can be oriented in an open orientation, wherein lawn refuse can be inserted into the interior cavity **160** through the top opening **106** of the bag body **110**. The top end **102** of the bag body **110** can also be oriented in a closed orientation, as further shown and described with respect to FIGS. 5 and 6. According to example aspects, in the upright and assembled orientation, as shown, the bottom panel **130** of the lawn refuse bag **100** can be configured to rest on a ground surface (e.g., a lawn or yard). Example aspects of the bottom panel **130** can be substantially flat and can provide suitable dimensions for providing a stable base for the lawn refuse bag **100**, which can aid in preventing the lawn refuse bag **100** from tipping over from the desired upright orientation. The lawn refuse bag **100** can further be sized to allow a substantial amount of lawn refuse to be received within the interior cavity **160**. Moreover, the top opening **106** of the bag body **110** can be dimensioned to allow a substantially sized cluster of lawn refuse to be inserted therethrough into the lawn refuse bag **100**.

(35) Various example aspects of the bag body **110** can comprise a substantially flexible material, such as paper, as shown. In some aspects, the bag body **110** can comprise a single layer of paper, while in other aspects, the bag body **110** can comprise a double layer of paper. In aspects comprising a double layer of paper, the stiffness and strength of the bag body **110** can be increased. Other aspects of the bag body **110** can comprise any other suitable number of layers. Furthermore, other aspects of the bag body **110** can define any other suitable flexible material, such as, for example, flexible plastic, fabric, or any other suitable flexible material or combination thereof. However, still other aspects of the bag body **110** can define a more rigid material, such as, for example, paperboard, polymer, metal, wood, composite, or any other suitable material or combination thereof. In some aspects, the inner sidewall surface **152** and/or inner bottom panel surface **132** can comprise a coating, such as, for example, a water resistant coating. Other aspects of the lawn refuse bag **100** may not comprise such a coating.

(36) According to example aspects, each of the handle assemblies **170a,170b** can comprise a handle portion **172** and a connection portion **174**. The connection portion **174** can be coupled to the lawn refuse bag **100** and the handle portion **172** can extend away from the lawn refuse bag **100**, as shown. In the present aspect, each handle assembly **170a,170b** can generally define an inverted U-shape, relative to the orientation shown, wherein the connection portion **174** can define the ends of the U-shape and the handle portion **172** can define the middle of the U-shape. As shown, a first one of the handle assemblies **170a** can be coupled with the front sidewall panel **112** and a second one of the handle assemblies **170b** can be coupled with the rear sidewall panel **114**. Referring to the second handle assembly **170b**, the connection portion **174** can be secured to the rear sidewall panel **114** to attach the handle assembly **170b** to the lawn refuse bag **100**, and the handle portion **172** can extend away from the top end **102** of the bag body **110** proximate the top opening **106**. The connection portion **174** can be secured to the rear sidewall panel **114** on the inner sidewall surface **152** by a fastener, such as, for example, an adhesive, such as tape or glue. In other aspects, any other suitable type of fastener known in the art can be used. The first handle assembly **170a** can be similarly formed and secured to the front sidewall panel **112**.

(37) In example aspects, such as the aspect depicted in FIG. 1A, the handle assemblies **170a,170b**

can be formed from twisted paper cord. Twisted paper cord can be made from paper that can be tightly twisted, and in some cases can define a crinkle texture, such that the strength and thickness of the paper can be increased. The increased strength and thickness of the handle assemblies **170a,170b** can allow the lawn refuse bag **100** to be carried by the handle assemblies **170a,170b** even when weighted down by lawn refuse. In other aspects, the handle assemblies **170a,170b** can be formed from any other suitable material known in that art having a sufficient strength to allow for carrying the bag in weighted conditions. Furthermore, according to some example aspects, a flexible wire (not shown) or other similar reinforcing structure can extend through each of the handle assemblies **170a,170b** to supply additional strength and stiffness to the handle assemblies **170a,170b**.

(38) According to example aspects, one or more flaps segments **140** can extend from the top end **102** of the bag body **110**. For example, in the present aspect, each of the sidewall panels **112,114,116,118** can comprise a corresponding top flap segment **140** extending from the first end **156** of the sidewall enclosure **150**. Each of the top flap segments **140** can be folded inward about 180° relative to the corresponding sidewall panel **112,114,116,118**, such that the top flap segments **140** can lie against the inner sidewall surface **152** of the sidewall enclosure **150**. The top flap segments **140** can be secured to the corresponding sidewall panels **112,114,116,118** by a fastener, such as, for example, an adhesive, such as tape or glue. In other aspects, any other suitable fastener known in the art can secure the top flap segments **140** to the inner sidewall surface **152**. In some aspects, as shown, one or more slits **142** can be formed in the top flap segments **140** extending from the front and rear sidewall panels **112,114** to accommodate folding the top flap segments **140** around the corresponding handle assemblies **170a,170b**. For example, in the present aspect, the corresponding top flap segments **140** can comprise a pair of the slits **142** which can be configured to receive corresponding portions of the corresponding handle assembly **170a,170b** therein. In some aspects, the top flap segments **140** of the front and rear sidewall panels **112,114** can partially overlay the corresponding handle assembly **170a,b**, and the connection portions **174** can be secured between the top flap segment **140** and the corresponding front or rear sidewall panel **112,114**. The second handle assembly **170b** is shown and described in further detail with reference to FIG. **1B**.

(39) Furthermore, in some aspects, a first reinforcement strip (not shown) can be received between the bag body **110** and a corresponding one of the top flap segments **140** for granting added structure to the bag body **110** at the top end **102** thereof. Example aspects of the first reinforcement strip can be more rigid than the bag body **110**. For example, in a particular aspect, the first reinforcement strip can be a substantially rectangular piece of paperboard. In the present aspect, the first reinforcement strip can be received between the front sidewall panel **112** and the corresponding top flap where the connection portion **174** of the first handle assembly **170a** can be attached. As such, the first reinforcement strip can also serve to reinforce the first handle assembly **170a**. According to example aspects, a second reinforcement strip (not shown) may also be providing for granting added structure to the rear sidewall panel **114** where the second handle assembly **170b** can be attached. Moreover, in other aspects, reinforcement strips may also be provided between each of the right and left sidewall panels **116,118** and the corresponding top flap segments **140**.

(40) In the present aspect, the lawn refuse bag **100** is in an open orientation wherein the top opening **106** can be fully open and access to the interior cavity **160** through the top opening **106** can be unrestricted. The handle assemblies **170a,170b** can be disengaged from one another in the open orientation, as shown. According to example aspects, the lawn refuse bag **100** can also be oriented in a closed orientation (shown in FIG. **5**), wherein the handle portions **172** of the handle assemblies **170a,170b** can be engaged with one another (for example, tied together) to close or partially close the top opening **106** of the lawn refuse bag **100**. In the closed orientation, the lawn refuse received within the interior cavity **160** can be prevented from escaping the interior cavity **160** and additional lawn refuse can be prevented from insertion into the interior cavity **160**. The closed orientation and the method for tying the handle assemblies **170a,170b** together are shown

and described in further detail with reference to FIGS. 5 and 6.

(41) FIG. 1B is a close-up view of the second handle assembly **170b** attached to the rear sidewall panel **114** of the lawn refuse bag **100**. As shown, the corresponding top flap segment **140** is folded inward to lie against the rear sidewall panel **114** and can partially overlay the connection portions **174**. FIG. 1C is top view of the lawn refuse bag **100**, illustrating the inner sidewall surface **152** of the sidewall enclosure **150** and the interior cavity **160** for receiving the lawn refuse. The inner bottom panel surface **132** of the bottom panel **130**, according to one particular example aspect of the lawn refuse bag **100**, is also illustrated. As shown, the bottom panel **130** can be folded to form various bottom panel seams **126** of the bottom panel **130** in the assembled orientation. According to example aspects, the bottom panel **130** can be folded at a plurality of bottom panel bend lines **250** (shown in FIG. 2) to form the bottom panel seams **126**. FIG. 1D illustrates an outer bottom panel surface **134** of the bottom panel **130**, opposite the inner bottom panel surface **132** (shown in FIG. 1A), according to one particular example aspect of the lawn refuse bag **100**. The various bottom panel seams **126** of the bottom panel **130** in the assembled orientation are also shown.

(42) FIG. 2 illustrates the bag blank **200** for forming the lawn refuse bag **100** (shown in FIG. 1A) in an unassembled orientation. Various dimensions for the bag blank **200** are shown in inches, according to an example aspect of the present disclosure. The dimensions disclosed herein are merely examples and should not be construed as limiting. As shown, the bag blank **200** can be a single, continuous blank defining a first blank end, such as a left blank end **202**, relative to the orientation shown, and an opposite second blank end, such as a right blank end **204**, relative to the orientation shown. Each of the sidewall panels **112,114,116,118** can be connected to adjacent sidewall panels **112,114,116,118** by a corner bend line **210**, and the corner bend lines **210** can define the vertical corners **154** (shown in FIG. 1A) in the assembled orientation (shown in FIG. 1A). For example, the first rear sidewall subpanel **120** of the rear sidewall panel **114** can be connected to the left sidewall panel **118** by a first corner bend line **210a**, the left sidewall panel **118** can be connected to the front sidewall panel **112** by a second corner bend line **210b**, the front sidewall panel **112** can be connected to the right sidewall panel **116** by a third corner bend line **210c**, and the right sidewall panel **116** can be connected to the second rear sidewall subpanel **122** of the rear sidewall panel **114** by a fourth corner bend line **210d**.

(43) Each of the left sidewall panel **118** and right sidewall panel **116** can also comprise a vertical center bend line **220a,b**, respectively, relative to the orientation shown, extending along a centerline thereof. The center bend lines **220a,b** can facilitate folding of the lawn refuse bag **100**, as described in further detail with reference to FIG. 3A. Additionally, the bag blank **200** can define a horizontal bend line **238**, relative to the orientation shown, that can extend across the sidewall panels **112,114,116,118** about perpendicular to the corner bend lines **210a,b,c,d** and center bend lines **220a,b**. As shown, the bend line **238** can be oriented between the first end **156** of the sidewall enclosure **150** and the second end **158** of the sidewall enclosure **150**. Moreover, each of the left sidewall panel **118** and right sidewall panel **116** can define a pair of opposing angled bend lines **230a,b** and **232a,b**, respectively. For example, referring to the left sidewall panel **118**, a first one of the angled bend lines **230a** can extend at about a 45° angle between the corresponding center bend line **220a** the intersection of the left sidewall panel **118** with the bottom panel **130** and the first rear sidewall subpanel **120**. A second one of the angled bend lines **230b** can extend at about a 45° angle between the center bend line **220a** and the intersection of the left sidewall panel **118** with the bottom panel **130** and the front sidewall panel **112**. As such, the pair of angled bend lines **230a,b** can substantially define an inverted V-shape, wherein an apex of the inverted V-shape can intersect the horizontal bend line **238**, as shown. The angled bend lines **232a,b** of the right sidewall panel **116** can be similarly formed. The pairs of angled bend lines **230a,b** and **232a,b** and the bend line **238** can further aid in folding the lawn refuse bag **100**, as described in further detail with reference to FIG. 3B. In the present aspect, the various bend lines of the bag blank **200** can be formed by a crease; however, in other aspects, some or all of the bend lines can be formed by a perforation, a

series of perforations, or any other suitable arrangement configured to weaken the area of the bend line to facilitate bending along the bend line.

(44) As shown, the top flap segments **140** can be formed as a single strip of material extending fully along the length of the sidewall enclosure **150** from the left blank end **202** to the right blank end **204**. The top flap segments **140** can be divided from one another by the corresponding corner bend lines **210a,b,c,d**. Furthermore, the top flap segments **140** can be connected to the first end **156** of the sidewall enclosure **150** by a top flap bend line **234**. The bottom panel **130** can also extend along fully along the length of the sidewall enclosure **150** from the left blank end **202** to the right blank end **204**, and can be connected to the second end **158** of the sidewall enclosure **150** by a bottom panel bend line **236**. A first fastening flap, such as a left fastening flap **240**, relative to the orientation shown, can be formed at the left blank end **202** and can extend along the first rear sidewall subpanel **120**, the corresponding top flap segment **140**, and the bottom panel **130**. A second fastening flap, such as a right fastening flap **242**, relative to the orientation shown, can be formed at the right blank end **204** and can extend along the second rear sidewall subpanel **122**, the corresponding top flap segment **140**, and the bottom panel **130**. A first step in assembling the lawn refuse bag **100** from the blank can comprise overlapping and securing the left fastening flap **240** to the right fastening flap **242**, which can define the joining seam **124** (shown in FIG. 1A) in the assembled orientation.

(45) According to example aspects, a second step in assembling the lawn refuse bag **100** can comprising folding the bottom panel **130** and securing the bottom panel **130** in the folded configuration. As shown, multiple bottom panel bend lines **250** can be provided to facilitate folding the bottom panel **130** into the orientation substantially perpendicular to the sidewall enclosure **150** in the assembled orientation (shown in FIG. 1A). As shown, the bottom panel **130** can also comprise one or more base panel attachment regions, such as bottom panel attachment regions **252**, that can be secured to the lawn refuse bag **100** (e.g., each other and/or other portions of the bottom panel **130**) to retain the bottom panel **130** in the folded configuration of the assembled orientation, and to form the bottom panel seams **126** (shown in FIGS. 1C and 1D). The bottom panel attachment regions **252** can be secured in the folded configuration by a fastener, such as, for example, an adhesive, such as glue or tape. In other aspects, the first and second steps for assembling the lawn refuse bag **100** can be performed in reverse order.

(46) FIG. 3A illustrates the lawn refuse bag **100** in a partially folded orientation. As shown, the lawn refuse bag **100** can be folded along the center bend lines **220a,b** of the left sidewall panel **118** and right sidewall panel **116**, respectively. In folding the lawn refuse bag **100** along the center bend lines **220a,b**, the front sidewall panel **112** and rear sidewall panel **114** can be drawn towards one another, closing or partially closing the top opening **106** at the top end **102** of the bag body **110**. FIG. 3B illustrates the lawn refuse bag **100** in a fully folded orientation. The lawn refuse bag **100** can be folded along the angled bend lines **230a,b** of the left sidewall panel **118** and the angled bend lines **232a,b** of the right sidewall panel **116**. The lawn refuse bag **100** can then be further folded along the bend line **238**, such that at least a portion of the bottom panel **130** of the lawn refuse bag **100** can be folded to lie substantially flat against the rear sidewall panel **114**, as shown. In other aspects, the at least a portion of the bottom panel **130** can be folded to lie substantially flat against the front sidewall panel **112** (shown in FIG. 1).

(47) FIGS. 4A and 4B illustrate another example method of folding another aspect of the lawn refuse bag **100**. As shown in FIG. 4A, the lawn refuse bag **100** can be folded in a similar manner to the folded lawn refuse bag **100** shown in FIGS. 3A and 3B. Example aspects of the current lawn refuse bag **100** can also comprise an additional bend line **410** extending horizontally, relative to the orientation shown, across the sidewall panels **112,114,116,118** (rear sidewall panel **114** shown in FIG. 1). The bend line **410** can be oriented between the bend line **238** and the first end **156** of the sidewall enclosure **150**, and can be substantially perpendicular to the same. The bend line **410** can also generally define an upper region **420** and an opposite lower region **430** of the lawn refuse bag

100. As shown in FIG. 4B, the lawn refuse bag **100** can further be folded at the bend line **410**, such that the lower region **430** of the lawn refuse bag **100** can lie substantially flat against the upper region **420** of the lawn refuse bag **100** to further reduce the footprint of the folded lawn refuse bag **100**.

(48) FIG. 5 illustrates the top end **102** of the bag body **110** in a closed orientation. In the closed orientation, the top end **102** of the bag body **110** can be fully closed or can be partially closed, as shown. As shown, in the closed orientation, the handle portion **172** of the first handle assembly **170a** can be tied together with the handle portion **172** of the second handle assembly **170b**. For example, in the present aspect, the handle portions **172** can be tied together in the fashion of a double knot, such that the handle portions **172** can be retained in a tied configuration. However, in other aspects, the handle portions **172** can be tied together in a single knot or in any other suitable fashion that can retain the handle portions **172** in the tied configuration. When the handle portions **172** are tied together, the front sidewall panel **112** and rear sidewall panel **114** can be drawn together at the top end **102** of the bag body **110**, and the top opening **106** of the bag body **110** can be closed or partially closed, as shown. As such, in the closed orientation, the lawn refuse received within the interior cavity **160** can be restricted from escaping the interior cavity **160** and additional lawn refuse can be prevented from insertion into the interior cavity **160**. FIG. 6 is a detail view of the handle assemblies **170a, 170b** in the tied configuration.

(49) As such, an example method for using the lawn refuse bag **100** can comprising providing the lawn refuse bag **100** comprising the bag body **110**, the first handle assembly **170a**, and the second handle assembly **170b**, wherein the bag body **110** defines the interior cavity **160** and the top end **102**, and the top end **102** defines the top opening **106**. The method can further comprise inserting lawn refuse into the interior cavity **160** through the top opening **106** and then tying the handle portion **172** of the first handle assembly **170a** with the handle portion **172** of the second handle assembly **170b** to orient the top end **102** of the lawn refuse bag **100** in the closed orientation. To insert the lawn refuse into the lawn refuse bag **100**, a cluster of the lawn refuse can be shifted (e.g., scooped, shoveled, etc.) from the lawn or yard into the interior cavity **160** manually or using a tool, such as, for example a rake **750** (shown in FIG. 7). In some aspects, the method can further comprise unfolding the lawn refuse bag **100** from a folded orientation to an unfolded orientation prior to inserting the lawn refuse therein. The method may also comprise opening the top end **102** of the lawn refuse bag to orient the top end **102** in an open orientation prior to inserting the lawn refuse therein. Additional aspects can further comprise assembling the bag blank **200** to form the lawn refuse bag **100**. In one aspect, the lawn refuse bag **100** can be oriented in the upright orientation, as shown in FIG. 1A, wherein the bottom panel **130** of the bag body **110** is configured to lie on a ground surface (e.g., the yard, lawn, etc.). The lawn refuse can be scooped up off of the ground surface and dumped into the interior cavity **160**. In another aspect, the lawn refuse bag can be oriented in a sideways orientation (shown in FIG. 11), wherein the rear sidewall panel **114** of the bag body **110** can be configured to lie on the ground surface. In other aspects, any of the front sidewall panel **112**, right sidewall panel **116**, and left sidewall panel **118** can be configured to lie on the ground surface in the sideways orientation. In the sideways orientation, the lawn refuse can be shoveled directly from the ground surface into the interior cavity **160** through the top opening **106**, which can be oriented adjacent to the ground surface.

(50) FIG. 7 illustrates a first aspect of a refuse bag insert **700** according to the present disclosure. According to example aspects, the refuse bag insert **700** can be formed as a single, continuous insert blank. In other aspects, the refuse bag insert **700** can be formed from multiple insert blanks. As shown, the refuse bag insert **700** can comprise a bag stand **710** and at least one rake **750**. In the present aspect, the refuse bag insert **700** can comprise first and second matching rakes **750**. Example aspects of bag stand **710** can comprise a first side wall, for example a right wall **716**, a second side wall, for example a left wall **718**, and an end wall, for example, a rear wall **714**, extending between the left wall **718** and the right wall **716**. Other example aspects of the bag stand

710 can comprise more or fewer walls. For example, the bag stand **710** may further comprise a front wall (not shown). Alternatively, the bag stand **710** may comprise the rear wall **714** and only one of the side walls; for example, the rear wall **714** and the left wall **718** only, or the rear wall **714** and the right wall **716** only. According to example aspects, each of the left wall **718** and right wall **716** can be hingedly connected to the rear wall **714** by a stand bend line **712**. The stand bend lines **712** can be formed by, for example, a crease, a perforation, a series of perforations, or the like. In the present aspect, the stand bend lines **712** can be formed by a series of perforations **850** (shown in FIG. **8B**).

(51) Example aspects of the bag stand **710** can generally define a top stand end **720** and a bottom stand end **722** opposite the top stand end **720**. In the present aspect, each of the left wall **718** and right wall **716** can extend from the top stand end **720** to the bottom stand end **722**, while the rear wall **714** can extend from the top stand end **720** to an intermediate point **724** between the top stand end **720** and bottom stand end **722**. In the present aspect, the intermediate point **724** can be closer to the top stand end **720** than the bottom stand end **722**. However, in other aspects, the intermediate point **724** can be about equidistant between the top and bottom stand ends **720,722** or can be closer to the bottom stand end **722**. According to example aspects, the pair of rakes **750** can extend between the left wall **718** and right wall **716** from the intermediate point **724** to the bottom stand end **722**. In other aspects, the pair of rakes **750** may extend beyond the bottom stand end **722** (as shown in FIG. **12**) or may not extend as far as the bottom stand end **722**.

(52) According to example aspects, bag stand tear lines **756** formed by creasing, perforating, or other weakening means can be formed between the bag stand **710** and the rakes **750**, such that the rakes **750** can be detached from the bag stand **710** for use separately from the bag stand **710**. A rake tear line **758** can also be formed between the pair of rakes **750**, such that the rakes **750** can be separated from one another for independent use. Furthermore, as shown, a plurality of teeth cut-outs **754** can be formed between the rakes **750** at the rake tear line **758**. In the present aspect, the teeth cut-outs **754** can be formed as punch-out regions supplied with a weakened periphery (such as by perforations) to allow a user to punch through and remove each of the teeth cut-outs **754** to form corresponding teeth openings **910** (shown in FIG. **9**). In another aspect, the teeth cut-outs **754** can be removed during the manufacturing process or by a worker in a factory. Additionally, one or more rake cut-outs **752** can be defined in the refuse bag insert **700** between the rear wall **714** and an adjacent one of the rakes **750**, which can wholly or partially define an outer edge of the rake **750**. In the present aspect, each of the rake cut-outs **752** can be formed as an opening, as shown. In other aspects, each of the rake cut-outs **752** may be formed as a punch-out region, similar to the teeth cut-outs **754**, such that the rake cut-outs **752** can be punched through and removed by a user to form the illustrated opening. The rakes **750** are shown and described in further detail with respect to FIG. **9**.

(53) According to example aspects, as shown, each of the left wall **718** and right wall **716** can define a slot, for example, a substantially U-shaped slot **730**, formed therein proximate to the top stand end **720** of the bag stand **710**. Each of the U-shaped slots **730** can define a retainer tab **732** extending substantially downward, relative to the orientation shown. According to example aspects, the retainer tabs **732** can facilitate retaining the bag stand **710** on the lawn refuse bag **100** (shown in FIG. **1A**), as is shown and described in further detail with respect to FIG. **10**. Each of the left wall **718** and right wall **716** can also define a finger opening **734** formed between the corresponding retainer tab **732** and the top stand end **720** of the bag stand **710**. According to example aspects, the finger openings **734** can be configured to receive a finger, or fingers, of a user to facilitate inserting and removing the bag stand **710** from the lawn refuse bag **100**, as is described in further detail below.

(54) Example aspects of the refuse bag insert **700** can be formed from a rigid or semi-rigid material, such as, for example, a corrugated plastic sheet. An example corrugated plastic sheet material **860** of the refuse bag insert **700** is illustrated in detail in FIG. **8C**. In other aspects, the

refuse bag insert **700** can be formed from any other suitable rigid or semi-rigid material, including, but not limited to, paperboard such as linerboard, corrugated paperboard, a polymer, plastic, metal, alloy, wood, composite, or any suitable material or combination thereof.

(55) FIG. **8A** illustrates the bag stand **710** with the rakes **750** (shown in FIG. **7**) removed. As shown, with the rakes **750** removed, a gap **840** can be formed between the rear wall **714** and the bottom stand end **722** of the bag stand **710**. As such, the rear wall **714** can be suspended between the left wall **718** and the right wall **716**. In the present aspect, the rear wall **714** can define a concave rear top edge **842** at the top stand end **720** of the bag stand **710**, while the right wall **716** and left wall **718** can define substantially flat right and left top edges **844,846**, respectively, at the top stand end **720**. As such, as shown, the right and left top edges **844,846** can be oriented at a greater height than the rear top edge **842**. However, in other aspects, the rear top edge **842** may not be concave and may be oriented at any suitable height.

(56) Moreover, according to example aspects, each of the left wall **718** and right wall **716** can define a substantially consistent width $W_{sub.1}$ extending from the top stand end **720** of the bag stand **710** towards the bottom stand end **722** of the bag stand **710**. However, proximate to the bottom stand end **722** of the bag stand **710**, each of the right and left walls **716,718** can define a tapered section **820**, such that a width $W_{sub.2}$ of the right and left walls **716,718** at the bottom stand end **722** can be smaller than the width $W_{sub.1}$ at the top stand end **720**. The tapered sections **820** of the right and left walls **716,718** can facilitate sliding the bag stand **710** into the lawn refuse bag **100** (shown in FIG. **1A**), as described in further detail with respect to FIG. **10**.

(57) FIG. **8B** illustrates a close-up view of the stand bend line **712** formed between the left wall **718** and the rear wall **714** of the bag stand **710**. As shown, the stand bend line **712** can be formed by a series of perforations **850**. The perforations **850** can be spaced apart, as shown, with connecting segments **852** formed therebetween, wherein the connecting segments **852** can connect the left wall **718** to the rear wall **714**. The stand bend line **712** formed between the right wall **716** (shown in FIG. **7**) and the rear wall **714** can be similarly formed. FIG. **8C** illustrates a close-up view of the corrugated plastic sheet material **860** of the refuse bag insert **700**. As shown, the corrugated plastic sheet material **860** can comprise a substantially planar first layer **862**, a substantially planar second layer **864** extending about parallel to the first layer **862**, and a corrugated layer **866** between the first and second layers **862,864**.

(58) FIG. **9** illustrates the rakes **750** removed from the bag stand **710** (shown in FIG. **7**). For example, the rakes **750** can be detached from the bag stand **710** by tearing along the bag stand tear lines **756** (shown in FIG. **7**). The rakes **750** can further be detached from one another by tearing along the rake tear line **758** (shown in FIG. **7**) such that each of the rakes **750** can be independently used. Additionally, the teeth cut-outs **754** (shown in FIG. **7**) formed between the rakes **750** can be punched out to define the teeth openings **910**. According to example aspects, each of the rakes **750** can define a first rake end **920**, a second rake end **922** opposite the first rake end **920**, a teeth side **926**, and a grip side **928** opposite the teeth side **926**. As shown, the teeth openings **910** can define a plurality of teeth **912** extending from the teeth side **926** of each rake **750**. In some aspects, as shown, the teeth **912** can taper away from the teeth side **926**, while in other aspects, the teeth **912** may not taper.

(59) According to example aspects, the rakes **750** can be used to shift (e.g., scoop, shovel, etc.) a cluster of lawn refuse from the lawn or yard into the lawn refuse bag **100** (shown in FIG. **1A**). The rakes **750** can further be used to shift additional clusters of lawn refuse into the lawn refuse bag **100** until the lawn refuse bag **100** is full or until all of the lawn refuse is received within the lawn refuse bag **100**, whichever comes first. According to example aspects, the teeth **912** of the rakes **750** can facilitate grabbing lawn refuse from the lawn or yard. In some aspects, the teeth openings **910** can allow small debris, such as pebbles, to pass therethrough, but can be narrow enough to prohibit larger debris, such as leaves **1310** (shown in FIG. **13A**), from passing therethrough. Example aspects of the rakes **750** can further define hand indentation **930** formed at the grip side **928**, as

shown. A user can grip the rakes **750** at the hand indentations **930** when using the rakes **750** to gather lawn refuse. In some aspects, the hand indentations **930** can indicate a preferred gripping location to facilitate the best and easiest use of the rakes **750**. Furthermore, as shown, in some aspects, each of the first rake ends **920** and second rake ends **922** can define an angled portion **932** tapering towards the corresponding grip side **928**. In other aspects, the lawn refuse can also, or alternatively, be shifted into the lawn refuse bag **100** manually or using another tool.

(60) FIG. **10** illustrates the bag stand **710** assembled with the lawn refuse bag **100**, which together can define a lawn refuse disposal assembly **1010**. According to example aspects, the tapered sections **820** (shown in FIG. **8A**) of the right and left wall **716,718** of the bag stand **710** can allow the bottom stand end **722** (shown in FIG. **7**) to be easily inserted and slid down into the interior cavity **160** of the bag body **110**. As shown, the bag stand **710** can be substantially received within the interior cavity **160** of the lawn refuse bag **100**. The left wall **718** of the bag stand **710** can extend along the left sidewall panel **118** (shown in FIG. **1A**) of the lawn refuse bag **100**, the right wall **716** of the bag stand **710** can extend along the right sidewall panel **116** of the lawn refuse bag **100**, and the rear wall **714** can extend partially along the rear sidewall panel **114** of the lawn refuse bag **100**. According to example aspects, the bottom stand end **722** of the bag stand **710** can abut the bottom panel **130** (shown in FIG. **1A**) of the lawn refuse bag **100**. The rigid material of the bag stand **710** can provide added structure to the lawn refuse bag **100** at the rear, right, and left sidewall panels **114,116,118** to aid in preventing collapsing and/or tipping of the lawn refuse bag **100** during use.

(61) Furthermore, as shown, a portion of the top end **102** of the bag body **110** at the left sidewall panel **118** (such as the corresponding top flap segment **140**) can be inserted into the U-shaped slot **730** of the left wall **718**, such that the corresponding retainer tab **732** can be oriented external to the lawn refuse bag **100**. As such, a portion of the left sidewall panel **118** and the corresponding top flap segment **140** can be gripped between the left wall **718** of the bag stand **710** and the corresponding retainer tab **732** to retain the left wall **718** against the left sidewall panel **118**. Similarly, a portion of the top end **102** of the bag body **110** at the right sidewall panel **116** can be inserted into the corresponding U-shaped slot **730** of the right wall **716** to be retained between the right wall **716** and the corresponding retainer tab **732**. Thus, the bag stand **710** can support and engage the lawn refuse bag **100** to retain the lawn refuse bag **100** in the desired upright and open orientation, as shown.

(62) Once the bag stand **710** and lawn refuse bag **100** are assembled together, a user can fill the lawn refuse bag **100** with lawn refuse, such as grass clippings, dirt, sticks, and leaves **1310**, as shown and described in further detail with respect to FIG. **13A**. In some aspects, the lawn refuse bag **100** can also or alternatively be filled with other types of refuse, including, trash, biodegradable waste, and the like. When the lawn refuse bag **100** is appropriately filled with lawn refuse, the user can remove the bag stand **710** from the lawn refuse bag **100** and save the bag stand **710** for later use. For example, as shown, each of the finger openings **734** of the bag stand **710** can be oriented above the top end **102** of the lawn refuse bag **100**, relative to the orientation shown, when the bag stand **710** is assembled with the lawn refuse bag **100**, such that the lawn refuse bag **100** does not interfere with the finger openings **734**. To remove the bag stand **710** from the lawn refuse bag **100**, a user can engage each of the opposing finger openings **734** with a different hand and lift the bag stand **710** out of the lawn refuse bag **100**.

(63) The user can then tie the handle portions **172** of the handle assemblies **170a,170b** together such that the lawn refuse bag **100** can be retained in the closed orientation, as shown in FIGS. **5** and **6**. The user can then discard the lawn refuse bag **100** and the lawn refuse together. In other aspects, the user can empty the lawn refuse out of the lawn refuse bag **100** and into another receptacle (e.g., a trash can), such that the lawn refuse bag **100** can also be saved for later use.

(64) As such, in one aspect, a method for using the lawn refuse disposal assembly **1010** can comprising providing a lawn refuse bag insert **700** comprising a bag stand **710** and at least one rake

750, detaching the rake 750 from the bag stand 710, engaging the bag stand 710 with the lawn refuse bag 100, shifting lawn refuse with the rake 750 into the lawn refuse bag 100; disengaging the bag stand 710 from the lawn refuse bag 100; and tying a first one of the handle assemblies 170a of the lawn refuse bag 100 with a second one of the handle assemblies 170b of the lawn refuse bag 100. According to example aspects, the bag stand 710 can comprise an end wall, such as the rear wall 714, and at least one side wall, such as the right wall 716 and/or left wall 718, and engaging the bag stand 710 with the lawn refuse bag 100 can comprise gripping a portion of the lawn refuse bag 100 between the end wall and the corresponding retainer tab 732.

(65) FIG. 11 illustrates the lawn refuse disposal assembly 1010 comprising the bag stand 710 and the lawn refuse bag 100 in a sideways orientation, as opposed to the upright orientation illustrated in FIG. 10. As shown, according to example aspects, in the sideways orientation, the rear sidewall panel 114 of the bag body 110 can be configured to lie on the ground surface (e.g., the lawn, yard, etc.). In other aspects, any of the front sidewall panel 112, right sidewall panel 116, and left sidewall panel 118 can be configured to lie on the ground surface in the sideways orientation. According to example aspects, with the lawn refuse disposal assembly 1010 in the sideways orientation, the rakes 750 can be used to shovel lawn refuse directly into the lawn refuse bag 100 through the top opening 106, which can be oriented proximate to the ground surface, as shown and described in further detail with respect to FIG. 13B. In the present aspect, the bag stand 710 can provide added structure to the lawn refuse bag 100 to prevent the front sidewall panel 112 from collapsing towards the rear sidewall panel 114 and to maintain the top opening 106 in the open orientation.

(66) As shown in FIG. 12, according to various aspects, the refuse bag insert 700 can comprise indicia 1210 printed thereon. In other aspects, the indicia 1210 can be applied to the refuse bag insert 700 by other means, such as, for example, a sticker. In the present aspect, the indicia 1210 can comprise written directions and graphics indicating how to assemble and use the lawn refuse bag 100 (shown in FIG. 1A) and the refuse bag insert 700 (together, the lawn refuse disposal assembly 1010, shown in FIG. 10), as well as the rakes 750. For example, the indicia 1210 on the bag stand 710 can indicate that the lawn refuse bag 100 can be assembled in the unfolded, open, upright orientation, the rakes 750 can be detached from the bag stand 710, and the bag stand 710 can be inserted into the lawn refuse bag 100. The indicia 1210 on the bag stand 710 can also indicate that the lawn refuse disposal assembly 1010 can be used with the lawn refuse bag 100 in the upright orientation, as shown in FIG. 10, and the rakes 750 can be used to lift lawn refuse off the lawn and to dump the lawn refuse into the lawn refuse bag 100 through the top opening 106 (shown in FIG. 1A), as shown in FIG. 13A. The indicia 1210 on the bag stand 710 can further indicate an alternative method of use, wherein the lawn refuse disposal assembly 1010 can be used in the sideways orientation (shown and described with respect to FIG. 11), wherein the rakes 750 can be used to shovel lawn refuse from the lawn into the lawn refuse bag 100 through the top opening 106, as shown in FIG. 13B. According to example aspects, as shown, the indicia 1210 on the rakes 750 can comprise directions for separating the rakes 750 from one other, along with directions for using the rakes 750 to scoop, shovel, or otherwise shift lawn refuse into the lawn refuse bag 100. Other aspects of the indicia 1210 can comprise writing only or graphics only, or can comprise any other suitable forms of indicia in any combination. FIG. 12 also illustrates how the rakes 750 can extend beyond the bottom stand end 722 of the refuse bag insert 700 in some aspects.

(67) Referring to FIG. 13A, in a first aspect, the lawn refuse disposal assembly 1010 can be used with the lawn refuse bag 100 and the refuse bag insert 700 in the upright orientation, and the rakes 750 can be used to lift lawn refuse, such as leaves 1310, off the lawn and to dump the lawn refuse into the interior cavity 160 of the lawn refuse bag 100 from above the lawn refuse disposal assembly 1010. Referring to FIG. 13B, in another aspect, the lawn refuse disposal assembly 1010 can be used in the sideways orientation, wherein the rakes 750 can be used to shovel lawn refuse,

such as the leaves 1310, from the lawn into the lawn refuse bag 100 through the top opening 106 thereof.

(68) One should note that conditional language, such as, among others, “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more particular embodiments or that one or more particular embodiments necessarily include logic for deciding, with or without user input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment.

(69) It should be emphasized that the above-described embodiments are merely possible examples of implementations, merely set forth for a clear understanding of the principles of the present disclosure. Any process descriptions or blocks in flow diagrams should be understood as representing modules, segments, or portions of code which include one or more executable instructions for implementing specific logical functions or steps in the process, and alternate implementations are included in which functions may not be included or executed at all, may be executed out of order from that shown or discussed, including substantially concurrently or in reverse order, depending on the functionality involved, as would be understood by those reasonably skilled in the art of the present disclosure. Many variations and modifications may be made to the above-described embodiment(s) without departing substantially from the spirit and principles of the present disclosure. Further, the scope of the present disclosure is intended to cover any and all combinations and sub-combinations of all elements, features, and aspects discussed above. All such modifications and variations are intended to be included herein within the scope of the present disclosure, and all possible claims to individual aspects or combinations of elements or steps are intended to be supported by the present disclosure.

Claims

1. A lawn refuse bag insert for use with a lawn refuse bag, comprising: a rear wall disposed at a rear end of the lawn refuse bag insert, the rear wall defining a bottom edge; a first side wall hingedly coupled to the rear wall at a first side of the lawn refuse bag insert, the first side wall defining a bottom edge at a bottom end of the lawn refuse bag insert; and a second side wall hingedly coupled to the rear wall at a second side of the lawn refuse bag insert opposite the first side, the second side wall defining a bottom edge at the bottom end of the lawn refuse bag insert; wherein a top edge of the lawn refuse bag insert is disposed at a top end of each of the rear wall, the first side wall, and the second side wall of the lawn refuse bag insert; and wherein: each of the first side wall and the second side wall defines a U-shaped slot defining a retainer tab that is configured to slidably receive a corresponding top portion of the lawn refuse bag therein; each of the first side wall and the second side wall defines a straight section and a tapered section; each of the tapered sections is defined by a front linear edge and a rear linear edge angled toward one another; and the bottom edge of the rear wall extends between the first side wall and the second side wall at an intermediate point between the top edge of the lawn refuse bag insert and the bottom edges of the first side wall and the second side wall, the intermediate point being closer to the top edge of the lawn refuse bag insert than to the bottom edges of the first side wall and the second side wall.

2. The lawn refuse bag insert of claim 1, wherein the rear wall defines a rear top edge portion of the top edge, and wherein a downward portion of the rear top edge portion extends towards the bottom end of the lawn refuse bag insert.

3. The lawn refuse bag insert of claim 1, wherein: the first side wall defines a first opening; the second side wall defines a second opening; and the first opening and the second opening are configured to be engaged by a user's hands to facilitate lifting the lawn refuse bag insert out of the

lawn refuse bag.

4. The lawn refuse bag insert of claim 3, wherein: each of the first side wall and the second side wall extend from the rear end of the lawn refuse bag insert to a front end of the lawn refuse bag insert opposite the rear end; and the first opening is substantially centered on the first side wall between the front end and the rear end; and the second opening is substantially centered on the second side wall between the front end and the rear end.
 5. The lawn refuse bag insert of claim 1, wherein; the tapered section extends between the straight section and the bottom end of the lawn refuse bag insert; and a width of the tapered section at the bottom end is less than a width of the straight section.
 6. The lawn refuse bag insert of claim 1, wherein the lawn refuse bag insert is folded from a single, planar blank.
 7. The lawn refuse bag insert of claim 6, wherein the lawn refuse bag insert comprises a corrugated material.
 8. The lawn refuse bag insert of claim 7, wherein the corrugated material is a corrugated paperboard material.
 9. The lawn refuse bag insert of claim 1, wherein the lawn refuse bag insert further comprises a bend line formed between the rear wall and the first side wall.
 10. The lawn refuse bag insert of claim 9, wherein the bend line further comprises a series of perforations.
 11. The lawn refuse bag insert of claim 1, wherein the lawn refuse bag insert further comprises a finger opening.
 12. The lawn refuse bag insert of claim 1, wherein the lawn refuse bag insert further comprises indicia printed thereon.
-