

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12416394

Kind Code

B2

Date of Patent

September 16, 2025

Inventor(s)

Wickham; Timothy et al.

Recessed light fixture with housing with internal heat sink and an LED module with conductive base removably mounted therein and coupled to the heat sink

Abstract

A recessed light fixture has a heat sink and a removable light engine assembly. A thermally conductive base of the light engine assembly has an LED and has a thermal interface adapted for thermal coupling to a thermal interface of the heat sink. A mechanical connector in the enclosure can connect the base of the light engine assembly to the heat sink and couple the thermal interfaces of the light engine assembly and heat sink. The base of the light engine assembly is insertable through an opening in the ceiling aligned and can be urged into connected and disconnected states, from within the room, with a minimal clearance between the opening in the ceiling and the base, whereby the light engine assembly can be replaced or serviced from within the room without disturbing the ceiling and without the use of a large diameter trim.

Inventors: Wickham; Timothy (Tappan, NY), Starr; Oriana J. (New Paltz, NY), Cogliano; Frank (Pomona, NY), Delano; Howard D. (Kingston, NY)

Applicant: USAI, LLC (New Windsor, NY)

Family ID: 1000008818710

Assignee: USAI (New Windsor, NY)

Appl. No.: 18/589981

Filed: February 28, 2024

Prior Publication Data

Document Identifier

Publication Date

US 20240230066 A1

Jul. 11, 2024

Related U.S. Application Data

continuation parent-doc US 18313996 20230508 US 12031702 child-doc US 18589981
continuation parent-doc US 17841015 20220615 US 11644184 child-doc US 18313996
continuation parent-doc US 17577839 20220118 ABANDONED child-doc US 17841015
continuation parent-doc US 17201863 20210315 US 11226087 20220118 child-doc US 17577839
us-provisional-application US 63319703 20220314
us-provisional-application US 63210818 20210615
us-provisional-application US 62989148 20200313

Publication Classification

Int. Cl.: **F21S8/02** (20060101); **F21V19/04** (20060101); **F21V29/71** (20150101); F21Y115/10 (20160101)

U.S. Cl.:

CPC **F21V19/04** (20130101); **F21S8/026** (20130101); **F21V29/713** (20150115); F21Y2115/10 (20160801)

Field of Classification Search

CPC: F21S (8/026); F21V (19/04); F21V (29/70); F21V (29/71); F21V (29/713); F21V (29/717); F21V (29/73); F21V (29/74); F21V (29/745); F21V (29/75); F21V (29/76); F21V (29/763); F21V (29/767); F21V (29/77); F21V (29/773); F21V (29/777); F21V (29/78); F21Y (2115/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8092035	12/2011	Mandy	362/147	F21S 8/026
8262255	12/2011	Rashidi	N/A	N/A
8454204	12/2012	Chang et al.	N/A	N/A
9964266	12/2017	Danesh	N/A	N/A
10247390	12/2018	Kopitzke, IV	N/A	N/A
10488000	12/2018	Danesh et al.	N/A	N/A
2008/0165535	12/2007	Mazzochette	N/A	N/A
2012/0162994	12/2011	Wasniewski et al.	N/A	N/A
2016/0084489	12/2015	Yamaguchi et al.	N/A	N/A

Primary Examiner: May; Robert J
Attorney, Agent or Firm: Farber LLC

Background/Summary

FIELD OF THE INVENTION

(1) The invention pertains to the field of recessed lighting, and in particular, to small aperture

format recessed lighting with high light output.

BACKGROUND OF THE INVENTION

(2) For high output light assemblies and luminaries, a way must be provided to dissipate heat generated in creating the light. For small aperture format light fixtures, due to the ultra-small opening through which the light is emitted into the room, the fixture requires that the heat dissipater be much larger than the opening hole in the ceiling.

(3) Prior manufacturers have addressed this problem by creating a one-piece light fixture which must be cut out of the ceiling to repair or replace the fixture.

(4) Therefore, what is desired is a recessed lighting fixture with an extremely small intrusion opening in the ceiling which provides a substantial amount of illumination and which allows for the LED light engine to be replaced and serviced after installation and ceiling finishing, without altering the ceiling and without the use of a large diameter trim.

SUMMARY OF THE INVENTION

(5) In the present design a serviceable light fixture and method are provided to allow for removal and replacement of active components of the light fixture through a small opening in the ceiling having a minimal clearance with such components, without altering or damaging the ceiling and without the use of a large diameter trim.

(6) The recessed light fixture is adapted for illuminating a room through a small opening in a ceiling. The light fixture can have an enclosure with a bottom, and an aperture in the bottom. A heat sink is connected to the enclosure and has a thermal interface, and the heat sink can be non-removable through the aperture. A light engine assembly is insertable and removable through the aperture, along an insertion axis.

(7) The light engine assembly can have a base with a first end with an LED mounted thereto, and the base can have a thermal interface adapted for thermal coupling to the thermal interface of the heat sink. The base is preferably solid or substantially solid and comprises material having high thermal conductivity suitable for effective conduction of heat from the LED to the heat sink.

(8) A mechanical connector which is disposed within the enclosure and is connected to the heat sink, and is adapted to removably connect the base of the light engine assembly to the heat sink. In a connected state, the mechanical connector mechanically connects the base of the light engine assembly to the heat sink, and couples the thermal interface of the light engine assembly with the thermal interface of the heat sink, wherein the thermal interfaces of the base and heat sink are pressed together. The thermal interfaces of the base and the heat sink can be planar and, in the connected state, can be perpendicular to the insertion axis.

(9) In a disconnected state, the base of the light engine assembly is mechanically dis-connected from the heat sink, and the thermal interface of the light engine assembly is de-coupled with the thermal interface of the heat sink.

(10) The base of the light engine assembly is insertable through the opening in the ceiling aligned with the aperture and is operable to be selectively urged into the connected and disconnected states, from within the room, where a maximal clearance between the opening in the ceiling and the base is not substantially greater than required for the base to fit through the opening, for example where such clearance is no more than about 0.05-0.25 inches (e.g., no more than about 0.08 inch) for a 1 inch diameter opening (or 5%-25% of the diameter or corresponding dimension of the opening), and the base of the light engine assembly is removable through the opening in the ceiling, from within the room.

(11) Therefore, the light engine assembly can be replaced or serviced from within the room without disturbing the ceiling, and without the use of large diameter trims.

(12) The base of the light engine assembly can have a second end opposite the first end, and the thermal interface of the base can be disposed on the second end. In the connected state, the insertion axis can pass through the thermal interfaces of the base and heat sink.

(13) The light engine assembly can be operable to be urged from the disconnected state into the

connected state by rotation of the base relative to the heat sink in a first direction about the insertion axis, and from the connected state into the disconnected state by rotation of the base relative to the heat sink in a second direction opposite the first direction about the insertion axis.

(14) The mechanical connector comprises a bayonet connector mounted to the heat sink, and the bayonet can engage the base of the light engine assembly in the connected state.

(15) The recessed light fixture can include a light engine lock within the enclosure which has locked and unlocked states. In the locked state, the light engine lock is operable to prevent rotation of the base of the light engine assembly in the connected state, relative to the heat sink. In the unlock state, the light engine lock being operable to allow rotation of the base of the light engine in the connected state, relative to the heat sink, and the light engine lock is biased in the locked state.

(16) The base of the light engine assembly can have upper and lower portions, with the first end of the base being on the lower portion and the second end of the base being on the upper portion. A plurality of mounting pins can extend radially outwardly from the lower portion of the base.

(17) A service tool is adapted to releasably connect to the base for insertion and removal of the base through the opening in the ceiling. The service tool has a first end with a plurality of slots adapted to engage the mounting pins of the base, and the tool is adapted to rotate the base to urge the base between the connected and disconnected states.

(18) The light engine lock has a cam surface, and during connection and disconnection of the base from the heat sink, the service tool is adapted to engage the cam surface of the light engine lock and to urge the light engine lock into the unlocked state.

(19) The light engine assembly has a reflector module which can be in a mounted state wherein the reflector module is mounted to the lower portion of the base of the light engine assembly, and can be in a dismounted state wherein the reflector module is disconnected from the base. The reflector module is adapted to be urged from the dismounted state to the mounted state and vice versa by rotating the reflector module relative to the base about the insertion axis in a mounting direction and an opposite dismounting direction, respectively. In the mounted state, the reflector module is mounted to the base by the mounting pins of the base.

(20) The reflector module can have a plurality of mounting pins extending radially outwardly, and the service tool can be adapted to releasably connect to the reflector module for insertion and removal of the reflector module through the opening in the ceiling. The first end of the tool can be adapted to engage the mounting pins of the reflector module, and to rotate the reflector module relative to the base, to urge the reflector module between the mounted and dismounted states.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view from above the ceiling of a recessed lighting fixture constructed according to a first preferred embodiment of the inventive light fixture.
- (2) FIG. 2 is a perspective view from below the ceiling of a recessed lighting fixture of FIG. 1.
- (3) FIG. 3 is an exploded view of the light fixture of FIG. 1 showing the trim/diffuser assembly and the light engine assembly removed from the light fixture from below the ceiling.
- (4) FIG. 4 is a perspective view of the light engine assembly.
- (5) FIG. 5 is an exploded view of the light engine assembly.
- (6) FIG. 6 is an exploded view of the mechanical support and thermal components of the light fixture.
- (7) FIG. 7 is a perspective view of the heat dissipation assembly.
- (8) FIG. 8 is an exploded view showing the Ejector assembly.
- (9) FIG. 9 is a partial sectional view showing a version of the Wedge with integral cable.
- (10) FIG. 10 is a partial section view of the light fixture showing an alternate Wedge with integral

cable.

(11) FIG. 11 is a partial sectional view showing the Light Engine Assembly being expelled from the heat dissipation assembly and the keeper leg engaged between the two halves of the finned extrusion.

(12) FIG. 12 is a side elevation view of a light engine assembly according to a second preferred embodiment of the inventive light fixture;

(13) FIG. 13 is a perspective view of the light engine assembly of FIG. 12, from the top.

(14) FIG. 14 is an exploded view of the light engine assembly of FIG. 12.

(15) FIG. 15 is a perspective view of the second embodiment of the light fixture, from the top.

(16) FIG. 16 is a side elevation view of the light fixture of FIG. 15.

(17) FIG. 17 is a side elevation view of the light fixture of FIG. 15, showing the heat dissipation assembly in a lower limit position and the light engine assembly inserted.

(18) FIG. 18 is a side elevation view of the light fixture of FIG. 15, showing the heat dissipation assembly in an elevated position.

(19) FIG. 19 is a front elevation view of the light fixture of FIG. 15, showing the heat dissipation assembly in an elevated position.

(20) FIG. 20 is a perspective view of the light fixture of FIG. 15, from the top, showing the heat dissipation assembly in a lower limit position.

(21) FIG. 21 is a perspective view of the light fixture of FIG. 15, from the top, showing one half of the heat dissipation assembly in a lower limit position, with the other half removed.

(22) FIG. 22 is a side elevation view of the light fixture of FIG. 15, showing the slide lock.

(23) FIG. 23 is a perspective view of the light fixture, from the top.

(24) FIG. 24 is a top view of a third preferred embodiment of the inventive light fixture with the top cover removed, and showing the heat sink assembly in the light engine access position.

(25) FIG. 25A is a side elevation view of the heat sink assembly, of the light fixture of FIG. 24, with the heat sink shown in the elevated position.

(26) FIG. 25B is a side elevation view of the heat sink assembly of the light fixture of FIG. 24, with the heat sink shown in the lowered, unlocked position.

(27) FIG. 25C is a side elevation view of the heat sink assembly of the light fixture of FIG. 24, with the heat sink shown in the lowered, locked position.

(28) FIG. 26 is a bottom view of the heat sink assembly.

(29) FIG. 27 is a bottom view of the heat sink assembly, showing a light engine assembly attached to the heat sink.

(30) FIG. 28 is a side view of the light engine assembly.

(31) FIG. 29 is a side view of the light engine assembly in the disconnected state, and ready to be connected to or removed from the heat sink.

(32) FIG. 30 is a close up view of the disconnected state of FIG. 29, showing the locking ring shown as translucent.

(33) FIG. 31 is a side view of the light engine assembly in the connected state with the heat sink.

(34) FIG. 32 is a close up view of the connected state of FIG. 31, showing the locking ring shown as translucent.

(35) FIG. 33 is a side elevation view of light fixture, showing the heat sink in the lower position and the light engine assembly connected thereto.

(36) FIG. 34 is a side cross section view of light fixture, showing the heat sink in the elevated position and the light engine assembly connected thereto.

(37) FIG. 35 is a bottom view of the light fixture, showing the light engine assembly being removed through the aperture.

(38) FIG. 36 is a top view of the light fixture, with the top cover removed, and showing the heat sink assembly in the wire access position.

(39) FIG. 37 is a bottom view of the light fixture, showing the lighting driver being removed

through the aperture.

(40) FIG. 38 is a perspective view, from the top, of an embodiment of the light engine.

(41) FIGS. 39, 40A and 40B are bottom views of an embodiment of the heat sink adapted for the light engine assembly of FIG. 38.

(42) FIG. 41 is a side view of the light engine of FIG. 38 connected to the heat sink.

(43) FIG. 42 is a side view of a modular light engine assembly embodiment of the light fixture.

(44) FIG. 43 is a side view of LED module of the light engine assembly of FIG. 42.

(45) FIG. 44 is a side view of a reflector module of the light engine assembly.

(46) FIG. 45 is side view of a down-light trim module of the light fixture.

(47) FIG. 46 is a side view of a service tool for connecting the modules of the light engine assembly.

(48) FIG. 47 is side view of the service tool connected to the LED module.

(49) FIG. 48 is a side, cross-section view of the service tool connecting the LED module to the heat sink.

(50) FIG. 49 is a side view of the service tool connected to the reflector module.

(51) FIG. 50 is a side view of the service tool connecting the reflector module to the LED module.

(52) FIG. 51 is a side view of the downlight trim module positioned for connection to the light fixture.

(53) FIG. 52 is a side cross-section view of the modular light engine assembly installed in the light fixture.

(54) FIG. 53 is a side view of the connection tool removing the trim module.

(55) FIG. 54 is side view of an embodiment of the heat sink.

(56) FIG. 55 is a side view of the heat sink of FIG. 54, in the lowered position, and with a light engine assembly connected thereto.

(57) FIG. 56 is side view of the assembly of FIG. 55 in the lowered position, with the light engine assembly disposed below the ceiling.

(58) FIG. 57 is a side view as in FIG. 56, with the LED accessible for servicing.

(59) FIG. 58 is top view of a fourth preferred embodiment of the inventive light fixture.

(60) FIGS. 59 and 60 are each a side cross section view of the light fixture of FIG. 58.

(61) FIG. 61-64 are bottom images (inverted) of the light fixture of FIG. 58, showing an embodiment of the locking mechanism.

(62) FIG. 65 is an exploded view of a fifth preferred embodiment of the inventive light fixture.

(63) FIG. 66A is a front elevation view of the light fixture of FIG. 65.

(64) FIG. 66B is a side elevation view of the light fixture of FIG. 65.

(65) FIG. 66C is a bottom view of the light fixture of FIG. 65.

(66) FIG. 67 is a perspective view of a sixth preferred embodiment of the inventive light fixture.

(67) FIG. 68 is an exploded view of the light fixture of FIG. 67.

(68) FIG. 69 is a perspective view of a seventh preferred embodiment of the inventive light fixture.

(69) FIG. 70 is an exploded view of the light fixture of FIG. 69.

(70) FIG. 71 is a perspective view of a eighth preferred embodiment of the inventive light fixture.

(71) FIG. 72 is an exploded view of the light fixture of FIG. 71.

(72) FIG. 73 is a perspective view of a ninth preferred embodiment of the inventive light fixture, from the bottom, showing the cable retractor in the retracted position.

(73) FIG. 74 is a perspective view of light fixture of FIG. 73, from the bottom, showing the cable retractor in the extended position.

(74) FIG. 75 is a side cross-sectional view of a tenth preferred embodiment of the inventive light fixture.

(75) FIG. 76 is a side cross-sectional view of an eleventh preferred embodiment of the inventive light fixture.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS OF THE INVENTION

(76) Referring to FIGS. 1-5, the recessed light fixture is adapted to be installed above a ceiling or other surface and to project light into a room below, through an opening in the ceiling, which is typically, but not necessarily, a circular opening.

(77) The light fixture can include a trim/diffuser assembly **1** and a light engine assembly **2**. The light engine assembly **2** can be substantially cylindrical with a generally circular cross section and include a thermal gap filling pad **3**, a light engine power connector **4**, a light engine housing **5**, a reflector **6**, a LED support **7**, a LED module **8**, and an electrical connection **9** to connect the LED module to the light engine power connector **4**.

(78) Referring to FIGS. 6-7, the light fixture can also include a power input module **10**, a heat dissipation assembly **11**, a chassis **12**, a pair of hanger bars **13**, and a docking module and power input **14**.

(79) The heat dissipation assembly **11** can include a finned heat exchanger **15** with an opening in a center sized and shaped to closely receive the light engine assembly **2** therein and the opening can expand to receive the light engine assembly. Preferably, the finned heat exchanger **15** includes a compression spring **16** which biases the opening in a contracted position but which allows the opening to expand to receive the light engine assembly **2** into the opening. The finned heat exchanger **15** can include two halves connected by the compression spring **16** such that the two halves can separate slightly against the bias of the spring to enlarge the opening to receive the light engine assembly **2**. The two halves of finned heat exchanger **15** can separate in a horizontal direction perpendicular to a vertical axis of insertion of the light engine assembly into the opening of the heat dissipation assembly.

(80) A thermal interface area **17** surrounds the opening in the finned heat exchanger **15** and is adapted to thermally couple with the thermal gap filling pad **3** of the light engine assembly **2**.

(81) The bias of the compression spring **16** maintains a thermal couple and mechanical/friction couple between the heat dissipation assembly **11** and the light engine assembly **2** to provide both a thermal connection with and a mechanical support of the light engine assembly **2**.

(82) The heat dissipation assembly **11** can also include a light engine assembly ejector **18** which is operable to eject the light engine assembly **2**. The ejector assembly **18** is spring biased **21** downwardly and, when the light engine assembly **2** is installed, the ejector assembly **18** is urged upwardly by the light engine assembly **2** and exerts a downward force on upwardly extending legs **24** of the Light Engine Assembly **2** to help expel the sub-assembly from the ceiling. Specifically, downwardly extending ejector legs **19** of the ejector assembly **18** contact and exert force on the upwardly extending legs **24** of the light engine assembly **2**.

(83) To remove the light engine assembly **2**, the two halves of the Heat Dissipation Assembly **11**, are separated via a wedge **22** (and/or **23**) that is urged between the two halves of the heat dissipation assembly by pulling down on a cable **22'/23'** connected to the wedge, which cable is accessible from below the ceiling (e.g., from within the room). This causes the wedge to slide between and separate the two finned heat exchanger halves. As the wedge separates the two halves of the finned heat exchanger **15**, the light engine assembly **2** is at least partially ejected downwardly from the assembly by the ejector assembly **18** which moves downwardly, and a keeper leg **20** of the light engine ejector assembly **18** is thereby positioned between the two halves of the finned heat exchanger **18**. The keeper leg **20** is operable to hold the heat dissipation assembly open until the light engine assembly is fully re-inserted into the heat dissipation assembly. When the light engine assembly **2** is inserted back into the heat dissipation assembly, the light engine assembly **2** pushes the wedge back into a relaxed position wherein it is not separating the halves of the heat dissipation assembly. The light engine assembly also urges the ejector assembly **18** upwardly which displaces the keeper leg **20** from between the halves of the heat dissipation assembly, which allows the compression spring **16** to close the heat dissipation assembly onto the light engine assembly **2** as discussed above.

(84) The light engine assembly **2** can include one or more fins **25** extending upwardly from a top

portion. The fin(s) **25** are operable to dissipate heat and are also operable to properly align the power input module **10** so that the light engine power connector **4** makes a proper connection to a complementary socket on the bottom of the power input module **10**. As shown, the fins **25** can be angled generally upwardly and radially outward away from the docking module **14** so that they are operable to urge the power input module **10** toward the docking module **14** if required.

(85) Referring to FIG. **3**, the trim/diffuser assembly **1** and the light engine assembly **2** are removed through the opening in the ceiling material. The light engine assembly **2** provides the electrical connection to power the LED's, the thermal gap filling pad **3** to provide an interface to the heat dissipation assembly **11** and a thermally conductive (e.g. aluminum) light engine housing **5** that conducts the heat from the LED's and transfers it to the heat dissipation assembly **11** through the thermal pad **3**.

(86) The light engine assembly **2** also includes the high-performance reflector **6**, the LED light engine module **8**, the light engine support/holder **7** and the electrical interconnect **9**. The light engine assembly **2** is responsible for providing the highest output light level and light quality based on the input power being supplied to the assembly. Therefore, the reflector, diffuser and trim are specifically designed to provide the optimum light for each LED Light Engine.

(87) The heat dissipation assembly **11** and chassis **12** are installed prior to ceiling installation and remain above the ceiling, fastened to the joists that support the ceiling. The light engine assembly **2** is captured by the two halves of the finned heat exchanger **15** which are spring loaded to close around the outer diameter of the light engine assembly **2**, when the light engine assembly **2** is fully inserted into the finned heat exchanger **15**. This spring-loaded assembly provides pressure on the thermal pad **3** to insure optimal heat transfer. The electrical connection for the light engine assembly **2** is completed during the insertion process of the light engine assembly **2** insuring a proper electrical connection after assembly.

(88) The power input module **10** can also be removed through the same hole in the ceiling by rotating the pivoting power module dock **14** 90 degrees vertically so that the power input module **10** can be removed vertically downwardly out of the hole in the ceiling.

(89) The light engine assembly **2** is insertable through the opening in the ceiling aligned with the aperture and is operable to be selectively urged into connected and disconnected states, from within the room, where a maximal clearance between the opening in the ceiling and the light engine assembly is not substantially greater than required for the light engine assembly to fit through the opening, for example where such clearance is no more than about 0.05-0.25 inches (e.g., no more than about 0.08 inch) for a 1 inch diameter opening (or 5%-25% of the diameter or corresponding dimension of the opening), and the light engine assembly **2** is removable through the opening in the ceiling, from within the room. In this manner, the light engine assembly can be replaced or serviced from within the room without disturbing the ceiling.

(90) Referring to FIGS. **12-23**, in second preferred embodiment of the recessed light fixture, the light fixture can include a light engine assembly **102** with a trim/diffuser assembly **101**, a light engine lower housing **105**, a light engine upper housing **107**, a thermal gap filling pad **103**, a light engine power connector **104**, an LED module **108**, an electrical connection **109** to connect the LED module to the light engine power connector **104**, a reflector **106**, and a diffuser **106'**.

(91) The light fixture can also include a power input module **110**, a heat dissipation assembly **111**, a chassis **112**, a pair of hanger bars (not shown).

(92) The heat dissipation assembly **111** can include a finned heat exchanger **115** with a preferably circular opening in a center, which is sized and shaped to closely receive the (e.g., tubular) light engine assembly **102** therein and which can expand to receive the light engine assembly. Preferably, the finned heat exchanger **115** includes a spring **116** which biases the opening in a contracted state but which allows the opening to expand to selectively receive the light engine assembly **102** into the opening. The finned heat exchanger **115** can include two halves connected by the spring **116** such that the two halves can separate slightly against the bias of the spring to

enlarge the opening to receive the light engine assembly **102**. The two halves of finned heat exchanger **115** can separate in a horizontal direction perpendicular to a vertical axis of insertion of the light engine assembly into the opening of the heat dissipation assembly. For example, one half of the finned heat exchanger **115** can pivot in a horizontal plane relative to the other half to allow expansion and contraction of the opening.

(93) The heat dissipation assembly **111** includes a thermal interface area **117** that surrounds the opening in the finned heat exchanger **115** and is adapted to thermally couple with the thermal gap filling pad **103** of the light engine assembly **102**.

(94) The bias of the spring **116** maintains a thermal couple and mechanical/friction couple between the heat dissipation assembly **111** and the light engine assembly **102** to provide both a thermal connection and a mechanical support of the light engine assembly **102**.

(95) The light engine assembly **102** is inserted into and removed from the light fixture from within the room, through the opening in the ceiling material. The light engine assembly **102** provides the electrical connection to power the LED's, the thermal gap filling pad **103** provides an interface to the heat dissipation assembly **111** and a thermally conductive (e.g. aluminum) upper light engine housing **107** conducts the heat from the LED's and transfers it to the heat dissipation assembly **111** through the thermal pad **103**.

(96) The heat dissipation assembly **111** and chassis **112** are installed prior to ceiling installation and remain above the ceiling, fastened to the joists that support the ceiling, or other support structure. The light engine assembly **102** is captured by the two halves of the finned heat exchanger **115** which are spring loaded to close around the outer diameter of the light engine assembly **102**, when the light engine assembly **102** is inserted into the finned heat exchanger **115**. This spring-loaded assembly provides pressure on the thermal pad **103** to insure optimal heat transfer. The electrical connection for the light engine assembly **102** is completed during the insertion process of the light engine assembly **102** insuring a proper electrical connection after assembly.

(97) The heat dissipation assembly **111** is slidably mounted to a pair of guide post **130**, **132** connected to and projecting vertically upwardly from the chassis **112** such that the heat dissipation assembly **111** can move vertically relative to the chassis (and ceiling)—guided by the guide posts—from a lower limit position (See FIG. **17**) to a number of elevated positions (See FIGS. **18-19**). A first half of the heat dissipation assembly **111** has a pair of holes **134**, **136** and each one of the guide posts **130**, **132** extends through an associated one of the holes. Thus, the heat dissipation assembly **111** is confined to move only vertically relative to the chassis **112**, except that the second half can also move laterally (e.g., horizontally pivoting) away from the first half to allow insertion and removal of the light engine assembly.

(98) The light engine assembly **102** is insertable into the heat dissipation assembly **111** when the heat dissipation assembly **111** is in the lower limit position. In this position, the opening in the heat dissipation assembly **111** is in the expanded state and is operable to receive the light engine assembly **102** therein. When the light engine assembly **102** is fully inserted into heat dissipation assembly **111**, the power connector **104** makes electrical connection to the power input module **110** to provide a power path to the light engine assembly **102**.

(99) Pushing further upwardly on the light engine assembly **102** causes the light engine assembly **102** and heat dissipation assembly **111** to move upwardly from the lower limit position. As the heat dissipation assembly **111** moves upwardly from the lower limit position, the opening contracts around the light engine assembly **102** to make a thermal and mechanical coupling with the engine assembly **102**. The light engine assembly **102** can be pushed further upward until the trim element **101** (or a lower flange thereof) is flush with the ceiling lower surface. Preferably, the range of movement of the light engine assembly **102** and heat dissipation assembly **111** relative to the chassis **112** from the lower limit position to a maximal elevated position is preferably at least about 1 inch, and is preferably at least sufficient to accommodate a range of ceiling thicknesses, for example $\frac{3}{8}$ inch to 1 inch thick.

(100) To remove or replace the light engine assembly **102** from the light fixture, a downward pulling force is applied to the light engine assembly **102** from within the room, to pull the light engine assembly **102** and heat dissipation assembly **111** downward from the elevated position to the lower limit position. Downward movement of the heat dissipation assembly **111** into the lower limit position causes the heat dissipation assembly **111** to contact a wedge **140** fixed to the chassis **112** which causes the two halves of the heat dissipation assembly **111** to separate against the bias of the spring **116**, thereby expanding the opening and releasing the light engine assembly **102**.

(101) To assist in the downward movement, the light engine assembly **102** can include a pair of opposed wings **142** which extend laterally (radially) outwardly from the body which abut horizontal surfaces of the opposed halves of the heat dissipation assembly **111** such that a downward force can be exerted on the heat dissipation assembly **111** as the heat dissipation assembly **111** opens up while approaching the lower limit position as described above. The wings **142** can be formed as part of a printed circuit board interconnecting the power connector **104** and electrical connection **109**, or another component of the light engine assembly.

(102) To maintain the light engine assembly **102** in a desired elevated position (i.e., flush with the ceiling), the heat dissipation assembly **111** can include a pair of automatic slide locks **150**, **152** which engage the guide posts **103**, **132** to maintain the heat dissipation assembly **111** in the desired elevated position. Preferably the slide locks allow manual vertical movement of the heat dissipation assembly **111** and light engine assembly **102** but are sufficient to resist the force of gravity such that the heat dissipation assembly **111** and light engine assembly **102** maintain a desired, fixed elevated position when at rest.

(103) Each slide lock can include a base portion **160** which is slidably mounted to one of the guide posts **130**, **132**. The heat dissipation assembly **111** is supported by the base of the slide lock via a coil spring **146** disposed around the associated guide post such that the heat dissipation assembly **111** can move a certain distance downwardly relative to the slide lock. The slide lock can include a lever **144** which is pivotally connected to the base portion and includes an opening through which the associated guide post extends. The lever **144** is adapted to allow upward movement of the heat dissipation assembly **111** relative to the associated guide post and is adapted to prevent downward movement of the heat dissipation assembly **111** when in a locked state, by engaging the guide post. The lever **144** is biased in an upwardly pivoted (locked) state by a lever spring (not shown). The lever **144** includes a release tab **148** extending therefrom which is engaged by the heat dissipation assembly **111** during lowering to disengage the slide lock.

(104) In operation, when the heat dissipation assembly **111** is moved upwardly into an elevated position as described above, the heat dissipation assembly **111** pushes each slide lock upwardly (e.g., via the base) and when a desired position is reached, the biased lever **144** engages the guide post to prevent downward movement of the heat dissipation assembly **111**. To lower the heat dissipation assembly **111**, a downward force is applied to the heat dissipation assembly **111** which moves downward relative to each slide lock by compressing the coil spring **146** until the heat dissipation assembly **111** contacts the release tab **148** which causes the lever **144** to pivot downward against the bias of the lever spring resulting in disengagement (unlocking) of the slide lock to allow the heat dissipation assembly **111** to move further downward to the lower limit position. Preferably, the slide lock, when unlocked, provides little to no resistance to downward movement of the heat dissipation assembly **111**; and provides little to no resistance to upward movement at all times.

(105) As above, the light engine assembly **102** is insertable through the opening in the ceiling aligned with the aperture and is operable to be selectively urged into connected and disconnected states, from within the room, where a maximal clearance between the opening in the ceiling and the light engine assembly **102** is not substantially greater than required for the light engine assembly to fit through the opening, for example where such clearance is no more than about 0.05-0.25 inches (e.g., no more than about 0.08 inch) for a 1 inch diameter opening (or 5%-25% of the diameter or

corresponding dimension of the opening), and the light engine assembly **102** is removable through the opening in the ceiling, from within the room. In this manner, the light engine assembly **201** can be replaced or serviced from within the room without disturbing the ceiling.

(106) Referring to FIGS. **24-37** an embodiment of the light fixture **200** has an enclosure **202** with a top (not shown), side walls **205**, and a bottom wall **204** with an aperture **206** therethrough (FIGS. **35 & 37**), of for example a diameter of about 1 inch or more. The enclosure **202** is adapted to be fastened to support structure above a ceiling structure **272** (for example via hanger bars), and remains above the ceiling.

(107) The light fixture **200** includes a light engine assembly **208** (FIG. **28**), which can include an LED module **210**, a reflector **212** (FIG. **34**) and a trim element **214**. The LED module **210** can have a base **216** with a lower portion **211** having a lower surface **218** (normally downwardly facing), and with an upper portion **217** having an upper surface **220** (normally upwardly facing). An electrical connector **223** can be connected to the LED **222** by wires and is operable to releasably connect to the lighting driver **274** to power the LED. The light engine assembly **208** is adapted to be removed from the enclosure **202** through the aperture **206** of the enclosure **202** and the opening **273** in the ceiling **272**, from within the room, without removing the enclosure **202** and without disturbing the ceiling.

(108) At least one LED **222** (FIG. **27**) (for example a 6 mm chip-on-board (COB) LED) can be mounted to the lower surface **218** of the base **216**, and is operable to emit light through the light engine assembly **208** and into the room. The trim element **214** can be connected to the base **216**, such as by one or more screws **215**, and preferably surrounds the lower portion **211** of the base **216** and LED **222**. The reflector **212** can be disposed within the trim element, around the LED **222**.

(109) Portions of the lower and upper surfaces **218**, **220** of the base **216** form lower and upper thermal interfaces **224**, **226**, which are preferably substantially planar; however, the thermal interfaces can be stepped with several portions which on different planes. The upper portion **217** of the base **216** can be substantially cylindrical in shape, with a substantially circular cross section and with the upper surface **220** (and thermal interface **226** thereof) being substantially circular. For a light fixture configured for about a 1 inch diameter ceiling opening, for example, a maximal outside diameter of the upper portion **217** of the base **216** can be about 0.96 inches and the surface area of the upper thermal interface **226** can be about 0.72 square inches ($\pi \times (\text{diameter squared})/4$). For such an application, the base **216** can have a height of about 0.9 inches between the upper and lower surfaces thereof.

(110) The base **216** of the LED module **210** is preferably adapted and operable to effectively conduct heat generated by the LED **222** from the lower thermal interface **224** to the upper interface **226**. The base **216** can be solid (or at least substantially solid) and can include (or consist or consist essentially of) one or more materials having high thermally conductivity, such aluminum or copper, or another suitable metal or alloy, or non-metallic material.

(111) The light fixture **200** can also include a heat sink **228** which has a preferably planar thermal interface **230** (FIG. **26**) which is configured for thermal connection with the upper thermal interface **226** of the base **216** of the LED module **210**, and which is aligned with and disposed over the aperture **206** of the enclosure **202**. The heat sink **228** has a plurality of fins **231** which are integrally form with and/or thermally connected to the thermal interface **230**, such that the heat sink **228** is adapted and operable to receive heat generated by the LED **222** through the thermal interface **230** and to dissipate such heat to ambient air through the fins **231**. As depicted, the fins **231** can project laterally (horizontally) radially outwardly from a main body of the heat sink. The heat sink **228** is preferably larger than the aperture **206** of the enclosure **202** and is not removable through the aperture **206**. Therefor, the heat sink **228** preferably remains within the enclosure **202** (and above the ceiling **272**) during servicing of the light engine assembly **208** as described herein.

(112) The heat sink **228** is a component of a heat sink assembly **232** which includes a frame **234** having a base **236**, a top **238** and a plurality of legs **240** (for example three legs) interconnecting the

base and top **236**, **238**. The base **236** of the frame **234** includes an aperture **242** through which the light engine assembly **208** is received, as discussed below.

(113) Referring to FIGS. **25A** and **25B**, the heat sink **228** is preferably movably mounted within the frame **234** such that the heat sink **228** can move, for example, vertically (parallel to a Z axis) relative to the frame, between an elevated limit position (FIG. **25A**) and a lowered limit position (FIG. **25B**). The heat sink **228** can be slidably mounted on a plurality of (e.g., three) guide posts **244** disposed within the frame **234** which are vertically oriented and are located around the periphery of the heat sink **228**. The periphery of the heat sink **228** can include a plurality of channels **246**, each vertically oriented and sized and shaped to slidably receive and confine one of the guide posts **244**. As depicted, the guide posts **244** can be cylindrical in shape and the channels **246** can have a complementary tubular (or partially tubular) shape, sized to closely (but slidably) confine the guide posts.

(114) Preferably, the heat sink **228** is biased in the elevated limit position, which can be effected by, for example, compression springs **248**, disposed around the guide posts **244** between the base **236** of the frame **234** and the heat sink **228**, and preferably contacting the associated channel **246** of the heat sink **228**. Preferably, the springs **248** are in compression (or at rest) when the heat sink **228** is in the elevated position (FIG. **25A**) such that the heat sink **228** is biased toward the elevated position.

(115) As described further below, the heat sink **228** can preferably rotate relative to the frame **234** about the vertical axis (Z axis) between a lowered unlocked position (FIG. **25B**) and a lowered locked position (FIG. **25C**). Preferably, the guide posts **244** are confined between, but are not connected to, the base **236** and top **238** of the frame **234**, and the legs **240** thereof, such that the sub-assembly of the heat sink **228** and guide posts **244** can rotate within and relative to the frame **234** about the vertical axis (Z axis) a predetermined amount.

(116) Each leg **240** of the frame **234** preferably includes a guide slot **250** having vertical portion **252** connected, at a bottom thereof, to a horizontal portion **254**. The horizontal portion **254** of at least one guide slot **250** includes a locking projection **256** extending vertically downwardly at or adjacent the junction of the horizontal and vertical portions.

(117) The heat sink assembly **232** can include a plurality of radially outwardly projecting guide tabs **260** each of which extend through an associated one of the guide slots **250** in the legs **240** of the frame **234** to guide the vertical and rotational movement of the heat sink **228** relative to the frame **234**. The projecting guide tabs **260** can be part of a bottom plate **258** which is integral or connected to a bottom of the heat sink **228**. The bottom plate **258** of the heat sink can include an aperture **259** which is aligned with the aperture **242** of the base **236** of the heat sink assembly **232**, and through which the light engine assembly **208** is received.

(118) During vertical movement of the heat sink **228**, between the elevated position and the lowered position, each guide tab **260** moves within and is guided by the vertical portion **252** of the associated guide slot **250** of a guide post **240**. During rotational movement of the heat sink **228** between the lowered unlocked position (FIG. **25B**) the lowered locked position (FIG. **25C**), each guide tab **260** moves within and is guided and limited by the horizontal portion **254** of the associated guide slot **250**. A vertical height of each horizontal portion **254** is less than a corresponding vertical height of the associated guide tab **260** such that, when the guide tab is in the lowered locked position, guide tab **260** is urged upward by the aforementioned upward bias of the heat sink **228** due to compression springs **248**, such that the heat sink **228** is prevented from moving into the lowered unlocked position, by the locking projection **256**. To move the heat sink **228** into the lowered, unlocked position, the heat sink is urged downwardly against the upward bias until the guide tab **260** is below the locking projection **256**, and then the heat sink **228** can be rotated such that the guide tab **260** moves past the locking projection **256** and into the vertical portion **252** of the guide slot **250**. At this point the upward bias will urge the heat sink **228** into the elevated position.

(119) Referring to FIGS. 26-32, the heat sink 228 includes a bayonet connector 262 which is disposed within the enclosure 202 and is operable for releasably mounting the light engine assembly 208 to the heat sink with a twisting motion about an insertion axis A, from within the room. FIG. 26 shows a locking ring 264 of the bayonet connector 262, which is ring-shaped and is disposed around the thermal interface 230 of the heat sink 228. The locking ring 264 can move vertically (Z axis) relative to the main body of the heat sink 228. The vertical movement of the locking ring 264 is guided and limited by guide screws 267 which are directed through the locking ring and into the body of the heat sink 228 and which prevent rotational movement of the locking ring 264 relative to the heat sink 228. The locking ring 264 is biased toward the main body of the heat sink 228, by a plurality of compression springs 266 disposed around the guide screws 267 below the locking ring 264.

(120) The locking ring 264 has a plurality of (for example, three) locking tabs 268 which project horizontally radially inwardly from an inner circumference of the locking ring, and which are configured to engage with an associated one of an equal number of bayonet slots 270 (FIG. 28) in the upper portion 217 of the base 216 of the light engine assembly 208. Each bayonet slot 270 of the base 216 has an opening on the upper surface 220 of the base 216 which is configured to receive an associated locking tab 268 of the locking ring 264 and has a channel which extends partially around a periphery of the upper portion 217 of the base below the upper surface 220 thereof, and which communicates with the opening of the slot.

(121) FIGS. 29 and 30 are side views of the light engine assembly 208 in a disconnected state, ready to be connected to, or removed from, the heat sink 228. FIG. 30 is a close up view of the disconnected state of FIG. 29, showing a locking ring 264 of the bayonet connector 262 as translucent. FIGS. 31 and 32 are side views of the light engine assembly 210 in a connected state with the heat sink 228. FIG. 32 is a close up view of the connected state of FIG. 30, showing a locking ring 264 of the bayonet connector 262 as translucent.

(122) Referring to FIGS. 33, when the heat sink 228 is in the lowered, locked position (FIGS. 33 and 25C), the trim element 214 extends below the ceiling 272 and can be grasped by hand. In this position, the light engine assembly 208 can be connected and disconnected to the heat sink 228. To connect the light engine assembly 208 to the heat sink, the electrical connector 223 of the light engine assembly 208 can be connected to a complementary electrical connector connected to the lighting driver 274 and extending through the opening 273 of the ceiling 272 (e.g., as shown in FIG. 47), then the light engine assembly 208 can be inserted axially vertically upwardly along the insertion axis A through the opening 273 in the ceiling 272 and through the aperture 206 of the enclosure until the upper thermal interface 226 of the base 216 contacts the thermal interface 230 of the heat sink 228. At this point, the light engine assembly 208 is in the disconnected state (FIGS. 29 & 30). Then, the light engine assembly 208 can be urged into the connected state (FIGS. 31 & 32) by manually rotating the light engine assembly 208 by the trim element 214, for example by about 30-40 degrees in a first rotational direction, about the vertical insertion axis A, which is preferably in a clockwise direction as viewed from within the room. The insertion axis A can be an optical axis of the LED 222 and/or of the light engine assembly, which can be parallel to a vertical (Z) axis. When the light engine assembly 208 is in the connected state (and when transitioning between the connected and disconnected states) the insertion axis A preferably passes through centers of, and is perpendicular to, the thermal interfaces 216, 230.

(123) When the light engine assembly 208 is in the connected state (FIGS. 31 & 32), it can be urged into the disconnected state (FIGS. 29 & 30) by rotating the light engine assembly 208 by the same amount, but in an opposite rotational direction about the insertion axis A, for example in a counter-clockwise as viewed from the room. When in the disconnected state, the light engine assembly 208 can be removed axially vertically downwardly along the insertion axis A through the aperture 206 of the enclosure and the opening 237 of the ceiling 272. In this manner, the light engine assembly 208 can be readily serviced from within the room, without disturbing the ceiling

and without the use of large radius trims.

(124) Referring to FIG. 34, when the light engine assembly **208** is in the connected state with the heat sink **228**, the heat sink **228** can be moved into the lowered unlocked position and then into the elevated position. The upward bias urges the light engine assembly **208** upward until a radial flange **217** of the trim **214** contacts the room-side of the ceiling structure **272**, around the opening **273**. As can be appreciated, the variable upward bias of the heat sink **228** allows the light fixture **200** to adapt to ceiling materials of various thickness and various fixture installation heights relative to the ceiling.

(125) When the light engine assembly **208** is in the connected state, the locking ring **264** of the bayonet connector **226** is displaced downwardly (away from the heat sink **228**) against the upward bias which mechanically secures the light engine assembly **208** to the heat sink **228**, and in addition pushes the light engine assembly **208**, and particularly the base **216** thereof, against the heat sink **228** which causes the upper thermal interface **226** of the base **216** to press against the thermal interface **230** of the heat sink **228** which creates an efficient and effective thermal connection between the upper thermal interface **226** of the base **216** of the LED module **210** and the thermal interface **230** of the heat sink **228**. This allows the light fixture to use high-output LEDs, while effectively dissipating the heat generated thereby. For example the light fixture can use LEDs providing about 900-1000 lumens delivered into the room and at, for example about 9-15 watts, all serviceable through a small ceiling opening of, for example, a diameter of 1 inch.

(126) The axial insertion and rotational connection process, from within the room, provided by the configuration and operation of the light engine assembly **208** and bayonet connector **262** allow the light engine **208**, and in particular the LED module **210** and base **216** thereof, to be axially inserted through and removed from an extremely small opening **273** in the ceiling **272**, and particularly where the opening **273** is minimally larger than, and has minimal clearance around, the outer diameter of the light engine assembly **208**. For example, for a light fixture configured for about a 1 inch diameter ceiling opening, a maximal outside diameter of the upper portion **217** of the base **216** can be up to about 0.96 inches, providing a minimal clearance of about 0.04 inches (e.g., no more than about 0.05 or 0.08 inches) between the opening **273** of the ceiling **272** and the base **216** of the light engine assembly **208**. Furthermore, because the opening **273** in the ceiling **272** is only minimally larger than the diameter of the light engine assembly **208**, the radial flange **217** of the trim element **214** can be correspondingly small. It can be appreciated that the dimensions of the light engine assembly **208** can change; however, the minimal clearance provided between the opening **273** in the ceiling **272** and the light engine assembly **208** can remain minimal and substantially constant, while maintaining serviceability of the light fixture from within the room, without disturbing the ceiling.

(127) Referring to FIGS. 26 and 27, the heat sink assembly **232** can include a light engine lock **233** adapted to only allow disconnection of the light engine assembly **208** from the heat sink **228** when the heat sink **228** is in the lowered locked position. The light engine lock **233** can be pivotally connected to the base **236** of the heat sink assembly **232** and can include a free end **235** which is received within and engages a complementary locking recess **237** in the base **216** of the LED module **210** to prevent rotational movement thereof, when the light engine lock is in a locked state. The light engine lock **233** is in a locked state (FIG. 27) when the heat sink **228** is not in the lowered, locked position. The light engine lock **233** is in an unlocked state (FIG. 26) when the heat sink **228** is in the lowered, locked position. In the unlocked state, the free end **235** of the light engine lock **233** is retracted from the locking recess **237** in the base **216** of the LED module **210**, thereby allowing rotation of the LED module. The light engine lock **233** can be spring biased in the locked position and can be urged into the unlocked position by contacting a portion of the base **236** of the frame **234** of the heat sink assembly **232** during rotation of the heat sink **228** into the lowered, locked position.

(128) Referring to FIGS. 24 and 35-37, the heat sink assembly **232** can preferably move along the

bottom **204** of the enclosure **202** to allow selective removal of the light engine assembly **208** and the lighting driver, or the electrical connections for a remote driver **274**. The base **236** of the frame **234** of the heat sink assembly **232** can be pivotally connected to the bottom **204** of the enclosure **202** by, for example a fastener **276**. In a light engine access position (FIGS. **24** and **35**), the thermal interface **230** of the heat sink **228**, the aperture **259** of the bottom plate **258** of the heat sink **228** and the aperture **242** of the base **236** of the frame **234** are aligned with the aperture **206** of the bottom **204** of the enclosure **202** to allow insertion (connection) or removal (disconnection) of the light engine assembly **208** to/from the heat sink **228** through such aperture **206**, from within the room. In a wire access position (FIGS. **36** and **37**), the lighting driver **274** is aligned with the aperture **206** of the bottom **204** of the enclosure **202** to allow insertion or replacement of the lighting driver, or the electrical connections for a remote driver **274** through the aperture **206**, from within the room.

(129) Referring to FIGS. **38-41**, an embodiment of the heat sink **328** can have a rotating electrical connection ring **380** which can be disposed at least partially radially inwardly from the locking ring **264** of the bayonet connector **262** and at least partially around the thermal interface **230** of heat sink **328**. The ring **380** can be formed of, or can include a printed circuit board (PCB). The ring **380** can be configured to rotate relative to the main body of the heat sink **328** about the insertion axis A, during rotational connection and disconnection of the light engine assembly **308**, as described above. The electrical connection ring **380** can be disposed within a ring-shaped channel **231** recessed in the main body of the heat sink **328** and surrounding the thermal interface **230** thereof, and can be substantially confined to limited rotational movement about the insertion axis A.

(130) The light engine assembly **308** can include upwardly extending keying and rotating tabs **382** which are received within and interface with complementary keying features **384** of the ring **380** to cause complimentary rotation of the ring **380** during connection and disconnection of the light engine assembly **308**.

(131) The light engine assembly **308** can also include electrical connections **386** connected to the LED **222** which interface with electrical connections **388**, **390** of the ring **380**. The electrical connections **388**, **390** of the ring **380** can be connected to a power source, such as lighting driver **274**, by wires **392**. The ability of the ring **380** to rotate with the light engine assembly **308** provides for substantially solely normal/perpendicular axial/non-sliding electrical closing and opening operations (as opposed to lateral/sliding movements) which reduces the area required for the electrical connections **388**, **390** and avoids problems associated with sliding electrical connections. In addition, this configuration avoids a separate electrical connection step for the light engine assembly **308**. The act of connecting the light engine assembly **308** to the heat sink **328** with the bayonet connector **262** completes, in one step, the electrical connection, in addition to the mechanical and thermal connections described above.

(132) Referring to FIGS. **42-53**, an embodiment of the light engine assembly **408** can be composed of modular parts which can include an LED module **410**, a reflector module **412**, and a trim module **414**. The LED module **410** can have a base **416** with an upper portion **417** having a configuration and functionality similar to the corresponding structure described above, including that of base **216**. The LED module **410** can have an LED **422** connected thereto, as described above. The LED module **410** can be removably connected to, and removable from, the heat sink **228**, with, for example, the bayonet connector **226**, in the manner described above.

(133) The LED module **410** can include a pair of opposed mounting pins **427** which extend horizontally radially outwardly (perpendicular to the insertion axis A) from the lower portion **411** of the base **416** thereof. The reflector module **412** can be removably connected to the LED module **410** by, for example, a bayonet connection. The reflector module **412** can have a pair of bayonet slots **428** which engage the mounting pins **427** of the LED module **410**. The bayonet slots **428** of the reflector module **412** can have an upwardly-facing vertical opening adapted to receive an associated mounting pin **427** and can have a horizontal channel connected to the opening and adapted to confine the mounting pin. The reflector module **412** is mounted to the LED module by

first moving the reflector module **412** axially vertically, along the insertion axis A, to contact the LED module **410** and receive the mounting pins **427** into the openings of the bayonet slots **428**, and then rotating the reflector module **412** about the insertion axis, for example clockwise as viewed from the room. The reflector module **412** can be detached from the LED module **410** with a reverse process. Each bayonet slot **428** can include a detent **431** between the opening and the horizontal channel thereof and operable to resist passage of the associated mounting pin **427** of the LED module **410**, to temporarily secure the reflector module **412** to the service tool **420** during connection and disconnection of the reflector module **412**. The reflector module **412** can include a pair of opposed mounting pins **429** which extend horizontally radially outwardly therefrom.

(134) The trim module **414** can be removably connected to the enclosure **202**, such as to aperture plate **418** (FIG. 52), depending downwardly from the enclosure **202**. The trim module **414** can have a resilient, snap-fit or friction connector for removable connection.

(135) Referring to FIGS. 46-53, the light fixture **200** having the modular light engine assembly **410** can include a service tool **420** for mounting and removing the modules. The service tool **420** can have a first end **422** adapted to be inserted axially vertically through the opening **273** of the ceiling **272** and into the aperture **206** of the enclosure **202** from within the room, to rotate the modules to connect and disconnect modules to the heat sink, as described above. The first end **422** of the service tool **420** can be substantially tubular and adapted to separately receive at least lower portions of the LED module **410** and reflector module **412** therein. The first end **422** can have a pair of opposed, inverted T-slots **430** having an opening communicating with an edge of first end **422**. The T-slots are adapted to selectively engage the mounting pins **427**, **429** of the LED module **412** and reflector module **414** for mounting and removal of the modules.

(136) FIGS. 47-51 show the sequence of installing the modular light engine assembly **408** using the service tool **420**. First, FIG. 47 shows the LED module **410** connected to the service tool **420** and ready for axial insertion through the opening **273** of the ceiling **272**. FIG. 48 shows the LED module **410** in position to be rotated by the service tool **410** for connection to, or disconnection from, the heat sink **228**. Then, FIG. 49 shows the reflector module **412** connected to the service tool **420** and ready for axially insertion through the opening **273** of the ceiling **272**. FIG. 50 shows the reflector module **412** in position to be rotated by the service tool **410** for connection to, or disconnection from, the (installed) LED module **410**. Then, FIG. 51 shows the trim module **414** ready for manual connection to the light fixture. FIG. 52 shows all modules installed and connected to the light fixture. The sequence for removing the modules is the reverse process.

(137) Referring to FIGS. 46 & 53, the tool **420** can have a second end **424** adapted to engage a radially-outwardly extending flange **426** of the trim module **414** to assist in removal of the trim module **414**.

(138) Referring to FIGS. 54-57, an embodiment of heat sink **528** can include an elongated arm **532**, extending downwardly from, and preferably formed integrally with, the main body of the heat sink **528**. The arm **532** can have a free end **534** having a similar configuration, and performing the same function as, the lower portion **211**, **411** of the base **216**, **416** of the LED module **210**, **410** described above, including having a lower surface **518** supporting an LED **222**, conducting heat from such LED to the body of the heat sink **528**, and supporting the reflector element/module **212**, **412** and trim element/module **214**, **414**.

(139) When the heat sink **528** is in the elevated position for operation, the arm **532** is entirely retracted within the enclosure **202**, preferably wherein the lower surface **518** supporting the LED **222** is in a position corresponding to the position of the lower portion **211**, **411** of LED module **210**, **410**, and lower surface **218**, **418** thereof, when in the elevated position.

(140) When the heat sink **528** is in the lowered position as described above, the arm **532** extends through the various apertures described herein and through the ceiling structure **272** for servicing. A longitudinal axis L (parallel to Z axis) of the arm **532** is aligned with such apertures, and a length of the arm **532** is configured such that the free end **534** extends through the aperture **206** of the

enclosure **202** and through the opening **273** of the ceiling **272**, when the heat sink **528** is in the lowered position (FIGS. **55-57**). Preferably an electrical connector **536** is provided on the free end **534** of the arm **532**, and is accessible from the room, for connecting and disconnecting the LED **222** from the power source. In this position, free end **534** of the arm **532** and the lower surface **518** thereof (and LED **222** attached thereto) are disposed below the ceiling **227**, such that the trim element **214**, **414**, and the LED **222** can be removed and replaced from within the room, for servicing, without disturbing the ceiling structure.

(141) Referring to FIGS. **58-60**, an embodiment of the light fixture **600** can have a heat sink **628** having fins **631** projecting from a top surface and having a relatively low vertical profile (i.e., low height, e.g., 1-2 inches). The heat sink **628** can be fixed relative to the enclosure **602** for example within the enclosure, or above the enclosure **602** and optionally thereby forming a top of the enclosure. A light engine assembly **408**, for example having a structure as described above, can be connected to a bottom of the heat sink **628** in the manner described above, including through the opening **273** in the ceiling structure **272** and the aperture **606** of the enclosure **602**, from within the room, for example by using the service tool **420** to connect the light engine assembly **408** to the bayonet connector **262** mounted to the heat sink **628**, within the enclosure **602**.

(142) The aperture **606** of the enclosure **602** can be located on a bottom wall **604** of the enclosure. As described above, the thermal interface **630** of the heat sink **628** can be aligned with the aperture **606**, and can be recessed upwardly from the bottom of the heat sink **628** to assist in the proper location, and to guide the rotation, of the base **416** of the LED module **410** during mounting and dismounting of the LED module **10**.

(143) Referring to FIGS. **61-64**, an embodiment of the light engine lock **633** is operable to lock the LED module **410** in the bayonet connector **262** when in the LED module **410** is in the connected state, and is adapted to be actuated by the service tool **420**. The light engine lock **633** can be connected to a bottom of the heat sink **628** adjacent and radially outwardly from the bayonet connector **262**. The light engine lock **633** can have a locking projection **634** which extends radially inwardly toward and is received within and engages a locking recess **636** on a periphery of the LED module **410** to prevent rotation thereof, when the LED module **410** is in the connected state and when the lock **633** is in a locked position. The lock **633** can be biased in the locked position (FIGS. **61**, **63**, **64**), for example by a spring **638**. The light engine lock **633** can have an inclined cam surface **640** extending away from the heat sink **628** and radially outwardly from the LED module **410**. As shown in FIG. **62**, when the service tool **420** is connected to the LED module **410** attached to the bayonet connector **262**, the first end **422** of the service tool **420** contacts the cam surface **640** of the lock **633** and urges the lock **633** radially outward against the bias, and into an unlocked position, wherein the locking projection **634** of the lock **633** is displaced from the locking recess **636** of LED module **410** such that the LED module **410** can be rotated and removed from the bayonet connector **262**, using the service tool **420**. Preferably, the light engine lock **633** does not engage or limit rotation of the reflector module **412** relative to the LED module **410**, when the lock **633** is in the locked or unlocked positions. The reflector module **412** can include a recess **642** on a periphery thereof configured to avoid contact with the locking projection **634** and cam surface **640** of the lock such that the reflector module **412** can rotate when the lock **633** is in the locked state, for connection and removal of the reflector module **312** independent of the LED module, including when using the service tool **420**.

(144) Referring to FIGS. **65** and **66A-C**, in another preferred embodiment of the light fixture, the light engine assembly is composed of modular parts including an LED module **710**, a reflector module **712**, and a trim module **714**, as described herein regarding light engine assembly **408**. Heat sink **728** has a plurality of fins **731**. The light fixture has an enclosure **702** (without a top), side walls **705**, and a bottom wall **704** with an aperture **706** therethrough of, for example, a diameter of about 1 inch or more. In accordance with the present invention, the light fixture is serviceable from the room without the need to remove the ceiling material. In addition, LED module **710** includes a

removable heat sink that provides for efficient thermal coupling to permanent heat sink **728** of the fixture. When installed and in operation, the combination of the removable heat sink in LED module **710** coupled with permanent heat sink **728** allows for optimal thermal management, providing high quality light over the lifetime of the fixture. For example, a preferred embodiment of the fixture provides 475-1500 Lumens of delivered light through a 1-inch ceiling aperture (with a $\frac{3}{4}$ inch lens aperture) with only 7-15 watts of power. Reflector module **712** is field-changeable, parabolic and is capable of creating a soft, symmetric beam pattern (with narrow to wide beam spreads by simply swapping out the reflector from the room below). Trim module **714** also provides glare control (e.g., UGR<1, not measurable).

(145) Referring to FIGS. **67-72**, in other preferred embodiments of the light fixture, the light fixture can include a light engine assembly **802** with a trim module **814** (which may have a radially-outwardly extending flange **826**), spring connectors **878** (or spring-tab connectors **879**), a light engine lower housing **805**, a light engine upper housing **807**, and a heat sink **828**. The light fixture can further include an LED module **808**, a reflector **806**, a diffuser **806'** (and may also include a lens **806''**), and a reflector module **812** (which may have a wall wash trim **813**).

(146) Referring to FIGS. **73-74**, in another preferred embodiment, the light fixture **600** can include a cable retractor **902** which is operable to retract a power line **904** for the LED module **410** during installation to prevent the power line **904** from interfering with the installation.

(147) The power line **904** preferably includes a main power line **906** (or wiring harness), which can be connected to a power source or lighting driver. The power line **904** also includes an LED power cable **908** which is connected to the LED. The main power cable **906** and the LED power cable **908** are releasably connectable together such that the LED module **410** can be replaced if required, through the aperture, as described herein. Preferably the main power line **906** and the LED power cable **908** include modular connectors **910**, **912** adapted to releasably electrically and mechanically interconnect.

(148) The main lower line **906** can include a fixed section **932** which is fixed relative to the enclosure for example by one or more clamps **934** or the like, and can include a free section **936** which is connected to the LED power cable **908**.

(149) The cable retractor **902** can include a biasing element **914**, such as a coil spring (not shown), and a retractor cable **916** connected to the biasing element. The biasing element **914** is preferably substantially laterally (e.g., horizontally) offset from the LED module **410** when mounted such that it is operable to bias (pull) the retractor cable **916** into a retracted position laterally offset from the LED module **410** during mounting. The LED Module **410** can include a leash **920** which is preferably fixedly connected to the LED Module and releasably connectable to the retractor cable **916**.

(150) The light fixture **600** also preferably includes a retractor cable guide **918** connected to the light fixture and disposed between the biasing element **914** and the LED module **410** when mounted, and more preferably disposed adjacent the LED module. The retractor cable **916** (and preferably the power line **904**) pass through an opening or passage of, and/or are guided by, the retractor cable guide **918**, which is operable to limit downward movement of portions of the retractor cable **916** and leash **920** that are located between the biasing element **914** and the cable guide **918** during installation and removal. As shown, the retractor cable guide **918** can be in the form of a bridge connected to the light fixture **200** through which the retractor cable **916** and power cable **904** pass.

(151) Preferably, the cable guide **918** is located and operable to prevent the retractor cable **916** (under tension from the biasing element **914** of the cable retractor **902**) from substantially contacting or binding against an outer edge of the opening **273** in the ceiling and/or aperture **206** in the enclosure **202** during installation and removal of the LED module **410**. The cable guide **918** is preferably configured to guide the retractor cable **916** and the leash **920** connected thereto, substantially parallel to the insertion axis during installation and removal of the LED module **410**.

For example, the cable guide **918** can include a bearing portion **938** against which the retractor cable **916** bears (e.g., slides) during installation and removal of the LED module **410**, and the bearing portion **938** can be substantially aligned with (e.g., substantially vertically above or slightly radially outwardly from) an outer edge of the opening **273** in the ceiling and/or aperture **606** of the enclosure **602**. The cable guide **918** is preferably configured to guide the power line **904** in a similar manner, although the power line **904** is preferably not under tension.

(152) The retractor cable **916** is preferably connected to the modular connector **910** of the main power line **906**, and the retractor cable **916** can include a releasable connector **924** between the biasing element **914** and the module connector **910** of the main power line **906**. The leash **920** of the LED Module **410** is preferably releasably connectable to the retractor cable **916** by a releasable connector **922**, such as a pull chain type connector, or other suitable releasable connector.

(153) Preferably, the retractor cable **916** and leash **920** are configured such that the LED power cable **908** is substantially slack (i.e., not in any substantial tension) when the leash **920** is connected to the retractor cable **916** and the LED power cable **908** is connected to the main power line **906**, including when the power line **904** is in a retracted or extended state. For example, the taut length of the leash **920** plus the retractor cable **916** (between the leash and the modular connector **910**) is preferably greater than the length of the LED power cable **908** such that the LED power cable remains substantially slack during installation and removal, while the retractor cable **916** is in tension.

(154) The light fixture **200** can also include a retrieval line **926** which can be used to retrieve the main power line **906** in the event that the leash **920** is disconnected from the retractor cable **916** and the main power line **906** is disconnected from the LED power cable **908** and is retracted. The retrieval line **926** has a first end **928** which is connected to the light fixture adjacent to the LED module **410** and which can be accessed through the aperture, for example with a hook tool. A second end **930** of the retrieval line **926** is connected to modular connector **910** of the main power line **906** and/or the retractor cable **916**. The retrieval line **926** is preferably configured to pass through the retractor cable guide **918**. When needed, the retrieval line **926** can be engaged by a tool and pulled through the aperture to retrieve the main power line **906**.

(155) Referring to FIG. 75, in another preferred embodiment of the light fixture **600**, to increase the contact area of the thermal interfaces (and thereby increase the rate and/or efficiency of heat transfer), a base **1016** of an LED module **1010** can have a convex upper portion **1011** and the heat sink **1028** can have a recess **1029** having a complementary concave shape configured to closely receive the base **1016** of the LED module **1010** such that the base makes an effective mechanical and thermal connection with the heat sink **1028**. Alternatively, the convex/concave configuration of the base and heat sink can be reversed such that the upper portion **1011** of the base can have a concave recess which is configured to couple with a convex portion of the heat sink **1028**.

(156) Preferably, in each configuration, the thermal interfaces of the base and heat sink are configured to press together and thermally couple when in the connected state and are operable to relatively rotate under such pressure such that the light engine assembly can be urged between and into the connected and disconnected states as described herein. As an example, the convex upper portion **1011** of the base **1010** (or in the alternative configuration, the convex portion of the heat sink **1028**) can have a contiguous or non-contiguous surface of revolution about the insertion axis A such as a shape which is substantially conical, frustoconical, semi-spherical, or semi-ellipsoidal (along a major axis of the ellipsoid), or another suitable shape, and the recess **1029** of the heat sink **1028** (or base **1010** in the alternative) can have a complementary contiguous or non-contiguous shape that together are suitable to permit such relatively rotation under such pressure.

(157) Referring to FIG. 76, in another preferred embodiment, the light fixture **200** can include a driver enclosure **2000** connected to the (main) enclosure **2002** for housing an integrated driver.

Claims

1. A recessed light fixture for illuminating a room through an opening in a ceiling, the light fixture comprising: a housing having an aperture; a heat sink disposed within the housing, and the heat sink having a thermal interface; a LED module being insertable into and removable from the housing through the aperture, along an insertion axis; the LED module having a base with a first end and an LED mounted to the first end of the base, and the base having a second end with a thermal interface adapted for thermal coupling to the thermal interface of the heat sink; the base comprising material having high thermal conductivity, and the base being operable for effective conduction of heat from the first end of the base to the second end thereof, to effectively conduct heat from the LED to the heat sink; the LED module being operable to removably mount to the heat sink; in a connected state, the LED module being mounted to the heat sink, and the thermal interface of the base being thermally coupled with the thermal interface of the heat sink, wherein the thermal interfaces of the base and heat sink are pressed together; in a disconnected state, the LED module being dismounted from the heat sink, and the thermal interface of the base being thermally de-coupled from the thermal interface of the heat sink; and the LED module being insertable and removable through the aperture aligned with the opening in the ceiling and operable to be selectively urged into the connected and disconnected states from within the room; whereby the LED module can be replaced or serviced from within the room without disturbing the ceiling; and the LED module being operable to be urged from the disconnected state into the connected state by a partial rotation of the LED module in a first direction about the insertion axis, and being operable to be urged from the connected state into the disconnected state by a partial rotation of the LED module in a second direction opposite the first direction about the insertion axis.
2. The light fixture of claim 1, wherein: the heat sink has a recess configured to closely receive the base of the LED module; the thermal interface of the heat sink is disposed in the recess; and the recess is operable to position the base during mounting of the LED module to the heat sink.
3. The light fixture of claim 1, wherein: the heat sink has a recess configured for insertion of the base of the LED module therein; the thermal interface of the heat sink is disposed in the recess; and the recess is operable to position the base during mounting of the LED module to the heat sink.
4. The light fixture of claim 1, further comprising: a service tool adapted to insert and remove the LED module from the housing through the opening in the ceiling and the aperture; the service tool having a first end configured to releasably connect to the LED module; the first end of the service tool being operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, with the LED module connected thereto, and thereafter being operable to mount the LED module to the heat sink into the connected state, disconnect from the LED module and exit the housing; and the service tool being operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, without the LED module connected thereto, and thereafter being operable to connect to the LED module, dismount the LED module from the heat sink into the disconnected state and remove the LED module from the housing.
5. The light fixture of claim 4, wherein: the LED module has a plurality of mounting projections; the first end of the service tool has a plurality of slots adapted to engage the mounting projections of the LED module to releasably connect the LED module to the service tool.
6. The light fixture of claim 5, wherein: the service tool is operable to rotate the LED module relative to the heat sink in the connected state.
7. The light fixture of claim 4, wherein: the first end of the service tool has a plurality of slots adapted to releasably connect the service tool to the LED module.
8. The light fixture of claim 7, wherein: the first end of the service tool is substantially tubular and is adapted to receive at least a portion of the LED module.

9. The light fixture of claim 4, wherein: the first end of the service tool is substantially tubular and is adapted to receive at least a portion of the LED module.

10. The recessed light fixture of claim 1, further comprising: a mechanical connector disposed within the housing, and operable to removably mount the LED module to the heat sink; and in the connected state, the mechanical connector mechanically fixing the LED module relative to the heat sink, and thermally coupling the thermal interface of the base of the LED module with the thermal interface of the heat sink.

11. The recessed light fixture of claim 10, wherein: the mechanical connector comprises a bayonet connector; and the bayonet connector engages the LED module in the connected state.

12. The recessed light fixture of claim 1, further comprising: a plurality of mounting pins extending radially outwardly from the LED module; and a service tool adapted to releasably connect to the LED module for insertion and removal of the LED module through the opening in the ceiling, the service tool having a first end with a plurality of slots adapted to engage the mounting pins of the LED module, and adapted to rotate the base to urge the base between the connected and disconnected states.

13. The recessed light fixture of claim 12, further comprising: a light engine lock disposed within the housing and having locked and unlocked states; in the locked state, the light engine lock being operable to prevent rotation of the LED module in the connected state; in the unlock state, the light engine lock being operable to allow rotation of the LED module in the connected state; the light engine lock being biased in the locked state; the light engine lock having a cam surface; and during connection and disconnection of the LED module, the service tool is adapted to engage the cam surface of the light engine lock and to urge the light engine lock into the unlocked state.

14. The recessed light fixture of claim 13, further comprising: in the locked state, the light engine lock being operable to prevent rotation of the LED module in the connected state, relative to the heat sink; and in the unlock state, the light engine lock being operable to allow rotation of the LED module in the connected state, relative to the heat sink.

15. The recessed light fixture of claim 1, further comprising: a reflector module with a reflector; the reflector module having a mounted state wherein the reflector module is mounted to the LED module, and having a dismounted state wherein the reflector module is disconnected from the LED module; the reflector module being adapted to be urged from the dismounted state to the mounted state by a partial rotation of the reflector module relative to the LED module about the insertion axis in a mounting direction; and the reflector module being adapted to be urged from the mounted state to the dismounted state by a partial rotation of the reflector module relative to the LED module about the insertion axis in a dismounting direction opposite the mounting direction.

16. The recessed light fixture of claim 15, wherein: the LED module has a plurality of mounting pins extending radially outwardly; and in the mounted state, the reflector module is mounted by the mounting pins of the LED module.

17. The recessed light fixture of claim 16, further comprising: the reflector module having a plurality of mounting pins extending radially outwardly; and a service tool being adapted to releasably connect to the LED module and to insert and remove the LED module from the housing through the opening in the ceiling; and a first end of the tool being adapted to engage the mounting pins of the LED module, and adapted to rotate the LED module relative to the housing, to urge the LED module between the connected and disconnected states; the service tool being adapted to releasably connect to the reflector module and to insert and remove the reflector module from the housing through the opening in the ceiling; and the first end of the tool being adapted to engage the mounting pins of the reflector module, and adapted to rotate the reflector module relative to the LED module, to urge the reflector module between the mounted and dismounted states.

18. The recessed light fixture of claim 1, wherein: the thermal interface of the base is operable to be urged into contact with the thermal interface of the heat sink in an axial motion along the insertion axis and, when in such contact and under pressure, is operable to rotate relative to the thermal

interface of the heat sink about the insertion axis.

19. The recessed light fixture of claim 18, wherein: at least a portion of the thermal interfaces of the base and the heat sink are planar and are perpendicular to the insertion axis.

20. The recessed light fixture of claim 18, wherein: at least a portion of one of the thermal interface of the base and the thermal interface of the heat sink has a substantially convex shape and at least a portion of the other of the thermal interface of the base and the thermal interface of the heat sink has a substantially concave shape configured to couple with the at least a portion of one of the thermal interface.

21. The recessed light fixture of claim 20, wherein: the at least a portion of the one thermal interface having the substantially concave shape is at least a portion of the thermal interface of the heat sink and the at least a portion of the other of the thermal interface having the substantially convex shape is at least a portion of the thermal interface of the base.

22. The recessed light fixture of claim 1, further comprising: an LED power cable connected to and operable to deliver electric power to the LED; a main power line operable to releasably connect to the LED power cable; a cable retractor having a retractor cable connected to the main power line and having a biasing element operable to retract the retractor cable; a leash connected to the LED module and operable to releasably connect to the retractor cable; the cable retractor being operable to permit extension of the main power line through the opening in the ceiling during removal of the LED module and to retract the main power line during installation of the LED module.

23. The recessed light fixture of claim 22, further comprising: the biasing element being operable to bias the retractor cable into a retracted position laterally offset from the base in the connected state; and a retractor cable guide operable to prevent the retractor cable from substantially contacting or binding against an outer edge of the opening in the ceiling during installation and removal of the base.

24. A recessed light fixture for illuminating a room through an opening in a ceiling, the light fixture comprising: a housing having an aperture; a heat sink disposed within the housing, and the heat sink having a thermal interface; a LED module being insertable into and removable from the housing through the aperture; the LED module having a base with a first end and an LED mounted to the first end of the base, and the base having a second end with a thermal interface adapted for thermal coupling to the thermal interface of the heat sink; the base comprising material having high thermal conductivity, and the base being operable for effective conduction of heat from the first end of the base to the second end thereof, to effectively conduct heat from the LED to the heat sink; the LED module being operable to removably mount to the heat sink; in a connected state, the LED module being mounted to the heat sink, and the thermal interface of the base being thermally coupled with the thermal interface of the heat sink, wherein the thermal interfaces of the base and heat sink are pressed together; in a disconnected state, the LED module being dismounted from the heat sink, and the thermal interface of the base being thermally de-coupled from the thermal interface of the heat sink; the LED module being insertable and removable through the aperture aligned with the opening in the ceiling and operable to be selectively urged into the connected and disconnected states from within the room where a maximal clearance between the LED module and the opening in the ceiling is not substantially greater than required for the LED module to fit through the opening; whereby the LED module can be replaced or serviced from within the room without disturbing the ceiling; and the LED module being operable to be urged from the disconnected state into the connected state by a partial rotation of the LED module in a first direction about the insertion axis, and being operable to urged from the connected state into the disconnected state by a partial rotation of the LED module in a second direction opposite the first direction about the section axis.

25. The light fixture of claim 24, further comprising: a service tool adapted to insert and remove the LED module from the housing through the opening in the ceiling and the aperture; the service tool having a first end configured to releasably connect to the LED module; the first end of the

service tool being operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, with the LED module connected thereto, and thereafter being operable to mount the LED module to the heat sink into the connected state, disconnect from the LED module and exit the housing; and the service tool being operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, without the LED module connected thereto, and thereafter being operable to connect to the LED module, dismount the LED module from the heat sink into the disconnected state and remove the LED module from the housing.

26. The light fixture of claim 25, wherein: the LED module has a plurality of mounting projections; and the first end of the service tool has a plurality of slots adapted to engage the mounting projections of the LED module to releasably connect the LED module to the service tool.

27. A recessed light fixture for illuminating a room through an opening in a ceiling, the light fixture comprising: a housing having an aperture; a heat sink disposed within the housing, and the heat sink having a thermal interface; a LED module being insertable into and removable from the housing through the aperture, along an insertion axis; the LED module having a base with a first end and an LED mounted to the first end of the base, and the base having a second end with a thermal interface adapted for thermal coupling to the thermal interface of the heat sink; the base comprising material having high thermal conductivity, and the base being operable for effective conduction of heat from the first end of the base to the second end thereof, to effectively conduct heat from the LED to the heat sink; the LED module being operable to removably mount to the heat sink; in a connected state, the LED module being mounted to the heat sink, and the thermal interface of the base being thermally coupled with the thermal interface of the heat sink, wherein the thermal interfaces of the base and heat sink are pressed together; in a disconnected state, the LED module being dismounted from the heat sink, and the thermal interface of the base being thermally de-coupled from the thermal interface of the heat sink; the LED module being insertable and removable through the aperture aligned with the opening in the ceiling and operable to be selectively urged into the connected and disconnected states from within the room; whereby the LED module can be replaced or serviced from within the room without disturbing the ceiling; the heat sink has a recess configured for insertion of the base of the LED module therein; the thermal interface of the heat sink is disposed in the recess; and the recess is operable to position the base during mounting of the LED module to the heat sink.

28. The light fixture of claim 27, wherein: the recess is configured to closely receive the base of the LED module.

29. A recessed light fixture for illuminating a room through an opening in a ceiling, the light fixture comprising: a housing having an aperture; a heat sink disposed within the housing, and the heat sink having a thermal interface; a LED module being insertable into and removable from the housing through the aperture, along an insertion axis; the LED module having a base with a first end and an LED mounted to the first end of the base, and the base having a second end with a thermal interface adapted for thermal coupling to the thermal interface of the heat sink; the base comprising material having high thermal conductivity, and the base being operable for effective conduction of heat from the first end of the base to the second end thereof, to effectively conduct heat from the LED to the heat sink; the LED module being operable to removably mount to the heat sink; in a connected state, the LED module being mounted to the heat sink, and the thermal interface of the base being thermally coupled with the thermal interface of the heat sink, wherein the thermal interfaces of the base and heat sink are pressed together; in a disconnected state, the LED module being dismounted from the heat sink, and the thermal interface of the base being thermally de-coupled from the thermal interface of the heat sink; the LED module being insertable and removable through the aperture aligned with the opening in the ceiling and operable to be selectively urged into the connected and disconnected states from within the room; whereby the LED module can be replaced or serviced from within the room without disturbing the ceiling; a

service tool adapted to insert and remove the LED module from the housing through the opening in the ceiling and the aperture; the service tool having a first end configured to releasably connect to the LED module; the first end of the service tool being operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, with the LED module connected thereto, and thereafter being operable to mount the LED module to the heat sink into the connected state, disconnect from the LED module and exit the housing; the service tool being operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, without the LED module connected thereto, and thereafter being operable to connect to the LED module, dismount the LED module from the heat sink into the disconnected state and remove the LED module from the housing; the LED module has a plurality of mounting projections; and the first end of the service tool has a plurality of slots adapted to engage the mounting projections of the LED module to releasably connect the LED module to the service tool.

30. The light fixture of claim 29, wherein: the service tool is operable to rotate the LED module relative to the heat sink in the connected state.

31. A recessed light fixture for illuminating a room through an opening in a ceiling, the light fixture comprising: a housing having an aperture; a heat sink disposed within the housing, and the heat sink having a thermal interface; a LED module being insertable into and removable from the housing through the aperture, along an insertion axis; the LED module having a base with a first end and an LED mounted to the first end of the base, and the base having a second end with a thermal interface adapted for thermal coupling to the thermal interface of the heat sink; the base comprising material having high thermal conductivity, and the base being operable for effective conduction of heat from the first end of the base to the second end thereof, to effectively conduct heat from the LED to the heat sink; the LED module being operable to removably mount to the heat sink; in a connected state, the LED module being mounted to the heat sink, and the thermal interface of the base being thermally coupled with the thermal interface of the heat sink, wherein the thermal interfaces of the base and heat sink are pressed together; in a disconnected state, the LED module being dismounted from the heat sink, and the thermal interface of the base being thermally de-coupled from the thermal interface of the heat sink; the LED module being insertable and removable through the aperture aligned with the opening in the ceiling and operable to be selectively urged into the connected and disconnected states from within the room; whereby the LED module can be replaced or serviced from within the room without disturbing the ceiling; the LED module is operable to be urged from the disconnected state into the connected state by rotation of the LED module relative to the housing in a first direction about the insertion axis, and is operable to urged from the connected state into the disconnected state by rotation of the LED module relative to the housing in a second direction opposite the first direction about the insertion axis; a mechanical connector disposed within the housing, and operable to removably mount the LED module to the heat sink; in the connected state, the mechanical connector mechanically fixing the LED module relative to the heat sink, and thermally coupling the thermal interface of the base of the LED module with the thermal interface of the heat sink; the mechanical connector comprises a bayonet connector; and the bayonet connector engages the LED module in the connected state.

32. A recessed light fixture for illuminating a room through an opening in a ceiling, the light fixture comprising: a housing having an aperture; a heat sink disposed within the housing, and the heat sink having a thermal interface; a LED module being insertable into and removable from the housing through the aperture, along an insertion axis; the LED module having a base with a first end and an LED mounted to the first end of the base, and the base having a second end with a thermal interface adapted for thermal coupling to the thermal interface of the heat sink; the base comprising material having high thermal conductivity, and the base being operable for effective conduction of heat from the first end of the base to the second end thereof, to effectively conduct heat from the LED to the heat sink; the LED module being operable to removably mount to the heat sink; in a connected state, the LED module being mounted to the heat sink, and the thermal

interface of the base being thermally coupled with the thermal interface of the heat sink, wherein the thermal interfaces of the base and heat sink are pressed together; in a disconnected state, the LED module being dismounted from the heat sink, and the thermal interface of the base being thermally de-coupled from the thermal interface of the heat sink; the LED module being insertable and removable through the aperture aligned with the opening in the ceiling and operable to be selectively urged into the connected and disconnected states from within the room; whereby the LED module can be replaced or serviced from within the room without disturbing the ceiling; the LED module is operable to be urged from the disconnected state into the connected state by rotation of the LED module relative to the housing in a first direction about the insertion axis, and is operable to be urged from the connected state into the disconnected state by rotation of the LED module relative to the housing in a second direction opposite the first direction about the insertion axis; a plurality of mounting pins extending radially outwardly from the LED module; and a service tool adapted to releasably connect to the LED module for insertion and removal of the LED module through the opening in the ceiling, the service tool having a first end with a plurality of slots adapted to engage the mounting pins of the LED module, and adapted to rotate the base to urge the base between the connected and disconnected states.

33. The recessed light fixture of claim 32, further comprising: a light engine lock disposed within the housing and having locked and unlocked states; in the locked state, the light engine lock being operable to prevent rotation of the LED module in the connected state; in the unlock state, the light engine lock being operable to allow rotation of the LED module in the connected state; the light engine lock being biased in the locked state; the light engine lock having a cam surface; and during connection and disconnection of the LED module, the service tool is adapted to engage the cam surface of the light engine lock and to urge the light engine lock into the unlocked state.

34. The recessed light fixture of claim 33, further comprising: in the locked state, the light engine lock being operable to prevent rotation of the LED module in the connected state, relative to the heat sink; and in the unlock state, the light engine lock being operable to allow rotation of the LED module in the connected state, relative to the heat sink.

35. A recessed light fixture for illuminating a room through an opening in a ceiling, the light fixture comprising: a housing having an aperture; a heat sink disposed within the housing, and the heat sink having a thermal interface; a LED module being insertable into and removable from the housing through the aperture, along an insertion axis; the LED module having a base with a first end and an LED mounted to the first end of the base, and the base having a second end with a thermal interface adapted for thermal coupling to the thermal interface of the heat sink; the base comprising material having high thermal conductivity, and the base being operable for effective conduction of heat from the first end of the base to the second end thereof, to effectively conduct heat from the LED to the heat sink; the LED module being operable to removably mount to the heat sink; in a connected state, the LED module being mounted to the heat sink, and the thermal interface of the base being thermally coupled with the thermal interface of the heat sink, wherein the thermal interfaces of the base and heat sink are pressed together; in a disconnected state, the LED module being dismounted from the heat sink, and the thermal interface of the base being thermally de-coupled from the thermal interface of the heat sink; the LED module being insertable and removable through the aperture aligned with the opening in the ceiling and operable to be selectively urged into the connected and disconnected states from within the room; whereby the LED module can be replaced or serviced from within the room without disturbing the ceiling; a service tool adapted to insert and remove the LED module from the housing through the opening in the ceiling and the aperture; the service tool having a first end configured to releasably connect to the LED module; the first end of the service tool being operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, with the LED module connected thereto, and thereafter being operable to mount the LED module to the heat sink into the connected state, disconnect from the LED module and exit the housing; the service tool being

operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, without the LED module connected thereto, and thereafter being operable to connect to the LED module, dismount the LED module from the heat sink into the disconnected state and remove the LED module from the housing; and the first end of the service tool has a plurality of slots adapted to releasably connect the service tool to the LED module.

36. The light fixture of claim 35, wherein: the first end of the service tool is substantially tubular and is adapted to receive at least a portion of the LED module.

37. A recessed light fixture for illuminating a room through an opening in a ceiling, the light fixture comprising: a housing having an aperture; a heat sink disposed within the housing, and the heat sink having a thermal interface; a LED module being insertable into and removable from the housing through the aperture, along an insertion axis; the LED module having a base with a first end and an LED mounted to the first end of the base, and the base having a second end with a thermal interface adapted for thermal coupling to the thermal interface of the heat sink; the base comprising material having high thermal conductivity, and the base being operable for effective conduction of heat from the first end of the base to the second end thereof, to effectively conduct heat from the LED to the heat sink; the LED module being operable to removably mount to the heat sink; in a connected state, the LED module being mounted to the heat sink, and the thermal interface of the base being thermally coupled with the thermal interface of the heat sink, wherein the thermal interfaces of the base and heat sink are pressed together; in a disconnected state, the LED module being dismounted from the heat sink, and the thermal interface of the base being thermally de-coupled from the thermal interface of the heat sink; the LED module being insertable and removable through the aperture aligned with the opening in the ceiling and operable to be selectively urged into the connected and disconnected states from within the room; whereby the LED module can be replaced or serviced from within the room without disturbing the ceiling; a service tool adapted to insert and remove the LED module from the housing through the opening in the ceiling and the aperture; the service tool having a first end configured to releasably connect to the LED module; the first end of the service tool being operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, with the LED module connected thereto, and thereafter being operable to mount the LED module to the heat sink into the connected state, disconnect from the LED module and exit the housing; the service tool being operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, without the LED module connected thereto, and thereafter being operable to connect to the LED module, dismount the LED module from the heat sink into the disconnected state and remove the LED module from the housing; and the first end of the service tool is substantially tubular and is adapted to receive at least a portion of the LED module.

38. A recessed light fixture for illuminating a room through an opening in a ceiling, the light fixture comprising: a housing having an aperture; a heat sink disposed within the housing, and the heat sink having a thermal interface; a LED module being insertable into and removable from the housing through the aperture; the LED module having a base with a first end and an LED mounted to the first end of the base, and the base having a second end with a thermal interface adapted for thermal coupling to the thermal interface of the heat sink; the base comprising material having high thermal conductivity, and the base being operable for effective conduction of heat from the first end of the base to the second end thereof, to effectively conduct heat from the LED to the heat sink; the LED module being operable to removably mount to the heat sink; in a connected state, the LED module being mounted to the heat sink, and the thermal interface of the base being thermally coupled with the thermal interface of the heat sink, wherein the thermal interfaces of the base and heat sink are pressed together; in a disconnected state, the LED module being dismounted from the heat sink, and the thermal interface of the base being thermally de-coupled from the thermal interface of the heat sink; the LED module being insertable and removable through the aperture aligned with the opening in the ceiling and operable to be selectively urged into the connected and

disconnected states from within the room where a maximal clearance between the LED module and the opening in the ceiling is not substantially greater than required for the LED module to fit through the opening; whereby the LED module can be replaced or serviced from within the room without disturbing the ceiling; a service tool adapted to insert and remove the LED module from the housing through the opening in the ceiling and the aperture; the service tool having a first end configured to releasably connect to the LED module; the first end of the service tool being operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, with the LED module connected thereto, and thereafter being operable to mount the LED module to the heat sink into the connected state, disconnect from the LED module and exit the housing; the service tool being operable to be inserted into the housing through the opening in the ceiling and the aperture, from within the room, without the LED module connected thereto, and thereafter being operable to connect to the LED module, dismount the LED module from the heat sink into the disconnected state and remove the LED module from the housing; the LED module has a plurality of mounting projections; and the first end of the service tool has a plurality of slots adapted to engage the mounting projections of the LED module to releasably connect the LED module to the service tool.
