



US012418327B2

(12) **United States Patent**
Chan et al.

(10) **Patent No.:** **US 12,418,327 B2**

(45) **Date of Patent:** ***Sep. 16, 2025**

(54) **SYSTEMS AND METHODS FOR MACHINE LEARNING ZONE-BASED FOREIGN OBJECT DETECTION FOR WIRELESS POWER TRANSMISSION**

(56) **References Cited**

U.S. PATENT DOCUMENTS

787,412 A 4/1905 Tesla
2,811,624 A 10/1957 Haagenen
(Continued)

(71) Applicant: **Energous Corporation**, San Jose, CA (US)

FOREIGN PATENT DOCUMENTS

CN 101496222 A 7/2009
CN 201278367 Y 7/2009
(Continued)

(72) Inventors: **Howard Chan**, San Jose, CA (US);
Deepak Jain, San Ramon, CA (US)

(73) Assignee: **ENERGIOUS CORPORATION**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 50 days.

OTHER PUBLICATIONS

Energous Corp., IPRP, PCT/US2014/040697, Dec. 8, 2015, 9 pgs.
(Continued)

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/522,082**

Primary Examiner — Levi Gannon

(22) Filed: **Nov. 28, 2023**

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP; Colin Fowler

(65) **Prior Publication Data**

US 2024/0171218 A1 May 23, 2024

(57) **ABSTRACT**

Related U.S. Application Data

(63) Continuation of application No. 17/831,037, filed on Jun. 2, 2022, now Pat. No. 11,831,361, which is a
(Continued)

An example method is provided for detecting and classifying foreign objects. The method includes after a predetermined period of time, for a zone of a plurality of zones, enabling a beacon signal, obtaining a set of electrical measurements, and disabling the beacon signal. The method also includes determining, based on the set of electrical measurements and a trained classifier, a status of the zone. The status of the zone indicates whether there is a presence of foreign objects within the zone of the plurality of zones. The method further includes in accordance with an indication that there is the presence of the foreign objects, forgo transmitting wireless power to one or more wireless power receivers. The method further includes in accordance with an indication that there is an absence of the foreign objects, transmitting wireless power to the one or more wireless power receivers.

(51) **Int. Cl.**
H02J 50/60 (2016.01)
H02J 50/20 (2016.01)


(Continued)

(52) **U.S. Cl.**
CPC **H04B 5/79** (2024.01); **H02J 50/20**
(2016.02); **H02J 50/402** (2020.01); **H02J**
50/60 (2016.02)

(58) **Field of Classification Search**
CPC .. H02J 50/20; H02J 50/23; H02J 50/40; H02J
50/402; H02J 50/60; H02J 50/80

See application file for complete search history.

20 Claims, 18 Drawing Sheets



Related U.S. Application Data

continuation of application No. 17/026,196, filed on
Sep. 19, 2020, now Pat. No. 11,381,118.

- (60) Provisional application No. 62/903,674, filed on Sep.
20, 2019.

(51) **Int. Cl.**

H02J 50/40 (2016.01)

H04B 5/79 (2024.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,863,148	A	12/1958	Gammon et al.	7,215,296	B2	5/2007	Abramov et al.
3,167,775	A	1/1965	Guertler	7,222,356	B1	5/2007	Yonezawa et al.
3,434,678	A	3/1969	Brown et al.	7,274,334	B2	9/2007	O'Riordan et al.
3,696,384	A	10/1972	Lester	7,274,336	B2	9/2007	Carson
3,754,269	A	8/1973	Clavin	7,351,975	B2	4/2008	Brady et al.
4,101,895	A	7/1978	Jones, Jr.	7,359,730	B2	4/2008	Dennis et al.
4,360,741	A	11/1982	Fitzsimmons et al.	7,372,408	B2	5/2008	Gaucher
4,944,036	A	7/1990	Hyatt	7,392,068	B2	6/2008	Dayan
4,995,010	A	2/1991	Knight	7,403,803	B2	7/2008	Mickle et al.
5,142,292	A	8/1992	Chang	7,443,057	B2	10/2008	Nunally
5,200,759	A	4/1993	McGinnis	7,451,839	B2	11/2008	Perlman
5,211,471	A	5/1993	Rohrs	7,463,201	B2	12/2008	Chiang et al.
5,276,455	A	1/1994	Fitzsimmons et al.	7,471,247	B2	12/2008	Saily
5,548,292	A	8/1996	Hirshfield et al.	7,535,195	B1	5/2009	Horovitz et al.
5,556,749	A	9/1996	Mitsuhashi et al.	7,614,556	B2	11/2009	Overhultz et al.
5,568,088	A	10/1996	Dent et al.	7,639,994	B2	12/2009	Greene et al.
5,631,572	A	5/1997	Sheen et al.	7,643,312	B2	1/2010	Vanderelli et al.
5,646,633	A	7/1997	Dahlberg	7,652,577	B1	1/2010	Madhow et al.
5,697,063	A	12/1997	Kishigami et al.	7,663,555	B2	2/2010	Caimi et al.
5,712,642	A	1/1998	Hulderman	7,679,576	B2	3/2010	Riedel et al.
5,936,527	A	8/1999	Isaacman et al.	7,702,771	B2	4/2010	Ewing et al.
5,982,139	A	11/1999	Parise	7,786,419	B2	8/2010	Hyde et al.
6,046,708	A	4/2000	MacDonald, Jr. et al.	7,812,771	B2	10/2010	Greene et al.
6,061,025	A	5/2000	Jackson et al.	7,830,312	B2	11/2010	Choudhury et al.
6,127,799	A	10/2000	Krishnan	7,844,306	B2	11/2010	Shearer et al.
6,127,942	A	10/2000	Welle	7,868,482	B2	1/2011	Greene et al.
6,163,296	A	12/2000	Lier et al.	7,898,105	B2	3/2011	Greene et al.
6,176,433	B1	1/2001	Uesaka et al.	7,904,117	B2	3/2011	Doan et al.
6,271,799	B1	8/2001	Rief	7,911,386	B1	3/2011	Itoh et al.
6,289,237	B1	9/2001	Mickle et al.	7,925,308	B2	4/2011	Greene et al.
6,329,908	B1	12/2001	Freeska	7,948,208	B2	5/2011	Partovi et al.
6,400,586	B2	6/2002	Raddi et al.	8,049,676	B2	11/2011	Yoon et al.
6,421,235	B2	7/2002	Ditzik	8,055,003	B2	11/2011	Mittleman et al.
6,437,685	B2	8/2002	Hanaki	8,070,595	B2	12/2011	Alderucci et al.
6,456,253	B1	9/2002	Rummeli et al.	8,072,380	B2	12/2011	Crouch
6,476,795	B1	11/2002	Derocher et al.	8,092,301	B2	1/2012	Alderucci et al.
6,501,414	B2	12/2002	Arndt et al.	8,099,140	B2	1/2012	Arai
6,583,723	B2	6/2003	Watanabe et al.	8,115,448	B2	2/2012	John
6,597,897	B2	7/2003	Tang	8,159,090	B2	4/2012	Greene et al.
6,615,074	B2	9/2003	Mickle et al.	8,159,364	B2	4/2012	Zeine
6,650,376	B1	11/2003	Obitsu	8,180,286	B2	5/2012	Yamasuge
6,664,920	B1	12/2003	Mott et al.	8,184,454	B2	5/2012	Mao
6,680,700	B2	1/2004	Hilgers	8,228,194	B2	7/2012	Mickle
6,798,716	B1	9/2004	Charych	8,234,509	B2	7/2012	Gioscia et al.
6,803,744	B1	10/2004	Sabo	8,264,101	B2	9/2012	Hyde et al.
6,853,197	B1	2/2005	McFarland	8,264,291	B2	9/2012	Morita
6,856,291	B2	2/2005	Mickle et al.	8,276,325	B2	10/2012	Clifton et al.
6,911,945	B2	6/2005	Korva	8,278,784	B2	10/2012	Cook et al.
6,960,968	B2	11/2005	Odendaal et al.	8,284,101	B2	10/2012	Fusco
6,967,462	B1	11/2005	Landis	8,310,201	B1	11/2012	Wright
6,988,026	B2	1/2006	Breed et al.	8,338,991	B2	12/2012	Von Novak et al.
7,003,350	B2	2/2006	Denker et al.	8,362,745	B2	1/2013	Tinaphong
7,012,572	B1	3/2006	Schaffner et al.	8,380,255	B2	2/2013	Shearer et al.
7,027,311	B2	4/2006	Vanderelli et al.	8,384,600	B2	2/2013	Huang et al.
7,068,234	B2	6/2006	Sievenpiper	8,410,953	B2	4/2013	Zeine
7,068,991	B2	6/2006	Parise	8,411,963	B2	4/2013	Luff
7,079,079	B2	7/2006	Jo et al.	8,432,062	B2	4/2013	Greene et al.
7,183,748	B1	2/2007	Unno et al.	8,432,071	B2	4/2013	Huang et al.
7,191,013	B1	3/2007	Miranda et al.	8,446,248	B2	5/2013	Zeine
7,193,644	B2	3/2007	Carter	8,447,234	B2	5/2013	Cook et al.
7,196,663	B2	3/2007	Bolzer et al.	8,451,189	B1	5/2013	Fluhler
7,205,749	B2	4/2007	Hagen et al.	8,452,235	B2	5/2013	Kirby et al.
				8,457,656	B2	6/2013	Perkins et al.
				8,461,817	B2	6/2013	Martin et al.
				8,467,733	B2	6/2013	Leabman
				8,497,601	B2	7/2013	Hall et al.
				8,497,658	B2	7/2013	Von Novak et al.
				8,552,597	B2	10/2013	Song et al.
				8,558,661	B2	10/2013	Zeine
				8,560,026	B2	10/2013	Chanterac
				8,564,485	B2	10/2013	Milosavljevic et al.
				8,604,746	B2	12/2013	Lee
				8,614,643	B2	12/2013	Leabman
				8,621,245	B2	12/2013	Shearer et al.
				8,626,249	B2	1/2014	Ungari et al.
				8,629,576	B2	1/2014	Levine
				8,653,966	B2	2/2014	Rao et al.
				8,655,272	B2	2/2014	Saunamäki
				8,674,551	B2	3/2014	Low et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,686,685 B2	4/2014	Moshfeghi	9,590,444 B2	3/2017	Walley
8,686,905 B2	4/2014	Shtrom	9,620,996 B2	4/2017	Zeine
8,712,355 B2	4/2014	Black et al.	9,647,328 B2	5/2017	Dobric
8,712,485 B2	4/2014	Tam	9,706,137 B2	7/2017	Scanlon et al.
8,718,773 B2	5/2014	Wills et al.	9,711,999 B2	7/2017	Hietala et al.
8,729,737 B2	5/2014	Schatz et al.	9,723,635 B2	8/2017	Nambord et al.
8,736,228 B1	5/2014	Freed et al.	9,793,758 B2	10/2017	Leabman
8,760,113 B2	6/2014	Keating	9,793,764 B2	10/2017	Perry
8,770,482 B2	7/2014	Ackermann et al.	9,800,080 B2	10/2017	Leabman et al.
8,772,960 B2	7/2014	Yoshida	9,800,172 B1	10/2017	Leabman
8,823,319 B2	9/2014	Von Novak, III et al.	9,806,564 B2	10/2017	Leabman
8,832,646 B1	9/2014	Wendling	9,819,230 B2	11/2017	Petras et al.
8,854,176 B2	10/2014	Zeine	9,824,815 B2	11/2017	Leabman et al.
8,860,364 B2	10/2014	Low et al.	9,825,674 B1	11/2017	Leabman
8,897,770 B1	11/2014	Frolov et al.	9,831,718 B2	11/2017	Leabman et al.
8,903,456 B2	12/2014	Chu et al.	9,838,083 B2	12/2017	Bell et al.
8,917,057 B2	12/2014	Hui	9,843,213 B2	12/2017	Leabman et al.
8,923,189 B2	12/2014	Leabman	9,843,229 B2	12/2017	Leabman
8,928,544 B2	1/2015	Massie et al.	9,843,763 B2	12/2017	Leabman et al.
8,937,408 B2	1/2015	Ganem et al.	9,847,669 B2	12/2017	Leabman
8,946,940 B2	2/2015	Kim et al.	9,847,677 B1	12/2017	Leabman
8,963,486 B2	2/2015	Kirby et al.	9,847,679 B2	12/2017	Bell et al.
8,989,053 B1	3/2015	Skaakrud et al.	9,853,361 B2	12/2017	Chen et al.
9,000,616 B2	4/2015	Greene et al.	9,853,692 B1	12/2017	Bell et al.
9,001,622 B2	4/2015	Perry	9,859,756 B2	1/2018	Leabman et al.
9,006,934 B2	4/2015	Kozakai et al.	9,859,758 B1	1/2018	Leabman
9,021,277 B2	4/2015	Shearer et al.	9,866,279 B2	1/2018	Bell et al.
9,030,161 B2	5/2015	Lu et al.	9,867,032 B2	1/2018	Verma et al.
9,059,598 B2	6/2015	Kang et al.	9,871,301 B2	1/2018	Contopanagos
9,059,599 B2	6/2015	Won et al.	9,876,380 B1	1/2018	Leabman et al.
9,077,188 B2	7/2015	Moshfeghi	9,876,394 B1	1/2018	Leabman
9,083,595 B2	7/2015	Rakib et al.	9,876,536 B1	1/2018	Bell et al.
9,088,216 B2	7/2015	Garrity et al.	9,876,648 B2	1/2018	Bell
9,124,125 B2	9/2015	Leabman et al.	9,882,394 B1	1/2018	Bell et al.
9,130,397 B2	9/2015	Leabman et al.	9,882,427 B2	1/2018	Leabman et al.
9,130,602 B2	9/2015	Cook	9,887,584 B1	2/2018	Bell et al.
9,142,998 B2	9/2015	Yu et al.	9,887,739 B2	2/2018	Leabman et al.
9,143,000 B2	9/2015	Leabman et al.	9,891,669 B2	2/2018	Bell
9,143,010 B2	9/2015	Urano	9,893,554 B2	2/2018	Bell et al.
9,153,074 B2	10/2015	Zhou et al.	9,893,555 B1	2/2018	Leabman et al.
9,178,389 B2	11/2015	Hwang	9,893,564 B2	2/2018	De Rochemont
9,225,196 B2	12/2015	Huang et al.	9,899,744 B1	2/2018	Contopanagos et al.
9,240,469 B2	1/2016	Sun et al.	9,899,844 B1	2/2018	Bell et al.
9,242,411 B2	1/2016	Kritchman et al.	9,899,861 B1	2/2018	Leabman et al.
9,244,500 B2	1/2016	Cain et al.	9,899,873 B2	2/2018	Bell et al.
9,252,628 B2	2/2016	Leabman et al.	9,912,199 B2	3/2018	Leabman et al.
9,270,344 B2	2/2016	Rosenberg	9,916,485 B1	3/2018	Lilly et al.
9,276,329 B2	3/2016	Jones et al.	9,917,477 B1	3/2018	Bell et al.
9,282,582 B1	3/2016	Dunsbergen et al.	9,923,386 B1	3/2018	Leabman et al.
9,294,840 B1	3/2016	Anderson et al.	9,939,864 B1	4/2018	Bell et al.
9,297,896 B1	3/2016	Andrews	9,941,747 B2	4/2018	Bell et al.
9,318,898 B2	4/2016	John	9,965,009 B1	5/2018	Bell et al.
9,368,020 B1	6/2016	Bell et al.	9,966,765 B1	5/2018	Leabman
9,401,977 B1	7/2016	Gaw	9,966,784 B2	5/2018	Leabman
9,409,490 B2	8/2016	Kawashima	9,967,743 B1	5/2018	Bell et al.
9,419,335 B2	8/2016	Pintos	9,973,008 B1	5/2018	Leabman
9,419,443 B2	8/2016	Leabman	10,003,211 B1	6/2018	Leabman et al.
9,438,045 B1	9/2016	Leabman	10,008,777 B1	6/2018	Broyde et al.
9,438,046 B1	9/2016	Leabman	10,008,889 B2	6/2018	Bell et al.
9,444,283 B2	9/2016	Son et al.	10,014,728 B1	7/2018	Leabman
9,450,449 B1	9/2016	Leabman et al.	10,027,159 B2	7/2018	Hosseini
9,461,502 B2	10/2016	Lee et al.	10,038,337 B1	7/2018	Leabman et al.
9,520,725 B2	12/2016	Masaoka et al.	10,050,462 B1	8/2018	Leabman et al.
9,520,748 B2	12/2016	Hyde et al.	10,056,782 B1	8/2018	Leabman
9,522,270 B2	12/2016	Perryman et al.	10,063,064 B1	8/2018	Bell et al.
9,532,748 B2	1/2017	Denison et al.	10,063,105 B2	8/2018	Leabman
9,537,354 B2	1/2017	Bell et al.	10,063,106 B2	8/2018	Bell et al.
9,537,357 B2	1/2017	Leabman	10,068,703 B1	9/2018	Contopanagos
9,537,358 B2	1/2017	Leabman	10,075,008 B1	9/2018	Bell et al.
9,538,382 B2	1/2017	Bell et al.	10,075,017 B2	9/2018	Leabman et al.
9,544,640 B2	1/2017	Lau	10,079,515 B2	9/2018	Hosseini et al.
9,559,553 B2	1/2017	Bae	10,090,699 B1	10/2018	Leabman
9,564,773 B2	2/2017	Pogorelik et al.	10,090,714 B2	10/2018	Bohn et al.
9,571,974 B2	2/2017	Choi et al.	10,090,886 B1	10/2018	Bell et al.
9,590,317 B2	3/2017	Zimmerman et al.	10,103,552 B1	10/2018	Leabman et al.
			10,103,582 B2	10/2018	Leabman et al.
			10,110,046 B1	10/2018	Esquibel et al.
			10,122,219 B1	11/2018	Hosseini et al.
			10,122,415 B2	11/2018	Bell et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

10,124,754	B1	11/2018	Leabman	10,511,196	B2	12/2019	Hosseini
10,128,686	B1	11/2018	Leabman et al.	10,516,289	B2	12/2019	Leabman et al.
10,128,693	B2	11/2018	Bell et al.	10,516,301	B2	12/2019	Leabman
10,128,695	B2	11/2018	Leabman et al.	10,523,033	B2	12/2019	Leabman
10,128,699	B2	11/2018	Leabman	10,523,058	B2	12/2019	Leabman
10,134,260	B1	11/2018	Bell et al.	10,554,052	B2	2/2020	Bell et al.
10,135,112	B1	11/2018	Hosseini	10,594,165	B2	3/2020	Hosseini
10,135,286	B2	11/2018	Hosseini et al.	10,615,647	B2	4/2020	Johnston et al.
10,135,294	B1	11/2018	Leabman	10,680,319	B2	6/2020	Hosseini et al.
10,135,295	B2	11/2018	Leabman	10,714,984	B2	7/2020	Hosseini et al.
10,141,768	B2	11/2018	Leabman et al.	10,734,717	B2	8/2020	Hosseini
10,141,771	B1	11/2018	Hosseini et al.	10,778,041	B2	9/2020	Leabman
10,141,791	B2	11/2018	Bell et al.	10,790,674	B2	9/2020	Bell et al.
10,148,097	B1	12/2018	Leabman et al.	10,840,743	B2	11/2020	Johnston et al.
10,153,645	B1	12/2018	Bell et al.	10,879,740	B2	12/2020	Hosseini
10,153,653	B1	12/2018	Bell et al.	10,923,954	B2	2/2021	Leabman
10,153,660	B1	12/2018	Leabman et al.	10,958,095	B2	3/2021	Leabman et al.
10,158,257	B2	12/2018	Leabman	10,985,617	B1	4/2021	Johnston et al.
10,158,259	B1	12/2018	Leabman	11,011,942	B2	5/2021	Liu
10,164,478	B2	12/2018	Leabman	11,139,699	B2	10/2021	Johnston et al.
10,170,917	B1	1/2019	Bell et al.	11,381,118	B2	7/2022	Chan et al.
10,177,594	B2	1/2019	Contopanagos	11,451,096	B2	9/2022	Hoss
10,181,756	B2	1/2019	Bae et al.	11,710,987	B2	7/2023	Johnston et al.
10,186,892	B2	1/2019	Hosseini et al.	11,715,980	B2	8/2023	Johnston et al.
10,186,893	B2	1/2019	Bell et al.	11,831,361	B2	11/2023	Chan et al.
10,186,911	B2	1/2019	Leabman	11,863,001	B2	1/2024	Hoss
10,186,913	B2	1/2019	Leabman et al.	2002/0065052	A1	5/2002	Pande et al.
10,193,396	B1	1/2019	Bell et al.	2002/0103447	A1	8/2002	Terry
10,199,835	B2	2/2019	Leabman	2002/0171594	A1	11/2002	Fang
10,199,849	B1	2/2019	Bell	2003/0038750	A1	2/2003	Chen
10,199,850	B2	2/2019	Leabman	2003/0058187	A1	3/2003	Billiet et al.
10,205,239	B1	2/2019	Contopanagos et al.	2004/0020100	A1	2/2004	O'Brien et al.
10,206,185	B2	2/2019	Leabman et al.	2004/0130425	A1	7/2004	Dayan et al.
10,211,674	B1	2/2019	Leabman et al.	2004/0130442	A1	7/2004	Breed
10,211,680	B2	2/2019	Leabman et al.	2004/0145342	A1	7/2004	Lyon
10,211,682	B2	2/2019	Bell et al.	2004/0155832	A1	8/2004	Yuanzhu
10,211,685	B2	2/2019	Bell et al.	2004/0207559	A1	10/2004	Milosavljevic
10,218,207	B2	2/2019	Hosseini et al.	2004/0259604	A1	12/2004	Mickle et al.
10,218,227	B2	2/2019	Leabman et al.	2005/0007276	A1	1/2005	Barrick et al.
10,223,717	B1	3/2019	Bell	2005/0116683	A1	6/2005	Cheng
10,224,758	B2	3/2019	Leabman et al.	2005/0117660	A1	6/2005	Vialle et al.
10,224,982	B1	3/2019	Leabman	2005/0134517	A1	6/2005	Gottl
10,230,266	B1	3/2019	Leabman et al.	2005/0227619	A1	10/2005	Lee et al.
10,243,414	B1	3/2019	Leabman et al.	2005/0237258	A1	10/2005	Abramov et al.
10,256,657	B2	4/2019	Hosseini et al.	2006/0013335	A1	1/2006	Leabman
10,256,677	B2	4/2019	Hosseini et al.	2006/0019712	A1	1/2006	Choi
10,263,432	B1	4/2019	Leabman et al.	2006/0030279	A1	2/2006	Leabman et al.
10,263,476	B2	4/2019	Leabman	2006/0092079	A1	5/2006	de Rochemont
10,270,261	B2	4/2019	Bell et al.	2006/0094425	A1	5/2006	Mickle et al.
10,277,054	B2	4/2019	Hosseini	2006/0113955	A1	6/2006	Nunally
10,291,055	B1	5/2019	Bell et al.	2006/0119532	A1	6/2006	Yun et al.
10,291,056	B2	5/2019	Bell et al.	2006/0132360	A1	6/2006	Caimi et al.
10,291,066	B1	5/2019	Leabman	2006/0160517	A1	7/2006	Yoon
10,291,294	B2	5/2019	Leabman	2006/0199620	A1	9/2006	Greene et al.
10,298,024	B2	5/2019	Leabman	2006/0238365	A1	10/2006	Vecchione et al.
10,298,133	B2	5/2019	Leabman	2006/0266564	A1	11/2006	Perlman et al.
10,305,192	B1	5/2019	Rappaport	2006/0266917	A1	11/2006	Baldis et al.
10,305,315	B2	5/2019	Leabman et al.	2006/0281423	A1	12/2006	Caimi et al.
10,312,715	B2	6/2019	Leabman	2006/0284593	A1	12/2006	Nagy et al.
10,320,446	B2	6/2019	Hosseini	2007/0007821	A1	1/2007	Rossetti
10,333,332	B1	6/2019	Hosseini	2007/0019693	A1	1/2007	Graham
10,355,534	B2	7/2019	Johnston et al.	2007/0021140	A1	1/2007	Keyes, IV et al.
10,381,880	B2	8/2019	Leabman et al.	2007/0060185	A1	3/2007	Simon et al.
10,389,161	B2	8/2019	Hosseini et al.	2007/0090997	A1	4/2007	Brown et al.
10,396,588	B2	8/2019	Leabman	2007/0093269	A1	4/2007	Leabman et al.
10,396,604	B2	8/2019	Bell et al.	2007/0097653	A1	5/2007	Gilliland et al.
10,439,442	B2	10/2019	Hosseini et al.	2007/0103110	A1	5/2007	Sagoo
10,439,448	B2	10/2019	Bell et al.	2007/0106894	A1	5/2007	Zhang
10,447,093	B2	10/2019	Hosseini	2007/0109121	A1	5/2007	Cohen
10,476,312	B2	11/2019	Johnston et al.	2007/0139000	A1	6/2007	Kozuma
10,483,768	B2	11/2019	Bell et al.	2007/0149162	A1	6/2007	Greene et al.
10,490,346	B2	11/2019	Contopanagos	2007/0164868	A1	7/2007	Deavours et al.
10,491,029	B2	11/2019	Hosseini	2007/0173214	A1	7/2007	Mickle et al.
10,498,144	B2	12/2019	Leabman et al.	2007/0178857	A1	8/2007	Greene et al.
10,511,097	B2	12/2019	Kornaros et al.	2007/0178945	A1	8/2007	Cook et al.
				2007/0182367	A1	8/2007	Partovi
				2007/0191074	A1	8/2007	Harrist et al.
				2007/0191075	A1	8/2007	Greene et al.
				2007/0210960	A1	9/2007	Rofougaran et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0222681	A1	9/2007	Greene et al.	2010/0079011	A1	4/2010	Hyde et al.
2007/0228833	A1	10/2007	Stevens et al.	2010/0087227	A1	4/2010	Francois et al.
2007/0229261	A1	10/2007	Zimmerman et al.	2010/0090656	A1	4/2010	Shearer et al.
2007/0240297	A1	10/2007	Yang et al.	2010/0109443	A1	5/2010	Cook et al.
2007/0273486	A1	11/2007	Shiotsu	2010/0117926	A1	5/2010	DeJean, II
2007/0296639	A1	12/2007	Hook et al.	2010/0123618	A1	5/2010	Martin et al.
2007/0298846	A1	12/2007	Greene et al.	2010/0123624	A1	5/2010	Minear et al.
2008/0014897	A1	1/2008	Cook et al.	2010/0127660	A1	5/2010	Cook et al.
2008/0024376	A1	1/2008	Norris et al.	2010/0142418	A1	6/2010	Nishioka et al.
2008/0048917	A1	2/2008	Achour et al.	2010/0142509	A1	6/2010	Zhu et al.
2008/0067874	A1	3/2008	Tseng	2010/0148723	A1	6/2010	Cook et al.
2008/0074324	A1	3/2008	Puzella et al.	2010/0151808	A1	6/2010	Toncich et al.
2008/0089277	A1	4/2008	Alexander et al.	2010/0156741	A1	6/2010	Vazquez et al.
2008/0110263	A1	5/2008	Klessel et al.	2010/0164296	A1	7/2010	Kurs et al.
2008/0122297	A1	5/2008	Arai	2010/0164433	A1	7/2010	Janfalkner et al.
2008/0123383	A1	5/2008	Shionoiri	2010/0167664	A1	7/2010	Szini
2008/0169910	A1	7/2008	Greene et al.	2010/0171461	A1	7/2010	Baarma et al.
2008/0197802	A1	8/2008	Onishi	2010/0171676	A1	7/2010	Tani et al.
2008/0204350	A1	8/2008	Tam et al.	2010/0174629	A1	7/2010	Taylor et al.
2008/0210762	A1	9/2008	Osada et al.	2010/0176934	A1	7/2010	Chou et al.
2008/0211458	A1	9/2008	Lawther et al.	2010/0181961	A1	7/2010	Novak et al.
2008/0233890	A1	9/2008	Baker	2010/0181964	A1	7/2010	Huggins et al.
2008/0258993	A1	10/2008	Gummalla et al.	2010/0194206	A1	8/2010	Burdo et al.
2008/0266191	A1	10/2008	Hilgers	2010/0201189	A1	8/2010	Kirby et al.
2008/0278378	A1	11/2008	Chang et al.	2010/0201201	A1	8/2010	Mobarhan et al.
2008/0309452	A1	12/2008	Zeine	2010/0201314	A1	8/2010	Toncich et al.
2009/0002493	A1	1/2009	Kates	2010/0207572	A1	8/2010	Kirby et al.
2009/0010316	A1	1/2009	Rofougaran et al.	2010/0210233	A1	8/2010	Cook et al.
2009/0019183	A1	1/2009	Wu et al.	2010/0213895	A1	8/2010	Keating et al.
2009/0036065	A1	2/2009	Siu	2010/0214177	A1	8/2010	Parsche
2009/0039828	A1	2/2009	Jakubowski	2010/0222010	A1	9/2010	Ozaki et al.
2009/0047998	A1	2/2009	Alberth, Jr.	2010/0225270	A1	9/2010	Jacobs et al.
2009/0058361	A1	3/2009	John	2010/0227570	A1	9/2010	Hendin
2009/0058731	A1	3/2009	Geary et al.	2010/0244576	A1	9/2010	Hillan et al.
2009/0060012	A1	3/2009	Gresset et al.	2010/0253281	A1	10/2010	Li
2009/0067198	A1	3/2009	Graham et al.	2010/0256831	A1	10/2010	Abramo et al.
2009/0067208	A1	3/2009	Martin et al.	2010/0259447	A1	10/2010	Crouch
2009/0073066	A1	3/2009	Jordon et al.	2010/0264747	A1	10/2010	Hall et al.
2009/0096412	A1	4/2009	Huang	2010/0277003	A1	11/2010	Von Novak et al.
2009/0096413	A1	4/2009	Partovi	2010/0279606	A1	11/2010	Hillan et al.
2009/0102292	A1	4/2009	Cook et al.	2010/0289341	A1	11/2010	Ozaki et al.
2009/0102296	A1	4/2009	Greene et al.	2010/0295372	A1	11/2010	Hyde et al.
2009/0108679	A1	4/2009	Porwal	2010/0309088	A1	12/2010	Hyvonen et al.
2009/0122847	A1	5/2009	Nysen et al.	2010/0315045	A1	12/2010	Zeine
2009/0128262	A1	5/2009	Lee et al.	2010/0321086	A1	12/2010	See et al.
2009/0174604	A1	7/2009	Keskitalo	2010/0328044	A1	12/2010	Waffenschmidt et al.
2009/0200985	A1	8/2009	Zane et al.	2011/0009057	A1	1/2011	Saunamäki
2009/0206791	A1	8/2009	Jung	2011/0013198	A1	1/2011	Shirley
2009/0207092	A1	8/2009	Nysen et al.	2011/0018360	A1	1/2011	Baarma et al.
2009/0218884	A1	9/2009	Soar	2011/0028114	A1	2/2011	Kerselaers
2009/0218891	A1	9/2009	McCollough	2011/0032149	A1	2/2011	Leabman
2009/0243397	A1	10/2009	Cook et al.	2011/0032866	A1	2/2011	Leabman
2009/0256752	A1	10/2009	Akkermans et al.	2011/0034190	A1	2/2011	Leabman
2009/0264069	A1	10/2009	Yamasuge	2011/0034191	A1	2/2011	Leabman
2009/0271048	A1	10/2009	Wakamatsu	2011/0043047	A1	2/2011	Karalis et al.
2009/0281678	A1	11/2009	Wakamatsu	2011/0043163	A1	2/2011	Baarma et al.
2009/0284082	A1	11/2009	Mohammadian	2011/0043327	A1	2/2011	Baarma et al.
2009/0284220	A1	11/2009	Toncich et al.	2011/0050166	A1	3/2011	Cook et al.
2009/0284227	A1	11/2009	Mohammadian et al.	2011/0057607	A1	3/2011	Carobolante
2009/0286475	A1	11/2009	Toncich et al.	2011/0057853	A1	3/2011	Kim et al.
2009/0286476	A1	11/2009	Toncich et al.	2011/0062788	A1	3/2011	Chen et al.
2009/0291634	A1	11/2009	Saarisalo	2011/0074342	A1	3/2011	MacLaughlin
2009/0312046	A1	12/2009	Clevenger et al.	2011/0074349	A1	3/2011	Ghovanloo
2009/0322281	A1	12/2009	Kamijo et al.	2011/0109167	A1	5/2011	Park et al.
2010/0001683	A1	1/2010	Huang et al.	2011/0115303	A1	5/2011	Baarma et al.
2010/0007307	A1	1/2010	Baarma et al.	2011/0115432	A1	5/2011	El-Maleh
2010/0007569	A1	1/2010	Sim et al.	2011/0115605	A1	5/2011	Dimig et al.
2010/0019908	A1	1/2010	Cho et al.	2011/0121660	A1	5/2011	Azancot et al.
2010/0033021	A1	2/2010	Bennett	2011/0122018	A1	5/2011	Tarng et al.
2010/0034238	A1	2/2010	Bennett	2011/0122026	A1	5/2011	DeLaquil et al.
2010/0044123	A1	2/2010	Perlman et al.	2011/0127845	A1	6/2011	Walley et al.
2010/0060534	A1	3/2010	Oodachi	2011/0127952	A1	6/2011	Walley et al.
2010/0066631	A1	3/2010	Puzella et al.	2011/0133691	A1	6/2011	Hautanen
2010/0075607	A1	3/2010	Hosoya	2011/0151789	A1	6/2011	Viglione et al.
2010/0079005	A1	4/2010	Hyde et al.	2011/0154429	A1	6/2011	Stantchev
				2011/0156493	A1	6/2011	Bennett
				2011/0156494	A1	6/2011	Mashinsky
				2011/0156640	A1	6/2011	Moshfeghi
				2011/0175455	A1	7/2011	Hashiguchi

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0175461 A1	7/2011	Tinaphong	2012/0161544 A1	6/2012	Kashiwagi et al.
2011/0181120 A1	7/2011	Liu et al.	2012/0169276 A1	7/2012	Wang
2011/0182245 A1	7/2011	Malkamaki et al.	2012/0169278 A1	7/2012	Choi
2011/0184842 A1	7/2011	Melen	2012/0173418 A1	7/2012	Beardsmore et al.
2011/0194543 A1	8/2011	Zhao et al.	2012/0179004 A1	7/2012	Roesicke et al.
2011/0195722 A1	8/2011	Walter et al.	2012/0181973 A1	7/2012	Lyden
2011/0199046 A1	8/2011	Tsai et al.	2012/0182427 A1	7/2012	Marshall
2011/0215086 A1	9/2011	Yeh	2012/0187851 A1	7/2012	Huggins et al.
2011/0217923 A1	9/2011	Ma	2012/0188142 A1	7/2012	Shashi et al.
2011/0220634 A1	9/2011	Yeh	2012/0193999 A1	8/2012	Zeine
2011/0221389 A1	9/2011	Won et al.	2012/0200399 A1	8/2012	Chae
2011/0222272 A1	9/2011	Yeh	2012/0201153 A1	8/2012	Bharadia et al.
2011/0227725 A1	9/2011	Muirhead	2012/0201173 A1	8/2012	Jain et al.
2011/0243040 A1	10/2011	Khan et al.	2012/0206299 A1	8/2012	Valdes-Garcia
2011/0243050 A1	10/2011	Yanover	2012/0211214 A1	8/2012	Phan
2011/0244913 A1	10/2011	Kim et al.	2012/0212071 A1	8/2012	Miyabayashi et al.
2011/0248573 A1	10/2011	Kanno et al.	2012/0212072 A1	8/2012	Miyabayashi et al.
2011/0248575 A1	10/2011	Kim et al.	2012/0214462 A1	8/2012	Chu et al.
2011/0249678 A1	10/2011	Bonicatto	2012/0214536 A1	8/2012	Kim et al.
2011/0254377 A1	10/2011	Wildmer et al.	2012/0228392 A1	9/2012	Cameron et al.
2011/0254503 A1	10/2011	Widmer et al.	2012/0228956 A1	9/2012	Kamata
2011/0259953 A1	10/2011	Baarman et al.	2012/0231856 A1	9/2012	Lee et al.
2011/0273977 A1	11/2011	Shapira et al.	2012/0235636 A1	9/2012	Partovi
2011/0278941 A1	11/2011	Krishna et al.	2012/0242283 A1	9/2012	Kim et al.
2011/0279226 A1	11/2011	Chen et al.	2012/0248886 A1	10/2012	Kesler et al.
2011/0281535 A1	11/2011	Low et al.	2012/0248888 A1	10/2012	Kesler et al.
2011/0282415 A1	11/2011	Eckhoff et al.	2012/0248891 A1	10/2012	Drennen
2011/0285213 A1	11/2011	Kowalewski	2012/0249051 A1	10/2012	Son et al.
2011/0286374 A1	11/2011	Shin et al.	2012/0262002 A1	10/2012	Widmer et al.
2011/0291489 A1	12/2011	Tsai et al.	2012/0265272 A1	10/2012	Judkins
2011/0302078 A1	12/2011	Failing	2012/0267900 A1	10/2012	Huffman et al.
2011/0304216 A1	12/2011	Baarman	2012/0268238 A1	10/2012	Park et al.
2011/0304437 A1	12/2011	Beeler	2012/0270592 A1	10/2012	Ngai
2011/0304521 A1	12/2011	Ando et al.	2012/0274154 A1	11/2012	DeLuca
2012/0007441 A1	1/2012	John	2012/0280650 A1	11/2012	Kim et al.
2012/0013196 A1	1/2012	Kim et al.	2012/0286582 A1	11/2012	Kim et al.
2012/0013198 A1	1/2012	Uramoto et al.	2012/0292993 A1	11/2012	Mettler et al.
2012/0013296 A1	1/2012	Heydari et al.	2012/0293021 A1	11/2012	Teggatz et al.
2012/0019419 A1	1/2012	Prat et al.	2012/0293119 A1	11/2012	Park et al.
2012/0025622 A1	2/2012	Kim et al.	2012/0299389 A1	11/2012	Lee et al.
2012/0043887 A1	2/2012	Mesibov	2012/0299540 A1	11/2012	Perry
2012/0051109 A1	3/2012	Kim et al.	2012/0299541 A1	11/2012	Perry
2012/0051294 A1	3/2012	Guillouard	2012/0299542 A1	11/2012	Perry
2012/0056486 A1	3/2012	Endo et al.	2012/0300588 A1	11/2012	Perry
2012/0056741 A1	3/2012	Zhu et al.	2012/0300592 A1	11/2012	Perry
2012/0068906 A1	3/2012	Asher et al.	2012/0300593 A1	11/2012	Perry
2012/0074891 A1	3/2012	Anderson et al.	2012/0306284 A1	12/2012	Lee et al.
2012/0075072 A1	3/2012	Pappu	2012/0306433 A1	12/2012	Kim et al.
2012/0080944 A1	4/2012	Recker et al.	2012/0306572 A1	12/2012	Hietala et al.
2012/0080957 A1	4/2012	Cooper et al.	2012/0306705 A1	12/2012	Sakurai et al.
2012/0086281 A1	4/2012	Kanno	2012/0306707 A1	12/2012	Yang et al.
2012/0086284 A1	4/2012	Capanella et al.	2012/0306720 A1	12/2012	Tamai et al.
2012/0086615 A1	4/2012	Norair	2012/0307873 A1	12/2012	Kim et al.
2012/0095617 A1	4/2012	Martin et al.	2012/0309295 A1	12/2012	Maguire
2012/0098350 A1	4/2012	Campanella et al.	2012/0309308 A1	12/2012	Kim et al.
2012/0098485 A1	4/2012	Kang et al.	2012/0309332 A1	12/2012	Liao
2012/0099675 A1	4/2012	Kitamura et al.	2012/0313446 A1	12/2012	Park et al.
2012/0103562 A1	5/2012	Alexander	2012/0313449 A1	12/2012	Kurs
2012/0104849 A1	5/2012	Jackson	2012/0313835 A1	12/2012	Gebretnsae
2012/0105252 A1	5/2012	Wang	2012/0326660 A1	12/2012	Lu et al.
2012/0112532 A1	5/2012	Kesler et al.	2013/0002550 A1	1/2013	Zalewski
2012/0119914 A1	5/2012	Uchida	2013/0005252 A1	1/2013	Lee et al.
2012/0126743 A1	5/2012	Rivers, Jr	2013/0018439 A1	1/2013	Chow et al.
2012/0132647 A1	5/2012	Beverly et al.	2013/0024059 A1	1/2013	Miller et al.
2012/0133214 A1	5/2012	Yun et al.	2013/0026981 A1	1/2013	Van Der Lee
2012/0142291 A1	6/2012	Rath et al.	2013/0026982 A1	1/2013	Rothbaum
2012/0146426 A1	6/2012	Sabo	2013/0032589 A1	2/2013	Chung
2012/0146576 A1	6/2012	Partovi	2013/0033571 A1	2/2013	Steen
2012/0146577 A1	6/2012	Tanabe	2013/0038124 A1	2/2013	Newdoll et al.
2012/0147802 A1	6/2012	Ukita et al.	2013/0038402 A1	2/2013	Karalis et al.
2012/0149307 A1	6/2012	Terada et al.	2013/0043738 A1	2/2013	Park et al.
2012/0150670 A1	6/2012	Taylor et al.	2013/0044035 A1	2/2013	Zhuang
2012/0153894 A1	6/2012	Widmer et al.	2013/0049471 A1	2/2013	Oleynik
2012/0157019 A1	6/2012	Li	2013/0049475 A1	2/2013	Kim et al.
2012/0161531 A1	6/2012	Kim et al.	2013/0049484 A1	2/2013	Weissentern et al.
			2013/0057078 A1	3/2013	Lee
			2013/0057205 A1	3/2013	Lee et al.
			2013/0057210 A1	3/2013	Nergaard et al.
			2013/0057364 A1	3/2013	Kesler et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0058379	A1	3/2013	Kim et al.	2013/0285477	A1	10/2013	Lo et al.
2013/0062959	A1	3/2013	Lee et al.	2013/0285606	A1	10/2013	Ben-Shalom et al.
2013/0063082	A1	3/2013	Lee et al.	2013/0288600	A1	10/2013	Kuusilinnä et al.
2013/0063143	A1	3/2013	Adalsteinsson et al.	2013/0288617	A1	10/2013	Kim et al.
2013/0063266	A1	3/2013	Yunker et al.	2013/0293423	A1	11/2013	Moshfeghi
2013/0069444	A1	3/2013	Waffenschmidt et al.	2013/0300356	A1	11/2013	Yang
2013/0076308	A1	3/2013	Niskala et al.	2013/0307751	A1	11/2013	Yu-Juin et al.
2013/0077650	A1	3/2013	Traxler et al.	2013/0310020	A1	11/2013	Kazuhiro
2013/0078918	A1	3/2013	Crowley et al.	2013/0311798	A1	11/2013	Sultenfuss
2013/0082651	A1	4/2013	Park et al.	2013/0328417	A1	12/2013	Takeuchi
2013/0082653	A1	4/2013	Lee et al.	2013/0334883	A1	12/2013	Kim et al.
2013/0083774	A1	4/2013	Son et al.	2013/0339108	A1	12/2013	Ryder et al.
2013/0088082	A1	4/2013	Kang et al.	2013/0343208	A1	12/2013	Sexton et al.
2013/0088090	A1	4/2013	Wu	2013/0343251	A1	12/2013	Zhang
2013/0088192	A1	4/2013	Eaton	2013/0343585	A1	12/2013	Bennett et al.
2013/0088331	A1	4/2013	Cho	2014/0001608	A1	1/2014	McPartlin
2013/0093388	A1	4/2013	Partovi	2014/0001846	A1	1/2014	Mosebrook
2013/0099389	A1	4/2013	Hong et al.	2014/0001875	A1	1/2014	Nahidipour
2013/0099586	A1	4/2013	Kato	2014/0001876	A1	1/2014	Fujiwara et al.
2013/0106197	A1	5/2013	Bae et al.	2014/0006017	A1	1/2014	Sen
2013/0107023	A1	5/2013	Tanaka et al.	2014/0008993	A1	1/2014	Leabman
2013/0119777	A1	5/2013	Rees	2014/0009110	A1	1/2014	Lee
2013/0119778	A1	5/2013	Jung	2014/0011531	A1	1/2014	Burstrom et al.
2013/0119929	A1	5/2013	Partovi	2014/0015336	A1	1/2014	Weber et al.
2013/0120052	A1	5/2013	Siska	2014/0015344	A1	1/2014	Mohamadi
2013/0120205	A1	5/2013	Thomson et al.	2014/0021907	A1	1/2014	Yu et al.
2013/0120206	A1	5/2013	Biancotto et al.	2014/0021908	A1	1/2014	McCool
2013/0120217	A1	5/2013	Ueda et al.	2014/0024325	A1	1/2014	Iun et al.
2013/0130621	A1	5/2013	Kim et al.	2014/0035524	A1	2/2014	Zeine
2013/0132010	A1	5/2013	Winger et al.	2014/0035526	A1	2/2014	Tripathi et al.
2013/0134923	A1	5/2013	Smith	2014/0035786	A1	2/2014	Ley
2013/0137455	A1	5/2013	Xia	2014/0043248	A1	2/2014	Yeh
2013/0141037	A1	6/2013	Jenwatanavet et al.	2014/0049422	A1	2/2014	Von Novak et al.
2013/0148341	A1	6/2013	Williams	2014/0054971	A1	2/2014	Kissin
2013/0149975	A1	6/2013	Yu et al.	2014/0055098	A1	2/2014	Lee et al.
2013/0154387	A1	6/2013	Lee et al.	2014/0057618	A1	2/2014	Zirwas et al.
2013/0155748	A1	6/2013	Sundstrom	2014/0062395	A1	3/2014	Kwon et al.
2013/0157729	A1	6/2013	Tabe	2014/0082435	A1	3/2014	Kitgawa
2013/0162335	A1	6/2013	Kim et al.	2014/0086125	A1	3/2014	Polo et al.
2013/0169061	A1	7/2013	Miroshnichenko et al.	2014/0086592	A1	3/2014	Nakahara et al.
2013/0169219	A1	7/2013	Gray	2014/0091756	A1	4/2014	Ofstein et al.
2013/0169348	A1	7/2013	Shi	2014/0091968	A1	4/2014	Harel et al.
2013/0171939	A1	7/2013	Tian et al.	2014/0091974	A1	4/2014	Desclos et al.
2013/0175877	A1	7/2013	Abe et al.	2014/0103869	A1	4/2014	Radovic
2013/0178253	A1	7/2013	Karaoguz	2014/0104157	A1	4/2014	Burns
2013/0181881	A1	7/2013	Christie et al.	2014/0111147	A1	4/2014	Soar
2013/0187475	A1	7/2013	Vendik	2014/0111153	A1	4/2014	Kwon et al.
2013/0190031	A1	7/2013	Persson et al.	2014/0111156	A1	4/2014	Lee et al.
2013/0193769	A1	8/2013	Mehta et al.	2014/0113689	A1	4/2014	Lee
2013/0197320	A1	8/2013	Albert et al.	2014/0117946	A1	5/2014	Muller et al.
2013/0200064	A1	8/2013	Alexander	2014/0118140	A1	5/2014	Amis
2013/0207477	A1	8/2013	Nam et al.	2014/0128107	A1	5/2014	An
2013/0207604	A1	8/2013	Zeine	2014/0132210	A1	5/2014	Partovi
2013/0207879	A1	8/2013	Rada et al.	2014/0133279	A1	5/2014	Khuri-Yakub
2013/0210357	A1	8/2013	Qin et al.	2014/0139034	A1	5/2014	Sankar et al.
2013/0221757	A1	8/2013	Cho et al.	2014/0139039	A1	5/2014	Cook et al.
2013/0222201	A1	8/2013	Ma et al.	2014/0139180	A1	5/2014	Kim et al.
2013/0223538	A1	8/2013	Wang et al.	2014/0141838	A1	5/2014	Cai et al.
2013/0234530	A1	9/2013	Miyauchi	2014/0142876	A1	5/2014	John et al.
2013/0234536	A1	9/2013	Chemishkian et al.	2014/0143933	A1	5/2014	Low et al.
2013/0234658	A1	9/2013	Endo et al.	2014/0145879	A1	5/2014	Pan
2013/0241306	A1	9/2013	Aber et al.	2014/0145884	A1	5/2014	Dang et al.
2013/0241468	A1	9/2013	Moshfeghi	2014/0152117	A1	6/2014	Sanker
2013/0241474	A1	9/2013	Moshfeghi	2014/0152251	A1	6/2014	Kim et al.
2013/0249478	A1	9/2013	Hirano	2014/0159646	A1	6/2014	Sankar et al.
2013/0249479	A1	9/2013	Partovi	2014/0159651	A1	6/2014	Von Novak et al.
2013/0249682	A1	9/2013	Van Wiemeersch et al.	2014/0159652	A1	6/2014	Hall et al.
2013/0250102	A1	9/2013	Scanlon et al.	2014/0159662	A1	6/2014	Furui
2013/0254578	A1	9/2013	Huang et al.	2014/0159667	A1	6/2014	Kim et al.
2013/0264997	A1	10/2013	Lee et al.	2014/0169385	A1	6/2014	Hadani et al.
2013/0268782	A1	10/2013	Tam et al.	2014/0175893	A1	6/2014	Sengupta et al.
2013/0270923	A1	10/2013	Cook et al.	2014/0176054	A1	6/2014	Porat et al.
2013/0278076	A1	10/2013	Proud	2014/0176061	A1	6/2014	Cheatham, III et al.
2013/0278209	A1	10/2013	Von Novak, III et al.	2014/0176082	A1	6/2014	Visser
2013/0285464	A1	10/2013	Miwa	2014/0177399	A1	6/2014	Teng et al.
				2014/0183964	A1	7/2014	Walley
				2014/0184148	A1	7/2014	Van Der Lee et al.
				2014/0184155	A1	7/2014	Cha
				2014/0184163	A1	7/2014	Das et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0184170 A1	7/2014	Jeong	2015/0051750 A1	2/2015	Kurs et al.
2014/0191568 A1	7/2014	Partovi	2015/0061404 A1	3/2015	Lamenza et al.
2014/0191818 A1	7/2014	Waffenschmidt et al.	2015/0076917 A1	3/2015	Leabman et al.
2014/0194092 A1	7/2014	Wanstedt et al.	2015/0076927 A1	3/2015	Leabman et al.
2014/0194095 A1	7/2014	Wynne et al.	2015/0077036 A1	3/2015	Leabman et al.
2014/0197691 A1	7/2014	Wang	2015/0077037 A1	3/2015	Leabman et al.
2014/0203629 A1	7/2014	Hoffman et al.	2015/0091520 A1	4/2015	Blum et al.
2014/0206384 A1	7/2014	Kim et al.	2015/0091706 A1	4/2015	Chemishkian et al.
2014/0210281 A1	7/2014	Ito et al.	2015/0097442 A1	4/2015	Muurinen
2014/0217955 A1	8/2014	Lin	2015/0097663 A1	4/2015	Sloo et al.
2014/0217967 A1	8/2014	Zeine et al.	2015/0102764 A1	4/2015	Leabman et al.
2014/0225452 A1	8/2014	Kozaki et al.	2015/0102769 A1	4/2015	Leabman et al.
2014/0225805 A1	8/2014	Pan et al.	2015/0102942 A1	4/2015	Houser et al.
2014/0232320 A1	8/2014	Ento July et al.	2015/0102973 A1	4/2015	Hand et al.
2014/0232610 A1	8/2014	Shigemoto et al.	2015/0108848 A1	4/2015	Joehren
2014/0239733 A1	8/2014	Mach et al.	2015/0109181 A1	4/2015	Hyde et al.
2014/0241231 A1	8/2014	Zeine	2015/0115877 A1	4/2015	Arai et al.
2014/0245036 A1	8/2014	Oishi	2015/0115878 A1	4/2015	Park
2014/0246416 A1	9/2014	White	2015/0116153 A1	4/2015	Chen et al.
2014/0247152 A1	9/2014	Proud	2015/0128733 A1	5/2015	Taylor et al.
2014/0252813 A1	9/2014	Lee et al.	2015/0130285 A1	5/2015	Leabman et al.
2014/0252866 A1	9/2014	Walsh et al.	2015/0130293 A1	5/2015	Hajimiri et al.
2014/0265725 A1	9/2014	Angle et al.	2015/0137612 A1	5/2015	Yamakawa et al.
2014/0265727 A1	9/2014	Berte	2015/0148664 A1	5/2015	Stolka et al.
2014/0265943 A1	9/2014	Angle et al.	2015/0155737 A1	6/2015	Mayo
2014/0266025 A1	9/2014	Jakubowski	2015/0155738 A1	6/2015	Leabman et al.
2014/0266946 A1	9/2014	Bily et al.	2015/0162662 A1	6/2015	Chen et al.
2014/0273819 A1	9/2014	Nadakuduti et al.	2015/0162751 A1	6/2015	Leabman et al.
2014/0273892 A1	9/2014	Nourbakhsh	2015/0162779 A1	6/2015	Lee et al.
2014/0281655 A1	9/2014	Angle et al.	2015/0171512 A1	6/2015	Chen et al.
2014/0292090 A1	10/2014	Cordeiro et al.	2015/0171513 A1	6/2015	Chen et al.
2014/0292451 A1	10/2014	Zimmerman	2015/0171656 A1	6/2015	Leabman et al.
2014/0300452 A1	10/2014	Rofe et al.	2015/0171658 A1	6/2015	Manova-Elssibony et al.
2014/0312706 A1	10/2014	Fiorello et al.	2015/0171931 A1	6/2015	Won et al.
2014/0325218 A1	10/2014	Shimizu et al.	2015/0177326 A1	6/2015	Chakraborty et al.
2014/0327320 A1	11/2014	Muhs et al.	2015/0180133 A1	6/2015	Hunt
2014/0327390 A1	11/2014	Park et al.	2015/0180249 A1	6/2015	Jeon et al.
2014/0333142 A1	11/2014	Desrosiers	2015/0180284 A1	6/2015	Kang et al.
2014/0346860 A1	11/2014	Aubry et al.	2015/0181117 A1	6/2015	Park et al.
2014/0354063 A1	12/2014	Leabman et al.	2015/0187491 A1	7/2015	Yanagawa
2014/0354221 A1	12/2014	Leabman et al.	2015/0188352 A1	7/2015	Peek et al.
2014/0355718 A1	12/2014	Guan et al.	2015/0199665 A1	7/2015	Chu
2014/0368048 A1	12/2014	Leabman et al.	2015/0201385 A1	7/2015	Mercer et al.
2014/0368161 A1	12/2014	Leabman et al.	2015/0207333 A1	7/2015	Baarman et al.
2014/0368405 A1	12/2014	Ek et al.	2015/0207542 A1	7/2015	Zeine
2014/0375139 A1	12/2014	Tsukamoto	2015/0222126 A1	8/2015	Leabman et al.
2014/0375253 A1	12/2014	Leabman et al.	2015/0233987 A1	8/2015	Von Novak, III et al.
2014/0375258 A1	12/2014	Arkhipenkov	2015/0234144 A1	8/2015	Cameron et al.
2014/0375261 A1	12/2014	Manova-Elssibony et al.	2015/0236520 A1	8/2015	Baarman
2015/0001949 A1	1/2015	Leabman et al.	2015/0236877 A1	8/2015	Peng et al.
2015/0002086 A1	1/2015	Matos et al.	2015/0244070 A1	8/2015	Cheng et al.
2015/0003207 A1	1/2015	Lee et al.	2015/0244080 A1	8/2015	Gregoire
2015/0008980 A1	1/2015	Kim et al.	2015/0244187 A1	8/2015	Horie
2015/0011160 A1	1/2015	Jurgovan et al.	2015/0244201 A1	8/2015	Chu
2015/0015180 A1	1/2015	Miller et al.	2015/0244341 A1	8/2015	Ritter et al.
2015/0015182 A1	1/2015	Brandtman et al.	2015/0249484 A1	9/2015	Mach et al.
2015/0015192 A1	1/2015	Leabman et al.	2015/0255989 A1	9/2015	Walley et al.
2015/0021990 A1	1/2015	Myer et al.	2015/0256097 A1	9/2015	Gudan et al.
2015/0022008 A1	1/2015	Leabman et al.	2015/0260835 A1	9/2015	Widmer et al.
2015/0022010 A1	1/2015	Leabman et al.	2015/0262465 A1	9/2015	Pritchett
2015/0022194 A1	1/2015	Almalki et al.	2015/0263534 A1	9/2015	Lee et al.
2015/0023204 A1	1/2015	Wik et al.	2015/0263548 A1	9/2015	Cooper
2015/0028688 A1	1/2015	Masaoka	2015/0270618 A1	9/2015	Zhu et al.
2015/0028694 A1	1/2015	Leabman et al.	2015/0270622 A1	9/2015	Takasaki et al.
2015/0028697 A1	1/2015	Makino et al.	2015/0270741 A1	9/2015	Leabman et al.
2015/0028875 A1	1/2015	Irie et al.	2015/0278558 A1	10/2015	Priev et al.
2015/0035378 A1	2/2015	Calhoun et al.	2015/0280429 A1	10/2015	Makita et al.
2015/0035709 A1	2/2015	Lim	2015/0280484 A1	10/2015	Radziemski et al.
2015/0035715 A1	2/2015	Kim et al.	2015/0288074 A1	10/2015	Harper et al.
2015/0039482 A1	2/2015	Fujinaga	2015/0288214 A1	10/2015	Borngaber
2015/0041459 A1	2/2015	Leabman et al.	2015/0288438 A1	10/2015	Maltsev et al.
2015/0042265 A1	2/2015	Leabman et al.	2015/0311585 A1	10/2015	Church et al.
2015/0042287 A1	2/2015	Liu et al.	2015/0312721 A1	10/2015	Singh
2015/0044977 A1	2/2015	Ramasamy et al.	2015/0318729 A1	11/2015	Leabman
2015/0046526 A1	2/2015	Bush et al.	2015/0326024 A1	11/2015	Bell et al.
			2015/0326070 A1	11/2015	Petras et al.
			2015/0326072 A1	11/2015	Petras et al.
			2015/0326143 A1	11/2015	Petras et al.
			2015/0327085 A1	11/2015	Hadani

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0333528	A1	11/2015	Leabman	2017/0012448	A1	1/2017	Miller et al.
2015/0333573	A1	11/2015	Leabman	2017/0025887	A1	1/2017	Hyun et al.
2015/0333800	A1	11/2015	Perry et al.	2017/0025903	A1	1/2017	Song et al.
2015/0339497	A1	11/2015	Kurian	2017/0026087	A1	1/2017	Tanabe
2015/0340759	A1	11/2015	Bridgelall et al.	2017/0033611	A1	2/2017	Shin et al.
2015/0340903	A1	11/2015	Bell et al.	2017/0040700	A1	2/2017	Leung
2015/0341087	A1	11/2015	Moore et al.	2017/0043675	A1	2/2017	Jones et al.
2015/0358222	A1	12/2015	Berger et al.	2017/0047784	A1	2/2017	Jung et al.
2015/0365137	A1	12/2015	Miller et al.	2017/0063168	A1	3/2017	Uchida
2015/0365138	A1	12/2015	Miller et al.	2017/0077733	A1	3/2017	Jeong et al.
2016/0005068	A1	1/2016	Im et al.	2017/0077765	A1	3/2017	Bell et al.
2016/0012695	A1	1/2016	Bell et al.	2017/0077979	A1	3/2017	Papa et al.
2016/0013560	A1	1/2016	Daniels	2017/0077995	A1	3/2017	Leabman
2016/0013661	A1	1/2016	Kurs et al.	2017/0085120	A1	3/2017	Leabman et al.
2016/0013677	A1	1/2016	Bell et al.	2017/0085437	A1	3/2017	Condeixa et al.
2016/0013855	A1	1/2016	Campos	2017/0092115	A1	3/2017	Sloo et al.
2016/0020636	A1	1/2016	Khlat	2017/0110886	A1	4/2017	Reynolds et al.
2016/0028403	A1	1/2016	McCaughan et al.	2017/0110910	A1	4/2017	Zeine et al.
2016/0033254	A1	2/2016	Zeine et al.	2017/0117756	A1	4/2017	Muratov
2016/0042206	A1	2/2016	Pesavento et al.	2017/0127196	A1	5/2017	Blum et al.
2016/0043571	A1	2/2016	Kesler et al.	2017/0134686	A9	5/2017	Leabman
2016/0043572	A1	2/2016	Cooper et al.	2017/0141582	A1	5/2017	Adolf et al.
2016/0054440	A1	2/2016	Younis	2017/0141583	A1	5/2017	Adolf et al.
2016/0056635	A1	2/2016	Bell	2017/0141622	A1	5/2017	Meichle
2016/0056640	A1	2/2016	Mao	2017/0163076	A1	6/2017	Park et al.
2016/0065005	A1	3/2016	Won et al.	2017/0168595	A1	6/2017	Sakaguchi et al.
2016/0079799	A1	3/2016	Khlat	2017/0179763	A9	6/2017	Leabman
2016/0087483	A1	3/2016	Hietala et al.	2017/0179771	A1	6/2017	Leabman
2016/0087486	A1	3/2016	Pogorelik et al.	2017/0187244	A1	6/2017	Su
2016/0094074	A1	3/2016	Alves et al.	2017/0187422	A1	6/2017	Hosseini
2016/0094091	A1	3/2016	Shin et al.	2017/0212210	A1	7/2017	Chen et al.
2016/0094092	A1	3/2016	Davlatov et al.	2017/0214422	A1	7/2017	Na et al.
2016/0099601	A1	4/2016	Leabman et al.	2017/0274787	A1	9/2017	Salter et al.
2016/0099611	A1	4/2016	Leabman et al.	2017/0285207	A1	10/2017	Shao et al.
2016/0099612	A1	4/2016	Leabman et al.	2017/0338695	A1	11/2017	Port
2016/0099614	A1	4/2016	Leabman et al.	2018/0006611	A1	1/2018	de Jong et al.
2016/0099755	A1	4/2016	Leabman et al.	2018/0012082	A1	1/2018	Satazoda et al.
2016/0099757	A1	4/2016	Leabman et al.	2018/0040929	A1	2/2018	Chappelle
2016/0112787	A1	4/2016	Rich	2018/0048178	A1	2/2018	Leabman
2016/0126749	A1	5/2016	Shichino et al.	2018/0090992	A1	3/2018	Shrivastava et al.
2016/0126752	A1	5/2016	Vuori et al.	2018/0166924	A1	6/2018	Hosseini
2016/0126776	A1	5/2016	Kim et al.	2018/0166925	A1	6/2018	Hosseini
2016/0141908	A1	5/2016	Jakl et al.	2018/0205265	A1	7/2018	Park et al.
2016/0164563	A1	6/2016	Khawand et al.	2018/0219428	A1	8/2018	Bae
2016/0174162	A1	6/2016	Nadakuduti et al.	2018/0226840	A1	8/2018	Leabman
2016/0174293	A1	6/2016	Mow et al.	2018/0227018	A1	8/2018	Moshfeghi
2016/0181849	A1	6/2016	Govindaraj	2018/0241255	A1	8/2018	Leabman
2016/0181867	A1	6/2016	Daniel et al.	2018/0248409	A1	8/2018	Johnston
2016/0181873	A1	6/2016	Mitcheson et al.	2018/0262050	A1	9/2018	Yankowitz
2016/0182127	A1	6/2016	Karandikar et al.	2018/0262060	A1	9/2018	Johnston
2016/0197522	A1	7/2016	Zeine et al.	2018/0301934	A1	10/2018	Prabhala et al.
2016/0202343	A1	7/2016	Okutsu	2018/0309314	A1	10/2018	White, II et al.
2016/0204642	A1	7/2016	Oh	2018/0331581	A1	11/2018	Hosseini
2016/0204643	A1	7/2016	Manova-Elsibony	2018/0343040	A1	11/2018	Luzinski et al.
2016/0218545	A1	7/2016	Schroeder et al.	2018/0368065	A1	12/2018	Sarkas et al.
2016/0233582	A1	8/2016	Piskun	2018/0375368	A1	12/2018	Leabman et al.
2016/0238365	A1	8/2016	Wixey et al.	2018/0376235	A1	12/2018	Leabman
2016/0240908	A1	8/2016	Strong	2019/0052979	A1	2/2019	Chen et al.
2016/0248276	A1	8/2016	Hong et al.	2019/0074722	A1	3/2019	Shahsavari et al.
2016/0294225	A1	10/2016	Blum et al.	2019/0074728	A1	3/2019	Leabman
2016/0299210	A1	10/2016	Zeine	2019/0074730	A1	3/2019	Shahsavari et al.
2016/0301240	A1	10/2016	Zeine	2019/0074862	A1	3/2019	Wang et al.
2016/0322868	A1	11/2016	Akuzawa et al.	2019/0089396	A1	3/2019	Kim et al.
2016/0323000	A1	11/2016	Liu et al.	2019/0130215	A1	5/2019	Kaestle et al.
2016/0325680	A1	11/2016	Curtis et al.	2019/0131827	A1	5/2019	Johnston
2016/0336804	A1	11/2016	Son et al.	2019/0207570	A1	7/2019	Govindaraj
2016/0339258	A1	11/2016	Perryman et al.	2019/0245389	A1	8/2019	Johnston et al.
2016/0344098	A1	11/2016	Ming	2019/0288567	A1	9/2019	Kabiri et al.
2016/0359367	A1	12/2016	Rothschild	2019/0296586	A1	9/2019	Moshfeghi
2016/0380464	A1	12/2016	Chin et al.	2019/0326782	A1	10/2019	Graham et al.
2016/0380466	A1	12/2016	Yang et al.	2019/0363588	A1	11/2019	Daetwyler et al.
2017/0005481	A1	1/2017	Von Novak, III	2019/0372384	A1	12/2019	Hosseini et al.
2017/0005516	A9	1/2017	Leabman et al.	2019/0386522	A1	12/2019	Park et al.
2017/0005524	A1	1/2017	Akuzawa et al.	2019/0393729	A1	12/2019	Contopanagos et al.
2017/0005530	A1	1/2017	Zeine et al.	2019/0393928	A1	12/2019	Leabman
				2020/0006988	A1	1/2020	Leabman
				2020/0021128	A1	1/2020	Bell et al.
				2020/0052408	A1	2/2020	Rappaport
				2020/0091608	A1	3/2020	Alpman et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2020/0112204 A1 4/2020 Hosseini et al.
 2020/0119592 A1 4/2020 Hosseini
 2020/0144846 A1 5/2020 Shin
 2020/0153117 A1 5/2020 Papio-Toda et al.
 2020/0176890 A1 6/2020 Rappaport et al.
 2020/0202145 A1 6/2020 Mao et al.
 2020/0203837 A1 6/2020 Kornaros et al.
 2020/0225673 A1 7/2020 Ebrahimi Afrouzi et al.
 2020/0235614 A1 7/2020 Swan et al.
 2020/0244104 A1 7/2020 Katajamaki et al.
 2020/0244111 A1 7/2020 Johnston et al.
 2020/0252141 A1 8/2020 Sarajedini
 2020/0274397 A1 8/2020 Hwang et al.
 2021/0091606 A1 3/2021 Johnston et al.
 2021/0098882 A1 4/2021 Paulotto et al.
 2021/0226481 A1 7/2021 Chan et al.
 2021/0296936 A1 9/2021 Hosseini
 2022/0271572 A1 8/2022 Johnston et al.
 2023/0057092 A1 2/2023 Hoss
 2023/0378817 A1 11/2023 Johnston et al.
 2023/0420996 A1 12/2023 Johnston et al.

FOREIGN PATENT DOCUMENTS

CN 102089952 A 6/2011
 CN 102227884 A 10/2011
 CN 102292896 A 12/2011
 CN 102860037 A 1/2013
 CN 103094993 A 5/2013
 CN 103151848 A 6/2013
 CN 103348563 A 10/2013
 CN 203826555 U 9/2014
 CN 104090265 A 10/2014
 CN 104167773 A 11/2014
 CN 104347915 A 2/2015
 CN 104617680 A 5/2015
 CN 105207373 A 12/2015
 CN 105637727 A 6/2016
 CN 105765821 A 7/2016
 CN 105993105 A 10/2016
 CN 106329116 A 1/2017
 CN 106464027 A 2/2017
 CN 103380561 B 9/2017
 DE 20016655 U1 2/2002
 DE 102013216953 A1 2/2015
 EP 1028482 A2 8/2000
 EP 1081506 A1 3/2001
 EP 2346136 A1 7/2011
 EP 2397973 A1 2/2012
 EP 2545635 A2 1/2013
 EP 2747195 A1 6/2014
 EP 3067983 A1 9/2016
 EP 3118970 A1 1/2017
 EP 3145052 A1 3/2017
 GB 2404497 A 2/2005
 GB 2556620 A 6/2018
 JP 2000323916 A 11/2000
 JP 2002319816 A 10/2002
 JP 2006157586 A 6/2006
 JP 2006178910 A 7/2006
 JP 2007043432 A 2/2007
 JP 2008167017 A 7/2008
 JP 2009525715 A 7/2009
 JP 2009201328 A 9/2009
 JP 2010104098 A 5/2010
 JP 2012016171 A 1/2012
 JP 2012095226 A 5/2012
 JP 2012157167 A 8/2012
 JP 2012170194 A 9/2012
 JP 2013500693 A 1/2013
 JP 2013027074 A 2/2013
 JP 2013511908 A 4/2013
 JP 2013099249 A 5/2013
 JP 2013162624 A 8/2013
 JP 2013243908 A 12/2013

JP 2014075927 A 4/2014
 JP 2014112063 A 6/2014
 JP 2014176131 A 9/2014
 JP 2015027345 A 2/2015
 JP 2015128349 A 7/2015
 JP 2015128370 A 7/2015
 KR 20060061776 A 6/2006
 KR 20070044302 A 4/2007
 KR 100755144 B1 9/2007
 KR 20110132059 A 12/2011
 KR 20110135540 A1 12/2011
 KR 20120009843 A 2/2012
 KR 20120108759 A 10/2012
 KR 20130026977 A 3/2013
 KR 20140023409 A 2/2014
 KR 20140023410 A 3/2014
 KR 20140025410 A 3/2014
 KR 20140085200 A 7/2014
 KR 20140148270 A 12/2014
 KR 20150077678 A 7/2015
 KR 20160018826 A 2/2016
 KR 20190009237 A 1/2019
 RU 2658332 C1 6/2018
 WO WO 199508125 A1 3/1995
 WO WO 199831070 A1 7/1998
 WO WO 199952173 A1 10/1999
 WO WO 2000111716 A1 2/2001
 WO WO 2003091943 A1 11/2003
 WO WO 2004077550 A1 9/2004
 WO WO 2006122783 A2 11/2006
 WO WO 2007070571 A2 6/2007
 WO WO 2008024993 A2 2/2008
 WO WO 2008156571 A2 12/2008
 WO WO 2010022181 A1 2/2010
 WO WO 2010039246 A1 4/2010
 WO WO 2010138994 A1 12/2010
 WO WO 2011112022 A2 9/2011
 WO WO 2012177283 A1 12/2012
 WO WO 2013031988 A1 3/2013
 WO WO 2013035190 A1 3/2013
 WO WO 2013038074 A2 3/2013
 WO WO 2013042399 A1 3/2013
 WO WO 2013052950 A1 4/2013
 WO WO 2013105920 A2 7/2013
 WO WO 2013175596 A1 11/2013
 WO WO 2014068992 A1 5/2014
 WO WO 2014075103 A1 5/2014
 WO WO 2014113093 A1 7/2014
 WO WO 2014132258 A1 9/2014
 WO WO 2014134996 A1 9/2014
 WO WO 2014171348 A1 10/2014
 WO WO 2014182788 A2 11/2014
 WO WO 2014182788 A3 11/2014
 WO WO 2014197472 A1 12/2014
 WO WO 2014209587 A1 12/2014
 WO WO 2015038773 A1 3/2015
 WO WO 2015097809 A1 7/2015
 WO WO 2015130902 A1 9/2015
 WO WO 2015161323 A1 10/2015
 WO WO 2016024869 A1 2/2016
 WO WO 2016048512 A1 3/2016
 WO WO 2016088261 A1 6/2016
 WO WO 2016187357 A1 11/2016
 WO WO 2015177859 A1 4/2017
 WO WO 2017056260 A1 10/2017
 WO WO 2018203176 A1 11/2018
 WO WO 2019012372 A1 1/2019

OTHER PUBLICATIONS

Energous Corp., IPRP, PCT/US2014/040705, Dec. 8, 2015, 6 pgs.
 Energous Corp., IPRP, PCT/US2014/045119, Jan. 12, 2016, 9 pgs.
 Energous Corp., IPRP, PCT/US2014/048002, Feb. 12, 2015, 8 pgs.
 Energous Corp., IPRP, PCT/US2014/049669, Feb. 9, 2016, 8 pgs.
 Energous Corp., IPRP, PCT/US2014/059317, Apr. 12, 2016, 10 pgs.
 Energous Corp., IPRP, PCT/US2014/059340, Apr. 12, 2016, 11 pgs.
 Energous Corp., IPRP, PCT/US2014/059871, Apr. 12, 2016, 9 pgs.
 Energous Corp., IPRP, PCT/US2014/068282, Jun. 7, 2016, 10 pgs.

(56)

References Cited

OTHER PUBLICATIONS

Energous Corp., IPRP, PCT/US2014/068568, Jun. 14, 2016, 8 pgs.
Energous Corp., IPRP, PCT/US2015/067242, Jun. 27, 2017, 7 pgs.
Energous Corp., IPRP, PCT/US2015/067243, Jun. 27, 2017, 7 pgs.
Energous Corp., IPRP, PCT/US2015/067245, Jun. 27, 2017, 7 pgs.
Energous Corp., IPRP, PCT/US2015/067246, Jun. 27, 2017, 9 pgs.
Energous Corp., IPRP, PCT/US2015/067249, Jun. 27, 2017, 7 pgs.
Energous Corp., IPRP, PCT/US2015/067250, Mar. 30, 2016, 10 pgs.
Energous Corp., IPRP, PCT/US2015/067271, Jul. 4, 2017, 5 pgs.
Energous Corp., IPRP, PCT/US2015/067275, Jul. 4, 2017, 7 pgs.
Energous Corp., IPRP, PCT/US2015/067282, Jul. 4, 2017, 6 pgs.
Energous Corp., IPRP, PCT/US2015/067287, Jul. 4, 2017, 6 pgs.
Energous Corp., IPRP, PCT/US2015/067291, Jul. 4, 2017, 4 pgs.
Energous Corp., IPRP, PCT/US2015/067294, Jul. 4, 2017, 6 pgs.
Energous Corp., IPRP, PCT/US2015/067325, Jul. 4, 2017, 8 pgs.
Energous Corp., IPRP, PCT/US2015/067334, Jul. 4, 2017, 5 pgs.
Energous Corp., IPRP, PCT/US2016/068495, Jun. 26, 2018, 7 pgs.
Energous Corp., IPRP, PCT/US2016/068498, Jun. 28, 2018, 6 pgs.
Energous Corp., IPRP, PCT/US2016/068987, Jul. 3, 2018, 7 pgs.
Energous Corp., IPRP, PCT/US2016/068993, Jul. 3, 2018, 10 pgs.
Energous Corp., IPRP, PCT/US2017/046800, Feb. 12, 2019, 10 pgs.
Energous Corp., IPRP, PCT/US2017/065886, Jun. 18, 2019, 10 pgs.
Energous Corp., IPRP, PCT/US2018/012806, Jul. 9, 2019, 6 pgs.
Energous Corp., IPRP, PCT/US2018/025465, Oct. 1, 2019, 8 pgs.
Energous Corp., IPRP, PCT/US2018/031768, Nov. 12, 2019, 8 pgs.
Energous Corp., IPRP, PCT/US2018/051082, Mar. 17, 2020, 9 pgs.
Energous Corp., IPRP, PCT/US2018/058178, May 5, 2020, 7 pgs.
Energous Corp., IPRP, PCT/US2018/064289, Dec. 29, 2020, 8 pgs.
Energous Corp., IPRP, PCT/US2019/015820, Aug. 4, 2020, 7 pgs.
Energous Corp., IPRP, PCT/US2019/021817, Sep. 15, 2020, 7 pgs.
Energous Corp., IPRP, PCT/US2020/051692, Mar. 15, 2022, 6 pgs.
Energous Corp., IPRP, PCT/US2020/051694, Mar. 15, 2022, 7 pgs.
Energous Corp., ISRWO, PCT/US2014/037072, Sep. 12, 2014, 8 pgs.
Energous Corp., ISRWO, PCT/US2014/037109, Apr. 8, 2016, 12 pgs.
Energous Corp., ISRWO, PCT/US2014/037170, Sep. 15, 2014, 11 pgs.
Energous Corp., ISRWO, PCT/US2014/040648, Oct. 10, 2014, 11 pgs.
Energous Corp., ISRWO, PCT/US2014/040697, Oct. 1, 2014, 12 pgs.
Energous Corp., ISRWO, PCT/US2014/040705, Sep. 23, 2014, 8 pgs.
Energous Corp., ISRWO, PCT/US2014/041323, Oct. 1, 2014, 10 pgs.
Energous Corp., ISRWO, PCT/US2014/041342, Jan. 27, 2015, 10 pgs.
Energous Corp., ISRWO, PCT/US2014/041534, Oct. 13, 2014, 10 pgs.
Energous Corp., ISRWO, PCT/US2014/041546, Oct. 16, 2014, 12 pgs.
Energous Corp., ISRWO, PCT/US2014/041558, Oct. 10, 2014, 8 pgs.
Energous Corp., ISRWO, PCT/US2014/044810, Oct. 21, 2014, 12 pgs.
Energous Corp., ISRWO, PCT/US2014/045102, Oct. 28, 2014, 14 pgs.
Energous Corp., ISRWO, PCT/US2014/045119, Oct. 13, 2014, 11 pgs.
Energous Corp., ISRWO, PCT/US2014/045237, Oct. 13, 2014, 16 pgs.
Energous Corp., ISRWO, PCT/US2014/046961, Nov. 24, 2014, 16 pgs.
Energous Corp., ISRWO, PCT/US2014/047963, Nov. 7, 2014, 13 pgs.
Energous Corp., ISRWO, PCT/US2014/048002, Nov. 13, 2014, 11 pgs.

Energous Corp., ISRWO, PCT/US2014/049666, Nov. 10, 2014, 7 pgs.
Energous Corp., ISRWO, PCT/US2014/049669, Nov. 13, 2014, 10 pgs.
Energous Corp., ISRWO, PCT/US2014/049673, Nov. 18, 2014, 10 pgs.
Energous Corp., ISRWO, PCT/US2014/054891, Dec. 18, 2014, 12 pgs.
Energous Corp., ISRWO, PCT/US2014/054897, Feb. 17, 2015, 10 pgs.
Energous Corp., ISRWO, PCT/US2014/054953, Dec. 4, 2014, 7 pgs.
Energous Corp., ISRWO, PCT/US2014/055195, Dec. 22, 2014, 11 pgs.
Energous Corp., ISRWO, PCT/US2014/059317, Feb. 24, 2015, 13 pgs.
Energous Corp., ISRWO, PCT/US2014/059340, Jan. 15, 2015, 13 pgs.
Energous Corp., ISRWO, PCT/US2014/059871, Jan. 23, 2015, 12 pgs.
Energous Corp., ISRWO, PCT/US2014/062661, Jan. 27, 2015, 12 pgs.
Energous Corp., ISRWO, PCT/US2014/062672, Jan. 26, 2015, 11 pgs.
Energous Corp., ISRWO, PCT/US2014/062682, Feb. 12, 2015, 10 pgs.
Energous Corp., ISRWO, PCT/US2014/068282, Mar. 19, 2015, 13 pgs.
Energous Corp., ISRWO, PCT/US2014/068568, Mar. 20, 2015, 10 pgs.
Energous Corp., ISRWO, PCT/US2014/068586, Mar. 20, 2015, 11 pgs.
Energous Corp., ISRWO, PCT/US2015/067242, Mar. 16, 2016, 9 pgs.
Energous Corp., ISRWO, PCT/US2015/067243, Mar. 10, 2016, 11 pgs.
Energous Corp., ISRWO, PCT/US2015/067245, Mar. 17, 2016, 8 pgs.
Energous Corp., ISRWO, PCT/US2015/067246, May 11, 2016, 18 pgs.
Energous Corp., ISRWO, PCT/US2015/067249, Mar. 29, 2016, 8 pgs.
Energous Corp., ISRWO, PCT/US2015/067250, Mar. 30, 2016, 11 pgs.
Energous Corp., ISRWO, PCT/US2015/067271, Mar. 11, 2016, 6 pgs.
Energous Corp., ISRWO, PCT/US2015/067275, Mar. 3, 2016, 8 pgs.
Energous Corp., ISRWO, PCT/US2015/067279, Mar. 11, 2015, 13 pgs.
Energous Corp., ISRWO, PCT/US2015/067282, Jul. 5, 2016, 7 pgs.
Energous Corp., ISRWO, PCT/US2015/067287, Feb. 2, 2016, 8 pgs.
Energous Corp., ISRWO, PCT/US2015/067291, Mar. 4, 2016, 10 pgs.
Energous Corp., ISRWO, PCT/US2015/067294, Mar. 29, 2016, 7 pgs.
Energous Corp., ISRWO, PCT/US2015/067325, Mar. 10, 2016, 9 pgs.
Energous Corp., ISRWO, PCT/US2015/067334, Mar. 3, 2016, 6 pgs.
Energous Corp., ISRWO, PCT/US2016/068495, Mar. 30, 2017, 9 pgs.
Energous Corp., ISRWO, PCT/US2016/068498, May 17, 2017, 8 pgs.
Energous Corp., ISRWO, PCT/US2016/068504, Mar. 30, 2017, 8 pgs.
Energous Corp., ISRWO, PCT/US2016/068551, Mar. 17, 2017, 8 pgs.
Energous Corp., ISRWO, PCT/US2016/068565, Mar. 8, 2017, 11 pgs.
Energous Corp., ISRWO, PCT/US2016/068987, May 8, 2017, 10 pgs.

(56)

References Cited

OTHER PUBLICATIONS

- Energous Corp., ISRWO, PCT/US2016/068993, Mar. 13, 2017, 12 pgs.
- Energous Corp., ISRWO, PCT/US2016/069313, Nov. 13, 2017, 10 pgs.
- Energous Corp., ISRWO, PCT/US2016/069316, Mar. 16, 2017, 15 pgs.
- Energous Corp., ISRWO, PCT/US2017/046800, Sep. 11, 2017, 13 pgs.
- Energous Corp., ISRWO, PCT/US2017/065886, Apr. 6, 2018, 13 pgs.
- Energous Corp., ISRWO, PCT/US2018/012806, Mar. 23, 2018, 9 pgs.
- Energous Corp., ISRWO, PCT/US2018/025465, Jun. 22, 2018, 9 pgs.
- Energous Corp., ISRWO, PCT/US2018/031768, Jul. 3, 2018, 9 pgs.
- Energous Corp., ISRWO, PCT/US2018/031786, Aug. 8, 2018, 9 pgs.
- Energous Corp., ISRWO, PCT/US2018/039334, Sep. 11, 2018, 9 pgs.
- Energous Corp., ISRWO, PCT/US2018/051082, Dec. 12, 2018, 9 pgs.
- Energous Corp., ISRWO, PCT/US2018/058178, Mar. 13, 2019, 10 pgs.
- Energous Corp., ISRWO, PCT/US2018/064289, Apr. 25, 2019, 12 pgs.
- Energous Corp., ISRWO, PCT/US2019/015820, May 14, 2019, 9 pgs.
- Energous Corp., ISRWO, PCT/US2019/021817, Apr. 6, 2019, 11 pgs.
- Energous Corp., ISRWO, PCT/US2019/039014, Oct. 4, 2019, 15 pgs.
- Energous Corp., ISRWO, PCT/US2019/061445, Jan. 7, 2020, 19 pgs.
- Energous Corp., ISRWO, PCT/US2020/027409, Jul. 24, 2020, 11 pgs.
- Energous Corp., ISRWO, PCT/US2020/051692, Jan. 6, 2021, 9 pgs.
- Energous Corp., ISRWO, PCT/US2020/051694, Jan. 6, 2021, 11 pgs.
- Energous Corp., ISRWO, PCT/US2020/067566, Apr. 27, 2021, 12 pgs.
- Extended European Search Report, EP17882087.4, Sep. 17, 2019, 10 pgs.
- Notice of Intent to Issue Reexam Certificate: U.S. Appl. No. 90/013,793 Feb. 2, 2017, 8 pgs.
- Order Granting Reexamination Request, U.S. Appl. No. 90/013,793 Aug. 31, 2016, 23 pgs.
- Ossia Inc. vs Energous Corp.*, Declaration of Stephen B. Heppe in Support of Petition for Post-Grant Review of U.S. Pat. No. 9,124,125, PGR2016-00023, May 31, 2016, 144 pgs.
- Ossia Inc. vs Energous Corp.*, Declaration of Stephen B. Heppe in Support of Petition for Post-Grant Review of U.S. Pat. No. 9,124,125, PGR2016-00024, May 31, 2016, 122 pgs.
- Ossia Inc. vs Energous Corp.*, Patent Owner Preliminary Response, Sep. 8, 2016, 95 pgs.
- Ossia Inc. vs Energous Corp.*, Petition for Post Grant Review of U.S. Pat. No. 9,124,125, May 31, 2016, 86 pgs.
- Ossia Inc. vs Energous Corp.*, Petition for Post-Grant Review of U.S. Pat. No. 9,124,125, May 31, 2016, 92 pgs.
- Ossia Inc. vs Energous Corp.*, PGR2016-00023-Institution Decision, Nov. 29, 2016, 29 pgs.
- Ossia Inc. vs Energous Corp.*, PGR2016-00024-Institution Decision, Nov. 29, 2016, 50 pgs.
- Ossia Inc. vs Energous Corp.*, PGR2016-00024-Judgement-Adverse, Jan. 20, 2017, 3 pgs.
- Extended European Search Report, EP20866267.6, Nov. 6, 2023, 14 pgs.
- Adamiuk et al., "Compact, Dual-Polarized UWB-Antenna, Embedded in a Dielectric," IEEE Transactions on Antenna and Propagation, IEEE Service Center, Piscataway, NJ, US vol. 56, No. 2, Feb. 1, 2010, 8 pgs.
- César Sánchez-Pérez et al., "Design and Applications of a 300-800 MHz Tunable Matching Network", IEEE Journal on Emerging and Selected Topics in Circuits and Systems, vol. 3, No. 4, Dec. 2013, 10 pgs.
- Gill et al., "A System for Change Detection and Human Recognition in Voxel Space using the Microsoft Kinect Sensor," 2011 IEEE Applied Imagery Pattern Recognition Workshop, 8 pgs.
- Han et al., Enhanced Computer Vision with Microsoft Kinect Sensor: A Review, IEEE Transactions on Cybernetics vol. 43, No. 5, pp. 1318-1334, Oct. 3, 2013.
- Hsieh et al., "Development of a Retrodirective Wireless Microwave Power Transmission System", IEEE, 2003, pp. 393-396.
- Leabman, "Adaptive Band-partitioning for Interference Cancellation in Communication System," Thesis Massachusetts Institute of Technology, Feb. 1997, pp. 1-70.
- Li et al., "High-Efficiency Switching-Mode Charger System Design Considerations with Dynamic Power Path Management," Mar./Apr. 2012 Issue, 8 pgs.
- Mao et al., "BeamStar: An Edge-Based Approach to Routing in Wireless Sensors Networks", IEEE Transactions on Mobile Computing, IEEE Service Center, Los Alamitos, CA, vol. 6, No. 11, Nov. 1, 2007, 13 pgs.
- Mascarenas et al., "Experimental Studies of Using Wireless Energy Transmission for Powering Embedded Sensor Nodes," Nov. 28, 2009, Journal of Sound and Vibration, 13 pgs.
- Mishra et al., "SIW-based Slot Array Antenna and Power Management Circuit for Wireless Energy Harvesting Applications", IEEE APSURSI, Jul. 2012, 2 pgs.
- Nenzi et al., "U-Helix: On-Chip Short Conical Antenna", 7th European Conference on Antennas and Propagation (EUCAP), ISBN: 978-1-4673-2187-7, IEEE, Apr. 8, 2013, 5 pgs.
- Qing et al., "UHF Near-Field Segmented Loop Antennas with Enlarged Interrogation Zone," 2012 IEEE International Workshop on Antenna Technology (iWAT), Mar. 1, 2012, pp. 132-135, XP055572059, ISBN: 978-1-4673-0035-3.
- Singh, "Wireless Power Transfer Using Metamaterial Bonded Microstrip Antenna for Smart Grid WSN", 4th International Conference on Advances in Computing and Communications (ICACC), Aug. 27-29, 2014, 1 pg.
- Smolders, "Broadband Microstrip Array Antennas", Institute of Electrical and Electronics Engineers, Digest of the Antennas and Propagation Society International Symposium, Seattle, WA, Jun. 19-24, 1994, 3 pgs.
- Van Veen et al., "Beamforming: A Versatile Approach to Spatial Filtering", IEEE, ASSP Magazine, Apr. 1988, pp. 4-24.
- Wei et al., "Design of a Wideband Horizontally Polarized Omnidirectional Printed Loop Antenna," IEEE Antennas and Wireless Propagation Letters, vol. 11, Jan. 3, 2012, 4 pgs.
- Zeng et al., "A Compact Fractal Loop Rectenna for RF Energy Harvesting," IEEE Antennas and Wireless Propagation Letters, vol. 16, Jun. 26, 2017, 4 pgs.
- Zhai et al., "A Practical Wireless Charging System Based on Ultra-Wideband Retro-Reflective Beamforming", 2010 IEEE Antennas and Propagation Society International Symposium, Toronto, ON, 2010, 4 pgs.




Figure 1A




Figure 1B




FIGURE 1C




Figure 2A

Receiver 104




Figure 2B




Figure 3A




Figure 3B




Figure 3C




Figure 3D




Figure 3E




Figure 3F




Figure 3G




Figure 3H




Figure 3I




Figure 4






Figure 5

**Figure 6A**

**Figure 6B**

SYSTEMS AND METHODS FOR MACHINE LEARNING ZONE-BASED FOREIGN OBJECT DETECTION FOR WIRELESS POWER TRANSMISSION

RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/831,037, filed on Jun. 2, 2022, entitled “Systems And Methods For Machine Learning Based Foreign Object Detection For Wireless Power Transmission,” which is a continuation of U.S. patent application Ser. No. 17/026,196, filed on Sep. 19, 2020 (now U.S. Pat. No. 11,381,118), entitled “Systems And Methods For Machine Learning Based Foreign Object Detection For Wireless Power Transmission,” which claims priority to U.S. Provisional Application Ser. No. 62/903,674, filed Sep. 20, 2019, entitled “Systems And Methods For Machine Learning Based Foreign Object Detection For Wireless Power Transmission,” each of which is incorporated by reference herein in its entirety.

This application is related to U.S. patent application Ser. No. 17/026,191, which claims priority from Provisional Application Ser. No. 62/903,677, filed Sep. 20, 2019, entitled “Classifying And Detecting Foreign Objects Using A Power Amplifier Controller Integrated Circuit In Wireless Power Transmission Systems,” each of which is incorporated by reference herein in its entirety.

This application is related to U.S. patent application Ser. No. 16/045,637, entitled “Systems and Methods for Detecting Wireless Power Receivers and Other Objects at a Near-Field Charging Pad,” filed Jul. 25, 2018, which is incorporated herein in its entirety.

This application is related to PCT Patent Application No. PCT/US17/65886, filed Dec. 12, 2017, which is a continuation of U.S. Non-Provisional patent application Ser. No. 15/833,790, filed Dec. 6, 2017, which is a continuation-in-part of U.S. Non-Provisional patent application Ser. No. 15/424,552, filed Feb. 3, 2017, which claims priority to U.S. Provisional Application Ser. No. 62/433,227, filed Dec. 12, 2016. PCT Patent Application No. PCT/US17/65886 also claims priority to U.S. Provisional Application Ser. No. 62/541,581, filed Aug. 4, 2017. Each of these applications is hereby incorporated by reference in its respective entirety.

TECHNICAL FIELD

The embodiments herein generally relate to antennas, software, and devices used in wireless power transmission systems and, more specifically, to systems and methods for machine-learning based foreign object detection for wireless power transmission.

BACKGROUND

Building a wireless charging system for consumer devices typically requires complicated, and often, expensive antenna components to transmit and receive wirelessly delivered power. Conventionally, it is hard for a wireless power transmitter to accurately distinguish a valid wireless power receiver that needs to be charged, versus a foreign object that does not need to be charged. Users have encountered numerous frustrating issues with some conventional charging devices, including having damages caused to objects that include magnetic strips and/or RFID chips (e.g., credits cards, security badges, passports, key fobs, and the like). Moreover, many of these conventional charging devices

typically require placing the device to be charged at a specific position around the wireless power transmitter, and the device may not be moved to different positions, without interrupting or terminating the charging of the device. This results in a frustrating experience for many users as they may be unable to locate the device at the exact right position within the charging field of the wireless power transmitter in which to start charging their device, and may further end up with damages to important objects that they use on a daily basis.

SUMMARY

Accordingly, there is a need for wireless charging systems (e.g., radio frequency (RF) charging pads) that address the problems identified above. To this end, systems and methods are described herein that are capable of detecting and/or classifying objects for wireless power transmission. Such systems and methods of use thereof discover presence of objects in order to determine whether to proceed with delivery of wireless power or whether to forgo transmitting wireless power in order to avoid potentially damaging any of the detected objects. Such systems identify wireless power receivers and/or ignore one or more wireless power receivers that are not to be charged or powered and, thereby, avoid power leeching and other drains on the system as a whole, while ensuring that authorized wireless power receivers always receive power.

The systems disclosed herein use machine learning models to detect the presence of and/or to classify objects (including objects that are not wireless power receivers) that are present on or near the system. The machine learning models are trained apriori using a known set of objects and/or a predetermined set of features. During the training phase, the system transmits test power transmission signals and then receives reflected power back from one or more wireless power receivers or from one or more objects. The reflected power is collected and analyzed to identify signature signals (selected features) to train the machine learning models. The machine learning models are subsequently used by the wireless power transmission system to determine whether an authorized device is present and/or to determine whether an object other than a wireless power receiver is present.

In some embodiments, the process for reflecting power works even if an authorized wireless power receiver has no power remaining (e.g., its battery is completely drained), as the wireless power receiver is able to harness energy from the test power transmission signals to create impedance changes at the receiver side, which then cause different amounts of reflected power to be detected at the RF charging system (and within different power-transfer zones thereof), thereby allowing the receiver to convey data to the RF charging system. Such systems and methods could further manage power transfer control communication between the RF charging system and wireless power receivers without any data-communication capability and without using any sophisticated sensors.

In the description that follows, references are made to an RF charging system that includes various antenna zones. For the purposes of this description, power-transfer (or antenna) zones include one or more power-transferring elements (e.g., antennas such as a capacitive coupler) of the RF charging system, and each power-transfer zone may be individually addressable by a controlling integrated circuit (e.g., RF power transmitter integrated circuit 160, FIGS. 1A-1B) to allow for selective activation of each power-

transfer zone in order to determine which power-transfer zone is able to most efficiently transfer wireless power to a receiver. The system described herein can be used for near-field wireless charging (e.g., charging pads). For purposes of this disclosure, near-field wireless charging is the transmission of power over a distance of between 0 to 6 inches away from a wireless power transmitter. The techniques described herein may also be used for transmission of wireless power over longer distances.

- (A1) In some embodiments, a method of detecting and classifying foreign objects is performed at a computer system. The computer system has one or more processors and memory storing one or more programs configured for execution by the one or more processors. The method includes obtaining a plurality of electrical measurements while a wireless-power-transmitting antenna is transmitting different power beacons. The method also includes forming a feature vector according to the plurality of electrical measurements. The method further includes detecting a presence of one or more foreign objects prior to transmitting wireless power to one or more wireless power receivers by inputting the feature vector to trained one or more classifiers. Each classifier is a machine-learning model trained to detect foreign objects distinct from the one or more wireless power receivers.
- (A2) In some embodiments of the method of A1, each classifier is further trained to classify foreign objects, and the method further includes classifying the one or more foreign objects into one or more categories.
- (A3) In some embodiments of the method of any one of A1-A2, at least one respective power beacon of the different power beacons. Each zone corresponds to a distinct charging area. In some embodiments, each zone has an associated transmitting antenna, and all of the zones form a wireless-power-transmission system. Each of the transmitting antennas is responsible for sending power to a respective distinct charging area. The method includes obtaining a respective set of electrical measurements for each zone of the plurality of zones. The method also includes forming the feature vector comprises calculating a respective feature data for each set of electrical measurements, and aggregating each feature data to obtain the feature vector.
- (A4) In some embodiments of the method of any one of A1-A3, the method further includes, prior to inputting the feature vector to the trained one or more classifiers, transforming the feature vector to compensate for a predetermined set of conditions including environmental differences between when training the one or more classifiers to detect foreign objects and when operating the one or more classifiers to detect foreign objects (e.g., temperature, or board-to-board variation).
- (A5) In some embodiments of the method of any one of A1-A4, the method further includes, applying, at a first classifier of the one or more classifiers that has a first machine-learning model, reinforcement learning to adjust (or recalibrate) one or more weights used in the first machine-learning model upon determining that (i) the first classifier has detected a presence of the one or more foreign objects and (ii) wireless power received by the one or more wireless power receivers indicates that no foreign object is present.
- (A6) In some embodiments of the method of any one of A1-A5, the trained one or more classifiers detect that the one or more foreign objects are present. The method further includes continuing to (i) obtain the plurality of

electrical measurements, (ii) form the feature vector, and (iii) detect that the one or more foreign objects are present by inputting the feature vector to the trained one or more classifiers. The method further includes waiting to transmit wireless power to the one or more wireless power receivers until the one or more classifiers stop detecting that the one or more foreign objects are present.

- (A7) In some embodiments of the method of A6, each of the different power beacons is transmitted in an iterative fashion at each of a plurality of zones. Each zone corresponds to a distinct charging area of the wireless power transmitting antenna. The method includes obtaining a first set of electrical measurements for a first zone of the plurality of zones. The method also includes waiting to transmit wireless power to the one or more wireless power receivers until the one or more classifiers stop detecting that the one or more foreign objects are present in the first zone.
- (A8) In some embodiments of the method of A6, the plurality of electrical measurements are obtained at predetermined time intervals.
- (A9) In some embodiments of the method of any one of A1-A8, the plurality of electrical measurements include measurements of one or more of: load impedance, reflective power, forward power, drive current, drive voltage, magnetics, and temperature.
- (A10) In some embodiments of the method of any one of A1-A9, each classifier is trained to detect one or more of: coins, credit cards, and RFID tags.
- (A11) In some embodiments of the method of any one of A1-A10, the one or more classifiers are further trained to detect a presence of a first wireless power receiver. The method further includes transmitting wireless power to the first wireless power receiver. The method also includes, while transmitting the wireless power to the first wireless power receiver, continuing to (i) obtain the plurality of electrical measurements, (ii) form the feature vector, and (iii) detect that the first wireless power receiver is present by inputting the feature vector to the trained one or more classifiers. The method also includes ceasing to transmit wireless power from the wireless power transmitting antenna to the first wireless power receiver when the one or more classifiers stop detecting the presence of the first wireless power receiver.
- (A12) In some embodiments of the method of any one of A1-A11, the one or more classifiers are further trained to detect a charging state of a first wireless power receiver. The method further includes transmitting wireless power to the first wireless power receiver. The method also includes, while transmitting the wireless power to the first wireless power receiver, continuing to (i) obtain the plurality of electrical measurements, (ii) form the feature vector, and (iii) detect the charging state of the first wireless power receiver by inputting the feature vector to the trained one or more classifiers. The method also includes ceasing to transmit wireless power from the wireless power transmitting antenna to the first wireless power receiver when the one or more classifiers detect that the charging state of the first wireless power receiver has reached a predetermined threshold.
- (A13) In some embodiments of the method of any one of A1-A12, each power beacon of the different power beacons is transmitted as a low power burst (e.g., an electromagnetic signal that has 50% of a power level

5

used for transmission of wireless power to a receiving device) for a short period of time (e.g., lasts for less than 1 second, as compared to transmitting higher-power signals for minutes at a time while transmitting wireless power to a receiving device).

(A14) In some embodiments of the method of any one of A1-A13, each power beacon of the different power beacons is transmitted using transmission parameters selected from a predetermined set of transmission parameters specifying at least a power level and a frequency.

(A15) In some embodiments of the method of any one of A1-A14, the one or more classifiers include a K-means classifier trained to detect the one or more wireless power receivers and to distinguish the one or more wireless power receivers from the one or more foreign objects.

(A16) In some embodiments of the method of any one of A1-A15, the one or more classifiers include a k-nearest neighbor (k-NN) classifier trained to classify the one or more wireless power receivers and the one or more foreign objects into at least one category of a plurality of categories of objects.

(A17) In some embodiments of the method of any one of A1-A16, the wireless-power-transmitting antenna is one of a plurality of wireless-power transmitting antennas. Each wireless-power-transmitting antenna associated with a respective charging area. Each classifier of the one or more classifiers is trained to detect presence of the one or more foreign objects only in a respective charging area. The method includes detecting the presence of the one or more foreign objects by inputting a respective subset of features of the feature vector corresponding to a respective charging area to a respective classifier of the one or more classifiers that is trained to detect foreign objects in the respective charging area.

(A18) In some embodiments of the method of any one of A1-A17, each classifier of the one or more classifiers is trained to detect a respective class of foreign objects. The method includes detecting the presence of the one or more foreign objects by inputting the feature vector to each classifier to detect the presence of each class of foreign objects. In some embodiments, the one or more classifiers is further trained to detect a presence of foreign objects between the wireless power transmitting antenna and a first wireless power receiver. The method further includes continuing to obtain the plurality of electrical measurements to form the feature vectors to detect the presence of the first foreign objects between the wireless power transmitting antenna and the first wireless power receiver. The method also includes ceasing to transmit wireless power from the wireless power transmitting antenna to the first wireless power receiver until the one or more classifiers stop detecting the presence of the one or more foreign objects.

(A19) In some embodiments of the method of any one of A1-A18, the wireless power transmitting antenna is configured to match the load impedance of the one or more wireless power receivers for optimal power transfer.

(A20) In some embodiments of the method of any one of A1-A19, the wireless-power-transmitting antenna is a near-field transmitting antenna.

6

(A21) In some embodiments of the method of A20, the near-field transmitting antenna is configured to transmit at a center frequency of between 30-50 MHz.

(A22) In some embodiments of the method of A21, the near-field transmitting antenna is further configured to transmit at a sufficient power level to deliver 20 watts of usable power to the receiver. 20 watts is a high power delivery range beyond current capabilities of inductive-based charging techniques.

(A23) In some embodiments of the method of any one of A1-A22, the one or more classifiers are trained to detect foreign objects according to a set of features that show the most correlation to change in impedance.

In another aspect, an electronic device is provided. The electronic device includes one or more processors, and memory storing one or more programs for execution by the one or more processors. The one or more programs include instructions for performing or causing performance of the method of any one of (A1)-(A23).

In another aspect, a non-transitory computer-readable storage medium stores one or more programs for execution by one or more processors of an electronic device. The one or more programs including instructions for performing or causing performance of the method of any one of (A1)-(A23).

Thus, wireless charging systems configured in accordance with the principles described herein are able to perform one or more operations including (1) alerting a user about improper placement of receiver objects or obstruction of power transmitted to authorized wireless power receivers, (2) detecting presence of any foreign object between the transmission system and the wireless power receivers, and/or (3) managing power transfer between the wireless power transmission system and wireless power receivers, thereby providing numerous improvements and resolving numerous problems and limitations of conventional wireless power transmission systems.

Note that the various embodiments described above can be combined with any other embodiments described herein. The features and advantages described in the specification are not all inclusive and, in particular, many additional features and advantages will be apparent to one of ordinary skill in the art in view of the drawings, specification, and claims. Moreover, it should be noted that the language used in the specification has been principally selected for readability and instructional purposes, and not intended to circumscribe or limit the inventive subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

So that the present disclosure can be understood in greater detail, a more particular description may be had by reference to the features of various embodiments, some of which are illustrated in the appended drawings. The appended drawings, however, merely illustrate pertinent features of the present disclosure and are therefore not to be considered limiting, for the description may admit to other effective features.

FIG. 1A is a block diagram of an RF wireless power transmission system, in accordance with some embodiments.

FIG. 1B is a block diagram showing components of an example RF charging pad that includes an RF power transmitter integrated circuit and antenna zones, in accordance with some embodiments.

FIG. 1C is a block diagram showing components of an example RF charging pad that includes an RF power transmitter integrated circuit coupled to a switch, in accordance with some embodiments.

FIG. 2A is a block diagram illustrating an example RF charging pad, in accordance with some embodiments.

FIG. 2B is a block diagram illustrating an example receiver device, in accordance with some embodiments.

FIGS. 3A-3F illustrate an example of feature permutation for a hardware architecture, in accordance with some embodiments.

FIG. 3G illustrates an example robot gantry system used to collect data to train classifier models for detecting foreign objects, in accordance with some embodiments.

FIG. 3H illustrates a set of selected features (electrical measurements) and the results of classification by a classifier based on the selected features, in accordance with some embodiments.

FIG. 3I illustrates a set of selected features (electrical measurements) and the results of classification by another classifier based on the selected features, in accordance with some embodiments.

FIG. 4 is a sequence diagram of a machine learning-based foreign object detection system, in accordance with some embodiments.

FIG. 5 is a flow diagram showing a process of detecting foreign objects (and receivers) using trained classifiers in accordance with some embodiments.

FIG. 6A is a flow diagram showing a process of detecting a receiver by sending beacon signals periodically in accordance with some embodiments.

FIG. 6B is a flow diagram showing a process of optional training performed by a transmitter in accordance with some embodiments.

In accordance with common practice, the various features illustrated in the drawings may not be drawn to scale. Accordingly, the dimensions of the various features may be arbitrarily expanded or reduced for clarity. In addition, some of the drawings may not depict all of the components of a given system, method or device. Finally, like reference numerals may be used to denote like features throughout the specification and figures.

DESCRIPTION OF EMBODIMENTS

Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the various described embodiments. However, it will be apparent to one of ordinary skill in the art that the various described embodiments may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

FIG. 1A is a block diagram of an RF wireless power transmission system 150 in accordance with some embodiments. In some embodiments, the RF wireless power transmission system 150 includes a far-field transmitter (not shown). In some embodiments, the RF wireless power transmission system 150 includes a RF charging pad 100 (also referred to herein as a near-field (NF) charging pad 100 or RF charging pad 100). In some embodiments, the RF charging pad 100 includes an RF power transmitter integrated circuit 160 (described in more detail below). In some embodiments, the RF charging pad 100 includes one or more

communications components 204 (e.g., wireless communication components, such as WI-FI or BLUETOOTH radios), discussed in more detail below with reference to FIG. 2A. In some embodiments, the RF charging pad 100 also connects to one or more power amplifier units 108-1, . . . 108-n to control operation of the one or more power amplifier units when they drive external power-transfer elements (e.g., power-transfer elements 290). In some embodiments, RF power is controlled and modulated at the RF charging pad 100 via switch circuitry as to enable the RF wireless power transmission system to send RF power to one or more wireless receiving devices via the TX antenna array 210.

In some embodiments, the communication component(s) 204 enable communication between the RF charging pad 100 and one or more communication networks. In some embodiments, the communication component(s) 204 are capable of data communications using any of a variety of custom or standard wireless protocols (e.g., IEEE 802.15.4, Wi-Fi, ZigBee, 6LoWPAN, Thread, Z-Wave, Bluetooth Smart, ISA100.11a, WirelessHART, MiWi, etc.) custom or standard wired protocols (e.g., Ethernet, HomePlug, etc.), and/or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

In some instances, the communication component(s) 204 are not able to communicate with wireless power receivers for various reasons, e.g., because there is no power available for the communication component(s) to use for the transmission of data signals or because the wireless power receiver itself does not actually include any communication component of its own. As such, it is important to design near-field charging pads that are still able to uniquely identify different types of devices and, when a wireless power receiver is detected, figure out if that wireless power receiver is authorized to receive wireless power.

FIG. 1B is a block diagram of the RF power transmitter integrated circuit 160 (the “integrated circuit”) in accordance with some embodiments. In some embodiments, the integrated circuit 160 includes a CPU subsystem 170, an external device control interface, an RF subsection for DC to RF power conversion, and analog and digital control interfaces interconnected via an interconnection component, such as a bus or interconnection fabric block 171. In some embodiments, the CPU subsystem 170 includes a microprocessor unit (CPU) 202 with related Read-Only-Memory (ROM) 172 for device program booting via a digital control interface, e.g. an I²C port, to an external FLASH containing the CPU executable code to be loaded into the CPU Subsystem Random Access Memory (RAM) 174 (e.g., memory 206, FIG. 2A) or executed directly from FLASH. In some embodiments, the CPU subsystem 170 also includes an encryption module or block 176 to authenticate and secure communication exchanges with external devices, such as wireless power receivers that attempt to receive wirelessly delivered power from the RF charging pad 100.

In some embodiments, the RF IC 160 also includes (or is in communication with) a power amplifier controller IC 161A (PA IC) that is responsible for controlling and managing operations of a power amplifier, including for reading measurements of impedance at various measurement points within the power amplifier, which measurements are used in some instances to allow for detection of foreign objects. The PA IC may be on the same integrated circuit at the RF IC 160, or may be on its own integrated circuit that is separate from (but still in communication with) the RF IC 160. Additional details regarding the architecture and operation

of the PA IC are provided in U.S. Provisional Application No. 62/903,677, which disclosure is incorporated by reference in its entirety.

In some embodiments, executable instructions running on the CPU (such as those shown in the memory 206 in FIG. 2A and described below) are used to manage operation of the RF charging pad 100 and to control external devices through a control interface, e.g., SPI control interface 175, and the other analog and digital interfaces included in the RF power transmitter integrated circuit 160. In some embodiments, the CPU subsystem also manages operation of the RF subsection of the RF power transmitter integrated circuit 160, which includes an RF local oscillator (LO) 177 and an RF transmitter (TX) 178. In some embodiments, the RF LO 177 is adjusted based on instructions from the CPU subsystem 170 and is thereby set to different desired frequencies of operation, while the RF TX converts, amplifies, modulates the RF output as desired to generate a viable RF power level.

In the descriptions that follow, various references are made to antenna zones and power-transfer zones, which terms are used synonymously in this disclosure. In some embodiments the antenna/power-transfer zones may include antenna elements that transmit propagating radio frequency waves but, in other embodiments, the antenna/power transfer zones may instead include capacitive charging couplers that convey electrical signals but do not send propagating radio frequency waves.

In some embodiments, the RF power transmitter integrated circuit 160 provides the viable RF power level (e.g., via the RF TX 178) to an optional beamforming integrated circuit (IC) 109, which then provides phase-shifted signals to one or more power amplifiers 108. In some embodiments, the beamforming IC 109 is used to ensure that power transmission signals sent using two or more antennas 210 (e.g., each antenna 210 may be associated with a different antenna zone 290 or may each belong to a single antenna zone 290) to a particular wireless power receiver are transmitted with appropriate characteristics (e.g., phases) to ensure that power transmitted to the particular wireless power receiver is maximized (e.g., the power transmission signals arrive in phase at the particular wireless power receiver). In some embodiments, the beamforming IC 109 forms part of the RF power transmitter IC 160. In embodiments in which capacitive couplers (e.g., capacitive charging couplers 244) are used as the antennas 210, then optional beamforming IC 109 may not be included in the RF power transmitter integrated circuit 160.

In some embodiments, the RF power transmitter integrated circuit 160 provides the viable RF power level (e.g., via the RF TX 178) directly to the one or more power amplifiers 108 and does not use the beamforming IC 109 (or bypasses the beamforming IC if phase-shifting is not required, such as when only a single antenna 210 is used to transmit power transmission signals to a wireless power receiver). In some embodiments, the PA IC 161A receives the viable RF power level and provides that to the PAs 108.

In some embodiments, the one or more power amplifiers 108 then provide RF signals to the antenna zones 290 (also referred to herein as “power-transfer zones”) for transmission to wireless power receivers that are authorized to receive wirelessly delivered power from the RF charging pad 100. In some embodiments, each antenna zone 290 is coupled with a respective PA 108 (e.g., antenna zone 290-1 is coupled with PA 108-1 and antenna zone 290-N is coupled with PA 108-N). In some embodiments, multiple antenna zones are each coupled with a same set of PAs 108 (e.g., all PAs 108 are coupled with each antenna zone 290). Various

arrangements and couplings of PAs 108 to antenna zones 290 allow the RF charging pad 100 to sequentially or selectively activate different antenna zones in order to determine the most efficient antenna zone 290 to use for transmitting wireless power to a wireless power receiver. In some embodiments, the one or more power amplifiers 108 are also in communication with the CPU subsystem 170 to allow the CPU 202 to measure output power provided by the PAs 108 to the antenna zones of the RF charging pad 100. In some embodiments, the PAs 108 may include various measurement points that allow for at least measuring impedance values that are used to enable the foreign object detection techniques described herein (additional details and examples regarding such measurement points are provided in the incorporated-by-reference U.S. Provisional Application No. 62/903,677.

FIG. 1B also shows that, in some embodiments, the antenna zones 290 of the RF charging pad 100 may include one or more antennas 210A-N. In some embodiments, each antenna zones of the plurality of antenna zones includes one or more antennas 210 (e.g., antenna zone 290-1 includes one antenna 210-A and antenna zones 290-N includes multiple antennas 210). In some embodiments, a number of antennas included in each of the antenna zones is dynamically defined based on various parameters, such as a location of a wireless power receiver on the RF charging pad 100. In some embodiments, the antenna zones may include one or more of the meandering line antennas described in more detail below. In some embodiments, each antenna zone 290 may include antennas of different types (e.g., a meandering line antenna and a loop antenna), while in other embodiments each antenna zone 290 may include a single antenna of a same type (e.g., all antenna zones 290 include one meandering line antenna), while in still other embodiments, the antennas zones may include some antenna zones that include a single antenna of a same type and some antenna zones that include antennas of different types. In some embodiments the antenna/power-transfer zones may also or alternatively include capacitive charging couplers that convey electrical signals but do not send propagating radio frequency waves. Antenna zones are also described in further detail below.

In some embodiments, the RF charging pad 100 may also include a temperature monitoring circuit that is in communication with the CPU subsystem 170 to ensure that the RF charging pad 100 remains within an acceptable temperature range. For example, if a determination is made that the RF charging pad 100 has reached a threshold temperature, then operation of the RF charging pad 100 may be temporarily suspended until the RF charging pad 100 falls below the threshold temperature.

By including the components shown for RF power transmitter circuit 160 (FIG. 1B) on a single chip, such transmitter chips are able to manage operations at the transmitter chips more efficiently and quickly (and with lower latency), thereby helping to improve user satisfaction with the charging pads that are managed by these transmitter chips. For example, the RF power transmitter circuit 160 is cheaper to construct, has a smaller physical footprint, and is simpler to install. Furthermore, and as explained in more detail below in reference to FIG. 2A, the RF power transmitter circuit 160 may also include a secure element module 234 (e.g., included in the encryption block 176 shown in FIG. 1B) that is used in conjunction with a secure element module 282 (FIG. 2B) or a receiver 104 to ensure that only authorized receivers are able to receive wirelessly delivered power from the RF charging pad 100 (FIG. 1B).

11

FIG. 1C is a block diagram of a charging pad 294 in accordance with some embodiments. The charging pad 294 is an example of the charging pad 100 (FIG. 1A), however, one or more components included in the charging pad 100 are not included in the charging pad 294 for ease of discussion and illustration.

The charging pad 294 includes an RF power transmitter integrated circuit 160, one or more power amplifiers 108, a PA IC 161A (which may be on the same or a separate IC from the RF power transmitter IC 160), and a transmitter antenna array 290 having multiple antenna zones. Each of these components is described in detail above with reference to FIGS. 1A and 1B. Additionally, the charging pad 294 includes a switch 295 (i.e., transmitter-side switch), positioned between the power amplifiers 108 and the antenna array 290, having a plurality of switches 297-A, 297-B, . . . 297-N. The switch 295 is configured to switchably connect one or more power amplifiers 108 with one or more antenna zones of the antenna array 290 in response to control signals provided by the RF power transmitter integrated circuit 160.

To accomplish the above, each switch 297 is coupled with (e.g., provides a signal pathway to) a different antenna zone of the antenna array 290. For example, switch 297-A may be coupled with a first antenna zone 290-1 (FIG. 1B) of the antenna array 290, switch 297-B may be coupled with a second antenna zone 290-2 of the antenna array 290, and so on. Each of the plurality of switches 297-A, 297-B, . . . 297-N, once closed, creates a unique pathway between a respective power amplifier 108 (or multiple power amplifiers 108) and a respective antenna zone of the antenna array 290. Each unique pathway through the switch 295 is used to selectively provide RF signals to specific antenna zones of the antenna array 290. It is noted that two or more of the plurality of switches 297-A, 297-B, . . . 297-N may be closed at the same time, thereby creating multiple unique pathways to the antenna array 290 that may be used simultaneously.

In some embodiments, the RF power transmitter integrated circuit 160 (or the PA IC 161A, or both) is (are) coupled to the switch 295 and is configured to control operation of the plurality of switches 297-A, 297-B, . . . 297-N (illustrated as a “control out” signal in FIGS. 1A and 1C). For example, the RF power transmitter integrated circuit 160 may close a first switch 297-A while keeping the other switches open. In another example, the RF power transmitter integrated circuit 160 may close a first switch 297-A and a second switch 297-B, and keep the other switches open (various other combinations and configuration are possible). Moreover, the RF power transmitter integrated circuit 160 is coupled to the one or more power amplifiers 108 and is configured to generate a suitable RF signal (e.g., the “RF Out” signal) and provide the RF signal to the one or more power amplifiers 108. The one or more power amplifiers 108, in turn, are configured to provide the RF signal to one or more antenna zones of the antenna array 290 via the switch 295, depending on which switches 297 in the switch 295 are closed by the RF power transmitter integrated circuit 160.

To further illustrate, as described in some embodiments below, the charging pad is configured to transmit test power transmission signals and/or regular power transmission signals using different antenna zones, e.g., depending on a location of a receiver on the charging pad. Accordingly, when a particular antenna zone is selected for transmitting test signals or regular power signals, a control signal is sent to the switch 295 from the RF power transmitter integrated circuit 160 to cause at least one switch 297 to close. In doing

12

so, an RF signal from at least one power amplifier 108 can be provided to the particular antenna zone using a unique pathway created by the now-closed at least one switch 297.

In some embodiments, the switch 295 may be part of (e.g., internal to) the antenna array 290. Alternatively, in some embodiments, the switch 295 is separate from the antenna array 290 (e.g., the switch 295 may be a distinct component, or may be part of another component, such as the power amplifier(s) 108). It is noted that any switch design capable of accomplishing the above may be used, and the design of the switch 295 illustrated in FIG. 1C is merely one example.

FIG. 2A is a block diagram illustrating certain components of an RF charging pad 100 in accordance with some embodiments. In some embodiments, the RF charging pad 100 includes an RF power transmitter IC 160 (and the components included therein, such as those described above in reference to FIGS. 1A-1B), memory 206 (which may be included as part of the RF power transmitter IC 160, such as nonvolatile memory 206 that is part of the CPU subsystem 170), and one or more communication buses 208 for interconnecting these components (sometimes called a chipset). In some embodiments, the RF charging pad 100 includes one or more sensor(s) 212 (discussed below). In some embodiments, the RF charging pad 100 includes one or more output devices such as one or more indicator lights, a sound card, a speaker, a small display for displaying textual information and error codes, etc. In some embodiments, the RF charging pad 100 includes a location detection device, such as a GPS (global positioning satellite) or other geo-location receiver, for determining the location of the RF charging pad 100.

In some embodiments, the one or more sensor(s) 212 include one or more thermal radiation sensors, ambient temperature sensors, humidity sensors, IR sensors, occupancy sensors (e.g., RFID sensors), ambient light sensors, motion detectors, accelerometers, and/or gyroscopes.

In some embodiments, the RF charging pad 100 further includes a signature-signal receiving circuit 240, a reflected power coupler 242, and a capacitive charging coupler 244.

The memory 206 includes high-speed random access memory, such as DRAM, SRAM, DDR SRAM, or other random access solid state memory devices; and, optionally, includes non-volatile memory, such as one or more magnetic disk storage devices, one or more optical disk storage devices, one or more flash memory devices, or one or more other non-volatile solid state storage devices. The memory 206, or alternatively the non-volatile memory within memory 206, includes a non-transitory computer-readable storage medium. In some embodiments, the memory 206, or the non-transitory computer-readable storage medium of the memory 206, stores the following programs, modules, and data structures, or a subset or superset thereof:

- Operating logic 216 including procedures for handling various basic system services and for performing hardware dependent tasks;

- Communication module 218 for coupling to and/or communicating with remote devices (e.g., remote sensors, transmitters, receivers, servers, mapping memories, etc.) in conjunction with wireless communication component(s) 204;

- Sensor module 220 for obtaining and processing sensor data (e.g., in conjunction with sensor(s) 212) to, for example, determine the presence, velocity, and/or positioning of object in the vicinity of the RF charging pad 100;

- Power-wave generating module 222 for generating and transmitting power transmission signals (e.g., in conjunction with antenna zones 290 and the antennas 210

13

respectively included therein), including but not limited to, forming pocket(s) of energy at given locations. Power-wave generating module **222** may also be used to modify values of transmission characteristics (e.g., power level (i.e., amplitude), phase, frequency, etc.) used to transmit power transmission signals by individual antenna zones;

Database **224**, including but not limited to:

Sensor information **226** for storing and managing data received, detected, and/or transmitted by one or more sensors (e.g., sensors **212** and/or one or more remote sensors);

Device settings **228** for storing operational settings for the RF charging pad **100** and/or one or more remote devices;

Communication protocol information **230** for storing and managing protocol information for one or more protocols (e.g., custom or standard wireless protocols, such as ZigBee, Z-Wave, etc., and/or custom or standard wired protocols, such as Ethernet); and

Learned signature signals **232** for a variety of different wireless power receivers and other objects (which are not wireless power receivers).

a secure element module **234** for determining whether a wireless power receiver is authorized to receive wirelessly delivered power from the RF charging pad **100**;

an antenna zone selecting and tuning module **237** for coordinating a process of transmitting test power transmission signals with various antenna zones to determine which antenna zone or zones should be used to wirelessly deliver power to various wireless power receivers (as is explained in more detail below in reference to FIGS. **9A-9B** of incorporated-by-reference PCT Patent Application No. PCT/US17/65886);

an authorized receiver and object detection module **238** used for detecting various signature signals from wireless power receivers and from other objects, and then determining appropriate actions based on the detecting of the various signature signals (as is described in more detail below in reference to FIGS. **9A-9B**); and

a signature-signal decoding module **246** used to decode the detected signature signals and determine message or data content. In some embodiments, the module **246** includes an electrical measurement module **248** to collect electrical measurements from one or more receivers (e.g., in response to power beacon signals), a feature vector module **250** to compute feature vectors based on the electrical measurements collected by the electrical measurement module **246**, and/or machine learning classifier model(s) **264** that are trained to detect and/or classify foreign objects.

Each of the above-identified elements (e.g., modules stored in memory **206** of the RF charging pad **100**) is optionally stored in one or more of the previously mentioned memory devices, and corresponds to a set of instructions for performing the function(s) described above. The above-identified modules or programs (e.g., sets of instructions) need not be implemented as separate software programs, procedures, or modules, and thus various subsets of these modules are optionally combined or otherwise rearranged in various embodiments. In some embodiments, the memory **206**, optionally, stores a subset of the modules and data structures identified above.

FIG. **2B** is a block diagram illustrating a representative receiver device **104** (also sometimes called a receiver, power receiver, or wireless power receiver) in accordance with some embodiments. In some embodiments, the receiver

14

device **104** includes one or more processing units (e.g., CPUs, ASICs, FPGAs, microprocessors, and the like) **252**, one or more communication components **254**, memory **256**, antenna(s) **260**, power harvesting circuitry **259**, and one or more communication buses **258** for interconnecting these components (sometimes called a chipset). In some embodiments, the receiver device **104** includes one or more sensor(s) **262** such as the one or sensors **212** described above with reference to FIG. **2A**. In some embodiments, the receiver device **104** includes an energy storage device **261** for storing energy harvested via the power harvesting circuitry **259**. In various embodiments, the energy storage device **261** includes one or more batteries, one or more capacitors, one or more inductors, and the like.

In some embodiments, the power harvesting circuitry **259** includes one or more rectifying circuits and/or one or more power converters. In some embodiments, the power harvesting circuitry **259** includes one or more components (e.g., a power converter) configured to convert energy from power waves and/or energy pockets to electrical energy (e.g., electricity). In some embodiments, the power harvesting circuitry **259** is further configured to supply power to a coupled electronic device, such as a laptop or phone. In some embodiments, supplying power to a coupled electronic device include translating electrical energy from an AC form to a DC form (e.g., usable by the electronic device).

In some embodiments, the antenna(s) **260** include one or more of the meandering line antennas that are described in further detail in incorporated-by-reference PCT Patent Application No. PCT/US17/65886 (e.g., with reference to FIGS. **6A-7D**, and elsewhere). In some embodiments, the antenna(s) **260** may also or alternatively include capacitive charging couplers (such as those described with reference to FIGS. **5A-5B** of incorporated-by-reference U.S. patent application Ser. No. 16/045,637) that correspond in structure to those that may be present in a near-field charging pad.

In some embodiments, the receiver device **104** includes one or more output devices such as one or more indicator lights, a sound card, a speaker, a small display for displaying textual information and error codes, etc. In some embodiments, the receiver device **104** includes a location detection device, such as a GPS (global positioning satellite) or other geo-location receiver, for determining the location of the receiver device **103**.

In various embodiments, the one or more sensor(s) **262** include one or more thermal radiation sensors, ambient temperature sensors, humidity sensors, IR sensors, occupancy sensors (e.g., RFID sensors), ambient light sensors, motion detectors, accelerometers, and/or gyroscopes. It is noted that the foreign object detection techniques disclosed herein operate without relying on the one or more sensor(s) **262**.

The communication component(s) **254** enable communication between the receiver **104** and one or more communication networks. In some embodiments, the communication component(s) **254** are capable of data communications using any of a variety of custom or standard wireless protocols (e.g., IEEE 802.15.4, Wi-Fi, ZigBee, 6LoWPAN, Thread, Z-Wave, Bluetooth Smart, ISA100.11a, WirelessHART, MiWi, etc.) custom or standard wired protocols (e.g., Ethernet, HomePlug, etc.), and/or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document. It is noted that the foreign object detection techniques disclosed herein operate without relying on the communication component(s) **254**.

15

The communication component(s) **254** include, for example, hardware capable of data communications using any of a variety of custom or standard wireless protocols (e.g., IEEE 802.15.4, Wi-Fi, ZigBee, 6LoWPAN, Thread, Z-Wave, Bluetooth Smart, ISA100.11a, WirelessHART, MiWi, etc.) and/or any of a variety of custom or standard wired protocols (e.g., Ethernet, HomePlug, etc.), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

The memory **256** includes high-speed random access memory, such as DRAM, SRAM, DDR SRAM, or other random access solid state memory devices; and, optionally, includes non-volatile memory, such as one or more magnetic disk storage devices, one or more optical disk storage devices, one or more flash memory devices, or one or more other non-volatile solid state storage devices. The memory **256**, or alternatively the non-volatile memory within memory **256**, includes a non-transitory computer-readable storage medium. In some embodiments, the memory **256**, or the non-transitory computer-readable storage medium of the memory **256**, stores the following programs, modules, and data structures, or a subset or superset thereof:

Operating logic **266** including procedures for handling various basic system services and for performing hardware dependent tasks;

Communication module **268** for coupling to and/or communicating with remote devices (e.g., remote sensors, transmitters, receivers, servers, mapping memories, etc.) in conjunction with communication component(s) **254**;

Sensor module **270** for obtaining and processing sensor data (e.g., in conjunction with sensor(s) **262**) to, for example, determine the presence, velocity, and/or positioning of the receiver **103**, a RF charging pad **100**, or an object in the vicinity of the receiver **103**;

Wireless power-receiving module **272** for receiving (e.g., in conjunction with antenna(s) **260** and/or power harvesting circuitry **259**) energy from, capacitively-conveyed electrical signals, power waves, and/or energy pockets: optionally converting (e.g., in conjunction with power harvesting circuitry **259**) the energy (e.g., to direct current): transferring the energy to a coupled electronic device; and optionally storing the energy (e.g., in conjunction with energy storage device **261**);

Database **274**, including but not limited to:

Sensor information **276** for storing and managing data received, detected, and/or transmitted by one or more sensors (e.g., sensors **262** and/or one or more remote sensors);

Device settings **278** for storing operational settings for the receiver **103**, a coupled electronic device, and/or one or more remote devices; and

Communication protocol information **280** for storing and managing protocol information for one or more protocols (e.g., custom or standard wireless protocols, such as ZigBee, Z-Wave, etc., and/or custom or standard wired protocols, such as Ethernet);

a secure element module **282** for providing identification information to the RF charging pad **100** (e.g., the RF charging pad **100** uses the identification information to determine if the wireless power receiver **104** is authorized to receive wirelessly delivered power); and

a signature-signal generating module **283** used to control (e.g., in conjunction with a signature-signal generating circuit) various components to cause impedance changes at the antenna(s) **260** and/or power harvesting

16

circuitry **259** to then cause changes in reflected power as received by a signature-signal receiving circuit **240**.

Each of the above-identified elements (e.g., modules stored in memory **256** of the receiver **104**) is optionally stored in one or more of the previously mentioned memory devices, and corresponds to a set of instructions for performing the function(s) described above. The above-identified modules or programs (e.g., sets of instructions) need not be implemented as separate software programs, procedures, or modules, and thus various subsets of these modules are optionally combined or otherwise rearranged in various embodiments. In some embodiments, the memory **256**, optionally, stores a subset of the modules and data structures identified above. Furthermore, the memory **256**, optionally, stores additional modules and data structures not described above, such as an identifying module for identifying a device type of a connected device (e.g., a device type for an electronic device that is coupled with the receiver **104**).

In some embodiments, the near-field charging pads disclosed herein may use adaptive loading techniques to optimize power transfer. Such techniques are described in detail in commonly-owned and incorporated-by-reference PCT Application No. PCT/US17/65886 and, in particular, in reference to FIGS. 3A-8 and 12-15.

An Example Machine Learning Based Foreign Object Detection System

An example machine learning-based foreign object detection system (e.g., the RF charging pad **100**) is described herein, according to some embodiments. The system detects and classifies foreign objects in close proximity to (e.g., less than a few centimeters or inches of) a wireless power transmission system. In some embodiments, the system detects and classifies foreign objects for a near-field wireless power transmission system that is configured to transmit wireless power over a range of distance that extends from 0) to 6 inches of a housing the houses components of the system, but may also be configured to transmit such power over a range of up to 1 meter (e.g., for mid-field transmission of power), or to a range that extends to a few feet away (e.g., for far-field transmission of power). In some embodiments, the detection system utilizes system features (e.g., load impedance or reactance, reflective power, magnetics, temperature) that are measured directly (e.g., reflective power detection) by the transmitter (e.g., by the electrical measurements module **248**). In some embodiments, the detection system utilizes features that are measured indirectly (e.g. load voltage, load current) by the transmitter. The features are input to a machine learning model (e.g., the machine learning classifier models **264**) to infer the classification of objects (sometimes called foreign objects: e.g., receiver, coins, credit cards, RFID tags).

In some embodiments, the classification of the objects along with the transmitter's charging policy are used to control the power transmission. The detection system identifies the objects and determines whether it is safe to transmit power to charge devices, and/or whether certain adjustments to the transmission of power are needed to ensure that safety is maintained (e.g., reducing power levels, changing directivity to avoid certain objects, etc.). In some embodiments, the detection system indicates (to a user) a presence of a foreign object that is obstructing a device. In some embodiments, the detection system indicates if the foreign objects are within close proximity (e.g., within 6 inches) of one or more charging zones. In some embodiments, the detection system detects and classifies objects within a charging zone

as either a receiver, or a foreign object. In some embodiments, the detection system detects the absence (e.g., located beyond six inches) of objects in a charging zone. In some embodiments, the detection system detects objects between a receiver and a charging zone. In some embodiments, the detection system detects position of a receiver in a charging zone. In some embodiments, the detection system detects a charging state of a receiver in a charging zone. In some embodiments, the detection system detects and classifies objects in multiple charging zones. In some embodiments, the detection system determines a charging policy with respect to valid objects (e.g., receiver and business cards).

In some embodiments, the detection system uses self-calibration to adjust for temperature and/or wireless power hardware variations. In some embodiments, the detection system is calibrated during manufacturing for environmental conditions (e.g., board to board variations). In some embodiments, the detection system is calibrated for variations in components' tolerances. In some embodiments, the detection system is calibrated for manufacturing variability in antenna thickness, dielectric, etc. Such variations result in offsets or shifts of feature vector clustering. In some embodiments, calibration with reference objects, at the time of manufacturing (e.g., in a factory setting) is used to cancel out the offsets. In some embodiments, the calibration parameters are stored in non-volatile memory of the calibrated device.

In some embodiments, the detection system incorporates auto-calibration for fault tolerance (e.g., due to aging of devices or environmental changes). In some embodiments, the detection system incorporates an N-point calibration for normalization. In some embodiments, the detection system is calibrated by including unclassified objects. In some embodiments, the detection system is calibrated by excluding unclassified object classifications.

In some embodiments, the detection system detects devices for charging in the presence of safe objects (e.g., objects that are not harmed by the wireless power transmission). In some embodiments, the detection system disables charging and indicates error when unsafe objects (e.g., coins, paper clips, RFID tags, credit cards, metal) are present. In some embodiments, the detection system indicates active zones (i.e., zones where one or more objects are receiving power). In some embodiments, the detection system incorporates fault detection or handling (e.g., provide power back-off when unsafe objects are detected, provide alignment guide to guide user to resolve failure by removing objects, shifting receivers, etc.).

In wireless power transmission systems, the transmitter is designed to match the load impedance or reactance of the receiver for optimal power transfer. This impedance matching is affected by many factors, such as matching receiving and transmitting antenna, output load of receivers, antenna angle and position with respect to transmitter and receiver, obstructions between transmitter and receiver within the charging zones, temperature, and system to system variations (sometimes called wireless power hardware variations). These factors are either directly or indirectly observed as measurable electrical changes stimulated by a power beacon (e.g., short low power burst(s) sweeping over different power levels, frequency, position, etc. into a charging zone). In some embodiments, these electrical measurements (e.g., reflective power, forward power, drive current, drive voltage, temperature, etc.) are captured during the beacon and saved as a set of feature values. In some embodiments, the feature values are processed by the transmitter to yield a classification and decision. Selection of the

features is critical to the classification performance. Each hardware architecture generates a different set of features which can be numerous, especially when different beacons are iterated over power, frequency and position.

FIGS. 3A-3F illustrate an example of the feature permutation for a hardware architecture. Not all features are optimal or useful for classification and often many combinations (of the features) are not obvious (for automatic inference). For example, in some orientations, a first object in the charging zone may appear to be another object (from the perspective of its impedance). FIGS. 3A-3F show a pair plot where each feature has been plotted against every other feature. The common labels are on the far left and near the bottom of the respective images. The features illustrated in FIGS. 3A-3F are various ADC values available in the hardware and the grouping represent different objects (ERX, NOLOAD, etc.). The colors (orange, and blue) corresponds to labels. In this case it is either a 'noload' (i.e., empty) or 'erx.' Although, in practice, there can be many clusters, FIGS. 3A-3F are simplified illustrations. In particular, some features were removed to show a more zoomed in view of the illustration. As illustrated, there are at least 7 features: adc1_0, adc2_0 (IdPA), adc3_0, adc4_0, pdet1_0 (power detector), pdet0_0, ts_0 (temperature), according to some embodiments. These 7 features are plotted against each other, so that there are 7x7 subplots. The middle diagonal is a distribution which can be ignored, since plotting a feature against itself doesn't have any meaning. The lower triangle (i.e., the triangle below the diagonal) is a mirror of the upper triangle (i.e., the triangle above the diagonal). So, as illustrated, there are really only 21 combinations: (all combinations—diagonal) divided by 2=(7x7-7)/2=21 combinations. Some subplots show very poor separation (e.g., adc1_0 vs adc4_0) between the different colors. This means that it is not easy to tell from those features if the 'label' is 'noload' or 'erx'. Some plots show separation of features, but there is no clear separation, because the result is dominated by a single feature (e.g., adc2_0 vs ts_0 (temperature)). Some features are easier for a software to categorize (e.g., adc2_0 (IdPA) vs pdet0_0 (power detector)) than other features. Some embodiments select features that show a high degree of separation.

In some embodiments, the data collection process utilizes an automated gantry system, such as the system shown in FIG. 3G (e.g., a robot with 4-5 degrees of freedom), that iterates through a set of objects representing receiver, no-load, and various foreign objects placed in a charging zone. In some embodiments, the robot gantry system places an object at a predetermined position and orientation. Power is transmitted and signals or features are sampled. Optionally, the tests are run over temperature (sometimes called temperature cycling: e.g., by changing temperature in the environment using an oven) if compensation is required. In some embodiments, the sampled data is stored in a data warehouse. In some embodiments, a first object (e.g., a key, coin, or other type of foreign object) is swapped and another object (e.g., a different foreign object, such as a different key, different coin, or another type of foreign object) is placed and the sampling process is repeated. In some embodiments, multiple objects are placed or combined so as to train the machine learning models to detect the presence of more than one object. In some embodiments, the data collection process includes sweep or cycling of several features (e.g., power, frequency, zones, and antenna detune). In some embodiments, the data collection process includes feature unrolling (i.e., each feature in a separate column in a table

of features). In some embodiments, the data collection process includes sweep sequencing of features.

The data collected is sampled into a labeled data set. In some embodiments, the collected data sets are aggregated and then processed by feature selection algorithms that look for features with the highest correlation. In some embodiments, data features are selected from the aggregated data set by both standard feature selection algorithms and by a tester or a developer (a user) using standard visualization tools (e.g., cluster visualization tools). In some embodiments, the process is iterated or repeated several times for better performance.

FIG. 3H illustrates a set of features selected by the above process. The x-axis and the y-axis each corresponds to a selected feature. The selected features show the most correlation to change in impedance, according to some embodiments. Once the features are selected, the data features are used in a supervised training of a set of candidate machine learning models that are evaluated for their performance. In some embodiments, other factors, such as robustness and ease of calibration, are also considered during model selection. Once models are trained, the models are integrated into the detection system. In some embodiments, the detection system employs multiple machine learning models, each model tuned to detect and/or classify objects in specific zones. In some embodiments, results from multiple models are combined. In some instances, it is easier to combine results from multiple simpler models than to design a more complex model. In some embodiments, the detection system employs multiple machine learning models, each model tuned to detect and/or classify specific types of objects.

In some embodiments, a KMeans algorithm (or classifier) classifies known and unknown objects based on the selected features. For example, in FIG. 3H, the different shades in the plot indicate classification, by a KMeans classifier, of different types of objects (no load, erx or receiver objects, and foreign objects), according to some embodiments. No load corresponds to absence of receivers and foreign objects in the zone. By way of experimentation, in some embodiments, a KMeans classifier is chosen to classify known and unknown objects, or to classify and/or to detect objects distinct from a known set of objects. In some embodiments, the KMeans classifier is used to detect specific devices for charging. In some embodiments, a k-nearest neighbors classifier (k-NN classifier) classifies specific set of objects, as illustrated in FIG. 3I, according to some embodiments. As shown in FIG. 3I, the k-NN classifier identifies a coin, a receiver (indicated as eRX), a tag (or a RFID tag), a card (e.g., a credit card), and, in some instances, the fact that the charging zone is empty (i.e., no objects are present), according to some embodiments.

In some embodiments, the sample data (sometimes called the data set) is split into a training set and a test set. The machine learning model is trained with different hyperparameters using the training set, and the model's performance is evaluated with the test set. This process is repeated until a tuned model with the desired level of performance is created. The model is subsequently integrated and deployed in the detection system.

FIG. 4 is a sequence diagram of a machine learning-based foreign object detection system 400, in accordance with some embodiments. The foreign object detection system 400 operates in a loop (420) detecting and/or classifying objects in one or more charging zones. A power transmission hardware (HW) 406 (e.g., the RF charging pad 100, FIG. 1B) operates in a continuous loop (428), iterating (430) through different permutations (432) of power amplifier

(PA) zones (sometimes called charging zones), power levels, switches, frequency, etc. The HW 406 enables the antenna system 408 to transmit power (sometimes called power beacons, beacons, or beacon signals) using the transmission parameters (corresponding to each permutation) during each iteration. The HW 406 also samples (436), from the antenna system 408 (e.g., which includes the antennas 210, FIG. 1B), analog readings from the selected set of features representing key hardware points in the system. The impedance interaction between the antenna system 408 and the object 410 is indicated by the label 434 (e.g., this impedance interaction involves the PA IC 161A receiving impedance measurements from various measurement points along one or more of the PAs 108). The HW module 406 returns (438) aggregate feature data (i.e., a collection of feature data at the end of the loop 428) to the detection system 402 (described above in reference to FIGS. 3A-3I). Optionally (440), the detection system 402 transforms (444) the sample data (sometimes called the feature data or the aggregate feature data), if required, to compensate (442) for environmental variations (e.g., board to board variations). In some embodiments, the transforming is performed by the RF IC 160, but certain operations can also be performed by the PA IC 161A in certain embodiments or circumstances.

Subsequently, the detection system 402 calculates (446) inference (i.e., detects and/or classifies objects) by inputting the feature data to the trained machine learning model 404 (described above). The machine learning model 404 returns (454) decision or classification result. The detection system 402 handles (456) or uses the result from the machine learning model 404 to drive higher level system behavior, such as to generate user alerts, to determine charging levels for objects, etc. In some embodiments, the detection system 402 and the ML model 404 reside on the RF IC 160, and these also operate based on the measurements received via the PA IC 161A.

In some embodiments, the machine learning model 404 optionally (448) applies (450) calibration (e.g., feature scaling, normalization of data) if required. In some embodiments, the machine learning model 404 applies (452) model calibration data. In some embodiments, the calibration step is performed at the time of manufacturing (sometimes called factory calibration) of the wireless power transmission system (that incorporates the foreign object detection system). Sometimes a user of the system performs a calibration procedure to recalibrate the system. Some embodiments perform auto calibration during operation. For example, some embodiments use reinforcement learning where small deviations that were categorized as chargeable are used to adjust the models' accuracy as the devices age. To further illustrate, in some embodiments, after a receiver is detected, the wireless power transmission system communicates with the receiver (e.g., using Bluetooth LE) to establish that sufficient power is received from the transmitter, thereby indicating that the coupling between the wireless power transmission system and the receiver is effective. This in turn indicates that the concerned feature vector has provided a reference for a true positive detection result. This observation is used to reinforce or adjust the stored calibrated points. In some embodiments, as receiver devices age, calibration points shift slowly so the auto calibration is used to auto correct the behavior of the transmission system. As another example, when the device is able to charge, the transmitter can record shifts and increase the adjustments weighting towards the new shift for each successful charging. If the charge is unsuccessful, then the weighting is diminished to counter the adjustments.

21

FIG. 5 is a flow diagram showing a process of detecting foreign objects (and receivers) using trained classifiers in accordance with some embodiments.

In some embodiments, a method 500 of detecting and classifying foreign objects is performed at a computer system (e.g., the system 100 as described above in reference to FIG. 2A, with the RF Power Transmitter IC 160 responsible for controlling operation of the method 500, based in part on the measurements received from the PA IC 161A). The computer system (e.g., the system 100) has one or more processors and memory storing one or more programs configured for execution by the one or more processors. The method includes obtaining (502) a plurality of electrical measurements (e.g., using the electrical measurements module 248, which operates in conjunction with the PA IC 161A) while a wireless-power-transmitting antenna (e.g., one of the antennas 210-A, . . . , 210-N) is transmitting different power beacons. The method also includes forming (504) a feature vector (e.g., by the feature vector module 250) according to the plurality of electrical measurements. The method further includes detecting (508) a presence of one or more foreign objects prior to transmitting wireless power to one or more wireless power receivers by inputting the feature vector to trained one or more classifiers (e.g., the classifier model(s) 264). Detecting presence can include detecting that the one or more foreign objects are located within a wireless-power-transmission range of the system, such as within a near-field wireless-power-transmission range of between 0 to 6 inches. Each classifier is a machine-learning model trained to detect foreign objects distinct from the one or more wireless power receivers. In some embodiments, the method includes determining (514) if foreign objects are detected and/or determining if receivers' absence is detected. In accordance with a determination that no foreign objects are detected and/or that receivers are present, the method further includes transmitting (516) power to the receivers. Example classifiers and the training processes are described above in the section titled "An Example Machine Learning Based Foreign Object Detection System."

In some embodiments, each classifier is further trained to classify (510) foreign objects, and the method further includes classifying the one or more foreign objects into one or more categories. FIG. 3I (described above) provides an example of a classifier that can classify objects into a known list of categories, according to some embodiments.

In some embodiments, at least one respective power beacon of the different power beacons is transmitted at each of a plurality of antennas zones. Each zone corresponds to a distinct charging area. In some embodiments, each zone has an associated transmitting antenna, and all of the zones form a wireless-power-transmission system. Each of the transmitting antennas is responsible for sending power to a respective distinct charging area. FIGS. 1B and 1C (described above) illustrate an antenna array 290 and transmission zones 290-1 through 290-N, according to some embodiments. In the example shown in FIGS. 1B and 1C, each antenna (e.g., antenna 210-A, 210-N) are configured to transmit power to a respective power transfer zone. The method includes obtaining a respective set of electrical measurements for each zone of the plurality of zones. The method also includes forming the feature vector comprises calculating a respective feature data for each set of electrical measurements, and aggregating each feature data to obtain the feature vector.

In some embodiments, the method further includes, prior to inputting the feature vector to the trained one or more classifiers, transforming (506) the feature vector (e.g., by the

22

feature vector module 250) to compensate for a predetermined set of conditions including environmental differences between when training the one or more classifiers to detect foreign objects and when operating the one or more classifiers to detect foreign objects (e.g., temperature, or board-to-board variation).

In some embodiments, the method further includes, applying (518), at a first classifier of the one or more classifiers that has a first machine-learning model, reinforcement learning to adjust (or recalibrate) one or more weights used in the first machine-learning model upon determining that (i) the first classifier has detected a presence of the one or more foreign objects and (ii) wireless power received by the one or more wireless power receivers indicates that no foreign object is present.

In some embodiments, the trained one or more classifiers detect that the one or more foreign objects are present (e.g., within a near-field wireless power transmission range of 0-6 inches from an outer surface of a housing that houses the RF charging pad 100). The method further includes continuing to (i) obtain the plurality of electrical measurements, (ii) form the feature vector, and (iii) detect that the one or more foreign objects are present by inputting the feature vector to the trained one or more classifiers. The method further includes waiting to transmit wireless power to the one or more wireless power receivers until the one or more classifiers stop detecting that the one or more foreign objects are present.

In some embodiments, each of the different power beacons is transmitted in an iterative fashion at each of a plurality of zones. Each zone corresponds to a distinct charging area of the wireless power transmitting antenna. The method includes obtaining a first set of electrical measurements for a first zone of the plurality of zones. The method also includes waiting to transmit wireless power to the one or more wireless power receivers until the one or more classifiers stop detecting that the one or more foreign objects are present in the first zone. FIG. 1B (described above) illustrates antenna 210-A configured to transfer power to zone 2901-1 and antenna 210-N configured to transfer power to zone 290-N, according to some embodiments. The circuit 160 controls the antenna array to iterate over the plurality of zones, according to some embodiments.

In some embodiments, the plurality of electrical measurements are obtained (e.g., obtained via the PA IC 161A based on electrical measurements at one of the PAs 108) at predetermined time intervals.

In some embodiments, the plurality of electrical measurements include measurements of one or more of: load impedance, reflective power, forward power, drive current, drive voltage, magnetics, and temperature. FIGS. 3A-3F (described above) illustrate several features or electrical measurements aimed at training classifiers for detecting and classifying foreign objects.

In some embodiments, each classifier is trained to detect one or more of: coins, credit cards, and RFID tags. For example, FIG. 3I (described above) illustrates classification of objects, according to some embodiments.

In some embodiments, the one or more classifiers are further trained to detect (512) a presence of a first wireless power receiver. FIGS. 3A-3I (described above) provide examples of training classifiers, according to some embodiments. In some embodiments, the classifiers are trained to detect the presence of specific one or more receivers, and can also detect whether or not each receiver is authorized to receive wireless power from the system (to avoid allowing unauthorized receivers to leech power from the system). The

23

method further includes transmitting wireless power to the first wireless power receiver. The method also includes, while transmitting the wireless power to the first wireless power receiver, continuing to (i) obtain the plurality of electrical measurements, (ii) form the feature vector, and (iii) detect that the first wireless power receiver is present by inputting the feature vector to the trained one or more classifiers. The method also includes ceasing to transmit wireless power from the wireless power transmitting antenna to the first wireless power receiver when the one or more classifiers stop detecting the presence of the first wireless power receiver.

In some embodiments, the one or more classifiers are further trained to detect (512) a charging state of a first wireless power receiver. To illustrate, when a receiver's battery charges (e.g., because the receiver received power from the wireless power transmission system), the load impedance of the battery changes. This will result in the feature vector to change as the battery charges reaches full capacity. The one or more classifiers are trained to detect this change thereby detecting a charging state of the receiver. The method further includes transmitting wireless power to the first wireless power receiver. The method also includes, while transmitting the wireless power to the first wireless power receiver, continuing to (i) obtain the plurality of electrical measurements, (ii) form the feature vector, and (iii) detect the charging state of the first wireless power receiver by inputting the feature vector to the trained one or more classifiers. The method also includes ceasing to transmit wireless power from the wireless power transmitting antenna to the first wireless power receiver when the one or more classifiers detect that the charging state of the first wireless power receiver has reached a predetermined threshold.

In some embodiments, each power beacon of the different power beacons is transmitted as a low power burst (e.g., an electromagnetic signal that has 50% of a power level used for transmission of wireless power to a receiving device) for a short period of time (e.g., lasts for less than 1 second, as compared to transmitting higher-power signals for minutes at a time while transmitting wireless power to a receiving device). In some embodiments, each power beacon of the different power beacons is transmitted using transmission parameters selected from a predetermined set of transmission parameters specifying at least a power level and a frequency.

In some embodiments, the one or more classifiers include a K-means classifier trained to detect the one or more wireless power receivers and to distinguish the one or more wireless power receivers from the one or more foreign objects. A K-means classifier is described above in reference to FIG. 3H, according to some embodiments.

In some embodiments, the one or more classifiers include a k-nearest neighbor (k-NN) classifier trained to classify the one or more wireless power receivers and the one or more foreign objects into at least one category of a plurality of categories of objects. A k-NN classifier is described above in reference to FIG. 3I, according to some embodiments.

In some embodiments, the wireless-power-transmitting antenna is one of a plurality of wireless-power transmitting antennas. Each wireless-power-transmitting antenna associated with a respective charging area. Each classifier of the one or more classifiers is trained to detect presence of the one or more foreign objects only in a respective charging area. The method includes detecting the presence of the one or more foreign objects by inputting a respective subset of features of the feature vector corresponding to a respective

24

charging area to a respective classifier of the one or more classifiers that is trained to detect foreign objects in the respective charging area.

In some embodiments, each classifier of the one or more classifiers is trained to detect a respective class of foreign objects. The method includes detecting the presence of the one or more foreign objects by inputting the feature vector to each classifier to detect the presence of each class of foreign objects. In some embodiments, the one or more classifiers is further trained to detect a presence of foreign objects between the wireless power transmitting antenna and a first wireless power receiver. The method further includes continuing to obtain the plurality of electrical measurements to form the feature vectors to detect the presence of the first foreign objects between the wireless power transmitting antenna and the first wireless power receiver. The method also includes ceasing to transmit wireless power from the wireless power transmitting antenna to the first wireless power receiver until the one or more classifiers stop detecting the presence of the one or more foreign objects.

In some embodiments, the wireless power transmitting antenna is configured to match the load impedance of the one or more wireless power receivers for optimal power transfer.

In some embodiments, the wireless-power-transmitting antenna is a near-field transmitting antenna. For example, the system 100 (described above) illustrates antennas 210-A through 210-N. In some embodiments, the near-field transmitting antenna is configured to transmit at a center frequency of between 30-50 MHz. In some embodiments, the near-field transmitting antenna is further configured to transmit at a sufficient power level to deliver 20 watts of usable power to the receiver. 20 watts is a high power delivery range beyond current capabilities of inductive-based charging techniques.

In some embodiments, the one or more classifiers are trained to detect foreign objects according to a set of features that show the most correlation to changes in impedance values. For example, FIGS. 3A-3F (described above) illustrates several electrical measurements or features, and FIG. 3H illustrates two features that show the most correlation to change in impedance, according to some embodiments. In some embodiments, the set of features includes drive current power amplifier drive current and/or power detectors for reflective power. In some embodiments, the set of features includes FWD and/or power detectors for reflective power of multiple zones.

FIG. 6A is a flow diagram 600 showing a process of using a trained classifier for detecting foreign objects in accordance with some embodiments that use a zone-based power transmission system (such as that shown in the example of FIG. 1B). Some embodiments detect a receiver 104 along with any foreign objects (such as keys, coins, or other objects that might be placed on or near the NF charging pad) by sending beacon signals (also referred to herein as "test power transmission signals") periodically. In some embodiments, each power-transfer zone 290 starts (602) a timer so as to send the beacon signals periodically. In some embodiments, when the timer expires (604), each power-transfer zone 290 of the NF charging pad (also referred to herein as an RF charging pad) 100 sends a respective beacon signal (606). In some embodiments, at step 608, a signature-signal circuit of the transmitter (e.g., a component capable of receiving analog signals (such as reflected power measurements after a beacon signal is transmitted and then some part of it is reflected back) and converting them to a digital representation that forms a signature representing a foreign

25

object) determines signature-signals after transmitting the beacon signal (the signature-signals representing one or more receivers and/or one or more foreign objects). The transmitter beacon signal is disabled (610), the samples from ADC are analyzed (612) to help determine the signature-signals discussed above, and the zone status is evaluated (614) (e.g., as discussed with reference to FIG. 5). After the zone status is determined and the matching between each respective zone and the receiver 104 is evaluated, the timer is restarted (616) to start the next period for sending beacon signals. In this way, each zone of the system is able to determine those objects (receivers and/or foreign objects) located nearby and can determine whether to transmit wireless power and, if so, any adjustments that should be made to account for presence of any foreign objects. In some embodiments, the start step (602) is preceded by an optional training process as discussed with reference to FIG. 6B.

FIG. 6B is a flow diagram 650 showing a process of optional training performed by the power-transfer zone 290 in accordance with some embodiments. In some embodiments, optional training includes aiding foreign object detection (FOD) using signature-signal-based detection. In some embodiments, this can be done at one time with known sets of receivers and FOD devices. In some embodiments, enough ADC samples are collected (652) to enable classification of FOD, and the derived parameters provide the ability to classify the object detection status including (1) no object present (654), (2) one or more foreign objects present (654), (3) receiver only present (658), and (4) foreign object in between the receiver 104 and the power-transfer zone 290 (660). The process further includes analyzing (662) ADC samples to derive FOD parameters, and storing (664) the FOD in memory (e.g., in non-volatile memory). More details regarding example training or learning processes are described above in reference to FIG. 5, and can involve use of the gantry robot to allow for automation of the optional training process and enable training for many types of receivers and foreign objects in a short period of time.

All of these examples are non-limiting and any number of combinations and multi-layered structures are possible using the example structures described above.

The terminology used in the description of the invention herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used in the description of the invention and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, steps, operations, elements, components, and/or groups thereof.

It will also be understood that, although the terms “first,” “second,” etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first region could be termed a second region, and, similarly, a second region could be termed a first region, without changing the meaning of the description, so long as all occurrences of the “first region” are renamed consistently and all occurrences of the “second

26

region” are renamed consistently. The first region and the second region are both regions, but they are not the same region.

The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. A non-transitory, computer-readable storage medium storing instructions that, when executed by one or more processors of a wireless-power transmitter including a wireless-power-transmitting antenna, cause the wireless-power transmitter to perform operations, comprising:

after the wireless-power transmitter has been enabled for a predetermined period of time, for each zone of a plurality of zones:

enabling a beacon signal,

obtaining a set of electrical measurements, wherein the set of electrical measurements includes measurements of a plurality of electrical features of an object;

selecting, via a feature selection algorithm, two measurements from the set of electrical measurements having a highest object categorization performance when plotted against one another, wherein the two measurements are measurements of different electrical features;

disabling the beacon signal, and

determining, using a trained classifier configured to receive the set of electrical measurements, a zone status indicating presence of a foreign object within a respective zone of the plurality of zones, wherein the trained classifier is a clustering algorithm trained to classify known and unknown objects based on the two selected measurements;

in accordance with a first zone status indicating that a foreign object is present within a first zone of the plurality of zones, forgo transmitting wireless power to one or more wireless power receivers within the first zone of the plurality of zones; and

in accordance with a second zone status indicating an absence of a foreign object within a second zone of the plurality of zones, transmitting wireless power to one or more wireless power receivers within the second zone of the plurality of zones.

2. The non-transitory computer readable storage medium of claim 1, wherein obtaining the set of electrical measurements for each zone of the plurality of zones further comprises forming a respective feature vector for each set of electrical measurements.

3. The non-transitory computer readable storage medium of claim 2, wherein the instructions, when executed by the one or more processors of the wireless-power transmitter, cause the wireless-power transmitter to perform operations, further comprising:

for each zone of a plurality of zones:

continuing to (i) obtain the set of electrical measurements, (ii) form the respective feature vector, and

27

(iii) determine a respective zone status by inputting the respective feature vector to the trained classifier; and

waiting to transmit wireless power to the one or more wireless power receivers until the trained classifier stops detecting that the one or more foreign objects are present.

4. The non-transitory computer readable storage medium of claim 2, wherein forming the feature vector further comprises calculating a respective feature data for the set of electrical measurements, and aggregating the respective feature data to obtain the feature vector.

5. The non-transitory computer readable storage medium of claim 1, wherein the trained classifier includes a machine-learning model and applies reinforcement learning to adjust one or more weights used in the machine-learning model upon determining that (i) the trained classifier has detected the presence of the one or more foreign objects and (ii) wireless power received by the one or more wireless power receivers indicates that no foreign object is present.

6. The non-transitory computer readable storage medium of claim 1, wherein the trained classifier is further trained to classify the one or more foreign objects into one or more categories.

7. The non-transitory computer readable storage medium of claim 1, wherein the set of electrical measurements is obtained at predetermined time intervals.

8. The non-transitory computer readable storage medium of claim 1, wherein the set of electrical measurements include measurements of one or more of: load impedance, reflective power, forward power, drive current, drive voltage, magnetics, and temperature.

9. The non-transitory computer readable storage medium of claim 1, wherein the trained classifier detects one or more of: coins, credit cards, and radio-frequency identification (RFID) tags.

10. The non-transitory computer readable storage medium of claim 1, wherein the beacon signal is transmitted as a low power burst for a short period of time.

11. The non-transitory computer readable storage medium of claim 1, wherein the beacon signal is transmitted using transmission parameters selected from a predetermined set of transmission parameters specifying at least a power level and a frequency.

12. The non-transitory computer readable storage medium of claim 1, wherein the trained classifier includes a K-means classifier trained to detect the one or more wireless power receivers and to distinguish the one or more wireless power receivers from the one or more foreign objects.

13. The non-transitory computer readable storage medium of claim 1, wherein the trained classifier includes a k-nearest neighbor (k-NN) classifier trained to classify the one or more wireless power receivers and the one or more foreign objects into at least one category of a plurality of categories of objects.

14. The non-transitory computer readable storage medium of claim 1, wherein the wireless-power-transmitting antenna is configured to match load impedance of the one or more wireless power receivers for optimal power transfer.

15. The non-transitory computer readable storage medium of claim 1, wherein the wireless-power-transmitting antenna is a near-field transmitting antenna.

28

16. A wireless-power transmitter, comprising:
a wireless-power-transmitting antenna;
one or more processors; and

memory storing one or more programs that are configured for execution by the one or more processors, the one or more programs including instructions for:

after the wireless-power transmitter has been enabled for a predetermined period of time, for each zone of a plurality of zones:

enabling a beacon signal,

obtaining a set of electrical measurements, wherein the set of electrical measurements includes measurements of a plurality of electrical features of an object;

selecting, via a feature selection algorithm, two measurements from the set of electrical measurements having a highest object categorization performance when plotted against one another wherein the two measurements are measurements of different electrical features;

disabling the beacon signal, and

based on the two selected measurements, determining, using a trained classifier configured to receive the set of electrical measurements, a zone status indicating presence of a foreign object within a respective zone of the plurality of zones;

in accordance with a first zone status indicating that a foreign object is present within a first zone of the plurality of zones, forgo transmitting wireless power to one or more wireless power receivers within the first zone of the plurality of zones; and

in accordance with a second zone status indicating an absence of a foreign object within a second zone of the plurality of zones, transmitting wireless power to one or more wireless power receivers within the second zone of the plurality of zones.

17. The wireless-power transmitter of claim 16, wherein obtaining the set of electrical measurements for each zone of the plurality of zones further comprises forming a respective feature vector for each set of electrical measurements.

18. The wireless-power transmitter of claim 17, wherein the one or more programs stored in the memory further include instructions for:

for each zone of a plurality of zones:

continuing to (i) obtain the set of electrical measurements, (ii) form the respective feature vector, and (iii) determine a respective zone status by inputting the respective feature vector to the trained classifier; and

waiting to transmit wireless power to the one or more wireless power receivers until the trained classifier stops detecting that the one or more foreign objects are present.

19. A method of detecting and classifying foreign objects, comprising:

after a wireless-power transmitter including a wireless-power-transmitting antenna has been enabled for a predetermined period of time, for each zone of a plurality of zones of the wireless-power transmitter:

enabling a beacon signal,

obtaining a set of electrical measurements, wherein the set of electrical measurements includes measurements of a plurality of electrical features of an object;

selecting, via a feature selection algorithm, two measurements from the set of electrical measurements having a highest object categorization performance

when plotted against one another, wherein the two measurements are measurements of different electrical features;

disabling the beacon signal, and

based on the two selected measurements, determining, 5

using a trained classifier configured to receive the set of electrical measurements, a zone status indicating presence of a foreign object within a respective zone of the plurality of zones;

in accordance with a first zone status indicating that a 10

foreign object is present within a first zone of the plurality of zones, forgo transmitting wireless power to one or more wireless power receivers within the first zone of the plurality of zones; and

in accordance with a second zone status indicating an 15

absence of a foreign object within a second zone of the plurality of zones, transmitting wireless power to one or more wireless power receivers within the second zone of the plurality of zones.

20. The method of claim 19, wherein obtaining the set of 20 electrical measurements for each zone of the plurality of zones further comprises forming a respective feature vector for each set of electrical measurements.

* * * * *