

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418620
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Tsuruyama; Shinichi

Printing control device, method for controlling printing control device, and non-transitory computer-readable storage medium storing program

Abstract

A first server device is a first server device communicably connected to a first printer and a second server device disposed at a customer support center. The first server device includes: a first acquisition unit configured to acquire, from the first printer, question information indicating a content of a question input from a user by voice regarding an operation method of the first printer; and a transmission unit configured to transmit, to the second server device, inquiry information including the question information.

Inventors:	Tsuruyama; Shinichi (Shiojiri, JP)
Applicant:	SEIKO EPSON CORPORATION (Tokyo, JP)
Family ID:	1000008818755
Assignee:	Seiko Epson Corporation (Tokyo, JP)
Appl. No.:	18/614834
Filed:	March 25, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240333846 A1	Oct. 03, 2024

Foreign Application Priority Data

JP	2023-049541	Mar. 27, 2023
----	-------------	---------------

Publication Classification

Int. Cl.: G06F15/00 (20060101); G06Q30/015 (20230101); H04N1/00 (20060101); H04N1/32 (20060101)

U.S. Cl.:

CPC H04N1/00344 (20130101); G06Q30/015 (20230101); H04N1/00244 (20130101); H04N1/00403 (20130101); H04N1/00488 (20130101); H04N1/32101 (20130101); H04N2201/3209 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2010/0302586	12/2009	Takahashi	709/219	G06T 3/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3901881	12/2020	EP	G06F 16/9532
2005-122658	12/2004	JP	N/A

Primary Examiner: Milia; Mark R
Attorney, Agent or Firm: WORKMAN NYDEGGER

Background/Summary

(1) The present application is based on, and claims priority from JP Application Serial Number 2023-049541, filed Mar. 27, 2023, the disclosure of which is hereby incorporated by reference herein in its entirety.

BACKGROUND

1. Technical Field

(2) The present disclosure relates to a printing control device, a method for controlling a printing control device, and a non-transitory computer-readable storage medium storing a program.

2. Related Art

(3) JP-A-2005-122658 discloses a system for notifying an ID of a user by the user calling customer support when a defect occurs in a printer.

(4) JP-A-2005-122658 is an example of the related art.

SUMMARY

(5) However, in the system described in JP-A-2005-122658, when a defect occurs in a printer or when a method of operating a printer is unknown, a user takes time and effort to call customer support, which deteriorates the convenience.

(6) A printing control device according to an aspect for solving the above problems is a printing control device communicably connected to an image forming device and a server device disposed at a customer support center. The printing control device includes: a first acquisition unit

configured to acquire, from the image forming device, question information indicating a content of a question input from a user by voice regarding an operation method of the image forming device; and a transmission unit configured to transmit, to the server device, inquiry information including the question information.

(7) A method for controlling a printing control device according to another aspect for solving the above problems is a method for controlling a printing control device communicably connected to an image forming device and a server device disposed at a customer support center. The method includes: a first acquisition step of acquiring, from the image forming device, question information indicating a content of a question input from a user by voice regarding an operation method of the image forming device; and a transmission step of transmitting, to the server device, inquiry information including the question information.

(8) According to a non-transitory computer-readable storage medium storing a program executed by a processor of a printing control device, the printing control device being communicably connected to an image forming device and a server device disposed at a customer support center, the program causes the processor to function as: a first acquisition unit configured to acquire, from the image forming device, question information indicating a content of a question input from a user by voice regarding an operation method of the image forming device; and a transmission unit configured to transmit, to the server device, inquiry information including the question information.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a diagram showing an example of a configuration of a printing control system according to an embodiment.

(2) FIG. 2 is a diagram showing an example of a configuration of a first server device according to the embodiment.

(3) FIG. 3 is a diagram showing an example of a configuration of a printer according to the embodiment.

(4) FIG. 4 is a perspective view showing an example of a configuration of a printing mechanism.

(5) FIG. 5 is a flowchart showing an example of an operation of the printing control system.

(6) FIG. 6 is a flowchart showing another example of the operation of the printing control system.

DESCRIPTION OF EMBODIMENTS

(7) Hereinafter, the embodiment will be described with reference to the drawings.

(8) First, a configuration of a printing control system 1 according to the embodiment will be described with reference to FIG. 1. FIG. 1 is a diagram showing an example of the configuration of the printing control system 1 according to the embodiment. As shown in FIG. 1, the printing control system 1 includes a first server device 100 and a printer 300.

(9) The first server device 100 is communicably connected to the printer 300 via a first network NWA. The first network NWA is, for example, the Internet.

(10) In the embodiment, a case where the first network NWA is the Internet will be described, but the present disclosure is not limited thereto. The first network NWA may be, for example, a local area network (LAN) or a wide area network (WAN).

(11) The first server device 100 is communicably connected to a second server device 200 via a second network NWS. The second network NWS is, for example, a LAN. In the embodiment, a case where the second network NWS is a LAN will be described, but the present disclosure is not limited thereto. The second network NWS may be, for example, a WAN or the Internet.

(12) The second server device 200 is communicably connected to a terminal device 250 via the second network NWS.

(13) The terminal device 250 is, for example, a personal computer. The terminal device 250

includes a first terminal device **250A** and a second terminal device **250B**. The first terminal device **250A** is operated by a first operator PA. The second terminal device **250B** is operated by a second operator PB. The first operator PA and the second operator PB are included in an operator P. The operator P is an operator of the terminal device **250**.

(14) The second server device **200** and the terminal device **250** are disposed at a customer support center CSC. In other words, the second server device **200** and the terminal device **250** constitute a customer support system.

(15) The printer **300** includes a first printer **300A** and a second printer **300B**. As shown in FIG. 1, the first printer **300A** is disposed at a room HA of a first user UA, and the second printer **300B** is disposed at a room HB of a second user UB. The first user UA is a user of the first printer **300A**. The second user UB is a user of the second printer **300B**. The first user UA and the second user UB are included in a user U. The user U is a user of the printer **300**.

(16) The printer **300** corresponds to an example of an “image forming device”.

(17) In the embodiment, a case where the “image forming device” is the printer **300** will be described, but the present disclosure is not limited thereto. The “image forming device” may be, for example, a copying machine. In addition, the “image forming device” may be, for example, a so-called multifunction machine.

(18) The first printer **300A** accepts a question related to an operation method of the first printer **300A** from the first user UA by voice. The first printer **300A** transmits, to the first server device **100**, question information QA indicating a content of the accepted question.

(19) The first server device **100** acquires the question information QA from the first printer **300A**. The first server device **100** transmits, to the second server device **200**, inquiry information EQA including the question information QA. The second server device **200** transmits the inquiry information EQA to, for example, the first terminal device **250A**.

(20) The first operator PA operates the first terminal device **250A** to generate, based on the inquiry information EQA, first answer information AA1 indicating an answer to the question information QA. In accordance with an instruction from the first operator PA, the first terminal device **250A** transmits the first answer information AA1 to the second server device **200**. The second server device **200** receives the first answer information AA1 and transmits the first answer information AA1 to the first server device **100**.

(21) The first server device **100** acquires the first answer information AA1 from the second server device **200** by receiving the first answer information AA1 from the second server device **200**. The first server device **100** causes the first printer **300A** to output the first answer information AA1. The first server device **100** causes the first printer **300A** to output the first answer information AA1 by at least one of printing, voice, or image, for example. In the embodiment, the first server device **100** causes the first printer **300A** to output the first answer information AA1 by voice, for example.

(22) The second printer **300B** receives a question related to an operation method of the second printer **300B** from the second user UB by voice. The second printer **300B** transmits, to the first server device **100**, question information QB indicating a content of the accepted question.

(23) The first server device **100** acquires the question information QB from the second printer **300B**. The first server device **100** transmits, to the second server device **200**, inquiry information EQB including the question information QB. The second server device **200** transmits the inquiry information EQB to, for example, the second terminal device **250B**.

(24) The second operator PB operates the second terminal device **250B** to generate, based on the inquiry information EQB, first answer information AB1 indicating an answer to the question information QB. In accordance with an instruction from the second operator PB, the second terminal device **250B** transmits the first answer information AB1 to the second server device **200**. The second server device **200** receives the first answer information AB1 and transmits the first answer information AB1 to the first server device **100**.

(25) The first server device **100** acquires the first answer information AB1 from the second server

device **200** by receiving the first answer information **AB1** from the second server device **200**. The first server device **100** causes the second printer **300B** to output the first answer information **AB1**. The first server device **100** causes the second printer **300B** to output the first answer information **AB1** by at least one of printing, voice, or image, for example. In the embodiment, the first server device **100** causes the second printer **300B** to output the first answer information **AB1** by voice, for example.

(26) The first printer **300A** and the second printer **300B** have substantially the same configuration. When it is not necessary to distinguish between the first printer **300A** and the second printer **300B**, each of the first printer **300A** and the second printer **300B** may be referred to as a printer **300** in the following description.

(27) The first server device **100** corresponds to an example of a “printing control device”.

(28) In the embodiment, a case where the “printing control device” is the first server device **100** will be described, but the present disclosure is not limited thereto. The “printing control device” may be, for example, a personal computer. In addition, the printing control device may be a tablet terminal.

(29) The second server device **200** corresponds to an example of a “server device”.

(30) In the embodiment, a case where the second server device **200** is provided separately from the first server device **100** will be described, but the present disclosure is not limited thereto. The second server device **200** may be integrated with the first server device **100**.

(31) Next, a configuration of the first server device **100** will be described with reference to FIG. 2. FIG. 2 is a diagram showing an example of the configuration of the first server device **100** according to the embodiment.

(32) As shown in FIG. 2, the first server device **100** includes a first control unit **110**, a first operation mechanism **120**, a first display mechanism **130**, and a first communication interface **140**. The first control unit **110** controls units of the first server device **100**. The first operation mechanism **120**, the first display mechanism **130**, and the first communication interface **140** are each communicably connected to the first control unit **110**.

(33) The first control unit **110** includes a first processor **110A** such as a central processing unit (CPU) and a first memory **110B** such as a read only memory (ROM). The first memory **110B** stores a first control program **PG1**.

(34) The first processor **110A** may include a plurality of processors, or may include a single processor.

(35) The first processor **110A** may be hardware that is programmed to implement functions of the respective units to be described later. That is, the first processor **110A** may have a configuration in which the first control program **PG1** is mounted as a hardware circuit. In this case, for example, the first processor **110A** is implemented by an application specific integrated circuit (ASIC), a field-programmable gate array (FPGA), or the like.

(36) In the following description, a case where the first processor **110A** executes the first control program **PG1** to implement various functions of the first control unit **110** will be described.

(37) The first memory **110B** has a storage area for storing a program executed by the first processor **110A** and data processed by the first processor **110A**. The first memory **110B** stores the first control program **PG1** executed by the first processor **110A**, and various pieces of image data, setting data, and the like related to an operation of the first server device **100**.

(38) The first memory **110B** has a nonvolatile storage area for storing a program and data in a nonvolatile manner. The first memory **110B** may have, for example, a ROM, a random access memory (RAM), a hard disk drive (HDD), and a solid state drive (SSD) as a nonvolatile storage area. The first memory **110B** may also have a volatile storage area, and form a work area for temporarily storing a program executed by the first processor **110A** and data to be processed. The first memory **110B** may include, for example, a RAM as a volatile storage area.

(39) The first operation mechanism **120** includes an operation switch provided in the first server

device **100** and an input unit such as a touch panel. The first operation mechanism **120** detects an operation of a user and outputs a detection signal corresponding to the operation to the first control unit **110**. The first control unit **110** executes processing corresponding to the operation of the user based on input from the first operation mechanism **120**. The user is, for example, an administrator of the first server device **100**.

(40) The first display mechanism **130** includes a display panel such as a liquid crystal display (LCD), and displays information on the display panel under the control of the first control unit **110**.

(41) The first communication interface **140** is a communication interface that communicates with the printer **300** and the second device **200** according to the Ethernet (registered trademark) standard. The first communication interface **140** includes a connector to which an Ethernet (registered trademark) cable is coupled, and an interface circuit that processes a signal transmitted through the connector. The first communication interface **140** is an interface board having a connector and an interface circuit, and is coupled to a main board on which the first processor **110A** of the first control unit **110** and the like are mounted. Alternatively, the connector and the interface circuit constituting the first communication interface **140** are mounted on the main board of the first control unit **110**. The first communication interface **140** receives the question information QA, the question information QB, and the like from the printer **300**. The first communication interface **140** transmits the inquiry information EQA, the inquiry information EQB, and the like to the second server device **200**.

(42) As shown in FIG. 2, the first control unit **110** includes a first acquisition unit **111**, a second acquisition unit **112**, a third acquisition unit **113**, a generation unit **114**, a transmission unit **115**, an instruction unit **116**, a first communication control unit **117**, an answer storage unit **118**, and a question-and-answer storage unit **119**. These units are implemented by cooperation between software and hardware, for example, by the first processor **110A** executing the first control program PG1. In other words, the first processor **110A** executes the first control program PG1 to function as the first acquisition unit **111**, the second acquisition unit **112**, the third acquisition unit **113**, the generation unit **114**, the transmission unit **115**, the instruction unit **116**, and the first communication control unit **117**. When the first processor **110A** executes the first control program PG1, the first memory **110B** functions as the answer storage unit **118** and the question-and-answer storage unit **119**.

(43) The first processor **110A** corresponds to an example of a “processor”.

(44) The first control program PG1 corresponds to an example of a “program”.

(45) In the following description, for convenience, a case where the printer **300** is the first printer **300A** will be described.

(46) The answer storage unit **118** stores question information Q and answer information A in association with each other. The answer storage unit **118** is a so-called database that stores a large number of, for example, 10000 pieces of question information Q and a large number of, for example, 10000 pieces of answer information A in association with each other.

(47) When the answer information A differs depending on a model of the printer **300**, the answer storage unit **118** stores the answer information A in association with model information MP. The answer storage unit **118** stores the answer information A corresponding to model information MP1 in association with the model information MP1, for example. The answer storage unit **118** stores the answer information A corresponding to model information MP2 in association with the model information MP2, for example.

(48) The question-and-answer storage unit **119** stores the question information QA, the first answer information AA1, and the second answer information AA2 in association with one another. The question-and-answer storage unit **119** stores the question information QA, the first answer information AA1, and the second answer information AA2 in association with a user ID of the first user UA, for example.

(49) The question information QA is acquired from the first printer **300A** by the first acquisition

unit **111** and stored in the question-and-answer storage unit **119** by the first acquisition unit **111**. The first answer information **AA1** is acquired from the second server device **200** by the second acquisition unit **112** and stored in the question-and-answer storage unit **119** by the second acquisition unit **112**. The second answer information **AA2** is generated by the generation unit **114** and stored in the question-and-answer storage unit **119** by the generation unit **114**.

(50) For example, the first acquisition unit **111** acquires the question information **QA** indicating a content of a question input from the first user **UA** regarding the operation method of the first printer **300A**. The first user **UA** inputs the question to the first printer **300A** by voice, for example. The first printer **300A** converts the voice from the first user **UA** to a voice signal by a microphone **320**, and converts the voice signal to text information by voice recognition to generate the question information **QA**. The first printer **300A** transmits the question information **QA** to the first server device **100**. The first acquisition unit **111** acquires the question information **QA** by receiving the question information **QA**. The first acquisition unit **111** stores the question information **QA** in the question-and-answer storage unit **119** in association with the user ID of the first user **UA**.

(51) The transmission unit **115** transmits, to the second server device **200**, the inquiry information **EQA** including the question information **QA**.

(52) The second server device **200** receives the inquiry information **EQA** from the transmission unit **115**, and transmits the inquiry information **EQA** to, for example, the first terminal device **250A**. The first operator **PA** operates the first terminal device **250A** to generate, based on the inquiry information **EQA**, first answer information **AA1** indicating an answer to the question information **QA**. In accordance with an instruction from the first operator **PA**, the first terminal device **250A** transmits the first answer information **AA1** to the second server device **200**. The second server device **200** receives the first answer information **AA1** and transmits the first answer information **AA1** to the first server device **100**.

(53) The second acquisition unit **112** acquires the first answer information **AA1** from the second server device **200**. The first answer information **AA1** corresponds to the question information **QA** and indicates an answer input by the first operator **PA** of the customer support center **CSC**. The second acquisition unit **112** acquires the first answer information **AA1** from the second server device **200** by receiving the first answer information **AA1** from the second server device **200**.

(54) The third acquisition unit **113** acquires a telephone number **TN** of the first user **UA** from the first printer **300A**. The third acquisition unit **113** acquires the telephone number **TN** of the first user **UA** from the first printer **300A** by voice of the first user **UA**, for example.

(55) The first user **UA** inputs the telephone number **TN** to the first printer **300A** by voice, for example. The first printer **300A** converts the voice from the first user **UA** into a voice signal by the microphone **320**, and converts the voice signal into text information by voice recognition to generate the telephone number **TN**. Then, the first printer **300A** transmits the telephone number **TN** to the first server device **100**. The third acquisition unit **113** acquires the telephone number **TN** by receiving the telephone number **TN**.

(56) The generation unit **114** generates, based on the question information **QA** acquired by the first acquisition unit **111** from the first printer **300A**, the second answer information **AA2** indicating an answer to the question. The generation unit **114** extracts a keyword from the question information **QA**, for example. The generation unit **114** generates the second answer information **AA2** by reading the second answer information **AA2** corresponding to the extracted keyword from the answer information **A** stored in the answer storage unit **118**. The generation unit **114** stores the second answer information **AA2** in the question-and-answer storage unit **119** in association with the question information **QA**.

(57) The transmission unit **115** transmits, to the second server device **200**, the telephone number **TN** of the first user **UA** that is acquired by the third acquisition unit **113**.

(58) The second server device **200** transmits the telephone number **TN** of the first user **UA** to the first terminal device **250A**. As a result, the first operator **PA** can know the telephone number **TN** of

the first user UA.

(59) The instruction unit **116** causes the first printer **300A** to output the first answer information **AA1** acquired by the second acquisition unit **112**. The instruction unit **116** causes the first printer **300A** to output the first answer information **AA1** by at least one of voice, image, or printing, for example. In the embodiment, the instruction unit **116** causes the first printer **300A** to output the first answer information **AA1** by voice, for example.

(60) The instruction unit **116** causes the first printer **300A** to output the second answer information **AA2** generated by the generation unit **114**. The instruction unit **116** causes the first printer **300A** to output the second answer information **AA2** by at least one of voice, image, or printing, for example. In the embodiment, the instruction unit **116** causes the first printer **300A** to output the second answer information **AA2** by voice, for example.

(61) The transmission unit **115** determines whether the number of times of outputting the second answer information **AA2** reaches a predetermined number of times **N**. When the number of times of outputting the second answer information **AA2** reaches the predetermined number of times **N**, the transmission unit **115** transmits the inquiry information **EQA** to the second server device **200**. The inquiry information **EQA** includes the question information **QA** and the second answer information **AA2**. The predetermined number of times **N** is, for example, two.

(62) The second server device **200** receives the inquiry information **EQA** from the transmission unit **115**, and transmits the inquiry information **EQA** to, for example, the first terminal device **250A**. The first operator **PA** operates the first terminal device **250A** to generate, based on the inquiry information **EQA**, first answer information **AA1** indicating an answer to the question information **QA**. In accordance with an instruction from the first operator **PA**, the first terminal device **250A** transmits the first answer information **AA1** to the second server device **200**. The second server device **200** receives the first answer information **AA1** and transmits the first answer information **AA1** to the first server device **100**.

(63) The second acquisition unit **112** acquires the first answer information **AA1** from the second server device **200**. The instruction unit **116** causes the first printer **300A** to output the first answer information **AA1** acquired by the second acquisition unit **112**.

(64) The instruction unit **116** also causes the first printer **300A** to output a fact that the telephone number **TN** of the first user **UA** is transmitted to the second server device **200**. The instruction unit **116** causes the first printer **300A** to output, by at least one of voice, image, or printing, for example, the fact that the telephone number **TN** of the first user **UA** is transmitted to the second server device **200**. In the embodiment, the instruction unit **116** causes the first printer **300A** to output, by voice, for example, the fact that the telephone number **TN** of the first user **UA** is transmitted to the second server device **200**.

(65) The first communication control unit **117** receives the question information **QA** and the telephone number **TN** of the first user **UA** from the first printer **300A**.

(66) The first communication control unit **117** transmits inquiry information **EQ** to the second server device **200**. The first communication control unit **117** receives the first answer information **AA1** from the second server device **200**.

(67) The first communication control unit **117** also transmits the first answer information **AA1** and the second answer information **AA2** to the first printer **300A**.

(68) Next, a configuration of the first printer **300A** will be described with reference to FIG. 3. FIG. 3 is a diagram showing an example of the configuration of the printer **300** according to the embodiment. The first printer **300A** and the second printer **300B** have substantially the same configuration. The configuration of the first printer **300A** will be described with reference to FIG. 3.

(69) As shown in FIG. 3, the first printer **300A** includes a second control unit **310**, the microphone **320**, a speaker **325**, a second operation mechanism **330**, a second display mechanism **340**, a second communication interface **350**, a printing mechanism **360**, an ink supply unit **370**, and a printing

medium accommodating unit **380**.

(70) The second control unit **310** controls an operation of each unit of the first printer **300A**. The microphone **320**, the speaker **325**, the second operation mechanism **330**, the second display mechanism **340**, the second communication interface **350**, and the printing mechanism **360** each communicate with the second control unit **310**.

(71) The second control unit **310** includes a second processor **310A** such as a CPU, and a second memory **310B** such as a ROM and a RAM, and controls units of the first printer **300A**. The second memory **310B** stores a second control program PG2. The second memory **310B** may include a magnetic storage device such as an HDD and a semiconductor storage device such as an SSD.

(72) In the second control unit **310**, the second processor **310A** executes processing of reading the second control program PG2 stored in the second memory **310B**. In other words, the second control unit **310** executes processing by cooperation of hardware and software.

(73) The second processor **310A** may include a single processor, or a plurality of processors may be provided to function as the second processor **310A**.

(74) In the embodiment, the second processor **310A** executes the second control program PG2 to control the units of the printer **300**, but the present disclosure is not limited thereto. The second control unit **310** may include, for example, an ASIC, and the ASIC may execute processing by using an implemented function. The second control unit **310** may include, for example, a signal processing circuit, and the signal processing circuit may execute signal processing to execute the processing.

(75) The microphone **320** accepts voice from the first user UA, generates a voice signal, and transmits the generated voice signal to the second control unit **310**.

(76) The speaker **325** outputs the voice under the control of the second control unit **310**. The speaker **325** outputs, for example, voice generated by a voice synthesis unit **314**.

(77) The second operation mechanism **330** includes an operation switch provided in the first printer **300A** and an input unit such as a touch panel. The second operation mechanism **330** detects an operation of the first user UA on the input unit, and outputs a detection signal corresponding to the operation to the second control unit **310**. The second control unit **310** executes processing corresponding to the operation of the first user UA based on input from the second operation mechanism **330**.

(78) The second display mechanism **340** includes a plurality of light emitting diodes (LEDs) and a display panel such as an LCD. The second display mechanism **340** executes lighting, extinction, and blinking of the LEDs in a predetermined mode, display of information on the display panel, and the like under the control of the second control unit **310**.

(79) The second communication interface **350** is a communication interface that communicates with the first server device **100** according to the Ethernet (registered trademark) standard. The second communication interface **350** includes a connector to which an Ethernet (registered trademark) cable is coupled, and an interface circuit that processes a signal transmitted through the connector. The second communication interface **350** is an interface board having a connector and an interface circuit, and is coupled to a main board on which the second processor **310A** of the second control unit **310** and the like are mounted. Alternatively, the connector and the interface circuit constituting the second communication interface **350** are mounted on the main board of the second control unit **310**. The second communication interface **350** receives the first answer information AA1, the second answer information AA2, and the like from the first server device **100**.

(80) The printing mechanism **360** prints characters, images, and the like on a printing medium M such as printing paper using ink under the control of the second control unit **310**. The printing mechanism **360** includes, as a configuration related to printing, a printing head **361**, a carriage **362**, a scanning motor **363**, and a conveyance motor **364**.

(81) The printing head **361** is an ink jet type, and ejects ink supplied from the ink supply unit **370**

toward the printing medium M. The carriage **362** carries the printing head **361** and scans in a main scanning direction X. The main scanning direction X intersects a sub scanning direction Y. The sub scanning direction Y indicates a conveyance direction of the printing medium M. The scanning motor **363** causes the carriage **362** to scan in the main scanning direction X. The conveyance motor **364** conveys the printing medium M in the conveyance direction.

(82) The printing mechanism **360** executes a printing function. The printing mechanism **360** will be further described with reference to FIG. 4.

(83) The ink supply unit **370** accommodates an ink tank that stores ink, and supplies ink from the ink tank to the printing head **361** of the printing mechanism **360**. The ink supplied by the ink supply unit **370** is, for example, cyan (C) ink, magenta (M) ink, yellow (Y) ink, and black (K) ink.

(84) The printing medium accommodating unit **380** can accommodate the printing medium M. When the printing medium M is cut paper, the printing medium accommodating unit **380** feeds the accommodated cut paper to a conveyance path (not shown) by conveyance of the conveyance motor **364**. The printing medium accommodating unit **380** may collect printed matter which is the printing medium M after printing. The printed matter may be collected by placing the cut paper in a stacked manner.

(85) Next, functional blocks of the second control unit **310** of the first printer **300A** will be described.

(86) The second control unit **310** includes, as the functional blocks, a voice acceptance unit **311**, a voice recognition unit **312**, an instruction acceptance unit **313**, a voice synthesis unit **314**, a display control unit **315**, a printing control unit **316**, and a second communication control unit **317**. When the second processor **310A** executes the second control program PG2, the second processor **310A** functions as the voice acceptance unit **311**, the voice recognition unit **312**, the instruction acceptance unit **313**, the voice synthesis unit **314**, the display control unit **315**, the printing control unit **316**, and the second communication control unit **317**.

(87) The voice acceptance unit **311** accepts, via the microphone **320**, a voice signal VQ indicating a question related to the operation method of the first printer **300A** from the first user UA. The voice signal VQ corresponds to the question information QA.

(88) The voice acceptance unit **311** accepts, via the microphone **320**, a voice signal VN indicating the telephone number TN from the first user UA.

(89) The voice recognition unit **312** performs voice recognition on the voice signal VQ accepted by the voice acceptance unit **311**, and generates the question information QA as text information corresponding to the voice signal VQ. The voice recognition unit **312** transmits the generated question information QA to the first server device **100**.

(90) The voice recognition unit **312** performs voice recognition on the voice signal VN accepted by the voice acceptance unit **311**, and generates the telephone number TN as text information corresponding to the voice signal VN. The voice recognition unit **312** transmits the generated telephone number TN to the first server device **100**.

(91) The instruction acceptance unit **313** accepts, from the first server device **100**, instruction information CM indicating to output, by at least one of printing, voice, or image, the first answer information AA1 and the second answer information AA2.

(92) The instruction acceptance unit **313** accepts, from the first server device **100**, the instruction information CM indicating to output, by at least one of printing, voice, or image, the fact that the telephone number TN of the first user UA is transmitted to the server device.

(93) When the instruction information CM indicates to output by voice, the voice synthesis unit **314** generates, by voice first synthesis, voice information SA1 corresponding to the first answer information AA1, and causes the speaker **325** to output the first voice information SA1. When the instruction information CM indicates to output by voice, the voice synthesis unit **314** generates, by voice synthesis, second voice information SA2 corresponding to the second answer information AA2, and causes the speaker **325** to output the second voice information SA2.

(94) When the instruction information CM indicates to output by voice, the voice synthesis unit **314** generates, by voice synthesis, voice information ST indicating that the telephone number TN is transmitted to the first server device **100**, and causes the speaker **325** to output the voice information ST.

(95) When the instruction information CM indicates to output by image, the display control unit **315** generates first image information PA1 corresponding to the first answer information AA1, and causes the display panel of the second display mechanism **340** to display the first image information PA1. When the instruction information CM indicates to output by image, the display control unit **315** generates second image information PA2 corresponding to the second answer information AA2, and causes the display panel of the second display mechanism **340** to display the second image information PA2.

(96) When the instruction information CM indicates to output by image, the display control unit **315** generates image information PT indicating that the telephone number TN is transmitted to the first server device **100**, and causes the display panel of the second display mechanism **340** to display the image information PT.

(97) When the instruction information CM indicates to output by printing, the printing control unit **316** generates first printing information TA1 corresponding to the first answer information AA1, and causes the printing mechanism **360** to print the first printing information TA1. When the instruction information CM indicates to output by printing, the printing control unit **316** generates second printing information TA2 corresponding to the second answer information AA2, and causes the printing mechanism **360** to print the second printing information TA2.

(98) When the instruction information CM indicates to output by printing, the printing control unit **316** generates printing information TT indicating that the telephone number TN is transmitted to the first server device **100**, and causes the printing mechanism **360** to print the printing information TT.

(99) The second communication control unit **317** transmits the question information QA and the telephone number TN of the first user UA to the first server device **100**.

(100) The second communication control unit **317** receives the instruction information CM from the first server device **100**. The instruction information CM indicates to output, by voice, the first answer information AA1 and the second answer information AA2. The instruction information CM indicates to output, by at least one of printing, voice, or image, the fact that the telephone number TN is transmitted to the first server device **100**.

(101) In the embodiment, a case where the printer **300** includes the microphone **320** and the speaker **325**, and the second control unit **310** of the printer **300** includes the voice recognition unit **312** and the voice synthesis unit **314** is described, but the present disclosure is not limited thereto. The printer **300** may be communicably connected to, for example, a smartphone, the smartphone may include the microphone **320** and the speaker **325**, and a control unit of the smartphone may include the voice recognition unit **312** and the voice synthesis unit **314**. The printer **300** may be communicably connected to, for example, a so-called AI speaker, the AI speaker may include the microphone **320** and the speaker **325**, and a control unit of the AI speaker may include the voice recognition unit **312** and the voice synthesis unit **314**.

(102) Next, a configuration of the printing mechanism **360** will be described with reference to FIG. 4. FIG. 4 is a perspective view showing an example of the configuration of the printing mechanism **360**.

(103) As shown in FIG. 4, the printing mechanism **360** includes the carriage **362**, the scanning motor **363**, a paper feed roller **365**, a traction belt **366**, a guide rail **367**, a platen **368**, and the printing medium accommodating unit **380**.

(104) The paper feed roller **365** is driven by the conveyance motor **364**. The traction belt **366** is driven by the scanning motor **363**. The guide rail **367** movably supports the carriage **362** in the main scanning direction X. The carriage **362** is supported by the guide rail **367** and driven by the

scanning motor **363** via the traction belt **366** in the main scanning direction X.

(105) A head unit **36A** is mounted on the carriage **362**.

(106) The head unit **36A** includes a plurality of (for example, four) ink cartridges **36B** and the printing head **361**. The ink cartridge **36B** is provided in the ink supply unit **370**.

(107) The plurality of ink cartridges **36B** are attachable to and detachable from the carriage **362**. The plurality of ink cartridges **36B** each include ink of a different color. For example, cyan (C) ink, magenta (M) ink, yellow (Y) ink, and black (K) ink are accommodated in the ink cartridges **36B**. The ink accommodated in the ink cartridge **36B** is supplied to the printing head **361**.

(108) The printing head **361** has a nozzle **36C** and the like. A plurality of nozzles **36C** are arranged on a surface of the printing head **361** facing the platen **368** along the sub scanning direction Y. The printing head **361** ejects ink from the nozzle **36C** toward the printing medium M.

(109) The printing medium M is wound around the paper feed roller **365** from the printing medium accommodating unit **380**, and is conveyed along the surface of the platen **368** in the sub scanning direction Y. The carriage **362** is pulled by the traction belt **366** driven by the scanning motor **363** and moves along the guide rail **367** in the main scanning direction X. The printing head **361** mounted on the carriage **362** also moves in the main scanning direction X.

(110) The main scanning direction X is a direction orthogonal to the sub scanning direction Y.

(111) With such a configuration, the printing mechanism **360** alternately repeats a liquid ejection operation in which the printing head **361** ejects ink from the nozzle **36C** while moving in the main scanning direction X and a conveyance operation in which the printing medium M is conveyed in the sub scanning direction Y. As a result, the printing mechanism **360** prints an image such as characters and figures on the printing medium M.

(112) Next, an example of an operation of the printing control system **1** will be described with reference to FIG. 5. FIG. 5 is a flowchart showing the example of the operation of the printing control system **1**.

(113) First, in step **S101**, the voice acceptance unit **311** of the first printer **300A** accepts the voice signal VQ indicating a question from the first user UA via the microphone **320**.

(114) Next, in step **S103**, the voice recognition unit **312** of the first printer **300A** performs voice recognition on the voice signal VQ accepted by the voice acceptance unit **311**, and generates the question information QA as the text information corresponding to the voice signal VQ. Then, the voice recognition unit **312** transmits the question information QA to the first server device **100**.

(115) Next, in step **S105**, the first acquisition unit **111** of the first server device **100** receives the question information QA.

(116) Next, in step **S107**, the transmission unit **115** of the first server device **100** transmits, to the second server device **200**, the inquiry information EQA including the question information QA. The inquiry information EQA includes, for example, the question information QA, the user ID of the first user UA, and the model information MP of the first printer **300A**.

(117) The second server device **200** receives the inquiry information EQA from the transmission unit **115**, and transmits the inquiry information EQA to, for example, the first terminal device **250A**. The first operator PA operates the first terminal device **250A** to generate, based on the inquiry information EQA, first answer information AA1 indicating an answer to the question information QA. In accordance with an instruction from the first operator PA, the first terminal device **250A** transmits the first answer information AA1 to the second server device **200**. The second server device **200** receives the first answer information AA1 and transmits the first answer information AA1 to the first server device **100**.

(118) Next, in step **S109**, the second acquisition unit **112** of the first server device **100** acquires the first answer information AA1 by receiving the first answer information AA1 from the second server device **200**.

(119) Next, in step **S111**, the instruction unit **116** of the first server device **100** transmits, to the first printer **300A**, the instruction information CM instructing to output the first answer information

AA1 by voice.

(120) Next, in step S113, the instruction acceptance unit 313 of the first printer 300A accepts the instruction information CM by receiving the instruction information CM.

(121) Next, in step S115, the voice synthesis unit 314 of the first printer 300A outputs the first answer information AA1 by voice. The voice synthesis unit 314 of the first printer 300A generates the first voice information SA1 corresponding to the first answer information AA1 by voice synthesis, and causes the speaker 325 to output the first voice information SA1.

(122) Next, in step S117, the voice acceptance unit 311 of the first printer 300A accepts the voice signal VN indicating the telephone number TN from the first user UA via the microphone 320.

(123) Next, in step S119, the voice recognition unit 312 of the first printer 300A performs voice recognition on the voice signal VN accepted by the voice acceptance unit 311, and generates the telephone number TN as the text information corresponding to the voice signal VN. The voice recognition unit 312 of the first printer 300A transmits the generated telephone number TN to the first server device 100.

(124) Next, in step S121, the third acquisition unit 113 of the first server device 100 acquires the telephone number TN by receiving the telephone number TN from the first printer 300A.

(125) Next, in step S123, the transmission unit 115 of the first server device 100 transmits, to the second server device 200, the telephone number TN of the first user UA that is acquired by the third acquisition unit 113. The second server device 200 transmits the telephone number TN of the first user UA to the first terminal device 250A.

(126) Next, in step S125, the instruction unit 116 of the first server device 100 transmits, to the first printer 300A, the instruction information CM instructing to output, by voice, the fact that the telephone number TN of the first user UA is transmitted to the second server device 200.

(127) Next, in step S127, the instruction acceptance unit 313 of the first printer 300A accepts the instruction information CM by receiving the instruction information CM.

(128) Next, in step S129, the voice synthesis unit 314 of the first printer 300A outputs the first answer information AA1 by voice. The voice synthesis unit 314 of the first printer 300A generates, by voice synthesis, the voice information ST indicating that the telephone number TN of the first user UA is transmitted to the second server device 200, and causes the speaker 325 to output the voice information ST. Thereafter, the processing ends.

(129) Step S105 corresponds to an example of a “first acquisition step”. Step S107 corresponds to an example of a “transmission step”.

(130) As described above with reference to FIG. 5, the telephone number TN of the first user UA is transmitted to the first terminal device 250A operated by the first operator PA after the first printer 300A outputs the first answer information AA1 from the first operator PA for the question from the first user UA. Therefore, the first operator PA can call the first user UA as necessary and respond to the question of the first user UA. On the other hand, the first user UA does not need to call the customer support center CSC to ask the operator P a question. That is, convenience of the first user UA can be improved.

(131) Next, another example of the operation of the printing control system 1 will be described with reference to FIG. 6. FIG. 6 is a flowchart showing the other example of the operation of the printing control system 1.

(132) First, in step S201, the voice acceptance unit 311 of the first printer 300A accepts the voice signal VQ indicating a question from the first user UA via the microphone 320.

(133) Next, in step S203, the voice recognition unit 312 of the first printer 300A performs voice recognition on the voice signal VQ accepted by the voice acceptance unit 311, and generates the question information QA as the text information corresponding to the voice signal VQ. Then, the voice recognition unit 312 transmits the question information QA to the first server device 100.

(134) Next, in step S205, the first acquisition unit 111 of the first server device 100 acquires the question information QA by receiving the question information QA from the first printer 300A.

(135) Next, in step S207, the generation unit **114** of the first server device **100** generates, based on the question information QA, the second answer information AA2 indicating an answer to the question.

(136) Next, in step S209, the instruction unit **116** of the first server device **100** transmits, to the first printer **300A**, the instruction information CM instructing to output the second answer information AA2 by voice.

(137) Next, in step S211, the instruction acceptance unit **313** of the first printer **300A** accepts the instruction information CM by receiving the instruction information CM.

(138) Next, in step S213, the voice synthesis unit **314** of the first printer **300A** outputs the second answer information AA2 by voice. That is, the voice synthesis unit **314** of the first printer **300A** generates, by voice synthesis, the second voice information SA2 indicating the second answer information AA2, and causes the speaker **325** to output the second voice information SA2.

(139) Next, in step S215, the transmission unit **115** of the first server device **100** determines whether the number of times of outputting the second answer information AA2 reaches the predetermined number of times N.

(140) When the transmission unit **115** determines that the number of times of outputting the second answer information AA2 does not reach the predetermined number of times N (step S215; NO), the processing returns to step S201. Then, the processing from step S201 to step S215 is repeatedly executed. When the transmission unit **115** determines that the number of times of outputting the second answer information AA2 reaches the predetermined number of times N (step S215; YES), the processing proceeds to step S217.

(141) In step S217, the voice acceptance unit **311** of the first printer **300A** accepts the voice signal VQ indicating a question from the first user UA via the microphone **320**.

(142) Next, in step S219, the voice recognition unit **312** of the first printer **300A** performs voice recognition on the voice signal VQ accepted by the voice acceptance unit **311**, and generates the question information QA as the text information corresponding to the voice signal VQ. Then, the voice recognition unit **312** transmits the question information QA to the first server device **100**.

(143) Next, in step S221, the first acquisition unit **111** of the first server device **100** acquires the question information QA by receiving the question information QA from the first printer **300A**.

(144) Next, in step S223, the transmission unit **115** of the first server device **100** transmits, to the second server device **200**, the inquiry information EQA including the question information QA. The inquiry information EQA includes, for example, the question information QA, the second answer information AA2, the user ID of the first user UA, and the model information MP of the first printer **300A**.

(145) The second server device **200** receives the inquiry information EQA from the transmission unit **115**, and transmits the inquiry information EQA to, for example, the first terminal device **250A**. The first operator PA operates the first terminal device **250A** to generate, based on the inquiry information EQA, first answer information AA1 indicating an answer to the question information QA. In accordance with an instruction from the first operator PA, the first terminal device **250A** transmits the first answer information AA1 to the second server device **200**. The second server device **200** receives the first answer information AA1 and transmits the first answer information AA1 to the first server device **100**.

(146) Next, in step S225, the second acquisition unit **112** of the first server device **100** acquires the first answer information AA1 by receiving the first answer information AA1 from the second server device **200**.

(147) Next, in step S227, the instruction unit **116** of the first server device **100** transmits, to the first printer **300A**, the instruction information CM instructing to output the first answer information AA1 by voice.

(148) Next, in step S229, the instruction acceptance unit **313** of the first printer **300A** accepts the instruction information CM by receiving the instruction information CM.

(149) Next, in step S231, the voice synthesis unit 314 of the first printer 300A outputs the first answer information AA1 by voice. That is, the voice synthesis unit 314 of the first printer 300A generates the first voice information SA1 corresponding to the first answer information AA1 by voice synthesis, and causes the speaker 325 to output the first voice information SA1. Thereafter, the processing ends.

(150) Step S221 corresponds to an example of the “first acquisition step”. Step S223 corresponds to an example of the “transmission step”.

(151) As described with reference to FIG. 6, when the number of times of outputting the second answer information AA2 generated by the generation unit 114 reaches the predetermined number of times N, the transmission unit 115 transmits, to the second server device 200, the inquiry information EQA including the question information QA. The second server device 200 acquires the first answer information AA1 generated by the first operator PA from the first terminal device 250A, and transmits the first answer information AA1 to the first server device 100. In accordance with the instruction from the first server device 100, the speaker 325 outputs the first voice information SA1 corresponding to the first answer information AA1 generated by the first operator PA.

(152) That is, when the number of times of outputting the second answer information AA2 generated by the generation unit 114 reaches the predetermined number of times N, the first user UA can know the first answer information AA1 generated by the first operator PA in response to the question information QA of the first user UA. Therefore, the first user UA can know the first answer information AA1 generated by the first operator PA of the customer support center CSC without calling the customer support center CSC. Accordingly, the convenience of the first user UA can be improved.

(153) By setting the predetermined number of times N to an appropriate number of times, a timing of changing to acquire the first answer information AA1 generated by the first operator PA instead of the second answer information AA2 generated by the generation unit 114 can be appropriately set. Accordingly, the convenience of the first user UA can be improved.

(154) In the embodiment, the case where the instruction unit 116 of the first server device 100 causes the first printer 300A to output the first answer information AA1 and the second answer information AA2 by voice is described, but the present disclosure is not limited thereto. The instruction unit 116 may cause the first printer 300A to output the first answer information AA1 and the second answer information AA2 by at least one of printing, voice, or image. For example, the instruction unit 116 may cause the first printer 300A to output the first answer information AA1 and the second answer information AA2 by voice and image. For example, the instruction unit 116 may cause the first printer 300A to output the first answer information AA1 and the second answer information AA2 by printing.

(155) As described above with reference to FIGS. 1 to 6, the first server device 100 according to the embodiment is the first server device communicably connected to the first printer 300A and the second server device 200 disposed at the customer support center CSC. The first server device 100 includes: the first acquisition unit 111 configured to acquire, from the first printer 300A, the question information QA indicating the content of the question input from the first user UA by voice regarding the operation method of the first printer 300A; and the transmission unit 115 configured to transmit, to the second server device 200, the inquiry information EQ including the question information QA.

(156) According to this configuration, the inquiry information EQ including the question information QA indicating the content of the question input from the first user UA by voice regarding the operation method of the first printer 300A is transmitted to the second server device 200 disposed at the customer support center CSC. Therefore, the operator P of the customer support center CSC can transmit an answer to the question information QA to the first user UA. Accordingly, the convenience of the first user UA can be improved.

(157) The first server device **100** according to the embodiment further includes: the second acquisition unit **112** configured to acquire, from the second server device **200**, the first answer information AA1 corresponding to the question information QA and indicating an answer input by the first operator PA of the customer support center CSC; and the instruction unit **116** configured to cause the first printer **300A** to output the first answer information AA1.

(158) According to this configuration, the first answer information AA1 corresponding to the question information QA and indicating the answer input by the first operator PA of the customer support center CSC is acquired from the second server device **200** and output to the first printer **300A**. Therefore, the first user UA can know the first answer information AA1 corresponding to the question information QA and indicating the answer input by the first operator PA of the customer support center CSC. Accordingly, the convenience of the first user UA can be improved.

(159) The first server device **100** according to the embodiment further includes: the third acquisition unit **113** configured to acquire the telephone number TN of the first user UA from the first printer **300A**. The transmission unit **115** transmits the telephone number TN to the second server device **200**. The instruction unit **116** causes the first printer **300A** to output a fact that the telephone number TN is transmitted to the second server device **200**.

(160) According to this configuration, since the telephone number TN of the first user UA is transmitted to the second server device **200**, the operator P of the customer support center CSC can answer the first user UA by calling as necessary. Therefore, the first user UA does not need to call the customer support center CSC to ask the operator P a question. Accordingly, the convenience of the first user UA can be improved.

(161) Since the first printer **300A** outputs the fact that the telephone number TN is transmitted to the second server device **200**, the first user UA can know that his or her own telephone number TN is transmitted to the second server device **200**. Therefore, the first user UA may wait for the call from the operator P. In other words, the first user UA does not need to call the customer support center CSC to ask the operator P a question. Accordingly, the convenience of the first user UA can be improved.

(162) In the first server device **100** according to the embodiment, the third acquisition unit **113** acquires the telephone number TN by voice from the first user UA, and the instruction unit **116** causes the first printer **300A** to output, by voice, the fact that the telephone number TN is transmitted to the second server device **200**.

(163) According to this configuration, the telephone number TN is acquired by voice from the first user UA, and the first printer **300A** outputs, by voice, the fact that the telephone number TN is transmitted to the second server device **200**. Therefore, when the first user UA utters the telephone number TN, the third acquisition unit **113** can acquire the telephone number TN. The first user UA can know that the telephone number TN is transmitted to the second server device **200** by listening to the voice output from the first printer **300A**. Accordingly, the convenience of the first user UA can be improved.

(164) The first server device **100** according to the embodiment further includes: the generation unit **114** configured to generate the second answer information AA2 indicating an answer corresponding to the question information QA. The instruction unit **116** causes the first printer **300A** to output the second answer information AA2. When the number of times of outputting the second answer information AA2 reaches the predetermined number of times N, the transmission unit **115** transmits the inquiry information EQ to the second server device **200**.

(165) According to this configuration, when the number of times of outputting the second answer information AA2 generated by the generation unit **114** reaches the predetermined number of times N, the inquiry information EQ is transmitted to the second server device **200**. Therefore, when the number of times of outputting the second answer information AA2 generated by the generation unit **114** reaches the predetermined number of times N, the first user UA can know the first answer information AA1 generated by the first operator PA in response to the question information QA of

the first user UA. Therefore, the first user UA can know the first answer information AA1 generated by the first operator PA of the customer support center CSC without calling the customer support center CSC. Accordingly, the convenience of the first user UA can be improved.

(166) By setting the predetermined number of times N to an appropriate number of times, a timing of changing to acquire the first answer information AA1 generated by the first operator PA instead of the second answer information AA2 generated by the generation unit 114 can be appropriately set. Accordingly, the convenience of the first user UA can be improved.

(167) In the first server device 100 according to the embodiment, the inquiry information EQ includes the question information QA and the second answer information AA2.

(168) According to this configuration, since the inquiry information EQ includes the question information QA and the second answer information AA2, the first operator PA of the customer support center CSC can know the question information QA and the second answer information AA2. Therefore, the first operator PA can generate the appropriate first answer information AA1. Accordingly, the first user UA can know the appropriate first answer information AA1. As a result, the convenience of the first user UA can be improved.

(169) The method for controlling the first server device 100 according to the embodiment is the method for controlling the first server device 100 communicably connected to the first printer 300A and the second server device 200 disposed at the customer support center CSC. The method includes: the first acquisition step of acquiring, from the first printer 300A, the question information QA indicating the content of the question input from the first user UA by voice regarding the operation method of the first printer 300A; and the transmission step of transmitting, to the second server device 200, the inquiry information EQ including the question information QA.

(170) According to this configuration, the same effects as those of the first server device 100 according to the embodiment are achieved.

(171) The first control program PG1 according to the embodiment is the first control program PG1 executed by the first processor 110A of the first server device 100, the first server device 100 being communicably connected to the first printer 300A and the second server device 200 disposed at the customer support center CSC. The first control program PG1 causes the first processor 110A to function as: the first acquisition unit 111 configured to acquire, from the first printer 300A, the question information QA indicating the content of the question input from the first user UA by voice regarding the operation method of the first printer 300A; and the transmission unit 115 configured to transmit, to the second server device 200, the inquiry information EQ including the question information QA.

(172) According to this configuration, the same effects as those of the first server device 100 according to the embodiment are achieved.

(173) The embodiment shows one aspect, and can be freely modified and applied without departing from the gist.

(174) In the embodiment, the case where the “printing control device” is the first server device 100 is described, but the present disclosure is not limited thereto. The “printing control device” may be, for example, a personal computer or a tablet terminal.

(175) In the embodiment, the case where the “image forming device” is the ink jet-type printer 300 is described, but the present disclosure is not limited thereto. The “image forming device” may be, for example, a copying machine. Alternatively, the “image forming device” may be, for example, a so-called multifunction machine.

(176) In the embodiment, the case where the printer 300 includes the microphone 320 and the speaker 325, and the second control unit 310 of the printer 300 includes the voice recognition unit 312 and the voice synthesis unit 314 is described, but the present disclosure is not limited thereto. The printer 300 may be communicably connected to, for example, a smartphone, the smartphone may include the microphone 320 and the speaker 325, and a control unit of the smartphone may

include the voice recognition unit **312** and the voice synthesis unit **314**. The printer **300** may be communicably connected to, for example, a so-called AI speaker, the AI speaker may include the microphone **320** and the speaker **325**, and a control unit of the AI speaker may include the voice recognition unit **312** and the voice synthesis unit **314**.

(177) In the embodiment, a control method implemented by the first processor **110A** of the first server device **100** executing the first control program **PG1** is described, but the first control program **PG1** executed by the first processor **110A** to implement the control method can also be implemented in a form of a computer-readable recording medium or a transmission medium that transmits the first control program **PG1**.

(178) A magnetic or optical recording medium, or a semiconductor memory device may be used as the recording medium. Examples of the recording medium include portable or fixed recording media such as a flexible disk, an HDD, a compact disk read only memory (CD-ROM), a digital versatile disk ((DVD), a Blu-ray (registered trademark) disc, a magneto-optical disk, a flash memory, and a card-type recording medium.

(179) The recording medium may be a nonvolatile storage device such as a RAM, a ROM, or an HDD that is an internal storage device included in the first server device **100**.

(180) The function of the first control unit **110** of the first server device **100** may be implemented by one or a plurality of processors or a semiconductor chip. The first control unit **110** may further include a co-processor such as a system-on-a-chip (SoC), a micro control unit (MCU), or an FPGA. The first control unit **110** may cause both the CPU and the co-processor to cooperate with each other, or may selectively use one of both to perform various controls.

(181) The processing units of the flowcharts in FIGS. **5** and **6** are divided according to the main processing contents in order to facilitate understanding of the processing of the first control unit **110** of the first server device **100** and the second control unit **310** of the printer **300**, and are not limited by the way of dividing the processing units and the names. The processing unit of the flowchart may be further divided into more processing units according to the processing content. One processing unit may be divided so as to include more kinds of processing. An order of the processing may be appropriately changed within a range that does not interfere with the purpose.

(182) Each functional unit shown in FIGS. **2** and **3** shows a functional configuration, and a specific implementation form is not particularly limited. There is no need to mount hardware corresponding to each functional unit, and it is also possible to implement a configuration in which one processor executes programs to implement functions of a plurality of functional units. A part of the functions implemented by software in the above-described embodiment may be hardware, or a part of functions implemented by hardware may be software. In addition, specific detailed configurations of other units of the first server device **100** and the printer **300** can be freely changed without departing from the gist.

Claims

1. A printing control device communicably connected to an image forming device and a server device disposed at a customer support center, the printing control device comprising: one or more processors; and a memory including instructions stored therein that, when executed by the one or more processors, cause the printing control device to: determine whether or not a number of times of outputting answer information to question information is greater than or equal to a predetermined number; and in a case where the number of times of outputting the answer information to the question information is determined to be greater than or equal to the predetermined number: acquire, from the image forming device, question information indicating a content of a question input from a user by voice regarding an operation method of the image forming device; and transmit, to the server device, inquiry information including the question information.

2. The printing control device according to claim 1, wherein the instructions, when executed by the one or more processors, further cause the printing control device to: acquire, from the server device, first answer information corresponding to the question information and indicating an answer input by an operator of the customer support center; and cause the image forming device to output the first answer information.
 3. The printing control device according to claim 2, wherein the instructions, when executed by the one or more processors, further cause the printing control device to: acquire a telephone number of the user from the image forming device, wherein the telephone number is transmitted to the server device, and the image forming device is caused to output a fact that the telephone number is transmitted to the server device.
 4. The printing control device according to claim 3, wherein the telephone number is acquired from the user by voice, and the image forming device is caused to output, by voice, the fact that the telephone number is transmitted to the server device.
 5. The printing control device according to claim 2, wherein the instructions, when executed by the one or more processors, further cause the printing control device to: generate second answer information indicating an answer corresponding to the question information, wherein the image forming device is caused to output the second answer information, and when the number of times of outputting the second answer information reaches a predetermined number of times, the inquiry information is transmitted to the server device.
 6. The printing control device according to claim 5, wherein the inquiry information includes the question information and the second answer information.
 7. A method for controlling a printing control device communicably connected to an image forming device and a server device disposed at a customer support center, the method comprising: determining whether or not a number of times of outputting answer information to question information is greater than or equal to a predetermined number; and in a case where the number of times of outputting the answer information to the question information is determined to be greater than or equal to the predetermined number; acquiring, from the image forming device, question information indicating a content of a question input from a user by voice regarding an operation method of the image forming device; and transmitting, to the server device, inquiry information including the question information.
 8. A non-transitory computer-readable storage medium storing a program executed by a processor of a printing control device, the printing control device being communicably connected to an image forming device and a server device disposed at a customer support center, the program causing the processor to: determine whether or not a number of times of outputting answer information to question information is greater than or equal to a predetermined number; and in a case where the number of times of outputting the answer information to the question information is determined to be greater than or equal to the predetermined number; a first acquisition unit configured to acquire, from the image forming device, question information indicating a content of a question input from a user by voice regarding an operation method of the image forming device; and transmit, to the server device, inquiry information including the question information.
-